

INTALIOREST call from xForms

Tempo

[Log In](#) 

View **Info**

 [Browse Space](#)

Added by [Nicolas Modrzyk](#), last edited by [Nicolas Modrzyk](#) on Oct 01, 2008

REST call from xForms.

In the xforms model section of the form, you can define a submission, similar to the abstract code below:

```
<xforms:model schema="form.xform.xsd">
...
<xforms:submission id="fillvalues" method="get" action="http://127.0.0.1:8888/myrestservice" replace="instance" instance="myinstance">
  <xforms:message ev:event="xforms-submit-error">...error message ...</xforms:message>
</xforms:submission>
...
</xforms:model>
```

You can then use this submission for example at load time, to fill values in your form:

```
<xforms:action ev:event="DOMActivate">
  <xforms:send submission="fillvalues"/>
</xforms:action>
```

And the instance will be loaded with the needed data.

There is also a [REST section](#) on the Orbeon website, for more information.

Comments

Site powered by a free **Open Source Project / Non-profit License** ([more](#)) of [Confluence - the Enterprise wiki](#).
[Learn more](#) or [evaluate Confluence for your organisation](#).

Powered by [Atlassian Confluence](#), the [Enterprise Wiki](#). (Version: 1.4.1 Build:#212 Jun 02, 2005) - [Bug/feature request](#) - [Contact Administrators](#)