



Added by [Nicolas Modrzyk](#), last edited by [Nicolas Modrzyk](#) on Nov 18, 2008

Disable validation on a PATask

In the xFormsManager webapp, look for the following [act.xpl](#) file.

And look for the following section:

```
<xforms:submission id="completeSubmission" ref="instance('taskoutput')" validate="true" action="/formManager/complete" method="post" replace="all">
  <xforms:delete ev:event="xforms-submit" nodeset="instance('taskoutput')/@saved" at="0"/>
  <xforms:toggle ev:event="xforms-submit" case="submit-wait"/>
  <xforms:toggle ev:event="xforms-submit-done" case="refresh-all"/>
  <xforms:action ev:event="xforms-submit-error">
    <xforms:toggle case="viewTask"/>
    <xforms:message level="modal">Can not complete task because the form is not correctly filled out</xforms:message>
  </xforms:action>
</xforms:submission>
```

Then update the validate tag from

```
validate="true"
```

to

```
validate="false"
```

This will disable validation of the form, and will send a request to the server, as coded in the [complete.xpl](#) file.

Comments

Site powered by a free [Open Source Project / Non-profit License](#) ([more](#)) of [Confluence - the Enterprise wiki](#).
[Learn more](#) or [evaluate Confluence for your organisation](#).