118 lines (99 loc) · 4.39 KB


```java
/* 1. Дан список Person (String firstName, String lastName, int age).
Необходимо используя стрим реализовать метод, который вернет список String,
где в алфавитном порядке будут перечислены все  ФИО людей (в виде Иванов И.) старше 18 лет.*/



import java.util.*;
import java.util.function.Function;
import java.util.function.Predicate;
import java.util.stream.Collectors;
import java.util.stream.Stream;

public class Main {


    static class  AccWithPerson{
        private String account;
        private PersonWithAccounts person;

        public AccWithPerson(String account, PersonWithAccounts person) {
            this.account = account;
            this.person = person;
        }

        public String getAccount() {
            return account;
        }

        public PersonWithAccounts getPerson() {
            return person;
        }
    }
    public static void main(String[] args) {
        List<Person> people = List.of(
                new Person("Jack", 15),
                new Person("Leon", 18),
                new Person("Ann", 13),
                new Person("Nike", 22),
                new Person("Mike", 29),
                new Person("John", 24)
        );
        List<String> list = listHandler(
                people,
                person -> person.getAge() > 13,
```

```
45                  person -> getStringName(person),
46                  (n1, n2) -> n1.compareTo(n2)
47          );
48
49          System.out.println(list);
50          //[Jack J., John J., Leon L., Mike M., Nike N.]
51      /*
52          Stream<Person> streamPerson = people.stream().filter(p -> p.getName().startsWith("J"));
53
54          List<Person> list1 = streamPerson.sorted().toList();
55          streamPerson.forEach(p-> System.out.println(p)); /// !!!!!Error Do not use finalized Stream
56      */
57          Set<Person> collect = listPersonHandler(people).collect(Collectors.toSet());
58          System.out.println(collect);
59          /*[Person{name='Ann', age=13}, Person{name='Leon', age=18}, Person{name='John', age=24},
60          Person{name='Jack', age=15}, Person{name='Nike', age=22}, Person{name='Mike', age=29}]*/
61
62          Map<String, Integer> collect1 = listPersonHandler(people)
63                                              .collect(Collectors
64                                              .toMap(p -> p.getName(), p -> p.getAge()));
65          System.out.println(collect1);
66          // {Ann=13, Nike=22, Mike=29, John=24, Jack=15, Leon=18}
67
68          List<PersonWithAccounts> peopleWihAcc = List.of(
69                  new PersonWithAccounts("Jack", 15, List.of("1","4")),
70                  new PersonWithAccounts("Leon", 18, List.of("2")),
71                  new PersonWithAccounts("Ann", 13, List.of("3")),
72                  new PersonWithAccounts("Nike", 22, List.of("5","6")),
73                  new PersonWithAccounts("Mike", 29, List.of("6","7","8")),
74                  new PersonWithAccounts("John", 24, List.of("9"))
75          );
76          peopleWihAcc.stream()
77                  .flatMap(pwa->pwa.getAccounts().stream().map(s->new AccWithPerson(s,pwa)))
78                  .filter(s-> s.getAccount().compareTo("6")>0)
79                  .collect(Collectors.toMap(acc->acc.account, acc->acc.getPerson().getName()));
80      }
81
82      private static String getStringName(Person person) {
83          StringBuilder sb = new StringBuilder(person.getName());
84          return sb.append(" ")
85                  .append(person.getName().charAt(0))
86                  .append(".")
87                  .toString();
88      }
89
90      /*
91          public static <T,R> List<R> listHandler(List<T>  list, Predicate<T> predicate, Function<T,R> function){
92              List<R> resultList = new ArrayList<>();
93              for (T element: list){
94                  if(predicate.test(element)){
95                      resultList.add(function.apply(element));
96                  }
97              }
98              return resultList;
99
100         }*/
101
102     public static <T,R> List<R> listHandler(List<T>  list,
103                                             Predicate<T> predicate,
104                                             Function<T,R> function,
105                                             Comparator<R> comparator
106     ){
```

```
107             return list.stream()
108                     .filter(predicate)
109                     .map(function)
110                     .sorted()
111                     .collect(Collectors.toList());
112 
113         }
114 
115         public static Stream<Person> listPersonHandler(List<Person> list){
116             return list.stream().filter(p->p!=null);
117         }
118     }
```