Name: Ilya

Assignment number: Task #216621

Date of submitting report: 24.10.2018

Description of assigment:

Construct an array of 1000 random integers within range [0, 100]

An input file input.txt is provide. Each line of input.txt is a query integer that you need to check how many of that number is in your random integer array. For each query integer, fork a new child process to do the counting. The output is for each input query, output the count and child process id. For example:

$> query: 13 count: 5 pid: 13342

$> query: 22 count: 3 pid: 13357

Solution’s logic:

Create an array of 1000 randomly generated items. Open the file "input.txt" if possible. We search for the number read from the file in an array of random numbers until we reach the end of the file. Displays in the format specified by the task.

Input:

5
13
24
6
17
20
1
51
36
42
2
19
67
35
64
91
96
84
72

Output:

```
$> query: 5     count: 10       pid: 7244
$> query: 13    count: 11       pid: 7244
$> query: 24    count: 13       pid: 7244
$> query: 6     count: 7        pid: 7244
$> query: 17    count: 11       pid: 7244
$> query: 20    count: 8        pid: 7244
$> query: 1     count: 9        pid: 7244
$> query: 51    count: 5        pid: 7244
$> query: 36    count: 13       pid: 7244
$> query: 42    count: 12       pid: 7244
$> query: 2     count: 12       pid: 7244
$> query: 19    count: 9        pid: 7244
$> query: 67    count: 10       pid: 7244
$> query: 35    count: 10       pid: 7244
$> query: 64    count: 10       pid: 7244
$> query: 91    count: 9        pid: 7244
$> query: 96    count: 8        pid: 7244
$> query: 84    count: 7        pid: 7244
$> query: 72    count: 7        pid: 7244
$> query: 72    count: 7        pid: 7244
```

Demonstration of work:



