


CSARCH2
Long Exam 1: Mock Exam
Name of Contributor(s) :
Clive Jarel Ang

Note: This reviewer is intended for distribution under the name of PTS. Only the contributor or the organization may distribute it directly. For distribution by other organizations, please contact the Peer Tutors Society. For any concerns, reach out to the Peer Tutors Society's Academics Committee.

DLSU PTS Facebook
https://www.facebook.com/pts.dlsu/
DLSU PTS Website
https://dlsupts.vercel.app/

CSARCH2 Mock Long Exam 1

by: Clive Jarel Ang

Important Reminders:

1. Read ALL instructions carefully and thoroughly before answering this mock exam.
2. The use of calculators and other computing devices are NOT allowed in the exam. However, you will be answering this in the comfort of your own home, so I literally have 0 control over the enforcement of that rule. ¯_(ツ)_/¯
3. Cheating in ANY form during the actual exam will be considered a major offense, merit you a 0.0 in the course, and would result in both Sir Rog and I becoming very sad.
4. This exam is GOOD FOR 3 HOURS. To be sufficiently prepared for the long exam proper, try to finish this mock exam in a shorter amount of time (while keeping a high score obv).
5. Yes, I'm sadistic and this mock exam reflects that.

I. Concepts of Data Representation in Memory

1) Which signed integer format/s has a different representation for both -0 and +0?	
2) What is the bias or excess for E' in IEEE-754 single-precision?	
3) What is the bias or excess for E' in IEEE-754 double-precision?	
4) What does sNaN stand for?	
5) What special case in binary floating point numbers has the quiet bit set to 1?	
6) What is the default rule used when performing Round to Nearest? (tie away from zero, tie to even)	

II. Understanding Integer Representation

Bits	Format	Lower bound	Upper Bound
8	Unsigned		
	S&M		
	1's C		
	2's C		

Bits	Format	Lower bound	Upper Bound
16	Unsigned		
	S&M		
	1's C		
	2's C		

III. Integer Representation

Represent the following decimal integers to the specified integer representation. **Answer in hexadecimal**. If the number cannot be represented, write "N/A".

Decimal	8-bit Unsigned Integer	8-bit Signed Integer (S&M)	8-bit Signed Integer (1's C)	8-bit Signed Integer (2's C)
-0				
+42				
-82				
+127				
-127				
+128				
-128				
+255				
-256				

Decimal	16-Bit Unsigned Integer	16-Bit Signed Integer (S&M)	16-Bit Signed Integer (1's C)	16-Bit Signed Integer (2's C)
-32768				
+32767				
+65535				

IV. Operations on Signed and Unsigned Integers

Equation	Output	Will it overflow if seen as...	
		unsigned?	signed?
0010 1010 - 0101 1010			
1100 1101 + 1001 1111			
1100 0001 - 1001 1100			
0110 1000 + 0101 1010			

V. Floating Point Representation

- For E', put a space every 4 bits.
- For the fractional part, use ellipse.
- If the answer is specified to be in hex, put a space every 4 hex digits.
- Write "N/A" if it can't be represented.
- If applicable, specify special cases after mantissa (+/- Infinity, sNaN, qNaN, Denormalized).

Express the following using IEEE 754 Single Precision (Binary-32) format:

1. $-1.011_2 \times 2^{-2}$
2. $-0.0000001_2 \times 2^{-143}$
3. $-101.25_{10} \times 2^2$
4. $+110.1001101011_2 \times 2^{127}$

#	Sign Bit	Exponent	Mantissa
1.			
2.			
3.			
4.			

Express the following using IEEE 754 Double Precision (Binary-64) format:

1. $+1.1_2 \times 2^{1023}$
2. $+19.0375_{10} \times 10^3$

#	IEEE 754 Double Precision Format (**IN HEX**)
1.	
2.	

VI. Internal Memory Representation

- Write "N/A" if it can't be represented.
- If applicable, specify special cases (+/- Infinity, sNaN, qNaN, Denormalized).

Internal Memory (hexadecimal)	View as ...	Decimal or Special Case Equivalent
	%hhu	105
	%hhd	-2
0xFFFFC	%hd	
0x7FC00000	%f	
	%f	- Infinity
0x8000000000000008	%lf	

VII. Internal Memory Representation

Note: there may be more than 1 correct answer per question.

```c
int main() {
  float float1 = 1.5;
  double float2 = float1;
  float float3 = float2;

  return 0;
}
```

1. `float1 = 1.5f` is stored in IEEE-754 single precision. After `double float2 = float1`, which statement is correct?
   a) The true binary exponent remains the same, so the exponent bits do not differ.
   b) The significand is exactly preserved, with extra zero bits appended in double.
   c) Conversion introduces rounding error because 1.5 cannot be exactly represented in IEEE-754.
   d) Converting back to `float3` from double yields a different bit pattern than the original `float1`.
   e) None of the above.

```c
int main() {
  double i = sqrt(-1);
  double j = i * i;
  double k = sqrt(-1) * sqrt(-1);

  return 0;
}
```

2. Consider the values of `i` and `j`. Which of the ff. statements are correct?
   a) `i` contains `qNaN`.
   b) `j` propagates the `NaN`, so it is also `NaN`.
   c) IEEE-754 mandates that `NaN * NaN` = $+\infty$.
   d) In C, `NaN == NaN` is `true`.
   e) None of the above.

3. Which of the following are true about sNaN vs qNaN?
   a) `sNaN`s raise invalid-operation exceptions when used in arithmetic, `qNaN`s propagate silently.
   b) C `<math.h>` functions like `sqrt(-1)` always return `sNaN`s to signal domain errors.
   c) Hardware often uses the lowest mantissa bit to distinguish `qNaN` vs `sNaN`.
   d) By default, compilers favor `qNaN` results because they do not trigger traps.
   e) None of the above.

VIII. Floating Point Rounding 1

Round to 7 bits	Truncate	Floor	Ceiling	Round to nearest (tie to even)
$+12345.6789_{10}$				
-0.00098650_{10}				
$+1.10110110_2$				
-0.00011011_2				
$+9.99999949_{10}$				
-101.111111_2				

IX. Floating Point Rounding 2

$+69.490550_{10}$	7 decimal digits	6 decimal digits	5 decimal digits	4 decimal digits
Truncate				
Floor				
Ceiling				
Round to nearest (tie to even)				

-111.1101010_2	8 binary digits	7 binary digits	6 binary digits	5 binary digits
Truncate				
Floor				
Ceiling				
Round to nearest (tie to even)				

X. Floating Point Operations

Perform the computation $1.011001011011_2 \times 2^6 \ + \ 1.1001101101_2 \times 2^3$ to 8 bits (use round to nearest, ties to even if needed). All answers should be in normalized form.

a) Perform without guard, round, and sticky bits.

		$Base^{Exp}$
Operand 1		
Operand 2		
Final Sum		

b) Perform with guard(G), round(R), and sticky(S) bits.

		G	R	S	$Base^{Exp}$
Operand 1					
Operand 2					
Final Sum		-	-	-	

1) Which method should theoretically be more accurate? (Rounding or GRS method)	

XI. Understanding Computer Organization 1

- Write "N/A" if it can't be represented.

Data Type	Bits	Format Specifier	
		Unsigned	Signed
char			
short			
int			
SP float			
long long int			
DP float			

XII. Understanding Computer Organization 2


1) What is the LSCrumb of 0xFACADE?	
2) Assuming 32-bit architecture, what is the MSWord of 0xDEFACED1?	
3) How many bytes are there in 4 gigabytes?	
4) How many bytes are there in 2 kibibytes?	
5) A group of 4 bits is also known as a what?	
6) Let addr 00 contain 0x01; addr 01 is 0x23; addr 02 is 0x45; addr 03 is 0x67. What is the 1-byte data at addr 3 assuming Little Endian?	
7) Let addr 03 contain 0x01; addr 02 is 0x23; addr 01 is 0x45; addr 00 is 0x67. What is the 2-byte data at addr 2 assuming Big Endian?	

XIII. Memorizing Base-2 [Bonus]

x	2^x
1	
2	
3	
4	
5	
6	
7	
8	
9	

x	2^x
10	
11	
12	
13	
14	
15	
16	
17	
18	

x	2^x
19	
20	
21	
22	
23	
24	
25	



Verified and Checked by:

Anthony Baybayon - Vice President for Academics
anthony_baybayon@dlsu.edu.ph
Clive Jarel Ang - Associate Vice President for Academics
clive_jarel_c_ang@dlsu.edu.ph

Contact for Concerns:

Roemer Gabriel Caliboso - President
roemer_caliboso@dlsu.edu.ph
Anthony Baybayon - Vice President for Academics
anthony_baybayon@dlsu.edu.ph
Clive Jarel Ang - Associate Vice President for Academics
clive_jarel_c_ang@dlsu.edu.ph