

Hilbert's 10th Problem, Undecidability, & The Halting Problem

A mini-lecture series

CSE498 Collaborative Design (W) - Secure and Efficient C++ Software Development

03/24/2025

Kira Chan

<https://cse.msu.edu/~chanken1/>

David Hilbert

- Brilliant mathematician in the early 1900s
- During his speech to the International Congress of Mathematicians in 1900, he presented 23 unsolved problems
- His 10th problem:
 - For any given Diophantine equation, can we *decide* whether the equation has a solution?
- This problem remained unsolved for 70 years, until 1970



Decidability

- In computer theory, an undecidable problem is one which it is impossible to construct an algorithm that can always lead to a yes or no answer
- Hilbert called it ***Entscheidungsproblem*** (decision problem)
- Example: Halting problem

Halting Problem

- Can you write a computer program P that:
 - For a given input, a computer program i , determine whether i will:
 - Halt (exit execution)
 - Run indefinitely
- To prove this, you must show that
 - Decide on ALL existing programs, even ones that have not existed
 - OR use prove by contradiction (show an instance of the problem that cannot logically exist)

Alan Turing's Paper in 1936

230

A. M. TURING

[Nov. 12,

ON COMPUTABLE NUMBERS, WITH AN APPLICATION TO THE ENTSCHEIDUNGSPROBLEM


By A. M. TURING.

[Received 28 May, 1936.—Read 12 November, 1936.]

The “computable” numbers may be described briefly as the real numbers whose expressions as a decimal are calculable by finite means. Although the subject of this paper is ostensibly the computable *numbers*, it is almost equally easy to define and investigate computable functions of an integral variable or a real or computable variable, computable predicates, and so forth. The fundamental problems involved are, however, the same in each case, and I have chosen the computable numbers for explicit treatment as involving the least cumbrous technique. I hope shortly to give an account of the relations of the computable numbers, functions, and so forth to one another. This will include a development of the theory of functions of a real variable expressed in terms of computable numbers. According to my definition, a number is computable if its decimal can be written down by a machine.


Halting Problem

- Suppose there exist a program h_* that can magically decide whether a program halts or not




Halting Problem

- Let's construct a new program H , based on h_* as follows
 - If h_* says that the problem halts, then run forever
 - Else, halt



Contradiction

- What happens when we feed the program an instance of itself?
 - If H halts, then h_+ returns yes; but it runs forever
 - If H does not halt, then h_+ returns no; but it does halt



Halting Problem - Results

- The halting problem showed an instance of a problem that *cannot be solved by computers*
- This problem showed that some functions are mathematically definable, but not computable

Implications

- Actually equivalent (can be reduced) to Hilbert's 10th problem
 - Proved by Matiyasevich
- Previously, we discussed that exhaustive testing is mathematically infeasible
- Microsoft rolls out a new update, and they want to make sure that it does not break backwards compatibility at all. This is actually just the halting problem
- Practically, it is to be able to tell your boss that “what you are asking for is mathematically impossible, and I can prove it”
 - Write a program that can automatically debug other programs

XKCD - 1425



IN CS, IT CAN BE HARD TO EXPLAIN
THE DIFFERENCE BETWEEN THE EASY
AND THE VIRTUALLY IMPOSSIBLE.

Summary

- One of the most important results in our field
- Halting problem showed that there exist problems in which computers cannot compute
- Some what defines the limits of what programming can do

Person of the day

David Parnas

- Another prominent figure in software engineering
- Information hiding
- Modularity, component-based reuse
- Separation of concerns
- Software of defence planes
- Abstraction
- Scalability
- Design patterns are really based on things that Parnas came up with

