# pastclim:: cheat sheet

### **Basics**

pastclim is an R package to easily download and manipulate paleoclimatic data.

#### **INSTALLATION**

Installation through devtools



library(devtools)

install\_github("EvolEcolGroup/pastclim", build\_vignettes = TRUE)

#### **VIGNETTE**



."vignette("pastclim\_overview "package = "pastclim")

### Data

#### **NATIVE DATASETS**



#### Beyer2020:

- 28 variables
- present-120k years ago
- every 1000/2000 years

#### **Krapp2021:**

- 25 variables
- present-800k years ago
- · every 1000 years



#### Example: -

- 3 variables
- 3 time slices

#### LIST ALL AVAILABLE DATASETS



vignette("available\_datasets", package = "pastclim")

Do not use for

analyses!

#### ADD MORE DATA

Follow the instructions from the "custom datasets" vignette



vignette("custom\_datasets", package = "pastclim")

### Download the data

Download the full dataset

By default it will be stored within the package



download\_dataset(dataset="Beyer2020")

Download only a few variables



You can change where the data is saved



set\_data\_path(path\_to\_nc = "~/climate")

## Working with locations

Retrieve the climate for several locations scattered in time and/or space.

Format them as a data.frame with longitude, latitude, age.



$$\label{eq:continuous} \begin{split} & \text{locations} <\text{- data.frame(} \\ & \text{x=c(0,90,-120,-7),} & \text{\# longitude} \\ & \text{y=c(20,45,60,37),} & \text{\# latitude} \\ & \text{time=c(0,-10000, -20000, -10000))} \end{split}$$

#### Retrieve the climate



location\_slice(

x= locations[,c("x", "y")],
time\_bp = locations\$time,
bio\_variables=c("bio01","bio12"),
dataset="Example")

warning: Some locations may fall under ice or water, where the climate is unavailable.

nn interpol = TRUE (the default) interpolates the climate among the neighbouring cells.

Retrieve time series of the climate for each location (interpolation not available)



location\_series(
 x= locations[,c("x", "y")],
 bio\_variables=c("bio01","bio12"),
 dataset="Example")

### Working with regions

Get climate for the world



region\_slice(
time\_bp = -20000,
bio\_variables=c("bio01", "bio12"),
dataset = "Example")

Get time series for the world

df\_from\_region\_slice() and
 df\_from\_region\_series()
will transform the outputs
 into dataframes

• "N\_America"



region\_series(

bio\_variables=c("bio01", "bio12"),
dataset = "Example")

Both functions can include the arguments

- 'crop' to crop results based on a polygon
- 'ext' to crop results based on an extent

# Cropping

Pre-set rectangular extents are available:



names(region\_extent)

- "Africa" "America" "Asia"
- "Europe""Eurasia""S\_America""Oceania"

Get time series for Asia using an extent



region\_series(
 bio\_variables=c("bio01", "bio12"),
 dataset = "Example",
 ext=region\_extent\$Asia)

Pre-generated masks detailing specific continental masses



names(region\_outline)

- "Africa" "N\_America" "Eurasia" "Oceania" "S\_America"
- Get climate from Africa using a mask



region\_slice(
 time\_bp = -20000,
 bio\_variables=c("bio01", "bio12"),
 dataset = "Example",
 crop = region\_outline\$Africa)

# Sampling

Sampling 100 random points from a region

```
climate_20k <- region_slice(
    time_bp = -20000,
    bio_variables = c("bio01", "bio10"),
    dataset = "Example")

sample_region_slice(
    climate 20k,
```

Sampling from a time series, 100 points from the first time slice, 50 from the second.

size = 100

```
climate_ts <- region_series(
    time_bp = c(-20000,-10000),
    bio_variables = c("bio10", "bio12"),
    dataset = "Example")

sample_region_series(
    climate_ts,
    size = c(100,50))

To sample the same amount from all time slices write only one number
```

### Citation

Cite pastclim

citation("pastclim")

Cite database

help("Beyer2020")

# Need help?



https://rdrr.io/github/EvolEcolGroup/ pastclim/man/



https://github.com/EvolEcolGroup/pastclim



https://evolecolgroup.github.io/pastclim/



<u>am315@cam.ac.uk</u> (Andrea Manica)

