Request API handover

A sample integration guide for the fictional Northwind request service.

Create a request

Send a title, category, and requester reference. The service returns the request identifier and initial status.

```http
POST /requests
Content-Type: application/json

{
  "title": "Prepare a new workspace",
  "category": "equipment",
  "requester": "team-delivery"
}
```

Field contract

Field	Required	Meaning
title	Yes	Short description of the requested outcome
category	Yes	Routing category agreed with the service owner
requester	Yes	Stable caller-owned reference

Read the response

```json
{
  "id": "REQ-1042",
  "status": "submitted"
}
```

> **Integration checklist**
>
> Agree authentication, retry behavior, validation errors, and rate limits with the service owner. The payloads here describe a fictional API.

Support handover

Record the integration owner, an escalation route, and a representative successful request before enabling a production caller.

Handle an unsuccessful request

Response	Caller action
400 - Invalid payload	Correct the named field before sending another request
401 - Authentication required	Check the configured identity and credential lifetime
429 - Rate limited	Respect the agreed retry delay and avoid parallel retries
503 - Service unavailable	Use a bounded retry policy and contact the service owner

Record a handover example

```text
Environment: test
Caller: workspace-intake
Request: REQ-1042
Result: submitted
Integration owner: Workplace team
Service contact: Operations queue
```

Before enabling the caller

- Verify one accepted request and one rejected request.
- Agree how to detect and prevent duplicate submissions.
- Keep credentials and personal data out of diagnostic logs.
- Confirm the support route and the first review date.