

NEPTUNE : FINITE ELEMENT MODELLING @ UKAEA

Owen Parry, UKAEA

Will Saunders, UKAEA

Ed Threlfall, UKAEA

NEPTUNE Workshop

5-6 September 2022

© Crown Copyright 2022



UK Atomic
Energy
Authority

FEM in NEPTUNE

Summary of UKAEA activities

1. 1D scrape-off layer modelling with finite elements
(Will Saunders, Owen Parry)
2. Nektar++ changes for NEPTUNE integration
(Owen Parry)
3. Finite element exterior calculus
(Ed Threlfall)

1D SOL Proxyapp

Model description





Image from Riva, 2019

- Simple, 1D model of the tokamak scrape-off layer
- Flux tube aligned with a magnetic field line
- Mass deposited into the domain by perpendicular transport
- Single fluid of electrons and ions
- Sonic outflow at either end to approximate sheath BCs

- No neutrals



$$U_r \frac{\partial n}{\partial t} = -\frac{\partial}{\partial s}(nu) + S^n,$$

$$U_r \frac{\partial}{\partial t}(nu) = -\frac{\partial}{\partial s}(nu^2) - \frac{\partial}{\partial s}(nT) + S^u,$$


$$U_r \frac{\partial}{\partial t}((g-2)nT + nu^2) = -\frac{\partial}{\partial s}(gnuT + nu^3) + \kappa_d \frac{\partial^2 T}{\partial s^2} + S^E,$$

g : Specific heat capacity
 κ_d : Conduction coefficient


1D SOL Proxyapp

Soldrake (Will Saunders)


- *Firedrake* used to implement equations in weak form with Unified Form Language (UFL)
- Continuous Lagrange basis functions
- *Irksome* used for (Runge-Kutta) time integration
- Evolve to near equilibrium from ICs, add small amount of diffusion to stabilise.
- Use result as initial guess for



Varying conduction



Error as a function of N_p




Including neutrals

[75] W. Saunders and E. Threlfall. *Finite Element Models: Performance*. Tech. rep. CD/EXCALIBUR-FMS0047-M2.2.2. https://github.com/ExCALIBUR-NEPTUNE/Documents/blob/main/reports/ukaea_reports/CD-EXCALIBUR-FMS0047-M2.2.2.pdf. UKAEA, 2021.

1D SOL Proxyapp

Nektar++ solver

- Nektar++ version of the same solver, implemented by Dave Moxey with support from OP
- Choose constants such that the problem reduces to solving incompressible Euler equations
- Discretisation: Discontinuous Galerkin
- Time evolution: 4th order Runge-Kutta



to match Soldrake implementation


New Nektar++ solver

- Define equation system, based on existing advection solver
- Specify desired source terms via Forcing function framework
- Configure and run solver on simple 1D domain

Code at <https://github.com/ExCALIBUR-NEPTUNE/nektar-1d-sol>

1D SOL Proxyapp

Nektar++ results



- Good agreement with analytical solution presented by Arter (and with Soldraker)


Source: Arter, Study of source terms in the SOLF1D edge code. Technical report, Eurofusion/CCFE, 2015. CCFE-DETACHMENT-RP2-Draft.

Nektar++ integration in NEPTUNE

NESO

- Nektar functionality already being used in NEPTUNE prototype code
- See *NESO* git repo at <https://github.com/ExCALIBUR-NEPTUNE/NESO> + Will and James' talks:

Coupling between PIC code, Nektar++
in NESO



NESO
overview



Nektar++ integration in NEPTUNE

Changes to Nektar core libraries

tatus quo: define session in one or more XML files

XML session file

```
<?xml version="1.0" encoding="utf-8" ?>
<NEKTAR>
  <GEOMETRY DIM="1" SPACE="1">
    <VERTEX>
    <ELEMENT>
    <COMPOSITE>
    <DOMAIN>
  </GEOMETRY>
  <EXPANSIONS>
  <FORCING>
  <CONDITIONS>
    <PARAMETERS>
    <SOLVERINFO>
    <VARIABLES>
    <BOUNDARYREGIONS>
    <BOUNDARYCONDITIONS>
    <FUNCTION NAME="InitialConditions">
    <FUNCTION NAME="ExactSolution">
  </CONDITIONS>
</NEKTAR>
```

Solver code

Session, including mesh, read here

```
SessionReaderSharedPtr session = SessionReader::CreateInstance(argc, argv);
MeshGraphSharedPtr mesh = MeshGraph::Read(session);
string driverName("Standard");
DriverSharedPtr driver = GetDriverFactory().CreateInstance(driverName, session, mesh);
driver->Execute();
session->Finalise();
```

Pass session filepath(s) to the solver at runtime:

```
my_solver.exe [path_to_session.xml]
```


Nektar++ integration in NEPTUNE

Changes to Nektar core libraries

```
<CONDITIONS>
  <PARAMETERS>
    <P> TimeStep      = 5e-4          </P>
    <P> NumSteps      = 1000000       </P>
    <P> IO_CheckSteps = 10000         </P>
    <P> IO_InfoSteps  = 1000          </P>
    <P> Gamma         = 5.0/3.0       </P>
    <P> GasConstant   = 1.0           </P>
    <P> pInf           = 1.0           </P>
    <P> rhoInf         = 1.0           </P>
    <P> uInf           = 1.0           </P>
  </PARAMETERS>
  <SOLVERINFO>
    <I> PROPERTY="EQTYPE"          VALUE="SOL"          </I>
    <I> PROPERTY="Projection"      VALUE="DisContinuous" </I>
    <I> PROPERTY="AdvectionType"   VALUE="WeakDG"      </I>
    <I> PROPERTY="TimeIntegrationMethod" VALUE="ClassicalRungeKutta4" </I>
    <I> PROPERTY="UpwindType"      VALUE="ExactToro"     </I>
  </SOLVERINFO>
  <VARIABLES>
    <V ID="0"> rho </V>
    <V ID="1"> rhou </V>
    <V ID="2"> E </V>
  </VARIABLES>
```

XML session configuration

```
// Variable names
std::vector<std::string> varNames = { "rho", "rhou", "E" };

// Set params of type double
std::map<std::string, NekDouble> dblParams;
dblParams["TimeStep"] = 5e-4;
dblParams["Gamma"] = 5.0/3;
dblParams["GasConstant"] = 1.0;
dblParams["pInf"] = 1.0;
dblParams["rhoInf"] = 1.0;
dblParams["uInf"] = 1.0;

// Set params of type int
std::map<std::string, int> intParams;
intParams["IO_CheckSteps"] = 10000;
intParams["IO_InfoSteps"] = 1000;
intParams["NumSteps"] = 1000000;

// Set solver properties
std::map<std::string, std::string> solverInfo;
solverInfo["EQTYPE"] = "SOL";
solverInfo["Projection"] = "DisContinuous";
solverInfo["AdvectionType"] = "WeakDG";
solverInfo["TimeIntegrationMethod"] = "ClassicalRungeKutta4";
solverInfo["UpwindType"] = "ExactToro";

// Set up session
LibUtilities::SessionConfigurableSharedPtr session;
session = LibUtilities::SessionConfigurable::CreateInstance(argc, argv,
    "sol1D", varNames, dblParams, intParams, solverInfo);
```

Programmatic session configuration

Finite element exterior calculus (FEEC)

(Work by Ed Threlfall)

- Framework for formulating finite element methods with useful numerical properties
- Developed by Douglas Arnold, and others, in early 2000s
- Combines ideas from homological algebra, functional analysis, exterior calculus

Can be used to ensure that a numerical method

- is naturally stable without adding artificial dissipation
- explicitly conserves certain quantities (e.g. electric charge)

Used in several major PIC codes: GEMPIC, EMPIRE

Numerous examples in the literature that illustrate FEEC utility; for instance...

Finite element exterior calculus (FEEC)

An example with Firedrake

Example from Douglas Arnold's book, run with Firedrake

D.N. Arnold, *Finite Element Exterior Calculus*, CBMS-NSF regional conference series in applied mathematics 93, SIAM.


- “re-entrant corner” problem:

Solve $\nabla^2 \underline{u} = \underline{f}$ on an L-shaped domain with source on interior
with $\underline{f} = (1, 0)$ and $\underline{u} \cdot \underline{n} = \nabla \times \underline{u} = 0$ on the boundary.

Solution: singularity of the form
(r : distance from the corner)

6th order vector Lagrange FS for

Attempt 1



Converged, smooth... wrong! Need *mixed* formulation

Finite element exterior calculus (FEEC)

An example with Firedrake


- “Re-entrant corner” problem:

Solve $\nabla^2 \underline{u} = \underline{f}$ on an L-shaped domain with source on interior
with $\underline{f} = (1, 0)$ and $\underline{u} \cdot \underline{n} = \nabla \times \underline{u} = 0$ on the boundary.

Solution: singularity of the form
(r: distance from the corner)

6th order vector Lagrange FS for
6th order scalar Lagrange FS for


Attempt 2



Spurious oscillations due to
inconsistent choice of function
spaces

6th order vector Raviart-Thomas “Edge”
FS for

6th order scalar Lagrange FS for
Attempt 3



Smooth, resolves
singularity

Finite element exterior calculus (FEEC)

Lessons

- FEEC framework can help guarantee stability and conservation in FEM approaches
- Principles are easily demonstrated in idealised examples, but apply equally to real-world modelling
- Wide range of element types available – need to study literature to make a sensible choice
- FEEC increasingly being applied in PIC codes – may well be an essential ingredient for NEPTUNE

Conclusion

Progress towards Nektar++/NEPTUNE integration

- Nektar++ already applied to several problems relevant to edge-plasma physics
- FEEC offers a promising avenue to improve solver stability, apply conservation laws in FEM
- PIC code / Nektar++ coupling: already started in NESO
- FEM-related NEPTUNE development:
- Nektar++ setup without XML: almost complete
- FEEC in Nektar++: future challenge