```sql
BEGIN;

-- Tablas (coinciden con tus entidades)
CREATE TABLE IF NOT EXISTS usr (
  id              INTEGER GENERATED BY DEFAULT AS IDENTITY PRIMARY KEY,
  name            VARCHAR(120),
  identification  VARCHAR(60) UNIQUE NOT NULL,
  email           VARCHAR(180) UNIQUE NOT NULL,
  password        VARCHAR(120) NOT NULL,
  role            VARCHAR(60),
  lon             DOUBLE PRECISION,
  lat             DOUBLE PRECISION
);

CREATE TABLE IF NOT EXISTS vehicle (
  id               INTEGER GENERATED BY DEFAULT AS IDENTITY PRIMARY KEY,
  type             VARCHAR(40),
  plate            VARCHAR(15) UNIQUE NOT NULL,
  soat_rate_type   VARCHAR(40),
  model            INTEGER,
  soat_expiration  DATE,
  techno_expiration   DATE,
  usr_id           INTEGER REFERENCES usr(id) ON DELETE CASCADE
);

-- Limpieza (idempotente)
TRUNCATE TABLE vehicle RESTART IDENTITY CASCADE;
TRUNCATE TABLE usr RESTART IDENTITY CASCADE;

-- Usuarios
INSERT INTO usr (name, identification, email, password, role, lon, lat) VALUES
  ('Ana Romero',      'CC1001', 'ana.romero@example.com',
'$2a$10$8TcBzrwjMGYiNAMipQ4YO.rfc1AMhpOBhd7lVJRYnKLILvFb/.5Eq', 'Cliente',
-74.108108, 4.5940736),
  ('Bruno Pérez',     'CC1002', 'bruno.perez@example.com',
'$2a$10$8TcBzrwjMGYiNAMipQ4YO.rfc1AMhpOBhd7lVJRYnKLILvFb/.5Eq', 'Cliente',
-74.120000, 4.5950000),
  ('Carla Díaz',      'CC1003', 'carla.diaz@example.com',
'$2a$10$8TcBzrwjMGYiNAMipQ4YO.rfc1AMhpOBhd7lVJRYnKLILvFb/.5Eq', 'Cliente',
-74.090000, 4.5930000),
  ('Diego Fernández', 'CC1004', 'diego.fernandez@example.com',
'$2a$10$8TcBzrwjMGYiNAMipQ4YO.rfc1AMhpOBhd7lVJRYnKLILvFb/.5Eq', 'Cliente',
-74.105000, 4.5935000),
  ('Elena García',    'CC1005', 'elena.garcia@example.com',
'$2a$10$8TcBzrwjMGYiNAMipQ4YO.rfc1AMhpOBhd7lVJRYnKLILvFb/.5Eq', 'Cliente',
-74.099000, 4.5942000),
```

```sql
  ('Fabio Núñez',      'CC1006', 'fabio.nunez@example.com',
'$2a$10$8TcBzrwjMGYiNAMipQ4YO.rfc1AMhpOBhd7lVJRYnKLlLvFb/.5Eq', 'PARTNER',
-74.115000, 4.5928000),
  ('Gina López',       'CC1007', 'gina.lopez@example.com',
'$2a$10$8TcBzrwjMGYiNAMipQ4YO.rfc1AMhpOBhd7lVJRYnKLlLvFb/.5Eq', 'Cliente',
-74.101000, 4.5941000),
  ('Hugo Salazar',     'CC1008', 'hugo.salazar@example.com',
'$2a$10$8TcBzrwjMGYiNAMipQ4YO.rfc1AMhpOBhd7lVJRYnKLlLvFb/.5Eq', 'Cliente',
-74.095000, 4.5946000);

-- Vehículos (columnas alineadas: SIN techno_classification, CON model INT)
INSERT INTO vehicle
  (type,            plate,   soat_rate_type, model, soat_expiration, techno_expiration, usr_id)
VALUES
  -- Ana (id 1)
  ('Liviano Particular','ABC123','100',       2020,  DATE '2025-06-15', DATE '2025-07-10', 1),
  ('Motos',            'XYZ09A','100',        2020,  DATE '2026-03-20', DATE '2026-04-05', 1),

  -- Bruno (id 2)
  ('Liviano Particular','DEF456','100',       2020,  DATE '2024-12-20', DATE '2025-01-15', 2),
  ('Liviano Particular','TRK789','100',       2020,  DATE '2025-02-28', DATE '2025-03-10', 2),

  -- Carla (id 3)
  ('Liviano Particular','GHI321','100',       2020,  DATE '2026-01-01', DATE '2025-11-01', 3),
  ('Liviano Particular','MOT777','Moto',      2020,  DATE '2025-05-05', DATE '2025-06-01', 3),

  -- Diego (id 4)
  ('Liviano Particular','JKL654','100',       2020,  DATE '2026-08-30', DATE '2026-09-15', 4),

  -- Elena (id 5)
  ('Liviano Particular','MNO987','100',       2020,  DATE '2025-08-01', DATE '2025-08-20', 5),

  -- Fabio (id 6)
  ('Liviano Particular','CGR111','100',       2020,  DATE '2026-02-14', DATE '2026-02-28', 6),
  ('Liviano Particular','VAN222','100',       2020,  DATE '2025-09-15', DATE '2025-09-20', 6),

  -- Gina (id 7)
  ('Liviano Particular','PRV333','100',       2020,  DATE '2026-05-10', DATE '2026-05-25', 7),

  -- Hugo (id 8)
  ('Liviano Particular','BIK444','100',       2020,  DATE '2025-04-14', DATE '2025-04-30', 8);

COMMIT;
```