

Technical Specification

Person API



Table of Contents

1 Introduction	3
1.1 Prerequisites	3
1.1.1 Bus card information	3
2 Domain model	4
3 Entities	5
3.1 Properties	5
3.2 Person	5
3.2.1 Person attributes	5
3.2.2 Person extensions	6
3.2.3 Person extra attributes	6
3.3 Buscardinfo	7
4 Services	8
4.1 Export of person information	8
4.2 Update person contact information	8
4.3 Create extra attributes	9
4.4 Get extra attributes	9
4.5 Update extra attributes	10
4.6 Delete extra attributes	10
4.7 Get bus card information	10
4.8 Update bus card information	11
5 Appendix	12
5.1 References	12
5.2 Vocabulary	12

1 Introduction

The Person API provides services that make it possible to get, create and update information of persons – and some person related information – in the Tieto Education system. The services in the Person API are accessed via URIs.

This document describes following:

- Which person information that can be fetched and updated.
- How the entities are structured.


1.1 Prerequisites

Before you can get access to the Person API you must request a license key from Tieto. You should have basic knowledge about the W3C XML before you start using the API.

1.1.1 Bus card information


To have the reading and writing of bus card information work properly, a setup must be used in the code registry in Tieto Education.

To identify which code in the code registry that shall identify a BusCard, open the Code Registry in Tieto Education with a System administrator role for Compulsory School. Using **Menu -> Basic information -> Code** and filtering for “Skolskjuts”, you get all available codes. Update the one to use for BusCard with the value “API” in Xtrainfo (see picture below). If no code has this mark, the Bus card information API will not work.



2 Domain model

The diagram below describes how the information of person and extra attributes are related.



The model describing bus card information is a single object without relations.

3 Entities

3.1 Properties

The delivery information of the Person packaging that is used to manage the exchange of data between source and target system.

Name	Description
datasource	This is the source identifier of data source
comments	Input values for the service.
type	Enumerated as PersonInfo, BusCardInfo
datetime	The date and time the XML information were generated. The format is as [YYYY-MM-DDTHH:MM:SS]
timeframe	Timeframe for the person data

3.2 Person

The person object contains information about person in Tieto Education Student management system. All persons are identified with a personal identity and Globally Unique Identifier (GUID). The personal identity could be temporary or generated from Skatteverket, for more information see www.skatteverket

3.2.1 Person attributes

Name	Description	Read-only
sourcedid.id	The persistent unique identity of the person	Yes
userid.value	Alternative unique identifiers of the person	Yes
userid.useridtype	Enumerated as PID, GUID	Yes
name.fn	Formatted name ([middle name] [lastname], [firstname])	Yes
name.n.given	The given name and not necessarily the first name	Yes
name.n.partname.partnametype	The type of partname. "Middle" is used for middle name.	Yes
name.n.partname.Value	Middle name	Yes
name.n.family	This is the family name	Yes
emailhome	Email home address	No
emailworkschool	Work email for staff, school email for students	No
tel	Phone numbers	No
tel.teltype	Identifies the type of telephone number. Enumerated as Voice, Mobile and Work, where Voice is home phone.	No
adr.pcode	The post identity number	Yes
adr.street	The actual street address	Yes

Common extended properties for all persons

Name	Description	Read-only
privacy	The person has restrictions. This is enumerated as None, Level1. Level1 means privacy highlighted by the "Skatteverket".	Yes
geographickeycode	Geographic key code	Yes
municipalitycode	Municipality code, formatted [NNNN], for more information see www.ski.se	Yes
municipalityname	Municipality name	Yes
timestamp	Date and time when person is created, updated or deleted.	Yes
status	Status Normal The person is alive and lives in Sweden Deceased The person has deceased Emigrated The person has emigrated	Yes
residentstatus	AsylumSeeker Asylum seeker EuEssSwitzerlandCitizen Citizen within EU, ESS, Schweiz NordicCitizen Nordic citizen ExchangeStudent Exchange student SwedishForeign Swedes that live abroad OtherForeignCitizen Other foreign citizen DiplomatChildrenWithinEuEs sSwitzerland Diplomatic children within EU, ESS, Schweiz DiplomatChildrenOutsideEuE ssSwitzerland Diplomatic children outside EU, ESS, Schewiz PermitApplicationSeeker Permit application seeker Unknown Unknown Resident status	Yes
nativelanguage	Native language, formatted as longer a form of language name	Yes

It is possible to attach extra information to a person. This information will not be visible anywhere in the Tieto Education interface. The API ensures that the data is stored and can be retrieved on demand. When a person is deleted in the UI the extra attributes attached to that person are also deleted. These are modelled on a combination of sources to provide enough freedom for a range of integration scenarios. See [Section 5.1](#) for more information.

Name	Description	Read-only
attributeld	GUID that uniquely identifies this set of attributes	Yes
service	A descriptive identifier what these attributes are for. Examples can be Azure Ad, Google. Three service names are reserved by Tieto Education for possible future use, these are eduroam , swamid , skolfederation	Required during create, cannot be changed.
eduPersonPersistentId	Max 256 characters. Free to use for any purpose. Modelled on section 8.3.7 of SAML 2.0 core	No
eduPersonPrincipalName	Max 256 characters. Free to use for any purpose. Recommendation is to map this to UserPrincipalName in AD or Azure AD.	No
eduPersonUniqueId	Max 321 characters. Free to use for any purpose.	No
eduPersonTargetedId	Max 2500 characters. Free to use for any purpose	No
eduPersonAffiliation	A list of strings, each string can be max 256 characters. Free to use for any purpose	No
eduPersonScopedAffiliation	A list of strings, each string can be max 256 characters. Free to use for any purpose	No
eduPersonEntitlement	A list of strings, each string can be max 1024 characters. Free to use for any purpose	No

3.3 Buscardinfo

Name	Description	Read-only
student.id	Unique identifier for the student	Yes
student.name	Students full name	Yes
eligible-for-buscard	Tells if the student eligible for a bus card or not. Not currently used	Yes
dateframe.start	First day when the bus card is valid. Iso-8601 formatted date	No
dateframe.end	Last day when the bus card is valid. ISO-8601 formatted date. Defaults to 9999-12-31 which means no end date set.	No
distance	Distance in km between where the student lives and the school.	No
buscardtype	Enumeration, either BusCard or Unknown. When updating, BusCard is the only valid value	Yes
buscardnumber	Number of the bus card assigned to this student	No

4 Services

All services are based on HTTP REST technology. “Get services” are using the method HTTP GET, “Update services” and “Create services” are using the method HTTP POST and “Delete services” are using the method HTTP DELETE.

Base paths for these services are:

- For internet use: [https://\[host\]/WE.Education.Integration.Host.Proxy/LES/Person/V1/Person](https://[host]/WE.Education.Integration.Host.Proxy/LES/Person/V1/Person)
- For intranet use: [http://\[host\]/WE.Education.Integration.Host/LES/Person/V1/Person.svc](http://[host]/WE.Education.Integration.Host/LES/Person/V1/Person.svc)

4.1 Export of person information

These services return specific person information, in the <person-root>-element.

As input this service takes XML information according to the XML schema for “person-root” in the Person API xsd.

Parameters:

Parameter	Mandatory	Description
PersonId	Yes	The id can be GUID or PID for the person.
EmailType	No	Email type specifies which email id field to be exported. Possible values are <ul style="list-style-type: none">- EPOSTARB - Exports EPOSTARB value from person, this is the default value- EPOSTGEN - Exports EPOSTGEN value from person
ExtraAttributes	No	Boolean. True includes all stored extra attributes for the person

Services:

Service	Description
GetPersonInfo	Returns person information.

4.2 Update person contact information

This service is used to update contact information of persons (email and telephone numbers). If an email or phone number is not supplied in the supplied data, the corresponding value in Tieto Education is not changed.

As input this service takes XML information according to the XML schema for “person-contact-root” in the Person API xsd.

Parameters:

Parameter	Mandatory	Description
EmailType	No	Email type specifies which email id field to be updated. Possible values are <ul style="list-style-type: none"> - EPOSTARB - Updates EPOSTARB value for person, this is the default value - EPOSTGEN - Updates EPOSTGEN value for person - EPOSTARB_EPOSTGEN - update both EPOSTARB and EPOSTGEN values for person

Services:

Service	Description
UpdateContactInformation	Update persons contact information

4.3 Create extra attributes

This service is used to create a new set of attributes for a service and person. A complete person object with services is returned.

It is not allowed to create extra attributes for services that the person already has.

As input this service takes XML information according to the XML schema for "person" in the Person API xsd. The identification of the person is done by setting (at least) one of the "userid"-elements. No other elements (beside "extraattribute") will be handled in this operation and can therefore be omitted.

Services:

Service	Description
CreateExtraAttributes	Create attributes for one or more new services.

4.4 Get extra attributes

This service allows fetching the attributes for a single service and person.

Parameters

Parameter	Mandatory	Description
attributeld	Yes	GUID that uniquely identifies this service and person.

Services:

Service	Description
GetExtraAttributes	Returns the attributes for a single service and person

4.5 Update extra attributes

This service allows updating attributes for one or more services and persons. Any attributes left out of the request will be deleted if they're previously stored.

As input this service takes XML information according to the XML schema for "extraattributes" in the Person API xsd.

Services:

Service	Description
UpdateExtraAttributes	update attributes for one or more stored services.

4.6 Delete extra attributes

This service allows deleting attributes for a single service

Parameters

Parameter	Mandatory	Description
attributeld	Yes	GUID that uniquely identifies this service and person.

Services:

Service	Description
DeleteExtraAttributes	deletes the attributes for a single service and person

4.7 Get bus card information

This service allows getting bus card information, for either a single student, or all on-going and future bus cards.

Parameters:

Parameter	Mandatory	Description
PersonId	No	GUID or PID that uniquely identifies the person to retrieve bus card information about. Supersedes SearchDate.
SearchDate	No	The search date. Current date will be used if SearchDate is not specified. The oldest search date that can be used is current date minus ten years.

Services:

Service	Description
GetBusCardInformation	Returns the bus card information according to the given parameters.

4.8 Update bus card information

This service allows updating of bus card information, for a number of students.

Each given bus card information in the input is compared to existing data in the system. For a given input that has a counterpart in the system, the system will be updated. Otherwise a new object will be created.

The criteria for finding a counterpart is that:

- Same student
- Both are bus cards
- Both have same bus card number
- Overlapping periods

An update only changes the <dateframe>.

A create sets all values of the bus card info. Only compulsory students are allowed as <student>. Only BusCard is allowed as <buscardtype>.

As input this service takes XML information according to the XML schema for “person-root” with “buscardinfo” elements in the Person API xsd.

Services:

Service	Description
UpdateBusCardInformation	Update bus card information according to the input data.

5 Appendix

5.1 References

Name	Address
IMS Enterprise Information Model	http://www.imsglobal.org/enterprise/entv1p1/imsent_infov1p1.html
IMS Enterprise XML Binding Specification	http://www.imsglobal.org/enterprise/entv1p1/imsent_bindv1p1.html
IMS Enterprise Best Practices and Implementation Guide	http://www.imsglobal.org/enterprise/entv1p1/imsent_bestv1p1.html
Person API XML schemas and examples	https://github.com/ExchangeServices
SAML 2.0	http://saml.xml.org/saml-specifications
SWAMID	https://www.sunet.se/swamid/
Skolfederation	https://www.skolfederation.se/
REFEDS EduPerson	https://wiki.refeds.org/pages/viewpage.action?pageId=44957737

5.2 Vocabulary

Word	Description
PID	Personal identity, formatted [YYYYMMDDNNNN]
GUID	Global unique identifier