

# Lifecare Exchange Services

## Message API




## Table of Contents

<b>1 Introduction .....</b>	<b>3</b>
1.1 Prerequisites .....	3
<b>2 Entities .....</b>	<b>4</b>
2.1 Message .....	4
2.2 FaultContract .....	4
<b>3 Services .....</b>	<b>5</b>
3.1.1 SendMessage .....	5
<b>4 WSDL .....</b>	<b>6</b>

## 1 Introduction

The Message API in Lifecare Exchange Services defines a common interface to send and retrieve e-mail, SMS text messages. By default Tieto offer services for SMS and email notifications. Customers with existing notification infrastructure can implement this message interface to replace default message provider.



### 1.1 Prerequisites

Before you can get retrieve any messages you must request a license key from Tieto. You should also have basic knowledge Web Services technology before you begin to implement the API.

## 2 Entities

### 2.1 Message

Message structure for SMS and email notifications.

Parameter	Mandatory	Description
Recipients	Yes	One or more receivers of the message. All receivers are identified with a personal number, phone number or email address.
Sender	No	Identity of the actual sender.
Subject	No	Message subject or title.
Text	Yes	Message text. The messages total size depends on type of message, like SMS are limited to 160 characters.
Type	Yes	Type of message: <i>EMAIL</i> E-post <i>SMS</i> SMS text message <i>E-SERVICE</i> My pages
Encoding	No	Mime encoding plain/text Unformatted plan text application/html Formatted text
Attachments	No	One or more base64 encoded files.

### 2.2 FaultContract

Error SOAP fault structure.

Parameter	Mandatory	Description
ErrorId	No	Identifies error
ErrorMessage	No	Error description
CorrelationId	No	Identity to persistent technical description in log system

## 3 Services

### 3.1.1 SendMessage

Services contract for incoming and outgoing messages between message providers and the business system

#### Service input parameters

Parameter	Mandatory	Description
domain	False	Customer domain name, used for multitenant service providers.
source	False	System or function identity.
message	Yes	The received or sent message.

#### Service output

Successful operation returns a unique transaction identity. On fault the service returns an error structure containing error codes and description, see FaultContract.

## 4 WSDL

### XML Schema for messaging services

```
<?xml version="1.0" encoding="utf-8"?>
<wsdl:definitions xmlns:wsap="http://schemas.xmlsoap.org/ws/2004/08/addressing/policy"
  xmlns:wsa10="http://www.w3.org/2005/08/addressing"
  xmlns:tns="http://open.tieto.com/V1/Message/"
  xmlns:msc="http://schemas.microsoft.com/ws/2005/12/wsdl/contract"
  xmlns:soapenc="http://schemas.xmlsoap.org/soap/encoding/"
  xmlns:wsx="http://schemas.xmlsoap.org/ws/2004/09/mex"
  xmlns:wsp="http://schemas.xmlsoap.org/ws/2004/09/policy"
  xmlns:i0="http://open.tieto.com/V1/Message"
  xmlns:wsam="http://www.w3.org/2007/05/addressing/metadata"
  xmlns:wsa="http://schemas.xmlsoap.org/ws/2004/08/addressing"
  xmlns:soap12="http://schemas.xmlsoap.org/wsdl/soap12/"
  xmlns:wsaw="http://www.w3.org/2006/05/addressing/wsdl"
  xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/"
  xmlns:wsu="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-
utility-1.0.xsd"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  name="Message"
  targetNamespace="http://open.tieto.com/V1/Message/"
  xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:types>
    <xs:schema elementFormDefault="qualified" targetNamespace="http://open.tieto.com/V1/Message/"
      xmlns:xs="http://www.w3.org/2001/XMLSchema">
      <xs:import
        namespace="http://schemas.datacontract.org/2004/07/HCW.Welfare.Common.MessageGateway.Contracts.V1.D
        ataContracts" />
      <xs:element name="SendMessage">
        <xs:complexType>
          <xs:sequence>
            <xs:element minOccurs="0" name="domain" nillable="true" type="xs:string" />
            <xs:element minOccurs="0" name="source" nillable="true" type="xs:string" />
          </xs:sequence>
        </xs:complexType>
      </xs:element>
      <xs:element name="SendMessageResponse">
        <xs:complexType>
          <xs:sequence>
            <xs:element minOccurs="0" name="SendMessageResult" nillable="true" type="xs:string" />
          </xs:sequence>
        </xs:complexType>
      </xs:element>
    </xs:schema>
    <xs:schema xmlns:tns="http://schemas.microsoft.com/2003/10/Serialization/"
      attributeFormDefault="qualified" elementFormDefault="qualified"
      targetNamespace="http://schemas.microsoft.com/2003/10/Serialization/"
      xmlns:xs="http://www.w3.org/2001/XMLSchema">
      <xs:element name="anyType" nillable="true" type="xs:anyType" />
      <xs:element name="anyURI" nillable="true" type="xs:anyURI" />
      <xs:element name="base64Binary" nillable="true" type="xs:base64Binary" />
      <xs:element name="boolean" nillable="true" type="xs:boolean" />
      <xs:element name="byte" nillable="true" type="xs:byte" />
      <xs:element name="dateTime" nillable="true" type="xs:dateTime" />
      <xs:element name="decimal" nillable="true" type="xs:decimal" />
      <xs:element name="double" nillable="true" type="xs:double" />
      <xs:element name="float" nillable="true" type="xs:float" />
      <xs:element name="int" nillable="true" type="xs:int" />
      <xs:element name="long" nillable="true" type="xs:long" />
      <xs:element name="QName" nillable="true" type="xs:QName" />
      <xs:element name="short" nillable="true" type="xs:short" />
      <xs:element name="string" nillable="true" type="xs:string" />
      <xs:element name="unsignedByte" nillable="true" type="xs:unsignedByte" />
      <xs:element name="unsignedInt" nillable="true" type="xs:unsignedInt" />
    </xs:schema>
  </wsdl:types>
  <wsdl:message name="SendMessage" type="tns:SendMessage" />
  <wsdl:message name="SendMessageResponse" type="tns:SendMessageResponse" />
  <wsdl:portType name="IMessageGateway" >
    <wsdl:operation name="SendMessage" message="tns:SendMessage" />
    <wsdl:operation name="SendMessageResponse" message="tns:SendMessageResponse" />
  </wsdl:portType>
  <wsdl:binding name="Soap11" type="tns:IMessageGateway" >
    <wsdl:soap:binding style="document" />
    <wsdl:operation name="SendMessage" message="tns:SendMessage" />
    <wsdl:operation name="SendMessageResponse" message="tns:SendMessageResponse" />
  </wsdl:binding>
  <wsdl:binding name="Soap12" type="tns:IMessageGateway" >
    <wsdl:soap:binding style="document" />
    <wsdl:operation name="SendMessage" message="tns:SendMessage" />
    <wsdl:operation name="SendMessageResponse" message="tns:SendMessageResponse" />
  </wsdl:binding>
  <wsdl:service name="MessageGateway" >
    <wsdl:port name="Soap11" binding="tns:Soap11" />
    <wsdl:port name="Soap12" binding="tns:Soap12" />
  </wsdl:service>
</wsdl:definitions>
```



```
<xs:element name="unsignedLong" nillable="true" type="xs:unsignedLong" />
<xs:element name="unsignedShort" nillable="true" type="xs:unsignedShort" />
<xs:element name="char" nillable="true" type="tns:char" />
<xs:simpleType name="char">
  <xs:restriction base="xs:int" />
</xs:simpleType>
<xs:element name="duration" nillable="true" type="tns:duration" />
<xs:simpleType name="duration">
  <xs:restriction base="xs:duration">
    <xs:pattern value="\-?P(\d*D)?(T(\d*H)?(\d*M)?(\d*(\.\d*)?S)?)?" />
    <xs:minInclusive value="-P10675199DT2H48M5.4775808S" />
    <xs:maxInclusive value="P10675199DT2H48M5.4775807S" />
  </xs:restriction>
</xs:simpleType>
<xs:element name="guid" nillable="true" type="tns:guid" />
<xs:simpleType name="guid">
  <xs:restriction base="xs:string">
    <xs:pattern value="[\da-fA-F]{8}-[\da-fA-F]{4}-[\da-fA-F]{4}-[\da-fA-F]{4}-[\da-fA-F]{12}" />
  </xs:restriction>
</xs:simpleType>
<xs:attribute name="FactoryType" type="xs:QName" />
<xs:attribute name="Id" type="xs:ID" />
<xs:attribute name="Ref" type="xs:IDREF" />
</xs:schema>
<xs:schema
  xmlns:tns="http://schemas.datacontract.org/2004/07/HCW.Welfare.Common.MessageGateway.Contracts.V1.D
ataContracts" elementFormDefault="qualified"
  targetNamespace="http://schemas.datacontract.org/2004/07/HCW.Welfare.Common.MessageGateway.Contract
s.V1.DataContracts" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:import namespace="http://schemas.microsoft.com/2003/10/Serialization/Arrays" />
  <xs:complexType name="Message">
    <xs:sequence>
      <xs:element xmlns:q1="http://schemas.microsoft.com/2003/10/Serialization/Arrays"
minOccurs="0" name="Attachments" nillable="true" type="q1:ArrayOfArrayOfstring" />
      <xs:element minOccurs="0" name="Encoding" nillable="true" type="xs:string" />
      <xs:element xmlns:q2="http://schemas.microsoft.com/2003/10/Serialization/Arrays"
minOccurs="0" name="Recipients" nillable="true" type="q2:ArrayOfstring" />
      <xs:element minOccurs="0" name="Sender" nillable="true" type="xs:string" />
      <xs:element minOccurs="0" name="Subject" nillable="true" type="xs:string" />
      <xs:element minOccurs="0" name="Text" nillable="true" type="xs:string" />
      <xs:element minOccurs="0" name="Type" nillable="true" type="xs:string" />
    </xs:sequence>
  </xs:complexType>
  <xs:element name="Message" nillable="true" type="tns:Message" />
</xs:schema>
<xs:schema xmlns:tns="http://schemas.microsoft.com/2003/10/Serialization/Arrays"
  elementFormDefault="qualified"
  targetNamespace="http://schemas.microsoft.com/2003/10/Serialization/Arrays"
  xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexType name="ArrayOfArrayOfstring">
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="unbounded" name="ArrayOfstring" nillable="true"
type="tns:ArrayOfstring" />
    </xs:sequence>
  </xs:complexType>
  <xs:element name="ArrayOfArrayOfstring" nillable="true" type="tns:ArrayOfArrayOfstring" />
  <xs:complexType name="ArrayOfstring">
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="unbounded" name="string" nillable="true"
type="xs:string" />
    </xs:sequence>
  </xs:complexType>
  <xs:element name="ArrayOfstring" nillable="true" type="tns:ArrayOfstring" />
</xs:schema>
<xs:schema
  xmlns:tns="http://schemas.datacontract.org/2004/07/HCW.Welfare.Common.MessageGateway.Contracts.V1.F
aultContracts"
  elementFormDefault="qualified"

  targetNamespace="http://schemas.datacontract.org/2004/07/HCW.Welfare.Common.MessageGateway.Contract
s.V1.FaultContracts">
```

```
        xmlns:xs="http://www.w3.org/2001/XMLSchema">
        <xs:import namespace="urn:HCW.Welfare.Common.ServiceModel.V2" />
        <xs:complexType name="MessageServiceFault">
            <xs:complexContent mixed="false">
                <xs:extension xmlns:q1="urn:HCW.Welfare.Common.ServiceModel.V2" base="q1:FaultContract">
                    <xs:sequence />
                </xs:extension>
            </xs:complexContent>
        </xs:complexType>
        <xs:element name="MessageServiceFault" nillable="true" type="tns:MessageServiceFault" />
    </xs:schema>
    <xs:schema xmlns:tns="urn:HCW.Welfare.Common.ServiceModel.V2" elementFormDefault="qualified"
targetNamespace="urn:HCW.Welfare.Common.ServiceModel.V2"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
        <xs:complexType name="FaultContract">
            <xs:sequence>
                <xs:element name="ErrorId" type="xs:int" />
                <xs:element name="ErrorMessage" nillable="true" type="xs:string" />
                <xs:element name="CorrelationId" nillable="true" type="xs:string" />
            </xs:sequence>
        </xs:complexType>
        <xs:element name="FaultContract" nillable="true" type="tns:FaultContract" />
    </xs:schema>
</wsdl:types>
<wsdl:message name="IMessageGateway_SendMessage_InputMessage">
    <wsdl:part name="parameters" element="tns:SendMessage" />
</wsdl:message>
<wsdl:message name="IMessageGateway_SendMessage_OutputMessage">
    <wsdl:part name="parameters" element="tns:SendMessageResponse" />
</wsdl:message>
<wsdl:message name="IMessageGateway_SendMessage_MessageServiceFaultFault_FaultMessage">
    <wsdl:part
xmlns:q1="http://schemas.datacontract.org/2004/07/HCW.Welfare.Common.MessageGateway.Contracts.V1.Fa
ultContracts" name="detail" element="q1:MessageServiceFault" />
</wsdl:part>
<wsdl:portType name="IMessageGateway">
    <wsdl:operation name="SendMessage">
        <wsdl:input wsaw:Action="http://open.tieto.com/V1/Message/IMessageGateway/SendMessage"
message="tns:IMessageGateway_SendMessage_InputMessage" />
        <wsdl:output
wsaw:Action="http://open.tieto.com/V1/Message/IMessageGateway/SendMessageResponse"
message="tns:IMessageGateway_SendMessage_OutputMessage" />
        <wsdl:fault
wsaw:Action="http://open.tieto.com/V1/Message/IMessageGateway/SendMessageMessageServiceFaultFault"
name="MessageServiceFaultFault"
message="tns:IMessageGateway_SendMessage_MessageServiceFaultFault_FaultMessage" />
    </wsdl:operation>
</wsdl:portType>
<wsdl:binding name="BasicHttpBinding_IMessageGateway" type="tns:IMessageGateway">
    <soap:binding transport="http://schemas.xmlsoap.org/soap/http" />
    <wsdl:operation name="SendMessage">
        <soap:operation soapAction="http://open.tieto.com/V1/Message/IMessageGateway/SendMessage"
style="document" />
        <wsdl:input>
            <soap:body use="literal" />
        </wsdl:input>
        <wsdl:output>
            <soap:body use="literal" />
        </wsdl:output>
        <wsdl:fault name="MessageServiceFaultFault">
            <soap:fault use="literal" name="MessageServiceFaultFault" namespace="" />
        </wsdl:fault>
    </wsdl:operation>
</wsdl:binding>
<wsdl:service name="Message">
    <wsdl:port name="BasicHttpBinding_IMessageGateway"
binding="tns:BasicHttpBinding_IMessageGateway">
        <soap:address location="http://localhost:51159/LES/Message/V1/Message.svc" />
    </wsdl:port>
</wsdl:service>
</wsdl:definitions>
```