

# Technical Specification

## Organization API



## Table of Contents

<b>1 Introduction</b>	<b>4</b>
1.1 Prerequisites	4
<b>2 Supported school types</b>	<b>5</b>
<b>3 Structure and mapping</b>	<b>6</b>
3.1 Mapping	6
3.2 Examples of structures and mappings	7
3.2.1 Preschool organization example	7
3.2.2 Compulsory school organization example	8
3.2.3 Upper secondary school organization example	8
3.2.4 Municipal organization example	9
<b>4 School organization entities</b>	<b>10</b>
4.1 Properties	10
4.2 IMS Person	10
4.2.1 Person attributes	10
4.2.2 Person extensions	11
4.2.3 Person extension for students	11
4.3 IMS Group	12
4.3.1 Group extensions	12
4.3.2 Group extensions for class	13
4.3.3 Group extensions for other groups	13
4.3.4 Group extension for units	13
4.3.5 Group extension for departments	14
4.3.6 Group extension for department groups	14
4.4 IMS Membership	14
4.4.1 Membership extensions	15
4.4.2 Membership extensions for responsibilities	15
4.4.3 Membership extensions for placement	16
4.4.4 Membership extensions for activity	16
<b>5 Municipal organization entities</b>	<b>16</b>
5.1 Properties	16
5.2 IMS Group	17
5.3 IMS Membership	17
<b>6 Services</b>	<b>18</b>
6.1 Complete export of organization	18
6.2 Delta export of organization	19
6.2.1 Use cases	21
6.3 Get units	23
6.4 Update organization	24
6.5 Export of municipal organization	25
<b>7 Appendix</b>	<b>27</b>
7.1 References	27

7.2 Vocabulary .....27



## 1 Introduction

The Organization API provides services that make it possible to get the organization for a specified school type. The services in the Organization API are accessed via URIs. Each of the 12 supported school types has a unique URI. The organization information that you can get and set via the API follows the standard IMS Enterprise 1.1.

This document describes following:

- Which organization information that can be fetched. (This is described by specifying which attributes that is used for the different IMS entities.)
- How Tieto Education entities are mapped to IMS entities
- How the IMS entities, in the organization, are structured

Note:

IMS Enterprise 1.1 provides a number of attributes. These attributes are not sufficient for Organization API and therefore new attributes has been added as IMS extensions. Some IMS Enterprise 1.1 enumerations have also been extended to support Nordic school requirements, laws and regulations. These extensions are in line with the IMS standard.

### 1.1 Prerequisites

Before you can get access to the Organization API you must request a license key from Tieto. You should have basic knowledge about the IMS Enterprise standard and W3C XML before you starts using the API.

## 2 Supported school types

The table below describes the supported school types.

School types	Description	Code
Pedagogical care	Childcare groups for children between 1-12 years	PC
Preschool	Childcare for children between 1-6 years	FS
Leisure time centre	Childcare for school-aged children over 6 years	F
Preschool class	Preschool class for children 6 years of age	FK
Compulsory School	Primary school for younger students	GR
Compulsory School For Learning Disabilities	Compulsory school for learning disabilities	S
Upper Secondary School	Secondary school, 3-4 years education	GY
Upper Secondary School For Learning Disabilities	Secondary school for learning disabilities	GS
Swedish For Immigrants School	School for Swedish immigrants	SF
Adult School For Learning Disabilities	Adult school for learning disabilities	SV
Municipal Adult School	Municipality school for adults	KV
Higher Vocational Education	School for Higher Vocational Education	YH

### 3 Structure and mapping

All entities in the organization for specified school type are mapped into the IMS entities person, group and membership.

The memberships describe relations between persons and groups and groups and other groups.

#### 3.1 Mapping


This table describes how childcare and school entities in Tieto Education are mapped to IMS entities.

Type	IMS Type	Description
Class	Group	School class in education.
Unit	Group	Preschool and school units
EducationGroup	Group	Education group
ScheduleGroup	Group	Schedule group
OtherGroup	Group	Other group without any connection to education courses or subjects.
ContactGroup	Group	Contact group for each child and student containing contacts, guardians and mentors
MentorGroup	Group	Group with a mentor and the students the mentor is responsible for
Department	Group	Preschool unit.
DepartmentGroup	Group	Preschool group
Contact	Person	Contact persons for student and child, including guardians for children below 18 year.
Student	Person	School students from preschool class to adult education.
Child	Person	Child 1-12 year in preschool, leisure time centre and pedagogical care.
Staff	Person	School administrative personnel, pedagogical personnel and principals.

## 3.2 Examples of structures and mappings


### 3.2.1 Preschool organization example

The diagram below shows an example of how a preschool organization is structured. It also shows mapping between Tieto Education entities and IMS entities.




### 3.2.2 Compulsory school organization example

The diagram below shows an example of how a compulsory school organization is structured. It also shows mapping between Tieto Education entities and IMS entities.



### 3.2.3 Upper secondary school organization example


The diagram below shows an example of how an upper secondary school organization is structured. It also shows mapping between Tieto Education entities and IMS entities.





### 3.2.4 Municipal organization example

The diagram below shows an example of how municipal organization is structured. It also shows mapping between Tieto Education entities and IMS entities.



## 4 School organization entities

### 4.1 Properties

The delivery information of the IMS Enterprise packaging that is used to manage the exchange of data between source and target system.

Name	Description
datasource	This is the source identifier of data source, for export the source contains customer domain and school type.
comments	Input values for the service.
type	Enumerated as CompleteOrganization, DeltaOrganization
datetime	The date and time the XML information were generated. The format is as [YYYY-MM-DDTHH:MM:SS]
schooltype	Exported schooltype
timeframe	Timeframe for the organization data

### 4.2 IMS Person

The person object contains information about child, students, professionals and contact persons in Tieto Education Student management system. All persons are identified with a personal identity and Globally Unique Identifier (GUID). The personal identity could be temporary or generated from Skatteverket, for more information see [www.skatteverket](http://www.skatteverket)

#### 4.2.1 Person attributes

Name	Description	Read-only
sourcedid.id	The persistent unique identity of the person	Yes
userid.value	Alternative unique identifiers of the person	Yes
userid.useridtype	Enumerated as PID, GUID	Yes
name.fn	Formatted name ([middle name] [lastname], [firstname])	Yes
name.n.given	The given name and not necessarily the first name	No
name.n.partname.partnametype	The type of partname. "Middle" is used for middle name.	No
name.n.partname.Value	Middle name	No
name.n.family	This is the family name and not necessarily the last name	No
email	Email home address	No
tel	Phone numbers	No
tel.teltype	Identifies the type of telephone number. Enumerated as Voice, Mobile and Work where Voice is home phone.	No
adr.pcode	The post identity number	No

adr.street	The actual street address	No
adr.locality	The locality component of the address e.g., the City	No
adr.extadd	C/O address	No
demographics.bday	The birth date of the Person. The format is [YYYY-MM-DD]	Yes
demographics.gender	The gender of the Person. This is enumerated as Unknown, Female and Male	Yes
institutionrole.institutionroletype	The role of the Person within the institution. This is enumerated as Student, Staff, Contact, Child	Yes
institutionrole.primaryrole	Identifies if the associated role is the primary one for the Person in the institution. Enumerated as Yes, No	Yes
systemrole.systemroletype	The role of the person within the software environment. The value is always None	Yes
datasource	Source for address information. SKV "Skatteverket"	Yes
recstatus	Indicator whether the person is added(1), updated(2) or deleted(3). This attribute is only valid in delta services.	Yes

## 4.2.2 Person extensions

Common extended properties for all persons

Name	Description	Read-only
privacy	The person has restrictions. This is enumerated as None, Level1. Level1 means privacy highlighted by the "Skatteverket".	Yes
geographickeycode	Geographic key code	No
municipalitycode	Municipality code, formatted [NNNN], for more information see <a href="http://www.skl.se">www.skl.se</a>	No
municipalityname	Municipality name	Yes
timestamp	Date and time when person is created updated or deleted.	Yes
status	Status Normal The person is alive and lives in Sweden Deceased The person has deceased Emigrated The person has emigrated	Yes

## 4.2.3 Person extension for students

Extended properties for students

Name	Description	Read-only
------	-------------	-----------

Name	Description	Read-only
nativelanguage	Native language, formatted as longer a form of language name	Yes
altadr.pcode	The post identity number for alternative address	Yes
altadr.street	The actual street address for alternative address	Yes
altadr.locality	The locality component of the address, e.g., the City, for alternative address	Yes
altadr.extadd	C/O address for alternative address	Yes

### 4.3 IMS Group

Group is used for school units, classes, programs, courses, subjects, education groups and other groups. Depending on school type, some groups exist only for a particular school type.

This implementation does not attribute relationship for group relations to other groups. All group and person relations are described by memberships.

Groups can have extensions depending on group type.

Name	Description	Read-only
sourcedid.id	The persistent unique identity of the group	Yes
description.short	Group code or name.	Yes
group.type.typevalue	The container for the type classification being assigned to the group. This is enumerated as Unit, Class, Subject, Course, OtherGroup, EducationGroup, ScheduleGroup, ContactGroup, MentorGroup, Department and DepartmentGroup	Yes
group.type.typevalue.level	The parameter is always set to "1"	Yes
timeframe.begin	Defines when a group is intended to be available. Formatted as [YYYY-MM-DD]. The parameter is used for Unit, Department, DepartmentGroup, Class, EducationGroup, ScheduleGroup. The parameter is not used for Subject, Course, ContactGroup and MentorGroup. The begin date is included in the timeframe.	Yes
timeframe.end	Defines when group is intended to end. Formatted as [YYYY-MM-DD]. The end date is included in the timeframe.	Yes
recstatus	Indicator whether the group is added(1), updated(2) or deleted(3). This attribute is only valid in delta services.	Yes

#### 4.3.1 Group extensions

Common extended properties for all groups

Name	Description	Read-only
------	-------------	-----------

Name	Description	Read-only
timestamp	Date and time when group is created updated or deleted.	Yes

#### 4.3.2 Group extensions for class

Extended properties for school classes

Name	Description	Read-only
schoolyear	School year. In case of a mixed class (with more than one school year) the value of this attribute is a range in the format "<startyear>-<endyear>".	Yes

#### 4.3.3 Group extensions for other groups

Extended properties for non-education groups

Name	Description	Read-only
groupusage	The group usage, e.g. group for bus tickets	Yes

#### 4.3.4 Group extension for units

Extended properties for units from preschool to higher vocational education

Name	Description	Read-only
schooltype	School types at the unit, for more information see defined school types in this documentation.	Yes
csncode	CSN code for schools in Sweden, for more information see <a href="http://www.csn.se">www.csn.se</a>	Yes
governedby	Owns and manages the business for this group. This is enumerated as Private, Municipal and State	Yes
phone	Phone number to school office	No
pcode	The post identity number	No
street	The actual street address	No
locality	The locality component of the address e.g., the City	No
web	The school web address	No
municipalitycode	Municipality code, formatted [NNNN], for more information see <a href="http://www.skl.se">www.skl.se</a>	Yes
municipalityname	Municipality name	Yes
period	Periods defined on the unit	Yes

Name	Description	Read-only
period.type	Type of period.	Yes
period.start	Start date for period	Yes
period.end	End date for period	Yes
geographickeycode	Geographic key code. This is only used for preschool, leisure time centre, preschool class, compulsory school and compulsory school for learning disabilities.	Yes
id	Unit id	Yes
email	E-mail address to the unit administrator office	Yes
officialunitname	Official name for the unit	Yes

#### 4.3.5 Group extension for departments

There are no other extensions for departments than what is mentioned in chapter 4.3.1

#### 4.3.6 Group extension for department groups

There are no other extensions for department groups than what is mentioned in chapter 4.3.1.

### 4.4 IMS Membership

The membership structure is used to define the members of a group or personal relations. A member can be a person or another group.

Members can have extensions depending on type of relation.

Name	Description	Read-only
complete	This is a Boolean flag	Yes
sourcedid.id	This is the persistent unique identifier assigned to the group structure for which the memberships are being defined.	Yes
member.sourcedid.id	This is the unique identifier assigned to the group structure which is the member of the host group	Yes
member.idtype	Indicates if the Member is a person or another group. Enumerated as Person or Group.	Yes
member.role.status	Indicates if a member is active or inactive in the group. The value is always set to "Active".	Yes

Name	Description	Read-only
member.role.roletype	The member's function within a group. The content is enumerated as: Instructor, Mentor, Administrator, Guardian, Contact, OtherResponsible, Child, Student, Principal, GradeAuthority, Unit, Class, OtherGroup, EducationGroup, ScheduleGroup, ContactGroup, MentorGroup, Department, DepartmentGroup and Responsible	Yes
member.role.timeframe.begin	Defines when a group is intended to be available for a person or a group. Formatted as [YYYY-MM-DD]. The time frame is within the timeframe for the group that owns the membership.	Yes
member.role.timeframe.end	Defines when group participation for a person or a group is intended to end. Formatted as [YYYY-MM-DD]. The time frame is within the timeframe for the group that owns the membership.	Yes
member.role.recstatus	Indicator whether the role is added(1), updated(2) or deleted(3). This attribute is only valid in delta services.	Yes

#### 4.4.1 Membership extensions

Common extended properties for all members in memberships.

Name	Description	Read-only
timestamp	Date and time when member in membership is created updated or deleted.	Yes

#### 4.4.2 Membership extensions for responsibilities

Extended properties for relationships between units and principals.

Name	Description	Read-only
responsibility	Contains information for all school units the principal is responsible for	Yes
responsibility.schoolunitcode	School unit code	Yes
responsibility.begin	Start date for responsibility	Yes
responsibility.end	End date for responsibility	Yes
responsibility.timestamp	Date and time responsibility is created updated or deleted.	Yes

#### 4.4.3 Membership extensions for placement

Extended properties for relationships between classes and students.

Name	Description	Read-only
placement	Contains information about a students placements in a class	Yes
placement.schoolyear	School year	Yes
placement.schoolunitcode	School unit code	Yes
placement.programcode	Program code	Yes
placement.programprofile	Profile	Yes
placement.programvariant	Variant	Yes
placement.begin	Start date for responsibility	Yes
placement.end	End date for responsibility	Yes
placement.timestamp	Date and time responsibility is created updated or deleted.	Yes

#### 4.4.4 Membership extensions for activity

Extended properties for relationships between classes/education groups and students/teachers.

Name	Description	Read-only
activity	Contains information about a student/teacher activities in a class or education group	Yes
activity.coursecode	Course code	Yes
activity.subjectcode	Subject code	Yes
activity.hours	Amount of hours for the activity	Yes
activity.cancelled	Indicates if the activity is cancelled	Yes
activity.begin	Start date for activity	Yes
activity.end	End date for activity	Yes
activity.timestamp	Date and time responsibility is created updated or deleted.	Yes

## 5 Municipal organization entities

### 5.1 Properties

The delivery information of the IMS Enterprise packaging that is used to manage the exchange of data between source and target system.



Name	Description
datasource	This is the source identifier of data source, for export the source contains customer domain and school type.
comments	Input values for the service.
type	Enumerated as MunicipalOrganization
datetime	The date and time the XML information were generated. The format is as [YYYY-MM-DDTHH:MM:SS]
schooltype	Exported schooltype
timeframe	Timeframe for the organization data

## 5.2 IMS Group

Group is used for the municipal and units (schools) within the municipal. If the municipal has been divided into smaller parts, these part can also be represented by a Group.

Groups can have extensions depending on group type.

Name	Description	Read-only
sourcedid.id	The persistent unique identity of the group	Yes
description.short	Group name.	Yes
grouptype.typevalue	The container for the type classification being assigned to the group. This is enumerated as Area and Unit	Yes
timeframe.begin	Defines when a group is intended to be available. Formatted as [YYYY-MM-DD]. The begin date is included in the timeframe.	Yes
timeframe.end	Defines when group is intended to end. Formatted as [YYYY-MM-DD]. The end date is included in the timeframe.	Yes

## 5.3 IMS Membership

The membership structure is used to define the members of a group. A member can be another group.

Name	Description	Read-only
sourcedid.id	This is the persistent unique identifier assigned to the group structure for which the memberships are being defined.	Yes
member.sourcedid.id	This is the unique identifier assigned to the group structure which is the member of the host group	Yes

Name	Description	Read-only
member.idtype	The value is always set to Group.	Yes
member.role.status	Indicates if a member is active or inactive in the group. The value is always set to Active.	Yes
member.role.roletype	The member's function within a group. The value is Area or Unit	Yes
member.role.timeframe.begin	Defines when a group is intended to be available for a person or a group. Formatted as [YYYY-MM-DD]. The time frame is within the timeframe for the group that owns the membership.	Yes
member.role.timeframe.end	Defines when group participation for a person or a group is intended to end. Formatted as [YYYY-MM-DD]. The time frame is within the timeframe for the group that owns the membership.	Yes

## 6 Services

All services are based on HTTP REST technology and organized in school types to match each school structure. "Update services" are using the method HTTP POST and "Get services" are using the method HTTP GET.

### 6.1 Complete export of organization

These services return the complete organization at a specific time. All services are using current time as default value for search date identified. By using search date you can get the organization from past or future.

Base path for services are:

[https://\[host\]/WE.Education.Integration.Host/LES/Organization/V3/Organization.svc](https://[host]/WE.Education.Integration.Host/LES/Organization/V3/Organization.svc)

Parameters – Alternative 1:

Parameter	Mandatory	Description
SearchDate	No	The search date. Current date will be used if SearchDate is not specified. The oldest search date that can be used is current date minus ten years.

Parameters – Alternative 2:

Parameter	Mandatory	Description
UnitId	No	Id for the school unit. Organization for all school units will be returned if UnitId is not specified.
SearchDate	No	The search date. Current date will be used if SearchDate is not

Parameter	Mandatory	Description
		specified. The oldest search date that can be used is current date minus ten years.

Parameters – Alternative 3:

Parameter	Mandatory	Description
PersonId	Yes	The id can be GUID or PID for the student.
SearchDate	No	The search date. Current date will be used if SearchDate is not specified. The oldest search date that can be used is current date minus ten years.

Services:

Service	Description
GetPedagogicalCareOrganization	Organization for pedagogical care.
GetPreSchoolOrganization	Organization for preschool.
GetLeisureTimeCentreOrganization	Organization for leisure time centre.
GetPreSchoolClassOrganization	Organization for preschool class
GetCompulsorySchoolOrganization	Organization for compulsory schools.
GetCompulsorySchoolForLearningDisabilitiesOrganization	Organization for compulsory school with learning disabilities.
GetUpperSecondarySchoolOrganization	Organization for upper secondary school.
GetUpperSecondarySchoolForLearningDisabilitiesOrganization	Organization for upper secondary school with learning disabilities.
GetSwedishForImmigrantsSchoolOrganization	Organization for Swedish for immigrants.
GetMunicipalAdultSchoolOrganization	Organization for municipal adult school.
GetAdultSchoolForLearningDisabilitiesOrganization	Organization for adult school with learning disabilities.
GetHigherVocationalEducationOrganization	Organization for higher vocational education.

## 6.2 Delta export of organization

These services give the organizational changes done within a specified timeframe. The output is XML information with changed organization entities. For each changed entity the attribute “recstatus” is used to indicate the type of change. The attribute “recstatus” is enumerated as 1=Add, 2=Update and 3=Delete. When deleting a group or person only the deleted entity is indicated as deleted, no cascading deletes for

memberships are reported. All changed entities have a timestamp stored in the extension attribute "timestamp" for all entities to secure information quality.

When person is updated the institution role type may be empty.

By examining the attribute "complete" (which is false by default) on the memberships, the client can determine whether the members are the complete set of members within the membership (complete = true), or just the differences due to events occurring during the specified timeframe (complete = false),

Base path for services are:

https://[host]/WE.Education.Integration.Host/LES/Organization/V3/Organization.svc

Parameters:

Parameter	Mandatory	Description
StartDate	Yes	Start date&time
EndDate	Yes	End date&time

Parameter value limitations:

- EndDate – StartDate >= 5 minutes
- EndDate – StartDate <= 24 hours
- Current time – EndDate >= 5 minutes
- Current time – StartDate <= 30 days

Services:

Service	Description
GetUpperSecondarySchoolOrganizationDelta	Organization delta for upper secondary school.
GetUpperSecondarySchoolForLearningDisabilitiesOrganizationDelta	Organization delta for upper secondary school with learning disabilities.
GetSwedishForImmigrantsSchoolOrganizationDelta	Organization delta for Swedish for immigrants school.
GetMunicipalAdultSchoolOrganizationDelta	Organization delta for municipal adult school.
GetAdultSchoolForLearningDisabilitiesOrganizationDelta	Organization delta for adult school with learning disabilities.
GetHigherVocationalEducationOrganizationDelta	Organization delta for higher vocational education.
GetCompulsorySchoolOrganizationDelta	Organization delta for compulsory schools.

Service	Description
GetCompulsorySchoolForLearningDisabilitiesOrganizationDelta	Organization delta for compulsory school with learning disabilities.
GetPreSchoolClassOrganizationDelta	Organization delta for preschool class
GetLeisureTimeCentreOrganizationDelta	Organization delta for leisure time centre

### 6.2.1 Use cases

Some use cases for delta export:

Organization change	Indicated with
New school unit and unit domain	- IMS group for the school unit (recstatus = 1)
Updated school unit or unit domain	- IMS group with new unit information (recstatus = 2)
New class	- IMS group for the class (recstatus = 1) - IMS membership for unit with the class as member
Update class	- IMS group for the class (recstatus = 2) - IMS membership for the class with the teachers, students as members
Delete class	- IMS group for the class (recstatus = 3)
New education group	- IMS group for the education group (recstatus = 1) - IMS membership for unit with the education group as member
Update education group	- IMS group for the education group (recstatus = 2) - IMS membership for the group with the teachers, students as members
Delete education group	- IMS group for the education group (recstatus = 3)
New other group	- IMS group for the other group (recstatus = 1) - IMS membership for unit with the other group as member
Update other group	- IMS group for the other group (recstatus = 2) - IMS membership for the other group with the teachers, students as members
Delete other group	- IMS group for the other group (recstatus = 3)
New contact for student	- IMS membership for the student's contact group (complete = true) - IMS persons for all contact persons - IMS group for contact group - IMS membership for unit with contact group as member
Update information on contact person	- IMS person for student with updated contact person - IMS persons for all contact persons - IMS group for contact group - IMS membership for unit with contact group as member - IMS membership for the contact group (complete = true)

Remove contact for student	<ul style="list-style-type: none"> <li>- Complete IMS membership for the students contact group (complete = true)</li> <li>- IMS persons for all contact persons</li> <li>- IMS group for contact group</li> <li>- IMS membership for unit with contact group as member</li> </ul>
New student in class	<ul style="list-style-type: none"> <li>- IMS person for student</li> <li>- IMS membership for the class with the student as member</li> <li>- IMS persons for all contact persons</li> <li>- IMS group for contact group</li> <li>- IMS membership for unit with contact group as member</li> <li>- IMS membership for the contact group (complete = true)</li> </ul>
Updated student in class	<ul style="list-style-type: none"> <li>- IMS person for student</li> <li>- IMS membership for the class with the student as member</li> <li>- IMS persons for all contact persons</li> <li>- IMS group for contact group</li> <li>- IMS membership for unit with contact group as member</li> <li>- IMS membership for the contact group (complete = true)</li> </ul>
Remove student from class	<ul style="list-style-type: none"> <li>- IMS person for student</li> <li>- IMS membership for the class with the student as member (recstatus = 3)</li> <li>- IMS persons for all contact persons</li> <li>- IMS group for contact group</li> <li>- IMS membership for unit with contact group as member</li> <li>- IMS membership for the contact group (complete = true)</li> </ul>
New student in education group	<ul style="list-style-type: none"> <li>- IMS person for student</li> <li>- IMS membership for the education group with the student as member</li> <li>- IMS persons for all contact persons</li> <li>- IMS group for contact group</li> <li>- IMS membership for unit with contact group as member</li> <li>- IMS membership for the contact group (complete = true)</li> </ul>
Updated student in education group	<ul style="list-style-type: none"> <li>- IMS person for student</li> <li>- IMS membership for the education group with the student as member (recstatus = 2)</li> <li>- IMS persons for all contact persons</li> <li>- IMS group for contact group</li> <li>- IMS membership for unit with contact group as member</li> <li>- IMS membership for the contact group (complete = true)</li> </ul>
Remove student in education group	<ul style="list-style-type: none"> <li>- IMS membership for the education group with the student as member (recstatus = 3)</li> </ul>
New teacher in class	<ul style="list-style-type: none"> <li>- IMS person for teacher</li> <li>- IMS membership for the class with the teacher as member</li> </ul>
Updated teacher in class	<ul style="list-style-type: none"> <li>- IMS person for teacher</li> <li>- IMS membership for the class with the teacher as member</li> </ul>
Remove teacher from class	<ul style="list-style-type: none"> <li>- IMS membership for the class with the teacher as member (recstatus = 3)</li> </ul>

New class responsible	<ul style="list-style-type: none"> <li>- IMS person for responsible</li> <li>- IMS membership for the class with the responsible as member (recstatus = 1)</li> </ul>
Update class responsible	<ul style="list-style-type: none"> <li>- IMS person for responsible</li> <li>- IMS membership for the class with the responsible as member (recstatus = 2)</li> </ul>
Remove class responsible	<ul style="list-style-type: none"> <li>- IMS membership for the class with the responsible as member (recstatus = 3)</li> </ul>
New teacher in educations group	<ul style="list-style-type: none"> <li>- IMS person for teacher</li> <li>- IMS membership for the education group with the teacher as member</li> </ul>
Update teacher in education group	<ul style="list-style-type: none"> <li>- IMS person for teacher</li> <li>- IMS membership for the education group with the teacher as member</li> </ul>
Remove teacher from education group	<ul style="list-style-type: none"> <li>- IMS membership for the education group with the teacher as member (recstatus = 3)</li> </ul>
Change principal for unit	<ul style="list-style-type: none"> <li>- IMS person for the new principal</li> <li>- IMS membership for the unit with one member for the resigning principle (recstatus = 3) and another for the new principal</li> </ul>

### 6.3 Get units

These services return the units for a specific school type.

Base path for services are:

[https://\[host\]/WE.Education.Integration.Host/LES/Organization/V3/Organization.svc](https://[host]/WE.Education.Integration.Host/LES/Organization/V3/Organization.svc)

Parameters:

Parameter	Mandatory	Description
SearchDate	No	The search date. Current date will be used if SearchDate is not specified. The oldest search date that can be used is current date minus ten years.

Services:

Service	Description
GetPedagogicalCareUnits	Units for pedagogical care.
GetPreSchoolUnits	Units for preschool.
GetLeisureTimeCentreUnits	Units for leisure time centre.
GetPreSchoolClassUnits	Organization for preschool class
GetCompulsorySchoolUnits	Organization for compulsory schools.
GetCompulsorySchoolForLearningDisabilitiesUnits	Organization for compulsory school with learning

Service	Description
	disabilities.
GetUpperSecondarySchoolUnits	Organization for upper secondary school.
GetUpperSecondarySchoolForLearningDisabilitiesUnits	Organization for upper secondary school with learning disabilities.
GetSwedishForImmigrantsSchoolUnits	Organization for Swedish for immigrants.
GetMunicipalAdultSchoolUnits	Organization for municipal adult school.
GetAdultSchoolForLearningDisabilitiesUnits	Organization for adult school with learning disabilities.
GetHigherVocationalEducationUnits	Organization for higher vocational education.

## 6.4 Update organization

The services add or update the organization at a school. Using the services you can

- add education group
- add and delete schedule group
- update schedule group

The services take no parameters.

At delta update of organization the attribute properties the attribute type shall be set to "DeltaOrganization".

As input these services take XML information according to the XML schema for the Organization API. See the table below.

Organization change	The XML information that is input to the service
New education group	<ul style="list-style-type: none"> <li>- IMS group for the education group (recstatus = 1)</li> <li>- IMS membership for the unit with the education group as member (recstatus = 1)</li> </ul>
Update education group	<ul style="list-style-type: none"> <li>- IMS group for the education group (recstatus = 2)</li> </ul>
New schedule group	<ul style="list-style-type: none"> <li>- IMS group for the schedule group (recstatus = 1)</li> <li>- IMS membership for the "parent group" (education group, class or unit) with the schedule group as member (recstatus = 1)</li> </ul>
Delete schedule group	<ul style="list-style-type: none"> <li>- IMS group for the schedule group (recstatus = 3)</li> <li>- IMS membership for the "parent group" (education group, class or unit) with the schedule group as member (recstatus = 3)</li> </ul>
Update schedule group	<ul style="list-style-type: none"> <li>- IMS group for the schedule group (recstatus = 2)</li> </ul>



Base path for services are:

[https://\[host\]/WE.Education.Integration.Host/LES/Organization/V3/Organization.svc](https://[host]/WE.Education.Integration.Host/LES/Organization/V3/Organization.svc)

Services:

Service	Description
UpdatePreSchoolClassOrganization	Update organization for preschool class.
UpdateCompulsorySchoolOrganization	Update organization for compulsory school
UpdateCompulsorySchoolForLearningDisabilitiesOrganization	Update organization for compulsory school for learning disabilities.
UpdateUpperSecondarySchoolOrganization	Update organization for secondary school.
UpdateUpperSecondarySchoolForLearningDisabilitiesOrganization	Update organization for upper secondary school for learning disabilities.
UpdateSwedishForImmigrantsSchoolOrganization	Update organization for SFI schools
UpdateMunicipalAdultSchoolOrganization	Update organization for municipal adult education
UpdateAdultSchoolForLearningDisabilitiesOrganization	Update organization for adult school for learning disabilities.
UpdateHigherVocationalEducationOrganization	Update organization for higher vocational education.
UpdateLeisureTimeCentreOrganization	Update organization for leisure time centre

## 6.5 Export of municipal organization

These services return the complete municipal organization at a specific time. All services are using current time as default value for search date identified. By using search date you can get the organization from past or future.

Base path for services are:

[https://\[host\]/WE.Education.Integration.Host/LES/Organization/V3/Organization.svc](https://[host]/WE.Education.Integration.Host/LES/Organization/V3/Organization.svc)

Parameters – Alternative 1:

Parameter	Mandatory	Description
SearchDate	No	The search date. Current date will be used if SearchDate is not specified. The oldest search date that can be used is current date minus ten years.

Services:

Service	Description
GetPedagogicalCareMunicipalOrganization	Municipal organization for pedagogical care.
GetPreSchoolMunicipalOrganization	Municipal organization for preschool.
GetLeisureTimeCentreMunicipalOrganization	Municipal organization for leisure time centre.
GetPreSchoolClassMunicipalOrganization	Municipal organization for preschool class
GetCompulsorySchoolMunicipalOrganization	Municipal organization for compulsory schools.
GetCompulsorySchoolForLearningDisabilitiesMunicipalOrganization	Municipal organization for compulsory school with learning disabilities.
GetUpperSecondarySchoolMunicipalOrganization	Municipal organization for upper secondary school.
GetUpperSecondarySchoolForLearningDisabilitiesMunicipalOrganization	Municipal organization for upper secondary school with learning disabilities.
GetSwedishForImmigrantsSchoolMunicipalOrganization	Municipal organization for Swedish for immigrants.
GetMunicipalAdultSchoolMunicipalOrganization	Municipal organization for municipal adult school.
GetAdultSchoolForLearningDisabilitiesMunicipalOrganization	Municipal organization for adult school with learning disabilities.
GetHigherVocationalEducationMunicipalOrganization	Municipal organization for higher vocational education.

## 7 Appendix

### 7.1 References

Name	Address
IMS Enterprise Information Model	<a href="http://www.imsglobal.org/enterprise/entv1p1/imsent_infov1p1.html">http://www.imsglobal.org/enterprise/entv1p1/imsent_infov1p1.html</a>
IMS Enterprise XML Binding Specification	<a href="http://www.imsglobal.org/enterprise/entv1p1/imsent_bindv1p1.html">http://www.imsglobal.org/enterprise/entv1p1/imsent_bindv1p1.html</a>
IMS Enterprise Best Practices and Implementation Guide	<a href="http://www.imsglobal.org/enterprise/entv1p1/imsent_bestv1p1.html">http://www.imsglobal.org/enterprise/entv1p1/imsent_bestv1p1.html</a>
Organization API XML schemas and examples	<a href="https://github.com/ExchangeServices">https://github.com/ExchangeServices</a>

### 7.2 Vocabulary

Word	Description
Mentor	School mentor for student
Instructor	Teacher
Guardian	Guardian is the person who has legal custody for a child. It can be either one or both parents or a person designated by the court
Contact	Student contacts
Other responsible	Other responsible to children below 18 years, for example foster parents
Child	Children below 6 year
Student	School student 6 year and older
Administrator	School administrator
PID	Personal identity, formatted [YYYYMMDDNNNN]
GUID	Global unique identifier
Other group	Non education groups
Education group	Student groups related to education course or subject depending on school types
Principal	Director of schools