



IMT Atlantique

Bretagne-Pays de la Loire
École Mines-Télécom

Quarkslab

Securing every bit of your data

Trace-based approach to compiler debugging

GT Debugging - GDR-GPL 2023

Bruno MATEU

June, 8th

Introduction



IMT Atlantique
Bretagne-Pays de la Loire
École Mines-Télécom

Quarkslab

Securing every bit of your data

Introduction

Obfuscations

```
; Function Attrs: mustprogress norecurse nosync nounwind ←  
    readnone sspstrong willreturn uwtable  
define dso_local i32 @foo(i32 noundef %0, i32 noundef %1, i32 noundef ←  
    %2) local_unnamed_addr #0 {  
    %4 = add nsw i32 %1, %0  
    ret i32 %4  
}
```

```
; Function Attrs: mustprogress norecurse nosync nounwind ←  
    readnone sspstrong willreturn uwtable  
define dso_local i32 @foo(i32 noundef %0, i32 noundef %1, i32 noundef ←  
    %2) local_unnamed_addr #0 {  
    %4 = xor i32 %1, %0  
    %5 = and i32 %1, %0  
    %6 = shl i32 %5, 1  
    %7 = add i32 %6, %4  
    ret i32 %7  
}
```

1 • Context

Quarkslab

Securing every bit of your data




IMT Atlantique

Bretagne-Pays de la Loire
École Mines-Télécom


Context

Finding bugs in compilers




Context

Finding bugs in compilers




Context

Finding bugs in compilers




Context

Finding bugs in compilers




Context

Compiler overview




Context

Compiler insides



Context

Compiler insides



2 • Motivations

Quarkslab

Securing every bit of your data




IMT Atlantique

Bretagne-Pays de la Loire
École Mines-Télécom


Motivations

Finding bugs in compilers




Motivations

Finding bugs in compilers




Motivations

Finding bugs in compilers




Motivations

Finding bugs in compilers



Motivations

Finding bugs in compilers



Finding bugs in compilers




Insufficient debugging tools

1st use-case


Insufficient debugging tools

1st use-case




Insufficient debugging tools

1st use-case




Insufficient debugging tools

1st use-case



Insufficient debugging tools

1st use-case




Debugging tools

- Debug information (DWARF)
- Debug outputs produced during transformations


Insufficient debugging tools

2nd use-case




Insufficient debugging tools

2nd use-case




Insufficient debugging tools

2nd use-case



Insufficient debugging tools

2nd use-case



Debugging tools

- Debug information (DWARF)
- Common debugging techniques, e.g. bisection

Insufficient debugging tools

Summary

Generic debugging tools

- Help compiler users to debug their code
- Hard to use for compilers

Insufficient debugging tools

Summary

Generic debugging tools

- Help compiler users to debug their code
- Hard to use for compilers

Towards specialized compiler debugging tools

- Offer higher-level, filtered information
- Aware of the compiler process
- **Understand the transformations that the compiler is doing**

Goal: Tracing high-level transformations

- This multiplication has been replaced by this optimized version that use bitwise shift
- This function has been inlined at these three places

Goal: Tracing high-level transformations


- This multiplication has been replaced by this optimized version that use bitwise shift
- This function has been inlined at these three places

Current status: Tracing atomic transformations

- The 'Instruction' `add nsw i32 %201 %202` has been created with identifier 203
- All occurrences of 'Instruction' 203 have been replaced by the 'Instruction' 210

Trace monitor

Current state of the trace API



3 • Conclusions

Quarkslab

Securing every bit of your data



IMT Atlantique

Bretagne-Pays de la Loire
École Mines-Télécom




Debugging compilers is hard

- Compiler-specific issues
- Benefits of specialized tools
- Poorly studied

Compiler traces


- Proposition to help compiler developers to understand a compilation process
- Could help for debugging...
- ...but also maybe useful in other situations, like certification

Bibliography

-  Chen, Junjie et al. “A Survey of Compiler Testing”. In: *ACM Computing Surveys* 53.1 (Feb. 2020), pp. 1–36. DOI: 10.1145/3363562.
-  IEEE. *IEEE Standard Glossary of Software Engineering Terminology*. 1990. DOI: 10.1109/ieeestd.1990.101064.
-  Gotel, Orlena et al. “Traceability Fundamentals”. In: *Software and Systems Traceability*. Springer London, Oct. 2011, pp. 3–22. DOI: 10.1007/978-1-4471-2239-5_1.

Context

Classification of compiler testing studies



Chen et al., “A Survey of Compiler Testing”

Traceability within compilers

- Create a traceability framework
- Not dedicated to a specific usage
- Implemented in LLVM, but designed with a global approach

Traceability within compilers

- Create a traceability framework
- Not dedicated to a specific usage
- Implemented in LLVM, but designed with a global approach

Trace is optional

- Enable and disable it on demand
- Partial traces must be useful
- No need to implement trace features in every compiler pass to produce useful data

5 • Existing work about traceability

Quarkslab

Securing every bit of your data



IMT Atlantique

Bretagne-Pays de la Loire
École Mines-Télécom

Using the trace

```
0x5555555519a <fib+90>    qid:22 mov     -0x8(%rbp),%edi
0x5555555519d <fib+93>    qid:51 xor     %eax,%eax
0x5555555519f <fib+95>    qid:51 sub     $0x1,%eax
0x555555551a2 <fib+98>    qid:52 add     %eax,%edi
0x555555551a4 <fib+100>   qid:0  call    0x55555555140 <fib>
0x555555551a9 <fib+105>   qid:0  mov     %eax,-0xc(%rbp)
0x555555551ac <fib+108>   qid:24 mov     -0x8(%rbp),%edi
0x555555551af <fib+111>   qid:54 add     $0x3fd1606c,%edi
0x555555551b5 <fib+117>   qid:55 sub     $0x2,%edi
0x555555551b8 <fib+120>   qid:56 sub     $0x3fd1606c,%edi
0x555555551bc <fib+126>   qid:0  call    0x55555555140 <fib>
0x555555551c3 <fib+131>   qid:0  mov     %eax,%ecx
0x555555551c5 <fib+133>   qid:0  mov     -0xc(%rbp),%eax
B+> 0x555555551c8 <fib+136>   qid:58 sub     $0xcfc58a84,%eax
0x555555551cd <fib+141>   qid:59 add     %ecx,%eax
0x555555551cf <fib+143>   qid:60 add     $0xcfc58a84,%eax
0x555555551d4 <fib+148>   qid:28 mov     %eax,-0x4(%rbp)
0x555555551d7 <fib+151>   qid:150 lea     0x2e3e(%rip),%rax
0x555555551de <fib+158>   qid:150 mov     (%rax),%eax
0x555555551e0 <fib+160>   qid:151 lea     0x2e39(%rip),%rcx
0x555555551e7 <fib+167>   qid:151 mov     (%rcx),%ecx
0x555555551e9 <fib+169>   qid:152 mov     %eax,%edx
0x555555551eb <fib+171>   qid:152 sub     $0x1,%edx
0x555555551ee <fib+174>   qid:153 imul    %edx,%eax
0x555555551f1 <fib+177>   qid:154 and     $0x1,%eax
0x555555551f4 <fib+180>   qid:155 cmp     $0x0,%eax

-Trace
Event: creation of 58
name: %20 = sub i32 %13, -809137532
operands: ['0', '57']
opcode: sub
in instants ['ModuleToFunctionPassAdaptor', 'InstructionsSubstitution']

Event: creation of 59
name: %21 = add i32 %20, %19
operands: ['58', '0']
opcode: add
in instants ['ModuleToFunctionPassAdaptor', 'InstructionsSubstitution']

Event: creation of 74
name: <badref> = add i32 %18, %17
operands: ['58', '0']
opcode: add
in instants ['BogusControlFlow']

Event: delete of 58
name: delete
in instants []

record-ful Thread 0x7ffff7f946 In: fib                                L46      PC: 0x555555551c8
(gdb) c
Continuing.

Breakpoint 2, fib (arg=<optimized out>) at debug_ir_-a24d11..ll:46
(gdb) █
```


Definitions of Trace

Debugging traces

*"A trace is a record of the execution of a computer program, showing the sequence of instructions executed, the names and values of variables, or both."*¹

¹IEEE, *IEEE Standard Glossary of Software Engineering Terminology*.

²Gotel et al., "Traceability Fundamentals".

Definitions of Trace

Debugging traces

*"A trace is a record of the execution of a computer program, showing the sequence of instructions executed, the names and values of variables, or both."*¹

More generally

*"Traceability is the potential to relate data 2 can be separate file or included in binary that is stored within artifacts of some kind, along with the ability to examine this relationship"*²

¹IEEE, *IEEE Standard Glossary of Software Engineering Terminology*.


²Gotel et al., "Traceability Fundamentals".

Costs

| Lua | | 88 kB source, 300 kB compiled | | | |
|-----------------|------------------|-------------------------------|-------|-------|-------|
| Options | | -O0 | -O1 | -O2 | -O3 |
| time (s) | Clang-14 | 1.16 | 3.81 | 4.24 | 4.42 |
| | Clang-15 patched | 17.00 | 22.36 | 23.44 | 23.70 |
| Trace size (MB) | | 5.80 | 43.51 | 48.53 | 50.04 |

| keepassxc | | 9.3 MB source, 6.9 MB compiled | | | |
|-----------------|------------------|--------------------------------|--------|---------|---------|
| Options | | -O0 | -O1 | -O2 | -O3 |
| time (s) | Clang-14 | 327.55 | 371.96 | 377.75 | 384.157 |
| | Clang-15 patched | 6302.95 | | 7790.97 | 7721.80 |
| Trace size (MB) | | 38 | | 250 | |

LLVM Metamodel



Existing concepts

- Artifacts: The IR at a given stage of the compilation process
- Trace links: Called events in my case

Existing concepts


- Artifacts: The IR at a given stage of the compilation process
- Trace links: Called events in my case

Instant: Timeline information

- Has a start and an end
- Describes a time window of the compilation process
- Can be nested

Trace monitor

Current state of the trace API




Trace monitor

Current state of the trace API

Trace Monitor

- Inside LLVM core
- API to register *Instants* and *Events*
- Accessible from anywhere




Trace monitor

Current state of the trace API

Integration with LLVM codebase

- Modifications to LLVM to use trace *events* and *instants*
- New *events* and *instants* types can be created to enrich the trace




Trace monitor

Current state of the trace API

Serializer

- No pre-analysis is done by the serializer
- Easily parseable by external tools




Trace monitor

Current state of the trace API

Serializer

- No pre-analysis is done by the serializer
- Easily parseable by external tools



Trace monitor

Current state of the trace API

Link with the binary

- Binary and Trace are separate artifacts
- Each *Value* is uniquely identified in the trace

