

Technical Service Information

THM 440-T4 **NEW 1-2 AND REVERSE BANDS**

CHANGE: Beginning July 2, 1990 (Julian Date 183) all 1991 THM 4T60 (440-T4) transaxles will be

built with the new 1-2 and reverse bands, that require no selective apply pins.

Ease of assembly, because of the elimination of the process for the measurement for the **REASON:**

selective pins.

PARTS AFFECTED:

(1) 1-2 BAND ASSEMBLY - A new manufacturing process machines the area where the case anchor pins contact the band (See Figure 1). With this new process, all of the 1-2 bands are the same size, and the selective band apply pins are eliminated.

NOTE: THE 1-2 BAND STOP LOCATED IN THE BARREL OF THE CASE (ON MODELS SO EQUIPPED) MUST BE REMOVED AND DISCARDED WHEN USING THE NEW BAND.

- (2) REVERSE BAND ASSEMBLY A new manufacturing process machines the area where the case anchor pins contact the band (See Figure 2). With this new process, all of the reverse bands are the same size, and selective band apply pins are eliminated. The new reverse band also has the new friction material to help decrease reverse engagement concerns.
- (3) **SELECTIVE BAND PINS** Eliminated, there is now only ONE size band apply pin required for the 1-2 band, and only ONE size band apply pin required for the reverse band (See Figures 1 and 2).

INTERCHANGEABILITY:

The new 1-2 band assembly will retro-fit back to all previous models, with the proper band apply pin installed (See Figure 1).

NOTE: THE 1-2 BAND STOP LOCATED IN THE BARREL OF THE CASE (ON MODELS SO EQUIPPED) MUST BE REMOVED AND..DISCARDED WHEN USING THE NEW BAND.

NGEABILITY: The new reverse band assembly will retro-fit back to all previous models, with the proper band apply pin (See Figure 2). and it also has the new . friction material to help decrease reverse engagement concerns.

SERVICE INFORMATION:

1-2 Band Assembly (Non-selective Style)	
1-2 Band Apply Pin (Non-selective Style)	
Reverse Band Assembly (Non-selective Style)	
Reverse Band Apply Pin (Non-selective Style)	



Technical Service Information




Figure 1



Technical Service Information




Figure 2