

NAME

exiv2 – Image metadata manipulation tool

SYNOPSIS

exiv2 [*options*] [*action*] *file* ...

DESCRIPTION

exiv2 is a program to read and write Exif, IPTC, XMP metadata and image comments and can read many vendor makernote tags. The program optionally converts between Exif tags, XMP properties and IPTC datasets as recommended by the Exif Standard, the IPTC Standard, the XMP specification and Metadata Working Group guidelines.

The following image formats are supported:

| Type | Exif | IPTC | XMP | Image Comments | ICC Profile |
|---------|------------|------------|------------|-----------------------|-------------|
| ARW | Read | Read | Read | - | - |
| AVIF | Read | Read | Read | - | - |
| BMP | - | - | - | - | - |
| CR2 | Read/Write | Read/Write | Read/Write | - | Read/Write |
| CR3 | Read | Read | Read | - | Read |
| CRW | Read/Write | - | - | Read/Write | - |
| DNG | Read/Write | Read/Write | Read/Write | - | Read/Write |
| EPS | - | - | Read/Write | - | - |
| EXV | Read/Write | Read/Write | Read/Write | Read/Write Read/Write | - |
| GIF | - | - | - | - | - |
| HEIC | Read | Read | Read | - | - |
| HEIF | Read | Read | Read | - | - |
| JP2 | Read/Write | Read/Write | Read/Write | - | Read/Write |
| JPEG | Read/Write | Read/Write | Read/Write | Read/Write | Read/Write |
| JPEG XL | Read | Read | Read | - | - |
| MRW | Read | Read | Read | - | - |
| NEF | Read/Write | Read/Write | Read/Write | - | Read/Write |
| ORF | Read/Write | Read/Write | Read/Write | - | - |
| PEF | Read/Write | Read/Write | Read/Write | - | Read/Write |
| PGF | Read/Write | Read/Write | Read/Write | Read/Write | Read/Write |
| PNG | Read/Write | Read/Write | Read/Write | Read/Write | Read/Write |
| PSD | Read/Write | Read/Write | Read/Write | - | - |
| RAF | Read | Read | Read | - | - |
| RW2 | Read | Read | Read | - | - |
| SR2 | Read | Read | Read | - | - |
| SRW | Read/Write | Read/Write | Read/Write | - | - |
| TGA | - | - | - | - | - |
| TIFF | Read/Write | Read/Write | Read/Write | - | Read/Write |
| WEBP | Read/Write | - | Read/Write | - | Read/Write |
| XMP | - | - | Read/Write | - | - |

- Support for GIF, TGA and BMP images is minimal: the image format is recognized, a MIME type assigned to it and the height and width of the image are determined.
- Reading other TIFF-like RAW image formats, which are not listed in the table, may also work.
- Support for BMFF file types such as CR3, HEIF, HEIC, AVIF, and JPEG XL is a build option. To check if this is enabled, use:

```
$ exiv2 --version --verbose | grep bmff
enable_bmff=1
```

- Naked codestream JPEG XL files do not contain Exif, IPTC, or XMP metadata.

ACTIONS

The *action* argument is only required if it is not clear from the *options* which action is implied.

pr | print

Print image metadata. This is the default action, i.e., the command `exiv2 image.jpg` will print a summary of the image Exif metadata.

ex | extract

Extract metadata to *.exv, XMP sidecar (*.xmp) and thumbnail image files. Modification commands can be applied on-the-fly.

in | insert

Insert metadata from corresponding *.exv, XMP sidecar (*.xmp) and thumbnail files. Use option `-S .suf` to change the suffix of the input files. Since files of any supported format can be used as input files, this command can be used to copy the metadata between files of different formats. Modification commands can be applied on-the-fly.

rm | delete

Delete image metadata from the files.

ad | adjust

Adjust Exif timestamps by the given time. Requires at least one of the options `-a time`, `-Y yrs`, `-O mon` or `-D day`.

mo | modify

Apply commands to modify (add, set, delete) the Exif, IPTC and XMP metadata of image files. Requires option `-c`, `-m` or `-M`.

mv | rename

Rename files and/or set file timestamps according to the Exif create timestamp. Uses the value of tag Exif.Photo.DateTimeOriginal or, if not present, Exif.Image.DateTime to determine the timestamp. The filename format can be set with `-r fmt`, timestamp options are `-t` and `-T`. When no rename format is provided, the default is `'%Y%m%d_%H%M%S'` using definitions from `strftime(3)`.

fi | fixiso

Copy the ISO setting from one of the proprietary Nikon or Canon makernote ISO tags to the regular Exif ISO tag, Exif.Photo.ISOSpeedRatings. Does not overwrite an existing standard Exif ISO tag.

fc | fixcom

Fix the character encoding of Exif Unicode user comments. Decodes the comment using the auto-detected or specified character encoding and writes it back in UCS-2. Use option `-n` to specify the current encoding of the comment if necessary.

COMMAND SUMMARY

exiv2 [opt [arg]]+ [act] file ...

| option [arg] | long option | description |
|--------------|---|--|
| -a tim | --adjust | Modify time stamps. [+ -]HH[:MM[:SS[.mmm]]] |
| -b | --binary | This option is obsolete and should not be used. Reserved for test suite (with option --comment) |
| -c txt | --comment | JPEG comment string to set in the image ('modify' action). ... |
| -d tgt | --delete | Delete target(s) for the 'delete' action. ... |
| -D +-n | --days | Time adjustment by a positive or negative number of days ... |
| -e tgt | --extract | Extract target(s) for the 'extract' action. |
| -f | --force | Do not prompt before overwriting existing files ... |
| -F | --Force | Do not prompt before renaming files (Force rename) ... |
| -g key | --grep | Only output info for this Exiv2 key |
| -h | --help | Display help and exit. |
| -i tgt | --insert | Insert target(s) for the 'insert' action. ... |
| -k | --keep | Preserve file timestamps when updating files |
| -K key | --key | Report key. Similar to -g (grep) however key must match exactly. |
| -l dir | --location | Location (directory) for files to be inserted or extracted. |
| -m file | --modify | read commands from cmd-file |
| -M cmd | --Modify | Command line for the 'modify' action. ... |
| -n enc | --encode | Charset to decode Exif Unicode user comments. See: man 3 iconv_open |
| -O +-n | --months | Time adjustment by a positive or negative number of months, ... |
| -p mod | --print | Print report (common reports) |
| -P flg | --Print | Print report (fine grained control) |
| -q | --quiet | Silence warnings and error messages from the Exiv2 library ... |
| -Q lvl | --log | Set the log-level to 'd'(ebug), 'i'(nfo), 'w'(arning), 'e'(rror) |
| -r fmt | --rename | Filename format for the 'rename' action. ... |
| -S suf | --suffix | Use suffix .suf for source files for insert command. |
| -t | --timestamp | Set the file timestamp according to the Exif create timestamp ... |
| -T | --Timestamp | Only set the file timestamp according to Exif create timestamp ... |
| -u | --unknown | Show unknown tags ... |
| -v | --verbose | verbose |
| -V | --version | Show the program version and exit. |
| -Y +-n | --years | Time adjustment by a positive or negative number of years ... |
| act | pr ex in rm ad mo mv fi fc | print, extract, insert, delete, adjust, modify, rename, fixiso, fixcom |
| cmd | See "Commands" below. | |
| flg | E I X x g k l n y c s v t h | Exif, IPTC, XMP, num, grp, key, label, name, type, count, size, vanilla, translated, hex |
| fmt | Default format is %Y%m%d_%H%M%S. | |
| lvl | d i i w e | debug, info, warning, error |
| mod | s a e t v h i x c p i C R S X | summary, all, exif, translated, vanilla, hex, iptc, xmp, comment, preview, ICC Profile, Recursive Structure, Simple Structure, raw XMP |
| tgt | a c e i p t x C X XX - | all, comment, exif, iptc, preview, thumb, xmp, ICC Profile, SideCar, RawXMP, stdin/out |

OPTIONS

- h** Display help and exit.
- V** Show the program version and exit.
When **-V** is combined with **-v** (Verbose version), build information is printed to standard output along with a list of shared libraries which have been loaded into memory. Verbose version is supported on Windows (MSVC, Cygwin and MinGW builds), macOS and Linux and is provided for test and debugging.
- v** Be verbose during the program run.
- q** Silence warnings and error messages from the Exiv2 library during the program run (quiet). Note that options **-v** and **-q** can be used at the same time.
- Q lvl** Set the log-level to 'd'(ebug), 'i'(nfo), 'w'(arning), 'e'(rror) or 'm'(ute). The default log-level is 'w'. **-Qm** is equivalent to **-q**. All log messages are written to standard error.
- u** Show unknown tags (default is to suppress tags which don't have a name).
- g key** Only keys which match the given key (grep).
Multiple **-g** options can be used to filter info to less keys. Example: `exiv2 -v -V -g webready -g time`. The default `exiv2` command prints a "summary report" which is quite short. When you use `-g` without a `-pmod` option, you do not get a summary report and in effect you get `-g pattern -pa image ...`

```
$ bin/exiv2 -g Date http://clanmills.com/Stonehenge.jpg
Exif.Image.DateTime          Ascii  20 2015:07:16 20:25:28
Exif.Photo.DateTimeOriginal  Ascii  20 2015:07:16 15:38:54
Exif.Photo.DateTimeDigitized Ascii  20 2015:07:16 15:38:54
Exif.NikonWt.DateDisplayFormat Byte  1  Y/M/D
Exif.GPSInfo.GPSDateStamp    Ascii  11 2015:07:16
Xmp.xmp.ModifyDate           XmpText 25 2015-07-16T20:25:28+01:00
```

You may use `-pmod` filters to further filter output. For example:

```
$ bin/exiv2 -px -g Date http://clanmills.com/Stonehenge.jpg
Xmp.xmp.ModifyDate           XmpText 25 2015-07-16T20:25:28+01:00
```

The option `-g` (`--grep`) applies to keys and not values.

The key may finish with the optional modifier `/i` to indicate case insensitive.

- K key** Only report data for given key.
Multiple **-K** options can be used to report more than a single key.
\$ `exiv2 -K Exif.Photo.DateTimeDigitized -K Exif.Photo.DateTimeOriginal -pt R.jpg`
Exif.Photo.DateTimeOriginal Ascii 20 2011:09:18 16:25:48
Exif.Photo.DateTimeDigitized Ascii 20 2011:09:18 16:25:48
- n enc** Charset to use to decode Exif Unicode user comments. *enc* is a name understood by `iconv_open(3)`, e.g., 'UTF-8'.
- k** Preserve file timestamps when updating files (keep). Can be used with all options which update files. The flag is ignored by read-only options.
- t** Set the file timestamp according to the Exif create timestamp in addition to renaming the file (overrides **-k**). This option is only used with the 'rename' action. See Exif DateTime below for additional information.
- T** Only set the file timestamp according to the Exif create timestamp, do not rename the file (overrides **-k**). This option is only used with the 'rename' action. Note: On Windows you may have to set the TZ environment variable for this option to work correctly. See Exif DateTime below for additional information.

-f,-F These options are used by the commands 'rename' and 'extract' to determine the file overwrite policy. These options are usually combined with -v/--verbose to provide additional status output.

The options --force and --Force apply to the 'rename' command. The 'extract' command treats --force and --Force as permission to overwrite.

The default behaviour is to prompt the user.

-f = Do not prompt before overwriting existing files.

-F = Do not prompt before renaming files. Appends '_1' ('_2', ...) to the name of the new file. For example:

```
$ curl --silent -O http://clanmills.com/Stonehenge.jpg
$ exiv2 --verbose --Force rename Stonehenge.jpg
File 1/1: Stonehenge.jpg
Renaming file to ./20150716_153854.jpg
$ curl --silent -O http://clanmills.com/Stonehenge.jpg
$ exiv2 --verbose --Force rename Stonehenge.jpg
File 1/1: Stonehenge.jpg
Renaming file to ./20150716_153854_1.jpg
```

The 'rename' command will only overwrite files when the option --force is used. The option --Force is provided to avoid unintentional loss of valuable image files.

The 'extract' command will overwrite files when either --force or --Force is used. Overwriting extracted files will not cause the loss of image files.

-r *fmt* Filename format for the 'rename' action. The format string uses **strftime(3)** definitions and supports the following keywords:

```
:basename:    original filename without extension
:dirname:     name of the directory holding the original file
:parentname:  name of parent directory
```

Note that the colons are part of the keyword.

-a *time* Time adjustment in the format [-]HH[:MM[:SS]]. This option is only used with the 'adjust' action. Examples: 1 adds one hour, 1:01 adds one hour and one minute, -0:00:30 subtracts 30 seconds. See Exif DateTime below for additional information.

-Y *yrs* Time adjustment by a positive or negative number of years, for the 'adjust' action.

-O *mon* Time adjustment by a positive or negative number of months, for the 'adjust' action.

-D *day* Time adjustment by a positive or negative number of days, for the 'adjust' action.

-p *mode* Print mode for the 'print' action. Possible modes are:

```
s : print a summary of the Exif metadata (the default)
a : print Exif, IPTC and XMP metadata (shortcut for -Pkycv)
e : print Exif metadata (shortcut for -PEkycv)
t : interpreted (translated) Exif tags (-PEkycv)
v : plain Exif tag values (-PExgnycv)
h : hexdump of the Exif data (-PExgnycvsh)
i : IPTC datasets (-PIkycv)
x : XMP properties (-PXkycv)
c : JPEG comment
```

p : list available image previews, sorted by preview image size in pixels
 C : print image ICC Profile (jpg, png, tiff, webp, cr2, jp2 only)
 R : print image structure recursively (jpg, png, tiff, webp, cr2, jp2 only)
 S : print image structure information (jpg, png, tiff, webp, cr2, jp2 only)
 X : print "raw" XMP (jpg, png, tiff, webp, cr2, jp2 only)

-P flgs Print flags for fine control of the tag list ('print' action). Allows control of the type of metadata as well as data columns included in the print output. Valid flags are:

E : include Exif tags in the list
 I : IPTC datasets
 X : XMP properties
 x : print a column with the tag number
 g : group name
 k : key
 l : tag label
 n : tag name
 y : type
 c : number of components (count)
 s : size in bytes
 v : plain data value (vanilla values)
 V : plain data value AND the word 'set ' (for use with exiv2 -m-)
 t : interpreted (translated) human readable data
 h : hexdump of the data

-d tgt Delete target(s) for the 'delete' action. Possible targets are:

a : all supported metadata (the default)
 e : Exif section
 t : Exif thumbnail only
 i : IPTC data
 x : XMP packet
 c : JPEG comment
 C : ICC Profile
 I : All IPTC data

-i tgt Insert target(s) for the 'insert' action. Possible targets are the same as those for the **-d** option, plus an optional modifier:

X : Insert metadata from an XMP sidecar file <file>.xmp. The remaining insert targets determine what metadata to insert from the sidecar file. Possible are Exif, IPTC and XMP and the default is all of these. Note that the inserted XMP properties include those converted to Exif and IPTC.

XX: Insert "raw" XMP metadata from a sidecar (see option -pX)

- : Read from stdin. This option is intended for "filter" operations such as:
 \$ exiv2 -e{tgt}- *filename* | xmllint | exiv2 -i{tgt}- *filename*

Only JPEG thumbnails can be inserted (not TIFF thumbnails), and must be named *file-thumb.jpg*.

-e tgt Extract target(s) for the 'extract' action. Possible targets are the same as those for the **-d** option, plus a target to extract preview images and a modifier to generate an XMP sidecar file:

p[<n>[,<m> ...]] : Extract preview images. The optional comma separated list of preview image numbers is used to determine which preview images to extract. The available preview images and their numbers are displayed with the 'print' option **-pp**.

C : Extract embedded ICC profile to <file>.icc

X : Extract metadata to an XMP sidecar file <file>.xmp. The remaining extract targets determine what metadata to extract to the sidecar file. Possible are Exif, IPTC and XMP and the default is all of these.

XX: Extract "raw" XMP metadata to a sidecar (see -pX)

You may not use modify commands with the -eXX option and only XMP is written to the sidecar.

– *Output to stdout (see -i tgt for an example of this feature)*

–**c** *txt* JPEG comment string to set in the image ('modify' action). This option can also be used with the 'extract' and 'insert' actions to modify metadata on-the-fly.

–**m** *file* Command file for the 'modify' action. This option can also be used with the 'extract' and 'insert' actions to modify metadata on-the-fly. -m- represents standard-input.

–**M** *cmd* Command line for the 'modify' action. This option can also be used with the 'extract' and 'insert' actions to modify metadata on-the-fly. The format for the commands is the same as that of the lines of a command file.

–**I** *dir* Location (directory) for files to be inserted or extracted.

–**S** *.suf* Use suffix *.suf* for source files in 'insert' action.

COMMANDS

Commands for the 'modify' action can be read from a command file, e.g.,

```
$ exiv2 -m cmd.txt image.jpg
```

or given on the command line, as in

```
$ exiv2 -M"add Iptc.Application2.Credit String Mr. Smith" image.jpg
```

Note the quotes. Multiple **-m** and **-M** options can be combined, and a non-standard XMP namespace registered.

```
$ exiv2 -M"reg myprefix http://ns.myprefix.me/" -M"add Xmp.myprefix.Whom Mr. Smith" -M"set Exif.Image.Artist M
```

When writing Exif, IPTC and XMP metadata, **exiv2** enforces only a correct metadata structure. It is possible to write tags with types and values different from those specified in the standards, duplicate Exif tags, undefined tags, or incomplete metadata. While **exiv2** is able to read all metadata that it can write, other programs may have difficulties with images that contain non standard-conforming metadata.

Command format

The format of a command is

```
set | add | del key [[type] value]
```

set Set the *value* of an existing tag with a matching *key* or add the tag.

add Add a tag (unless *key* is a non-repeatable IPTC key; nothing prevents you from adding duplicate Exif tags).

del Delete all occurrences of a tag (requires only a *key*).

key Exiv2 Exif, IPTC or XMP key.

type Exif keys: Byte | Ascii | Short | Long | Rational | Undefined | SShort | SLong | SRational | Comment
 IPTC keys: String | Date | Time | Short | Undefined
 XMP keys: XmpAlt | XmpBag | XmpSeq | LangAlt

A default *type* is used if none is explicitly given. The default is determined based on *key*.

value The remaining text on the line is the value. It can optionally be enclosed in single quotes ('*value*') or double quotes ("*value*").

The value is optional. Not providing any value is equivalent to an empty value ("") and is mainly useful to create an XMP array property, e.g., a bag.

The format of Exif **Comment** values include an optional charset specification at the beginning. Comments are used by the tags Exif.Photo.UserComment, Exif.GPSInfo.GPSProcessingMethod and Exif.GPSInfo.GPSAreaInformation. Comments are stored as Undefined tags with an 8 byte encoding definition follow by the encoded data. The charset is specified as follows:

```
[charset=Ascii|Jis|Unicode|Undefined] comment  

charset=Undefined is the default
```

```
$ exiv2 -M'set Exif.Photo.UserComment charset=Ascii My photo' x.jpg
$ exiv2 -pa --grep UserComment x.jpg
Exif.Photo.UserComment      Undefined 16 My photo
$ exiv2 -pv --grep UserComment x.jpg
0x9286 Photo      UserComment Undefined 16 charset=Ascii My photo
```



```
$ exiv2 -M'set Exif.Photo.UserComment charset=Unicode \u0052\u006f\u0062\u0069\u006e' x.jpg
$ exiv2 -pa --grep UserComment x.jpg
Exif.Photo.UserComment          Undefined 18 Robin
$ exiv2 -pv --grep UserComment x.jpg
0x9286 Photo      UserComment          Undefined 18 charset=Unicode Robin
```

```
$ exiv2 -M'set Exif.GPSInfo.GPSProcessingMethod HYBRID-FIX' x.jpg
$ exiv2 -pa --grep ProcessingMethod x.jpg
Exif.GPSInfo.GPSProcessingMethod Undefined 18 HYBRID-FIX
$ exiv2 -pv --grep ProcessingMethod x.jpg
0x001b GPSInfo    GPSProcessingMethod Undefined 18 HYBRID-FIX
```

The format for an IPTC **Date** value is: YYYY–MM–DD (year, month, day)

The format for an IPTC **Time** value is: HH:MM:SS (hours, minutes, seconds) and may optionally be followed by: -HH:MM or +HH:MM (hours, minutes ahead/behind UTC)

The format of **Rational** (and **SRational**) is one of: **integer** | **integer/integer** | **Fnumber** | **number**
Rational Examples:

```
$ exiv2 -M'set Exif.Photo.MaxApertureValue 557429/62500' X.jpg
$ exiv2 -M'set Exif.Photo.MaxApertureValue F5.6' X.jpg
```

The **Rational** format Fnumber is for the convenience of setting aperture values. Aperture values are stored in Exif as an **APEX** value which can be evaluated by the expression:

```
apex-value = log(Fnumber) * 2.0 / log(2.0)
number     = exp(apex-value * log(2.0) / 2.0)
```

The **Rational** format Fnumber is valid for any **Rational**, even when the key is not an Aperture. More information about **APEX** value is available from: http://en.wikipedia.org/wiki/APEX_system

The format of XMP **LangAlt** values includes an optional language qualifier:
lang="language-code" text

The double quotes around the *language-code* are optional. If no language qualifier is supplied, then the value of "x-default" is used. More information on the language format can be found at: <https://www.ietf.org/rfc/rfc3066.txt>

```
$ exiv2 -M'set Xmp.dc.title lang="de-DE" Euros' X.jpg
$ exiv2 -M'set Xmp.dc.title lang="en-GB" Pounds' X.jpg
$ exiv2 -M'set Xmp.dc.title lang="en-US" In God We Trust' X.jpg
$ exiv2 -M'set Xmp.dc.title lang=fr-FR Euros' X.jpg
$ exiv2 -M'set Xmp.dc.title lang=jp Yen' X.jpg
$ exiv2 -M'set Xmp.dc.title All others pay cash' X.jpg
```

To remove a language specification, set the value to "" (empty string)

```
$ exiv2 -M'set Xmp.dc.title lang="en-US" X.jpg
```

To remove all language specifications, delete the key:

```
$ exiv2 -M'del Xmp.dc.title' X.jpg
```

To register additional XMP namespaces, combine the command with:

reg prefix namespace

Command file format

Empty lines and lines starting with # in a command file are ignored (comments). Remaining lines are commands as described above.

EXIF TAGNAMES AND VALUES

Exiv2 displays metadata tags and values.

The tag is a triplet of Family.Group.Tagname. The following groups are defined for the family Exif:

| | | | | | |
|-----------|--------------|-----------|--------------|----------------|----------------------|
| GPSInfo | Canon | Fujifilm | NikonMe | OlympusFe7 | SonyMisc2b |
| Image | CanonCf | | NikonPc | OlympusFe9 | SonyMisc3c |
| Image2 | CanonCs | Nikon1 | NikonPreview | OlympusFi | SonyMinolta |
| Image3 | CanonFi | Nikon2 | NikonSi01xx | OlympusIp | SonySInfo1 |
| Iop | CanonPa | Nikon3 | NikonSi02xx | OlympusRd | |
| MakerNote | CanonPi | NikonAFT | NikonSiD300a | OlympusRd2 | Samsung2 |
| MpfInfo | CanonPr | NikonAf | NikonSiD300b | OlympusRi | SamsungPictureWizard |
| Photo | CanonSi | NikonAf2 | NikonSiD40 | | SamsungPreview |
| SubImage1 | CanonTi | NikonAf22 | NikonSiD80 | Sigma | |
| SubImage2 | | NikonCb1 | NikonVr | | |
| SubImage3 | Casio | NikonCb2 | NikonWt | Sony1 | |
| SubImage4 | Casio2 | NikonCb2a | | Sony1Cs | |
| SubImage5 | | NikonCb3 | Olympus | Sony1Cs2 | |
| SubImage6 | Minolta | NikonCb4 | Olympus2 | Sony1MltCs7D | |
| SubImage7 | MinoltaCs5D | NikonFi | OlympusCs | Sony1MltCsA100 | |
| SubImage8 | MinoltaCs7D | NikonFl1 | OlympusEq | Sony1MltCsNew | |
| SubImage9 | MinoltaCsNew | NikonFl2 | OlympusFe1 | Sony1MltCsOld | |
| SubThumb1 | MinoltaCsOld | NikonFl3 | OlympusFe2 | Sony2 | |
| Thumbnail | | NikonLi | OlympusFe3 | Sony2Cs | |
| | Panasonic | NikonLd1 | OlympusFe4 | Sony2Cs2 | |
| Pentax | PanasonicRaw | NikonLd2 | OlympusFe5 | Sony2Fp | |
| PentaxDng | | NikonLd3 | OlympusFe6 | SonyMisc1 | |

Exiv2 supports Exif 2.2 Standard Tags. Exiv2 also supports reading and writing manufacturer's Maker-Note. The information in Exif.Photo.MakerNote is encoded as manufacturer's sub-records. For example, CanonCs are Camera Settings, NikonAf are Nikon Auto Focus records, NikonCb are Nikon Color Balance Records. Every tag is defined by a unique tagId (16 bit integer) which is unique within a Group.

You can query Exiv2 groups and tags with the sample program taglist which is documented in README-SAMPLES.md

Exif Metadata values are defined in the Exif Standard. All data is an array of data elements. The Count defines the number elements in the array. All elements in an array have the same type.

| Type | Explanation |
|--------------|-------------------------------------|
| 1 BYTE | An 8-bit unsigned integer. |
| 2 ASCII | 7-bit ASCII. NUL terminated. |
| 3 SHORT | A 16-bit (2-byte) unsigned integer. |
| 4 LONG | A 32-bit (4-byte) unsigned integer. |
| 5 RATIONAL | Two LONGs. Numerator, denominator. |
| 7 UNDEFINED | An 8-bit byte. |
| 8 SSHORT | A 16-bit (2-byte) signed integer. |
| 9 SLONG | A 32-bit (4-byte) signed integer. |
| 10 SRATIONAL | Two SLONGs. Numerator, denominator. |

The printing flag `t` = translated and is intended for human use. Scripts should never use translated values as they are localised and the format may change as Exiv2 evolves. The printing flag `v` reports the values recorded in the metadata and should be used by scripts.

Exif DateTime

An Exif DateTime string is stored as 20 ascii bytes (including trailing nul) in the format:

YYYY:MM:DD HH:MM:SS

The exiv2 command-line program options `-t` and `-T` will accept files in which the Date has been incorrectly stored as YYYY-MM-DD. The option `-a` enables the user to adjust the DateTime in the file and applies the YYYY:MM:DD HH:MM:SS standard.

CONFIGURATION FILE

Exiv2 can read an optional configuration file `~/exiv2` on Unix systems and `%USERPROFILE%\exiv2.ini` on Windows (using a Visual Studio build). Cygwin and MinGW/msys2 follow the unix convention and use `~/exiv2`. You can determine the location of the configuration file with the command:

```
$ exiv2 --verbose --version --grep config_path
exiv2 0.27.0.1
config_path=/Users/rmills/.exiv2
```

The purpose of the configuration file is to define your own lenses for recognition by Exiv2. The configuration file is in Windows .ini format and has sections for each of the major camera manufactures canon, nikon, pentax, minolta, olympus and sony. The lens metadata is stored as a integer called the lensID. You can change the lens name associated with any lensID.

```
$ cat ~/.exiv2
[nikon]
146=Robin's Sigma Lens <--- The name of your lens
```

You obtain the lensID for your camera with the command:

```
$ exiv2 -pv --grep lens/i http://clanmills.com/Stonehenge.jpg
0x0083 Nikon3    LensType      Byte    1 14
0x0084 Nikon3    Lens          Rational  4 180/10 2500/10 35/10 63/10
0x008b Nikon3    LensFStops     Undefined 4 55 1 12 0
0x000c NikonLd3  LensIDNumber   Byte    1 146 <--- This number
0x000d NikonLd3  LensFStops     Byte    1 55
```

EXAMPLES

```
$ exiv2 *.jpg
```

Prints a summary of the Exif information for all JPEG files in the directory. The summary report is rather brief and presentation does not use the Family.Group.Tag convention.

If you use `--grep` pattern, the default becomes `-pa`. See `-g/grep` above.

```
$ exiv2 -g Date http://clanmills.com/Stonehenge.jpg
```

```
$ exiv2 -pi image.jpg
```

Prints the IPTC metadata of the image.

```
$ exiv2 rename img_1234.jpg
```

Renames `img_1234.jpg` (taken on 13-Nov-05 at 22:58:31) to `20051113_225831.jpg`

```
$ exiv2 -r'basename_%Y%m' rename img_1234.jpg
```

Renames `img_1234.jpg` to `img_1234_200511.jpg`

```
$ exiv2 -et img1.jpg img2.jpg
```

Extracts the Exif thumbnails from the two files into `img1-thumb.jpg` and `img2-thumb.jpg`.

```
$ exiv2 -it img1.jpg img2.jpg
```

Inserts (copies) metadata from `img1.exv` to `img1.jpg` and from `img2.exv` to `img2.jpg`.

```
$ exiv2 -ep1,2 image.jpg
```

Extracts previews 1 and 2 from the image to the files `image-preview1.jpg` and `image-preview2.jpg`.

```
$ exiv2 -eiX image.jpg
```

Extracts IPTC datasets into an XMP sidecar file `image.xmp` and in the process converts them to "IPTC Core" XMP schema.

```
$ exiv2 -iixX image.jpg
```

Inserts IPTC and XMP metadata from an XMP sidecar file `image.xmp` into `image.jpg`. The resulting IPTC datasets are converted from the "IPTC Core" XMP schema properties in the sidecar file to the older IPTC IIM4 format. The inserted XMP properties include those in the "IPTC Core" XMP schema.

```
$ exiv2 -M"set Exif.Photo.UserComment charset=Ascii New Exif comment" image.jpg
```

Sets the Exif comment to an ASCII string.

```
$ exiv2 -M"set Exif.GPSInfo.GPSLatitude 4/1 15/1 33/1" \ -M"set Exif.GPSInfo.GPSLatitudeRef N" image.jpg
```

Sets the latitude to 4 degrees, 15 minutes and 33 seconds north. The Exif standard stipulates that the GPS-Latitude tag consists of three Rational numbers for the degrees, minutes and seconds of the latitude and `GPSLatitudeRef` contains either 'N' or 'S' for north or south latitude respectively.

```
$ exiv2 -l/tmp -S.CRW insert /data/*.JPG
```

Copy all metadata from CRW files in the `/tmp` directory to JPG files with corresponding basenames in the `/data` directory. Note that this copies metadata as is, without any modifications to adapt it to the requirements of the target format. Some tags copied like this may not make sense in the target image.

SEE ALSO

<https://exiv2.org/sample.html#modify>

Sample command files.

<https://exiv2.org/metadata.html>

Taglists with *key* and default *type* values.

AUTHORS

exiv2 was written by Andreas Huggel and others.

The Exiv2 project web site is <https://exiv2.org>.

The code is hosted on GitHub at <https://github.com/exiv2/exiv2>