xVio Scan

Sample API Callouts

Complete HTTP request and response examples for all xVio Scan API endpoints, including authentication headers, request bodies, and response formats. All sensitive values are masked with descriptive placeholders.

Prepared by

ExonPro Innovations LLP

Base URL

`https://api.xvio.ai/v1`

Date

March 2026

Common Headers

All requests use HTTPS (TLS 1.2+). All responses are JSON (`Content-Type: application/json`).

HEADER	VALUE	DESCRIPTION
`Authorization`	`Bearer {MASKED_JWT_TOKEN}`	RS256 JWT issued by xVio Scan (required on authenticated endpoints)
`X-App-ID`	`xvio-scan`	Application identifier (required on tenant endpoints)
`Content-Type`	`application/json`	Request body format
`Origin`	`https://scan.xvio.ai`	CORS origin (validated against allowlist)

Error Response Format (all endpoints)

```
HTTP/1.1 {statusCode}
Content-Type: application/json

{
  "error": "ERROR_CODE",
  "message": "Human-readable description",
  "errorCode": "ERROR_CODE"
}
```

Common error codes: `UNAUTHORIZED` , `FORBIDDEN` , `NOT_FOUND` , `VALIDATION_ERROR` , `RATE_LIMITED` , `QUOTA_EXCEEDED`

1. Authentication Endpoints

1a. POST /tenant/auth/login

Initiates Salesforce OAuth 2.0 + PKCE login flow. Returns available auth methods and Salesforce authorization URL.

REQUEST

```
POST /v1/tenant/auth/login HTTP/1.1
Host: api.xvio.ai
Content-Type: application/json
X-App-ID: xvio-scan
Origin: https://scan.xvio.ai

{
  "customId": "free",
  "redirectUri": "https://scan.xvio.ai/auth/callback"
}
```

RESPONSE 200 OK

```
HTTP/1.1 200 OK
Content-Type: application/json
Access-Control-Allow-Origin: https://scan.xvio.ai
Access-Control-Allow-Credentials: true

{
  "authMethods": {
    "salesforce": {
      "authUrl": "https://login.salesforce.com/services/oauth2/authorize?response_
type=code&client_id={SF_CLIENT_ID}&redirect_uri=...&state={CSRF_STATE}&code_challe
nge={PKCE_CHALLENGE}&code_challenge_method=S256&scope=api+refresh_token",
      "state": "{CSRF_STATE}"
    },
    "cognito": { "enabled": true }
  },
  "tenant": {
    "id": "{TENANT_ID}",
    "name": "xVio Free",
    "customId": "free"
  }
}
```

> Rate limit: 10 requests per minute per IP.

1b. GET /tenant/auth/callback

Salesforce OAuth callback. Exchanges authorization code for tokens. Redirects to web app or mobile deep link.

REQUEST

```
GET /v1/tenant/auth/callback?code={SF_AUTH_CODE}&state={CSRF_STATE} HTTP/1.1
Host: api.xvio.ai
```

RESPONSE 302 (Web)

```
HTTP/1.1 302 Found
Location: https://scan.xvio.ai/auth/callback?authSuccess=true
Set-Cookie: token={MASKED_JWT_TOKEN}; HttpOnly; Secure; SameSite=None; Domain=.xvio.ai; Path=/; Max-Age=900
Set-Cookie: tenantId={TENANT_ID}; Secure; SameSite=None; Domain=.xvio.ai; Path=/; Max-Age=2592000
```

RESPONSE 302 (Mobile)

```
HTTP/1.1 302 Found
Location: xvio://oauth/callback?authSuccess=true&code={ONE_TIME_CODE}&tenantId={TENANT_ID}
```

> Mobile redirects use a one-time auth code (60s TTL) instead of tokens in the URL.

1c. POST /tenant/auth/exchange

Exchanges one-time auth code for JWT tokens. Used by mobile apps after deep link callback.

REQUEST

```
POST /v1/tenant/auth/exchange HTTP/1.1
Host: api.xvio.ai
Content-Type: application/json

{
  "code": "{ONE_TIME_AUTH_CODE}"
}
```

RESPONSE 200 OK

```
HTTP/1.1 200 OK
Content-Type: application/json

{
  "accessToken": "{MASKED_JWT_TOKEN}",
  "token": "{MASKED_JWT_TOKEN}",
  "refreshToken": "{REFRESH_TOKEN}",
  "expiresIn": 900,
  "tenantId": "{TENANT_ID}",
  "user": {
    "id": "{USER_ID}",
    "email": "{USER_EMAIL}",
    "name": "{USER_NAME}"
  }
}
```

> The one-time code expires after 60 seconds and is deleted after first use.

1d. POST /tenant/auth/refresh

Refreshes an expired JWT using the refresh token.

REQUEST

```
POST /v1/tenant/auth/refresh HTTP/1.1
Host: api.xvio.ai
Content-Type: application/json

{
  "refreshToken": "{REFRESH_TOKEN}",
  "tenantId": "{TENANT_ID}"
}
```

RESPONSE 200 OK

```
HTTP/1.1 200 OK
Content-Type: application/json
Set-Cookie: token={MASKED_JWT_TOKEN}; HttpOnly; Secure; SameSite=None; Domain=.xvi
o.ai; Path=/; Max-Age=900

{
  "accessToken": "{MASKED_JWT_TOKEN}",
  "expiresIn": 900
}
```

> Rate limit: 30 requests per minute per IP.

1e. POST /tenant/auth/logout

Invalidates session, revokes JWT and optionally the refresh token.

REQUEST

```
POST /v1/tenant/auth/logout HTTP/1.1
Host: api.xvio.ai
Authorization: Bearer {MASKED_JWT_TOKEN}
Content-Type: application/json

{
  "refreshToken": "{REFRESH_TOKEN}"
}
```

RESPONSE 200 OK

```
HTTP/1.1 200 OK
Content-Type: application/json
Set-Cookie: token=; HttpOnly; Secure; SameSite=None; Domain=.xvio.ai; Path=/; Max-
Age=0
Set-Cookie: tenantId=; Secure; SameSite=None; Domain=.xvio.ai; Path=/; Max-Age=0

{
  "success": true,
  "message": "Logged out successfully"
}
```

2. Scanning and Jobs Endpoints

2a. POST /tenant/jobs

Upload a document for AI scanning. Accepts base64-encoded file.

REQUEST

```
POST /v1/tenant/jobs HTTP/1.1
Host: api.xvio.ai
Authorization: Bearer {MASKED_JWT_TOKEN}
Content-Type: application/json
X-App-ID: xvio-scan

{
  "tenantId": "{TENANT_ID}",
  "userId": "{USER_ID}",
  "serviceId": "{SERVICE_ID}",
  "file": {
    "name": "business-card.jpg",
    "type": "image/jpeg",
    "data": "{BASE64_FILE_DATA}"
  }
}
```

RESPONSE 201 Created

```
HTTP/1.1 201 Created
Content-Type: application/json

{
  "jobId": "{JOB_ID}",
  "status": "pending",
  "progress": 0,
  "serviceId": "{SERVICE_ID}",
  "serviceName": "Business Card Scanner",
  "createdAt": "2026-03-09T10:00:00.000Z"
}
```

> File size limit: 20MB for base64. For larger files (up to 50MB), use the presigned upload endpoint.

2b. POST /tenant/services/{serviceId}/upload-presigned

Get a presigned S3 URL for large file uploads.

REQUEST

```
POST /v1/tenant/services/{SERVICE_ID}/upload-presigned HTTP/1.1
Host: api.xvio.ai
Authorization: Bearer {MASKED_JWT_TOKEN}
Content-Type: application/json
X-App-ID: xvio-scan

{
  "tenantId": "{TENANT_ID}",
  "userId": "{USER_ID}",
  "filename": "invoice-scan.pdf",
  "contentType": "application/pdf"
}
```

RESPONSE 200 OK

```
HTTP/1.1 200 OK
Content-Type: application/json

{
  "uploadUrl": "{PRESIGNED_S3_URL}",
  "jobId": "{JOB_ID}",
  "expiresIn": 300
}
```

2c. GET /tenant/jobs

List scanned documents with pagination and delta sync support.

REQUEST

```
GET /v1/tenant/jobs?tenantId={TENANT_ID}&userId={USER_ID}&limit=50 HTTP/1.1
Host: api.xvio.ai
Authorization: Bearer {MASKED_JWT_TOKEN}
X-App-ID: xvio-scan
```

RESPONSE 200 OK

```
HTTP/1.1 200 OK
Content-Type: application/json

{
  "jobs": [
    {
      "jobId": "{JOB_ID}",
      "tenantId": "{TENANT_ID}",
      "appId": "xvio-scan",
      "userId": "{USER_ID}",
      "type": "scan",
      "status": "completed",
      "progress": 100,
      "serviceId": "{SERVICE_ID}",
      "serviceName": "Business Card Scanner",
      "summaryData": {
        "firstName": "Jane",
        "lastName": "Smith",
        "email": "jane@example.com",
        "phone": "+91 XXXXX XXXXX",
        "Company": "Example Corp",
        "jobTitle": "Director of Engineering"
      },
      "metadata": { "filename": "business-card.jpg", "fileSize": 245678 },
      "createdAt": "2026-03-09T10:00:00.000Z",
      "updatedAt": "2026-03-09T10:00:45.000Z"
    }
  ],
  "total": 1,
  "nextToken": null
}
```

Delta sync: Add `updatedAfter=2026-03-09T09:00:00.000Z` to fetch only changes since last sync.

2d. GET /tenant/jobs/{jobId}

Get full scan details including all extracted data.

REQUEST

```
GET /v1/tenant/jobs/{JOB_ID}?tenantId={TENANT_ID}&userId={USER_ID} HTTP/1.1
Host: api.xvio.ai
Authorization: Bearer {MASKED_JWT_TOKEN}
X-App-ID: xvio-scan
```

RESPONSE 200 OK

```
HTTP/1.1 200 OK
Content-Type: application/json

{
  "jobId": "{JOB_ID}",
  "tenantId": "{TENANT_ID}",
  "appId": "xvio-scan",
  "userId": "{USER_ID}",
  "status": "completed",
  "progress": 100,
  "serviceId": "{SERVICE_ID}",
  "serviceName": "Business Card Scanner",
  "summaryData": {
    "firstName": "Jane", "lastName": "Smith",
    "email": "jane@example.com", "Company": "Example Corp"
  },
  "extractedData": {
    "firstName": "Jane", "lastName": "Smith",
    "email": "jane@example.com", "phone": "+91 XXXXX XXXXX",
    "Company": "Example Corp", "jobTitle": "Director of Engineering",
    "city": "Mumbai", "website": "www.example.com"
  },
  "metadata": { "filename": "business-card.jpg", "fileSize": 245678 },
  "createdAt": "2026-03-09T10:00:00.000Z",
  "updatedAt": "2026-03-09T10:00:45.000Z",
  "completedAt": "2026-03-09T10:00:45.000Z"
}
```

2e. PUT /tenant/jobs/{jobId}

Update extracted field values (manual correction before export).

REQUEST

```
PUT /v1/tenant/jobs/{JOB_ID} HTTP/1.1
Host: api.xvio.ai
Authorization: Bearer {MASKED_JWT_TOKEN}
Content-Type: application/json
X-App-ID: xvio-scan

{
  "tenantId": "{TENANT_ID}",
  "userId": "{USER_ID}",
  "extractedData": {
    "firstName": "Jane", "lastName": "Smith-Johnson",
    "email": "jane.smith@example.com", "Company": "Example Corp Pvt Ltd"
  }
}
```

RESPONSE 200 OK

```
HTTP/1.1 200 OK
Content-Type: application/json

{
  "jobId": "{JOB_ID}",
  "status": "completed",
  "updatedAt": "2026-03-09T10:05:00.000Z"
}
```

2f. DELETE /tenant/jobs/{jobId}

Delete a scan and its associated S3 files.

REQUEST

```
DELETE /v1/tenant/jobs/{JOB_ID}?tenantId={TENANT_ID}&userId={USER_ID} HTTP/1.1
Host: api.xvio.ai
Authorization: Bearer {MASKED_JWT_TOKEN}
X-App-ID: xvio-scan
```

RESPONSE 200 OK

```
HTTP/1.1 200 OK
Content-Type: application/json

{
  "success": true,
  "message": "Job deleted successfully"
}
```

3. Salesforce Export Endpoints

3a. POST /tenant/ai/exporters/salesforce

Export scan data to Salesforce CRM as a Lead, Contact, Case, or custom sObject.

REQUEST

```
POST /v1/tenant/ai/exporters/salesforce HTTP/1.1
Host: api.xvio.ai
Authorization: Bearer {MASKED_JWT_TOKEN}
Content-Type: application/json
X-App-ID: xvio-scan

{
  "tenantId": "{TENANT_ID}",
  "userId": "{USER_ID}",
  "jobId": "{JOB_ID}",
  "createdAt": "2026-03-09T10:00:00.000Z",
  "objectType": "Lead"
}
```

RESPONSE 200 OK

```
HTTP/1.1 200 OK
Content-Type: application/json

{
  "exportId": "{EXPORT_ID}",
  "sfRecordId": "{SF_RECORD_ID}",
  "message": "Exported successfully"
}
```

> Uses admin-configured field mappings. Backend authenticates to Salesforce using stored OAuth tokens (AES-256-GCM encrypted). Auto-refreshes expired tokens.

3b. GET /tenant/ai/exporters/history

View export history for the current user.

REQUEST

```
GET /v1/tenant/ai/exporters/history?tenantId={TENANT_ID}&userId={USER_ID} HTTP/1.1
Host: api.xvio.ai
Authorization: Bearer {MASKED_JWT_TOKEN}
X-App-ID: xvio-scan
```

RESPONSE 200 OK

```
HTTP/1.1 200 OK
Content-Type: application/json

{
  "exports": [
    {
      "exportId": "{EXPORT_ID}",
      "jobId": "{JOB_ID}",
      "destination": "salesforce",
      "objectType": "Lead",
      "sfRecordId": "{SF_RECORD_ID}",
      "status": "success",
      "exportedAt": "2026-03-09T10:10:00.000Z"
    }
  ],
  "total": 1
}
```

4. Supporting Endpoints

4a. GET /tenant/quota

Check remaining scan quota (per-user and per-org levels).

REQUEST

```
GET /v1/tenant/quota?tenantId={TENANT_ID}&userId={USER_ID} HTTP/1.1
Host: api.xvio.ai
Authorization: Bearer {MASKED_JWT_TOKEN}
X-App-ID: xvio-scan
```

RESPONSE 200 OK

```
HTTP/1.1 200 OK
Content-Type: application/json

{
  "month": "2026-03",
  "services": [
    { "id": "{SERVICE_ID}", "name": "Business Card Scanner", "quota": 10, "used":
3, "remaining": 7 },
    { "id": "{SERVICE_ID_2}", "name": "Expense Scanner", "quota": 10, "used": 0,
"remaining": 10 },
    { "id": "{SERVICE_ID_3}", "name": "Invoice Scanner", "quota": 10, "used": 1,
"remaining": 9 }
  ]
}
```

4b. GET /tenant/services

List available scanning services for the tenant.

REQUEST

```
GET /v1/tenant/services?tenantId={TENANT_ID} HTTP/1.1
Host: api.xvio.ai
Authorization: Bearer {MASKED_JWT_TOKEN}
X-App-ID: xvio-scan
```

RESPONSE 200 OK

```
HTTP/1.1 200 OK
Content-Type: application/json

{
  "services": [
    {
      "id": "{SERVICE_ID}", "appId": "xvio-scan",
      "name": "Business Card Scanner",
      "description": "Scan business cards and extract contact information.",
      "order": 1, "icon": "id-card", "color": "#3B82F6",
      "isDefault": true, "contactsEnabled": true, "dedupEnabled": true,
      "allowedFileTypes": ["image", "pdf"], "showQuotaBar": false,
      "quotaConfig": { "userLimit": 10, "userResetPeriod": "lifetime" },
      "summaryFields": ["firstName", "lastName", "email", "phone", "Company", "job
Title", "city"],
      "scanFrame": { "enabled": false, "aspectRatio": "3.5:2" }
    },
    {
      "id": "{SERVICE_ID_2}", "appId": "xvio-scan",
      "name": "Expense Scanner",
      "description": "Scan receipts and extract expense details.",
      "order": 2, "icon": "receipt", "color": "#10B981",
      "isDefault": false, "dedupEnabled": true,
      "allowedFileTypes": ["image", "pdf"],
      "quotaConfig": { "userLimit": 10, "userResetPeriod": "lifetime" },
      "summaryFields": ["merchantName", "amount", "currency", "date", "category"]
    },
    {
      "id": "{SERVICE_ID_3}", "appId": "xvio-scan",
      "name": "Invoice Scanner",
      "description": "Scan invoices and extract billing details.",
      "order": 3, "icon": "file-text", "color": "#8B5CF6",
      "isDefault": false, "dedupEnabled": true,
      "allowedFileTypes": ["image", "pdf"],
      "quotaConfig": { "userLimit": 10, "userResetPeriod": "lifetime" },
      "summaryFields": ["vendorName", "invoiceNumber", "invoiceDate", "totalAmoun
t", "currency"]
    }
  ]
}
```

4c. GET /tenant/campaigns

List Salesforce campaigns for scan attribution (fetched from Salesforce in real-time).

REQUEST

```
GET /v1/tenant/campaigns?tenantId={TENANT_ID} HTTP/1.1
Host: api.xvio.ai
Authorization: Bearer {MASKED_JWT_TOKEN}
X-App-ID: xvio-scan
```

RESPONSE 200 OK

```
HTTP/1.1 200 OK
Content-Type: application/json

{
  "campaigns": [
    {
      "id": "{SF_CAMPAIGN_ID}",
      "name": "Trade Show 2026",
      "status": "Active",
      "type": "Conference"
    }
  ]
}
```

4d. GET /tenant/system/health

Health check endpoint (public, no authentication required).

REQUEST

```
GET /v1/tenant/system/health HTTP/1.1
Host: api.xvio.ai
```

RESPONSE 200 OK

```
HTTP/1.1 200 OK
Content-Type: application/json

{
  "status": "healthy",
  "timestamp": "2026-03-09T10:00:00.000Z"
}
```

---

5. JWT Token Structure

All authenticated endpoints require a Bearer JWT token. The JWT payload contains:

```
{
  "sub": "{USER_SUB}",
  "email": "{USER_EMAIL}",
  "tenantId": "{TENANT_ID}",
  "userId": "{USER_ID}",
  "type": "tenant_user",
  "jti": "{UNIQUE_JWT_ID}",
  "iss": "api.xvio.ai",
  "aud": "xvio-api",
  "iat": 1709971200,
  "exp": 1709972100
}
```

SETTING	VALUE
Algorithm	RS256 (asymmetric)
Default expiry	15 minutes (configurable per tenant: 5 to 1440 minutes)
Signing key	Stored in AWS Secrets Manager, cached in Lambda for 5 minutes

6. CORS and Security Headers

All API responses include the following security headers (via CloudFront Function):

```
Strict-Transport-Security: max-age=63072000; includeSubDomains; preload
X-Content-Type-Options: nosniff
X-Frame-Options: DENY
X-XSS-Protection: 1; mode=block
Referrer-Policy: strict-origin-when-cross-origin
Permissions-Policy: camera=(), microphone=(), geolocation=()
```

CORS headers on authenticated responses:

```
Access-Control-Allow-Origin: https://scan.xvio.ai
Access-Control-Allow-Credentials: true
Access-Control-Allow-Methods: GET, POST, PUT, DELETE, OPTIONS
Access-Control-Allow-Headers: Authorization, Content-Type, X-App-ID, X-API-Key, X-
API-Secret
```

Get in Touch

For questions about these API callouts, integration support, or to request API access for testing, please reach out to our team.

CONTACT SUPPORT

support@xvio.ai

ExonPro Innovations LLP

xVio Scan — Sample API Callouts

March 2026