Product name	Confidentiality level	
E3372h	CONFIDENTIAL	
Product version	Total 6 pages	
V1.0	Total 6 pages	

E3372h Firmware Release Notes V1.0

Prepared by	Tanzhengbin	Date	2015-2-6
Reviewed by	Xujun,zhaogang	Date	2015-2-6
Approved by		Date	



Huawei Technologies Co., Ltd.

All rights reserved

Revision Record

Date	Revision version	FW-WebUI/Stick Version	Change Description	Author
2014-9-30	1.0	FW 21.180.01.00.00	First version	Tanzhengbin
2014-11-10	2.0	FW 21.180.09.00.00	Second version	Tanzhengbin
2014-12-18	3.0	FW 21.200.01.00.00	Third version	Tanzhengbin
2014-12-28	4.0	FW 21.200.03.00.00	Fourth version	Tanzhengbin
2015-1-22	5.0	FW 21.200.05.00.00	Fifth version	Tanzhengbin
2015-2-6	6.0	FW 21.200.07.00.00	Sixth version	Huwuming

Table of Contents

1 M	ain Features	4
	ardware	
	Hardware Specifications	
	rmware	
	Version Description	
3.2	Firmware Specifications	5
3.3	Improvement in the Previous Version	6
	Known Limitations and Issues	



E3372h Firmware Release Notes V1.0

1 Main Features

The E3372h supports the following standards:

- LTE cat4 data service up to 150Mbit/s (Downlink) and 50Mbit/s(Uplink)
- DC-HSPA+ data service up to 43.2 Mbit/s
- HSPA+ data service up to 21.6 Mbit/s
- HSDPA packet data service of up to 14.4 Mbit/s
- HSUPA data service up to 5.76 Mbit/s
- WCDMA PS domain data service of up to 384 Kbit/s
- Equalizer and receive diversity
- microSD Card Slot (Up to 32G)
- Data and SMS Service
- Plug and play
- Standard USB interface
- CSFB

2 Hardware

2.1 Hardware Specifications

Item	Specifications		
Hardware Version	• CL2E3372HM		
Technical standard	LTE 3GPP R9HSPA+/UMTS: 3GPP R99/R5/R6/R7/R8GSM/GPRS/EDGE: 3GPP R99		
	USB: Type A with standard USB 2.0 High speed interface		
	LED: indicating the status of the Data Card		
External interfaces	SD card: standard TF card interface		
	SIM/USIM card: standard 6-pin SIM card interface		
	RF interface: external RF interface		
Maximum power consumption	≤ 3.5 W		
Power supply	5V		
Dimensions (D × W × H)) About 88mm(D) × 28mm(W) × 11.5mm (H)		
Weight	≤ 25 g		



Item	Specifications		
Temperature	Operating: −10℃ to +40℃ Operating: −10℃ to +40℃		
1	Storage: –20°C to +70°C		
Humidity	5% to 95%		
Base Information	Plug and play (PnP)		
	Standard USB 2.0 High Speed interface, auto installation, convenient for use		
Note:			
3GPP = The 3rd Generation Partnership Project			
TS = Technical Specification			
LED = Light-Emitting Diode			
SIM = Subscriber Identity Module			
USIM = UMTS Subscriber	USIM = UMTS Subscriber Identity Module		

3 Firmware

3.1 Version Description

Firmware Version: 21.200.07.00.00

Baseline information Balong V7R11 C30B200

3.2 Firmware Specifications

Firmware		
Item	Specifications	
Version	21.200.07.00.00	
	Platform	Balong V7R11
Information	Baseline	C30B200
	Feature	LTE Supported
	GSM CS domain	Uplink: 9.6/14.4 kbit/sDownlink: 9.6/14.4 kbit/s
	GPRS	Uplink: 85.6 kbit/sDownlink: 85.6 kbit/s
Data service	EDGE	Uplink: 236.8 kbit/sDownlink: 236.8 kbit/s
	UMTS PS domain	Uplink: 384 kbit/sDownlink: 384 kbit/s
	HSDPA	• 14.4Mbit/s
	HSUPA	• 5.76 Mbit/s



Firmware		
Item	Specifications	
	HSPA+	• 21.6Mbit/s
	DC HSPA+	Uplink:5.76 Mbit/sDownlink:43.2Mbit/s
	LTE FDD	Uplink: 50Mbit/sDownlink:150Mbit/s
SMS	SMS over SGs	
Operating System	Windows XP/Windows Vista/WIN 7/MAC/WIN8	

3.3 Improvement in the Previous Version

Index	Case ID	Issue Description

3.4 Known Limitations and Issues

Index	Case ID	Issue Description