Product name	Confidentiality level
E3372h-510	CONFIDENTIAL
Product version	Total 6 pages
V1.0	

E3372h Firmware Release Notes

V1.0

Prepared by	Huwuming	Date	2015-2-6
Reviewed by	Xujun,liuzhenbo	Date	2015-2-6
Approved by		Date	

Huawei Technologies Co., Ltd.

Revision Record

Date	Revision version	FW-WebUI/Stick Version	Change Description	Author
2014-11-10	*1.0*	*FW 21.180.09.00.00*	*First version*	Huwuming
2014-12-18	*1.0*	*FW 21.200.01.00.00*	*Second version*	Huwuming
2014-12-29	*1.0*	*FW 21.200.03.00.00*	*Third version*	Huwuming
2015-1-22	*1.0*	*FW 21.200.05.00.00*	*Fourth version*	Huwuming
2015-2-6	*1.0*	*FW 21.200.07.00.00*	*Fifth version*	Huwuming

Table of Contents

E3372h Firmware Release Notes V1.0

1 Main Features

The E3372h supports the following standards:

- LTE cat4 data service up to 150Mbit/s (Downlink) and 50Mbit/s(Uplink)
- DC-HSPA+ data service up to 43.2 Mbit/s
- HSPA+ data service up to 21.6 Mbit/s
- HSDPA packet data service of up to 14.4 Mbit/s
- HSUPA data service up to 5.76 Mbit/s
- WCDMA PS domain data service of up to 384 Kbit/s
- Equalizer and receive diversity
- microSD Card Slot (Up to 32G)
- Data and SMS Service
- Plug and play
- Standard USB interface
- CSFB

2 Hardware

2.1 Hardware Specifications

Item	Specifications
Hardware Version	• CL2E3372HM
Technical standard	• LTE 3GPP R9 • HSPA+/UMTS: 3GPP R99/R5/R6/R7/R8 • GSM/GPRS/EDGE: 3GPP R99
External interfaces	USB: Type A with standard USB 2.0 High speed interface
	LED: indicating the status of the Data Card
	SD card: standard TF card interface
	SIM/USIM card: standard 6-pin SIM card interface
	RF interface: external RF interface
Maximum power consumption	≤ 3.5 W
Power supply	5V
Dimensions (D × W × H)	About 88mm(D) × 28mm(W) × 11.5mm (H)
Weight	≤ 25 g

Item	Specifications
Temperature	• Operating: –10℃ to +40℃ • Storage: –20℃ to +70℃
Humidity	5% to 95%
Base Information	• Plug and play (PnP)
	• Standard USB 2.0 High Speed interface, auto installation, convenient for use
Note: 3GPP = The 3rd Generation Partnership Project TS = Technical Specification LED = Light-Emitting Diode SIM = Subscriber Identity Module USIM = UMTS Subscriber Identity Module	

3 Firmware

3.1 Version Description

Firmware Version: 21.200.07.00.00

Baseline information   Balong V7R11 C30B200

3.2 Firmware Specifications

Firmware		
Item	**Specifications**	
Version	21.200.07.00.00	
Information	Platform	Balong V7R11
	Baseline	C30B200
	Feature	LTE Supported
Data service	GSM CS domain	• Uplink: 9.6/14.4 kbit/s • Downlink: 9.6/14.4 kbit/s
	GPRS	• Uplink: 85.6 kbit/s • Downlink: 85.6 kbit/s
	EDGE	• Uplink: 236.8 kbit/s • Downlink: 236.8 kbit/s
	UMTS PS domain	• Uplink: 384 kbit/s • Downlink: 384 kbit/s
	HSDPA	• 14.4Mbit/s
	HSUPA	• 5.76 Mbit/s

Firmware		
Item	**Specifications**	
	HSPA+	• 21.6Mbit/s
	DC HSPA+	• Uplink:5.76 Mbit/s • Downlink:43.2Mbit/s
	LTE FDD	• Uplink: 50Mbit/s • Downlink:150Mbit/s
SMS	• SMS over SGs	
Operating System	• Windows XP/Windows Vista/WIN 7/MAC/WIN8	

3.3   Improvement in the Previous Version

Index	Case ID	Issue Description

3.4   Known Limitations and Issues

Index	Case ID	Issue Description