

Task 1: Problem Definition and Approval

- Define a meaningful real-world software quality problem

Embedded computer vision (CV) systems, like those used currently in autonomous robots, drones, and smart cameras, combine resource-strained hardware (microcontrollers, single-board computers) with computationally intensive vision models (such as YOLOv8, or MediaPipe) to make real-time decisions. In lots of development workflows, quality assurance for these systems focuses almost entirely on functional requirements: does the model detect and classify objects accurately? Non-functional requirements such as latency, frame-rate stability, throughput under load, and resource usage (CPU/memory), are frequently treated as inferior concerns, tested improperly or not at all. This is an important gap. A detection that is accurate but arrives too late, or a system that degrades under load, is a genuine failure in a real time context, not just a missed opportunity.

- Explain the background, motivation, stakeholders, users, and practical relevance of the selected problem

- Background

Real time embedded CV is common in robotics, autonomous navigation, robots, and drones, where timing and resource constraints are as critical as detection accuracy. A model that performs well during the benchmark can fail in deployment if it can't keep a consistent frame rate on constrained hardware, or if performance degrades unpredictably as the system load grows. This problem is motivated by direct exposure to this context, where the disconnect between "the model works" and "the system meets its real time requirements" is a recurring, practical concern.

- Stakeholders and Users

Developers/Engineers – Build embedded CV pipelines, who need confidence that functionality doesn't come at the cost of performance in real time

QA/Test engineers – Need a defined, repeatable way to test NFRs alongside FRs

End users – Affected if the system misses detections due to latency or degrades under bigger loads

Safety/compliance reviewers – In contexts where late or missed detections have real consequences

- Practical Relevance

This is a widely common problem across all forms of robotics. Any domain where CV runs on embedded hardware under real time constraints will eventually encounter issues. Addressing it produces a testing approach that is usable well beyond a single interaction.

- Identify the key software quality issues involved in the problem

- Key Software Quality Issues

Absence of clearly defined testable non-functional requirements for real-time CV systems

Lack of methods to measure and validate latency, framerate, and resource usage.

Difficulty differentiating between “the model is accurate” from “the system meets the real time requirements”

Risk of performance degradation under load or resource allocation.

Absence of defect management processes specifically for NFR

- Explain why the problem is suitable for a Software Quality Assurance Project

The problem centres on requirements quality (defining testable NFRs), test strategy design (functional vs non-functional approaches), defect management (tracking NFR violations differently from functional bugs), and quality metrics (latency thresholds, degradation curves) which all are core SQA requirements. It also supports a requirements traceability matrix, since both functional and non-functional requirements can be trace to measurable test cases.

- Confirm that the project is achievable within one semester

The project is a software-simulated prototype rather than physical embedded hardware, removing cost and hardware-access constraints. By using pre-recorded video/image datasets, an already existing lightweight CV mode, and simulated resource constraints, we can achieve the technical build within a few weeks, leaving the rest of the semester for QA artifacts (requirements analysis, test strategy, test cases, traceability matrix, defect management and metrics) which is where the assessment is mostly centred around.

Task 2: Requirements and Quality Analysis

- Initial Functional Requirements

ID	Requirement
FR-01	The system shall load and run a pre-tainted object detection model (e.g., YOLOv8n or MediaPipe) on input video/image data.
FR-02	The system shall detect and classify objects present in each processed frame.
FR-03	The system shall output bounding boxes, class labels, and confidence scores for each detected object.
FR-04	The system shall process video input from a pre-recorded file or image sequence, simulating a live feed.
FR-05	The system shall log each frame's detection results and associated timestamp for later analysis.
FR-06	The system shall allow configuration of a simulated resource constraint (e.g., limited CPU threads, memory cap) before a test run.
FR-07	The system shall generate a summary report of detection accuracy and performance metrics after a test run completes.
FR-08	The system shall allow a user to select between at least two load conditions (e.g., baseline vs high-load) for a given test run

- Initial non-functional requirements

ID	Requirement	Quality attribute
NFR-01	The system should process frames quickly.	Performance
NFR-02	The system should maintain a stable frame rate.	Performance and Reliability
NFR-03	The system should not use too much memory.	Resource Efficiency
NFR-04	The system should keep working under high load.	Reliability
NFR-05	The system should be easy to configure for different test scenarios.	Usability
NFR-06	The system should produce consistent results across repeated runs.	Reliability
NFR-07	The system should be portable across different simulated hardware profiles.	Portability

- Requirement Analysis

Each requirement was assessed against six quality criteria: clarity, completeness, consistency, correctness, feasibility, and testability.

- Clarity

The requirements labelled FR-01 to FR-08 are highly clear and unambiguous because they use strong action verbs such as explicitly stated operational phrases, "shall load". A contrast to these statements, the subsequent NFRs between 01 and 04 are mainly based on Vague qualifiers (example but not all were used) such as "quickly", "too much", "stable" and "keep working". As a result, this type of vague language unwittingly renders these requirements particularly vulnerable to the potentially various subjective interpretations while they also suffer from an absence of any well-articulated numerical parameters or objective performance standards.

- Completeness

While the Functional Requirements defined so far satisfy most of requirements corresponding to critical logic and common flow in detection pipeline, it is still severely limited by its incompleteness especially when it comes to handling errors. There is a complete lack of any formal specification for required system behaviour and expected automated remedies in case some specified frame were to fail an assertion that it can be processed correctly, the core underlying model file would turn out to just not exist at all or else incoming stream of input data could actually be found to have been corrupted.

- Consistency

No requirements were found to be in conflict. But FR-06 (configurable resource constraint) and NFR-03("should not use too much memory") are conceptually overlapping but explicitly not linked.

- Correctness

The requirements accurately reflect the problem that was defined in Task 1(The FR/NFR imbalance in embedded CV). No requirement was found that misinterpreted the intended system behaviour

- Feasibility

The FRs are all within the bounds of what can be verified on a software simulation prototype using recorded datasets (in line with agreed upon boundaries in Task 1). NFR-07 (portability across simulated hardware profiles) is only possible if ""hardware profile" means software-level constraints, like CPU/memory throttling instead of true cross-device deployment.

- Testability

This is the weakest point. This is because none of NFR-01 to NFR-05 have a defined numerical value and cannot be tested with absolute pass/fail. This is an expression of

the fundamental issue identified in Task 1: NFCs exist, but do not appear in a form suitable for QA validation.