```
Administrator: Windows PowerShell                          —    □    ✕

Windows PowerShell
Copyright (C) Microsoft Corporation. All rights reserved.

Try the new cross-platform PowerShell https://aka.ms/pscore6

PS C:\windows\system32> sqlite3 northwind.db
SQLite version 3.40.1 2022-12-28 14:03:47
Enter ".help" for usage hints.
sqlite> .tables
sqlite> .quit
PS C:\windows\system32> cd ..
PS C:\windows> cd ..
PS C:\> cd \Users\Eyad\Desktop\HOMEWORK1
PS C:\Users\Eyad\Desktop\HOMEWORK1> sqlite3 northwind.db
SQLite version 3.40.1 2022-12-28 14:03:47
Enter ".help" for usage hints.
sqlite> .tables
Category              EmployeeTerritory      Region
Customer              Order                  Shipper
CustomerCustomerDemo  OrderDetail            Supplier
CustomerDemographic   Product                Territory
Employee              ProductDetails_V
sqlite> .schema Category
CREATE TABLE IF NOT EXISTS "Category"
(
  "Id" INTEGER PRIMARY KEY,
  "CategoryName" VARCHAR(8000) NULL,
  "Description" VARCHAR(8000) NULL
);
sqlite>
```

```
Administrator: Windows PowerShell                                    —    □    ✕

Windows PowerShell
Copyright (C) Microsoft Corporation. All rights reserved.

Try the new cross-platform PowerShell https://aka.ms/pscore6

PS C:\windows\system32> sqlite3 northwind.db
SQLite version 3.40.1 2022-12-28 14:03:47
Enter ".help" for usage hints.
sqlite> .tables
sqlite> .quit
PS C:\windows\system32> cd ..
PS C:\windows> cd ..
PS C:\> cd \Users\Eyad\Desktop\HOMEWORK1
PS C:\Users\Eyad\Desktop\HOMEWORK1> sqlite3 northwind.db
SQLite version 3.40.1 2022-12-28 14:03:47
Enter ".help" for usage hints.
sqlite> .tables
Category              EmployeeTerritory     Region
Customer              Order                 Shipper
CustomerCustomerDemo  OrderDetail           Supplier
CustomerDemographic   Product               Territory
Employee              ProductDetails_V
sqlite> .schema Category
CREATE TABLE IF NOT EXISTS "Category"
(
  "Id" INTEGER PRIMARY KEY,
  "CategoryName" VARCHAR(8000) NULL,
  "Description" VARCHAR(8000) NULL
);
sqlite> .schema Order
CREATE TABLE IF NOT EXISTS "Order"
(
  "Id" INTEGER PRIMARY KEY,
  "CustomerId" VARCHAR(8000) NULL,
  "EmployeeId" INTEGER NOT NULL,
  "OrderDate" VARCHAR(8000) NULL,
  "RequiredDate" VARCHAR(8000) NULL,
  "ShippedDate" VARCHAR(8000) NULL,
  "ShipVia" INTEGER NULL,
  "Freight" DECIMAL NOT NULL,
  "ShipName" VARCHAR(8000) NULL,
  "ShipAddress" VARCHAR(8000) NULL,
  "ShipCity" VARCHAR(8000) NULL,
  "ShipRegion" VARCHAR(8000) NULL,
  "ShipPostalCode" VARCHAR(8000) NULL,
  "ShipCountry" VARCHAR(8000) NULL
);
sqlite>
```

```
  "ShipCity" VARCHAR(8000) NULL,
  "ShipRegion" VARCHAR(8000) NULL,
  "ShipPostalCode" VARCHAR(8000) NULL,
  "ShipCountry" VARCHAR(8000) NULL
);
sqlite> select count(*) from 'Order';
16818
sqlite>
```