

Web Application Reconnaissance

Command	Description
<code>knockpy -d "zu.edu.eg" --recon --bruteforce --json</code>	Discovers subdomains, ip and certs and saves to json file
<code>cat file.json grep -oP '"domain":\s*\K[~"]+' > subk.txt</code>	Create a txt file with discovered subdomains
<code>subdominator -d target.com -o subd.txt</code>	Discovers subdomains using passive sources and saves to file
<code>subfinder -d target.com > subf.txt</code>	Discovers subdomains using passive sources and saves to file
<code>assetfinder -subs-only target.com > ast.txt</code>	Finds domains and subdomains related to target and saves to file
<code>cat subf.txt ast.txt subk.txt subd.txt sort -u tee subdomains.txt</code>	Combines and deduplicates subdomain lists
<code>cat subdomains.txt httpx tee liveSubdomains.txt</code>	Probes for live subdomains (HTTP servers)
<code>cat liveSubdomains.txt gau tee gau.txt</code>	Fetches historical URLs from AlienVault OTX
<code>cat liveSubdomains.txt waybackurls tee wayback.txt</code>	Extracts URLs from Wayback Machine archives
<code>cat gau.txt wayback.txt sort -u tee urls.txt</code>	Merges and deduplicates all discovered URLs
<code>cat urls.txt fff tee liveUrls.txt</code>	Fetches URLs and saves responses with metadata

