
Make Linting Great Again

with **Sal** lint-staged



What the #\$&% is lint?!

"lint or a linter is any tool that flags suspicious usage in software written in any computer language."

"linter is a tool that finds stupid bugs."

```
. .
                                                           Same and the same of the same
 3 reportBuilder.js > 35 customizeChart.js × 35 calendar-hearmap.js ×
        import (getFractionalDigitsForData) from 1. /utils/FractionalDigitsUtils.js
        calendarModule.service('heatmapService', function()
            function renderCalendarHeetmap(renderToElementId. uiConfig, json) {
                const fractionalDigits = getFractionalDigitsForData(uiConfig.action.data, jsen.kpis)[6]
                if (uiConfig.action.data.monday === false) {
               } else if (uiConfig.action.data.monday) {
                    weekday = uiConfig.action.cata.weekday ? uiConfig.action.data.weekday : :
                if (uiConfig.action.deta.weekdey) {
                    weekday * uiConfig.action.cata.weekday;
                       return getIsoWeek(date, weekday) - 1
                    return weekFormatidatel:
                day = function(date) {
                       return (parseInt(weekdayFormat(date), 18) + 6) % 7
                        yar currentDay = parseInt(weekdayFormat(date), 10);
                        return (currentDay + weekdayMod) % 7
🔯 advertly div. Connection to advertly dev failed // Cinnection refused. Check that the hostname and port are correct and that the postmast _ more Z ministes ago) 10:39 LF4 VTF-84 Git cevelop4 🐌 🔮 👊 30:30
```

These things here :(

```
// first argument is the line number ?
if (typeof arguments[0] = 'number') {
  i++:
 m.line = arguments[0];
for (; i < arguments.length; i++) {</pre>
  a = arguments[i];
  if (a = null) {
   text.push('null');
  } else if (
    typeof a = 'number' || typeof a = 'string' || typeof a = 'date'
  ) {
    text.push(a);
  } else if (a.stack & a.lineNumber) {
    m.error = a;
    m.errmsg = exceptionFormat(a);
  } else if (typeof a = 'array') {
    text.push('[');
    text.push(a.join(','));
    text.push(']');
  } else if (a.nodeType) {
    text.push(node2text(a));
  } else if (typeof a.toJSON = 'function') {
    text.push(a.toJSON());
  } else {
```

typeof a = 'date'

tweed a = 'da



How to fix that?

Lint all the things!













Why lint?

"On average, software developers spend 50% of their time finding and fixing bugs."

- http://www.prweb.com/releases/2013/1/prweb10298185.htm

"...this inefficiency is estimated to cost the global economy \$312 billion per year."


– http://www.prweb.com/releases/2013/1/prweb10298185.htm



In reality, though...

"On average, software developers spend 50% of their time finding and fixing bugs."

"On average, software developers spend 50% of their time discussing code style."





You don't need to uglify your code if it's already ugly!

How to fix that?




npm install -D prettier

Using linters & formatters


- 1. Fewer (stupid) bugs
- 2. Better readability => less time in code reviews
- 3. But it can be tedious 🛞

A typical workflow...





Open a pull request



10 minutes later...



Review required
At least one approved review is required by reviewers with write access. Learn more.

Some checks were not successful
2 failing and 3 successful checks

Continuous-integration/travis-ci/pr — The Travis CI build failed

Required Details

Continuous-integration/travis-ci/push — The Travis CI build failed

Required Details

165:15 error Missing semicolon semi

1 problem (1 error, 0 warnings)





EN .	octocat added some commits 18 hours ago	
-0-	Platform switcher broken out into own component	6052d0c
-6-	using JS- classes so we know what is happening	a537a26
-6-	removing duplicate css	9cd086e
-0-	cleaning up the content	★ 5db9a5f

× 786d930

Content updates

octocat added some commits 18 hours ago

- Platform switcher broken out into own component
 - using JS- classes so we know what is happening
- \mathbb{T} removing duplicate css
- cleaning up the content
- Content updates
- Spacing on tips

6052d0c

a537a26


9cd086e

X 5db9a5f

× 786d930

√ 52a428d














Raise your hand if this sound familiar to you











"I wish I could lint *before* committing the changes to the repository"

Everyone

-Just use git hooks!



git hooks are

- 1. Hard to setup
- 2. Hard to manage
- 3. Hard to share across the team

npm install -D husky

```
{
  "scripts": {
    "precommit": "eslint ."
  }
}
```



1259:9 warning 'analytics' is assigned a value but never used no-unused-vars 1297:22 warning 'message' is defined but never used no-unused-vars 1309:10 warning 'askTweetPopup' is defined but never used no-unused-vars 'analytics' is assigned a value but never used 1327:9 warning no-unused-vars 'message' is defined but never used 1382:22 warning no-unused-vars 1400:10 'askTweetSelectionPopup' is defined but never used warning no-unused-vars 1402:9 'analytics' is assigned a value but never used no-unused-vars warning warning 'askFacebookPopup' is defined but never used no-unused-vars 1460:9 warning 'analytics' is assigned a value but never used no-unused-vars 1504:22 warning 'message' is defined but never used no-unused-vars 1526:10 'askBloggerPopup' is defined but never used no-unused-vars warning 1540:9 'id' is assigned a value but never used no-unused-vars warning 1543:9 warning 'source' is assigned a value but never used no-unused-vars 1546:9 warning 'postfix' is assigned a value but never used no-unused-vars no-unused-vars 1589:10 warning 'askHootsuitePopup' is defined but never used 'askReadabilityPopup' is defined but never used 1638:10 warning no-unused-vars 1681:10 'askLinkedInPopup' is defined but never used warning no-unused-vars 1725:10 warning 'askCustomSharingPopup' is defined but never used no-unused-vars 'postfix' is assigned a value but never used warning no-unused-vars warning 'askPocketPopup' is defined but never used no-unused-vars 1845:10 warning 'askInstapaperPopup' is defined but never used no-unused-vars 1891:10 'askRedefShare' is defined but never used warning no-unused-vars 1938:10 warning 'updateAppUnreadCount' is defined but never used no-unused-vars 1942:10 'CreateElementForExecCommand' is defined but never used no-unused-vars warning 'SelectContent' is defined but never used 1957:10 warning no-unused-vars

≭ 6284 problems (4284 errors, 2000 warnings)

- > husky pre-commit hook failed (add --no-verify to bypass)
- > husky to debug, use 'npm run precommit'

Thanks husky!

- 1. Hard to setup
- 2. Hard to manage
- 3. Hard to share across the team

...but linting the whole project

- 1. Can be quite slow
- 2. Will display irrelevant results

—What if we could run linters only on files we're about to commit?

Meet Oblint-staged!

npm install -D lint-staged

```
{
  "scripts": {
    "precommit": "lint-staged"
  }
}
```

```
{
  "scripts": {
    "precommit": "lint-staged"
  },
  "lint-staged": {
    "*.js": "eslint"
  }
}
```

npx mrm lint-staged

git hooks are

1. Hard to setup

A. Hade Enas O ME

- 3. Hard to share across the team
- 4. Very slow
- 5. Displaying irrelevant results

There is more!

Automatically fix lint errors

```
{
  "lint-staged": {
    "*.js": "eslint"
  }
}
```

```
{
  "lint-staged": {
    "*.js": [
        "eslint --fix",
        "git add"
    ]
}
```

Automatically reformat your code



```
{
  "lint-staged": {
    "*.js": [
        "eslint --fix",
        "git add"
    ]
}
```

```
{
  "lint-staged": {
    "*.js": [
        "prettier --write",
        "git add"
    ]
  }
}
```

```
Projects/OSS/react-dropzone on eslint-config-okonet [?$↑] via ● v6.10.2

→ g st

## eslint-config-okonet...origin/eslint-config-okonet [ahead 2]

?? test.js

Projects/OSS/react-dropzone on eslint-config-okonet [?$↑] via ● v6.10.2

→ ■
```

Use with other languages

```
{
  "lint-staged": {
    "*.js": [
        "prettier --write",
        "git add"
    ]
  }
}
```

```
{
  "lint-staged": {
    "*.{js,json,md,css,scss}": [
     "prettier --write",
     "git add"
  ]
  }
}
```




```
{
  "lint-staged": {
    "*.{js,json,md,css,scss}": [
     "prettier --write",
     "git add"
  ]
  }
}
```

```
{
  "lint-staged": {
    "*.re": [
        "refmt --in-place",
        "git add"
    ]
}
```



- Can run any task
- Easy to install via npm or mrm
- Easy to distribute across the team
- Easy to use!

lint-staged and prettier being used in create-react-app



Int-staged and prettier being used in Babel!



₩ Wow! @babeljs is now using 🛇 🕮 lintstaged to run prettier and @geteslint on precommit hook! github.com/babel/babel/pu ...

```
Instrument : Taise
   + "lint-staged": {
68 + "eslint --format=codeframe --fix",
69 + "git add"
```

Retweets















3:13 PM - 28 Jun 2017

Likes

Lots of people use 🔾 🙇 lint-staged



https://github.com/okonet/lint-staged



npx mrm lint-staged

Please solve real problems!

Thank You!



Andrey Okonetchnikov

@okonetchnikov

http://okonet.ru

https://github.com/okonet