

Quick Reference Handbook

(Imperial Version)

"This handbook contains suggested procedures only for quick reference. These procedures in no way supersede current procedures outlined in the approved Airplane Flight Manual and any revisions thereto. In case of conflict, the Airplane Flight Manual takes precedence."

MODEL CL-600-2B16 (Serial No. 5701 to 6049)	
48,200 lb MTOW	
FIRST ISSUED: Oct 05/06	REVISION 67: Nov 22/22

BOMBARDIER
CHALLENGER 605

CHALLENGER* 605 (MODEL CL-600-2B16)
QUICK REFERENCE HANDBOOK – IMPERIAL VERSION
VOLUME 1

Bombardier Aerospace
P.O. Box 6087, Station Centre-ville
Montreal, Quebec, Canada H3C 3G9

Consult the Terms and Conditions by signing in to the Customer Portal (<https://businessaircraft.bombardier.com/en>) and navigating to LIBRARY -> Technical Publications -> Technical Publication Terms and Condition.

For more information regarding Technical Publications please contact:

Bombardier Customer Services Business Aircraft

Customer Services Hotline (Technical Assistance & In-flight Emergencies)

North America: 1-866-JET-1247 (1-866-538-1247)

International: +1-514-855-2999

Email: ac.yul@aero.bombardier.com

User Comments (Technical Publications)

North America: 1-866-JET-1247 (1-866-538-1247)

International: +1-514-855-2999

Email: bbad.user.comments@aero.bombardier.com

Ordering & Distribution (Technical Publications)

North America: 1-866-JET-1247 (1-866-538-1247)

International: +1-514-855-2999

Facsimile: 514-855-2770

Email: bbad.pubs.dist@aero.bombardier.com

To ease the ordering process, the following Document Identification Number should be used: **CH 605 QRH-I**

QRH CONTENTS

VOLUME 1:

- Record of Revisions
- Record of Temporary Revisions
- Temporary Revisions – Letters of Transmittal
- List of Effective Pages
- Normal Procedures
- Performance Data
- Supplements

BOMBARDIER CHALLENGER 605	<i>TRANSMITTAL-1</i>
	<i>REV 67, Nov 22/22</i>

This is revision **67** to the CL-605 Quick Reference Handbook, PSP 605-15. To bring this manual up to date remove old pages and insert revised pages as detailed below:

	REMOVE	INSERT
Volume 1 Title	Revision 66	Revision 67
Record of Revisions	REC. of REV.-7	REC. of REV.-7
Record of Temporary Revisions	REC. of TR.-2	REC. of TR.-2
List of Effective Pages	A thru B	A thru B
Supplements	SUPP-01-15	SUPP-01-15

TRAINING PURPOSES ONLY

NOTE

Record the date you insert this revision in the Record of Revisions at the front of the manual.

QUICK REFERENCE HANDBOOK PSP 605-15	TRANSMITTAL LETTER
--	---------------------------

TRAINING PURPOSES ONLY

BOMBARDIER CHALLENGER 605	REC. OF REV.-1
	REV 13, Oct 20/09

REV. NO.	DESCRIPTION	INCORPORATED BY	DATE
1 Dec 21/06	Introduces miscellaneous minor changes to the QRH.		
2 Jan 11/07	AFM revision 2, Jan 11/07, has no impact on the QRH.		
3 Mar 19/07	Introduces changes to the QRH to reflect AFM revision 3, Mar 19/07.		
4 Apr 16/07	Introduces changes to the QRH to reflect AFM revision 4, Apr 16/07.		
5 Jun 04/07	Introduces a supplements section to the QRH and introduces changes to the QRH to reflect AFM revision 5, Jun 04/07.		
6 Jun 08/07	Introduces changes to the QRH to reflect AFM revision 6, Jun 08/07.		
7 Oct 31/07	Introduces changes to the QRH to reflect AFM revision 7, Oct 31/07.		
8 Jan 22/08	Introduces minor miscellaneous changes to the QRH and introduces changes to the GO / NO GO Guide.		
9 May 14/08	Introduces a correction to list of systems not available when on emergency power only. Introduces additional information to the QRH regarding fuel burn with the ADG deployed.		
10 Nov 07/08	Introduces changes to the QRH to reflect AFM revision 10, Nov07/08. Introduces revised deicing fluid holdover charts.		
11 Feb 17/09	Introduces changes to the QRH to reflect AFM revision 11, Feb 17/09. Introduces updates to the status messages of the Go / No Go Guide. Relocates windmill relight notes. Introduces a clarification to the bus inop list. Introduces a clarification to the ice detector status message.		
11A May 25/09	Introduces high speed driftdown data.		
12 Jul 17/09	Introduces changes to the QRH to reflect AFM revision 12, Jul 17/09.		
13 Oct 20/09	Introduces changes to the QRH to reflect AFM revision 13, Oct 20/09.		

QUICK REFERENCE HANDBOOK PSP 605-15	RECORD OF REVISIONS
--	----------------------------

BOMBARDIER CHALLENGER 605	REC. OF REV.-2
	REV 19, Jun 30/11

REV. NO.	DESCRIPTION	INCORPORATED BY	DATE
14 Feb 01/10	Introduces changes to the QRH to reflect AFM revision 14, Feb 01/10. Introduces revised deicing fluid holdover charts. Clarifies contaminated runway table for compacted snow. Adds metric values for fuel quantity. Relocates general notes within smoke and AFCS procedures.		
15 Jun 28/10	Introduces changes to the QRH to reflect AFM revision 15, Jun 28/10. Adds supplement for operation in volcanic ash. Revises CPAM FAULT MEL reference. Corrects bus inop reference in smoke/fire/fumes procedure. Adds note to display control panel failure. Revises AILERON MON OK advisory message. Revises FLAP MOTOR OVHT status message.		
16 Sep 09/10	Introduces changes to the QRH to reflect AFM revision 16, Sep 09/10. Incorporates Temporary Revision 605/2. Adds engine failure procedures for during take-off and approach. Expands single engine procedure to include go-around.		
17 Dec 10/10	Introduces changes to the QRH to reflect AFM revision 17, Dec 10/10. Clarifies stabilizer trim setting for take-off. Adds CAUTION during engine start regarding potential fuel spillage. Introduces revised deicing fluid holdover charts. Revises Go/NoGo guide for TAWS status messages. Clarifies 10th stage bleed selection for an APU bleed air relight during a double engine failure. Updates datalink advisory message.		
18 Mar 16/11	Introduces changes to the QRH to reflect AFM revision 18, Mar 16/11. Adds ATS check after engine start. Clarifies anti-ice duct failure.		
19 Jun 30/11	Introduces changes to the QRH to reflect AFM revision 19, Jun 30/11. Index revised to better locate messages starting with L (left) and R (right). Clarifies flap retraction during engine failure after achieving V ₁ .		

QUICK REFERENCE HANDBOOK PSP 605-15	RECORD OF REVISIONS
--	----------------------------

BOMBARDIER CHALLENGER 605		REC. OF REV.-3	
		REV 28, Mar 31/14	
REV. NO.	DESCRIPTION	INCORPORATED BY	DATE
20 Sep 20/11	Introduces changes to the QRH to reflect AFM revision 20, Sep 20/11. Clarification of start and before start checks. Introduces revised deicing fluid holdover charts.		
21 Jan 18/12	Introduces changes to the QRH to reflect AFM revision 21, Jan 18/12. Relocates APU assisted engine start to follow start check. Clarifies hydraulic engine driven pump failure procedure.		
22 Mar 16/12	Introduces changes to the QRH to reflect AFM revision 22, Mar 16/12. Reissue supplements 2 and 3 to correct hyperlinks. Revises note in generator failure procedure.		
23 Jun 26/12	Introduces changes to the QRH to reflect AFM revision 23, Jun 26/12. Revises fuel channel dispatch relief for DOT aircraft in Go/NoGo guide.		
24 Jan 11/13	Introduces changes to the QRH to reflect AFM revision 24, Jan 11/13. Emergency and abnormal contents rearranged in alphabetical order. Clarifies ENGINE overspeed / overtemperature procedure. Updates cold weather operations.		
25 Jul 08/13	Introduces changes to the QRH to reflect AFM revision 25, Jul 08/13. Clarifies low idling instructions. Corrects the indication for manual cabin pressurization. Adds RDC FAIL status message.		
26 Sep 25/13	Introduces changes to the QRH to reflect AFM revision 26, Sep 25/13.		
27 Jan 06/14	Introduces changes to the QRH to reflect AFM revision 27, Jan 06/14. Updates cold weather operations. Introduces supplement for ACN data. Revises nose wheel steering and HGS fail dispatch relief for FAA aircraft in Go/NoGo guide. Links added to Smoke/Fire /Fumes procedure. Clarifies aileron PCU failure.		
28 Mar 31/14	Introduces changes to the QRH to reflect AFM revision 28, Mar 31/14. Clarifies procedures for operation in volcanic ash. Clarifies go-around thrust for an engine failure, on or during approach. Clarifies bus inop list.		

BOMBARDIER CHALLENGER 605	REC. OF REV.-4
	REV 43, Mar 13/17

REV. NO.	DESCRIPTION	INCORPORATED BY	DATE
29 Jul 11/14	Clarifies first and last flight of the day notes. Clarifies ACN data. Clarifies low idling instructions. Adds information to APU BATTERY OFF procedure.		
30 Oct 01/14	Introduces changes to the QRH to reflect AFM revision 30, Oct 01/14. Updates cold weather operations. Clarifies PACK HI PRESS and HI TEMP indications. Adds CVR FAIL status message.		
31 Jan 21/15	Updates cold weather operations.		
32 Mar 18/15	Introduces changes to the QRH to reflect AFM revision 32, Mar 18/15.		
33 Jun 11/15	Introduces changes to the QRH to reflect AFM revision 33, Jun 11/15. Clarifies tail tank transfer manual override. Adds information to stabilizer trim failure. Updates Datalink status and advisory messages.		
34 Sep 03/15	Introduces changes to the QRH to reflect AFM revision 34, Sep 03/15.		
35 Oct 19/15	Introduces changes to the QRH to reflect AFM revision 35, Oct 19/15. Updates cold weather operations.		
36 Nov 27/15	Introduces changes to the QRH to reflect AFM revision 36, Nov 27/15.		
37 Dec 21/15	Revision 37, Dec 21/15, has no impact on the QRH.		
38 Mar 11/16	Introduces changes to the QRH to reflect AFM revision 38, Mar 11/16. Revision of landing corrections. Miscellaneous editorial changes.		
39 Jun 09/16	Introduces changes to the QRH to reflect AFM revision 39, Jun 09/16. Clarifies speed during single engine approach.		
40 Aug 30/16	Introduces changes to the QRH to reflect AFM revision 40, Aug 30/16.		
41 Nov 28/16	Introduces changes to the QRH to reflect AFM revision 41, Nov 28/16. Updates cold weather operations.		
42 Feb 23/17	Introduces changes to the QRH to reflect AFM revision 42, Feb 23/17. Adds MEL relief for MFD X-TALK FAIL Miscellaneous editorial changes. Revises uninhibited caution message list.		
43 Mar 13/17	Introduces changes to the QRH to reflect AFM revision 43, Mar 13/17.		

QUICK REFERENCE HANDBOOK PSP 605-15	RECORD OF REVISIONS
--	----------------------------

BOMBARDIER CHALLENGER 605	REC. OF REV.-5
	REV 55, Mar 18/20

REV. NO.	DESCRIPTION	INCORPORATED BY	DATE
44 Jun 16/17	Introduces changes to the QRH to reflect AFM revision 44, Jun 16/17. Clarifies steep approach supplement. Revises the GO / NO GO Guide MEL relief for tail tank messages. Clarifies 10th stage bleed duct failure.		
45 Dec 04/17	Introduces changes to the QRH to reflect AFM revision 45, Dec 04/17. Corrects hyperlinks.		
46 Mar 01/18	Introduces changes to the QRH to reflect AFM revision 46, Mar 01/18. Updates cold weather operations.		
47 May 29/18	Harmonizes step terminology.		
48 Aug 23/18	Introduces changes to the QRH to reflect AFM revision 48, Aug 23/18.		
49 Nov 19/18	Introduces changes to the QRH to reflect AFM revision 49, Nov 19/18. Updates cold weather operations. Relocates the GO / NO GO Guide to volume 2. Reformats and reissues volume 2 in it's entirety.		
50 Mar 25/19	Clarifies interpolation of performance data. Clarifies PACK selection in procedures. Clarifies thrust reverser selection in procedures. Clarifies 10TH DUCT fail procedure. Incorporates Temporary Revision 605/18.		
51 Apr 05/19	Revises ENG IGN A Circuit Breaker Location. Harmonizes lexicon between QRC and QRH. Adds QRC revision date and revision number on the cover page.		
52 Jun 20/19	Clarifies engine oil pressure low procedure. Corrects HYD 1 LO PRESS procedure. Revises COWL A/ICE procedure. Miscellaneous editorial changes.		
53 Sep 17/19	Updates cold weather operations. Corrects APR INOP procedure.		
54 Dec 18/19	Introduces changes to the QRH to reflect AFM revision 54, Dec 18/19.		
55 Mar 18/20	Incorporates Temporary Revision 605/19.		

QUICK REFERENCE HANDBOOK PSP 605-15	RECORD OF REVISIONS
--	----------------------------

BOMBARDIER CHALLENGER 605	REC. OF REV.-6
	REV 62, Nov 24/21

REV. NO.	DESCRIPTION	INCORPORATED BY	DATE
56 Jun 16/20	Revises GO / NO GO list to separate PAX DOOR LATCH and PAX DOOR OUT HNDL (UC20-01-16) Corrects circuit breaker location reference (UC19-11-20).		
57 Sep 11/20	In Volume 1, introduction of Operational Landing Distance (OLD). Revision to Volume 2 to harmonize the revision number.		
58 Dec 08/20	In Volume 1, incorporates Temporary Revision 605/20 (Cold weather Operations). In Volume 2, introduces changes to the QRH to reflect AFM revision 58, Dec 08/20.		
59 Jun 02/21	In Volume 1, replaces "page" with "pages" in the OLD description. Corrects a Note after the OLD RCC – Pilot–Reported Braking Action–Wheel Braking Correlation Matrix. In Volume 2, introduces changes to the QRH to reflect AFM revision 59, Jun 02/21.		
60 Jul 08/21	In Volume 1, revises Approach and Landing Data. In Volume 2, revises QRC revision date and revision number on the cover page and updates QRC Unreliable Airspeed procedure.		
61 Aug 27/21	In Volume 1, revises ROTR. In Volume 2, incorporates TR 605/21.		
62 Nov 24/21	In Volume 1, update Cold Weather Operations. In Volume 2, added Fuel Schematic, FUEL09-28 to FUEL09-29 (UC19-04-22). In Volume 2, In Display Control Panel (DCP) Failure, changed the objective as per (UC21-09-12). In Volume 2, In ADC Failure, Removed N1 step as per (UC15-12-41).		

QUICK REFERENCE HANDBOOK PSP 605-15	RECORD OF REVISIONS
--	----------------------------

BOMBARDIER CHALLENGER 605	REC. OF REV.-7
	REV 67, Nov 22/22

REV. NO.	DESCRIPTION	INCORPORATED BY	DATE
63 Mar 14/22	In Volume 2, introduces changes to the QRH to reflect AFM revision 63, Mar 14/22. In Volume 2, GO/NOGO GUIDE, Removed the footer that references the revision number of the MMEL of TCCA, FAA and EASA (UC19-08-02). In Volume 2, added TAIL TANK DUMP under fuel system and SOV inop under DC BATT BUS column of page ELEC 04-17 (UC19-07-14). In Volume 2, Caution procedure section, HYD11-1, Added note to return to the checklist after engine shutdown (UC19-09-03). In Volume 2, Caution procedure section, modified multiple steps from ICE12-5 to ICE12-10 (UC19-06-19). In Volume 2, corrected typo in condition statement of page ELEC 04-01 (UC21-01-08).		
64 Jun 02/22	In Volume 1, In PERF-04 SECTOR FUEL DATA, corrected typos "STILL" to "STILL" in the CRUISE MACH NUMBER table as per (UC21-08-25). In Volume 2, Chapter 10 – Gear / Brakes, Warning section – Corrections to steps to add the word lever after LDG GEAR. (UC21-12-04).		
65 Jun 24/22	Pages are issued with revision bars due to changes in the publishing software attributes and corrections to referenced page numbers. These changes correct hyperlink functionality issues (FMCR-CH6XX-Hotlinks check).		
66 Aug 29/22	Revision to Volume 1 to harmonize the revision number. Revision to Volume 2 to harmonize the revision number.		
67 Nov 22/22	Revision to Volume 1 to update ROTR. Revision to Volume 2, Chapter 02 – Avionics, Display Annunciations section issued with revision bars due to changes in the publishing software attributes.		

BOMBARDIER CHALLENGER 605	<i>REC. OF REV.-8</i>
	<i>REV 63, Mar 14/22</i>

THIS PAGE INTENTIONALLY LEFT BLANK

TRAINING PURPOSES ONLY

<i>QUICK REFERENCE HANDBOOK PSP 605-15</i>	<i>RECORD OF REVISIONS</i>
--	-----------------------------------

BOMBARDIER CHALLENGER 605	REC. OF TR.-1
	REV 41, Nov 28/16

T.R. NO.	DESCRIPTION	STATUS	DATE
605/1 Aug 17/09	To advise the flight crew of the introduction of procedures for enhanced vision system (EVS).	Incorporated by REV 14	
605/2 Jun 30/10	To advise the flight crew of an additional check to ensure that the aircraft is on the correct runway.	Incorporated by REV 16	
605/3 Jan 07/11	To advise the flight crew of additional information regarding nose wheel steering failure.	Incorporated by REV 18	
605/4 Oct 26/11	To advise the flight crew of an additional procedure for dual GPS failure during oceanic and remote operations.	Incorporated by REV 22	
605/5 Jun 27/12	To advise the flight crew of the addition of an altimeter cross-check during the take-off check.	Incorporated by REV 24	
605/6 Feb 14/13	To advise the flight crew of an additional procedure for uncommanded yaw motion.	Incorporated by REV 25	
605/7 Mar 25/13	To advise the flight crew of the removal of the requirement for the daily check of the oil chip detector.	Incorporated by REV 25	
605/8 Oct 08/13	To advise the flight crew of the addition of instructions to address nuisance AUTO TAIL XFER caution message when AC power is applied during aircraft power up.	Incorporated by REV 27	
605/9 Jul 07/14	To advise the flight crew of the addition of a procedure for total IRS failure.	Incorporated by REV 30	
605/10 Oct 03/14	To advise the flight crew of additional information regarding cold weather operations.	Incorporated by REV 31	
605/11 Feb 04/16	To advise the flight crew of the introduction of supplemental ground wing anti-icing for airplanes on the Canadian Registry.	Superseded by TR 605/11-1	
605/11-1 Mar 18/16	To advise the flight crew of the introduction of supplemental ground wing anti-icing.	Superseded by TR 605/11-2	
605/11-2 Aug 04/16	To advise the flight crew of the introduction of supplemental ground wing anti-icing.	Incorporated by REV 41	
605/12 Sep 26/16	To advise the flight crew of revised information regarding cold weather operations.	Incorporated by REV 41	

QUICK REFERENCE HANDBOOK PSP 605-15	RECORD OF TEMPORARY REVISIONS
--	--------------------------------------

BOMBARDIER CHALLENGER 605	<i>REC. OF TR.-2</i>
	<i>REV 67, Nov 22/22</i>

T.R. NO.	DESCRIPTION	STATUS	DATE
605/13 Oct 23/17	To advise the flight crew of revised information regarding cold weather operations.	Incorporated by REV 46	
605/14 Jan 29/18	To advise the flight crew of a revision of the procedure for loss of all normal electrical power, to address landing with ADG power only.	Incorporated by REV 46	
605/15 Jan 29/18	To advise the flight crew of a clarification to the tail tank to aux tank automatic transfer failure procedure.	Incorporated by REV 46	
605/16 Sep 04/18	To advise the flight crew of revised information regarding cold weather operations.	Incorporated by REV 49	
605/17 Oct 26/18	To advise the flight crew of the upcoming reformat and reissue of QRH Volume 2.	Removed by REV 49	
605/18 Nov 26/18	To update procedure to reflect Airplane Flight Manual.	Incorporated by REV 50	
605/19 Feb 12/20	To update procedure to reflect Airplane Flight Manual.	Incorporated by REV 55	
605/20 Nov 13/20	To advise the flight crew of revised information regarding cold weather operations.	Incorporated by REV 58	
605/21 Jan 11/21	To update Flaps Fail Caution message to reflect Airplane Flight Manual.	Incorporated by REV 61	
605/22 Oct 25/22	To advise the flight crew of revised information regarding cold weather operations.	Active	

QUICK REFERENCE HANDBOOK PSP 605-15	RECORD OF TEMPORARY REVISIONS
--	--------------------------------------

VOLUME 1

PAGE NO	DATE	PAGE NO	DATE	PAGE NO	DATE
Title.....	Nov 22/22	PERF-01-21.....	Oct 05/06	PERF-05-1.....	Oct 05/06
		PERF-01-22.....	Oct 05/06	PERF-05-2.....	Oct 05/06
REC. of REV.-1	Oct 20/09			PERF-05-3.....	Oct 05/06
REC. of REV.-2	Jun 30/11	PERF-02-1.....	Oct 05/06	PERF-05-4.....	Oct 05/06
REC. of REV.-3	Mar 31/14	PERF-02-2.....	Oct 05/06	PERF-05-5.....	Oct 05/06
REC. of REV.-4	Mar 13/17	PERF-02-3.....	Oct 05/06	PERF-05-6.....	Oct 05/06
REC. of REV.-5	Mar 18/20	PERF-02-4.....	Oct 05/06	PERF-05-7.....	Oct 05/06
REC. of REV.-6	Nov 24/21	PERF-02-5.....	Oct 05/06	PERF-05-8.....	Oct 05/06
REC. of REV.-7	Nov 22/22	PERF-02-6.....	Oct 05/06		
REC. of REV.-8	Mar 14/22	PERF-02-7.....	Oct 05/06	PERF-06-1.....	Mar 11/16
		PERF-02-8.....	Oct 05/06	PERF-06-2.....	Mar 11/16
REC. of TR.-1	Nov 28/16	PERF-02-9.....	Oct 05/06	PERF-06-3.....	Mar 11/16
REC. of TR.-2	Nov 22/22	PERF-02-10.....	Oct 05/06	PERF-06-4.....	Mar 11/16
				PERF-06-5.....	Mar 11/16
A	Nov 22/22	PERF-03-1.....	Oct 05/06	PERF-06-6.....	Mar 11/16
B	Nov 22/22	PERF-03-2.....	Oct 05/06	PERF-06-7.....	Mar 11/16
		PERF-03-3.....	Oct 05/06	PERF-06-8.....	Mar 11/16
NORMALS-1	Nov 28/16	PERF-03-4.....	Oct 05/06	PERF-06-9.....	Mar 11/16
NORMALS-2	Jul 08/13	PERF-03-5.....	Oct 05/06	PERF-06-10.....	Mar 11/16
NORMALS-3	May 29/18	PERF-03-6.....	Oct 05/06	PERF-06-11.....	Oct 05/06
NORMALS-4	May 29/18	PERF-03-7.....	Oct 05/06	PERF-06-12.....	Sep 11/20
NORMALS-5	Nov 28/16	PERF-03-8.....	Oct 05/06	PERF-06-13.....	Jun 02/21
NORMALS-6	Nov 28/16	PERF-03-9.....	Oct 05/06	PERF-06-14.....	Sep 11/20
NORMALS-7	Nov 28/16	PERF-03-10.....	Oct 05/06	PERF-06-15.....	Sep 11/20
NORMALS-8	Nov 28/16	PERF-03-11.....	Oct 05/06	PERF-06-16.....	Sep 11/20
NORMALS-9	May 29/18	PERF-03-12.....	Oct 05/06	PERF-06-17.....	Sep 11/20
NORMALS-10	May 29/18	PERF-03-13.....	Oct 05/06	PERF-06-18.....	Sep 11/20
NORMALS-11	Feb 23/17	PERF-03-14.....	Oct 05/06	PERF-06-19.....	Sep 11/20
NORMALS-12	Jun 16/17	PERF-03-15.....	Oct 05/06	PERF-06-20.....	Jul 08/21
NORMALS-13	Nov 28/16	PERF-03-16.....	Oct 05/06		
NORMALS-14	Jun 16/17	PERF-03-17.....	Oct 05/06	PERF-07-1.....	Oct 05/06
		PERF-03-18.....	Oct 05/06	PERF-07-2.....	Oct 05/06
PERF-00-1.....	Mar 25/19	PERF-03-19.....	Oct 05/06	PERF-07-3.....	Oct 01/14
PERF-00-2.....	Mar 25/19	PERF-03-20.....	Oct 05/06	PERF-07-4.....	Jun 04/07
PERF-00-3.....	Sep 11/20	PERF-03-21.....	Oct 05/06		
PERF-00-4.....	Mar 25/19	PERF-03-22.....	Oct 05/06	PERF-08-1.....	Oct 05/06
		PERF-03-23.....	Oct 05/06	PERF-08-2.....	May 25/09
PERF-01-1.....	Mar 01/18	PERF-03-24.....	Oct 05/06	PERF-08-3.....	May 25/09
PERF-01-2.....	Oct 05/06	PERF-03-25.....	Oct 05/06	PERF-08-4.....	May 25/09
PERF-01-3.....	Oct 05/06	PERF-03-26.....	Oct 05/06	PERF-08-5.....	May 25/09
PERF-01-4.....	Oct 05/06	PERF-03-27.....	Oct 05/06	PERF-08-6.....	May 25/09
PERF-01-5.....	Oct 05/06	PERF-03-28.....	Oct 05/06	PERF-08-7.....	May 25/09
PERF-01-6.....	Oct 05/06	PERF-03-29.....	Oct 05/06	PERF-08-8.....	May 25/09
PERF-01-7.....	Oct 05/06	PERF-03-30.....	Oct 05/06	PERF-08-9.....	May 25/09
PERF-01-8.....	Oct 05/06	PERF-03-31.....	Oct 05/06	PERF-08-10.....	May 25/09
PERF-01-9.....	Oct 05/06	PERF-03-32.....	Oct 05/06	PERF-08-11.....	May 25/09
PERF-01-10.....	Oct 05/06			PERF-08-12.....	May 25/09
PERF-01-11.....	Oct 05/06	PERF-04-1.....	Jun 02/22	PERF-08-13.....	May 25/09
PERF-01-12.....	Oct 05/06	PERF-04-2.....	Jun 02/22	PERF-08-14.....	May 25/09
PERF-01-13.....	Oct 05/06	PERF-04-3.....	Jun 02/22	PERF-08-15.....	May 25/09
PERF-01-14.....	Oct 05/06	PERF-04-4.....	Jun 02/22	PERF-08-16.....	May 25/09
PERF-01-15.....	Oct 05/06	PERF-04-5.....	Jun 02/22	PERF-08-17.....	May 25/09
PERF-01-16.....	Oct 05/06	PERF-04-6.....	Jun 02/22	PERF-08-18.....	May 25/09
PERF-01-17.....	Oct 05/06	PERF-04-7.....	Jun 02/22	PERF-08-19.....	May 25/09
PERF-01-18.....	Oct 05/06	PERF-04-8.....	Jun 02/22	PERF-08-20.....	May 25/09
PERF-01-19.....	Oct 05/06	PERF-04-9.....	Jun 02/22		
PERF-01-20.....	Oct 05/06	PERF-04-10.....	Oct 05/06	SUPP-00-1	Jun 24/22
				SUPP-00-2	Nov 19/18

VOLUME 1

PAGE NO DATE PAGE NO DATE PAGE NO DATE

SUPP-01-1	Jun 04/07	SUPP-02-7	Nov 19/18	SUPP-06-1	Jul 11/14
SUPP-01-2	Jun 04/07	SUPP-02-8	Nov 19/18	SUPP-06-2	Jan 06/14
SUPP-01-3	Jun 04/07	SUPP-02-9	Nov 19/18		
SUPP-01-4	Dec 08/20	SUPP-02-10	Nov 19/18	SUPP-07-1	Nov 19/18
SUPP-01-5	Nov 24/21	SUPP-02-11	Nov 19/18	SUPP-07-2	Nov 19/18
SUPP-01-6	Nov 24/21	SUPP-02-12	Nov 19/18	SUPP-07-3	Nov 19/18
SUPP-01-7	Nov 24/21	SUPP-02-13	Nov 19/18	SUPP-07-4	Nov 19/18
SUPP-01-8	Nov 24/21	SUPP-02-14	Nov 19/18	SUPP-07-5	Nov 19/18
SUPP-01-9	Nov 24/21	SUPP-02-15	Nov 19/18	SUPP-07-6	Nov 19/18
SUPP-01-10	Nov 24/21	SUPP-02-16	Nov 19/18	SUPP-07-7	Nov 19/18
SUPP-01-11	Nov 24/21	SUPP-02-17	Nov 19/18	SUPP-07-8	Nov 19/18
SUPP-01-12	Nov 24/21	SUPP-02-18	Nov 19/18	SUPP-07-9	Nov 19/18
SUPP-01-13	Nov 24/21	SUPP-02-19	Nov 19/18	SUPP-07-10	Nov 19/18
SUPP-01-14	Nov 24/21	SUPP-02-20	Nov 19/18	SUPP-07-11	Nov 19/18
SUPP-01-15	Nov 22/22	SUPP-02-21	Nov 19/18	SUPP-07-12	Nov 19/18
SUPP-01-16	Nov 24/21	SUPP-02-22	Nov 19/18	SUPP-07-13	Nov 19/18
SUPP-01-17	Nov 24/21			SUPP-07-14	Nov 19/18
SUPP-01-18	Nov 24/21	SUPP-03-1	Mar 16/12	SUPP-07-15	Nov 19/18
SUPP-01-19	Nov 24/21	SUPP-03-2	Mar 16/12	SUPP-07-16	Nov 19/18
SUPP-01-20	Nov 24/21			SUPP-07-17	Nov 19/18
		SUPP-04-1	Dec 04/17	SUPP-07-18	Nov 19/18
SUPP-02-1	Nov 19/18	SUPP-04-2	Jun 28/10	SUPP-07-19	Nov 19/18
SUPP-02-2	Jun 16/17			SUPP-07-20	Nov 19/18
SUPP-02-3	Nov 19/18	SUPP-05-1	Jan 06/14	SUPP-07-21	Nov 19/18
SUPP-02-4	Nov 19/18	SUPP-05-2	Jan 06/14	SUPP-07-22	Nov 19/18
SUPP-02-5	Nov 19/18	SUPP-05-3	Jan 06/14		
SUPP-02-6	Nov 19/18	SUPP-05-4	Jan 06/14		

NORMAL PROCEDURES CONTENTS**PAGE**

• Normal Power-Up Check	NORMALS-2
• Systems Check	NORMALS-3
• Before Start Check	NORMALS-5
• Start Check	NORMALS-5
• APU Assisted – Engine Start	NORMALS-6
• Failure to Start	NORMALS-6
• After Engine Start Check	NORMALS-7
• Taxi Check	NORMALS-7
• Stabilizer Trim Setting for Take-Off	NORMALS-8
• Take-Off Check	NORMALS-9
• After Take-Off Check	NORMALS-9
• Climb Check	NORMALS-9
• Cruise Check	NORMALS-9
• Descent Check	NORMALS-10
• In Range Check	NORMALS-10
• Before Landing Check	NORMALS-10
• Go-Around	NORMALS-11
• After Landing Check	NORMALS-11
• Shutdown Check	NORMALS-12
• Securing Check	NORMALS-12
• Battery/External Air – Engine Start	NORMALS-13
• Cross-Bleed – Engine Start	NORMALS-13
• External Air/AC Power – Engine Start	NORMALS-14

GENERAL

- ① Associated procedure or step is only required on the first flight of the day.

The Normal Power-Up Check and the Systems Check must be accomplished in its entirety on the first flight of the day.

On subsequent flights, if the airplane is powered-down (or if the flight crew is replaced), the above checks are accomplished with the exception of those items suffixed with ①.

- ② Associated procedure or step is only required on the last flight of the day.

NORMAL POWER-UP CHECK

- (1) Airplane and Flight Pubs ON BOARD
- (2) Circuit breakers CLOSED
- (3) Emergency equipment CHECK
- (4) Hydraulic pumps OFF
- (5) NOSE STEER OFF
- (6) LDG GEAR lever DN
- (7) FLIGHT SPOILER lever RETRACTED
- (8) FLAPS lever/position CHECK/MATCHED
- (9) ADG manual release STOWED
- (10) BATT MASTER ON
- (11) DC electrical page CHECK 22 VDC MINIMUM
- (12) Firex monitor system test ☐ COMPLETE
- (13) Fire detection systems test ☐ COMPLETE
- (14) NAV lights ON
- (15) APU (if required) START

After APU indications stabilize, select APU GEN to ON.

I If APU and AC external power are not available:

- (15) Battery/External Air – Engine Start COMPLETE
 - Proceed to step (22).
- (16) AC & DC electrics ESTABLISHED
- (17) Lamp test ☐ COMPLETE
- (18) Bleed leak detection test ☐ COMPLETE
- (19) APU LCV OPEN
- (20) 10TH STAGE ISOL OPEN
- (21) PACKs ON
- (22) All FMS POS INIT

SYSTEMS CHECK

- (1) Seat & harnessADJUST
 (2) Rudder pedalsADJUST

When nosewheel area is confirmed clear:

- (3) Hydraulic pump 3A ON
 (4) Nosewheel door CLOSED
 (5) Oxygen system check COMPLETE
 (6) Audio warning GUARDED/OFF
 (7) CVR TEST
 (8) Electrical power panel CHECK
 (9) APU AS REQUIRED
 (10) Hydraulic panel CHECK/AUTO/ON
 (11) Lights AS REQUIRED
 (12) Start/Ignition panel CHECK
 (13) Fuel panel CHECK
 (14) Air-conditioning panel CHECK
 (15) ELT ARM
 (16) Cabin pressurization panel CHECK
 (17) Bleed air panel CHECK
 (18) Anti-ice panel CHECK

On airplanes with Supplemental Ground Wing Anti-Icing:

- (19) Wing anti-ice switch test ☐ COMPLETE
 (20) Ice detector test ☐ COMPLETE
 (21) PASS SIGNS ON
 (22) Emergency lights ☐ CHECK/ARM
 (23) Standby compass CHECK
 (24) Glareshield CHECK
 (25) Air data/Altimeter SET
 (26) Side panels CHECK/SET
 (27) EFIS CHECK
 (28) EICAS CHECK
 (29) ISI CHECK
 (30) GPS clock CHECK/SET
 (31) SUPP GND WING ANTI-ICE
 panel (if installed) CHECK
 (32) Landing gear HORN GUARDED
 (33) ANTI SKID ARMED
 (34) MLG overheat detection system
 check ☐ COMPLETE
 (35) TAWS WARNING, TERRAIN AS REQUIRED
 (36) TAWS WARNING, FLAPS ON

SYSTEMS CHECK (CONT'D)

- (37) TAWS WARNING,
RAAS (if installed) ON
- (38) PITCH and ROLL DISC..... IN/STOWED
- (39) GND SPOILERS AUTO
- (40) Thrust reversers ARMED
- (41) FLIGHT SPOILER lever RETRACTED
- (42) Thrust levers..... SHUT OFF
- (43) FLAPS CHECK
- (44) Engine vibration test ☐ COMPLETE
- (45) ENG SPEED ON
- (46) Aural warning system check ☐ COMPLETE
- (47) Stall protection system check ☐ COMPLETE
- (48) DCP AS REQUIRED
- (49) CCP AS REQUIRED
- (50) Radio/Avionics..... SET/NO MESSAGES
- (51) Flight control trim systems
check ☐ COMPLETE
- (52) Yaw dampers ENGAGE
- (53) CDU and MFD TUNE INHIBIT
switches..... PRESS OUT
- (54) Reversionary selectors..... NORM
- (55) AFCS selector SET
- (56) IRS reversionary selectors..... AS REQUIRED
- (57) FMS 3 selector (if installed)..... AS REQUIRED
- (58) Landing gear manual release..... STOWED
- (59) ADG handle..... STOWED
- (60) ADG AUTO DEPLOY CONTROL LAMP

BEFORE START CHECK

- (1) Gravity crossflow check.....COMPLETE
- (2) Windshield/window heat testCOMPLETE
- (3) Wing overheat detection system
test.....COMPLETE
- (4) Pressurization.....SET
- (5) AltimetersSET
- (6) EFISSET FOR DEPARTURE
- (7) CASCHECK
- (8) Brakes and anti skid system
checkCOMPLETE
- (9) All FMSSET
- (10) FMS messagesCHECK
- (11) Radios/Nav aidsSET FOR DEPARTURE
- (12) Take-off dataSET
- (13) Take-off briefingCOMPLETE

START CHECK

- (1) Passenger doorCHECK CLOSED
- (2) Fuel quantity and balanceCHECK
- (3) BEACON (if installed)ON
- (4) L & R BOOST PUMPS.....ON
- (5) BLEED AIR.....SET FOR START
- (6) IGNITION A (B)ARM
- (7) EnginesSTART

APU ASSISTED – ENGINE START**With APU operating:**

- (1) APU LCV OPEN
(2) L (R) ENG START PRESS

When N₂ reaches 20% RPM and ITT is below 120°C:

- (3) Left or right thrust lever IDLE
(4) Engine instruments MONITOR
(5) Fuel system check valve
operation ☐ VERIFY



When operating with one engine,
select inoperative engine boost pump
to INOP.

If other engine is to be started using APU bleed air:

- (6) Thrust lever of operating engine IDLE
(7) Bleed air pressure CHECK
(8) L (R) ENG START PRESS

When N₂ reaches 20% RPM and ITT is below 120°C:

- (9) Thrust lever of starting engine IDLE
(10) Engine instruments MONITOR
(11) APU EGT CHECK
(12) Idle speed CHECK

FAILURE TO START

- (1) Thrust lever SHUT OFF
(2) IGNITION OFF

If one engine is operating:

- (3) Inoperative engine BOOST PUMP OFF
(4) Dry Motor ACCOMPLISH
until ITT is reduced below 120°C (maximum 90 seconds).

AFTER ENGINE START CHECK

- (1) GEN 1 & GEN 2 ON
- (2) AC and DC electrical pages CHECK
- (3) APU GEN AS REQUIRED
- (4) APU AS REQUIRED
- (5) Ignition DISARM
- (6) PACKs ON
- (7) 14TH stage valve check COMPLETE
- (8) Wing anti-ice check COMPLETE
- (9) Wing anti-ice/isolation valve
check ☐ COMPLETE
- (10) Anti-ice cowl check ☐ COMPLETE
- (11) Supplemental ground wing
anti-ice check (if installed) ☐ COMPLETE
- (12) Wing and cowl anti-ice AS REQUIRED
- (13) ATS CHECK
- (14) Flight controls CHECK
- (15) Ground spoilers check ☐ COMPLETE
- (16) Flight spoilers check ☐ COMPLETE
- (17) NOSE STEER ARMED
- (18) APR check COMPLETE
- (19) ADG AUTO DEPLOY CONTROL UNIT

On airplanes without SB 605-34-019:

- (20) FMS mode SYNC

TAXI CHECK

- (1) Transponder/TCAS AS REQUIRED
- (2) Brakes CHECK
- (3) FLAPS 20°
- (4) Thrust reversers check ☐ COMPLETE
- (5) Aileron and rudder trims NEUTRAL
- (6) Stabilizer trim SET FOR TAKE-OFF
- (7) Flight instruments CHECK & SET
- (8) Fuel balance CHECK
- (9) Wing and cowl anti-ice AS REQUIRED

STABILIZER TRIM SETTING FOR TAKE-OFF

C.G. Range (%MAC)	Trim Setting
16.0 – 16.2	7.2
16.3 – 17.2	7.0
17.3 – 18.3	6.8
18.4 – 19.3	6.6
19.4 – 20.3	6.4
20.4 – 21.3	6.2
21.4 – 22.4	6.0
22.5 – 23.4	5.8
23.5 – 24.4	5.6
24.5 – 25.5	5.4
25.6 – 26.5	5.2
26.6 – 27.5	5.0
27.6 – 28.5	4.8
28.6 – 29.6	4.6
29.7 – 30.6	4.4
30.7 – 31.6	4.2
31.7 – 32.6	4.0
32.7 – 33.7	3.8
33.8 – 34.7	3.6
34.8 – 36.5	3.4
36.6 – 38.0	3.2

NOTE

Trim data from the FMS should be rounded down to the next lowest multiple of 0.2 trim units.

TAKE-OFF CHECK

- (1) Correct runwayCONFIRM
- (2) IgnitionAS REQUIRED
- (3) Wing and cowl anti-iceAS REQUIRED
- (4) L & R WSHLD/WINDHI or LOW
- (5) PROBES ON
- (6) Cabin ADVISE
- (7) Cockpit lightingAS REQUIRED
- (8) External lightsAS REQUIRED
- (9) CASCHECK & CLEAR
- (10) Take-off data
(V₁, V_R, V₂ & distance)CHECK DISPLAYED
- (11) SUPP GND WING ANTI-ICE
panel (if installed)CHECK
- (12) Weather radar ON
- (13) Transponder/TCASSET
- (14) AltimetersCROSS-CHECK

AFTER TAKE-OFF CHECK

- (1) LDG GEAR leverUP
- (2) FLAPS 0°
- (3) Thrust reversers OFF
- (4) CASCHECK & CLEAR
- (5) IgnitionAS REQUIRED
- (6) Wing and cowl anti-iceAS REQUIRED

CLIMB CHECK

- (1) PressurizationCHECK
- (2) PACKs TRANSFER TO ENGINE
BLEED
- (3) Climb thrustSET
- (4) APU GEN OFF/RESET
- (5) APU SHUTDOWN
- (6) TAWS WARNING, TERRAINCHECK ON
- (7) PASS SIGNSAS REQUIRED
- (8) External lightsAS REQUIRED

At transition level:

- (9) AltimetersSET

CRUISE CHECK

- (1) Wing and cowl anti-iceAS REQUIRED
- (2) Cruise thrustSET
- (3) PressurizationCHECK
- (4) FuelMONITOR

DESCENT CHECK

- (1) ATIS COPY
- (2) CAS CHECK & CLEAR
- (3) TAWS WARNING, TERRAIN AS REQUIRED
- (4) Landing data SET
- (5) Approach briefing COMPLETE
- (6) Shoulder harness SECURE
- (7) Pressurization CHECK & SET
- (8) Wing and cowl anti-ice AS REQUIRED
- (9) L & R WSHLD/WIND HI or LOW
- (10) Fuel quantity & balance CHECK

At transition level:

- (11) Altimeters SET/CROSS-CHECK

IN RANGE CHECK

- (1) APU (if required) START
After APU indications stabilize, select APU GEN as required.

If APU is available:

- (2) PACKs TRANSFER TO APU BLEED
- (3) External lights AS REQUIRED
- (4) PASS SIGNS AS REQUIRED

BEFORE LANDING CHECK

- (1) Ignition AS REQUIRED
- (2) Wing and cowl anti-ice AS REQUIRED
- (3) Cabin ADVISE
- (4) PASS SIGNS ON
- (5) LDG GEAR lever DN/INDICATING
- (6) Brake and anti skid system check COMPLETE
- (7) Thrust reversers ARMED
- (8) FLAPS AS REQUIRED
- (9) ATS AS REQUIRED

GO-AROUND

If unreliable airspeed is suspected,
disregard all reference to TOGA.
Do not use TOGA.

- (1) ATS DISC DEPRESS
- (2) Thrust levers/TOGA ADVANCE/PRESS
- (3) FLIGHT SPOILER lever
(if extended) RETRACT
- (4) Airplane ROTATE
- (5) Pitch attitude ADJUST
- (6) FLAPS 20°

When a positive rate of climb is achieved:

- (7) LDG GEAR lever UP

At a safe altitude (not below 400 feet AGL):

- (8) FLAPS 0°
- (9) Thrust reversers OFF

AFTER LANDING CHECK

- (1) FLAPS AS REQUIRED
- (2) FLIGHT SPOILER lever RETRACTED
- (3) Transponder/TCAS AS REQUIRED
- (4) PROBES OFF
- (5) Wing and cowl anti-ice AS REQUIRED
- (6) Windshield/window heat AS REQUIRED
- (7) Ignition OFF
- (8) External lights AS REQUIRED
- (9) Landing lights OFF
- (10) Weather radar STANDBY
- (11) Trims RESET

SHUTDOWN CHECK

- (1) Parking brake AS REQUIRED
- (2) Thrust reversers STOW
- (3) Wing and cowl anti-ice OFF
- (4) L & R WSHLD/WIND OFF
- (5) APU START
After APU indications stabilize, select APU GEN to ON.
- (6) GEN 1 & GEN 2 OFF/RESET
- (7) Engine that started first SHUTDOWN
- (8) L & R BOOST PUMPs PRESS OUT
- (9) Fuel system check valve
operation ☐ COMPLETE
- (10) Other engine SHUTDOWN
- (11) Fuel system crossflow valve
operation ☐ CHECK
- (12) PASS SIGNS OFF
- (13) BEACON (if installed) OFF
- (14) NOSE STEER OFF

On airplanes with SB 605-23-008:

- (15) ATN LOG OFF
- (16) Transponder/TCAS STBY

SECURING CHECK

- (1) Parking brake AS REQUIRED
- (2) Thrust reversers OFF
- (3) External lights OFF
- (4) EMER LTS OFF
- (5) Hydraulic pumps OFF
- (6) APU GEN OFF/RESET
- (7) APU SHUTDOWN
- (8) PACKs OFF
- (9) APU LCV CLOSE
- (10) 10TH STAGE ISOL CLOSE
- (11) BATT MASTER OFF
- (12) MISC LTS OFF

BATTERY/EXTERNAL AIR – ENGINE START

- (1) Normal Power-Up Check.....AS INSTRUCTED
- (2) APU LCV CLOSE
- (3) External airCONNECTED
- (4) External cart 45 PSI MIN
- (5) R BOOST PUMPPRESS IN
- (6) IGNITION B ON
- (7) R ENG START PRESS

When N₂ reaches 20% RPM and ITT is below 120°C:

- (8) Right thrust leverIDLE
- (9) Engine instruments.....MONITOR
- (10) GEN 2..... ON
- (11) AC and DC electrical pagesCHECK
- (12) Lamp test ☐COMPLETE
- (13) Fuel system check valve
operation ☐VERIFY



When operating with one engine,
select inoperative engine boost pump
to INOP.

- (14) External airDISCONNECT
- (15) Bleed leak detection test ☐COMPLETE
- (16) R 10TH STAGE bleed OPEN
- (17) R PACK ON
- (18) Normal Power-Up Check.....COMPLETE

CROSS-BLEED – ENGINE START

- (1) APU LCV CLOSE
- (2) 10TH STAGE bleed of operating
engine OPEN
- (3) Thrust lever of operating engine..... ADVANCE
- (4) Bleed air pressure 60 PSI MIN
- (5) L (R) ENG START PRESS

When N₂ reaches 20% RPM and ITT is below 120°C:

- (6) Thrust lever of starting engineIDLE
- (7) Engine instruments.....MONITOR
- (8) Thrust lever of first engineIDLE
- (9) Idle speedCHECK
- (10) L & R 10TH STAGE bleeds OPEN

EXTERNAL AIR/AC POWER – ENGINE START

- (1) APU LCV CLOSE
- (2) External air CONNECTED
- (3) Bleed air pressure 45 PSI MIN
- (4) L (R) ENG START PRESS

When N₂ reaches 20% RPM and ITT is below 120°C:

- (5) Left or right thrust lever IDLE
- (6) Engine instruments MONITOR
- (7) Fuel system check valve
operation ☐ VERIFY



When operating with one engine,
select inoperative engine boost pump
to INOP.

- (8) Other engine START

NOTE

When starting the other engine using cross-bleed,
accomplish steps (9) to (11) first.

- (9) Applicable GEN ON
- (10) External AC power (if connected) DISCONNECT
- (11) External air DISCONNECT

NOTE

1. The performance data contained herein are derived from the Airplane Flight Manual, PSP 605–1 and the Flight Planning and Cruise Control Manual, PSP 604–23, and are to be used for reference purposes only.
2. It is the responsibility of the user to ascertain that the take-off and landing weights are appropriate, in accordance with AFM performance data, for the existing airport pressure altitude, ambient temperature, runway conditions and climb requirements.
3. The performance values herein are based on 30% MAC centre of gravity (c.g.) position. For every 5% c.g. variation from the 30% reference c.g. position, increase (forward c.g.) or decrease (aft c.g.) the fuel consumption obtained from these tables by approximately 1%.
4. Take-off data are based on zero runway slope and zero wind conditions.
5. Interpolation within tabular data and between tables is permitted and may provide a more accurate estimate of performance. Some values in the tables may be out of the airplane's operating envelope and are to be used only for interpolation.
6. In flight, outside air temperature (OAT) is equivalent to static air temperature (SAT).

CONTENTS

PAGE

PERFORMANCE DATA

Take-off Data

Normal Take-Off – Sea Level.....	PERF-01-2
Normal Take-Off – 500 feet.....	PERF-01-4
Normal Take-Off – 1,000 feet.....	PERF-01-6
Normal Take-Off – 2,000 feet.....	PERF-01-8
Normal Take-Off – 4,000 feet.....	PERF-01-10
Normal Take-Off – 6,000 feet.....	PERF-01-12
Normal Take-Off – 8,000 feet.....	PERF-01-14
Normal Take-Off – 10,000 feet.....	PERF-01-16
Normal Take-Off – 12,000 feet.....	PERF-01-18
Normal Take-Off – 14,000 feet.....	PERF-01-20

CONTENTS

PAGE

Climb Data

Maximum Climb Thrust, % N1	PERF-02-1
• 10th Stage Bleeds Open / Packs On.....	PERF-02-1
• 10th Stage Bleeds Open / Packs On / Cowl Anti-Ice On	PERF-02-1
• 10th Stage Bleeds Open / Packs On / Cowl & Wing Anti-Ice On.....	PERF-02-2
Climb Data	PERF-02-3
• 250 KIAS/0.72 M / Packs On / Anti-Ice Off / 30% C.G.	PERF-02-3
• 250/300 KIAS/0.78 M / Packs On / Anti-Ice Off / 30% C.G.....	PERF-02-7

Cruise Data

Maximum Cruise Thrust, % N1	PERF-03-1
• 10th Stage Bleeds Open / Packs On.....	PERF-03-1
• 10th Stage Bleeds Open / Packs On / Cowl Anti-Ice On	PERF-03-1
• 10th Stage Bleeds Open / Packs On / Cowl & Wing Anti-Ice On.....	PERF-03-2
Cruise Data	PERF-03-3
• Mach 0.72 / Packs On / Anti-Ice Off / 30% C.G.....	PERF-03-3
• Mach 0.74 / Packs On / Anti-Ice Off / 30% C.G.....	PERF-03-7
• Mach 0.77 / Packs On / Anti-Ice Off / 30% C.G.....	PERF-03-11
• Mach 0.80 / Packs On / Anti-Ice Off / 30% C.G.....	PERF-03-15
• Mach 0.82 / Packs On / Anti-Ice Off / 30% C.G.....	PERF-03-19
• Long Range Cruise / Packs On / Anti-Ice Off / 30% C.G.....	PERF-03-23
Cruise Ceiling.....	PERF-03-29
• Mach 0.74 / Packs On / Anti-Ice Off	PERF-03-29
• Mach 0.77 / Packs On / Anti-Ice Off	PERF-03-29
• Mach 0.80 / Packs On / Anti-Ice Off	PERF-03-30
• Mach 0.82 / Packs On / Anti-Ice Off	PERF-03-30
• Long Range Cruise / Packs On / Anti-Ice Off	PERF-03-31

CONTENTS	PAGE
-----------------	-------------

Sector Fuel Data

Sector Fuel Range Data.....	PERF-04-1
• Trip Fuel (lb) – Cruise Altitude 25,000 Feet – ISA	PERF-04-1
• Trip Fuel (lb) – Cruise Altitude 29,000 Feet – ISA	PERF-04-2
• Trip Fuel (lb) – Cruise Altitude 33,000 Feet – ISA	PERF-04-4
• Trip Fuel (lb) – Cruise Altitude 37,000 Feet – ISA	PERF-04-6
• Trip Fuel (lb) – Cruise Altitude 41,000 Feet – ISA	PERF-04-8

Descent Data

Descent Data	PERF-05-1
• 0.72 M/250 KIAS / Packs On / Anti-Ice Off / 30% C.G.	PERF-05-1
• 0.78 M / 300/250 KIAS / Packs On / Anti-Ice Off / 30% C.G.	PERF-05-5

Approach and Landing Data

Landing Speeds and Distances	PERF-06-1
• Altitude – Sea Level	PERF-06-1
• Altitude – 500 Feet	PERF-06-2
• Altitude – 1,000 Feet	PERF-06-3
• Altitude – 2,000 Feet	PERF-06-4
• Altitude – 4,000 Feet	PERF-06-5
• Altitude – 6,000 Feet	PERF-06-6
• Altitude – 8,000 Feet	PERF-06-7
• Altitude – 10,000 Feet	PERF-06-8
• Altitude – 12,000 Feet	PERF-06-9
• Altitude – 14,000 Feet	PERF-06-10
Landing Speed and Distance Corrections.....	PERF-06-11
Go-around Thrust Setting, % N1	PERF-06-11
Operational Landing Distance (OLD)	PERF-06-12

CONTENTS

PAGE

Miscellaneous Data

Reserve Fuel (Lbs) – NBAA/IFR Format.....	PERF-07-1
• Holding Time at Alternate – 0 minutes	PERF-07-1
• Holding Time at Alternate – 15 minutes	PERF-07-1
• Holding Time at Alternate – 30 minutes	PERF-07-1
• Holding Time at Alternate – 45 minutes	PERF-07-1
• Holding Time at Alternate – 60 minutes	PERF-07-2
Wind Component Conversion Table	PERF-07-3

Single Engine Data

Driftdown Speed.....	PERF-08-1
Driftdown – Based on Driftdown Speed	PERF-08-2
• 28,000 lb & 30,000 lb Initial Weight.....	PERF-08-2
• 32,000 lb & 34,000 lb Initial Weight.....	PERF-08-3
• 36,000 lb & 38,000 lb Initial Weight.....	PERF-08-4
• 40,000 lb & 42,000 lb Initial Weight.....	PERF-08-5
• 44,000 lb & 46,000 lb Initial Weight.....	PERF-08-6
• 48,000 lb & 50,000 lb Initial Weight.....	PERF-08-7
High Speed Driftdown – MACH 0.72 / 260 KIAS	PERF-08-8
• 28,000 lb & 30,000 lb Initial Weight.....	PERF-08-8
• 32,000 lb & 34,000 lb Initial Weight.....	PERF-08-9
• 36,000 lb & 38,000 lb Initial Weight.....	PERF-08-10
• 40,000 lb & 42,000 lb Initial Weight.....	PERF-08-11
• 44,000 lb & 46,000 lb Initial Weight.....	PERF-08-12
• 48,000 lb & 50,000 lb Initial Weight.....	PERF-08-13
High Speed Driftdown – MACH 0.72 / 300 KIAS	PERF-08-14
• 28,000 lb & 30,000 lb Initial Weight.....	PERF-08-14
• 32,000 lb & 34,000 lb Initial Weight.....	PERF-08-15
• 36,000 lb & 38,000 lb Initial Weight.....	PERF-08-16
• 40,000 lb & 42,000 lb Initial Weight.....	PERF-08-17
• 44,000 lb & 46,000 lb Initial Weight.....	PERF-08-18
• 48,000 lb & 50,000 lb Initial Weight.....	PERF-08-19

BOMBARDIER CHALLENGER 605	PERF-01-1
	REV 46, Mar 01/18

I TAKE-OFF DATA

I THIS PAGE INTENTIONALLY LEFT BLANK

TRAINING PURPOSES ONLY

NORMAL TAKE-OFF – SEA LEVEL

TAKE-OFF SPEEDS AND TAKE-OFF DISTANCE – APR ON

OAT (°C)		-40	-30	-20	-10	0	10	20	30	40	50
OAT (°F)		-40	-22	-4	14	32	50	68	86	104	122
WEIGHT (1000 LB)	DATA	TAKE-OFF SPEEDS (KIAS) AND DISTANCE (FEET) ZERO BLEED									
30.0 V _{FTO} =145	V ₁	113	113	113	113	113	112	112	112	112	113
	V _R	121	121	121	121	121	121	121	121	121	121
	V ₂	137	137	137	136	136	136	135	135	133	131
	DIST	3220	3220	3220	3220	3280	3340	3410	3470	3740	4100
32.0 V _{FTO} =145	V ₁	113	112	112	112	112	112	112	112	113	114
	V _R	121	121	121	121	121	121	121	121	121	121
	V ₂	136	135	135	135	135	134	134	134	132	130
	DIST	3240	3240	3240	3240	3300	3370	3440	3510	3810	4230
34.0 V _{FTO} =149	V ₁	113	113	113	113	113	113	113	113	114	115
	V _R	121	121	121	121	121	121	121	121	121	121
	V ₂	134	134	134	134	133	133	133	133	131	129
	DIST	3290	3290	3290	3290	3360	3430	3500	3570	3940	4430
36.0 V _{FTO} =154	V ₁	114	114	114	114	114	114	114	114	115	116
	V _R	121	121	121	121	121	121	121	121	121	121
	V ₂	133	133	133	132	132	132	132	132	130	129
	DIST	3380	3380	3380	3380	3470	3560	3650	3740	4180	4760
38.0 V _{FTO} =158	V ₁	116	116	116	116	116	116	116	116	119	121
	V _R	121	121	121	121	122	122	122	122	124	125
	V ₂	132	132	132	132	132	132	132	132	132	132
	DIST	3560	3560	3560	3560	3660	3780	3900	4010	4530	5220
40.0 V _{FTO} =162	V ₁	121	121	121	121	121	121	121	121	121	126
	V _R	126	126	126	126	126	126	127	127	128	130
	V ₂	136	136	136	136	136	136	136	136	136	136
	DIST	3880	3880	3880	3880	4020	4150	4290	4420	5020	5810
42.0 V _{FTO} =166	V ₁	125	125	125	125	125	125	125	125	128	130
	V _R	129	129	129	130	130	130	130	130	132	133
	V ₂	139	139	139	139	139	139	139	139	139	139
	DIST	4200	4200	4200	4200	4350	4500	4650	4800	5470	6370
44.0 V _{FTO} =170	V ₁	129	129	129	129	129	129	129	129	132	134
	V _R	133	133	133	133	133	133	134	134	135	137
	V ₂	142	142	142	142	142	142	142	142	142	142
	DIST	4530	4530	4530	4530	4690	4860	5030	5190	5960	6970
46.0 V _{FTO} =173	V ₁	132	132	132	132	133	133	133	133	136	138
	V _R	136	136	136	136	136	137	137	137	139	140
	V ₂	144	144	144	144	144	144	144	144	144	144
	DIST	4890	4890	4890	4890	5060	5250	5430	5610	6470	7610
47.6 V _{FTO} =176	V ₁	135	135	135	135	135	136	136	136	139	141
	V _R	139	139	139	139	139	139	139	140	141	143
	V ₂	146	146	146	146	146	146	146	146	146	146
	DIST	5210	5210	5210	5210	5400	5600	5800	6000	6940	8180
48.2 V _{FTO} =177	V ₁	136	136	136	136	137	137	137	137	140	143
	V _R	140	140	140	140	140	140	140	141	142	143
	V ₂	147	147	147	147	147	147	147	147	147	147
	DIST	5330	5330	5330	5330	5530	5740	5940	6150	7110	8400

QR1_DXT0_001

BOMBARDIER CHALLENGER 605	PERF-01-3
	<i>Oct 05/06</i>

NORMAL TAKE-OFF – SEA LEVEL

TAKE-OFF SPEEDS AND DISTANCE CORRECTIONS

OAT (°C)		-40	-30	-20	-10	0	10	20	30	40	50
OAT (°F)		-40	-22	-4	14	32	50	68	86	104	122
	DATA	CORRECTION TO V ₁ , V _R AND DISTANCE									
APR OFF	V ₁	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt
	V _R	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt
	DIST	+4 %	+4 %	+4 %	+4 %	+4 %	+4 %	+4 %	+4 %	+4 %	+4 %
PACKS ON	V ₁	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt	+1 Kt	+1 Kt	+1 Kt
	V _R	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt
	DIST	0 %	0 %	0 %	0 %	0 %	0 %	0 %	+2 %	+2 %	+2 %
COWL A/I ON	V ₁	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt				
	V _R	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt				
	DIST	0 %	0 %	0 %	+2 %	+2 %	+2 %				
COWL & WING A/I ON	V ₁	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+2 Kt				
	V _R	0 Kt	0 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt				
	DIST	0 %	0 %	0 %	+3 %	+3 %	+8 %				

TAKE-OFF THRUST SETTING, % N₁

OAT		BLEED LEVEL			
°C	°F	Zero Bleed	Packs On	Cowl A/I On	Cowl & Wing A/I
-40	-40	81.2	81.2	81.2	81.2
-35	-31	82.1	82.1	82.1	82.1
-30	-22	82.9	82.9	82.9	82.9
-25	-13	83.8	83.8	83.8	83.8
-20	-4	84.6	84.6	84.6	84.6
-15	5	85.4	85.4	85.4	85.4
-10	14	86.2	86.2	86.2	86.2
-5	23	87.0	87.0	87.0	87.0
0	32	87.8	87.8	87.8	87.8
5	41	88.6	88.6	88.6	87.8
10	50	89.4	89.4	89.4	87.8
15	59	90.2	90.2		
20	68	91.0	91.0		
25	77	91.7	91.7		
30	86	92.5	92.0		
35	95	91.4	90.9		
40	104	90.6	90.0		
45	113	89.8	89.1		
50	122	88.8	88.2		

NORMAL TAKE-OFF – 500 FEET

TAKE-OFF SPEEDS AND TAKE-OFF DISTANCE – APR ON

OAT (°C)		-40	-30	-20	-10	0	10	20	30	40	49
OAT (°F)		-40	-22	-4	14	32	50	68	86	104	120.2
WEIGHT (1000 LB)	DATA	TAKE-OFF SPEEDS (KIAS) AND DISTANCE (FEET) ZERO BLEED									
30.0 V _{FTO} =145	V ₁	112	112	112	112	112	112	112	111	112	113
	V _R	121	121	121	121	121	121	121	121	121	121
	V ₂	137	136	136	136	136	135	135	135	133	131
	DIST	3280	3280	3280	3280	3350	3410	3480	3560	3830	4170
32.0 V _{FTO} =145	V ₁	112	112	112	112	112	112	112	112	113	114
	V _R	121	121	121	121	121	121	121	121	121	121
	V ₂	135	135	135	134	134	134	134	133	131	130
	DIST	3300	3300	3300	3300	3370	3440	3510	3610	3930	4320
34.0 V _{FTO} =149	V ₁	113	113	113	113	113	113	113	113	114	115
	V _R	121	121	121	121	121	121	121	121	121	121
	V ₂	134	134	133	133	133	133	133	132	130	129
	DIST	3360	3360	3360	3360	3430	3510	3580	3680	4090	4530
36.0 V _{FTO} =154	V ₁	114	114	114	114	114	114	114	114	115	116
	V _R	121	121	121	121	121	121	121	121	121	121
	V ₂	133	133	132	132	132	132	132	131	130	129
	DIST	3470	3470	3470	3470	3560	3650	3750	3870	4340	4880
38.0 V _{FTO} =158	V ₁	117	117	117	117	117	117	117	117	120	122
	V _R	122	122	122	122	122	122	123	123	124	126
	V ₂	132	132	132	132	132	132	132	132	132	132
	DIST	3660	3660	3660	3660	3780	3900	4020	4180	4720	5370
40.0 V _{FTO} =162	V ₁	121	121	121	121	122	122	122	122	125	127
	V _R	126	126	126	127	127	127	127	128	129	130
	V ₂	136	136	136	136	136	136	136	136	136	136
	DIST	4020	4020	4020	4020	4160	4300	4440	4620	5240	5970
42.0 V _{FTO} =166	V ₁	125	125	125	125	126	126	126	126	129	131
	V _R	130	130	130	130	130	131	131	131	133	134
	V ₂	139	139	139	139	139	139	139	139	139	139
	DIST	4350	4350	4350	4350	4500	4660	4820	5020	5720	6550
44.0 V _{FTO} =170	V ₁	129	129	129	129	130	130	130	130	133	135
	V _R	133	133	133	134	134	134	134	135	136	137
	V ₂	142	142	142	142	142	142	142	142	142	142
	DIST	4690	4690	4690	4690	4860	5040	5210	5440	6240	7180
46.0 V _{FTO} =173	V ₁	133	133	133	133	133	133	133	134	137	139
	V _R	137	137	137	137	137	137	137	138	139	140
	V ₂	145	145	145	145	145	145	145	145	145	145
	DIST	5060	5060	5060	5060	5250	5440	5640	5890	6800	7850
47.6 V _{FTO} =176	V ₁	136	136	136	136	136	136	136	137	140	142
	V _R	139	139	139	139	140	140	140	140	142	143
	V ₂	147	147	147	147	147	147	147	147	147	147
	DIST	5400	5400	5400	5400	5610	5820	6020	6300	7290	8440
48.2 V _{FTO} =177	V ₁	137	137	137	137	137	137	137	138	141	143
	V _R	140	140	140	140	141	141	141	141	143	144
	V ₂	148	148	148	148	148	148	148	148	148	148
	DIST	5530	5530	5530	5530	5740	5960	6170	6460	7480	8660

QR1_DXT0_004

BOMBARDIER CHALLENGER 605	PERF-01-5
	<i>Oct 05/06</i>

NORMAL TAKE-OFF – 500 FEET

TAKE-OFF SPEEDS AND DISTANCE CORRECTIONS

OAT (°C)		-40	-30	-20	-10	0	10	20	30	40	49
OAT (°F)		-40	-22	-4	14	32	50	68	86	104	120.2
DATA		CORRECTION TO V ₁ , V _R AND DISTANCE									
APR OFF	V ₁	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt
	V _R	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt
	DIST	+4 %	+4 %	+4 %	+4 %	+4 %	+4 %	+4 %	+4 %	+4 %	+4 %
PACKS ON	V ₁	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt	+1 Kt	+1 Kt	+1 Kt
	V _R	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt
	DIST	0 %	0 %	0 %	0 %	0 %	0 %	0 %	+2 %	+2 %	+2 %
COWL A/I ON	V ₁	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt				
	V _R	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt				
	DIST	0 %	0 %	0 %	+2 %	+2 %	+2 %				
COWL & WING A/I ON	V ₁	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+2 Kt				
	V _R	0 Kt	0 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt				
	DIST	0 %	0 %	0 %	+3 %	+3 %	+9 %				

TAKE-OFF THRUST SETTING, % N₁

OAT		BLEED LEVEL			
°C	°F	Zero Bleed	Packs On	Cowl A/I On	Cowl & Wing A/I
-40	-40	81.5	81.5	81.5	81.5
-35	-31	82.3	82.3	82.3	82.3
-30	-22	83.2	83.2	83.2	83.2
-25	-13	84.0	84.0	84.0	84.0
-20	-4	84.8	84.9	84.9	84.9
-15	5	85.7	85.7	85.7	85.7
-10	14	86.5	86.5	86.5	86.5
-5	23	87.3	87.3	87.3	87.3
0	32	88.1	88.1	88.1	88.0
5	41	88.9	88.9	88.9	88.0
10	50	89.7	89.7	89.7	88.0
15	59	90.5	90.4		
20	68	91.2	91.2		
25	77	92.0	91.9		
30	86	92.5	92.0		
35	95	91.5	91.0		
40	104	90.6	90.0		
45	113	89.8	89.2		
49	120.2	88.9	88.4		

NORMAL TAKE-OFF – 1,000 FEET

TAKE-OFF SPEEDS AND TAKE-OFF DISTANCE – APR ON

OAT (°C)		-40	-30	-20	-10	0	10	20	30	40	48
OAT (°F)		-40	-22	-4	14	32	50	68	86	104	118.4
WEIGHT (1000 LB)	DATA	TAKE-OFF SPEEDS (KIAS) AND DISTANCE (FEET) ZERO BLEED									
30.0 V _{FTO} =145	V ₁	112	111	111	111	111	111	111	111	112	113
	V _R	121	121	121	121	121	121	121	121	121	121
	V ₂	136	136	136	135	135	135	135	134	132	131
	DIST	3340	3340	3340	3340	3410	3480	3550	3650	3930	4240
32.0 V _{FTO} =146	V ₁	112	112	112	112	112	112	112	112	113	114
	V _R	121	121	121	121	121	121	121	121	121	121
	V ₂	135	135	134	134	134	134	133	133	131	130
	DIST	3370	3370	3370	3370	3440	3520	3590	3710	4040	4400
34.0 V _{FTO} =150	V ₁	113	113	113	113	113	113	113	113	114	115
	V _R	121	121	121	121	121	121	121	121	121	121
	V ₂	134	133	133	133	133	132	132	132	130	129
	DIST	3430	3430	3430	3430	3510	3590	3660	3810	4230	4630
36.0 V _{FTO} =154	V ₁	114	114	114	114	114	114	114	115	115	117
	V _R	121	121	121	121	121	121	121	121	121	122
	V ₂	132	132	132	132	132	131	131	131	129	129
	DIST	3560	3560	3560	3560	3650	3750	3850	4020	4510	5010
38.0 V _{FTO} =159	V ₁	117	117	117	117	117	117	117	118	120	122
	V _R	123	123	123	123	123	123	123	124	125	126
	V ₂	133	133	133	133	133	133	133	133	133	133
	DIST	3780	3780	3780	3780	3900	4030	4150	4350	4920	5510
40.0 V _{FTO} =163	V ₁	122	122	122	122	122	122	122	123	125	127
	V _R	127	127	127	127	127	128	128	128	130	131
	V ₂	137	137	137	137	137	137	137	137	137	137
	DIST	4160	4160	4160	4160	4300	4440	4590	4820	5460	6140
42.0 V _{FTO} =166	V ₁	126	126	126	126	126	126	126	127	130	131
	V _R	131	131	131	131	131	131	131	132	133	134
	V ₂	140	140	140	140	140	140	140	140	140	140
	DIST	4500	4500	4500	4500	4660	4820	4990	5250	5980	6740
44.0 V _{FTO} =170	V ₁	130	130	130	130	130	130	130	131	134	136
	V _R	134	134	134	134	134	135	135	135	137	138
	V ₂	142	142	142	142	142	142	142	142	142	142
	DIST	4860	4860	4860	4860	5040	5220	5400	5690	6530	7380
46.0 V _{FTO} =174	V ₁	134	134	134	134	134	134	134	135	137	139
	V _R	137	137	137	138	138	138	138	138	140	141
	V ₂	145	145	145	145	145	145	145	145	145	145
	DIST	5250	5250	5250	5250	5440	5640	5840	6170	7120	8080
47.6 V _{FTO} =177	V ₁	137	137	137	137	137	137	137	138	140	143
	V _R	140	140	140	140	140	140	141	141	142	143
	V ₂	147	147	147	147	147	147	147	147	147	147
	DIST	5600	5600	5600	5600	5820	6030	6250	6610	7640	8690
48.2 V _{FTO} =178	V ₁	138	138	138	138	138	138	138	139	142	144
	V _R	141	141	141	141	141	141	142	142	143	144
	V ₂	148	148	148	148	148	148	148	148	148	148
	DIST	5740	5740	5740	5740	5960	6180	6410	6780	7840	8930

BOMBARDIER CHALLENGER 605	PERF-01-7
	Oct 05/06

NORMAL TAKE-OFF – 1,000 FEET

TAKE-OFF SPEEDS AND DISTANCE CORRECTIONS

OAT (°C)		-40	-30	-20	-10	0	10	20	30	40	48
OAT (°F)		-40	-22	-4	14	32	50	68	86	104	118.4
	DATA	CORRECTION TO V ₁ , V _R AND DISTANCE									
APR OFF	V ₁	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt
	V _R	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt
	DIST	+4 %	+4 %	+4 %	+4 %	+4 %	+4 %	+4 %	+4 %	+4 %	+4 %
PACKS ON	V ₁	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt	+1 Kt	+1 Kt
	V _R	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt
	DIST	0 %	0 %	0 %	0 %	0 %	0 %	0 %	0 %	+2 %	+2 %
COWL A/I ON	V ₁	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt				
	V _R	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt				
	DIST	0 %	0 %	0 %	+2 %	+2 %	+2 %				
COWL & WING A/I ON	V ₁	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+2 Kt				
	V _R	0 Kt	0 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt				
	DIST	0 %	0 %	0 %	+3 %	+4 %	+10 %				

TAKE-OFF THRUST SETTING, % N₁

OAT		BLEED LEVEL			
°C	°F	Zero Bleed	Packs On	Cowl A/I On	Cowl & Wing A/I
-40	-40	81.7	81.7	81.7	81.7
-35	-31	82.6	82.6	82.6	82.6
-30	-22	83.4	83.4	83.4	83.4
-25	-13	84.3	84.3	84.3	84.3
-20	-4	85.1	85.1	85.1	85.1
-15	5	85.9	85.9	85.9	85.9
-10	14	86.7	86.7	86.7	86.7
-5	23	87.6	87.6	87.6	87.6
0	32	88.4	88.4	88.4	88.1
5	41	89.1	89.1	89.1	88.1
10	50	89.9	89.9	89.9	88.1
15	59	90.7	90.7		
20	68	91.5	91.5		
25	77	92.3	92.1		
30	86	92.4	92.0		
35	95	91.5	91.0		
40	104	90.7	90.1		
45	113	89.8	89.2		
48	118.4	89.2	88.6		

NORMAL TAKE-OFF – 2,000 FEET

TAKE-OFF SPEEDS AND TAKE-OFF DISTANCE – APR ON

OAT (°C)		-40	-30	-20	-10	0	10	20	30	40	46
OAT (°F)		-40	-22	-4	14	32	50	68	86	104	114.8
WEIGHT (1000 LB)	DATA	TAKE-OFF SPEEDS (KIAS) AND DISTANCE (FEET) ZERO BLEED									
30.0 V _{FTO} =145	V ₁	112	112	112	112	112	112	112	112	113	113
	V _R	121	121	121	121	121	121	121	121	121	121
	V ₂	135	135	135	135	134	134	134	133	131	130
	DIST	3470	3470	3470	3470	3550	3620	3680	3820	4150	4380
32.0 V _{FTO} =147	V ₁	113	113	113	113	113	113	113	113	114	114
	V _R	121	121	121	121	121	121	121	121	121	121
	V ₂	134	134	134	133	133	133	133	132	130	129
	DIST	3510	3510	3510	3510	3590	3670	3750	3910	4290	4550
34.0 V _{FTO} =151	V ₁	114	114	114	114	114	114	114	114	115	115
	V _R	121	121	121	121	121	121	121	121	121	121
	V ₂	133	133	132	132	132	132	132	131	129	128
	DIST	3580	3580	3580	3580	3660	3750	3860	4070	4500	4830
36.0 V _{FTO} =156	V ₁	115	115	115	115	115	115	115	115	117	118
	V _R	121	121	121	121	121	121	121	121	122	122
	V ₂	132	132	131	131	131	131	131	130	130	130
	DIST	3740	3740	3740	3740	3850	3960	4080	4320	4840	5260
38.0 V _{FTO} =160	V ₁	119	119	119	119	119	119	119	120	122	123
	V _R	124	124	124	124	124	124	124	125	126	127
	V ₂	133	133	133	133	133	133	133	133	133	133
	DIST	4010	4010	4010	4010	4150	4280	4420	4700	5320	5800
40.0 V _{FTO} =164	V ₁	124	124	124	124	124	124	124	125	127	128
	V _R	128	128	128	129	129	129	129	130	131	132
	V ₂	137	137	137	137	137	137	137	137	137	137
	DIST	4430	4430	4430	4430	4580	4740	4890	5210	5920	6470
42.0 V _{FTO} =168	V ₁	128	128	128	128	128	128	128	129	131	133
	V _R	132	132	132	132	132	132	133	133	134	135
	V ₂	140	140	140	140	140	140	140	140	140	140
	DIST	4800	4800	4800	4800	4980	5150	5330	5690	6490	7110
44.0 V _{FTO} =171	V ₁	132	132	132	132	132	132	132	133	135	137
	V _R	135	135	135	135	136	136	136	137	138	139
	V ₂	143	143	143	143	143	143	143	143	143	143
	DIST	5200	5200	5200	5200	5390	5590	5790	6210	7110	7800
46.0 V _{FTO} =175	V ₁	136	136	136	136	136	136	136	137	139	141
	V _R	139	139	139	139	139	139	139	139	140	142
	V ₂	146	146	146	146	146	146	146	146	146	146
	DIST	5620	5620	5620	5620	5830	6050	6280	6750	7770	8560
47.6 V _{FTO} =178	V ₁	139	139	139	139	139	139	139	140	142	144
	V _R	141	141	141	141	142	142	142	142	144	144
	V ₂	148	148	148	148	148	148	148	148	148	148
	DIST	6010	6010	6010	6010	6240	6480	6730	7240	8350	9210
48.2 V _{FTO} =179	V ₁	140	140	140	140	140	140	140	141	143	145
	V _R	142	142	142	142	142	143	143	143	145	145
	V ₂	149	149	149	149	149	149	149	149	149	149
	DIST	6160	6160	6160	6160	6400	6650	6900	7430	8570	9460

QR1_DXT0_010

BOMBARDIER CHALLENGER 605	PERF-01-9
	Oct 05/06

NORMAL TAKE-OFF – 2,000 FEET

TAKE-OFF SPEEDS AND DISTANCE CORRECTIONS

OAT (°C)		-40	-30	-20	-10	0	10	20	30	40	46
OAT (°F)		-40	-22	-4	14	32	50	68	86	104	114.8
	DATA	CORRECTION TO V ₁ , V _R AND DISTANCE									
APR OFF	V ₁	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt
	V _R	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt
	DIST	+4 %	+4 %	+4 %	+4 %	+4 %	+4 %	+4 %	+4 %	+4 %	+4 %
PACKS ON	V ₁	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt	+1 Kt	+1 Kt	+1 Kt
	V _R	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt
	DIST	0 %	0 %	0 %	0 %	0 %	0 %	0 %	+2 %	+2 %	+3 %
COWL A/I ON	V ₁	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt				
	V _R	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt				
	DIST	0 %	0 %	0 %	+2 %	+2 %	+2 %				
COWL & WING A/I ON	V ₁	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+3 Kt				
	V _R	0 Kt	0 Kt	0 Kt	0 Kt	+1 Kt	+1 Kt				
	DIST	0 %	0 %	0 %	+3 %	+5 %	+11 %				

TAKE-OFF THRUST SETTING, % N₁

OAT		BLEED LEVEL			
°C	°F	Zero Bleed	Packs On	Cowl A/I On	Cowl & Wing A/I
-40	-40	82.2	82.2	82.2	82.2
-35	-31	83.1	83.1	83.1	83.1
-30	-22	83.9	83.9	83.9	83.9
-25	-13	84.8	84.8	84.8	84.8
-20	-4	85.6	85.6	85.6	85.6
-15	5	86.4	86.4	86.4	86.4
-10	14	87.3	87.3	87.3	87.3
-5	23	88.1	88.1	88.1	88.1
0	32	88.9	88.9	88.9	88.3
5	41	89.7	89.7	89.7	88.3
10	50	90.4	90.4	90.4	88.3
15	59	91.2	91.2		
20	68	92.0	92.0		
25	77	92.8	92.5		
30	86	92.4	91.9		
35	95	91.6	91.0		
40	104	90.7	90.2		
45	113	89.9	89.3		
46	114.8	89.7	89.0		

NORMAL TAKE-OFF – 4,000 FEET

TAKE-OFF SPEEDS AND TAKE-OFF DISTANCE – APR ON

OAT (°C)		-40	-30	-20	-10	0	10	20	30	40	42
OAT (°F)		-40	-22	-4	14	32	50	68	86	104	107.6
WEIGHT (1000 LB)	DATA	TAKE-OFF SPEEDS (KIAS) AND DISTANCE (FEET) ZERO BLEED									
30.0 V _{FTO} =145	V ₁	113	113	113	113	113	113	113	113	114	114
	V _R	121	121	121	121	121	121	121	121	121	121
	V ₂	134	134	134	133	133	133	133	131	130	129
	DIST	3780	3780	3780	3780	3870	3940	4030	4270	4670	4760
32.0 V _{FTO} =149	V ₁	114	114	114	114	114	114	114	114	115	115
	V _R	121	121	121	121	121	121	121	121	121	121
	V ₂	133	133	132	132	132	132	131	130	129	129
	DIST	3870	3870	3870	3870	3970	4050	4150	4430	4880	4990
34.0 V _{FTO} =154	V ₁	115	115	115	115	115	115	115	115	116	116
	V _R	121	121	121	121	121	121	121	121	121	121
	V ₂	132	131	131	131	131	131	130	129	128	128
	DIST	4010	4010	4010	4010	4140	4240	4340	4660	5230	5370
36.0 V _{FTO} =158	V ₁	117	117	117	117	117	117	117	118	121	121
	V _R	122	122	122	122	122	123	123	124	125	125
	V ₂	132	132	132	132	132	132	132	132	132	132
	DIST	4250	4250	4250	4250	4400	4520	4650	5050	5770	5940
38.0 V _{FTO} =162	V ₁	122	122	122	122	122	122	122	124	126	127
	V _R	127	127	127	127	127	127	127	128	129	130
	V ₂	135	135	135	135	135	135	135	135	135	135
	DIST	4620	4620	4620	4620	4790	4930	5090	5570	6400	6610
40.0 V _{FTO} =166	V ₁	127	127	127	127	127	127	127	129	131	132
	V _R	131	131	131	131	132	132	132	133	134	134
	V ₂	139	139	139	139	139	139	139	139	139	139
	DIST	5120	5120	5120	5120	5320	5480	5660	6200	7160	7400
42.0 V _{FTO} =170	V ₁	131	131	131	131	131	131	131	133	135	136
	V _R	135	135	135	135	135	135	135	136	137	138
	V ₂	142	142	142	142	142	142	142	142	142	142
	DIST	5590	5590	5590	5590	5810	5990	6200	6810	7880	8150
44.0 V _{FTO} =174	V ₁	135	135	135	135	135	135	135	137	139	140
	V _R	138	138	138	138	139	139	139	140	141	141
	V ₂	145	145	145	145	145	145	145	145	145	145
	DIST	6090	6090	6090	6090	6350	6550	6780	7460	8670	8980
46.0 V _{FTO} =178	V ₁	139	139	139	139	139	139	139	141	143	144
	V _R	142	142	142	142	142	142	142	142	143	144
	V ₂	148	148	148	148	148	148	148	148	148	148
	DIST	6620	6620	6620	6620	6910	7140	7400	8180	9560	9920
47.6 V _{FTO} =181	V ₁	142	142	142	142	142	142	142	144	147	147
	V _R	144	144	144	144	144	145	145	146	147	147
	V ₂	150	150	150	150	150	150	150	150	150	150
	DIST	7100	7100	7100	7100	7420	7670	7950	8790	10310	10700
48.2 V _{FTO} =182	V ₁	143	143	143	143	143	143	143	145	148	-
	V _R	145	145	145	145	145	146	146	147	148	-
	V ₂	151	151	151	151	151	151	151	151	151	-
	DIST	7280	7280	7280	7280	7610	7870	8150	9030	10600	-

QR1_DXT0_013

BOMBARDIER CHALLENGER 605	PERF-01-11
	<i>Oct 05/06</i>

NORMAL TAKE-OFF – 4,000 FEET

TAKE-OFF SPEEDS AND DISTANCE CORRECTIONS

OAT (°C)		-40	-30	-20	-10	0	10	20	30	40	42
OAT (°F)		-40	-22	-4	14	32	50	68	86	104	107.6
	DATA	CORRECTION TO V ₁ , V _R AND DISTANCE									
APR OFF	V ₁	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt
	V _R	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt
	DIST	+4 %	+4 %	+4 %	+4 %	+4 %	+4 %	+4 %	+4 %	+4 %	+4 %
PACKS ON	V ₁	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt	+1 Kt	+1 Kt	+1 Kt
	V _R	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt
	DIST	0 %	0 %	0 %	0 %	0 %	0 %	+1 %	+2 %	+3 %	+3 %
COWL A/I ON	V ₁	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt				
	V _R	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt				
	DIST	0 %	0 %	0 %	+2 %	+2 %	+2 %				
COWL & WING A/I ON	V ₁	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+2 Kt	+3 Kt				
	V _R	0 Kt	0 Kt	0 Kt	0 Kt	+1 Kt	+1 Kt				
	DIST	0 %	0 %	0 %	+3 %	+7 %	+13 %				

TAKE-OFF THRUST SETTING, % N₁

OAT		BLEED LEVEL			
°C	°F	Zero Bleed	Packs On	Cowl A/I On	Cowl & Wing A/I
-40	-40	83.1	83.1	83.1	83.1
-35	-31	84.0	84.0	84.0	84.0
-30	-22	84.8	84.8	84.8	84.8
-25	-13	85.7	85.7	85.7	85.7
-20	-4	86.5	86.5	86.5	86.5
-15	5	87.4	87.4	87.4	87.4
-10	14	88.2	88.2	88.2	88.2
-5	23	89.0	89.0	89.0	88.6
0	32	89.8	89.8	89.8	88.6
5	41	90.7	90.7	90.7	88.6
10	50	91.4	91.4	91.4	88.6
15	59	92.2	92.2		
20	68	93.1	92.8		
25	77	93.0	92.5		
30	86	92.4	91.9		
35	95	91.5	91.0		
40	104	90.7	90.1		
42	107.6	90.4	89.8		

NORMAL TAKE-OFF – 6,000 FEET

TAKE-OFF SPEEDS AND TAKE-OFF DISTANCE – APR ON

OAT (°C)		-40	-30	-20	-10	0	10	20	30	38
OAT (°F)		-40	-22	-4	14	32	50	68	86	100.4
WEIGHT (1000 LB)	DATA	TAKE-OFF SPEEDS (KIAS) AND DISTANCE (FEET) ZERO BLEED								
30.0 V _{FTO} =147	V ₁	114	114	114	114	114	114	114	114	115
	V _R	121	121	121	121	121	121	121	121	121
	V ₂	132	132	132	132	132	131	131	130	129
	DIST	4160	4160	4160	4160	4260	4340	4460	4800	5200
32.0 V _{FTO} =152	V ₁	115	115	115	115	115	115	115	115	116
	V _R	121	121	121	121	121	121	121	121	121
	V ₂	131	131	131	131	131	130	130	129	128
	DIST	4300	4300	4300	4300	4420	4510	4650	5030	5500
34.0 V _{FTO} =156	V ₁	115	115	115	115	115	115	116	117	120
	V _R	121	121	121	121	121	121	121	122	123
	V ₂	130	130	130	130	130	130	130	130	130
	DIST	4510	4510	4510	4510	4650	4770	4950	5410	6020
36.0 V _{FTO} =161	V ₁	120	120	120	120	120	120	120	122	125
	V _R	125	125	125	125	125	126	126	127	128
	V ₂	134	134	134	134	134	134	134	134	134
	DIST	4860	4860	4860	4860	5040	5190	5420	6000	6740
38.0 V _{FTO} =165	V ₁	125	125	125	125	125	125	126	127	130
	V _R	130	130	130	130	130	130	130	131	132
	V ₂	137	137	137	137	137	137	137	137	137
	DIST	5350	5350	5350	5350	5550	5720	5970	6690	7580
40.0 V _{FTO} =169	V ₁	130	130	130	130	130	130	131	133	135
	V _R	134	134	134	134	135	135	135	136	137
	V ₂	141	141	141	141	141	141	141	141	141
	DIST	5950	5950	5950	5950	6180	6370	6670	7480	8510
42.0 V _{FTO} =173	V ₁	135	135	135	135	135	135	135	137	140
	V _R	138	138	138	138	138	138	139	140	140
	V ₂	144	144	144	144	144	144	144	144	144
	DIST	6530	6530	6530	6530	6790	7000	7330	8250	9410
44.0 V _{FTO} =177	V ₁	139	139	139	139	139	139	139	141	144
	V _R	141	141	141	141	142	142	142	143	144
	V ₂	147	147	147	147	147	147	147	147	147
	DIST	7150	7150	7150	7150	7440	7680	8050	9090	10400
46.0 V _{FTO} =181	V ₁	143	143	143	143	143	143	143	145	147
	V _R	145	145	145	145	145	145	145	146	147
	V ₂	150	150	150	150	150	150	150	150	150
	DIST	7810	7810	7810	7810	8150	8420	8850	10050	11590
47.6 V _{FTO} =184	V ₁	146	146	146	146	146	146	146	148	-
	V _R	147	147	147	147	147	148	148	149	-
	V ₂	152	152	152	152	152	152	152	152	-
	DIST	8400	8400	8400	8400	8770	9060	9530	10840	-
48.2 V _{FTO} =185	V ₁	147	147	147	147	147	147	147	-	-
	V _R	148	148	148	148	148	148	149	-	-
	V ₂	153	153	153	153	153	153	153	-	-
	DIST	8620	8620	8620	8620	9000	9310	9780	-	-

QR1_DXTO_016

BOMBARDIER CHALLENGER 605	PERF-01-13
	Oct 05/06

NORMAL TAKE-OFF – 6,000 FEET

TAKE-OFF SPEEDS AND DISTANCE CORRECTIONS

OAT (°C)		-40	-30	-20	-10	0	10	20	30	38
OAT (°F)		-40	-22	-4	14	32	50	68	86	100.4
	DATA	CORRECTION TO V ₁ , V _R AND DISTANCE								
APR OFF	V ₁	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt
	V _R	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt
	DIST	+4 %	+4 %	+4 %	+4 %	+4 %	+4 %	+4 %	+4 %	+4 %
PACKS ON	V ₁	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt	+1 Kt	+1 Kt
	V _R	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt
	DIST	0 %	0 %	0 %	0 %	0 %	0 %	+2 %	+3 %	+3 %
COWL A/I ON	V ₁	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt			
	V _R	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt			
	DIST	0 %	0 %	0 %	+2 %	+2 %	+2 %			
COWL & WING A/I ON	V ₁	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+2 Kt	+4 Kt			
	V _R	0 Kt	0 Kt	0 Kt	+1 Kt	+1 Kt	+1 Kt			
	DIST	0 %	0 %	0 %	+4 %	+9 %	+17 %			

TAKE-OFF THRUST SETTING, % N₁

OAT		BLEED LEVEL			
°C	°F	Zero Bleed	Packs On	Cowl A/I On	Cowl & Wing A/I
-40	-40	84.0	84.0	84.0	84.0
-35	-31	84.9	84.9	84.9	84.9
-30	-22	85.8	85.8	85.8	85.8
-25	-13	86.7	86.7	86.7	86.7
-20	-4	87.5	87.5	87.5	87.5
-15	5	88.4	88.4	88.4	88.4
-10	14	89.2	89.2	89.2	88.9
-5	23	90.0	90.0	90.0	88.9
0	32	90.9	90.9	90.9	88.9
5	41	91.7	91.7	91.7	88.9
10	50	92.5	92.5	92.5	88.9
15	59	93.3	93.3		
20	68	93.7	93.1		
25	77	93.0	92.5		
30	86	92.3	91.8		
35	95	91.5	91.0		
38	100.4	91.1	90.5		

NORMAL TAKE-OFF – 8,000 FEET

TAKE-OFF SPEEDS AND TAKE-OFF DISTANCE – APR ON

OAT (°C)		-40	-30	-20	-10	0	10	20	30	34
OAT (°F)		-40	-22	-4	14	32	50	68	86	93.2
WEIGHT (1000 LB)	DATA	TAKE-OFF SPEEDS (KIAS) AND DISTANCE (FEET) ZERO BLEED								
30.0 V _{FTO} =149	V ₁	114	114	114	114	114	114	115	115	115
	V _R	121	121	121	121	121	121	121	121	121
	V ₂	131	131	131	131	130	130	130	128	128
	DIST	4580	4580	4580	4580	4680	4780	5030	5500	5730
32.0 V _{FTO} =154	V ₁	115	115	115	115	115	115	116	117	118
	V _R	121	121	121	121	121	121	121	121	121
	V ₂	130	130	130	130	129	129	129	128	128
	DIST	4780	4780	4780	4780	4900	5010	5290	5850	6110
34.0 V _{FTO} =159	V ₁	118	118	118	118	118	118	120	122	123
	V _R	124	124	124	124	124	124	125	125	126
	V ₂	132	132	132	132	132	132	132	132	132
	DIST	5110	5110	5110	5110	5260	5390	5720	6510	6870
36.0 V _{FTO} =163	V ₁	123	123	123	123	123	123	125	127	128
	V _R	128	128	128	128	128	129	129	130	130
	V ₂	136	136	136	136	136	136	136	136	136
	DIST	5620	5620	5620	5620	5800	5970	6400	7310	7740
38.0 V _{FTO} =167	V ₁	128	128	128	128	128	129	130	132	133
	V _R	133	133	133	133	133	133	134	134	135
	V ₂	139	139	139	139	139	139	139	139	139
	DIST	6220	6220	6220	6220	6430	6650	7180	8230	8720
40.0 V _{FTO} =172	V ₁	134	134	134	134	134	134	135	138	139
	V _R	137	137	137	137	138	138	138	139	139
	V ₂	143	143	143	143	143	143	143	143	143
	DIST	6950	6950	6950	6950	7200	7440	8050	9270	9840
42.0 V _{FTO} =176	V ₁	138	138	138	138	138	138	139	142	143
	V _R	141	141	141	141	141	141	142	143	143
	V ₂	146	146	146	146	146	146	146	146	146
	DIST	7650	7650	7650	7650	7930	8200	8890	10270	10910
44.0 V _{FTO} =180	V ₁	142	142	142	142	142	142	144	146	146
	V _R	144	144	144	144	145	145	145	146	146
	V ₂	149	149	149	149	149	149	149	149	149
	DIST	8410	8410	8410	8410	8720	9040	9820	11380	12110
46.0 V _{FTO} =184	V ₁	146	146	146	146	146	146	148	-	-
	V _R	148	148	148	148	148	148	148	-	-
	V ₂	152	152	152	152	152	152	152	-	-
	DIST	9260	9260	9260	9260	9620	9990	10900	-	-
47.6 V _{FTO} =188	V ₁	150	150	150	150	150	150	-	-	-
	V _R	150	150	150	150	150	150	-	-	-
	V ₂	154	154	154	154	154	154	-	-	-
	DIST	9980	9980	9980	9980	10380	10780	-	-	-
48.2 V _{FTO} =189	V ₁	151	151	151	151	-	-	-	-	-
	V _R	151	151	151	151	-	-	-	-	-
	V ₂	155	155	155	155	-	-	-	-	-
	DIST	10250	10250	10250	10250	-	-	-	-	-

QR1_DXTO_019

BOMBARDIER CHALLENGER 605	PERF-01-15
	Oct 05/06

NORMAL TAKE-OFF – 8,000 FEET

TAKE-OFF SPEEDS AND DISTANCE CORRECTIONS

OAT (°C)		-40	-30	-20	-10	0	10	20	30	34
OAT (°F)		-40	-22	-4	14	32	50	68	86	93.2
	DATA	CORRECTION TO V ₁ , V _R AND DISTANCE								
APR OFF	V ₁	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt
	V _R	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt
	DIST	+4 %	+4 %	+4 %	+4 %	+4 %	+4 %	+4 %	+4 %	+4 %
PACKS ON	V ₁	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt	+1 Kt	+1 Kt	+1 Kt
	V _R	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt
	DIST	0 %	0 %	0 %	0 %	0 %	0 %	+3 %	+3 %	+3 %
COWL A/I ON	V ₁	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt	+1 Kt			
	V _R	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt			
	DIST	0 %	0 %	0 %	+2 %	+2 %	+3 %			
COWL & WING A/I ON	V ₁	+1 Kt	+1 Kt	+1 Kt	+2 Kt	+3 Kt	+4 Kt			
	V _R	0 Kt	0 Kt	0 Kt	+1 Kt	+1 Kt	+2 Kt			
	DIST	0 %	0 %	0 %	+7 %	+14 %	+22 %			

TAKE-OFF THRUST SETTING, % N₁

OAT		BLEED LEVEL			
°C	°F	Zero Bleed	Packs On	Cowl A/I On	Cowl & Wing A/I
-40	-40	85.1	85.1	85.1	85.1
-35	-31	86.0	85.9	85.9	85.9
-30	-22	86.8	86.8	86.8	86.8
-25	-13	87.7	87.7	87.7	87.7
-20	-4	88.6	88.6	88.6	88.6
-15	5	89.4	89.4	89.4	89.4
-10	14	90.3	90.3	90.3	89.4
-5	23	91.1	91.1	91.1	89.4
0	32	92.0	92.0	92.0	89.4
5	41	92.8	92.8	92.8	89.4
10	50	93.6	93.6	93.5	89.4
15	59	94.2	93.7		
20	68	93.6	93.0		
25	77	93.0	92.4		
30	86	92.2	91.7		
34	93.2	91.7	91.1		

BOMBARDIER CHALLENGER 605	PERF-01-16
	<i>Oct 05/06</i>

NORMAL TAKE-OFF – 10,000 FEET

TAKE-OFF SPEEDS AND TAKE-OFF DISTANCE – APR ON

OAT (°C)		-40	-30	-20	-10	0	10	20	30
OAT (°F)		-40	-22	-4	14	32	50	68	86
WEIGHT (1000 LB)	DATA	TAKE-OFF SPEEDS (KIAS) AND DISTANCE (FEET) ZERO BLEED							
30.0 V _{FTO} =152	V ₁	115	115	115	115	115	115	116	116
	V _R	121	121	121	121	121	121	121	121
	V ₂	130	130	130	129	129	129	128	127
	DIST	5110	5110	5110	5150	5230	5340	5800	6410
32.0 V _{FTO} =157	V ₁	117	117	117	117	117	117	119	121
	V _R	122	122	122	122	122	122	123	124
	V ₂	130	130	130	130	130	130	130	130
	DIST	5390	5390	5390	5440	5520	5660	6200	6920
34.0 V _{FTO} =162	V ₁	122	122	122	122	122	122	124	126
	V _R	127	127	127	127	127	127	128	129
	V ₂	134	134	134	134	134	134	134	134
	DIST	5860	5860	5860	5940	6060	6250	6980	7940
36.0 V _{FTO} =166	V ₁	127	127	127	127	127	127	129	131
	V _R	131	131	131	131	131	132	132	133
	V ₂	138	138	138	138	138	138	138	138
	DIST	6570	6570	6570	6650	6780	7010	7870	9040
38.0 V _{FTO} =171	V ₁	133	133	133	133	133	133	135	137
	V _R	136	136	136	136	136	136	137	138
	V ₂	141	141	141	141	141	141	141	141
	DIST	7370	7370	7370	7470	7620	7880	8880	10230
40.0 V _{FTO} =175	V ₁	138	138	138	138	138	138	140	142
	V _R	140	140	140	141	141	141	142	142
	V ₂	145	145	145	145	145	145	145	145
	DIST	8270	8270	8270	8380	8570	8860	10020	11590
42.0 V _{FTO} =180	V ₁	142	142	142	142	142	142	145	146
	V _R	144	144	144	144	144	144	145	146
	V ₂	148	148	148	148	148	148	148	148
	DIST	9140	9140	9140	9270	9470	9810	11120	12910
44.0 V _{FTO} =184	V ₁	147	147	147	147	147	147	148	-
	V _R	147	147	147	147	148	148	148	-
	V ₂	151	151	151	151	151	151	151	-
	DIST	10090	10090	10090	10240	10470	10850	12350	-
46.0 V _{FTO} =188	V ₁	151	151	151	151	151	-	-	-
	V _R	151	151	151	151	151	-	-	-
	V ₂	154	154	154	154	154	-	-	-
	DIST	11230	11230	11230	11400	11670	-	-	-
47.6 V _{FTO} =191	V ₁	153	153	153	-	-	-	-	-
	V _R	153	153	153	-	-	-	-	-
	V ₂	156	156	156	-	-	-	-	-
	DIST	12140	12140	12140	-	-	-	-	-
48.2 V _{FTO} =193	V ₁	-	-	-	-	-	-	-	-
	V _R	-	-	-	-	-	-	-	-
	V ₂	-	-	-	-	-	-	-	-
	DIST	-	-	-	-	-	-	-	-

QR1_DXT0_022

BOMBARDIER CHALLENGER 605	PERF-01-17
	Oct 05/06

NORMAL TAKE-OFF – 10,000 FEET

TAKE-OFF SPEEDS AND DISTANCE CORRECTIONS

OAT (°C)		-40	-30	-20	-10	0	10	20	30
OAT (°F)		-40	-22	-4	14	32	50	68	86
	DATA	CORRECTION TO V ₁ , V _R AND DISTANCE							
APR OFF	V ₁	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt
	V _R	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt
	DIST	+4 %	+4 %	+4 %	+4 %	+4 %	+4 %	+4 %	+4 %
PACKS ON	V ₁	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt	+1 Kt	+1 Kt	0 Kt
	V _R	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt
	DIST	0 %	0 %	0 %	0 %	0 %	+2 %	+3 %	+4 %
COWL A/I ON	V ₁	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt		
	V _R	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt		
	DIST	0 %	0 %	0 %	+1 %	+3 %	+6 %		
COWL & WING A/I ON	V ₁	+1 Kt	+1 Kt	+1 Kt	+2 Kt	+3 Kt	+5 Kt		
	V _R	0 Kt	0 Kt	0 Kt	+1 Kt	+1 Kt	+2 Kt		
	DIST	0 %	0 %	0 %	+8 %	+17 %	+26 %		

TAKE-OFF THRUST SETTING, % N₁

OAT		BLEED LEVEL			
°C	°F	Zero Bleed	Packs On	Cowl A/I On	Cowl & Wing A/I
-40	-40	86.1	86.1	86.1	86.1
-35	-31	87.0	87.0	87.0	87.0
-30	-22	87.9	87.9	87.9	87.9
-25	-13	88.8	88.8	88.8	88.8
-20	-4	89.6	89.6	89.6	89.6
-15	5	90.5	90.5	90.5	89.8
-10	14	91.4	91.4	91.4	89.8
-5	23	92.2	92.2	92.2	89.8
0	32	93.1	93.1	93.1	89.8
5	41	93.9	93.9	93.9	89.8
10	50	94.7	94.2	93.9	89.8
15	59	93.9	93.4		
20	68	93.4	92.7		
25	77	92.7	92.1		
30	86	92.0	91.3		

NORMAL TAKE-OFF – 12,000 FEET

TAKE-OFF SPEEDS AND TAKE-OFF DISTANCE – APR ON

OAT (°C)		-40	-30	-20	-10	0	10	20	26
OAT (°F)		-40	-22	-4	14	32	50	68	78.8
WEIGHT (1000 LB)	DATA	TAKE-OFF SPEEDS (KIAS) AND DISTANCE (FEET) ZERO BLEED							
30.0 V _{FTO} =155	V ₁	116	116	116	116	116	116	117	118
	V _R	121	121	121	121	121	121	121	122
	V ₂	129	128	128	128	128	128	128	128
	DIST	5680	5680	5680	5700	5860	6200	6800	7350
32.0 V _{FTO} =160	V ₁	121	121	121	120	120	121	122	124
	V _R	125	125	125	125	125	126	126	127
	V ₂	132	132	132	132	132	132	132	132
	DIST	6200	6200	6200	6230	6410	6820	7590	8300
34.0 V _{FTO} =165	V ₁	126	126	126	126	126	127	128	130
	V _R	130	130	130	130	130	130	131	132
	V ₂	136	136	136	136	136	136	136	136
	DIST	6980	6980	6980	7010	7230	7720	8620	9460
36.0 V _{FTO} =169	V ₁	131	131	131	131	131	132	134	136
	V _R	134	134	134	135	135	135	136	136
	V ₂	140	140	140	140	140	140	140	140
	DIST	7870	7870	7870	7900	8160	8720	9770	10760
38.0 V _{FTO} =174	V ₁	137	137	137	137	137	138	140	141
	V _R	139	139	139	139	139	140	140	141
	V ₂	143	143	143	143	143	143	143	143
	DIST	8870	8870	8870	8910	9200	9850	11070	12220
40.0 V _{FTO} =179	V ₁	142	142	142	142	142	143	-	-
	V _R	144	144	144	144	144	144	-	-
	V ₂	148	148	148	148	148	148	-	-
	DIST	9990	9990	9990	10040	10380	11130	-	-
42.0 V _{FTO} =183	V ₁	147	147	147	147	147	-	-	-
	V _R	147	147	147	147	147	-	-	-
	V ₂	151	151	151	151	151	-	-	-
	DIST	11110	11110	11110	11160	11550	-	-	-
44.0 V _{FTO} =188	V ₁	151	151	151	-	-	-	-	-
	V _R	151	151	151	-	-	-	-	-
	V ₂	153	153	153	-	-	-	-	-
	DIST	12370	12370	12370	-	-	-	-	-
46.0 V _{FTO} =192	V ₁	-	-	-	-	-	-	-	-
	V _R	-	-	-	-	-	-	-	-
	V ₂	-	-	-	-	-	-	-	-
	DIST	-	-	-	-	-	-	-	-
47.6 V _{FTO} =195	V ₁	-	-	-	-	-	-	-	-
	V _R	-	-	-	-	-	-	-	-
	V ₂	-	-	-	-	-	-	-	-
	DIST	-	-	-	-	-	-	-	-
48.2 V _{FTO} =196	V ₁	-	-	-	-	-	-	-	-
	V _R	-	-	-	-	-	-	-	-
	V ₂	-	-	-	-	-	-	-	-
	DIST	-	-	-	-	-	-	-	-

QR1_DXT0_025

BOMBARDIER CHALLENGER 605	PERF-01-19
	Oct 05/06

NORMAL TAKE-OFF – 12,000 FEET

TAKE-OFF SPEEDS AND DISTANCE CORRECTIONS

OAT (°C)		-40	-30	-20	-10	0	10	20	26
OAT (°F)		-40	-22	-4	14	32	50	68	78.8
	DATA	CORRECTION TO V ₁ , V _R AND DISTANCE							
APR OFF	V ₁	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt
	V _R	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt
	DIST	+5 %	+5 %	+5 %	+5 %	+5 %	+6 %	+7 %	+7 %
PACKS ON	V ₁	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt	+1 Kt	+1 Kt
	V _R	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt
	DIST	0 %	0 %	0 %	0 %	0 %	0 %	0 %	0 %
COWL A/I ON	V ₁	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt		
	V _R	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt	+1 Kt		
	DIST	0 %	0 %	0 %	+1 %	+2 %	+5 %		
COWL & WING A/I ON	V ₁	+1 Kt	+1 Kt	+1 Kt	+2 Kt	+4 Kt	+4 Kt		
	V _R	0 Kt	0 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt		
	DIST	0 %	0 %	+1 %	+9 %	+17 %	+24 %		

TAKE-OFF THRUST SETTING, % N₁

OAT		BLEED LEVEL			
°C	°F	Zero Bleed	Packs On	Cowl A/I On	Cowl & Wing A/I
-40	-40	87.1	87.1	87.1	87.1
-35	-31	88.0	88.0	88.0	88.0
-30	-22	88.9	88.9	88.9	88.9
-25	-13	89.8	89.8	89.8	89.8
-20	-4	90.7	90.7	90.7	90.0
-15	5	91.6	91.6	91.6	90.0
-10	14	92.4	92.4	92.4	90.0
-5	23	93.3	93.3	93.3	90.0
0	32	94.1	94.2	94.2	90.0
5	41	95.0	94.6	94.2	90.0
10	50	94.4	93.8	93.4	89.4
15	59	93.8	93.2		
20	68	93.2	92.6		
25	77	92.5	91.8		
26	78.8	92.3	91.7		

BOMBARDIER CHALLENGER 605	PERF-01-20
	Oct 05/06

NORMAL TAKE-OFF – 14,000 FEET

TAKE-OFF SPEEDS AND TAKE-OFF DISTANCE – APR ON

OAT (°C)		-40	-30	-20	-10	0	10	20	22
OAT (°F)		-40	-22	-4	14	32	50	68	71.6
WEIGHT (1000 LB)	DATA	TAKE-OFF SPEEDS (KIAS) AND DISTANCE (FEET) ZERO BLEED							
30.0 V _{FTO} =157	V ₁	118	118	118	118	118	119	120	120
	V _R	123	123	123	123	123	123	124	124
	V ₂	129	129	129	129	129	129	129	129
	DIST	6560	6560	6560	6560	6760	7360	8220	8430
32.0 V _{FTO} =162	V ₁	123	123	123	123	123	124	126	126
	V _R	128	128	128	128	128	128	129	129
	V ₂	133	133	133	133	133	133	133	133
	DIST	7270	7270	7270	7270	7530	8310	9450	9740
34.0 V _{FTO} =167	V ₁	129	129	129	129	129	131	133	133
	V _R	133	133	133	133	133	133	134	134
	V ₂	137	137	137	137	137	137	137	137
	DIST	8250	8250	8250	8250	8560	9480	10840	11180
36.0 V _{FTO} =172	V ₁	135	135	135	135	135	137	138	-
	V _R	137	137	137	137	137	138	138	-
	V ₂	141	141	141	141	141	141	141	-
	DIST	9350	9350	9350	9350	9700	10780	12350	-
38.0 V _{FTO} =177	V ₁	141	141	141	141	141	-	-	-
	V _R	142	142	142	142	142	-	-	-
	V ₂	145	145	145	145	145	-	-	-
	DIST	10570	10570	10570	10570	10990	-	-	-
40.0 V _{FTO} =181	V ₁	146	146	146	-	-	-	-	-
	V _R	146	146	146	-	-	-	-	-
	V ₂	149	149	149	-	-	-	-	-
	DIST	11970	11970	11970	-	-	-	-	-
42.0 V _{FTO} =186	V ₁	150	150	-	-	-	-	-	-
	V _R	150	150	-	-	-	-	-	-
	V ₂	152	152	-	-	-	-	-	-
	DIST	13350	13350	-	-	-	-	-	-
44.0 V _{FTO} =190	V ₁	-	-	-	-	-	-	-	-
	V _R	-	-	-	-	-	-	-	-
	V ₂	-	-	-	-	-	-	-	-
	DIST	-	-	-	-	-	-	-	-
46.0 V _{FTO} =195	V ₁	-	-	-	-	-	-	-	-
	V _R	-	-	-	-	-	-	-	-
	V ₂	-	-	-	-	-	-	-	-
	DIST	-	-	-	-	-	-	-	-
47.6 V _{FTO} =198	V ₁	-	-	-	-	-	-	-	-
	V _R	-	-	-	-	-	-	-	-
	V ₂	-	-	-	-	-	-	-	-
	DIST	-	-	-	-	-	-	-	-
48.2 V _{FTO} =199	V ₁	-	-	-	-	-	-	-	-
	V _R	-	-	-	-	-	-	-	-
	V ₂	-	-	-	-	-	-	-	-
	DIST	-	-	-	-	-	-	-	-

QR1_DXTO_028

BOMBARDIER CHALLENGER 605	PERF-01-21
	Oct 05/06

NORMAL TAKE-OFF – 14,000 FEET

TAKE-OFF SPEEDS AND DISTANCE CORRECTIONS

OAT (°C)		-40	-30	-20	-10	0	10	20	22
OAT (°F)		-40	-22	-4	14	32	50	68	71.6
	DATA	CORRECTION TO V ₁ , V _R AND DISTANCE							
APR OFF	V ₁	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt
	V _R	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt
	DIST	+6 %	+6 %	+6 %	+6 %	+7 %	+7 %	+8 %	+8 %
PACKS ON	V ₁	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt
	V _R	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt
	DIST	0 %	0 %	0 %	0 %	0 %	0 %	0 %	0 %
COWL A/I ON	V ₁	+1 Kt	0 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt		
	V _R	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt	0 Kt		
	DIST	0 %	0 %	0 %	+2 %	+4 %	+7 %		
COWL & WING A/I ON	V ₁	+1 Kt	+1 Kt	+2 Kt	+3 Kt	+3 Kt	+2 Kt		
	V _R	0 Kt	0 Kt	+1 Kt	+1 Kt	+1 Kt	+1 Kt		
	DIST	0 %	0 %	+3 %	+14 %	+21 %	+29 %		

TAKE-OFF THRUST SETTING, % N₁

OAT		BLEED LEVEL			
°C	°F	Zero Bleed	Packs On	Cowl A/I On	Cowl & Wing A/I
-40	-40	88.1	88.1	88.1	88.1
-35	-31	89.0	89.0	89.0	89.0
-30	-22	89.9	89.9	89.9	89.9
-25	-13	90.8	90.8	90.8	90.3
-20	-4	91.7	91.7	91.7	90.3
-15	5	92.6	92.6	92.6	90.3
-10	14	93.4	93.5	93.4	90.3
-5	23	94.3	94.3	94.3	90.3
0	32	95.2	94.9	94.5	90.3
5	41	94.9	94.3	93.8	89.8
10	50	94.1	93.4	93.1	89.0
15	59	93.6	92.9		
20	68	92.9	92.2		
22	71.6	92.5	91.9		

BOMBARDIER CHALLENGER 605	<i>PERF-01-22</i>
	<i>Oct 05/06</i>

THIS PAGE INTENTIONALLY LEFT BLANK

TRAINING PURPOSES ONLY

<i>QUICK REFERENCE HANDBOOK</i> <i>PSP 605-15</i>	TAKE-OFF DATA
--	----------------------

MAXIMUM CLIMB THRUST, % N₁

10TH STAGE BLEEDS OPEN/PACKS ON

OAT		PRESSURE ALTITUDE (100 FT)								
°C	°F	SL	050	100	150	200	250	300	360	410
- 70	- 94								94.8	94.8
- 65	- 85							93.4	95.9	95.9
- 60	- 76						92.5	94.5	97.0	97.1
- 55	- 67						93.6	95.6	97.8	97.8
- 50	- 58					91.6	94.6	96.7	97.8	97.6
- 45	- 49				90.0	92.6	95.7	97.8	97.8	96.8
- 40	- 40	82.0	85.1	88.3	90.9	93.6	96.7	97.8	97.8	96.1
- 35	- 31	82.9	86.0	89.3	91.9	94.6	97.7	97.8	97.5	95.4
- 30	- 22	83.8	86.9	90.2	92.9	95.6	97.5	97.7	96.8	
- 25	- 13	84.6	87.8	91.1	93.8	96.5	96.8	97.0	96.2	
- 20	- 4	85.5	88.7	92.0	94.7	95.9	96.2	96.5		
- 15	5	86.3	89.6	92.9	95.7	95.5	95.9	95.9		
- 10	14	87.1	90.4	93.8	95.2	94.8	95.0	94.9		
- 5	23	88.0	91.3	94.7	94.6	93.9	94.2			
0	32	88.8	92.1	94.0	93.7	93.1	93.3			
5	41	89.6	93.0	93.2	92.8	92.1				
10	50	90.4	92.2	92.3	91.9	91.4				
15	59	91.2	91.4	91.5	91.2					
20	68	90.5	90.7	90.8	90.4					
25	77	89.8	90.0	90.1						
30	86	89.0	89.2	89.3						
35	95	88.1	88.4							
40	104	87.3	87.6							
45	113	86.5								
50	122	85.8								

QR1_DXCIB_001

10TH STAGE BLEEDS OPEN/PACKS ON/COWL ANTI-ICE ON

OAT		PRESSURE ALTITUDE (100 FT)							
°C	°F	SL	050	100	150	200	250	300	
- 70	- 94								92.3
- 65	- 85								93.4
- 60	- 76						92.4		94.5
- 55	- 67						93.6		95.6
- 50	- 58					91.6	94.6		96.7
- 45	- 49				90.0	92.6	95.7		97.7
- 40	- 40	82.0	85.1	88.3	90.9	93.6	96.7		97.4
- 35	- 31	82.9	86.0	89.3	91.9	94.6	96.9		97.1
- 30	- 22	83.8	86.9	90.2	92.9	95.5	96.5		96.3
- 25	- 13	84.6	87.8	91.1	93.8	95.5	95.6		95.7
- 20	- 4	85.5	88.7	92.0	95.0	95.0	95.3		95.2
- 15	5	86.3	89.6	92.9	95.0	94.5	94.5		94.2
- 10	14	87.1	90.4	94.0	94.3	93.6	93.7		93.1
- 5	23	88.0	91.3	94.0	93.5	92.8	92.8		
0	32	88.8	92.1	93.1	92.6	91.8	91.8		
5	41	89.6	92.2	92.3	91.7	90.9			
10	50	90.4	91.4	91.4	90.9	90.1			

QR1_DXCIB_002

MAXIMUM CLIMB THRUST, % N₁

**10TH STAGE BLEEDS OPEN/PACKS ON/COWL & WING
ANTI-ICE ON**

OAT		PRESSURE ALTITUDE (100 FT)						
°C	°F	SL	050	100	150	200	250	300
- 70	- 94							93.4
- 65	- 85							94.5
- 60	- 76						92.4	94.5
- 55	- 67						93.6	95.4
- 50	- 58					91.6	94.5	95.4
- 45	- 49				90.0	92.6	94.5	95.4
- 40	- 40	82.0	85.1	88.3	90.9	93.5	94.5	94.9
- 35	- 31	82.9	86.0	89.3	91.9	93.5	94.5	94.1
- 30	- 22	83.8	86.9	90.2	92.9	93.5	93.9	93.5
- 25	- 13	84.6	87.8	91.1	93.0	93.5	93.3	92.5
- 20	- 4	85.5	88.7	92.0	93.0	92.8	92.4	91.4
- 15	5	86.3	89.6	92.0	93.0	91.9	91.5	90.1
- 10	14	87.1	90.5	92.0	92.1	90.9	90.3	89.3
- 5	23	88.0	90.5	92.0	91.2	89.8	89.3	
0	32	88.8	90.5	91.2	90.2	88.9	88.2	
5	41	88.9	90.5	90.2	89.3	87.9		
10	50	88.9	89.6	89.4	88.4	86.9		

QR1_DXCIB.003

CLIMB DATA

250 KIAS/0.72 M/PACKS ON/ANTI-ICE OFF/30% C.G.

TOW 28 000 LB		PRESSURE ALTITUDE (100 FT)									
		200	250	270	290	310	330	350	370	390	410
ISA	TIME (min)	3.2	4.4	5.0	5.6	6.3	7.1	7.9	8.7	9.7	10.8
	DIST (nam)	15.4	22.3	25.7	29.6	34.2	39.8	45.1	50.7	57.4	65.4
	FUEL (lb)	280	356	389	423	459	499	534	569	607	649
ISA +5°C	TIME (min)	3.5	4.7	5.3	6.0	6.7	7.6	8.4	9.3	10.3	11.6
	DIST (nam)	16.8	24.2	27.9	32.1	37.1	43.0	48.7	54.8	62.2	71.0
	FUEL (lb)	292	372	406	441	479	521	558	595	635	680
ISA +10°C	TIME (min)	3.7	5.1	5.8	6.5	7.3	8.2	9.1	10.0	11.2	12.6
	DIST (nam)	18.3	26.5	30.5	35.1	40.4	46.8	53.1	59.7	67.8	77.9
	FUEL (lb)	305	389	425	463	503	547	586	625	668	717
TOW 30 000 LB		200	250	270	290	310	330	350	370	390	410
ISA	TIME (min)	3.5	4.8	5.4	6.0	6.8	7.7	8.5	9.4	10.5	11.9
	DIST (nam)	16.7	24.1	27.8	32.1	37.1	43.1	49.0	55.2	62.8	72.0
	FUEL (lb)	302	384	419	456	496	539	578	616	659	708
ISA +5°C	TIME (min)	3.7	5.1	5.7	6.5	7.3	8.2	9.1	10.1	11.3	12.8
	DIST (nam)	18.1	26.2	30.2	34.8	40.2	46.7	53.0	59.8	68.1	78.3
	FUEL (lb)	314	401	437	476	518	563	604	645	691	743
ISA +10°C	TIME (min)	4.0	5.5	6.2	7.0	7.9	8.9	9.9	10.9	12.2	13.9
	DIST (nam)	19.8	28.6	33.0	38.0	43.8	50.9	57.8	65.1	74.3	86.1
	FUEL (lb)	328	420	459	500	543	592	635	678	727	785
TOW 32 000 LB		200	250	270	290	310	330	350	370	390	410
ISA	TIME (min)	3.7	5.1	5.8	6.5	7.3	8.3	9.2	10.2	11.5	13.1
	DIST (nam)	17.9	26.0	29.9	34.6	40.1	46.7	53.1	60.0	68.6	79.4
	FUEL (lb)	324	412	450	491	534	581	624	666	715	771
ISA +5°C	TIME (min)	4.0	5.5	6.2	7.0	7.8	8.9	9.9	11.0	12.3	14.1
	DIST (nam)	19.5	28.2	32.5	37.5	43.4	50.5	57.5	65.1	74.5	86.6
	FUEL (lb)	337	431	470	512	558	608	653	698	750	811
ISA +10°C	TIME (min)	4.3	5.9	6.7	7.5	8.5	9.6	10.7	11.8	13.3	15.3
	DIST (nam)	21.3	30.9	35.6	41.0	47.4	55.1	62.7	71.0	81.5	95.5
	FUEL (lb)	353	451	493	538	586	638	687	735	791	859

QR1_DXCLB_004

CLIMB DATA

250 KIAS/0.72 M/PACKS ON/ANTI-ICE OFF/30% C.G. (Cont'd)

TOW 34 000 LB		PRESSURE ALTITUDE (100 FT)									
		200	250	270	290	310	330	350	370	390	410
ISA	TIME (min)	4.0	5.5	6.2	7.0	7.9	8.9	10.0	11.1	12.5	14.4
	DIST (nam)	19.2	27.9	32.2	37.2	43.2	50.4	57.5	65.2	75.0	87.9
	FUEL (lb)	346	442	483	526	573	625	672	720	775	842
ISA +5°C	TIME (min)	4.3	5.9	6.6	7.5	8.4	9.6	10.7	11.9	13.5	15.5
	DIST (nam)	20.9	30.3	35.0	40.4	46.8	54.6	62.3	70.8	81.6	96.1
	FUEL (lb)	361	461	504	550	599	654	704	754	814	887
ISA +10°C	TIME (min)	4.6	6.4	7.2	8.1	9.1	10.4	11.5	12.9	14.6	17.0
	DIST (nam)	22.8	33.2	38.3	44.2	51.1	59.6	68.0	77.3	89.5	106.6
	FUEL (lb)	377	484	529	578	630	688	741	795	860	944
TOW 36 000 LB		200	250	270	290	310	330	350	370	390	410
ISA	TIME (min)	4.3	5.9	6.6	7.5	8.5	9.6	10.8	12.0	13.7	15.9
	DIST (nam)	20.6	29.9	34.5	40.0	46.4	54.3	62.2	70.9	82.2	97.9
	FUEL (lb)	370	472	516	563	614	671	723	777	841	923
ISA +5°C	TIME (min)	4.6	6.3	7.1	8.0	9.1	10.3	11.5	12.9	14.7	17.3
	DIST (nam)	22.4	32.5	37.5	43.4	50.4	58.9	67.5	77.0	89.7	107.7
	FUEL (lb)	385	493	540	589	643	703	758	815	885	976
ISA +10°C	TIME (min)	4.9	6.8	7.7	8.7	9.8	11.2	12.5	14.0	16.0	19.1
	DIST (nam)	24.4	35.6	41.1	47.5	55.1	64.4	73.8	84.3	98.7	120.5
	FUEL (lb)	403	518	567	619	676	740	799	860	937	1043
TOW 38 000 LB		200	250	270	290	310	330	350	370	390	410
ISA	TIME (min)	4.5	6.2	7.1	8.0	9.1	10.3	11.6	13.0	15.0	17.9
	DIST (nam)	22.0	31.9	36.9	42.8	49.9	58.6	67.3	77.1	90.4	110.6
	FUEL (lb)	394	504	551	602	658	720	778	838	914	1019
ISA +5°C	TIME (min)	4.9	6.7	7.6	8.6	9.7	11.1	12.5	14.0	16.2	19.6
	DIST (nam)	23.9	34.8	40.2	46.5	54.1	63.5	73.1	83.9	99.0	122.8
	FUEL (lb)	411	527	577	630	689	754	816	881	964	1084
ISA +10°C	TIME (min)	5.3	7.3	8.2	9.3	10.6	12.0	13.5	15.2	17.7	22.0
	DIST (nam)	26.1	38.1	44.1	51.0	59.3	69.5	80.0	92.0	109.3	139.8
	FUEL (lb)	430	553	606	663	725	795	861	932	1024	1172

QR1_DXCIB_005

CLIMB DATA

250 KIAS/0.72 M/PACKS ON/ANTI-ICE OFF/30% C.G. (Cont'd)

TOW 40 000 LB		PRESSURE ALTITUDE (100 FT)									
		200	250	270	290	310	330	350	370	390	410
ISA	TIME (min)	4.8	6.7	7.5	8.5	9.7	11.1	12.5	14.2	16.5	20.7
	DIST (nam)	23.4	34.1	39.5	45.9	53.5	63.1	72.8	84.0	100.1	128.8
	FUEL (lb)	418	536	588	643	703	771	836	905	996	1145
ISA +5°C	TIME (min)	5.2	7.2	8.1	9.2	10.4	11.9	13.5	15.3	17.9	23.0
	DIST (nam)	25.4	37.1	43.0	49.9	58.2	68.5	79.2	91.7	110.1	145.8
	FUEL (lb)	437	561	615	673	737	809	878	953	1054	1234
ISA +10°C	TIME (min)	5.6	7.8	8.8	10.0	11.3	13.0	14.6	16.6	19.7	27.0
	DIST (nam)	27.8	40.7	47.2	54.8	63.8	75.1	86.9	100.8	122.5	174.2
	FUEL (lb)	457	590	648	709	777	854	929	1010	1126	1376
TOW 42 000 LB		200	250	270	290	310	330	350	370	390	410
ISA	TIME (min)	5.1	7.1	8.0	9.1	10.4	11.9	13.5	15.4	18.4	25.9
	DIST (nam)	24.9	36.3	42.2	49.1	57.4	68.0	78.9	91.9	112.3	163.8
	FUEL (lb)	444	570	626	685	751	827	899	979	1094	1360
ISA +5°C	TIME (min)	5.5	7.6	8.7	9.8	11.2	12.9	14.6	16.7	20.1	31.1
	DIST (nam)	27.0	39.6	45.9	53.4	62.5	73.9	86.0	100.6	124.5	201.2
	FUEL (lb)	464	597	656	719	788	868	946	1034	1165	1548
ISA +10°C	TIME (min)	6.0	8.3	9.4	10.7	12.2	14.0	15.9	18.2	22.3	
	DIST (nam)	29.6	43.5	50.5	58.7	68.6	81.2	94.5	111.1	140.2	
	FUEL (lb)	486	629	691	758	832	918	1002	1099	1254	
TOW 44 000 LB		200	250	270	290	310	330	350	370	390	410
ISA	TIME (min)	5.4	7.5	8.6	9.7	11.1	12.9	14.6	16.9	21.0	
	DIST (nam)	26.4	38.7	45.0	52.5	61.6	73.3	85.7	101.2	129.1	
	FUEL (lb)	471	606	665	730	802	886	968	1063	1221	
ISA +5°C	TIME (min)	5.8	8.1	9.2	10.5	12.0	13.9	15.8	18.4	23.3	
	DIST (nam)	28.7	42.2	49.1	57.2	67.1	79.9	93.6	111.3	145.6	
	FUEL (lb)	492	635	698	767	843	932	1021	1126	1315	
ISA +10°C	TIME (min)	6.3	8.9	10.1	11.4	13.1	15.1	17.3	20.1	26.6	
	DIST (nam)	31.5	46.4	54.0	62.9	73.8	87.9	103.3	123.5	168.8	
	FUEL (lb)	516	669	737	810	892	988	1084	1202	1443	

QR1_DXCIB_006

CLIMB DATA

250 KIAS/0.72 M/PACKS ON/ANTI-ICE OFF/30% C.G. (Cont'd)

TOW 46 000 LB		PRESSURE ALTITUDE (100 FT)									
		200	250	270	290	310	330	350	370	390	410
ISA	TIME (min)	5.7	8.0	9.1	10.4	11.9	13.9	15.9	18.7	25.3	
	DIST (nam)	28.0	41.2	48.0	56.1	66.2	79.2	93.4	112.6	158.4	
	FUEL (lb)	498	643	707	778	857	951	1045	1162	1420	
ISA +5°C	TIME (min)	6.2	8.7	9.8	11.2	12.9	15.0	17.2	20.4	29.6	
	DIST (nam)	30.5	45.0	52.4	61.2	72.2	86.5	102.4	124.7	188.7	
	FUEL (lb)	522	675	743	818	902	1002	1105	1238	1587	
ISA +10°C	TIME (min)	6.7	9.4	10.7	12.2	14.0	16.3	18.9	22.6	39.4	
	DIST (nam)	33.5	49.5	57.7	67.5	79.6	95.4	113.4	139.4	258.0	
	FUEL (lb)	548	712	785	865	956	1064	1177	1329	1953	
TOW 48 000 LB		200	250	270	290	310	330	350	370	390	410
ISA	TIME (min)	6.1	8.5	9.7	11.1	12.8	15.0	17.4	21.0	44.1	
	DIST (nam)	29.7	43.8	51.1	60.0	71.2	85.8	102.5	127.6	286.8	
	FUEL (lb)	527	683	752	829	916	1022	1132	1286	2173	
ISA +5°C	TIME (min)	6.6	9.2	10.5	12.0	13.8	16.2	18.9	23.2		
	DIST (nam)	32.4	47.9	55.9	65.6	77.7	93.9	112.8	143.0		
	FUEL (lb)	552	717	791	873	966	1079	1201	1381		
ISA +10°C	TIME (min)	7.1	10.0	11.5	13.1	15.1	17.7	20.8	26.0		
	DIST (nam)	35.5	52.8	61.8	72.5	85.9	104.0	125.5	162.5		
	FUEL (lb)	581	758	837	925	1026	1149	1285	1500		
TOW 50 000 LB		200	250	270	290	310	330	350	370	390	410
ISA	TIME (min)	6.4	9.0	10.3	11.9	13.8	16.2	19.1	24.5		
	DIST (nam)	31.4	46.6	54.5	64.3	76.7	93.5	113.6	150.5		
	FUEL (lb)	558	724	799	884	981	1101	1234	1460		
ISA +5°C	TIME (min)	7.0	9.8	11.2	12.9	14.9	17.6	20.9	27.8		
	DIST (nam)	34.3	51.1	59.7	70.4	84.0	102.6	125.7	173.9		
	FUEL (lb)	585	762	842	932	1036	1167	1315	1602		
ISA +10°C	TIME (min)	7.6	10.7	12.3	14.1	16.3	19.4	23.2	32.6		
	DIST (nam)	37.7	56.4	66.1	78.0	93.1	114.1	141.0	207.4		
	FUEL (lb)	616	806	893	990	1103	1247	1416	1801		

QR1_DXCLB_007

CLIMB DATA

250/300 KIAS/0.78 M/PACKS ON/ANTI-ICE OFF/30% C.G.

TOW 28 000 LB		PRESSURE ALTITUDE (100 FT)									
		200	250	270	290	310	330	350	370	390	410
ISA	TIME (min)	3.7	5.1	5.8	6.6	7.4	8.1	9.0	9.9	11.1	12.6
	DIST (nam)	19.8	29.5	34.6	40.9	46.7	52.5	58.8	66.1	75.0	85.9
	FUEL (lb)	323	417	460	509	551	590	630	672	721	775
ISA +5°C	TIME (min)	4.0	5.5	6.3	7.2	8.1	8.9	9.8	10.9	12.2	13.9
	DIST (nam)	21.8	32.8	38.4	45.5	51.9	58.4	65.4	73.5	83.5	95.7
	FUEL (lb)	339	442	489	542	587	630	673	719	772	831
ISA +10°C	TIME (min)	4.3	6.1	6.9	8.0	8.9	9.9	10.9	12.1	13.6	15.5
	DIST (nam)	24.1	36.4	42.9	50.9	58.2	65.5	73.4	82.4	93.8	108.6
	FUEL (lb)	358	469	521	580	630	677	724	775	833	902
TOW 30 000 LB		200	250	270	290	310	330	350	370	390	410
ISA	TIME (min)	3.9	5.5	6.2	7.1	7.9	8.8	9.7	10.8	12.2	13.9
	DIST (nam)	21.4	31.9	37.4	44.3	50.5	56.9	64.0	72.1	82.2	94.9
	FUEL (lb)	347	449	496	549	595	638	682	730	785	847
ISA +5°C	TIME (min)	4.3	6.0	6.8	7.8	8.7	9.7	10.7	11.9	13.4	15.3
	DIST (nam)	23.5	35.4	41.5	49.3	56.3	63.5	71.2	80.3	91.6	106.0
	FUEL (lb)	365	476	527	585	635	682	730	781	841	910
ISA +10°C	TIME (min)	4.7	6.6	7.5	8.6	9.7	10.7	11.9	13.2	14.9	17.2
	DIST (nam)	26.0	39.3	46.4	55.2	63.2	71.3	80.0	90.2	103.3	120.9
	FUEL (lb)	386	506	562	627	682	734	786	843	910	992
TOW 32 000 LB		200	250	270	290	310	330	350	370	390	410
ISA	TIME (min)	4.2	5.9	6.7	7.7	8.6	9.5	10.5	11.7	13.3	15.3
	DIST (nam)	23.0	34.3	40.2	47.7	54.6	61.6	69.4	78.5	90.1	105.0
	FUEL (lb)	372	482	532	590	640	687	736	790	852	927
ISA +5°C	TIME (min)	4.6	6.4	7.3	8.4	9.4	10.5	11.6	12.9	14.7	16.9
	DIST (nam)	25.3	38.1	44.7	53.1	60.9	68.7	77.4	87.5	100.6	117.8
	FUEL (lb)	391	511	566	629	684	736	789	847	915	999
ISA +10°C	TIME (min)	5.0	7.0	8.1	9.3	10.4	11.6	12.9	14.4	16.4	19.2
	DIST (nam)	27.9	42.3	49.9	59.6	68.4	77.3	87.1	98.5	113.7	135.4
	FUEL (lb)	413	543	604	675	735	793	851	915	993	1094

QR1_DXCLB_008

CLIMB DATA

250/300 KIAS/0.78 M/PACKS ON/ANTI-ICE OFF/30% C.G.
 (Cont'd)

TOW 34 000 LB		PRESSURE ALTITUDE (100 FT)									
		200	250	270	290	310	330	350	370	390	410
ISA	TIME (min)	4.5	6.3	7.2	8.2	9.2	10.2	11.4	12.7	14.5	17.0
	DIST (nam)	24.6	36.7	43.2	51.3	58.8	66.5	75.1	85.3	98.7	117.1
	FUEL (lb)	397	515	570	633	687	739	793	853	925	1016
ISA +5°C	TIME (min)	4.9	6.9	7.8	9.0	10.1	11.3	12.5	14.1	16.1	18.9
	DIST (nam)	27.1	40.8	48.0	57.1	65.6	74.3	83.9	95.4	110.6	132.0
	FUEL (lb)	418	547	606	675	735	792	851	917	996	1100
ISA +10°C	TIME (min)	5.4	7.5	8.7	10.0	11.3	12.5	13.9	15.7	18.0	21.7
	DIST (nam)	29.9	45.4	53.7	64.2	73.8	83.7	94.6	107.6	125.6	153.8
	FUEL (lb)	442	582	648	725	791	855	920	993	1085	1216
TOW 36 000 LB		200	250	270	290	310	330	350	370	390	410
ISA	TIME (min)	4.8	6.7	7.6	8.8	9.9	11.0	12.3	13.8	15.9	19.1
	DIST (nam)	26.2	39.3	46.2	55.0	63.1	71.6	81.2	92.8	108.5	132.0
	FUEL (lb)	423	550	609	677	736	793	853	921	1006	1122
ISA +5°C	TIME (min)	5.2	7.3	8.4	9.7	10.9	12.1	13.5	15.3	17.7	21.4
	DIST (nam)	28.9	43.7	51.4	61.3	70.6	80.2	90.9	104.0	122.0	150.4
	FUEL (lb)	446	584	648	723	788	851	917	992	1087	1223
ISA +10°C	TIME (min)	5.7	8.1	9.3	10.8	12.1	13.5	15.1	17.1	19.9	25.2
	DIST (nam)	31.9	48.6	57.5	69.0	79.6	90.5	102.7	117.6	139.5	179.6
	FUEL (lb)	472	622	693	777	850	920	994	1077	1188	1374
TOW 38 000 LB		200	250	270	290	310	330	350	370	390	410
ISA	TIME (min)	5.1	7.1	8.1	9.4	10.6	11.8	13.2	15.0	17.6	21.9
	DIST (nam)	27.9	41.9	49.3	58.8	67.7	77.1	87.8	101.0	120.1	152.4
	FUEL (lb)	450	585	649	722	787	850	917	995	1098	1257
ISA +5°C	TIME (min)	5.6	7.8	9.0	10.4	11.7	13.1	14.6	16.6	19.6	25.1
	DIST (nam)	30.8	46.6	55.0	65.7	75.9	86.4	98.5	113.6	135.9	177.0
	FUEL (lb)	474	622	691	772	844	913	987	1074	1191	1389
ISA +10°C	TIME (min)	6.1	8.6	9.9	11.5	13.0	14.6	16.4	18.7	22.3	31.3
	DIST (nam)	34.0	51.9	61.6	74.0	85.7	97.8	111.6	129.0	156.8	225.5
	FUEL (lb)	502	663	740	832	912	990	1073	1170	1311	1629

QR1_DXCIB_009

CLIMB DATA

250/300 KIAS/0.78 M/PACKS ON/ANTI-ICE OFF/30% C.G.
(Cont'd)

TOW 40 000 LB		PRESSURE ALTITUDE (100 FT)									
		200	250	270	290	310	330	350	370	390	410
ISA	TIME (min)	5.4	7.6	8.7	10.0	11.3	12.7	14.3	16.3	19.6	26.5
	DIST (nam)	29.7	44.6	52.6	62.8	72.6	82.9	94.9	110.4	134.5	185.8
	FUEL (lb)	477	622	690	770	840	909	985	1076	1205	1459
ISA +5°C	TIME (min)	5.9	8.3	9.5	11.1	12.5	14.0	15.8	18.2	22.0	31.9
	DIST (nam)	32.7	49.7	58.6	70.3	81.4	93.2	106.7	124.6	153.5	228.3
	FUEL (lb)	504	662	736	824	902	979	1063	1165	1316	1675
ISA +10°C	TIME (min)	6.5	9.2	10.6	12.3	14.0	15.7	17.8	20.5	25.5	
	DIST (nam)	36.2	55.3	65.8	79.3	92.1	105.7	121.5	142.3	180.3	
	FUEL (lb)	533	706	789	888	977	1064	1158	1274	1468	
TOW 42 000 LB		200	250	270	290	310	330	350	370	390	410
ISA	TIME (min)	5.7	8.0	9.2	10.7	12.1	13.6	15.4	17.9	22.2	40.9
	DIST (nam)	31.4	47.3	55.9	67.0	77.7	89.1	102.8	121.3	153.6	292.8
	FUEL (lb)	505	660	732	819	895	972	1058	1167	1341	2022
ISA +5°C	TIME (min)	6.3	8.8	10.2	11.8	13.4	15.1	17.1	20.0	25.4	
	DIST (nam)	34.7	52.8	62.5	75.1	87.3	100.4	116.0	137.6	178.3	
	FUEL (lb)	534	703	782	877	963	1050	1145	1269	1482	
ISA +10°C	TIME (min)	6.9	9.8	11.3	13.2	15.0	17.0	19.3	22.7	30.5	
	DIST (nam)	38.4	58.9	70.1	84.8	99.0	114.3	132.6	158.4	217.9	
	FUEL (lb)	566	751	840	948	1045	1143	1253	1397	1699	
TOW 44 000 LB		200	250	270	290	310	330	350	370	390	410
ISA	TIME (min)	6.1	8.5	9.8	11.4	12.9	14.6	16.7	19.7	26.3	
	DIST (nam)	33.3	50.2	59.4	71.4	83.1	95.9	111.7	134.6	183.5	
	FUEL (lb)	534	699	777	870	954	1040	1140	1274	1536	
ISA +5°C	TIME (min)	6.6	9.4	10.8	12.6	14.3	16.3	18.7	22.3	31.4	
	DIST (nam)	36.7	56.1	66.4	80.1	93.6	108.4	126.7	154.0	222.7	
	FUEL (lb)	565	745	830	934	1029	1126	1238	1394	1753	
ISA +10°C	TIME (min)	7.3	10.4	12.0	14.1	16.1	18.3	21.2	25.6	44.3	
	DIST (nam)	40.7	62.6	74.8	90.8	106.6	124.0	145.7	179.5	322.3	
	FUEL (lb)	599	797	893	1011	1119	1231	1361	1549	2268	

QR1_DXCLB_010

CLIMB DATA

250/300 KIAS/0.78 M/PACKS ON/ANTI-ICE OFF/30% C.G.
(Cont'd)

TOW 46 000 LB		PRESSURE ALTITUDE (100 FT)									
		200	250	270	290	310	330	350	370	390	410
ISA	TIME (min)	6.4	9.0	10.4	12.1	13.8	15.7	18.2	22.1	37.0	
	DIST (nm)	35.2	53.2	63.1	76.1	89.0	103.5	122.2	151.8	262.7	
	FUEL (lb)	564	739	823	924	1017	1115	1232	1405	1997	
ISA +5°C	TIME (min)	7.0	9.9	11.5	13.4	15.4	17.6	20.4	25.3		
	DIST (nm)	38.9	59.5	70.7	85.6	100.6	117.4	139.3	176.3		
	FUEL (lb)	597	789	881	994	1099	1210	1345	1555		
ISA +10°C	TIME (min)	7.7	11.0	12.8	15.0	17.3	19.9	23.4	29.7		
	DIST (nm)	43.1	66.5	79.7	97.3	114.9	135.0	161.7	210.1		
	FUEL (lb)	634	845	949	1079	1200	1329	1489	1758		
TOW 48 000 LB		200	250	270	290	310	330	350	370	390	410
ISA	TIME (min)	6.8	9.5	11.0	12.9	14.8	16.9	20.0	25.6		
	DIST (nm)	37.1	56.3	67.0	81.2	95.5	112.1	134.8	176.8		
	FUEL (lb)	596	782	872	982	1085	1197	1340	1585		
ISA +5°C	TIME (min)	7.4	10.5	12.2	14.3	16.5	19.0	22.6	30.1		
	DIST (nm)	41.1	63.1	75.2	91.5	108.3	127.9	155.2	211.7		
	FUEL (lb)	630	836	935	1059	1177	1305	1473	1794		
ISA +10°C	TIME (min)	8.1	11.7	13.6	16.1	18.7	21.7	26.2	37.3		
	DIST (nm)	45.6	70.7	84.9	104.4	124.4	148.1	182.5	267.5		
	FUEL (lb)	670	896	1009	1152	1289	1442	1647	2118		
TOW 50 000 LB		200	250	270	290	310	330	350	370	390	410
ISA	TIME (min)	7.1	10.1	11.7	13.7	15.8	18.4	22.2	32.1		
	DIST (nm)	39.2	59.7	71.2	86.7	102.8	122.2	151.0	225.0		
	FUEL (lb)	628	827	924	1044	1160	1291	1472	1902		
ISA +5°C	TIME (min)	7.8	11.2	12.9	15.3	17.8	20.8	25.5	42.3		
	DIST (nm)	43.4	67.0	80.0	98.0	117.0	140.4	176.2	303.1		
	FUEL (lb)	666	885	992	1128	1262	1415	1635	2352		
ISA +10°C	TIME (min)	8.6	12.4	14.5	17.3	20.2	23.9	30.2			
	DIST (nm)	48.3	75.2	90.7	112.2	135.2	164.2	212.0			
	FUEL (lb)	708	951	1074	1232	1390	1576	1861			

QR1_DXCLB_011

MAXIMUM CRUISE THRUST, % N₁

10TH STAGE BLEEDS OPEN/PACKS ON

OAT		PRESSURE ALTITUDE (100 FT)								
°C	°F	SL	050	100	150	200	250	300	360	410
- 70.0	- 94.0								94.8	94.0
- 65.0	- 85.0							93.4	95.9	95.0
- 60.0	- 76.0						92.1	94.5	97.0	96.1
- 55.0	- 67.0						93.2	95.6	97.8	96.7
- 50.0	- 58.0					91.5	94.3	96.7	97.8	95.8
- 45.0	- 49.0				89.6	92.5	95.3	97.7	97.4	95.2
- 40.0	- 40.0	80.4	83.7	87.2	90.5	93.5	96.3	97.8	96.6	94.6
- 35.0	- 31.0	81.3	84.5	88.1	91.5	94.5	97.5	97.0	96.0	94.0
- 30.0	- 22.0	82.1	85.4	89.0	92.5	95.5	96.9	96.5	95.5	
- 25.0	- 13.0	83.0	86.3	89.9	93.4	96.5	96.5	96.1	94.6	
- 20.0	- 4.0	83.8	87.1	90.8	94.3	96.1	95.8	95.2		
- 15.0	5.0	84.6	88.0	91.7	95.3	95.2	94.9	94.2		
- 10.0	14.0	85.4	88.8	92.6	94.5	94.3	93.9	93.3		
- 5.0	23.0	86.2	89.7	93.4	93.6	93.4	93.1			
0.0	32.0	87.0	90.5	92.7	92.8	92.7	92.4			
5.0	41.0	87.8	91.3	92.0	92.2	92.0				
10.0	50.0	88.6	90.7	91.4	91.5	91.3				
15.0	59.0	89.4	90.0	90.6	90.8					
20.0	68.0	88.7	89.3	90.0	90.2					
25.0	77.0	87.9	88.6	89.4						
30.0	86.0	87.1	87.8	88.8						
35.0	95.0	86.3	87.1							
40.0	104.0	85.6	86.3							
45.0	113.0	84.9								
50.0	122.0	84.1								

QR1_DXCZR_001

10TH STAGE BLEEDS OPEN/PACKS ON/COWL ANTI-ICE ON

OAT		PRESSURE ALTITUDE (100 FT)							
°C	°F	SL	050	100	150	200	250	300	
- 70	- 94								93.4
- 65	- 85								
- 60	- 76						92.1		94.5
- 55	- 67						93.2		95.6
- 50	- 58					91.5	94.3		96.7
- 45	- 49				89.6	92.5	95.3		97.3
- 40	- 40	80.4	83.6	87.2	90.5	93.5	96.5		96.5
- 35	- 31	81.3	84.5	88.1	91.5	94.5	96.5		95.9
- 30	- 22	82.1	85.4	89.0	92.5	95.9	96.0		95.6
- 25	- 13	83.0	86.3	89.9	93.4	95.9	95.6		94.7
- 20	- 4	83.8	87.1	90.8	94.4	95.1	94.6		93.8
- 15	5	84.6	88.0	91.7	94.4	94.2	93.7		92.7
- 10	14	85.4	88.8	92.7	93.6	93.2	92.7		
- 5	23	86.2	89.7	92.7	92.7	92.4	91.9		
0	32	87.0	90.6	91.9	92.0	91.7	91.2		
5	41	87.8	90.6	91.3	91.3	91.0			
10	50	88.6	89.9	90.5	90.5	90.3			

QR1_DXCZR_002

MAXIMUM CRUISE THRUST, % N₁

**10TH STAGE BLEEDS OPEN/PACKS ON/COWL & WING
ANTI-ICE ON**

OAT		PRESSURE ALTITUDE (100 FT)						
°C	°F	SL	050	100	150	200	250	300
- 70	- 94							93.4
- 65	- 85							94.7
- 60	- 76						92.1	94.7
- 55	- 67						93.2	94.7
- 50	- 58					91.5	94.6	94.7
- 45	- 49				89.6	92.5	94.6	94.7
- 40	- 40	80.4	83.6	87.2	90.5	93.7	94.6	94.2
- 35	- 31	81.3	84.5	88.1	91.5	93.7	94.6	93.5
- 30	- 22	82.1	85.4	89.0	92.6	93.7	93.9	92.6
- 25	- 13	83.0	86.3	89.9	92.6	93.7	92.9	91.3
- 20	- 4	83.8	87.1	90.9	92.6	92.9	91.9	90.2
- 15	5	84.6	88.0	90.9	92.6	91.9	90.9	89.2
- 10	14	85.4	89.0	90.9	91.6	91.0	90.0	88.2
- 5	23	86.2	89.0	90.9	90.8	90.2	89.1	
0	32	87.1	89.0	90.3	90.0	89.3	88.3	
5	41	87.1	89.0	89.5	89.2	88.6		
10	50	87.1	88.2	88.7	88.5	87.9		

QR1_DXCZR_003

CRUISE DATA

MACH 0.72/PACKS ON/ANTI-ICE OFF/30% C.G.

WEIGHT 28 000 LB		PRESSURE ALTITUDE (100 FT)								
		250	270	290	310	330	350	370	390	410
ISA -10°C	KTAS	424	421	417	413	409	405	403	403	403
	% N ₁	80.5	80.1	79.8	79.5	79.3	79.2	79.6	80.6	82.0
	Lb/Hr/Eng	1156	1069	989	916	850	792	748	717	693
ISA	KTAS	433	430	426	422	419	415	413	413	413
	% N ₁	82.3	82.0	81.7	81.4	81.3	81.2	81.6	82.7	84.1
	Lb/Hr/Eng	1194	1104	1022	948	881	822	776	743	717
ISA +10°C	KTAS	442	439	435	432	428	424	422	422	422
	% N ₁	84.2	83.8	83.5	83.3	83.2	83.1	83.6	84.7	86.1
	Lb/Hr/Eng	1229	1138	1055	979	911	850	802	768	741
30 000 LB		250	270	290	310	330	350	370	390	410
ISA -10°C	KTAS	424	421	417	413	409	405	403	403	403
	% N ₁	80.7	80.3	80.1	79.8	79.7	79.7	80.2	81.5	83.1
	Lb/Hr/Eng	1163	1077	998	927	863	807	766	739	719
ISA	KTAS	433	430	426	422	419	415	413	413	413
	% N ₁	82.5	82.2	81.9	81.7	81.6	81.6	82.2	83.5	85.3
	Lb/Hr/Eng	1202	1113	1032	960	894	838	795	766	744
ISA +10°C	KTAS	442	439	435	432	428	424	422	422	422
	% N ₁	84.3	84.0	83.8	83.6	83.5	83.6	84.2	85.6	87.3
	Lb/Hr/Eng	1237	1147	1065	991	924	866	822	791	768
32 000 LB		250	270	290	310	330	350	370	390	410
ISA -10°C	KTAS	424	421	417	413	409	405	403	403	403
	% N ₁	80.8	80.5	80.3	80.1	80.1	80.2	80.9	82.4	84.5
	Lb/Hr/Eng	1172	1087	1009	939	878	824	787	764	748
ISA	KTAS	433	430	426	422	419	415	413	413	413
	% N ₁	82.7	82.4	82.2	82.1	82.0	82.2	83.0	84.5	86.6
	Lb/Hr/Eng	1210	1123	1044	973	909	856	816	791	773
ISA +10°C	KTAS	442	439	435	432	428	424	422	422	422
	% N ₁	84.5	84.3	84.1	84.0	84.0	84.2	85.0	86.6	88.7
	Lb/Hr/Eng	1246	1157	1076	1003	939	885	844	818	798

QR1_DXCZR_004

CRUISE DATA

MACH 0.72/PACKS ON/ANTI-ICE OFF/30% C.G. (Cont'd)

WEIGHT 34 000 LB		PRESSURE ALTITUDE (100 FT)								
		250	270	290	310	330	350	370	390	410
ISA -10°C	KTAS	424	421	417	413	409	405	403	403	403
	% N ₁	81.0	80.8	80.6	80.5	80.6	80.8	81.7	83.5	86.1
	Lb/Hr/Eng	1181	1098	1021	953	894	844	810	791	781
ISA	KTAS	433	430	426	422	419	415	413	413	413
	% N ₁	82.9	82.6	82.5	82.4	82.5	82.8	83.8	85.7	88.2
	Lb/Hr/Eng	1220	1134	1056	987	926	876	840	819	808
ISA +10°C	KTAS	442	439	435	432	428	424	422	422	422
	% N ₁	84.7	84.5	84.4	84.3	84.5	84.8	85.8	87.7	90.5
	Lb/Hr/Eng	1256	1168	1089	1017	956	905	868	846	833
36 000 LB		250	270	290	310	330	350	370	390	410
ISA -10°C	KTAS	424	421	417	413	409	405	403	403	403
	% N ₁	81.2	81.0	80.9	80.9	81.1	81.5	82.6	84.8	87.8
	Lb/Hr/Eng	1192	1109	1034	968	912	866	836	821	820
ISA	KTAS	433	430	426	422	419	415	413	413	413
	% N ₁	83.1	82.9	82.8	82.8	83.1	83.5	84.8	87.0	90.0
	Lb/Hr/Eng	1230	1146	1069	1003	945	898	866	849	847
ISA +10°C	KTAS	442	439	435	432	428	424	422	422	422
	% N ₁	84.9	84.8	84.7	84.8	85.0	85.5	86.8	89.1	92.1
	Lb/Hr/Eng	1266	1180	1102	1033	976	928	895	877	875
38 000 LB		250	270	290	310	330	350	370	390	410
ISA -10°C	KTAS	424	421	417	413	409	405	403	403	403
	% N ₁	81.5	81.3	81.3	81.3	81.6	82.3	83.7	86.4	89.9
	Lb/Hr/Eng	1203	1121	1049	985	933	890	864	856	868
ISA	KTAS	433	430	426	422	419	415	413	413	413
	% N ₁	83.3	83.2	83.2	83.3	83.6	84.3	85.8	88.5	92.2
	Lb/Hr/Eng	1241	1158	1084	1020	966	922	894	886	897
ISA +10°C	KTAS	442	439	435	432	428	424	422	422	422
	% N ₁	85.2	85.1	85.1	85.2	85.6	86.3	87.9	90.7	94.4
	Lb/Hr/Eng	1278	1192	1117	1052	997	953	925	913	927

QR1_DXCZR_005

CRUISE DATA

MACH 0.72/PACKS ON/ANTI-ICE OFF/30% C.G. (Cont'd)

WEIGHT 40 000 LB		PRESSURE ALTITUDE (100 FT)								
		250	270	290	310	330	350	370	390	410
ISA -10°C	KTAS	424	421	417	413	409	405	403	403	403
	% N ₁	81.7	81.6	81.6	81.8	82.3	83.1	84.9	88.0	92.6
	Lb/Hr/Eng	1215	1135	1065	1005	955	917	895	896	926
ISA	KTAS	433	430	426	422	419	415	413	413	413
	% N ₁	83.6	83.5	83.6	83.8	84.3	85.2	87.1	90.2	94.9
	Lb/Hr/Eng	1253	1172	1101	1039	989	949	926	927	959
ISA +10°C	KTAS	442	439	435	432	428	424	422	422	422
	% N ₁	85.4	85.4	85.5	85.8	86.3	87.2	89.2	92.4	95.7
	Lb/Hr/Eng	1290	1206	1134	1072	1021	981	957	957	957
42 000 LB		250	270	290	310	330	350	370	390	410
ISA -10°C	KTAS	424	421	417	413	409	405	403	403	
	% N ₁	82.0	81.9	82.1	82.4	83.0	84.1	86.4	89.9	
	Lb/Hr/Eng	1227	1150	1082	1026	980	946	930	945	
ISA	KTAS	433	430	426	422	419	415	413	413	
	% N ₁	83.8	83.8	84.0	84.3	85.0	86.2	88.5	92.2	
	Lb/Hr/Eng	1266	1187	1119	1060	1014	978	962	976	
ISA +10°C	KTAS	442	439	435	432	428	424	422	422	
	% N ₁	85.7	85.7	85.9	86.3	87.0	88.3	90.6	94.4	
	Lb/Hr/Eng	1303	1222	1152	1094	1047	1011	993	1010	
44 000 LB		250	270	290	310	330	350	370	390	410
ISA -10°C	KTAS	424	421	417	413	409	405	403	403	
	% N ₁	82.2	82.3	82.5	83.0	83.8	85.2	87.8	92.4	
	Lb/Hr/Eng	1241	1167	1102	1049	1008	977	970	1002	
ISA	KTAS	433	430	426	422	419	415	413	413	
	% N ₁	84.1	84.2	84.5	85.0	85.9	87.4	90.0	94.7	
	Lb/Hr/Eng	1280	1204	1138	1084	1041	1010	1004	1037	
ISA +10°C	KTAS	442	439	435	432	428	424	422		
	% N ₁	86.0	86.1	86.4	86.9	87.9	89.4	92.2		
	Lb/Hr/Eng	1318	1240	1173	1118	1075	1043	1036		

QR1_DXCRZ_006

CRUISE DATA

MACH 0.72/PACKS ON/ANTI-ICE OFF/30% C.G. (Cont'd)

WEIGHT 46 000 LB		PRESSURE ALTITUDE (100 FT)							
		250	270	290	310	330	350	370	390 410
ISA -10°C	KTAS	424	421	417	413	409	405	403	
	% N ₁	82.5	82.7	83.0	83.6	84.7	86.5	89.5	
	Lb/Hr/Eng	1256	1184	1124	1074	1037	1012	1018	
ISA	KTAS	433	430	426	422	419	415	413	
	% N ₁	84.4	84.6	84.9	85.7	86.8	88.7	91.8	
	Lb/Hr/Eng	1296	1222	1159	1109	1070	1046	1052	
ISA +10°C	KTAS	442	439	435	432	428	424	422	
	% N ₁	86.3	86.5	86.9	87.6	88.8	90.8	94.0	
	Lb/Hr/Eng	1334	1259	1195	1144	1105	1079	1087	
48 000 LB		250	270	290	310	330	350	370	390 410
ISA -10°C	KTAS	424	421	417	413	409	405	403	
	% N ₁	82.9	83.1	83.5	84.4	85.7	87.9	91.7	
	Lb/Hr/Eng	1273	1203	1147	1101	1067	1051	1074	
ISA	KTAS	433	430	426	422	419	415	413	
	% N ₁	84.8	85.1	85.5	86.4	87.8	90.0	94.0	
	Lb/Hr/Eng	1313	1242	1183	1137	1102	1087	1109	
ISA +10°C	KTAS	442	439	435	432	428	424	422	
	% N ₁	86.6	86.9	87.5	88.4	89.9	92.2	96.2	
	Lb/Hr/Eng	1352	1280	1220	1173	1137	1120	1146	
50 000 LB		250	270	290	310	330	350	370	390 410
ISA -10°C	KTAS	424	421	417	413	409	405	403	
	% N ₁	83.2	83.6	84.1	85.2	86.9	89.3	94.5	
	Lb/Hr/Eng	1291	1225	1171	1130	1101	1096	1150	
ISA	KTAS	433	430	426	422	419	415	413	
	% N ₁	85.1	85.5	86.1	87.2	89.0	91.6	96.9	
	Lb/Hr/Eng	1331	1264	1208	1165	1138	1133	1191	
ISA +10°C	KTAS	442	439	435	432	428	424		
	% N ₁	87.0	87.4	88.1	89.3	91.1	93.8		
	Lb/Hr/Eng	1370	1301	1246	1202	1172	1170		

QR1_DXCZR_007

CRUISE DATA

MACH 0.74/PACKS ON/ANTI-ICE OFF/30% C.G.

WEIGHT 28 000 LB		PRESSURE ALTITUDE (100 FT)								
		250	270	290	310	330	350	370	390	410
ISA -10°C	KTAS	436	432	428	425	421	417	415	415	415
	% N ₁	81.8	81.5	81.1	80.8	80.6	80.4	80.7	81.8	83.1
	Lb/Hr/Eng	1229	1136	1051	972	901	837	787	753	724
ISA	KTAS	445	442	438	434	430	427	424	424	424
	% N ₁	83.7	83.4	83.0	82.8	82.6	82.4	82.8	83.9	85.2
	Lb/Hr/Eng	1268	1174	1086	1007	934	868	817	780	749
ISA +10°C	KTAS	455	451	447	444	440	436	434	434	434
	% N ₁	85.5	85.2	84.9	84.7	84.5	84.4	84.8	85.9	87.3
	Lb/Hr/Eng	1306	1209	1120	1038	964	898	845	807	774
30 000 LB		250	270	290	310	330	350	370	390	410
ISA -10°C	KTAS	436	432	428	425	421	417	415	415	415
	% N ₁	82.0	81.7	81.4	81.1	80.9	80.8	81.3	82.6	84.1
	Lb/Hr/Eng	1237	1145	1060	983	913	851	805	774	747
ISA	KTAS	445	442	438	434	430	427	424	424	424
	% N ₁	83.9	83.6	83.3	83.1	82.9	82.9	83.4	84.7	86.3
	Lb/Hr/Eng	1277	1183	1096	1018	946	883	836	801	773
ISA +10°C	KTAS	455	451	447	444	440	436	434	434	434
	% N ₁	85.7	85.4	85.2	85.0	84.9	84.8	85.4	86.7	88.4
	Lb/Hr/Eng	1315	1218	1130	1049	977	913	864	828	798
32 000 LB		250	270	290	310	330	350	370	390	410
ISA -10°C	KTAS	436	432	428	425	421	417	415	415	415
	% N ₁	82.2	81.9	81.6	81.4	81.3	81.3	82.0	83.4	85.4
	Lb/Hr/Eng	1246	1155	1071	994	926	868	825	796	774
ISA	KTAS	445	442	438	434	430	427	424	424	424
	% N ₁	84.1	83.8	83.5	83.4	83.3	83.4	84.1	85.6	87.5
	Lb/Hr/Eng	1286	1192	1107	1029	959	900	856	824	801
ISA +10°C	KTAS	455	451	447	444	440	436	434	434	434
	% N ₁	85.9	85.6	85.4	85.3	85.2	85.3	86.1	87.6	89.7
	Lb/Hr/Eng	1324	1228	1141	1061	991	930	885	851	826

QR1_DXCZR_008

CRUISE DATA

MACH 0.74/PACKS ON/ANTI-ICE OFF/30% C.G. (Cont'd)

WEIGHT 34 000 LB		PRESSURE ALTITUDE (100 FT)								
		250	270	290	310	330	350	370	390	410
ISA -10°C	KTAS	436	432	428	425	421	417	415	415	415
	% N ₁	82.4	82.1	81.9	81.7	81.7	81.9	82.8	84.5	86.9
	Lb/Hr/Eng	1256	1165	1082	1007	942	887	846	820	805
ISA	KTAS	445	442	438	434	430	427	424	424	424
	% N ₁	84.2	84.0	83.8	83.7	83.7	84.0	84.9	86.6	89.0
	Lb/Hr/Eng	1295	1203	1119	1042	975	920	877	849	834
ISA +10°C	KTAS	455	451	447	444	440	436	434	434	434
	% N ₁	86.1	85.9	85.7	85.6	85.7	86.0	86.9	88.7	91.3
	Lb/Hr/Eng	1334	1239	1153	1075	1007	951	907	877	860
36 000 LB		250	270	290	310	330	350	370	390	410
ISA -10°C	KTAS	436	432	428	425	421	417	415	415	415
	% N ₁	82.6	82.3	82.2	82.1	82.2	82.6	83.6	85.7	88.4
	Lb/Hr/Eng	1266	1176	1094	1022	960	908	870	849	842
ISA	KTAS	445	442	438	434	430	427	424	424	424
	% N ₁	84.5	84.3	84.1	84.1	84.2	84.6	85.7	87.9	90.7
	Lb/Hr/Eng	1306	1214	1131	1056	994	940	900	878	871
ISA +10°C	KTAS	455	451	447	444	440	436	434	434	434
	% N ₁	86.3	86.1	86.0	86.0	86.2	86.7	87.8	90.0	92.8
	Lb/Hr/Eng	1345	1251	1165	1090	1026	972	931	906	900
38 000 LB		250	270	290	310	330	350	370	390	410
ISA -10°C	KTAS	436	432	428	425	421	417	415	415	415
	% N ₁	82.8	82.6	82.5	82.5	82.7	83.3	84.6	87.1	90.3
	Lb/Hr/Eng	1277	1188	1108	1039	980	930	895	882	887
ISA	KTAS	445	442	438	434	430	427	424	424	424
	% N ₁	84.7	84.5	84.4	84.5	84.8	85.4	86.7	89.3	92.6
	Lb/Hr/Eng	1317	1226	1144	1074	1014	962	927	913	917
ISA +10°C	KTAS	455	451	447	444	440	436	434	434	434
	% N ₁	86.5	86.4	86.3	86.4	86.8	87.4	88.8	91.5	94.8
	Lb/Hr/Eng	1356	1263	1179	1108	1047	994	958	942	947

QR1_DXCRR_009

CRUISE DATA

MACH 0.74/PACKS ON/ANTI-ICE OFF/30% C.G. (Cont'd)

WEIGHT 40 000 LB		PRESSURE ALTITUDE (100 FT)								
		250	270	290	310	330	350	370	390	410
ISA -10°C	KTAS	436	432	428	425	421	417	415	415	415
	% N ₁	83.0	82.9	82.8	83.0	83.4	84.1	85.8	88.5	92.7
	Lb/Hr/Eng	1288	1200	1123	1057	1001	954	925	920	938
ISA	KTAS	445	442	438	434	430	427	424	424	424
	% N ₁	84.9	84.8	84.8	85.0	85.4	86.2	87.9	90.8	95.0
	Lb/Hr/Eng	1328	1239	1159	1093	1035	986	957	952	971
ISA +10°C	KTAS	455	451	447	444	440	436	434	434	
	% N ₁	86.8	86.7	86.7	86.9	87.4	88.2	90.0	93.0	
	Lb/Hr/Eng	1368	1276	1195	1128	1069	1019	988	983	
42 000 LB		250	270	290	310	330	350	370	390	410
ISA -10°C	KTAS	436	432	428	425	421	417	415	415	
	% N ₁	83.2	83.1	83.2	83.5	84.0	85.0	87.1	90.3	
	Lb/Hr/Eng	1300	1213	1141	1078	1024	980	958	965	
ISA	KTAS	445	442	438	434	430	427	424	424	
	% N ₁	85.1	85.1	85.2	85.5	86.1	87.1	89.2	92.6	
	Lb/Hr/Eng	1340	1253	1177	1114	1058	1013	992	997	
ISA +10°C	KTAS	455	451	447	444	440	436	434	434	
	% N ₁	87.0	87.0	87.1	87.5	88.1	89.2	91.4	94.8	
	Lb/Hr/Eng	1380	1291	1214	1149	1093	1047	1023	1031	
44 000 LB		250	270	290	310	330	350	370	390	410
ISA -10°C	KTAS	436	432	428	425	421	417	415	415	
	% N ₁	83.5	83.5	83.6	84.0	84.8	86.0	88.3	92.4	
	Lb/Hr/Eng	1313	1229	1160	1099	1048	1010	996	1015	
ISA	KTAS	445	442	438	434	430	427	424	424	
	% N ₁	85.4	85.4	85.6	86.1	86.8	88.2	90.7	94.8	
	Lb/Hr/Eng	1353	1269	1197	1135	1082	1044	1031	1051	
ISA +10°C	KTAS	455	451	447	444	440	436	434		
	% N ₁	87.3	87.3	87.6	88.1	88.9	90.3	92.8		
	Lb/Hr/Eng	1394	1307	1234	1171	1117	1077	1064		

QR1_DXCRZ_010

CRUISE DATA

MACH 0.74/PACKS ON/ANTI-ICE OFF/30% C.G. (Cont'd)

WEIGHT 46 000 LB		PRESSURE ALTITUDE (100 FT)								
		250	270	290	310	330	350	370	390	410
ISA -10°C	KTAS	436	432	428	425	421	417	415	415	
	% N ₁	83.8	83.8	84.1	84.6	85.6	87.3	90.0	95.3	
	Lb/Hr/Eng	1326	1247	1180	1122	1074	1043	1040	1091	
ISA	KTAS	445	442	438	434	430	427	424		
	% N ₁	85.7	85.8	86.1	86.7	87.7	89.4	92.2		
	Lb/Hr/Eng	1367	1287	1218	1158	1109	1078	1075		
ISA +10°C	KTAS	455	451	447	444	440	436	434		
	% N ₁	87.6	87.7	88.1	88.7	89.8	91.6	94.4		
	Lb/Hr/Eng	1408	1325	1256	1195	1144	1112	1111		
48 000 LB		250	270	290	310	330	350	370	390	410
ISA -10°C	KTAS	436	432	428	425	421	417	415		
	% N ₁	84.1	84.3	84.6	85.3	86.5	88.5	91.8		
	Lb/Hr/Eng	1342	1267	1201	1146	1103	1080	1089		
ISA	KTAS	445	442	438	434	430	427	424		
	% N ₁	86.0	86.2	86.7	87.4	88.7	90.6	94.2		
	Lb/Hr/Eng	1383	1306	1239	1182	1139	1117	1126		
ISA +10°C	KTAS	455	451	447	444	440	436	434		
	% N ₁	87.9	88.1	88.6	89.4	90.8	92.9	96.4		
	Lb/Hr/Eng	1424	1346	1278	1220	1175	1152	1163		
50 000 LB		250	270	290	310	330	350	370	390	410
ISA -10°C	KTAS	436	432	428	425	421	417	415		
	% N ₁	84.4	84.7	85.2	86.1	87.6	89.8	94.2		
	Lb/Hr/Eng	1359	1287	1223	1172	1136	1122	1153		
ISA	KTAS	445	442	438	434	430	427	424		
	% N ₁	86.3	86.7	87.2	88.1	89.8	92.1	96.6		
	Lb/Hr/Eng	1400	1327	1262	1209	1174	1159	1195		
ISA +10°C	KTAS	455	451	447	444	440	436			
	% N ₁	88.2	88.6	89.2	90.2	91.9	94.2			
	Lb/Hr/Eng	1443	1367	1300	1246	1209	1197			

QR1_DXCZRZ_011

CRUISE DATA

MACH 0.77/PACKS ON/ANTI-ICE OFF/30% C.G.

WEIGHT 28 000 LB		PRESSURE ALTITUDE (100 FT)								
		250	270	290	310	330	350	370	390	410
ISA -10°C	KTAS	454	450	446	442	438	434	431	431	431
	% N ₁	84.0	83.6	83.2	82.9	82.6	82.5	82.8	83.8	85.1
	Lb/Hr/Eng	1352	1249	1155	1068	988	917	859	816	779
ISA	KTAS	464	460	456	452	448	444	442	442	442
	% N ₁	85.9	85.5	86.4	84.9	84.7	84.5	84.9	85.9	87.3
	Lb/Hr/Eng	1393	1289	1192	1104	1022	950	890	845	807
ISA +10°C	KTAS	473	469	466	462	458	454	452	452	452
	% N ₁	87.8	87.4	87.2	86.9	86.7	86.6	86.9	88.0	89.4
	Lb/Hr/Eng	1436	1329	1230	1139	1056	982	921	873	832
30 000 LB		250	270	290	310	330	350	370	390	410
ISA -10°C	KTAS	454	450	446	442	438	434	431	431	431
	% N ₁	84.1	83.8	83.4	83.2	83.0	82.9	83.3	84.5	86.1
	Lb/Hr/Eng	1361	1259	1165	1078	1000	930	875	835	802
ISA	KTAS	464	460	456	452	448	444	442	442	442
	% N ₁	86.1	85.7	86.7	85.2	85.0	85.0	85.5	86.7	88.3
	Lb/Hr/Eng	1402	1299	1202	1115	1035	963	906	864	831
ISA +10°C	KTAS	473	469	466	462	458	454	452	452	452
	% N ₁	88.0	87.6	87.4	87.2	87.0	87.0	87.5	88.8	90.5
	Lb/Hr/Eng	1446	1339	1241	1150	1069	996	937	893	857
32 000 LB		250	270	290	310	330	350	370	390	410
ISA -10°C	KTAS	454	450	446	442	438	434	431	431	431
	% N ₁	84.3	84.0	83.7	83.5	83.3	83.4	84.0	85.4	87.3
	Lb/Hr/Eng	1370	1269	1176	1091	1014	946	893	856	828
ISA	KTAS	464	460	456	452	448	444	442	442	442
	% N ₁	86.2	85.9	86.9	85.5	85.4	85.5	86.1	87.6	89.5
	Lb/Hr/Eng	1412	1309	1213	1127	1049	979	924	886	857
ISA +10°C	KTAS	473	469	466	462	458	454	452	452	452
	% N ₁	88.2	87.9	87.6	87.5	87.4	87.5	88.2	89.7	91.7
	Lb/Hr/Eng	1455	1349	1252	1163	1084	1012	956	915	885

QR1_DXCfZ_012

CRUISE DATA

MACH 0.77/PACKS ON/ANTI-ICE OFF/30% C.G. (Cont'd)

WEIGHT 34 000 LB		PRESSURE ALTITUDE (100 FT)							
		250	270	290	310	330	350	370	390 410
ISA -10°C	KTAS	454	450	446	442	438	434	431	431 431
	% N ₁	84.5	84.2	83.9	83.8	83.8	83.9	84.7	86.5 88.4
	Lb/Hr/Eng	1379	1279	1187	1104	1029	963	913	880 858
ISA	KTAS	464	460	456	452	448	444	442	442 442
	% N ₁	86.4	86.2	87.2	85.8	85.8	86.0	86.9	88.6 90.8
	Lb/Hr/Eng	1421	1320	1225	1140	1064	996	945	911 887
ISA +10°C	KTAS	473	469	466	462	458	454	452	452 452
	% N ₁	88.3	88.1	87.9	87.8	87.9	88.1	89.0	90.8 92.9
	Lb/Hr/Eng	1465	1360	1264	1177	1099	1030	977	940 917
36 000 LB		250	270	290	310	330	350	370	390 410
ISA -10°C	KTAS	454	450	446	442	438	434	431	431 431
	% N ₁	84.7	84.4	84.2	84.1	84.2	84.5	85.6	87.5 90.0
	Lb/Hr/Eng	1389	1290	1200	1118	1045	982	935	907 895
ISA	KTAS	464	460	456	452	448	444	442	442 442
	% N ₁	86.6	86.4	87.5	86.2	86.3	86.7	87.8	89.7 92.3
	Lb/Hr/Eng	1432	1331	1238	1154	1080	1015	968	939 925
ISA +10°C	KTAS	473	469	466	462	458	454	452	452 452
	% N ₁	88.6	88.3	88.2	88.2	88.3	88.7	89.9	92.0 94.5
	Lb/Hr/Eng	1476	1372	1278	1192	1116	1050	1000	969 956
38 000 LB		250	270	290	310	330	350	370	390 410
ISA -10°C	KTAS	454	450	446	442	438	434	431	431 431
	% N ₁	84.9	84.7	84.5	84.5	84.7	85.2	86.6	88.6 91.9
	Lb/Hr/Eng	1400	1302	1213	1133	1063	1003	960	938 939
ISA	KTAS	464	460	456	452	448	444	442	442 442
	% N ₁	86.8	86.6	87.8	86.6	86.8	87.4	88.7	91.0 94.3
	Lb/Hr/Eng	1443	1343	1252	1170	1098	1036	994	971 972
ISA +10°C	KTAS	473	469	466	462	458	454	452	452 452
	% N ₁	88.8	88.6	88.5	88.6	88.9	89.5	90.9	93.1 93.1
	Lb/Hr/Eng	1487	1385	1292	1208	1134	1072	1026	1003 1003

QR1_DXCZRZ_013

CRUISE DATA

MACH 0.77/PACKS ON/ANTI-ICE OFF/30% C.G. (Cont'd)

WEIGHT 40 000 LB		PRESSURE ALTITUDE (100 FT)								
		250	270	290	310	330	350	370	390	410
ISA -10°C	KTAS	454	450	446	442	438	434	431	431	431
	% N ₁	85.1	84.9	84.9	85.0	85.3	86.0	87.5	90.1	94.3
	Lb/Hr/Eng	1412	1315	1228	1150	1082	1026	987	977	993
ISA	KTAS	464	460	456	452	448	444	442	442	442
	% N ₁	87.1	86.9	88.2	87.0	87.4	88.2	89.8	92.4	96.7
	Lb/Hr/Eng	1455	1356	1267	1187	1118	1060	1022	1009	1029
ISA +10°C	KTAS	473	469	466	462	458	454	452	452	
	% N ₁	89.0	88.9	88.9	89.1	89.5	90.3	92.0	94.6	
	Lb/Hr/Eng	1499	1398	1306	1225	1154	1095	1055	1044	
42 000 LB		250	270	290	310	330	350	370	390	410
ISA -10°C	KTAS	454	450	446	442	438	434	431	431	
	% N ₁	85.4	85.2	85.2	85.5	86.0	86.9	88.6	91.9	
	Lb/Hr/Eng	1425	1329	1243	1168	1103	1051	1019	1021	
ISA	KTAS	464	460	456	452	448	444	442	442	
	% N ₁	87.3	87.2	88.5	87.5	88.1	89.1	90.9	94.2	
	Lb/Hr/Eng	1469	1371	1283	1206	1140	1087	1054	1056	
ISA +10°C	KTAS	473	469	466	462	458	454	452		
	% N ₁	89.2	89.2	89.3	89.6	90.2	91.3	93.1		
	Lb/Hr/Eng	1512	1412	1322	1244	1176	1121	1089		
44 000 LB		250	270	290	310	330	350	370	390	410
ISA -10°C	KTAS	454	450	446	442	438	434	431	431	
	% N ₁	85.6	85.5	85.6	86.0	86.7	87.9	89.9	94.1	
	Lb/Hr/Eng	1438	1344	1260	1188	1127	1078	1057	1074	
ISA	KTAS	464	460	456	452	448	444	442	442	
	% N ₁	87.6	87.5	88.9	88.1	88.9	90.0	92.2	96.4	
	Lb/Hr/Eng	1482	1386	1300	1226	1164	1115	1092	1113	
ISA +10°C	KTAS	473	469	466	462	458	454	452		
	% N ₁	89.5	89.5	89.7	90.2	91.0	92.3	94.4		
	Lb/Hr/Eng	1526	1427	1340	1264	1200	1149	1130		

QR1_DXCZR_014

CRUISE DATA

MACH 0.77/PACKS ON/ANTI-ICE OFF/30% C.G. (Cont'd)

WEIGHT 46 000 LB		PRESSURE ALTITUDE (100 FT)							
		250	270	290	310	330	350	370	390 410
ISA -10°C	KTAS	454	450	446	442	438	434	431	
	% N ₁	85.9	85.9	86.1	86.6	87.5	88.8	91.5	
	Lb/Hr/Eng	1452	1359	1279	1209	1152	1110	1102	
ISA	KTAS	464	460	456	452	448	444	442	
	% N ₁	87.8	87.9	89.4	88.7	89.7	91.0	93.9	
	Lb/Hr/Eng	1497	1402	1319	1249	1191	1147	1138	
ISA +10°C	KTAS	473	469	466	462	458	454	452	
	% N ₁	89.8	89.9	90.2	90.8	91.8	93.3	96.1	
	Lb/Hr/Eng	1540	1443	1359	1285	1226	1184	1176	
48 000 LB		250	270	290	310	330	350	370	390 410
ISA -10°C	KTAS	454	450	446	442	438	434	431	
	% N ₁	86.2	86.3	86.6	87.3	88.4	90.0	93.4	
	Lb/Hr/Eng	1466	1376	1298	1233	1179	1147	1151	
ISA	KTAS	464	460	456	452	448	444	442	
	% N ₁	88.1	88.3	89.9	89.4	90.6	92.3	95.8	
	Lb/Hr/Eng	1512	1420	1339	1273	1219	1185	1191	
ISA +10°C	KTAS	473	469	466	462	458	454		
	% N ₁	90.1	90.3	90.7	91.5	92.7	94.4		
	Lb/Hr/Eng	1555	1461	1379	1310	1255	1223		
50 000 LB		250	270	290	310	330	350	370	390 410
ISA -10°C	KTAS	454	450	446	442	438	434		
	% N ₁	86.5	86.7	87.2	88.0	89.4	91.4		
	Lb/Hr/Eng	1482	1395	1320	1258	1210	1190		
ISA	KTAS	464	460	456	452	448	444		
	% N ₁	88.4	88.7	90.4	90.1	91.5	93.7		
	Lb/Hr/Eng	1528	1439	1361	1298	1250	1228		
ISA +10°C	KTAS	473	469	466	462	458	454		
	% N ₁	90.4	90.7	91.3	92.3	93.7	95.9		
	Lb/Hr/Eng	1571	1480	1402	1337	1288	1269		

QR1_DXCZR_015

CRUISE DATA

MACH 0.80/PACKS ON/ANTI-ICE OFF/30% C.G.

WEIGHT 28 000 LB		PRESSURE ALTITUDE (100 FT)								
		250	270	290	310	330	350	370	390	410
ISA -10°C	KTAS			463	459	455	450	448	448	448
	% N ₁			86.0	85.7	85.4	85.3	86.7	87.7	88.6
	Lb/Hr/Eng			1293	1194	1102	1022	954	903	859
ISA	KTAS			473	469	465	461	459	459	459
	% N ₁			89.3	87.8	87.5	87.4	87.9	89.0	90.3
	Lb/Hr/Eng			1335	1233	1139	1056	988	935	888
ISA +10°C	KTAS			484	480	476	472	469	469	469
	% N ₁			90.1	89.8	89.6	89.6	90.1	91.2	92.4
	Lb/Hr/Eng			1376	1271	1176	1092	1021	965	918
30 000 LB		250	270	290	310	330	350	370	390	410
ISA -10°C	KTAS			463	459	455	450	448	448	448
	% N ₁			86.2	85.9	85.8	85.8	87.3	88.2	89.3
	Lb/Hr/Eng			1303	1204	1115	1036	970	921	882
ISA	KTAS			473	469	465	461	459	459	459
	% N ₁			89.5	88.0	87.9	87.9	88.5	89.8	91.1
	Lb/Hr/Eng			1345	1244	1153	1071	1005	954	912
ISA +10°C	KTAS			484	480	476	472	469	469	469
	% N ₁			90.3	90.1	90.0	90.1	90.7	92.0	93.4
	Lb/Hr/Eng			1386	1282	1190	1107	1037	985	944
32 000 LB		250	270	290	310	330	350	370	390	410
ISA -10°C	KTAS			463	459	455	450	448	448	448
	% N ₁			86.5	86.3	86.2	86.3	87.8	88.8	90.3
	Lb/Hr/Eng			1313	1217	1130	1051	987	942	913
ISA	KTAS			473	469	465	461	459	459	459
	% N ₁			89.8	88.4	88.4	88.5	89.2	90.6	92.3
	Lb/Hr/Eng			1355	1257	1167	1087	1023	975	943
ISA +10°C	KTAS			484	480	476	472	469	469	469
	% N ₁			90.6	90.5	90.5	90.6	91.4	92.7	94.6
	Lb/Hr/Eng			1396	1294	1204	1122	1055	1008	976

QR1_DXCZR_016

CRUISE DATA

MACH 0.80/PACKS ON/ANTI-ICE OFF/30% C.G. (Cont'd)

WEIGHT 34 000 LB		PRESSURE ALTITUDE (100 FT)								
		250	270	290	310	330	350	370	390	410
ISA -10°C	KTAS			463	459	455	450	448	448	448
	% N ₁			86.8	86.6	86.7	86.9	88.4	89.6	91.6
	Lb/Hr/Eng			1325	1231	1145	1068	1007	968	948
ISA	KTAS			473	469	465	461	459	459	459
	% N ₁			90.0	88.8	88.9	89.1	90.0	91.5	93.9
	Lb/Hr/Eng			1367	1272	1183	1105	1043	1002	982
ISA +10°C	KTAS			484	480	476	472	469	469	
	% N ₁			90.9	90.8	91.0	91.3	92.2	93.6	
	Lb/Hr/Eng			1408	1309	1220	1140	1076	1036	
36 000 LB		250	270	290	310	330	350	370	390	410
ISA -10°C	KTAS			463	459	455	450	448	448	448
	% N ₁			87.1	87.1	87.2	87.5	89.0	90.6	93.3
	Lb/Hr/Eng			1338	1246	1161	1086	1029	1001	989
ISA	KTAS			473	469	465	461	459	459	459
	% N ₁			90.4	89.2	89.4	89.7	90.6	92.7	95.7
	Lb/Hr/Eng			1381	1287	1200	1123	1066	1035	1025
ISA +10°C	KTAS			484	480	476	472	469	469	
	% N ₁			91.2	91.3	91.5	91.9	92.9	94.9	
	Lb/Hr/Eng			1422	1324	1236	1158	1101	1071	
38 000 LB		250	270	290	310	330	350	370	390	410
ISA -10°C	KTAS			463	459	455	450	448	448	
	% N ₁			87.4	87.5	87.7	88.2	89.7	91.8	
	Lb/Hr/Eng			1353	1261	1178	1106	1058	1038	
ISA	KTAS			473	469	465	461	459	459	
	% N ₁			90.7	89.6	89.9	90.4	91.5	94.2	
	Lb/Hr/Eng			1396	1303	1218	1144	1093	1074	
ISA +10°C	KTAS			484	480	476	472	469		
	% N ₁			91.6	91.8	92.1	92.6	93.8		
	Lb/Hr/Eng			1437	1341	1254	1180	1131		

QR1_DXCZRZ_017

CRUISE DATA

MACH 0.80/PACKS ON/ANTI-ICE OFF/30% C.G. (Cont'd)

WEIGHT 40 000 LB		PRESSURE ALTITUDE (100 FT)								
		250	270	290	310	330	350	370	390	410
ISA -10°C	KTAS			463	459	455	450	448	448	
	% N ₁			87.8	88.0	88.3	88.9	90.7	93.5	
	Lb/Hr/Eng			1368	1278	1197	1130	1091	1081	
ISA	KTAS			473	469	465	461	459	459	
	% N ₁			91.1	90.1	90.5	91.2	92.8	95.9	
	Lb/Hr/Eng			1412	1319	1237	1168	1127	1119	
ISA +10°C	KTAS			484	480	476	472	469		
	% N ₁			92.0	92.3	92.7	93.3	95.0		
	Lb/Hr/Eng			1453	1358	1274	1206	1167		
42 000 LB		250	270	290	310	330	350	370	390	410
ISA -10°C	KTAS			463	459	455	450	448		
	% N ₁			88.2	88.5	89.0	89.7	91.8		
	Lb/Hr/Eng			1384	1295	1217	1158	1129		
ISA	KTAS			473	469	465	461	459		
	% N ₁			91.5	90.6	91.1	92.0	94.1		
	Lb/Hr/Eng			1428	1337	1258	1198	1166		
ISA +10°C	KTAS			484	480	476	472	469		
	% N ₁			92.4	92.8	93.4	94.1	96.4		
	Lb/Hr/Eng			1469	1376	1296	1236	1205		
44 000 LB		250	270	290	310	330	350	370	390	410
ISA -10°C	KTAS			463	459	455	450	448		
	% N ₁			88.7	89.0	89.6	90.7	93.3		
	Lb/Hr/Eng			1400	1314	1242	1192	1171		
ISA	KTAS			473	469	465	461	459		
	% N ₁			91.8	91.2	91.8	93.0	95.7		
	Lb/Hr/Eng			1445	1356	1282	1231	1211		
ISA +10°C	KTAS			484	480	476	472			
	% N ₁			92.9	93.3	94.1	95.2			
	Lb/Hr/Eng			1487	1397	1322	1272			

QR1_DXCZR_018

CRUISE DATA

MACH 0.80/PACKS ON/ANTI-ICE OFF/30% C.G. (Cont'd)

WEIGHT 46 000 LB		PRESSURE ALTITUDE (100 FT)								
		250	270	290	310	330	350	370	390	410
ISA -10°C	KTAS			463	459	455	450	448		
	% N ₁			89.1	89.6	90.3	91.9	95.3		
	Lb/Hr/Eng			1418	1335	1271	1229	1231		
ISA	KTAS			473	469	465	461	459		
	% N ₁			92.2	91.9	92.6	94.3	97.8		
	Lb/Hr/Eng			1462	1377	1311	1270	1274		
ISA +10°C	KTAS			484	480	476	472			
	% N ₁			93.4	93.9	94.8	96.5			
	Lb/Hr/Eng			1505	1419	1354	1311			
48 000 LB		250	270	290	310	330	350	370	390	410
ISA -10°C	KTAS			463	459	455	450			
	% N ₁			89.6	90.3	91.2	93.3			
	Lb/Hr/Eng			1437	1358	1304	1270			
ISA	KTAS			473	469	465	461			
	% N ₁			92.6	92.5	93.6	95.6			
	Lb/Hr/Eng			1481	1402	1346	1313			
ISA +10°C	KTAS			484	480	476				
	% N ₁			93.9	94.5	95.7				
	Lb/Hr/Eng			1526	1445	1389				
50 000 LB		250	270	290	310	330	350	370	390	410
ISA -10°C	KTAS			463	459	455	450			
	% N ₁			90.2	91.0	92.3	94.9			
	Lb/Hr/Eng			1458	1387	1340	1323			
ISA	KTAS			473	469	465	461			
	% N ₁			93.1	93.1	94.6	97.4			
	Lb/Hr/Eng			1503	1431	1383	1369			
ISA +10°C	KTAS			484	480	476				
	% N ₁			94.5	95.2	96.9				
	Lb/Hr/Eng			1548	1475	1426				

QR1_DXCZR_019

CRUISE DATA

MACH 0.82/PACKS ON/ANTI-ICE OFF/30% C.G.

WEIGHT 28 000 LB		PRESSURE ALTITUDE (100 FT)								
		250	270	290	310	330	350	370	390	410
ISA -10°C	KTAS				470	466	462	459	459	459
	% N ₁				88.5	88.3	88.2	89.3	90.1	91.2
	Lb/Hr/Eng				1311	1211	1122	1050	996	952
ISA	KTAS				481	477	473	470	470	470
	% N ₁				90.7	90.5	90.5	90.9	92.1	93.6
	Lb/Hr/Eng				1354	1252	1161	1087	1030	986
ISA +10°C	KTAS				492	488	483	481	481	
	% N ₁				92.8	92.7	92.6	93.2	94.3	
	Lb/Hr/Eng				1395	1290	1197	1123	1067	
30 000 LB		250	270	290	310	330	350	370	390	410
ISA -10°C	KTAS				470	466	462	459	459	459
	% N ₁				88.8	88.8	88.8	89.8	90.6	92.5
	Lb/Hr/Eng				1323	1226	1140	1071	1020	983
ISA	KTAS				481	477	473	470	470	470
	% N ₁				91.0	90.9	91.0	91.6	93.0	94.9
	Lb/Hr/Eng				1367	1267	1179	1107	1055	1018
ISA +10°C	KTAS				492	488	483	481	481	
	% N ₁				93.1	93.2	93.2	93.8	95.3	
	Lb/Hr/Eng				1407	1305	1216	1144	1092	
32 000 LB		250	270	290	310	330	350	370	390	410
ISA -10°C	KTAS				470	466	462	459	459	459
	% N ₁				89.2	89.2	89.3	90.4	91.7	94.1
	Lb/Hr/Eng				1337	1243	1159	1092	1048	1020
ISA	KTAS				481	477	473	470	470	470
	% N ₁				91.4	91.4	91.7	92.4	94.1	96.6
	Lb/Hr/Eng				1380	1285	1199	1130	1085	1058
ISA +10°C	KTAS				492	488	483	481	481	
	% N ₁				93.5	93.7	93.7	94.6	96.4	
	Lb/Hr/Eng				1422	1323	1237	1168	1121	

QR1_DXCZR_020

CRUISE DATA

MACH 0.82/PACKS ON/ANTI-ICE OFF/30% C.G. (Cont'd)

WEIGHT 34 000 LB		PRESSURE ALTITUDE (100 FT)								
		250	270	290	310	330	350	370	390	410
ISA -10°C	KTAS				470	466	462	459	459	
	% N ₁				89.7	89.7	90.0	91.0	93.0	
	Lb/Hr/Eng				1354	1262	1180	1119	1081	
ISA	KTAS				481	477	473	470	470	
	% N ₁				91.9	91.9	92.3	93.3	95.4	
	Lb/Hr/Eng				1397	1303	1220	1156	1120	
ISA +10°C	KTAS				492	488	483	481		
	% N ₁				93.9	94.2	94.4	95.5		
	Lb/Hr/Eng				1440	1344	1259	1196		
36 000 LB		250	270	290	310	330	350	370	390	410
ISA -10°C	KTAS				470	466	462	459	459	
	% N ₁				90.2	90.2	90.7	92.0	94.7	
	Lb/Hr/Eng				1372	1282	1203	1149	1122	
ISA	KTAS				481	477	473	470	470	
	% N ₁				92.3	92.5	92.9	94.3	97.0	
	Lb/Hr/Eng				1415	1323	1243	1187	1164	
ISA +10°C	KTAS				492	488	483	481		
	% N ₁				94.4	94.7	95.2	96.6		
	Lb/Hr/Eng				1459	1366	1285	1226		
38 000 LB		250	270	290	310	330	350	370	390	410
ISA -10°C	KTAS				470	466	462	459		
	% N ₁				90.7	90.8	91.5	93.2		
	Lb/Hr/Eng				1391	1303	1230	1183		
ISA	KTAS				481	477	473	470		
	% N ₁				92.8	93.2	93.8	95.6		
	Lb/Hr/Eng				1436	1346	1271	1224		
ISA +10°C	KTAS				492	488	483			
	% N ₁				95.0	95.3	96.1			
	Lb/Hr/Eng				1480	1390	1313			

QR1_DXCZR_021

CRUISE DATA

MACH 0.82/PACKS ON/ANTI-ICE OFF/30% C.G. (Cont'd)

WEIGHT 40 000 LB		PRESSURE ALTITUDE (100 FT)								
		250	270	290	310	330	350	370	390	410
ISA -10°C	KTAS				470	466	462	459		
	% N ₁				91.2	91.5	92.5	94.7		
	Lb/Hr/Eng				1412	1328	1261	1226		
ISA	KTAS				481	477	473	470		
	% N ₁				93.3	93.8	94.8	97.1		
	Lb/Hr/Eng				1457	1371	1303	1269		
ISA +10°C	KTAS				492	488	483			
	% N ₁				95.6	96.0	97.1			
	Lb/Hr/Eng				1502	1415	1345			
42 000 LB		250	270	290	310	330	350	370	390	410
ISA -10°C	KTAS				470	466	462			
	% N ₁				91.6	92.3	93.6			
	Lb/Hr/Eng				1434	1356	1296			
ISA	KTAS				481	477	473			
	% N ₁				93.8	94.6	96.0			
	Lb/Hr/Eng				1478	1399	1340			
ISA +10°C	KTAS				492	488				
	% N ₁				96.1	96.8				
	Lb/Hr/Eng				1525	1443				
44 000 LB		250	270	290	310	330	350	370	390	410
ISA -10°C	KTAS				470	466	462			
	% N ₁				92.2	93.2	95.0			
	Lb/Hr/Eng				1458	1386	1340			
ISA	KTAS				481	477	473			
	% N ₁				94.5	95.5	97.4			
	Lb/Hr/Eng				1504	1431	1386			
ISA +10°C	KTAS				492					
	% N ₁				96.8					
	Lb/Hr/Eng				1551					

QR1_DXCZR_022

CRUISE DATA

MACH 0.82/PACKS ON/ANTI-ICE OFF/30% C.G. (Cont'd)

WEIGHT 46 000 LB		PRESSURE ALTITUDE (100 FT)							
		250	270	290	310	330	350	370	390 410
ISA -10°C	KTAS				470	466			
	% N ₁				93.0	94.2			
	Lb/Hr/Eng				1485	1421			
ISA	KTAS				481	477			
	% N ₁				95.3	96.6			
	Lb/Hr/Eng				1533	1469			
ISA +10°C	KTAS								
	% N ₁								
	Lb/Hr/Eng								
48 000 LB		250	270	290	310	330	350	370	390 410
ISA -10°C	KTAS				470	466			
	% N ₁				93.8	95.4			
	Lb/Hr/Eng				1516	1463			
ISA	KTAS				481	477			
	% N ₁				96.1	97.8			
	Lb/Hr/Eng				1565	1513			
ISA +10°C	KTAS								
	% N ₁								
	Lb/Hr/Eng								
50 000 LB		250	270	290	310	330	350	370	390 410
ISA -10°C	KTAS				470				
	% N ₁				94.7				
	Lb/Hr/Eng				1550				
ISA	KTAS				481				
	% N ₁				97.0				
	Lb/Hr/Eng				1601				
ISA +10°C	KTAS								
	% N ₁								
	Lb/Hr/Eng								

QR1_DXCZRZ_023

CRUISE DATA

LONG RANGE CRUISE/PACKS ON/ANTI-ICE OFF/30% C.G.

WEIGHT 28 000 LB		PRESSURE ALTITUDE (100 FT)									
		100	150	200	230	250	270	290	330	370	410
ISA -10°C	MACH	.411	.449	.480	.510	.531	.551	.572	.621	.665	.707
	KTAS	258	276	289	303	313	322	331	353	372	396
	% N ₁	58.8	62.1	64.7	67.0	68.5	69.9	71.2	74.1	76.9	81.4
	Lb/Hr/Eng	802	760	710	700	691	683	676	670	661	675
ISA	MACH	.408	.445	.479	.509	.529	.550	.571	.615	.660	.708
	KTAS	261	279	294	309	319	329	338	358	379	406
	% N ₁	59.8	63.1	66.0	68.5	70.0	71.5	72.8	75.6	78.7	83.5
	Lb/Hr/Eng	814	770	726	718	709	702	695	684	678	700
ISA +10°C	MACH	.408	.442	.474	.506	.526	.545	.566	.610	.657	.705
	KTAS	265	282	297	313	323	332	342	363	386	414
	% N ₁	60.9	64.1	67.1	69.7	71.3	72.8	74.2	77.2	80.4	85.4
	Lb/Hr/Eng	829	784	738	733	725	716	711	701	698	720
30 000 LB		100	150	200	230	250	270	290	330	370	410
ISA -10°C	MACH	.423	.456	.493	.525	.546	.565	.587	.638	.682	.726
	KTAS	265	280	297	312	322	330	340	363	382	407
	% N ₁	60.2	63.1	66.1	68.5	70.0	71.2	72.6	75.5	78.4	83.4
	Lb/Hr/Eng	841	787	747	739	730	721	716	711	705	728
ISA	MACH	.421	.453	.493	.523	.543	.564	.584	.633	.678	.726
	KTAS	269	284	303	317	327	336	346	368	389	416
	% N ₁	61.3	64.1	67.5	69.9	71.4	72.8	74.2	77.1	80.2	85.5
	Lb/Hr/Eng	857	800	767	757	746	740	733	728	725	751
ISA +10°C	MACH	.418	.452	.490	.521	.541	.561	.581	.629	.680	.726
	KTAS	272	289	307	323	332	342	351	374	399	426
	% N ₁	62.2	65.4	68.7	71.3	72.8	74.3	75.7	78.7	82.2	87.6
	Lb/Hr/Eng	869	819	784	776	766	759	752	747	753	777

QR1_DXCZR_024

CRUISE DATA

LONG RANGE CRUISE/PACKS ON/ANTI-ICE OFF/30% C.G.
(Cont'd)

WEIGHT 32 000 LB		PRESSURE ALTITUDE (100 FT)									
		100	150	200	230	250	270	290	330	370	410
ISA -10°C	MACH	.435	.462	.508	.538	.558	.580	.603	.652	.696	.744
	KTAS	272	284	306	320	329	339	349	371	390	417
	% N ₁	61.5	63.9	67.6	69.8	71.2	72.6	74.0	76.8	79.8	85.6
	Lb/Hr/Eng	879	814	789	778	767	761	756	750	747	779
ISA	MACH	.432	.461	.507	.535	.555	.576	.596	.645	.694	.741
	KTAS	276	289	312	325	334	344	353	375	398	425
	% N ₁	62.6	65.2	69.0	71.2	72.6	74.0	75.4	78.3	81.7	87.6
	Lb/Hr/Eng	896	833	810	795	785	777	770	766	772	803
ISA +10°C	MACH	.429	.460	.506	.534	.553	.575	.594	.645	.694	.744
	KTAS	279	294	317	331	340	351	359	383	407	437
	% N ₁	63.5	66.5	70.4	72.7	74.1	75.6	77.0	80.1	83.6	89.9
	Lb/Hr/Eng	908	855	831	817	806	802	793	792	798	832
34 000 LB		100	150	200	230	250	270	290	330	370	410
ISA -10°C	MACH	.444	.472	.523	.552	.572	.595	.619	.664	.707	.753
	KTAS	278	290	315	328	337	347	358	377	396	422
	% N ₁	62.6	65.1	69.1	71.1	72.4	73.9	75.3	77.9	81.1	87.5
	Lb/Hr/Eng	913	850	832	818	807	802	798	787	790	825
ISA	MACH	.442	.471	.520	.549	.569	.588	.612	.660	.706	.753
	KTAS	282	295	319	333	342	351	362	384	405	432
	% N ₁	63.7	66.4	70.3	72.5	73.9	75.2	76.7	79.6	83.1	89.7
	Lb/Hr/Eng	931	870	849	836	826	817	815	810	818	854
ISA +10°C	MACH	.439	.469	.519	.548	.567	.587	.613	.660	.706	.751
	KTAS	285	299	325	339	349	358	371	392	414	440
	% N ₁	64.8	67.6	71.8	74.0	75.4	76.9	78.5	81.4	85.1	91.7
	Lb/Hr/Eng	949	889	873	860	850	842	843	837	844	877

QR1_DXCZRZ_025

CRUISE DATA

LONG RANGE CRUISE/PACKS ON/ANTI-ICE OFF/30% C.G.
(Cont'd)

WEIGHT 36 000 LB		PRESSURE ALTITUDE (100 FT)									
		100	150	200	230	250	270	290	330	370	410
ISA -10°C	MACH	.453	.486	.536	.564	.583	.607	.632	.677	.722	.757
	KTAS	283	298	322	335	344	354	366	385	404	424
	% N ₁	63.7	66.5	70.3	72.3	73.6	75.0	76.4	79.0	82.7	89.2
	Lb/Hr/Eng	948	894	872	857	845	840	838	829	839	870
ISA	MACH	.450	.483	.532	.562	.582	.601	.629	.675	.724	.759
	KTAS	287	303	327	341	350	359	372	393	415	435
	% N ₁	64.8	67.7	71.6	73.8	75.2	76.4	78.1	80.9	84.9	91.5
	Lb/Hr/Eng	965	913	891	879	869	858	861	857	872	901
ISA +10°C	MACH	.447	.481	.532	.561	.580	.600	.630	.677	.721	.756
	KTAS	291	307	333	347	356	366	381	403	423	443
	% N ₁	65.8	69.0	73.2	75.4	76.7	78.1	79.9	82.9	86.8	93.6
	Lb/Hr/Eng	983	934	916	904	892	885	891	889	897	927
38 000 LB		100	150	200	230	250	270	290	330	370	410
ISA -10°C	MACH	.462	.499	.546	.575	.595	.620	.644	.690	.737	.762
	KTAS	289	307	329	342	351	362	373	392	413	427
	% N ₁	64.8	67.9	71.4	73.4	74.7	76.1	77.5	80.2	84.4	91.4
	Lb/Hr/Eng	985	940	909	895	884	882	877	874	891	923
ISA	MACH	.460	.496	.544	.574	.594	.617	.641	.690	.738	.761
	KTAS	294	311	334	348	358	368	380	402	424	436
	% N ₁	65.9	69.1	72.8	75.0	76.3	77.7	79.2	82.2	86.6	93.6
	Lb/Hr/Eng	1005	958	932	920	911	906	903	906	924	952
ISA +10°C	MACH	.455	.495	.544	.573	.593	.617	.642	.692	.738	
	KTAS	296	316	341	355	365	376	388	411	433	
	% N ₁	66.8	70.4	74.3	76.6	77.9	79.5	81.0	84.2	88.7	
	Lb/Hr/Eng	1018	982	959	947	938	936	934	938	954	

QR1_DXC0RZ_026

CRUISE DATA

LONG RANGE CRUISE/PACKS ON/ANTI-ICE OFF/30% C.G.
(Cont'd)

WEIGHT 40 000 LB		PRESSURE ALTITUDE (100 FT)									
		100	150	200	230	250	270	290	330	370	410
ISA -10°C	MACH	.468	.511	.557	.586	.608	.634	.655	.699	.749	.764
	KTAS	293	314	335	348	358	370	379	398	419	428
	% N ₁	65.6	69.1	72.5	74.5	75.8	77.2	78.5	81.4	86.2	93.8
	Lb/Hr/Eng	1015	982	950	935	927	925	918	916	939	978
ISA	MACH	.467	.509	.557	.585	.606	.633	.654	.702	.748	.764
	KTAS	298	319	342	355	365	378	387	408	429	438
	% N ₁	66.8	70.4	74.0	76.1	77.4	79.0	80.3	83.4	88.3	96.2
	Lb/Hr/Eng	1037	1005	976	961	953	955	948	952	971	1012
ISA +10°C	MACH	.463	.508	.554	.584	.607	.634	.655	.700	.751	
	KTAS	301	324	347	361	373	387	396	416	440	
	% N ₁	67.9	71.8	75.4	77.7	79.1	80.8	82.1	85.3	90.6	
	Lb/Hr/Eng	1056	1030	1001	989	984	987	980	981	1008	
42 000 LB		100	150	200	230	250	270	290	330	370	410
ISA -10°C	MACH	.475	.522	.568	.598	.622	.646	.666	.711	.755	
	KTAS	297	320	342	355	366	378	385	404	423	
	% N ₁	66.4	70.2	73.5	75.6	76.9	78.3	79.5	82.6	87.7	
	Lb/Hr/Eng	1049	1022	990	977	971	968	959	963	985	
ISA	MACH	.474	.521	.567	.596	.620	.644	.667	.711	.755	
	KTAS	302	327	348	362	373	385	395	414	433	
	% N ₁	67.7	71.6	75.0	77.1	78.5	80.0	81.4	84.6	90.0	
	Lb/Hr/Eng	1074	1048	1017	1004	999	997	994	997	1019	
ISA +10°C	MACH	.472	.519	.566	.596	.621	.645	.668	.712	.755	
	KTAS	307	331	355	369	382	393	404	423	443	
	% N ₁	68.9	72.9	76.6	78.8	80.3	81.8	83.3	86.7	92.2	
	Lb/Hr/Eng	1098	1074	1046	1032	1031	1030	1027	1031	1052	

QR1_DXCZR_027

CRUISE DATA

LONG RANGE CRUISE/PACKS ON/ANTI-ICE OFF/30% C.G.
(Cont'd)

WEIGHT 44 000 LB		PRESSURE ALTITUDE (100 FT)									
		100	150	200	230	250	270	290	330	370	410
ISA -10°C	MACH	.485	.532	.579	.610	.635	.656	.680	.722	.758	
	KTAS	303	327	348	363	374	383	393	411	424	
	% N ₁	67.5	71.3	74.5	76.6	77.9	79.2	80.6	83.9	89.2	
	Lb/Hr/Eng	1090	1064	1031	1020	1016	1008	1008	1013	1029	
ISA	MACH	.483	.531	.577	.609	.633	.655	.680	.725	.760	
	KTAS	309	333	355	370	381	391	402	422	436	
	% N ₁	68.8	72.7	76.1	78.2	79.6	81.0	82.5	86.1	91.5	
	Lb/Hr/Eng	1116	1091	1060	1050	1045	1040	1043	1052	1068	
ISA +10°C	MACH	.482	.530	.577	.609	.635	.658	.681	.724	.757	
	KTAS	313	338	361	377	390	401	412	430	444	
	% N ₁	70.0	74.1	77.6	79.9	81.4	82.9	84.4	88.1	93.6	
	Lb/Hr/Eng	1142	1119	1090	1083	1081	1077	1077	1083	1099	
46 000 LB		100	150	200	230	250	270	290	330	370	410
ISA -10°C	MACH	.496	.542	.590	.622	.645	.666	.692	.739	.762	
	KTAS	311	333	355	370	380	389	400	420	427	
	% N ₁	68.6	72.3	75.5	77.6	78.8	80.1	81.7	85.5	91.0	
	Lb/Hr/Eng	1136	1105	1074	1064	1057	1050	1056	1071	1081	
ISA	MACH	.494	.542	.588	.622	.646	.668	.691	.736	.762	
	KTAS	316	339	361	377	389	399	409	428	437	
	% N ₁	69.9	73.7	77.1	79.3	80.7	82.0	83.6	87.5	93.3	
	Lb/Hr/Eng	1162	1135	1103	1096	1093	1089	1091	1102	1117	
ISA +10°C	MACH	.492	.541	.587	.623	.649	.670	.692	.739	.761	
	KTAS	320	345	368	386	399	408	419	439	446	
	% N ₁	71.1	75.2	78.6	81.0	82.6	83.9	85.5	89.7	95.5	
	Lb/Hr/Eng	1189	1164	1134	1132	1131	1127	1126	1142	1154	

QR1_DXCZR_028

CRUISE DATA

LONG RANGE CRUISE/PACKS ON/ANTI-ICE OFF/30% C.G.
(Cont'd)

WEIGHT 48 000 LB		PRESSURE ALTITUDE (100 FT)									
		100	150	200	230	250	270	290	330	370	410
ISA -10°C	MACH	.508	.552	.600	.633	.657	.679	.700	.746	.765	
	KTAS	318	339	361	376	387	396	405	424	429	
	% N ₁	69.8	73.2	76.4	78.5	79.8	81.1	82.6	86.8	93.0	
	Lb/Hr/Eng	1184	1147	1116	1108	1103	1100	1099	1116	1138	
ISA	MACH	.505	.552	.598	.633	.657	.681	.701	.746	.764	
	KTAS	323	346	368	384	395	406	415	434	438	
	% N ₁	71.1	74.7	78.0	80.2	81.6	83.1	84.6	89.0	95.3	
	Lb/Hr/Eng	1210	1178	1147	1144	1138	1139	1138	1152	1173	
ISA +10°C	MACH	.503	.550	.599	.635	.658	.681	.700	.748		
	KTAS	327	351	375	394	404	415	423	445		
	% N ₁	72.3	76.2	79.7	82.1	83.4	85.0	86.5	91.2		
	Lb/Hr/Eng	1239	1209	1182	1181	1174	1175	1170	1191		
50 000 LB		100	150	200	230	250	270	290	330	370	410
ISA -10°C	MACH	.518	.562	.610	.644	.667	.690	.708	.752		
	KTAS	324	345	367	383	393	403	410	428		
	% N ₁	70.9	74.1	77.3	79.4	80.7	82.1	83.6	88.2		
	Lb/Hr/Eng	1230	1189	1159	1152	1146	1148	1144	1162		
ISA	MACH	.515	.561	.610	.644	.666	.691	.710	.752		
	KTAS	329	351	375	391	401	413	420	437		
	% N ₁	72.1	75.6	79.0	81.2	82.5	84.1	85.7	90.5		
	Lb/Hr/Eng	1255	1221	1194	1187	1181	1187	1184	1200		
ISA +10°C	MACH	.515	.560	.612	.645	.667	.690	.707	.752		
	KTAS	335	358	383	400	410	421	427	447		
	% N ₁	73.5	77.1	80.7	83.0	84.3	85.9	87.5	92.5		
	Lb/Hr/Eng	1288	1254	1232	1226	1218	1220	1214	1237		

QR1_DXCZR_029

CRUISE CEILING

MACH 0.74/PACKS ON/ANTI-ICE OFF

WEIGHT (1000 LB)	MAXIMUM PRESSURE ALTITUDE (FT)			
	ISA - 10° C	ISA	ISA + 10° C	ISA + 20° C
28	41000	41000	41000	41000
30	41000	41000	41000	41000
32	41000	41000	41000	41000
34	41000	41000	41000	41000
36	41000	41000	41000	40590
38	41000	41000	41000	39740
40	41000	41000	40330	38900
42	40730	40670	39490	38120
44	39880	39820	38700	37330
46	39050	38990	37960	36580
48	38220	38160	37220	35750
50	37400	37340	36490	34710

QR1_DXCZRZ_030

MACH 0.77/PACKS ON/ANTI-ICE OFF

WEIGHT (1000 LB)	MAXIMUM PRESSURE ALTITUDE (FT)			
	ISA - 10° C	ISA	ISA + 10° C	ISA + 20° C
28	41000	41000	41000	41000
30	41000	41000	41000	41000
32	41000	41000	41000	41000
34	41000	41000	41000	40500
36	41000	41000	41000	39680
38	41000	41000	40550	38870
40	41000	41000	39710	38110
42	40330	40260	38890	37330
44	39490	39420	38150	36580
46	38650	38580	37410	35720
48	37810	37740	36690	34580
50	36980	36910	35930	33430

QR1_DXCZRZ_031

BOMBARDIER CHALLENGER 605	PERF-03-30
	<i>Oct 05/06</i>

CRUISE CEILING

MACH 0.80/PACKS ON/ANTI-ICE OFF

WEIGHT (1000 LB)	MAXIMUM PRESSURE ALTITUDE (FT)			
	ISA - 10° C	ISA	ISA + 10° C	ISA + 20° C
28	41000	41000	41000	40790
30	41000	41000	41000	40050
32	41000	41000	41000	39270
34	41000	41000	40650	38500
36	41000	41000	39790	37730
38	40710	40620	38940	36940
40	39820	39740	38180	36190
42	38920	38840	37410	34850
44	38010	37930	36670	33310
46	37110	37030	35890	31360
48	36270	36180	34680	
50	35330	35220	33470	

QR1_DXCZ_032

MACH 0.82/PACKS ON/ANTI-ICE OFF

WEIGHT (1000 LB)	MAXIMUM PRESSURE ALTITUDE (FT)			
	ISA - 10° C	ISA	ISA + 10° C	ISA + 20° C
28	41000	41000	40820	37770
30	41000	41000	39950	37000
32	41000	41000	39040	36260
34	40460	40360	38250	33370
36	39500	39390	37440	
38	38520	38400	36660	
40	37530	37400	35700	
42	36570	36440	34050	
44	35520	35350	32280	
46	34380	34210	30220	
48	33260	33070		
50	32130	31940		

QR1_DXCZ_033

QUICK REFERENCE HANDBOOK <i>PSP 605-15</i>	CRUISE DATA
--	--------------------

CRUISE CEILING

LONG RANGE CRUISE/PACKS ON/ANTI-ICE OFF

WEIGHT (1000 LB)	MAXIMUM PRESSURE ALTITUDE (FT)			
	ISA - 10° C	ISA	ISA + 10° C	ISA + 20° C
28	41000	41000	41000	41000
30	41000	41000	41000	41000
32	41000	41000	41000	41000
34	41000	41000	41000	41000
36	41000	41000	41000	40180
38	41000	41000	40740	39290
40	41000	41000	39870	38480
42	40360	40290	39020	37660
44	39500	39440	38270	36900
46	38650	38590	37510	36110
48	37800	37740	36740	35080
50	36980	36910	36000	34000

QR1_DXCZ_034

BOMBARDIER CHALLENGER 605	<i>PERF-03-32</i>
	<i>Oct 05/06</i>

THIS PAGE INTENTIONALLY LEFT BLANK

TRAINING PURPOSES ONLY

<i>QUICK REFERENCE HANDBOOK</i> <i>PSP 605-15</i>	<i>CRUISE DATA</i>
--	---------------------------

SECTOR FUEL RANGE DATA

TRIP FUEL (LB) – CRUISE ALTITUDE 25,000 FEET – ISA

(Total Fuel = Trip Fuel[†] + NBAA / IFR Reserves[★])

CRUISE MACH NUMBER 0.72

STILL AIR RANGE (NM)	TAKE-OFF WEIGHT (LB)			
	35 000	40 000	45 000	48 200
125	876	929*	958*	1000*
200	1259	1303*	1357*	1398*
400	2387	2454	2536*	2599*
800	4629	4738	4873*	4975*
1000	5743	5872	6031*	6151*
1500	8513	8687	8901	9063*
2000	11256	11475	11737	11934
2500	13976	14237	14543	14772
3000	16671	16975	17323	17580

CRUISE MACH NUMBER 0.74

125	886	934*	963*	1000*
200	1277	1319*	1371*	1409*
400	2443	2507	2584*	2641*
800	4759	4865	4991*	5082*
1000	5911	6036	6185*	6293*
1500	8770	8942	9145	9291*
2000	11602	11820	12071	12252
2500	14407	14671	14967	15179
3000	17185	17494	17836	18076

CRUISE MACH NUMBER 0.77

125	899	934*	963*	1000*
200	1310	1348*	1397*	1433*
400	2539	2599	2674*	2729*
800	4983	5085	5208*	5298*
1000	6199	6319	6465*	6572*
1500	9217	9383	9581	9726*
2000	12207	12418	12662	12841
2500	15167	15426	15713	15922
3000	18099	18403	18737	18973

QR1_DXSf_001

[†] = Trip fuel includes 1 min. take-off (50 lb), climb, cruise & descent;
Taxi and reserve fuel not included.

[★] = NBAA / IFR reserve fuel tables are given in PERF-07-1 thru 2.

* = Landing weight limited (38,000 lb)

** = Fuel load limited (20,000 lb)

SECTOR FUEL RANGE DATA

TRIP FUEL (LB) – CRUISE ALTITUDE 29,000 FEET – ISA

(Total Fuel = Trip Fuel† + NBAA / IFR Reserves★)

CRUISE MACH NUMBER 0.72

STILL AIR RANGE (NM)	TAKE-OFF WEIGHT (LB)			
	35 000	40 000	45 000	48 200
200	1191	1249*	1331*	1378*
500	2677	2781	2909*	3004*
1000	5126	5302	5520*	5683*
1500	7546	7784	8079	8302*
2000	9938	10232	10594	10869
2500	12304	12650	13072	13391
3000	14646	15041	15517	15875
3500	16963	17407	17932	18325
4000	19256	19747	20320**	20744**

CRUISE MACH NUMBER 0.74

200	1203	1257*	1341*	1386*
500	2735	2831	2953*	3044*
1000	5264	5424	5625*	5783*
1500	7764	7982	8251	8462*
2000	10237	10508	10838	11094
2500	12682	13005	13390	13686
3000	15102	15475	15912	16243
3500	17495	17918	18404	18768
4000	19864	20335**	20870**	21265**

CRUISE MACH NUMBER 0.77

200	1224	1275*	1361*	1402*
500	2838	2930	3039*	3123*
1000	5501	5657	5841*	5980*
1500	8135	8347	8597	8785*
2000	10741	11004	11315	11546
2500	13322	13633	13997	14267
3000	15876	16234	16647	16952
3500	18405	18810	19269	19605
4000	20911**	21359**	21863**	22229**

- † = Trip fuel includes 1 min. take-off (50 lb), climb, cruise & descent;
Taxi and reserve fuel not included.
- ★ = NBAA / IFR reserve fuel tables are given in PERF-07-1 thru 2.
- * = Landing weight limited (38,000 lb)
- ** = Fuel load limited (20,000 lb)

SECTOR FUEL RANGE DATA

**TRIP FUEL (LB) – CRUISE ALTITUDE 29,000 FEET – ISA
(Cont'd)**

(Total Fuel = Trip Fuel[†] + NBAA / IFR Reserves[★])

CRUISE MACH NUMBER 0.80

STILL AIR RANGE (NM)	TAKE-OFF WEIGHT (LB)			
	35 000	40 000	45 000	48 200
200	1256	1301*	1375*	1416*
500	2991	3077	3180*	3255*
1000	5856	6003	6181*	6308*
1500	8693	8891	9135	9310*
2000	11503	11746	12046	12264
2500	14287	14575	14921	15177
3000	17045	17377	17767	18053
3500	19778	20153**	20586**	20899**
4000	22487**			

- [†] = Trip fuel includes 1 min. take-off (50 lb), climb, cruise & descent;
Taxi and reserve fuel not included.
- [★] = NBAA / IFR reserve fuel tables are given in PERF-07-1 thru 2.
- * = Landing weight limited (38,000 lb)
- ** = Fuel load limited (20,000 lb)

SECTOR FUEL RANGE DATA

TRIP FUEL (LB) – CRUISE ALTITUDE 33,000 FEET – ISA

(Total Fuel = Trip Fuel[†] + NBAA / IFR Reserves[★])

CRUISE MACH NUMBER 0.72

STILL AIR RANGE (NM)	TAKE-OFF WEIGHT (LB)			
	35 000	40 000	45 000	48 200
200	1169	1249*	1331*	1378*
500	2480	2618	2784*	2904*
1000	4653	4893	5189*	5405*
1500	6789	7117	7525	7827*
2000	8892	9297	9803	10179*
2500	10966	11439	12029	12469
3000	13012	13547	14210	14707
3500	15030	15626	16353	16899
4000	17023	17676	18463	19050

CRUISE MACH NUMBER 0.74

200	1178	1257*	1341*	1386*
500	2520	2650	2804*	2917*
1000	4751	4978	5246*	5444*
1500	6949	7255	7628	7901*
2000	9118	9491	9956	10297
2500	11258	11693	12234	12636
3000	13370	13865	14471	14925
3500	15457	16008	16673	17170
4000	17518	18123	18845	19379

CRUISE MACH NUMBER 0.77

200	1194	1275*	1361*	1402*
500	2597	2714	2858*	2965*
1000	4940	5140	5388*	5575*
1500	7251	7522	7862	8117*
2000	9530	9868	10285	10600
2500	11780	12179	12665	13032
3000	14002	14459	15008	15420
3500	16196	16710	17317	17770
4000	18364	18932	19596	20085**

QR1_DXSf_004

[†] = Trip fuel includes 1 min. take-off (50 lb), climb, cruise & descent;
Taxi and reserve fuel not included.

[★] = NBAA / IFR reserve fuel tables are given in PERF-07-1 thru 2.

* = Landing weight limited (38,000 lb)

** = Fuel load limited (20,000 lb)

SECTOR FUEL RANGE DATA

TRIP FUEL (LB) – CRUISE ALTITUDE 33,000 FEET – ISA
(Cont’d)

(Total Fuel = Trip Fuel † + NBAA / IFR Reserves★)

CRUISE MACH NUMBER 0.80				
STILL AIR RANGE (NM)	TAKE-OFF WEIGHT (LB)			
	35 000	40 000	45 000	48 200
200	1219	1301*	1375*	1416*
500	2715	2824	2957*	3062*
1000	5226	5416	5645*	5827*
1500	7699	7963	8278	8522*
2000	10140	10469	10862	11161
2500	12551	12940	13401	13751
3000	14934	15378	15901	16296
3500	17287	17786	18366	18800
4000	19614	20165**	20799**	21268**

CRUISE MACH NUMBER 0.82				
200	1244	1326*	1375*	1416*
500	2849	2961	3107*	3222*
1000	5540	5746	6011*	6222*
1500	8189	8477	8840	9129*
2000	10801	11158	11607	11960
2500	13378	13798	14321	14729
3000	15921	16401	16988	17444
3500	18431	18970	19617	20113**
4000	20910**	21505**	22209**	

- † = Trip fuel includes 1 min. take–off (50 lb), climb, cruise & descent;
 Taxi and reserve fuel not included.
 ★ = NBAA / IFR reserve fuel tables are given in PERF–07–1 thru 2.
 * = Landing weight limited (38,000 lb)
 ** = Fuel load limited (20,000 lb)

SECTOR FUEL RANGE DATA

TRIP FUEL (LB) – CRUISE ALTITUDE 37,000 FEET – ISA

(Total Fuel = Trip Fuel[†] + NBAA / IFR Reserves[★])

CRUISE MACH NUMBER 0.72

STILL AIR RANGE (NM)	TAKE-OFF WEIGHT (LB)			
	35 000	40 000	45 000	48 200
200	1169	1249*	1331*	1378*
500	2362	2537	2749*	2910*
1000	4342	4663	5055*	5364*
1500	6273	6720	7268	7698*
2000	8159	8718	9402	9932*
2500	10007	10663	11468	12084
3000	11819	12563	13472	14166
3500	13597	14423	15424	16185
4000	15343	16246	17329	18149

CRUISE MACH NUMBER 0.74

200	1178	1257*	1341*	1386*
500	2384	2547	2749*	2901*
1000	4403	4694	5064*	5352*
1500	6376	6780	7292	7692*
2000	8307	8814	9446	9940*
2500	10202	10800	11539	12111
3000	12063	12742	13579	14219
3500	13893	14648	15570	16271
4000	15693	16519	17517	18274

CRUISE MACH NUMBER 0.77

200	1194	1275*	1361*	1402*
500	2432	2587	2775*	2923*
1000	4528	4803	5143*	5418*
1500	6583	6959	7431	7806*
2000	8601	9066	9651	10111*
2500	10587	11129	11812	12346
3000	12541	13154	13921	14520
3500	14466	15147	15987	16640
4000	16363	17108	18016	18716

[†] = Trip fuel includes 1 min. take–off (50 lb), climb, cruise & descent; Taxi and reserve fuel not included.
[★] = NBAA / IFR reserve fuel tables are given in PERF–07–1 thru 2.
 * = Landing weight limited (38,000 lb)
 ** = Fuel load limited (20,000 lb)

SECTOR FUEL RANGE DATA

TRIP FUEL (LB) – CRUISE ALTITUDE 37,000 FEET – ISA
(Cont’d)

(Total Fuel = Trip Fuel[†] + NBAA / IFR Reserves[★])

CRUISE MACH NUMBER 0.80				
STILL AIR RANGE (NM)	TAKE-OFF WEIGHT (LB)			
	35 000	40 000	45 000	48 200
200	1219	1301*	1375*	1416*
500	2519	2666	2862*	3018*
1000	4749	5010	5374*	5672*
1500	6939	7294	7789	8200*
2000	9090	9529	10129	10629
2500	11206	11723	12411	12979
3000	13286	13878	14644	15269
3500	15334	15997	16835	17509
4000	17350	18080	18988	19706

CRUISE MACH NUMBER 0.82				
200	1244	1326*	1375*	1416*
500	2636	2799	3040*	3222*
1000	5036	5342	5792*	6139*
1500	7382	7802	8413	8940*
2000	9680	10198	10934	11522
2500	11933	12540	13378	14046
3000	14143	14835	15759	16492
3500	16313	17085	18091	18876
4000	18445	19293	20375**	21209**

- [†] = Trip fuel includes 1 min. take–off (50 lb), climb, cruise & descent;
 Taxi and reserve fuel not included.
- [★] = NBAA / IFR reserve fuel tables are given in PERF–07–1 thru 2.
- ^{*} = Landing weight limited (38,000 lb)
- ^{**} = Fuel load limited (20,000 lb)

SECTOR FUEL RANGE DATA

TRIP FUEL (LB) – CRUISE ALTITUDE 41,000 FEET – ISA

(Total Fuel = Trip Fuel[†] + NBAA / IFR Reserves[★])

CRUISE MACH NUMBER 0.72

STILL AIR RANGE (NM)	TAKE-OFF WEIGHT (LB)			
	35 000	40 000	45 000	48 200
200	1169	1249*	1331*	1378*
500	2316	2553	2749*	2910*
1000	4195	4650	5095*	5364*
1500	6007	6641	7299	7735*
2000	7760	8547	9432	9967*
2500	9462	10381	11433	12092
3000	11117	12154	13347	14149
3500	12728	13873	15188	16084
4000	14300	15544	16967	17942

CRUISE MACH NUMBER 0.74

200	1178	1257*	1341*	1386*
500	2321	2546	2749*	2901*
1000	4214	4640	5081*	5352*
1500	6045	6637	7286	7710*
2000	7823	8555	9407	9942*
2500	9556	10406	11414	12076
3000	11246	12202	13340	14117
3500	12897	13950	15198	16063
4000	14512	15655	17000	17937

CRUISE MACH NUMBER 0.77

200	1194	1275*	1361*	1402*
500	2348	2565	2775*	2923*
1000	4293	4699	5142*	5418*
1500	6181	6736	7389	7811*
2000	8019	8701	9539	10081*
2500	9812	10606	11583	12260
3000	11565	12459	13553	14321
3500	13280	14266	15462	16306
4000	14960	16030	17319	18228

QR1_DXSF_008

[†] = Trip fuel includes 1 min. take-off (50 lb), climb, cruise & descent;
Taxi and reserve fuel not included.

[★] = NBAA / IFR reserve fuel tables are given in PERF-07-1 thru 2.

* = Landing weight limited (38,000 lb)

** = Fuel load limited (20,000 lb)

SECTOR FUEL RANGE DATA

TRIP FUEL (LB) – CRUISE ALTITUDE 41,000 FEET – ISA
(Cont’d)

(Total Fuel = Trip Fuel[†] + NBAA / IFR Reserves[★])

CRUISE MACH NUMBER 0.80				
STILL AIR RANGE (NM)	TAKE-OFF WEIGHT (LB)			
	35 000	40 000	45 000	48 200
200	1219	1301*	1375*	1416*
500	2419	2638	2862*	3018*
1000	4477	4904	5371*	5672*
1500	6468	7064	7753	8200*
2000	8408	9136	10032	10600
2500	10307	11136	12169	12893
3000	12168	13084	14236	15101
3500	13992	14990	16234	17244
4000	15783	16857	18179	19336

CRUISE MACH NUMBER 0.82				
200	1244	1326*	1375*	1416*
500	2572	2799	3040*	3222*
1000	4796	5286	5792*	6139*
1500	6950	7671	8413	8940*
2000	9034	9970	10934	11522
2500	11060	12039	13225	14046
3000	13031	14121	15507	16492
3500	14952	16144	17726	18876
4000	16827	18113	19892	21209**

- [†] = Trip fuel includes 1 min. take–off (50 lb), climb, cruise & descent;
 Taxi and reserve fuel not included.
[★] = NBAA / IFR reserve fuel tables are given in PERF–07–1 thru 2.
 * = Landing weight limited (38,000 lb)
 ** = Fuel load limited (20,000 lb)

BOMBARDIER CHALLENGER 605	<i>PERF-04-10</i>
	<i>Oct 05/06</i>

THIS PAGE INTENTIONALLY LEFT BLANK

TRAINING PURPOSES ONLY

<i>QUICK REFERENCE HANDBOOK</i> <i>PSP 605-15</i>	SECTOR FUEL DATA
--	-------------------------

DESCENT DATA

0.72 M / 250 KIAS / PACKS ON / ANTI-ICE OFF / 30% C.G.
 (3,000 fpm max. ROD - Sea level Final Altitude)

Initial Weight 28 000 LB		PRESSURE ALTITUDE (100 FT)									
		050	100	150	200	250	300	350	370	390	410
ISA -10°C	TIME (min)	2.5	4.9	7.3	9.7	12.0	14.4	16.9	18.0	19.2	20.7
	DIST (nam)	10.8	21.6	33.3	45.7	58.7	73.4	90.2	97.5	106.1	115.6
	FUEL (lb)	36	65	95	125	154	185	222	239	259	280
ISA	TIME (min)	2.6	5.0	7.4	9.8	12.0	14.3	16.6	17.5	18.6	19.8
	DIST (nam)	11.1	22.3	34.3	47.0	60.1	74.2	89.9	96.4	104.0	112.2
	FUEL (lb)	38	68	98	128	155	182	214	227	243	260
ISA +10°C	TIME (min)	2.6	5.1	7.5	9.8	12.1	14.3	16.4	17.3	18.3	19.3
	DIST (nam)	11.5	23.0	35.3	48.2	61.6	75.6	90.5	96.5	103.4	111.0
	FUEL (lb)	39	70	100	130	156	182	209	220	233	247
IDW 30 000 LB		050	100	150	200	250	300	350	370	390	410
ISA -10°C	TIME (min)	2.7	5.2	7.7	10.2	12.6	15.1	17.8	18.9	20.2	21.5
	DIST (nam)	11.4	22.9	35.2	48.3	62.0	77.4	94.9	102.3	111.0	120.3
	FUEL (lb)	39	69	101	133	162	195	234	251	271	292
ISA	TIME (min)	2.7	5.3	7.8	10.3	12.7	15.1	17.5	18.4	19.5	20.7
	DIST (nam)	11.8	23.6	36.3	49.7	63.5	78.3	94.7	101.4	109.0	117.3
	FUEL (lb)	40	71	103	135	164	192	225	239	255	272
ISA +10°C	TIME (min)	2.8	5.4	7.9	10.4	12.8	15.1	17.3	18.2	19.2	20.3
	DIST (nam)	12.1	24.3	37.3	51.0	65.0	79.8	95.4	101.6	108.7	116.2
	FUEL (lb)	41	74	106	137	165	192	220	232	245	259
IDW 32 000 LB		050	100	150	200	250	300	350	370	390	410
ISA -10°C	TIME (min)	2.8	5.5	8.1	10.7	13.2	15.9	18.6	19.7	21.0	22.3
	DIST (nam)	12.0	24.1	37.0	50.7	65.0	81.1	99.1	106.6	115.2	124.3
	FUEL (lb)	41	73	106	139	170	204	244	262	281	302
ISA	TIME (min)	2.9	5.6	8.2	10.8	13.3	15.8	18.3	19.3	20.4	21.6
	DIST (nam)	12.4	24.8	38.1	52.1	66.6	82.1	99.0	105.8	113.5	121.6
	FUEL (lb)	42	75	109	142	172	201	236	250	265	282
ISA +10°C	TIME (min)	2.9	5.6	8.3	10.9	13.4	15.8	18.1	19.0	20.1	21.1
	DIST (nam)	12.8	25.6	39.2	53.5	68.2	83.6	99.8	106.2	113.3	120.9
	FUEL (lb)	43	77	111	144	173	201	231	242	256	270

QR1_DXDSC_001

DESCENT DATA

0.72 M / 250 KIAS / PACKS ON / ANTI-ICE OFF / 30% C.G.
(Cont'd)
 (3,000 fpm max. ROD - Sea level Final Altitude)

Initial Weight 34 000 LB		PRESSURE ALTITUDE (100 FT)									
		050	100	150	200	250	300	350	370	390	410
ISA -10°C	TIME (min)	3.0	5.7	8.5	11.2	13.8	16.5	19.3	20.4	21.7	23.0
	DIST (nam)	12.5	25.1	38.6	52.9	67.7	84.3	102.8	110.3	118.8	127.6
	FUEL (lb)	42	76	110	145	177	213	253	271	290	310
ISA	TIME (min)	3.0	5.8	8.6	11.3	13.9	16.4	19.0	20.0	21.1	22.3
	DIST (nam)	12.9	26.0	39.8	54.4	69.4	85.4	102.9	109.7	117.4	125.4
	FUEL (lb)	44	79	113	148	179	210	245	259	275	291
ISA +10°C	TIME (min)	3.0	5.9	8.7	11.4	14.0	16.5	18.9	19.8	20.8	21.9
	DIST (nam)	13.3	26.8	41.0	55.8	71.1	87.1	103.8	110.3	117.4	124.9
	FUEL (lb)	45	81	116	150	181	209	240	252	265	279
IDW 36 000 LB		050	100	150	200	250	300	350	370	390	410
ISA -10°C	TIME (min)	3.1	6.0	8.8	11.6	14.3	17.1	19.9	21.0	22.2	23.5
	DIST (nam)	13.0	26.1	40.1	54.8	70.1	87.1	105.9	113.5	121.8	130.3
	FUEL (lb)	44	79	115	150	184	220	262	279	298	317
ISA	TIME (min)	3.1	6.0	8.9	11.7	14.4	17.0	19.6	20.6	21.7	22.9
	DIST (nam)	13.5	27.0	41.3	56.4	71.8	88.4	106.2	113.1	120.7	128.5
	FUEL (lb)	46	82	118	153	185	217	253	267	283	299
ISA +10°C	TIME (min)	3.2	6.1	9.0	11.8	14.5	17.0	19.5	20.4	21.5	22.5
	DIST (nam)	13.9	27.8	42.5	57.9	73.7	90.1	107.3	113.8	121.0	128.3
	FUEL (lb)	47	84	121	156	187	217	248	260	274	287
IDW 38 000 LB		050	100	150	200	250	300	350	370	390	410
ISA -10°C	TIME (min)	3.2	6.2	9.1	12.0	14.7	17.6	20.4	21.5	22.7	23.9
	DIST (nam)	13.5	27.0	41.4	56.6	72.2	89.6	108.7	116.1	124.3	132.3
	FUEL (lb)	46	82	118	155	189	226	268	286	304	323
ISA	TIME (min)	3.2	6.2	9.2	12.1	14.8	17.5	20.2	21.2	22.3	23.4
	DIST (nam)	13.9	27.9	42.7	58.2	74.0	91.0	109.1	116.0	123.5	131.0
	FUEL (lb)	47	84	121	158	191	224	260	274	290	305
ISA +10°C	TIME (min)	3.3	6.3	9.3	12.2	14.9	17.6	20.1	21.0	22.0	23.0
	DIST (nam)	14.4	28.7	43.9	59.8	75.9	92.8	110.3	116.9	124.0	131.1
	FUEL (lb)	49	87	125	161	193	223	255	268	281	294

QR1_DXDSC_002

DESCENT DATA

0.72 M / 250 KIAS / PACKS ON / ANTI-ICE OFF / 30% C.G.
(Cont'd)
 (3,000 fpm max. ROD - Sea level Final Altitude)

Initial Weight 40 000 LB		PRESSURE ALTITUDE (100 FT)									
		050	100	150	200	250	300	350	370	390	410
ISA -10°C	TIME (min)	3.3	6.3	9.4	12.3	15.1	18.0	20.9	22.0	23.1	24.3
	DIST (nam)	13.9	27.8	42.5	58.1	74.0	91.8	110.9	118.3	126.2	133.8
	FUEL (lb)	47	84	122	159	194	232	274	291	309	327
ISA	TIME (min)	3.3	6.4	9.5	12.4	15.2	17.9	20.6	21.6	22.7	23.7
	DIST (nam)	14.3	28.7	43.9	59.7	75.9	93.2	111.5	118.4	125.7	132.9
	FUEL (lb)	49	87	125	162	196	229	266	280	295	310
ISA +10°C	TIME (min)	3.4	6.5	9.6	12.5	15.3	18.0	20.6	21.5	22.5	23.5
	DIST (nam)	14.8	29.6	45.1	61.4	77.9	95.1	112.9	119.5	126.4	133.3
	FUEL (lb)	50	89	128	165	198	229	261	274	287	300
IDW 42 000 LB		050	100	150	200	250	300	350	370	390	410
ISA -10°C	TIME (min)	3.4	6.5	9.6	12.6	15.4	18.3	21.2	22.3	23.4	24.5
	DIST (nam)	14.2	28.5	43.6	59.4	75.6	93.6	112.9	120.1	127.6	134.8
	FUEL (lb)	48	86	124	163	198	237	279	296	313	330
ISA	TIME (min)	3.4	6.6	9.7	12.7	15.5	18.3	21.1	22.0	23.1	24.1
	DIST (nam)	14.7	29.4	44.9	61.1	77.6	95.2	113.6	120.4	127.5	134.3
	FUEL (lb)	50	89	128	166	200	234	271	285	300	314
ISA +10°C	TIME (min)	3.5	6.7	9.8	12.8	15.7	18.4	21.0	21.9	22.9	23.8
	DIST (nam)	15.1	30.3	46.2	62.8	79.7	97.2	115.2	121.7	128.5	135.1
	FUEL (lb)	51	92	131	169	203	234	267	279	292	304
IDW 44 000 LB		050	100	150	200	250	300	350	370	390	410
ISA -10°C	TIME (min)	3.4	6.6	9.8	12.8	15.7	18.7	21.5	22.6	23.7	24.7
	DIST (nam)	14.5	29.0	44.4	60.5	77.0	95.1	114.4	121.4	128.6	135.3
	FUEL (lb)	49	88	127	166	202	241	283	299	316	331
ISA	TIME (min)	3.5	6.7	9.9	12.9	15.8	18.7	21.4	22.3	23.3	24.3
	DIST (nam)	15.0	30.0	45.8	62.2	79.0	96.8	115.3	122.0	128.8	135.3
	FUEL (lb)	51	91	130	169	204	238	275	289	303	317
ISA +10°C	TIME (min)	3.5	6.8	10.0	13.1	16.0	18.7	21.3	22.2	23.2	24.1
	DIST (nam)	15.4	30.9	47.2	64.0	81.2	98.9	117.0	123.4	130.0	136.3
	FUEL (lb)	52	93	134	173	207	239	271	283	296	307

QR1_DXDSC_003

DESCENT DATA

0.72 M / 250 KIAS / PACKS ON / ANTI-ICE OFF / 30% C.G.
(Cont'd)
 (3,000 fpm max. ROD - Sea level Final Altitude)

Initial Weight 46 000 LB		PRESSURE ALTITUDE (100 FT)									
		050	100	150	200	250	300	350	370	390	410
ISA -10°C	TIME (min)	3.5	6.7	9.9	13.0	15.9	18.9	21.8	22.8	23.8	24.7
	DIST (nam)	14.8	29.5	45.1	61.4	78.1	96.3	115.4	122.3	129.2	135.3
	FUEL (lb)	50	89	129	169	205	244	286	302	318	332
ISA	TIME (min)	3.5	6.8	10.0	13.1	16.1	18.9	21.6	22.6	23.5	24.4
	DIST (nam)	15.3	30.5	46.6	63.2	80.2	98.1	116.6	123.1	129.7	135.7
	FUEL (lb)	52	92	133	172	207	242	279	292	306	318
ISA +10°C	TIME (min)	3.6	6.9	10.2	13.3	16.2	19.0	21.6	22.5	23.4	24.2
	DIST (nam)	15.7	31.5	47.9	65.0	82.4	100.3	118.4	124.7	131.1	137.0
	FUEL (lb)	53	95	136	175	210	242	275	287	299	310
IDW 48 000 LB		050	100	150	200	250	300	350	370	390	410
ISA -10°C	TIME (min)	3.5	6.8	10.1	13.2	16.1	19.1	21.9	22.9	23.9	24.7
	DIST (nam)	15.0	30.0	45.7	62.1	79.0	97.2	116.2	122.8	129.3	134.9
	FUEL (lb)	51	90	131	171	207	246	288	303	318	331
ISA	TIME (min)	3.6	6.9	10.2	13.3	16.3	19.1	21.8	22.7	23.6	24.5
	DIST (nam)	15.5	31.0	47.2	64.0	81.1	99.1	117.5	123.8	130.1	135.6
	FUEL (lb)	52	94	134	174	210	244	281	294	307	318
ISA +10°C	TIME (min)	3.6	7.0	10.3	13.4	16.4	19.2	21.8	22.7	23.6	24.3
	DIST (nam)	16.0	31.9	48.6	65.8	83.4	101.4	119.4	125.6	131.8	137.2
	FUEL (lb)	54	96	138	178	212	245	278	289	301	311
IDW 50 000 LB		050	100	150	200	250	300	350	370	390	410
ISA -10°C	TIME (min)	3.6	6.9	10.2	13.3	16.3	19.2	22.0	23.0	23.9	24.6
	DIST (nam)	15.2	30.3	46.2	62.7	79.6	97.8	116.5	122.8	128.9	134.0
	FUEL (lb)	51	91	132	172	209	248	289	304	318	329
ISA	TIME (min)	3.6	7.0	10.3	13.4	16.4	19.3	21.9	22.8	23.7	24.4
	DIST (nam)	15.7	31.3	47.7	64.6	81.9	99.8	118.0	124.1	130.1	135.1
	FUEL (lb)	53	95	136	176	212	246	283	295	308	318
ISA +10°C	TIME (min)	3.7	7.1	10.4	13.6	16.6	19.4	21.9	22.8	23.6	24.4
	DIST (nam)	16.2	32.3	49.1	66.5	84.2	102.2	120.1	126.1	131.9	137.0
	FUEL (lb)	55	98	139	179	215	247	279	291	302	312

QR1_DXDSC_004

DESCENT DATA

0.78 M / 300/250 KIAS / PACKS ON / ANTI-ICE OFF / 30% C.G.
 (3,000 fpm max. ROD - Sea level Final Altitude)

Initial Weight 28 000 LB		PRESSURE ALTITUDE (100 FT)									
		050	100	150	200	250	300	350	370	390	410
ISA -10°C	TIME (min)	2.5	4.9	7.1	8.7	10.3	11.9	13.4	14.2	15.0	16.0
	DIST (nam)	10.8	21.6	33.6	43.7	54.5	66.1	77.9	83.1	89.3	96.2
	FUEL (lb)	36	65	99	126	153	181	211	223	236	251
ISA	TIME (min)	2.6	5.0	7.2	8.9	10.5	12.2	13.9	14.5	15.3	16.1
	DIST (nam)	11.1	22.3	35.0	45.6	57.1	69.6	82.2	87.3	92.9	99.2
	FUEL (lb)	38	68	104	134	163	195	228	238	249	261
ISA +10°C	TIME (min)	2.6	5.1	7.3	9.0	10.8	12.5	14.3	15.0	15.7	16.4
	DIST (nam)	11.4	23.0	36.3	47.6	59.8	73.0	86.5	91.8	97.2	103.1
	FUEL (lb)	39	69	109	142	174	208	244	255	265	275
IDW 30 000 LB		050	100	150	200	250	300	350	370	390	410
ISA -10°C	TIME (min)	2.7	5.2	7.4	9.0	10.6	12.2	13.8	14.5	15.4	16.3
	DIST (nam)	11.4	22.9	35.1	45.1	55.9	67.6	79.3	84.8	91.1	98.1
	FUEL (lb)	39	69	100	125	150	176	205	217	231	245
ISA	TIME (min)	2.7	5.3	7.5	9.2	10.8	12.5	14.2	14.9	15.7	16.5
	DIST (nam)	11.8	23.6	36.4	47.1	58.6	71.1	83.7	88.9	94.7	101.1
	FUEL (lb)	40	71	105	133	160	189	221	232	243	255
ISA +10°C	TIME (min)	2.8	5.4	7.6	9.4	11.1	12.9	14.6	15.3	16.0	16.8
	DIST (nam)	12.1	24.3	37.8	49.1	61.4	74.6	88.0	93.4	98.9	105.0
	FUEL (lb)	41	74	110	140	171	203	238	248	258	269
IDW 32 000 LB		050	100	150	200	250	300	350	370	390	410
ISA -10°C	TIME (min)	2.8	5.5	7.7	9.3	10.9	12.5	14.1	14.9	15.8	16.7
	DIST (nam)	12.0	24.1	36.5	46.6	57.4	69.0	80.9	86.4	93.0	100.0
	FUEL (lb)	41	73	101	123	145	170	199	211	225	240
ISA	TIME (min)	2.9	5.6	7.8	9.5	11.2	12.8	14.5	15.2	16.0	16.9
	DIST (nam)	12.4	24.9	37.8	48.5	60.0	72.5	85.1	90.3	96.4	102.8
	FUEL (lb)	42	75	106	130	156	183	214	224	236	248
ISA +10°C	TIME (min)	2.9	5.6	8.0	9.7	11.4	13.2	14.9	15.6	16.4	17.2
	DIST (nam)	12.8	25.6	39.2	50.6	62.8	76.0	89.5	94.8	100.6	106.7
	FUEL (lb)	43	77	111	138	166	197	231	241	251	262

QR1_DXDSC_005

BOMBARDIER CHALLENGER 605	PERF-05-6
	<i>Oct 05/06</i>

DESCENT DATA

0.78 M / 300/250 KIAS / PACKS ON / ANTI-ICE OFF / 30% C.G.
(Cont'd)
 (3,000 fpm max. ROD - Sea level Final Altitude)

Initial Weight 34 000 LB		PRESSURE ALTITUDE (100 FT)									
		050	100	150	200	250	300	350	370	390	410
ISA -10°C	TIME (min)	3.0	5.7	8.1	9.7	11.3	12.9	14.5	15.3	16.2	17.2
	DIST (nam)	12.6	25.2	38.2	48.7	59.6	71.2	83.1	88.9	95.4	102.4
	FUEL (lb)	42	76	105	127	148	171	199	211	225	240
ISA	TIME (min)	3.0	5.8	8.2	9.8	11.5	13.2	14.8	15.6	16.4	17.3
	DIST (nam)	13.0	26.0	39.5	50.3	61.8	74.2	86.8	92.2	98.3	104.8
	FUEL (lb)	44	79	108	131	154	180	209	220	232	244
ISA +10°C	TIME (min)	3.0	5.9	8.3	10.0	11.7	13.5	15.2	15.9	16.7	17.5
	DIST (nam)	13.3	26.8	40.7	52.0	64.2	77.5	90.9	96.3	102.2	108.4
	FUEL (lb)	45	81	112	136	162	190	223	233	243	254
IDW 36 000 LB		050	100	150	200	250	300	350	370	390	410
ISA -10°C	TIME (min)	3.1	6.0	8.4	10.1	11.8	13.5	15.1	15.9	16.8	17.7
	DIST (nam)	13.0	26.2	39.9	50.8	62.2	74.1	86.1	91.9	98.5	105.4
	FUEL (lb)	44	79	109	132	154	177	204	217	231	245
ISA	TIME (min)	3.1	6.1	8.5	10.3	11.9	13.6	15.3	16.0	16.8	17.7
	DIST (nam)	13.5	27.0	41.1	52.4	64.1	76.5	89.1	94.6	100.8	107.2
	FUEL (lb)	46	82	113	136	157	181	210	220	232	245
ISA +10°C	TIME (min)	3.2	6.1	8.6	10.4	12.1	13.8	15.6	16.3	17.1	17.9
	DIST (nam)	13.9	27.8	42.4	54.0	66.2	79.4	92.9	98.4	104.3	110.5
	FUEL (lb)	47	84	116	139	162	189	221	231	241	252
IDW 38 000 LB		050	100	150	200	250	300	350	370	390	410
ISA -10°C	TIME (min)	3.2	6.2	8.7	10.5	12.3	14.0	15.6	16.4	17.3	18.2
	DIST (nam)	13.5	27.0	41.4	52.8	64.6	77.0	89.1	95.0	101.5	108.3
	FUEL (lb)	46	82	113	137	160	183	210	223	237	251
ISA	TIME (min)	3.2	6.3	8.8	10.6	12.4	14.1	15.8	16.5	17.3	18.2
	DIST (nam)	13.9	27.9	42.7	54.4	66.6	79.1	91.7	97.3	103.5	109.9
	FUEL (lb)	47	84	117	141	163	185	213	224	236	248
ISA +10°C	TIME (min)	3.3	6.3	8.9	10.8	12.5	14.3	16.0	16.7	17.5	18.3
	DIST (nam)	14.4	28.8	44.0	56.0	68.5	81.8	95.2	100.7	106.7	112.8
	FUEL (lb)	49	87	120	144	166	191	222	232	242	253

QR1_DXDSC_006

BOMBARDIER CHALLENGER 605	<i>PERF-05-7</i>
	<i>Oct 05/06</i>

DESCENT DATA

0.78 M / 300/250 KIAS / PACKS ON / ANTI-ICE OFF / 30% C.G.
(Cont'd)

(3,000 fpm max. ROD - Sea level Final Altitude)

Initial Weight 40 000 LB		PRESSURE ALTITUDE (100 FT)									
		050	100	150	200	250	300	350	370	390	410
ISA -10°C	TIME (min)	3.3	6.3	9.0	10.9	12.7	14.4	16.1	16.9	17.8	18.7
	DIST (nam)	13.9	27.8	42.7	54.6	66.9	79.6	91.9	97.8	104.3	110.9
	FUEL (lb)	47	84	117	142	165	189	216	229	243	257
ISA	TIME (min)	3.3	6.4	9.1	11.0	12.8	14.6	16.2	17.0	17.8	18.7
	DIST (nam)	14.3	28.7	44.1	56.3	68.9	81.8	94.5	100.1	106.3	112.5
	FUEL (lb)	49	87	120	145	168	191	218	229	241	253
ISA +10°C	TIME (min)	3.4	6.5	9.2	11.1	13.0	14.7	16.5	17.2	18.0	18.8
	DIST (nam)	14.8	29.6	45.4	58.0	70.9	84.3	97.8	103.3	109.3	115.3
	FUEL (lb)	50	89	124	149	171	195	225	235	245	256
IDW 42 000 LB		050	100	150	200	250	300	350	370	390	410
ISA -10°C	TIME (min)	3.4	6.5	9.2	11.2	13.1	14.9	16.5	17.4	18.2	19.1
	DIST (nam)	14.2	28.5	43.9	56.3	69.1	82.2	94.5	100.4	106.8	113.2
	FUEL (lb)	48	86	120	146	170	195	221	234	248	261
ISA	TIME (min)	3.4	6.6	9.3	11.3	13.2	15.0	16.7	17.4	18.3	19.1
	DIST (nam)	14.7	29.4	45.3	58.1	71.1	84.5	97.1	102.8	108.9	115.0
	FUEL (lb)	50	89	124	150	173	197	224	235	246	258
ISA +10°C	TIME (min)	3.5	6.7	9.5	11.5	13.4	15.2	16.9	17.6	18.4	19.2
	DIST (nam)	15.1	30.3	46.7	59.8	73.2	86.9	100.3	105.9	111.9	117.8
	FUEL (lb)	51	92	127	153	176	200	229	239	249	260
IDW 44 000 LB		050	100	150	200	250	300	350	370	390	410
ISA -10°C	TIME (min)	3.4	6.6	9.5	11.5	13.4	15.3	17.0	17.8	18.6	19.5
	DIST (nam)	14.5	29.1	45.0	57.8	71.0	84.5	96.9	102.7	109.0	115.2
	FUEL (lb)	49	88	123	150	175	200	226	239	252	265
ISA	TIME (min)	3.5	6.7	9.6	11.6	13.6	15.4	17.1	17.9	18.7	19.5
	DIST (nam)	15.0	30.0	46.5	59.6	73.2	86.9	99.6	105.2	111.2	117.2
	FUEL (lb)	51	91	127	154	178	202	228	239	251	262
ISA +10°C	TIME (min)	3.5	6.8	9.7	11.8	13.7	15.6	17.3	18.0	18.8	19.6
	DIST (nam)	15.5	30.9	47.9	61.4	75.3	89.4	102.8	108.4	114.3	120.1
	FUEL (lb)	52	94	130	157	181	205	234	244	254	264

QR1_DXDCS_007

QUICK REFERENCE HANDBOOK PSP 605-15	DESCENT DATA
--	---------------------

BOMBARDIER CHALLENGER 605	PERF-05-8
	<i>Oct 05/06</i>

DESCENT DATA

0.78 M / 300/250 KIAS / PACKS ON / ANTI-ICE OFF / 30% C.G.
(Cont'd)

(3,000 fpm max. ROD - Sea level Final Altitude)

Initial Weight 46 000 LB		PRESSURE ALTITUDE (100 FT)									
		050	100	150	200	250	300	350	370	390	410
ISA -10°C	TIME (min)	3.5	6.7	9.6	11.7	13.8	15.6	17.3	18.1	19.0	19.8
	DIST (nam)	14.8	29.6	46.0	59.2	72.8	86.6	99.0	104.9	111.0	116.9
	FUEL (lb)	50	89	126	153	179	205	231	243	256	269
ISA	TIME (min)	3.5	6.8	9.8	11.9	13.9	15.8	17.5	18.2	19.0	19.8
	DIST (nam)	15.3	30.5	47.5	61.1	75.0	89.0	101.8	107.4	113.3	119.0
	FUEL (lb)	52	92	129	157	182	207	233	244	255	266
ISA +10°C	TIME (min)	3.6	6.9	9.9	12.0	14.1	16.0	17.7	18.4	19.2	19.9
	DIST (nam)	15.7	31.5	49.0	62.9	77.3	91.6	105.1	110.6	116.4	122.1
	FUEL (lb)	53	95	133	161	186	210	238	248	258	268
IDW 48 000 LB		050	100	150	200	250	300	350	370	390	410
ISA -10°C	TIME (min)	3.5	6.8	9.8	12.0	14.0	16.0	17.7	18.4	19.3	20.0
	DIST (nam)	15.0	30.0	46.9	60.5	74.4	88.5	101.0	106.7	112.6	118.3
	FUEL (lb)	51	91	128	156	183	209	235	247	260	272
ISA	TIME (min)	3.6	6.9	10.0	12.1	14.2	16.1	17.8	18.6	19.3	20.1
	DIST (nam)	15.5	31.0	48.4	62.4	76.7	91.0	103.7	109.3	115.1	120.5
	FUEL (lb)	53	94	132	160	186	211	237	247	258	269
ISA +10°C	TIME (min)	3.6	7.0	10.1	12.3	14.4	16.3	18.0	18.8	19.5	20.2
	DIST (nam)	16.0	31.9	49.9	64.3	79.0	93.7	107.1	112.6	118.3	123.8
	FUEL (lb)	54	97	136	164	190	214	242	252	262	271
IDW 50 000 LB		050	100	150	200	250	300	350	370	390	410
ISA -10°C	TIME (min)	3.6	6.9	10.0	12.2	14.3	16.3	17.9	18.7	19.5	20.2
	DIST (nam)	15.2	30.3	47.7	61.6	75.9	90.2	102.6	108.3	114.0	119.2
	FUEL (lb)	51	92	130	159	186	213	238	250	263	274
ISA	TIME (min)	3.6	7.0	10.1	12.3	14.5	16.4	18.1	18.8	19.6	20.3
	DIST (nam)	15.7	31.3	49.2	63.5	78.2	92.8	105.5	111.0	116.6	121.8
	FUEL (lb)	53	95	134	163	189	215	240	251	262	272
ISA +10°C	TIME (min)	3.7	7.1	10.2	12.5	14.6	16.6	18.3	19.1	19.8	20.5
	DIST (nam)	16.2	32.3	50.7	65.5	80.5	95.5	109.0	114.4	120.0	125.3
	FUEL (lb)	55	98	138	167	193	218	246	255	265	275

QR1_DXDSC_008

QUICK REFERENCE HANDBOOK PSP 605-15	DESCENT DATA
--	---------------------

LANDING SPEEDS AND DISTANCES

ALTITUDE – SEA LEVEL

- V_{REF} = Speed at 50 ft screen height – KIAS

V_{AC} = Approach climb speed (Flap 20°) – KIAS

V_{FTO} = Final segment speed (Flap 0°) – KIAS

LFL = Landing Field Length – Feet – Zero wind

ALD = Actual Landing Distance – Feet – Zero wind and zero runway gradient
- Gradient Correction:

Wind Correction:

Landing Speed Correction:
- Increase by 750 ft for every 1% DOWNHILL

No correction for UPHILL gradient

Increase by 140 ft for every knot TAILWIND

Decrease by 10 ft for every knot HEADWIND (refer to PERF–07–3 for wind component conversions)

Increase distance by 11% for every 10 knots above V_{REF}

Shaded area indicates landing data above maximum landing weight

WT LB	V _{REF} V _{AC} V _{FTO}	LFL		ALD TEMPERATURE - °C											
				-40	-10	0	10	15	20	25	30	35	40	45	50
28000	116	3910	DRY	2340	2340	2340	2340	2340	2370	2400	2430	2450	2480	2510	2540
	129														
	145	4490	WET	3370	3370	3370	3370	3370	3420	3470	3510	3560	3600	3650	3690
30000	117	3950	DRY	2370	2370	2370	2370	2370	2400	2430	2460	2480	2510	2540	2570
	129														
	145	4540	WET	3420	3420	3420	3420	3420	3470	3520	3570	3610	3660	3700	3750
32000	121	4120	DRY	2470	2470	2470	2470	2470	2500	2530	2560	2590	2620	2650	2680
	129														
	145	4740	WET	3590	3590	3590	3590	3590	3630	3680	3730	3780	3830	3880	3930
34000	125	4290	DRY	2570	2570	2570	2570	2570	2610	2640	2670	2700	2730	2760	2790
	129														
	149	4930	WET	3750	3750	3750	3750	3750	3800	3850	3900	3950	4010	4060	4110
36000	128	4460	DRY	2680	2680	2680	2680	2680	2710	2740	2780	2810	2840	2870	2900
	129														
	154	5120	WET	3910	3910	3910	3910	3910	3960	4020	4070	4130	4180	4230	4290
38000	132	4620	DRY	2780	2780	2780	2780	2780	2810	2850	2880	2910	2950	2980	3020
	132														
	158	5320	WET	4070	4070	4070	4070	4070	4130	4180	4240	4300	4360	4410	4470
40000	136	4830	DRY	2900	2900	2900	2900	2900	2940	2970	3010	3040	3080	3120	3150
	136														
	162	5550	WET	4260	4260	4260	4260	4260	4320	4380	4450	4500	4570	4630	4690
42000	139	5000	DRY	3000	3000	3000	3000	3000	3040	3080	3120	3150	3190	3230	3270
	139														
	166	5750	WET	4420	4420	4420	4420	4420	4490	4550	4620	4680	4740	4810	4870
44000	143	5170	DRY	3100	3100	3100	3100	3100	3140	3180	3220	3260	3300	3340	3380
	143														
	170	5940	WET	4590	4590	4590	4590	4590	4660	4720	4790	4850	4920	4990	5050
46000	146	5320	DRY	3190	3190	3190	3190	3190	3230	3270	3320	3360	3400	3440	3480
	146														
	173	6110	WET	4740	4740	4740	4740	4740	4810	4870	4950	5010	5080	5150	5220

QRH_WETLDGDATA_S_L_F20_IMP_CL604_16JUN04

LANDING SPEEDS AND DISTANCES

ALTITUDE – 500 FEET

- V_{REF} = Speed at 50 ft screen height – KIAS
V_{AC} = Approach climb speed (Flap 20°) – KIAS
V_{FTO} = Final segment speed (Flap 0°) – KIAS
LFL = Landing Field Length – Feet – Zero wind
ALD = Actual Landing Distance – Feet – Zero wind and zero runway gradient
- Gradient Correction: Increase by 750 ft for every 1% DOWNHILL
No correction for UPHILL gradient
- Wind Correction: Increase by 140 ft for every knot TAILWIND
Decrease by 10 ft for every knot HEADWIND
(refer to PERF–07–3 for wind component conversions)
- Landing Speed Correction: Increase distance by 11% for every 10 knots above V_{REF}

Shaded area indicates landing data above maximum landing weight

WT LB	V _{REF} V _{AC} V _{FTO}	LFL		ALD TEMPERATURE – °C											
				–40	–10	0	10	15	20	25	30	35	40	45	49
28000	116	3940	DRY	2370	2370	2370	2370	2370	2400	2430	2460	2480	2510	2540	2560
	129														
	145	4530	WET	3410	3410	3410	3410	3420	3460	3510	3560	3600	3650	3690	3730
30000	117	3990	DRY	2390	2390	2390	2390	2400	2430	2460	2490	2510	2540	2570	2590
	129														
	145	4580	WET	3460	3460	3460	3460	3470	3520	3560	3610	3660	3700	3750	3790
32000	121	4160	DRY	2500	2500	2500	2500	2500	2530	2560	2590	2620	2650	2680	2710
	129														
	145	4780	WET	3620	3620	3620	3620	3630	3680	3730	3780	3830	3880	3930	3970
34000	125	4330	DRY	2600	2600	2600	2600	2610	2640	2670	2700	2730	2760	2800	2820
	129														
	149	4980	WET	3790	3790	3790	3790	3800	3850	3900	3960	4010	4060	4110	4150
36000	128	4500	DRY	2700	2700	2700	2700	2710	2740	2780	2810	2840	2880	2910	2930
	129														
	154	5170	WET	3950	3950	3950	3950	3960	4020	4070	4130	4180	4240	4290	4340
38000	132	4670	DRY	2800	2800	2800	2800	2810	2850	2880	2920	2950	2990	3020	3050
	132														
	158	5370	WET	4110	4110	4110	4110	4120	4180	4240	4300	4360	4420	4470	4520
40000	136	4880	DRY	2930	2930	2930	2930	2940	2970	3010	3050	3080	3120	3160	3190
	136														
	162	5610	WET	4310	4310	4310	4310	4320	4380	4450	4510	4570	4630	4690	4740
42000	139	5050	DRY	3030	3030	3030	3030	3040	3080	3120	3160	3190	3230	3270	3300
	139														
	166	5800	WET	4470	4470	4470	4470	4490	4550	4620	4680	4750	4810	4880	4930
44000	143	5220	DRY	3130	3130	3130	3130	3140	3180	3220	3270	3300	3350	3390	3420
	143														
	170	6000	WET	4640	4640	4640	4640	4650	4720	4790	4860	4930	4990	5060	5110
46000	146	5370	DRY	3230	3230	3230	3230	3230	3280	3320	3360	3400	3440	3490	3520
	146														
	173	6180	WET	4790	4790	4790	4790	4810	4880	4950	5020	5090	5160	5230	5280

QR1_DXLDG_002

QRH_WETLDGDATA0.5K_F20_IMP_CL604_16JUN04

LANDING SPEEDS AND DISTANCES

ALTITUDE – 1,000 FEET

- VREF = Speed at 50 ft screen height – KIAS
- VAC = Approach climb speed (Flap 20°) – KIAS
- VFTO = Final segment speed (Flap 0°) – KIAS
- LFL = Landing Field Length – Feet – Zero wind
- ALD = Actual Landing Distance – Feet – Zero wind and zero runway gradient
- Gradient Correction: Increase by 750 ft for every 1% DOWNHILL
No correction for UPHILL gradient
- Wind Correction: Increase by 140 ft for every knot TAILWIND
Decrease by 10 ft for every knot HEADWIND
(refer to PERF–07–3 for wind component conversions)
- Landing Speed Correction: Increase distance by 11% for every 10 knots above VREF

Shaded area indicates landing data above maximum landing weight

WT LB	VREF VAC VFTO	LFL		ALD TEMPERATURE – °C											
				–40	–10	0	10	15	20	25	30	35	40	45	48
28000	116	3980	DRY	2390	2390	2390	2390	2400	2430	2460	2490	2510	2540	2570	2590
	129														
	145	4570	WET	3440	3440	3440	3440	3460	3510	3560	3600	3650	3700	3740	3770
30000	118	4040	DRY	2430	2430	2430	2430	2440	2470	2500	2530	2550	2580	2610	2630
	129														
	145	4650	WET	3510	3510	3510	3510	3530	3580	3630	3680	3720	3770	3820	3850
32000	121	4220	DRY	2530	2530	2530	2530	2540	2570	2610	2640	2670	2700	2730	2750
	129														
	145	4850	WET	3680	3680	3680	3680	3700	3750	3800	3850	3900	3950	4000	4030
34000	125	4390	DRY	2640	2640	2640	2640	2650	2680	2710	2750	2780	2810	2840	2860
	129														
	149	5050	WET	3840	3840	3840	3840	3860	3920	3970	4030	4080	4130	4190	4220
36000	129	4570	DRY	2740	2740	2740	2740	2750	2790	2820	2860	2890	2920	2960	2980
	129														
	154	5250	WET	4010	4010	4010	4010	4030	4090	4150	4200	4260	4320	4370	4410
38000	132	4740	DRY	2850	2850	2850	2850	2860	2900	2930	2970	3000	3040	3070	3100
	133														
	158	5450	WET	4180	4180	4180	4180	4200	4260	4320	4380	4440	4500	4560	4590
40000	136	4950	DRY	2970	2970	2970	2970	2990	3020	3060	3100	3140	3180	3210	3240
	137														
	162	5690	WET	4380	4380	4380	4380	4400	4470	4530	4590	4650	4720	4780	4820
42000	140	5120	DRY	3080	3080	3080	3080	3090	3130	3170	3210	3250	3290	3330	3350
	140														
	166	5890	WET	4550	4550	4550	4550	4570	4640	4700	4770	4840	4900	4970	5010
44000	143	5300	DRY	3180	3180	3180	3180	3200	3240	3280	3320	3360	3410	3450	3470
	143														
	170	6090	WET	4720	4720	4720	4720	4740	4810	4880	4950	5020	5090	5160	5200
46000	146	5460	DRY	3280	3280	3280	3280	3290	3340	3380	3420	3460	3510	3550	3580
	146														
	173	6270	WET	4870	4870	4870	4870	4900	4970	5040	5120	5190	5260	5330	5370

QR1_WETLGDGDATA1K_F20_IMP_GL604_16JUN04

LANDING SPEEDS AND DISTANCES

ALTITUDE – 2,000 FEET

- V_{REF} = Speed at 50 ft screen height – KIAS
V_{AC} = Approach climb speed (Flap 20°) – KIAS
V_{FTO} = Final segment speed (Flap 0°) – KIAS
LFL = Landing Field Length – Feet – Zero wind
ALD = Actual Landing Distance – Feet – Zero wind and zero runway gradient
- Gradient Correction: Increase by 750 ft for every 1% DOWNHILL
No correction for UPHILL gradient
- Wind Correction: Increase by 140 ft for every knot TAILWIND
Decrease by 10 ft for every knot HEADWIND
(refer to PERF-07-3 for wind component conversions)
- Landing Speed Correction: Increase distance by 11% for every 10 knots above V_{REF}

Shaded area indicates landing data above maximum landing weight

WT LB	V _{REF} V _{AC} V _{FTO}	LFL		ALD TEMPERATURE – °C											
				-40	-10	0	10	15	20	25	30	35	40	45	46
28000	116	4050	DRY	2430	2430	2430	2430	2460	2490	2520	2550	2570	2600	2630	2640
	129														
	145	4660	WET	3510	3510	3510	3510	3550	3600	3650	3700	3750	3790	3840	3850
30000	118	4150	DRY	2490	2490	2490	2490	2520	2550	2580	2610	2640	2670	2700	2700
	129														
	145	4780	WET	3610	3610	3610	3610	3650	3700	3750	3810	3850	3900	3950	3970
32000	122	4340	DRY	2600	2600	2600	2600	2630	2660	2690	2730	2760	2790	2820	2830
	129														
	145	4980	WET	3790	3790	3790	3790	3830	3880	3940	3990	4040	4100	4150	4160
34000	126	4520	DRY	2710	2710	2710	2710	2740	2770	2810	2840	2870	2910	2940	2950
	129														
	149	5190	WET	3960	3960	3960	3960	4010	4060	4120	4180	4230	4290	4340	4350
36000	130	4700	DRY	2820	2820	2820	2820	2850	2890	2920	2960	2990	3030	3060	3070
	130														
	154	5400	WET	4130	4130	4130	4130	4180	4240	4300	4360	4420	4480	4540	4550
38000	133	4880	DRY	2930	2930	2930	2930	2960	3000	3030	3070	3110	3150	3180	3190
	133														
	158	5610	WET	4310	4310	4310	4310	4360	4420	4480	4550	4610	4670	4730	4750
40000	137	5100	DRY	3060	3060	3060	3060	3090	3130	3170	3210	3250	3290	3330	3340
	138														
	162	5860	WET	4520	4520	4520	4520	4570	4640	4700	4770	4830	4900	4970	4980
42000	141	5280	DRY	3170	3170	3170	3170	3200	3240	3290	3330	3370	3410	3450	3460
	141														
	166	6070	WET	4690	4690	4690	4690	4750	4820	4890	4960	5030	5100	5160	5180
44000	144	5460	DRY	3280	3280	3280	3280	3310	3360	3400	3450	3490	3530	3580	3580
	144														
	170	6280	WET	4870	4870	4870	4870	4930	5000	5070	5150	5220	5290	5360	5380
46000	147	5630	DRY	3380	3380	3380	3380	3410	3460	3500	3550	3590	3640	3680	3690
	147														
	173	6470	WET	5030	5030	5030	5030	5090	5170	5240	5320	5390	5470	5540	5560

QR1_DXLDG_004

QRH_WETLDGDATA2K_F20_JMP_CL604_16JUN04

LANDING SPEEDS AND DISTANCES

ALTITUDE – 4,000 FEET

- V_{REF} = Speed at 50 ft screen height – KIAS
- V_{AC} = Approach climb speed (Flap 20°) – KIAS
- V_{FTO} = Final segment speed (Flap 0°) – KIAS
- LFL = Landing Field Length – Feet – Zero wind
- ALD = Actual Landing Distance – Feet – Zero wind and zero runway gradient
- Gradient Correction: Increase by 750 ft for every 1% DOWNHILL
No correction for UPHILL gradient
- Wind Correction: Increase by 140 ft for every knot TAILWIND
Decrease by 10 ft for every knot HEADWIND
(refer to PERF–07–3 for wind component conversions)
- Landing Speed Correction: Increase distance by 11% for every 10 knots above V_{REF}

Shaded area indicates landing data above maximum landing weight

WT LB	V _{REF} V _{AC} V _{FTO}	LFL		ALD TEMPERATURE – °C											
				–40	–10	0	10	15	20	25	30	35	40	42	
28000	116	4210	DRY	2530	2530	2530	2550	2580	2610	2640	2670	2700	2740	2750	
	129														
	145	4840	WET	3660	3660	3660	3690	3750	3800	3850	3900	3950	4010	4030	
30000	120	4390	DRY	2640	2640	2640	2660	2690	2720	2760	2790	2820	2860	2870	
	129														
	145	5050	WET	3840	3840	3840	3870	3920	3980	4040	4090	4150	4200	4220	
32000	124	4590	DRY	2760	2760	2760	2780	2810	2850	2880	2920	2950	2990	3000	
	129														
	147	5280	WET	4020	4020	4020	4060	4120	4180	4240	4300	4350	4410	4430	
34000	127	4790	DRY	2880	2880	2880	2900	2930	2970	3010	3050	3080	3120	3140	
	129														
	152	5510	WET	4210	4210	4210	4250	4310	4370	4440	4500	4560	4620	4650	
36000	131	4990	DRY	2990	2990	2990	3020	3060	3090	3130	3170	3210	3250	3270	
	132														
	156	5730	WET	4400	4400	4400	4440	4510	4570	4640	4700	4770	4830	4860	
38000	135	5180	DRY	3110	3110	3110	3140	3180	3220	3260	3300	3340	3380	3400	
	135														
	160	5960	WET	4590	4590	4590	4630	4700	4770	4840	4910	4980	5040	5070	
40000	139	5420	DRY	3250	3250	3250	3280	3320	3370	3410	3460	3500	3540	3560	
	139														
	164	6230	WET	4820	4820	4820	4860	4930	5010	5080	5160	5230	5300	5330	
42000	142	5620	DRY	3370	3370	3370	3400	3450	3490	3540	3580	3630	3670	3690	
	143														
	168	6460	WET	5010	5010	5010	5050	5130	5210	5280	5360	5440	5510	5540	
44000	146	5820	DRY	3490	3490	3490	3520	3570	3620	3660	3710	3760	3810	3830	
	146														
	172	6690	WET	5200	5200	5200	5250	5330	5410	5490	5570	5650	5730	5760	
46000	149	5990	DRY	3600	3600	3600	3630	3680	3730	3780	3830	3880	3930	3950	
	149														
	176	6890	WET	5380	5380	5380	5420	5510	5590	5680	5760	5840	5920	5960	

QR1_WETLGDATA4K_F20_IMP_CL604_16JUN04

LANDING SPEEDS AND DISTANCES

ALTITUDE – 6,000 FEET

- V_{REF} = Speed at 50 ft screen height – KIAS
V_{AC} = Approach climb speed (Flap 20°) – KIAS
V_{FTO} = Final segment speed (Flap 0°) – KIAS
LFL = Landing Field Length – Feet – Zero wind
ALD = Actual Landing Distance – Feet – Zero wind and zero runway gradient
- Gradient Correction: Increase by 750 ft for every 1% DOWNHILL
No correction for UPHILL gradient
- Wind Correction: Increase by 140 ft for every knot TAILWIND
Decrease by 10 ft for every knot HEADWIND
(refer to PERF-07-3 for wind component conversions)
- Landing Speed Correction: Increase distance by 11% for every 10 knots above V_{REF}

Shaded area indicates landing data above maximum landing weight

WT LB	V _{REF} V _{AC} V _{FTO}	LFL		ALD TEMPERATURE – °C													
				-40	-10	0	10	15	20	25	30	35	38				
28000	117	4460	DRY	2680	2680	2680	2720	2760	2790	2830	2860	2890	2910				
	129																
	145	5120	WET	3900	3900	3900	3980	4040	4090	4150	4210	4260	4300				
30000	121	4670	DRY	2810	2810	2810	2850	2890	2930	2960	3000	3040	3060				
	129																
	145	5370	WET	4110	4110	4110	4190	4250	4310	4370	4430	4490	4530				
32000	125	4890	DRY	2930	2930	2930	2990	3030	3060	3100	3140	3180	3200				
	129																
	150	5620	WET	4310	4310	4310	4400	4460	4530	4590	4660	4720	4760				
34000	129	5100	DRY	3060	3060	3060	3120	3160	3200	3240	3280	3320	3350				
	130																
	154	5860	WET	4510	4510	4510	4610	4680	4740	4810	4880	4950	4990				
36000	133	5310	DRY	3190	3190	3190	3250	3290	3340	3380	3420	3460	3490				
	134																
	159	6110	WET	4720	4720	4720	4820	4890	4960	5030	5110	5180	5220				
38000	136	5530	DRY	3320	3320	3320	3380	3430	3470	3520	3560	3610	3640				
	137																
	163	6350	WET	4930	4930	4930	5030	5100	5180	5260	5330	5410	5450				
40000	141	5790	DRY	3470	3470	3470	3540	3590	3640	3680	3730	3780	3810				
	141																
	167	6650	WET	5170	5170	5170	5280	5360	5440	5520	5600	5680	5730				
42000	144	6000	DRY	3600	3600	3600	3670	3720	3770	3820	3880	3920	3960				
	145																
	171	6900	WET	5380	5380	5380	5500	5580	5660	5750	5830	5920	5970				
44000	148	6220	DRY	3730	3730	3730	3800	3860	3910	3960	4020	4070	4100				
	148																
	175	7150	WET	5590	5590	5590	5710	5800	5890	5970	6070	6150	6210				
46000	151	6410	DRY	3850	3850	3850	3920	3980	4040	4100	4160	4210	4250				
	151																
	179	7370	WET	5780	5780	5780	5910	6000	6090	6180	6280	6360	6420				

QR1_DXLDG_006

QR1_WETLDGDATA@K_F20_IMP_CL604_16JUN04

LANDING SPEEDS AND DISTANCES**ALTITUDE – 8,000 FEET**V_{REF} = Speed at 50 ft screen height – KIASV_{AC} = Approach climb speed (Flap 20°) – KIASV_{FTO} = Final segment speed (Flap 0°) – KIAS

LFL = Landing Field Length – Feet – Zero wind

ALD = Actual Landing Distance – Feet – Zero wind and zero runway gradient

Gradient Correction: Increase by 750 ft for every 1% DOWNHILL
No correction for UPHILL gradientWind Correction: Increase by 140 ft for every knot TAILWIND
Decrease by 10 ft for every knot HEADWIND
(refer to PERF-07-3 for wind component conversions)Landing Speed Correction: Increase distance by 11% for every
10 knots above V_{REF}

Shaded area indicates landing data above maximum landing weight

WT LB	V _{REF} V _{AC} V _{FTO}	LFL		ALD TEMPERATURE - °C													
				-40	-10	0	10	15	20	25	30	34					
28000	119	4750	DRY	2850	2850	2860	2930	2970	3010	3040	3080	3110					
	129																
	145	5460	WET	4190	4190	4200	4320	4380	4440	4510	4570	4620					
30000	123	4980	DRY	2990	2990	3000	3080	3120	3160	3200	3240	3270					
	129																
	148	5730	WET	4410	4410	4420	4550	4620	4680	4750	4820	4870					
32000	127	5210	DRY	3130	3130	3140	3220	3260	3310	3350	3390	3430					
	129																
	152	6000	WET	4630	4630	4640	4780	4850	4920	4990	5070	5120					
34000	131	5450	DRY	3270	3270	3280	3370	3410	3460	3500	3550	3580					
	132																
	157	6260	WET	4850	4850	4870	5010	5090	5160	5240	5320	5380					
36000	135	5680	DRY	3410	3410	3420	3510	3560	3610	3650	3700	3740					
	136																
	161	6530	WET	5080	5080	5090	5250	5320	5400	5480	5570	5630					
38000	138	5910	DRY	3550	3550	3560	3660	3710	3760	3810	3860	3900					
	139																
	165	6800	WET	5300	5300	5310	5480	5560	5640	5730	5820	5880					
40000	143	6190	DRY	3720	3720	3730	3830	3890	3940	3990	4050	4090					
	144																
	169	7120	WET	5570	5570	5580	5760	5850	5930	6020	6120	6190					
42000	146	6430	DRY	3860	3860	3870	3980	4040	4090	4150	4210	4260					
	147																
	174	7390	WET	5800	5800	5810	5990	6090	6180	6270	6370	6450					
44000	149	6660	DRY	4000	4000	4010	4130	4190	4250	4310	4380	4440					
	150																
	178	7660	WET	6020	6020	6040	6230	6330	6430	6540	6640	6730					
46000	152	6890	DRY	4130	4130	4150	4280	4350	4430	4500	4580	4640					
	153																
	182	7920	WET	6230	6230	6250	6450	6560	6670	6780	6890	6980					

QR1_WETLDGDATA8K_F20_IMP_GL604_16JUN04

QR1_DXLDG_007

LANDING SPEEDS AND DISTANCES

ALTITUDE – 10,000 FEET

- V_{REF} = Speed at 50 ft screen height – KIAS
V_{AC} = Approach climb speed (Flap 20°) – KIAS
V_{FTO} = Final segment speed (Flap 0°) – KIAS
LFL = Landing Field Length – Feet – Zero wind
ALD = Actual Landing Distance – Feet – Zero wind and zero runway gradient
- Gradient Correction: Increase by 750 ft for every 1% DOWNHILL
No correction for UPHILL gradient
- Wind Correction: Increase by 140 ft for every knot TAILWIND
Decrease by 10 ft for every knot HEADWIND
(refer to PERF-07-3 for wind component conversions)
- Landing Speed Correction: Increase distance by 11% for every 10 knots above V_{REF}

Shaded area indicates landing data above maximum landing weight

WT LB	V _{REF} V _{AC} V _{FTO}	LFL		ALD TEMPERATURE – °C											
				-40	-10	0	10	15	20	25	30				
28000	120	5080	DRY	3050	3050	3090	3170	3220	3260	3300	3340				
	129														
	145	5840	WET	4530	4530	4590	4730	4800	4870	4940	5010				
30000	124	5340	DRY	3200	3200	3250	3330	3380	3420	3470	3510				
	129														
	150	6140	WET	4770	4770	4840	4980	5060	5130	5210	5280				
32000	129	5590	DRY	3360	3360	3400	3490	3540	3590	3640	3690				
	130														
	155	6430	WET	5010	5010	5080	5240	5320	5400	5470	5560				
34000	133	5840	DRY	3510	3510	3560	3660	3710	3760	3810	3860				
	134														
	159	6720	WET	5250	5250	5330	5490	5580	5660	5750	5830				
36000	136	6100	DRY	3660	3660	3710	3820	3870	3920	3980	4030				
	138														
	164	7010	WET	5500	5500	5580	5750	5840	5930	6020	6110				
38000	140	6350	DRY	3810	3810	3870	3980	4030	4090	4150	4200				
	141														
	168	7300	WET	5740	5740	5830	6010	6100	6200	6290	6390				
40000	144	6660	DRY	4000	4000	4050	4170	4230	4300	4360	4430				
	146														
	173	7660	WET	6030	6030	6120	6320	6420	6520	6630	6740				
42000	148	6920	DRY	4150	4150	4210	4350	4420	4480	4550	4630				
	149														
	177	7950	WET	6280	6280	6380	6590	6700	6820	6930	7040				
44000	151	7190	DRY	4320	4320	4390	4530	4610	4690	4760	4850				
	152														
	181	8270	WET	6540	6540	6650	6870	6990	7110	7220	7340				
46000	154	7490	DRY	4500	4500	4580	4740	4830	4910	5000	5090				
	155														
	185	8620	WET	6780	6780	6890	7130	7250	7370	7490	7620				

QR1_WETLDGDATA10K_F20_IMP_CL604_16JUN04

QR1_DXLDG_008

LANDING SPEEDS AND DISTANCES

ALTITUDE – 12,000 FEET

- V_{REF} = Speed at 50 ft screen height – KIAS
- V_{AC} = Approach climb speed (Flap 20°) – KIAS
- V_{FTO} = Final segment speed (Flap 0°) – KIAS
- LFL = Landing Field Length – Feet – Zero wind
- ALD = Actual Landing Distance – Feet – Zero wind and zero runway gradient
- Gradient Correction: Increase by 750 ft for every 1% DOWNHILL
No correction for UPHILL gradient
- Wind Correction: Increase by 140 ft for every knot TAILWIND
Decrease by 10 ft for every knot HEADWIND
(refer to PERF-07-3 for wind component conversions)
- Landing Speed Correction: Increase distance by 11% for every 10 knots above V_{REF}

Shaded area indicates landing data above maximum landing weight

WT LB	V _{REF} V _{AC} V _{FTO}	LFL		ALD TEMPERATURE – °C												
				-40	-10	0	10	15	20	21						
28000	122	5470	DRY	3280	3280	3360	3450	3500	3540	3550						
	129															
	147	6290	WET	4930	4930	5060	5210	5280	5360	5370						
30000	126	5740	DRY	3450	3450	3530	3630	3680	3730	3740						
	129															
	152	6610	WET	5190	5190	5330	5490	5570	5650	5670						
32000	130	6020	DRY	3610	3610	3700	3810	3860	3910	3920						
	132															
	157	6920	WET	5460	5460	5600	5770	5860	5940	5960						
34000	134	6300	DRY	3780	3780	3880	3990	4040	4100	4110						
	136															
	162	7240	WET	5720	5720	5880	6060	6140	6230	6260						
36000	138	6580	DRY	3950	3950	4050	4160	4220	4280	4300						
	140															
	167	7580	WET	5990	5990	6150	6340	6440	6530	6560						
38000	142	6850	DRY	4110	4110	4220	4350	4420	4490	4500						
	143															
	171	7880	WET	6250	6250	6430	6640	6740	6850	6880						
40000	146	7200	DRY	4320	4320	4450	4590	4670	4740	4760						
	148															
	176	8280	WET	6580	6580	6770	7000	7120	7230	7260						
42000	149	7510	DRY	4510	4510	4640	4800	4870	4950	4970						
	151															
	180	8640	WET	6870	6870	7070	7310	7430	7550	7580						
44000	153	7850	DRY	4710	4710	4860	5040	5120	5210	5240						
	155															
	185	9030	WET	7160	7160	7370	7630	7750	7880	7910						
46000	156	8230	DRY	4940	4940	5110	5310	5410	5510	5540						
	158															
	189	9480	WET	7420	7420	7650	7910	8040	8170	8200						

QR1_WETLDGDATA12K_F20_IMP_CL604_16JUN04

QR1_DXLDG_009

LANDING SPEEDS AND DISTANCES

ALTITUDE – 14,000 FEET

- VREF = Speed at 50 ft screen height – KIAS
- VAC = Approach climb speed (Flap 20°) – KIAS
- VFTO = Final segment speed (Flap 0°) – KIAS
- LFL = Landing Field Length – Feet – Zero wind
- ALD = Actual Landing Distance – Feet – Zero wind and zero runway gradient
- Gradient Correction:

Increase by 750 ft for every 1% DOWNHILL

No correction for UPHILL gradient
- Wind Correction:

Increase by 140 ft for every knot TAILWIND

Decrease by 10 ft for every knot HEADWIND

(refer to PERF–07–3 for wind component conversions)
- Landing Speed Correction:

Increase distance by 11% for every 10 knots above VREF

Shaded area indicates landing data above maximum landing weight

WT LB	VREF VAC VFTO	LFL		ALD TEMPERATURE – °C											
				–40	–10	0	10	15	17						
28000	123	5880	DRY	3530	3550	3650	3750	3800	3820						
	129														
	150	6760	WET	5380	5420	5570	5730	5810	5840						
30000	128	6180	DRY	3710	3740	3840	3940	4000	4020						
	129														
	155	7100	WET	5660	5710	5870	6030	6120	6160						
32000	132	6480	DRY	3890	3920	4030	4140	4200	4220						
	133														
	160	7450	WET	5940	5990	6170	6350	6440	6480						
34000	135	6780	DRY	4070	4100	4220	4340	4410	4440						
	137														
	165	7790	WET	6230	6280	6470	6660	6770	6820						
36000	139	7080	DRY	4250	4280	4420	4560	4630	4670						
	141														
	170	8140	WET	6520	6570	6780	7000	7110	7160						
38000	143	7400	DRY	4440	4490	4630	4780	4860	4890						
	145														
	175	8510	WET	6820	6880	7110	7340	7450	7510						
40000	147	7810	DRY	4690	4730	4890	5050	5130	5160						
	149														
	180	8980	WET	7190	7250	7500	7740	7870	7920						
42000	151	8160	DRY	4900	4940	5120	5290	5380	5430						
	153														
	184	9380	WET	7500	7570	7830	8080	8220	8280						
44000	154	8580	DRY	5150	5200	5400	5600	5710	5760						
	157														
	188	9860	WET	7820	7890	8160	8430	8570	8630						
46000	157	9050	DRY	5430	5490	5720	5950	6080	6130						
	160														
	193	10400	WET	8100	8180	8460	8740	8890	8960						

QFH_WETLDGDATA14K_F20_IMP_CL604_16JUN04

QR1_DXLDG_010

LANDING SPEED AND DISTANCE CORRECTIONS

ABNORMAL PROCEDURES - FLAPS FAILURE - OTHER THAN 45°			
Flaps Setting (Degrees)	ΔV_{REF} (KTS)	ALD Factor (Without Thrust Reversers)	ALD Factor (With Thrust Reversers)
0	30	1.80 (80%)	1.75 (75%)
20	14	1.55 (55%)	1.50 (50%)
30	7	1.40 (40%)	1.35 (35%)

QR1_DXLDG_012

GO-AROUND THRUST SETTING, % N₁

NORMAL TAKEOFF THRUST (All Engine, Zero Bleed) - GO AROUND								
Fan Speed (N1 %)	PRESSURE ALTITUDE (ft)							
	SL	500	1000	2000	4000	6000	8000	10000
	90.2	90.3	90.4	90.6	91.0	91.4	91.8	92.3

QR1_DXLDG_011

BOMBARDIER CHALLENGER 605	PERF-06-12
	REV 57, Sep 11/20

OPERATIONAL LANDING DISTANCE (OLD)

The Factored Operational Landing Distance (FOLD) is provided at the following runway surface conditions for in-flight assessment of the landing distance at time of arrival.

NOTE

Landing performance data are calculated based on the assumption that maximum available reverse thrust is used down to a speed of 60 KIAS, and that 60% N1 reverse thrust is used below 60 KIAS for cases with thrust reverser(s).

NOTE

The landing distance (ALD) presented in the APPROACH AND LANDING section of this manual should be used for the following cases:

- Assessment of landing distance at time of dispatch.
- Assessment of landing distance in conjunction with the Emergency Procedures or Non-Normal Procedures of the AFM.

OPERATIONAL LANDING DISTANCE (OLD)**Runway Surface Condition – Pilot–Reported Braking Action –
Wheel Braking Correlation Matrix**

RUNWAY CONDITION CODE (RCC)	RUNWAY SURFACE CONDITION DESCRIPTION	PILOT-REPORTED BRAKING ACTION
6	Dry	–
5	- Frost - Wet (includes damp and 1/8in (3mm) depth or less of water) 1/8in (3mm) depth or less of: - Slush - Dry snow - Wet snow	Good
4	–15°C and colder OAT: Compacted snow	Good to Medium [1]
3	- Wet (“Slippery when wet” runway) - Dry snow or wet snow (any depth) over compacted snow Greater than 1/8in (3mm) depth of: - Dry snow - Wet snow Warmer than –15°C OAT: - Compacted snow	Medium [1]
2	Greater than 1/8in (3mm) depth of: - Water - Slush	Medium [1] to Poor
1	Ice	Poor
0	- Wet ice - Water on top of compacted snow - Dry snow or wet snow over ice	Nil

[1] The braking action term “FAIR” is in the process of being changed to “MEDIUM” throughout the FAA. Until an official change is published, the term “FAIR” may be used.

NOTE

- Do not operate on a runway surface condition corresponding to Runway Condition Code 0.
- Initial selection of the Runway Condition Code must be based on the RCC reported and if not available then the runway surface condition description. The Equivalent Pilot–reported braking action must only be considered if it downgrades the runway condition (i.e. reduces the Runway Condition Code).

OPERATIONAL LANDING DISTANCE (OLD)

VREF
TWO THRUST REVERSERS
RUNWAY CONDITION CODE 6

ZERO WIND
ZERO SLOPE
ISA

FACTORED OPERATIONAL LANDING DISTANCE (FOLD – FT) – RCC 6								
WEIGHT (LB)	PRESSURE ALTITUDE (FT)							
	0	2000	4000	6000	8000	10000	12000	14000
28000	3207	3340	3480	3680	3912	4165	4441	4720
30000	3256	3433	3639	3863	4106	4372	4662	4956
32000	3406	3592	3807	4042	4297	4576	4880	5188
34000	3553	3747	3973	4219	4485	4776	5094	5418
36000	3697	3900	4136	4392	4670	4975	5307	5645
38000	3839	4051	4296	4563	4853	5171	5518	5871
40000	4007	4228	4485	4765	5069	5403	5767	6138
42000	4146	4376	4643	4934	5251	5598	5976	6362
44000	4284	4522	4799	5102	5431	5791	6184	6584
46000	4407	4653	4939	5252	5592	5964	6370	6784

<CL604_FOLD_RCC6_IMP_08JUL20.ps>

Add the following corrections together based on the conditions and apply the total correction on the uncorrected FOLD value obtained from the table above:

- + 1.3 % / kt above V_{REF}
- + 0.3 % / °C above ISA, – 0.2 % / °C below ISA
- + 2.1 % / kt tailwind, – 0.4 % / kt headwind
- + 1.2 % / % downhill slope, – 0.8 % / % uphill slope

If required, multiply the corrections below to the result above:

Thrust Reversers

- One thrust reverser inoperative X 1.031
- Two thrust reversers inoperative X 1.072

MMEL

- Ground spoilers inoperative X 1.14
- Anti-skid inoperative X 1.95

NOTE: The Factored Operational Landing Distance includes a 15% operational distance factor.

OPERATIONAL LANDING DISTANCE (OLD)

VREF
TWO THRUST REVERSERS
RUNWAY CONDITION CODE 5

ZERO WIND
ZERO SLOPE
ISA

FACTORED OPERATIONAL LANDING DISTANCE (FOLD – FT) – RCC 5								
WEIGHT (LB)	PRESSURE ALTITUDE (FT)							
	0	2000	4000	6000	8000	10000	12000	14000
28000	3862	4053	4260	4544	4874	5240	5645	6068
30000	3950	4199	4490	4811	5164	5556	5990	6443
32000	4161	4427	4737	5079	5455	5873	6337	6821
34000	4373	4655	4984	5348	5748	6193	6686	7201
36000	4585	4884	5233	5618	6042	6514	7037	7583
38000	4797	5113	5482	5889	6338	6837	7389	7967
40000	5045	5380	5771	6203	6681	7211	7797	8412
42000	5260	5613	6024	6480	6983	7540	8157	8807
44000	5476	5846	6279	6758	7285	7872	8521	9205
46000	5675	6062	6515	7015	7567	8180	8860	9577

<CL604_FOLD_RCC5_IMP_08JUL20.ps>

Add the following corrections together based on the conditions and apply the total correction on the uncorrected FOLD value obtained from the table above:

- + 1.2 % / kt above V_{REF}
- + 0.4 % / °C above ISA, – 0.3 % / °C below ISA
- + 2.4 % / kt tailwind, – 0.5 % / kt headwind
- + 2.4 % / % downhill slope, – 1.3 % / % uphill slope

If required, multiply the corrections below to the result above:

Thrust Reversers

- One thrust reverser inoperative X 1.12
- Two thrust reversers inoperative X 1.34

MMEL

- Ground spoilers inoperative X 1.14
- Anti-skid inoperative X 1.95

NOTE: The Factored Operational Landing Distance includes a 15% operational distance factor.

OPERATIONAL LANDING DISTANCE (OLD)

VREF
TWO THRUST REVERSERS
RUNWAY CONDITION CODE 4ZERO WIND
ZERO SLOPE
ISA

FACTORED OPERATIONAL LANDING DISTANCE (FOLD – FT) – RCC 4								
WEIGHT (LB)	PRESSURE ALTITUDE (FT)							
	0	2000	4000	6000	8000	10000	12000	14000
28000	4045	4231	4430	4699	5009	5349	5722	6106
30000	4133	4372	4647	4948	5277	5638	6033	6441
32000	4334	4587	4878	5196	5543	5925	6342	6773
34000	4534	4800	5107	5442	5808	6210	6650	7104
36000	4733	5012	5335	5687	6072	6494	6956	7433
38000	4930	5223	5561	5931	6334	6776	7261	7761
40000	5158	5467	5823	6212	6636	7102	7612	8139
42000	5355	5677	6049	6455	6898	7384	7917	8467
44000	5551	5887	6274	6697	7159	7666	8221	8796
46000	5730	6078	6480	6919	7398	7924	8501	9097

<CL604_FOLD_RCC4/IMP_08JUL20.ps>

Add the following corrections together based on the conditions and apply the total correction on the uncorrected FOLD value obtained from the table above:

- + 1.1 % / kt above V_{REF}
- + 0.4 % / °C above ISA, – 0.2 % / °C below ISA
- + 2.2 % / kt tailwind, – 0.4 % / kt headwind
- + 2.3 % / % downhill slope, – 1.5 % / % uphill slope

If required, multiply the corrections below to the result above:

Thrust Reversers

- One thrust reverser inoperative X 1.10
- Two thrust reversers inoperative X 1.26

MMEL

- Ground spoilers inoperative X 1.14
- Anti-skid inoperative Prohibited

NOTE: The Factored Operational Landing Distance includes a 15% operational distance factor.

OPERATIONAL LANDING DISTANCE (OLD)

VREF
TWO THRUST REVERSERS
RUNWAY CONDITION CODE 3

ZERO WIND
ZERO SLOPE
ISA

FACTORED OPERATIONAL LANDING DISTANCE (FOLD – FT) – RCC 3								
WEIGHT (LB)	PRESSURE ALTITUDE (FT)							
	0	2000	4000	6000	8000	10000	12000	14000
28000	4294	4499	4717	5010	5346	5715	6119	6538
30000	4398	4657	4955	5282	5639	6030	6460	6905
32000	4617	4891	5207	5553	5930	6345	6799	7270
34000	4835	5124	5458	5822	6220	6658	7137	7633
36000	5051	5356	5707	6091	6509	6969	7473	7995
38000	5267	5587	5955	6358	6797	7280	7808	8357
40000	5515	5852	6240	6664	7126	7635	8192	8770
42000	5731	6083	6488	6931	7414	7946	8528	9133
44000	5945	6313	6735	7197	7702	8256	8864	9496
46000	6143	6524	6963	7443	7967	8543	9175	9831

<CL604_FOLD_RCC3_IMP_08JUL20.ps>

Add the following corrections together based on the conditions and apply the total correction on the uncorrected FOLD value obtained from the table above:

- + 1.0 % / kt above V_{REF}
- + 0.4 % / °C above ISA, – 0.2 % / °C below ISA
- + 2.3 % / kt tailwind, – 0.4 % / kt headwind
- + 2.8 % / % downhill slope, – 1.8 % / % uphill slope

If required, multiply the corrections below to the result above:

Thrust Reversers

- One thrust reverser inoperative X 1.13
- Two thrust reversers inoperative X 1.36

MMEL

- Ground spoilers inoperative X 1.14
- Anti-skid inoperative Prohibited

NOTE: The Factored Operational Landing Distance includes a 15% operational distance factor.

OPERATIONAL LANDING DISTANCE (OLD)

VREF
TWO THRUST REVERSERS
RUNWAY CONDITION CODE 2

ZERO WIND
ZERO SLOPE
ISA

FACTORED OPERATIONAL LANDING DISTANCE (FOLD – FT) – RCC 2								
WEIGHT (LB)	PRESSURE ALTITUDE (FT)							
	0	2000	4000	6000	8000	10000	12000	14000
28000	4599	4855	5128	5486	5897	6345	6841	7360
30000	4741	5061	5425	5826	6260	6741	7269	7828
32000	5014	5352	5742	6162	6627	7137	7702	8302
34000	5286	5644	6053	6499	6993	7538	8138	8775
36000	5558	5933	6366	6838	7360	7937	8577	9256
38000	5828	6223	6676	7178	7730	8343	9018	9736
40000	6132	6551	7031	7562	8150	8799	9519	10285
42000	6406	6842	7350	7908	8526	9214	9970	10775
44000	6678	7139	7672	8257	8905	9631	10430	11275
46000	6929	7415	7971	8586	9268	10021	10862	11751

<CL604_FOLD_RCC2_IMP_08JUL20.ps>

Add the following corrections together based on the conditions and apply the total correction on the uncorrected FOLD value obtained from the table above:

- + 1.1 % / kt above V_{REF}
- + 0.5 % / °C above ISA, – 0.3 % / °C below ISA
- + 2.6 % / kt tailwind, – 0.5 % / kt headwind
- + 3.8 % / % downhill slope, – 2.0 % / % uphill slope

If required, multiply the corrections below to the result above:

Thrust Reversers

- One thrust reverser inoperative X 1.20
- Two thrust reversers inoperative X 1.67

MMEL

- Ground spoilers inoperative X 1.14
- Anti-skid inoperative Prohibited

NOTE: The Factored Operational Landing Distance includes a 15% operational distance factor.

OPERATIONAL LANDING DISTANCE (OLD)

VREF
TWO THRUST REVERSERS
RUNWAY CONDITION CODE 1

ZERO WIND
ZERO SLOPE
ISA

FACTORED OPERATIONAL LANDING DISTANCE (FOLD – FT) – RCC 1								
WEIGHT (LB)	PRESSURE ALTITUDE (FT)							
	0	2000	4000	6000	8000	10000	12000	14000
28000	5056	5323	5611	5982	6406	6872	7384	7921
30000	5214	5543	5919	6332	6783	7280	7825	8397
32000	5494	5843	6243	6681	7160	7687	8265	8872
34000	5773	6143	6566	7029	7536	8093	8705	9347
36000	6052	6442	6888	7376	7911	8499	9144	9821
38000	6330	6740	7209	7723	8285	8904	9583	10296
40000	6642	7075	7570	8112	8705	9358	10075	10828
42000	6921	7375	7893	8461	9082	9766	10518	11308
44000	7200	7674	8216	8809	9459	10175	10961	11788
46000	7461	7955	8519	9136	9813	10559	11379	12241

<CL604_FOLD_RCC1_IMP_08JUL20.ps>

Add the following corrections together based on the conditions and apply the total correction on the uncorrected FOLD value obtained from the table above:

- + 0.9 % / kt above V_{REF}
- + 0.4 % / °C above ISA, – 0.3 % / °C below ISA
- + 2.5 % / kt tailwind, – 0.5 % / kt headwind
- + 4.8 % / % downhill slope, – 2.7 % / % uphill slope

If required, multiply the corrections below to the result above:

Thrust Reversers

- One thrust reverser inoperative X 1.26
- Two thrust reversers inoperative X 1.88

MMEL

- Ground spoilers inoperative X 1.14
- Anti-skid inoperative Prohibited

NOTE: The Factored Operational Landing Distance includes a 15% operational distance factor.

OPERATIONAL LANDING DISTANCE (OLD)**Flaps 45° Operational Landing Distance (OLD) Factors to Convert FMS Dry ALD to FOLD**

As an alternate method of determining the Factored Operational Landing Distance (FOLD), the FMS factors presented in the tables in this section can be used to conservatively increase the FMS DRY ALD to the required FOLD.

The factor include a 15% operational distance factor.

1. Enter all applicable landing configuration and condition inputs into the FMS Arrival Performance pages.
2. Select DRY runway in the FMS.
3. Determine the factor using the tables presented in this section based on the runway condition code.
4. Enter the appropriate factor into the FACTOR field in the FMS.

The ALD field in the FMS will provide a conservative estimate of the required FOLD.

NOTE

1. If the factor exceeds the input capability of the FMS, consider the use of 2 thrust reversers.
2. Interpolation between the two thrust reverser data and zero thrust reverser data is prohibited.

TWO THRUST REVERSERS

FACTORS TO CONVERT FMS DRY ALD TO FOLD						
RCC	ISA + 15°C AND BELOW			ISA + 35°C		
	V _{REF}	V _{REF} + 10 KTS	V _{REF} + 20 KTS	V _{REF}	V _{REF} + 10 KTS	V _{REF} + 20 KTS
6	1.48	1.67	1.88	1.56	1.76	1.98
5	2.03	2.23	2.43	2.19	2.41	2.63
4	2.09	2.29	2.48	2.24	2.46	2.67
3	2.15	2.34	2.53	2.29	2.50	2.71
2	2.56	2.75	2.96	2.77	2.99	3.22
1	2.78	2.95	3.13	2.97	3.16	3.38

<CH604_FOLD_FACTORS_03JUL20_2TR>

ZERO THRUST REVERSERS

FACTORS TO CONVERT FMS DRY ALD TO FOLD						
RCC	ISA + 15°C AND BELOW			ISA + 35°C		
	V _{REF}	V _{REF} + 10 KTS	V _{REF} + 20 KTS	V _{REF}	V _{REF} + 10 KTS	V _{REF} + 20 KTS
6	1.55	1.77	2.01	1.64	1.87	2.13
5	2.79	3.08	3.36	3.00	3.31	3.61
4	-	-	-	-	-	-
3	-	-	-	-	-	-
2	-	-	-	-	-	-
1	-	-	-	-	-	-

<CH604_FOLD_FACTORS_03JUL20_0TR>

RESERVE FUEL (LBS) – NBAA/IFR FORMAT

HOLDING TIME AT ALTERNATE – 0 MINUTES

ZFW LB	ALTERNATE DISTANCE (NM) - STILL AIR									
	50	100	150	200	250	300	350	400	450	500
26000	555	806	1012	1188	1358	1529	1701	1873	2046	2219
27000	563	818	1031	1211	1385	1560	1736	1912	2089	2266
28000	572	832	1048	1234	1412	1591	1770	1950	2131	2313
29000	580	843	1064	1256	1438	1621	1805	1990	2175	2361
30000	589	855	1082	1278	1465	1652	1840	2029	2218	2409
31000	598	868	1099	1300	1491	1683	1875	2068	2262	2457
32000	607	880	1114	1322	1518	1714	1910	2108	2307	2506

QR1_DXMISC_001

HOLDING TIME AT ALTERNATE – 15 MINUTES

ZFW LB	ALTERNATE DISTANCE (NM) - STILL AIR									
	50	100	150	200	250	300	350	400	450	500
26000	865	1119	1327	1504	1676	1848	2020	2194	2368	2543
27000	882	1139	1352	1534	1710	1886	2063	2240	2418	2597
28000	898	1157	1377	1564	1743	1924	2104	2286	2468	2652
29000	913	1178	1401	1594	1778	1962	2147	2333	2520	2708
30000	930	1198	1425	1624	1812	2000	2190	2380	2571	2763
31000	947	1219	1451	1654	1846	2039	2234	2428	2623	2820
32000	963	1238	1473	1683	1880	2078	2276	2476	2676	2877

QR1_DXMISC_002

HOLDING TIME AT ALTERNATE – 30 MINUTES

ZFW LB	ALTERNATE DISTANCE (NM) - STILL AIR									
	50	100	150	200	250	300	350	400	450	500
26000	1179	1433	1644	1822	1995	2168	2342	2517	2692	2868
27000	1203	1462	1676	1860	2036	2214	2392	2571	2750	2930
28000	1226	1487	1709	1897	2077	2259	2441	2625	2808	2993
29000	1250	1516	1740	1935	2120	2306	2492	2680	2868	3057
30000	1274	1543	1772	1972	2161	2352	2543	2735	2927	3121
31000	1299	1572	1803	2009	2204	2398	2594	2790	2987	3185
32000	1323	1599	1835	2046	2245	2445	2645	2846	3049	3252

QR1_DXMISC_003

HOLDING TIME AT ALTERNATE – 45 MINUTES

ZFW LB	ALTERNATE DISTANCE (NM) - STILL AIR									
	50	100	150	200	250	300	350	400	450	500
26000	1495	1750	1963	2143	2317	2491	2666	2842	3019	3196
27000	1526	1786	2002	2187	2365	2544	2723	2903	3084	3266
28000	1557	1820	2041	2232	2414	2597	2781	2966	3151	3337
29000	1588	1855	2082	2278	2464	2652	2840	3028	3218	3408
30000	1621	1891	2122	2323	2514	2706	2898	3092	3286	3481
31000	1653	1925	2160	2368	2564	2760	2957	3155	3354	3554
32000	1685	1962	2200	2413	2614	2815	3017	3220	3424	3628

QR1_DXMISC_004

RESERVE FUEL (LBS) – NBAA/IFR FORMAT

HOLDING TIME AT ALTERNATE – 60 MINUTES

ZFW LB	ALTERNATE DISTANCE (NM) - STILL AIR									
	50	100	150	200	250	300	350	400	450	500
26000	1814	2071	2283	2466	2641	2817	2993	3170	3348	3527
27000	1852	2111	2331	2517	2697	2877	3057	3239	3421	3604
28000	1890	2155	2377	2570	2754	2938	3123	3309	3496	3684
29000	1930	2197	2425	2624	2812	3000	3190	3380	3571	3763
30000	1970	2242	2474	2677	2870	3063	3257	3452	3647	3844
31000	2010	2284	2520	2729	2927	3125	3323	3523	3724	3925
32000	2048	2328	2566	2782	2986	3188	3392	3596	3802	4008

QR1_DXMSC_005

TRAINING PURPOSES ONLY

WIND COMPONENT CONVERSION TABLE

Angle (DEG)	Wind velocity (knots)									
	5	10	15	20	25	30	35	40	50	60
0	5	10	15	20	25	30	35	40	50	60
	0	0	0	0	0	0	0	0	0	0
10	5	10	15	20	25	30	34	39	49	59
	1	2	3	3	4	5	6	7	9	10
20	5	9	14	19	23	28	33	38	47	56
	2	3	5	7	9	10	12	14	17	21
30	4	9	13	17	22	26	30	35	43	52
	2	5	7	10	12	15	17	20	25	30
40	4	8	11	15	19	23	27	31	38	46
	3	6	10	13	16	19	22	26	32	39
50	3	6	10	13	16	19	22	26	32	39
	4	8	11	15	19	23	27	31	38	46
60	3	5	8	10	13	15	18	20	25	30
	4	9	13	17	22	26	30	35	43	52
70	2	3	5	7	9	10	12	14	17	21
	5	9	14	19	23	28	33	38	47	56
80	1	2	3	3	4	5	6	7	9	10
	5	10	15	20	25	30	34	39	49	59
90	0	0	0	0	0	0	0	0	0	0
	5	10	15	20	25	30	35	40	50	60
100	-1	-2	-3	-3	-4	-5	-6	-7	-9	-10
	5	10	15	20	25	30	34	39	49	59
110	-2	-3	-5	-7	-9	-10	-12	-14	-17	-21
	5	9	14	19	23	28	33	38	47	56
120	-2	-5	-7	-10	-12	-15	-17	-20	-25	-30
	4	9	13	17	22	26	30	35	43	52
130	-3	-6	-10	-13	-16	-19	-22	-26	-32	-39
	4	8	11	15	19	23	27	31	38	46
140	-4	-8	-11	-15	-19	-23	-27	-31	-38	-46
	3	6	10	13	16	19	22	26	32	39
150	-4	-9	-13	-17	-22	-26	-30	-35	-43	-52
	3	5	8	10	13	15	18	20	25	30
160	-5	-9	-14	-19	-23	-28	-33	-38	-47	-56
	2	3	5	7	9	10	12	14	17	21
170	-5	-10	-15	-20	-25	-30	-34	-39	-49	-59
	1	2	3	3	4	5	6	7	9	10
180	-5	-10	-15	-20	-25	-30	-35	-40	-50	-60
	0	0	0	0	0	0	0	0	0	0

Upper values (shaded): Components parallel to the runway

Lower values: Crosswind components

Angle measured between wind and runway

QR1MISC_001

BOMBARDIER CHALLENGER 605	<i>PERF-07-4</i>
	<i>REV 5, Jun 04/07</i>

THIS PAGE INTENTIONALLY LEFT BLANK

TRAINING PURPOSES ONLY

<i>QUICK REFERENCE HANDBOOK</i> <i>PSP 605-15</i>	MISCELLANEOUS DATA
--	---------------------------

DRIFTDOWN SPEED

VALID FOR ALL C.G.'S AND TEMPERATURES – KIAS

FLIGHT LEVEL	GROSS WEIGHT - 1000 LB						
	26	30	34	38	42	46	50
410	180	195	209	222	235	247	259
390	180	194	208	221	233	245	257
370	176	190	203	215	227	239	250
350	162	174	186	197	208	219	229
330	160	172	184	195	205	215	225
310	158	170	181	192	203	213	222
290	156	168	179	189	200	209	219
270	153	165	176	187	196	206	215
250	151	163	174	184	194	203	212
230	149	161	171	181	191	200	209
210	147	158	169	179	188	197	206
200	146	157	168	177	187	196	204
190	146	157	168	177	187	195	204
170	146	157	167	177	186	195	204
150	146	157	167	177	186	195	203

QR1_DXSE_001

DRIFTDOWN – BASED ON DRIFTDOWN SPEED**28,000 LB & 30,000 LB INITIAL WEIGHT**

(Maximum Continuous Thrust / One Pack on High / Anti-Ice Off / 30 % C.G.)

Initial Weight 28 000 LB		INITIAL PRESSURE ALTITUDE (100 FT)									
		230	250	270	290	310	330	350	370	390	410
ISA -10°C	Time(min)							29.5	34.0	35.7	37.0
	Dist(nam)							147	169	179	186
	Fuel(lb)							543	610	633	648
	Level Off(ft)							34351	34399	34421	34434
ISA	Time(min)							29.8	33.8	35.6	36.3
	Dist(nam)							152	171	182	187
	Fuel(lb)							566	627	652	658
	Level Off(ft)							34288	34332	34353	34365
ISA +10°C	Time(min)							29.5	32.9	34.9	36.3
	Dist(nam)							153	171	182	191
	Fuel(lb)							575	628	656	676
	Level Off(ft)							34215	34256	34275	34287
30000 LB		230	250	270	290	310	330	350	370	390	410
ISA -10°C	Time(min)						28.0	34.8	37.3	39.0	40.3
	Dist(nam)						141	172	184	194	202
	Fuel(lb)						552	665	702	725	742
	Level Off(ft)						32810	32897	32920	32939	32953
ISA	Time(min)						28.1	34.6	36.7	38.5	39.2
	Dist(nam)						144	175	185	196	201
	Fuel(lb)						571	682	713	738	746
	Level Off(ft)						32748	32828	32850	32867	32882
ISA +10°C	Time(min)						27.9	34.4	36.1	37.2	38.7
	Dist(nam)						146	177	186	194	202
	Fuel(lb)						584	696	720	735	756
	Level Off(ft)						32685	32758	32778	32795	32809

QR1_DXSE_002

DRIFTDOWN – BASED ON DRIFTDOWN SPEED**32,000 LB & 34,000 LB INITIAL WEIGHT**

(Maximum Continuous Thrust / One Pack on High / Anti-Ice Off / 30 % C.G.)

Initial Weight 32000 LB		INITIAL PRESSURE ALTITUDE (100 FT)									
		230	250	270	290	310	330	350	370	390	410
ISA -10°C	Time(min)						34.9	37.7	39.4	41.2	42.1
	Dist(nam)						173	186	194	205	212
	Fuel(lb)						710	752	775	802	813
	Level Off(ft)						31478	31511	31527	31545	31557
ISA	Time(min)						34.0	37.2	38.3	40.1	41.2
	Dist(nam)						172	187	194	205	211
	Fuel(lb)						713	763	777	806	819
	Level Off(ft)						31417	31447	31462	31480	31491
ISA +10°C	Time(min)						34.1	36.4	38.2	39.5	40.6
	Dist(nam)						176	187	197	206	213
	Fuel(lb)						734	768	798	816	830
	Level Off(ft)						31345	31374	31387	31405	31416
34000LB		230	250	270	290	310	330	350	370	390	410
ISA -10°C	Time(min)					31.9	37.4	39.9	41.7	42.6	43.8
	Dist(nam)					159	185	197	206	212	220
	Fuel(lb)					693	791	828	857	869	888
	Level Off(ft)					30091	30156	30179	30194	30204	30215
ISA	Time(min)					31.8	37.3	39.3	40.6	41.5	42.7
	Dist(nam)					162	188	198	205	211	219
	Fuel(lb)					711	811	841	859	873	893
	Level Off(ft)					30029	30092	30114	30129	30138	30148
ISA +10°C	Time(min)					31.7	36.5	38.6	40.0	41.0	41.6
	Dist(nam)					164	188	199	207	213	218
	Fuel(lb)					726	815	850	870	886	894
	Level Off(ft)					29960	30020	30041	30055	30063	30074

QR1_DXSE_003

DRIFTDOWN – BASED ON DRIFTDOWN SPEED**36,000 LB & 38,000 LB INITIAL WEIGHT**

(Maximum Continuous Thrust / One Pack on High / Anti-Ice Off / 30 C.G.)

Initial Weight 36000 LB		INITIAL PRESSURE ALTITUDE (100 FT)									
		230	250	270	290	310	330	350	370	390	410
ISA -10°C	Time(min)				32.6	36.3	39.9	42.2	43.4	44.2	45.0
	Dist(nam)				163	179	196	208	214	220	226
	Fuel(lb)				752	813	876	912	932	943	954
	Level Off(ft)				28765	28812	28850	28878	28883	28895	28906
ISA	Time(min)				32.0	36.1	39.3	41.7	42.3	43.2	44.0
	Dist(nam)				163	182	198	210	214	220	226
	Fuel(lb)				759	832	889	928	936	949	961
	Level Off(ft)				28701	28744	28781	28808	28813	28825	28835
ISA +10°C	Time(min)				32.1	35.8	38.6	41.0	41.7	42.6	43.5
	Dist(nam)				167	184	198	211	215	221	228
	Fuel(lb)				782	846	895	938	948	962	975
	Level Off(ft)				28631	28672	28707	28733	28737	28748	28758
38000 LB		230	250	270	290	310	330	350	370	390	410
ISA -10°C	Time(min)				35.5	39.8	41.7	43.8	44.8	45.6	
	Dist(nam)				175	196	205	216	222	227	
	Fuel(lb)				840	921	951	986	1000	1013	
	Level Off(ft)				27512	27569	27591	27610	27621	27629	
ISA	Time(min)				35.1	39.2	41.2	42.7	43.8	44.6	
	Dist(nam)				177	197	207	215	222	227	
	Fuel(lb)				855	933	966	991	1007	1020	
	Level Off(ft)				27449	27503	27524	27543	27553	27560	
ISA +10°C	Time(min)				34.6	38.9	40.5	42.1	43.2	44.0	
	Dist(nam)				178	199	208	216	223	228	
	Fuel(lb)				863	952	975	1002	1019	1034	
	Level Off(ft)				27376	27428	27448	27466	27475	27482	

QR1_DXSE_004

DRIFTDOWN – BASED ON DRIFTDOWN SPEED**40,000 LB & 42,000 LB INITIAL WEIGHT**

(Maximum Continuous Thrust / One Pack on High / Anti-Ice Off / 30 C.G.)

Initial Weight 40000 LB		INITIAL PRESSURE ALTITUDE (100 FT)									
		230	250	270	290	310	330	350	370	390	410
ISA -10°C	Time(min)			33.0	38.4	41.8	43.6	45.8	46.2	47.2	
	Dist(nam)			164	188	205	214	226	229	235	
	Fuel(lb)			825	936	1001	1030	1070	1072	1091	
	Level Off(ft)			26249	26317	26357	26374	26392	26399	26406	
ISA	Time(min)			32.8	38.2	41.2	43.1	44.8	45.2	46.2	
	Dist(nam)			166	191	207	216	225	229	235	
	Fuel(lb)			844	959	1016	1049	1076	1080	1101	
	Level Off(ft)			26191	26254	26293	26309	26327	26333	26340	
ISA +10°C	Time(min)			33.0	37.4	40.6	42.5	43.6	44.7	45.1	
	Dist(nam)			171	191	207	217	224	230	234	
	Fuel(lb)			872	961	1024	1061	1075	1096	1102	
	Level Off(ft)			26121	26181	26219	26233	26252	26257	26263	
42000 LB		230	250	270	290	310	330	350	370	390	410
ISA -10°C	Time(min)			37.3	40.9	43.6	45.4	46.8	47.5		
	Dist(nam)			183	200	213	223	231	235		
	Fuel(lb)			956	1030	1080	1111	1136	1146		
	Level Off(ft)			25110	25155	25182	25204	25214	25220		
ISA	Time(min)		32.7	37.0	40.3	43.0	44.9	45.8	46.5		
	Dist(nam)		167	185	201	215	225	230	234		
	Fuel(lb)		893	975	1043	1098	1132	1143	1155		
	Level Off(ft)		24995	25050	25093	25119	25140	25150	25155		
ISA +10°C	Time(min)		32.8	36.6	40.1	42.3	44.3	45.2	45.3		
	Dist(nam)		170	187	204	216	227	232	233		
	Fuel(lb)		915	989	1064	1107	1145	1159	1155		
	Level Off(ft)		24937	24978	25019	25044	25064	25073	25079		

QR1_DXSE_005

DRIFTDOWN – BASED ON DRIFTDOWN SPEED**44,000 LB & 46,000 LB INITIAL WEIGHT**

(Maximum Continuous Thrust / One Pack on High / Anti-Ice Off / 30 C.G.)

Initial Weight 44000 LB		INITIAL PRESSURE ALTITUDE (100 FT)									
		230	250	270	290	310	330	350	370	390	410
ISA -10°C	Time(min)		35.2	39.7	43.4	44.9	46.1	47.4	48.2		
	Dist(nam)		173	194	212	220	226	234	238		
	Fuel(lb)		953	1047	1126	1151	1168	1191	1207		
	Level Off(ft)		23949	24008	24045	24065	24078	24089	24094		
ISA	Time(min)		34.7	39.5	42.2	44.5	45.6	46.4	47.2		
	Dist(nam)		174	197	211	222	228	233	238		
	Fuel(lb)		965	1073	1126	1171	1190	1199	1217		
	Level Off(ft)		23893	23949	23986	24005	24016	24028	24032		
ISA +10°C	Time(min)		34.6	39.3	42.1	43.8	45.0	45.8	46.1		
	Dist(nam)		177	199	214	223	230	235	237		
	Fuel(lb)		985	1092	1151	1183	1204	1215	1218		
	Level Off(ft)		23824	23876	23911	23930	23941	23952	23957		
46000 LB		230	250	270	290	310	330	350	370	390	410
ISA -10°C	Time(min)	31.5	38.6	42.5	44.2	46.4	47.5	48.7			
	Dist(nam)	158	188	207	215	226	233	240			
	Fuel(lb)	904	1069	1155	1186	1229	1246	1265			
	Level Off(ft)	22795	22890	22938	22959	22976	22990	23003			
ISA	Time(min)	32.0	38.3	41.9	43.7	45.3	46.5	47.7			
	Dist(nam)	163	191	208	217	226	233	240			
	Fuel(lb)	941	1092	1170	1204	1235	1254	1274			
	Level Off(ft)	22746	22834	22880	22900	22917	22931	22943			
ISA +10°C	Time(min)	32.2	37.9	41.7	43.0	44.7	45.9	47.1			
	Dist(nam)	167	193	211	218	227	234	241			
	Fuel(lb)	969	1106	1192	1213	1247	1268	1289			
	Level Off(ft)	22679	22761	22805	22824	22841	22853	22866			

QR1_DXSE_006

DRIFTDOWN – BASED ON DRIFTDOWN SPEED**48,000 LB & 50,000 LB INITIAL WEIGHT**

(Maximum Continuous Thrust / One Pack on High / Anti-Ice Off / 30 C.G.)

Initial Weight 48000 LB		INITIAL PRESSURE ALTITUDE (100 FT)									
		230	250	270	290	310	330	350	370	390	410
ISA -10°C	Time(min)	36.7	41.6	44.9	46.2	47.6	49.1	50.1			
	Dist(nam)	180	202	218	224	232	241	247			
	Fuel(lb)	1069	1185	1256	1277	1301	1330	1348			
	Level Off(ft)	21774	21832	21869	21887	21903	21917	21926			
ISA	Time(min)	36.8	40.9	43.7	45.7	47.1	48.1	49.2			
	Dist(nam)	184	203	217	227	234	241	247			
	Fuel(lb)	1101	1198	1258	1299	1326	1340	1360			
	Level Off(ft)	21721	21777	21813	21829	21844	21858	21867			
ISA +10°C	Time(min)	36.7	40.7	43.6	45.0	46.5	47.5	48.6			
	Dist(nam)	187	205	220	228	236	242	249			
	Fuel(lb)	1124	1218	1284	1311	1340	1356	1378			
	Level Off(ft)	21648	21701	21736	21751	21766	21780	21789			
50000 LB		230	250	270	290	310	330	350	370	390	410
ISA -10°C	Time(min)	40.5	44.1	46.2	47.8	49.4	50.3	51.7			
	Dist(nam)	196	213	224	232	240	246	254			
	Fuel(lb)	1207	1289	1332	1362	1395	1410	1437			
	Level Off(ft)	20747	20790	20817	20836	20850	20861	20872			
ISA	Time(min)	39.7	43.5	45.7	47.3	48.4	49.3	50.7			
	Dist(nam)	197	215	226	234	241	246	255			
	Fuel(lb)	1217	1308	1355	1387	1405	1421	1451			
	Level Off(ft)	20694	20735	20761	20779	20793	20804	20814			
ISA +10°C	Time(min)	39.9	42.7	45.0	46.7	47.8	48.8	49.6			
	Dist(nam)	201	215	227	236	242	248	254			
	Fuel(lb)	1251	1313	1365	1400	1421	1438	1452			
	Level Off(ft)	20617	20658	20682	20700	20713	20723	20734			

QR1_DXSE_007

HIGH SPEED DRIFTDOWN – MACH 0.72/260 KIAS**28,000 LB & 30,000 LB INITIAL WEIGHT****(Maximum Continuous Thrust / One Pack on High / Anti-Ice Off / 30 % C.G.)**

Initial Weight 28 000 LB		INITIAL PRESSURE ALTITUDE (100 FT)									
		230	250	270	290	310	330	350	370	390	410
ISA -10°C	Time(min)	31.5	35.1	37.4	39.2	40.8	42.4	43.6	45.3	47.0	48.3
	Dist(nam)	187	209	223	235	246	256	265	276	287	296
	Fuel(lb)	969	1068	1124	1167	1205	1240	1263	1294	1325	1341
	Level Off(ft)	21647	21662	21670	21676	21681	21685	21689	21693	21697	21700
ISA	Time(min)	31.3	34.9	36.7	38.6	40.2	41.3	42.6	44.3	45.6	47.4
	Dist(nam)	189	212	224	236	247	255	264	275	285	296
	Fuel(lb)	992	1091	1138	1184	1225	1248	1272	1306	1326	1358
	Level Off(ft)	21507	21521	21528	21534	21539	21543	21547	21551	21555	21557
ISA +10°C	Time(min)	31.1	34.5	36.5	37.9	39.6	40.7	42.0	43.7	45.0	46.3
	Dist(nam)	191	213	226	236	247	255	265	277	286	295
	Fuel(lb)	1011	1108	1160	1195	1237	1262	1289	1326	1346	1367
	Level Off(ft)	21359	21372	21378	21385	21388	21392	21397	21400	21404	21407
30 000 LB		230	250	270	290	310	330	350	370	390	410
ISA -10°C	Time(min)	32.8	36.5	38.8	40.6	42.1	43.7	45.4	46.6	48.3	49.6
	Dist(nam)	194	217	231	242	253	263	275	283	295	304
	Fuel(lb)	1017	1116	1173	1215	1252	1286	1322	1340	1371	1388
	Level Off(ft)	21373	21389	21397	21405	21410	21414	21419	21424	21427	21431
ISA	Time(min)	32.3	36.2	38.1	39.9	41.6	42.7	44.4	45.6	47.4	48.7
	Dist(nam)	195	219	231	243	254	262	274	283	295	304
	Fuel(lb)	1031	1141	1188	1234	1273	1295	1334	1353	1387	1406
	Level Off(ft)	21236	21251	21259	21266	21271	21276	21280	21285	21288	21292
ISA +10°C	Time(min)	32.2	35.5	37.4	39.3	40.5	42.1	43.4	44.6	46.4	47.7
	Dist(nam)	198	219	232	244	252	263	273	282	294	303
	Fuel(lb)	1055	1146	1198	1246	1273	1312	1338	1360	1396	1417
	Level Off(ft)	21092	21106	21114	21120	21125	21129	21134	21138	21141	21145

CL604_CL605_QRH_drift_260k_wgt1_imp_May09.ps

QR1_DXSE_008

HIGH SPEED DRIFTDOWN – MACH 0.72/260 KIAS**32,000 LB & 34,000 LB INITIAL WEIGHT****(Maximum Continuous Thrust / One Pack on High / Anti-Ice Off / 30 % C.G.)**

Initial Weight 32 000 LB		INITIAL PRESSURE ALTITUDE (100 FT)									
		230	250	270	290	310	330	350	370	390	410
ISA -10°C	Time(min)	34.6	38.2	40.5	42.2	43.8	45.3	47.0	48.7	50.0	51.3
	Dist(nam)	204	226	240	252	262	272	284	295	304	313
	Fuel(lb)	1080	1175	1233	1274	1310	1344	1380	1412	1430	1448
	Level Off(ft)	21078	21094	21102	21110	21115	21120	21125	21129	21134	21137
ISA	Time(min)	34.2	37.9	39.8	41.6	43.2	44.3	46.0	47.3	48.6	50.4
	Dist(nam)	205	229	241	253	263	271	283	292	301	313
	Fuel(lb)	1097	1202	1250	1294	1333	1355	1393	1413	1433	1469
	Level Off(ft)	20944	20959	20968	20975	20980	20985	20990	20994	20998	21001
ISA +10°C	Time(min)	34.1	37.6	39.5	41.4	42.5	43.6	45.4	46.7	48.0	49.3
	Dist(nam)	209	231	243	256	264	272	284	294	303	312
	Fuel(lb)	1123	1222	1274	1321	1347	1370	1411	1433	1455	1477
	Level Off(ft)	20798	20812	20820	20827	20832	20837	20842	20846	20850	20854
34 000 LB		230	250	270	290	310	330	350	370	390	410
ISA -10°C	Time(min)	36.1	39.9	42.2	44.0	45.5	47.0	48.3	50.0	51.3	52.6
	Dist(nam)	212	235	249	261	271	281	290	302	310	319
	Fuel(lb)	1134	1236	1296	1337	1372	1406	1428	1461	1480	1499
	Level Off(ft)	20753	20770	20780	20788	20794	20800	20806	20811	20815	20819
ISA	Time(min)	35.7	39.2	41.1	42.9	44.5	46.1	47.3	49.0	50.3	51.7
	Dist(nam)	214	236	248	260	270	281	290	302	311	320
	Fuel(lb)	1155	1252	1301	1345	1383	1419	1443	1478	1498	1519
	Level Off(ft)	20618	20635	20645	20653	20659	20664	20670	20674	20679	20683
ISA +10°C	Time(min)	35.7	38.9	40.9	42.7	43.9	45.0	46.7	48.0	49.3	50.6
	Dist(nam)	218	238	251	263	271	279	292	301	310	319
	Fuel(lb)	1184	1274	1327	1374	1399	1422	1463	1485	1507	1530
	Level Off(ft)	20472	20488	20497	20505	20511	20517	20522	20527	20531	20535

CL604_CL605_QRH_drift_260k_wgt2_imp_May09.ps

QR1_DXSE_009

HIGH SPEED DRIFTDOWN – MACH 0.72/260 KIAS

36,000 LB & 38,000 LB INITIAL WEIGHT
(Maximum Continuous Thrust / One Pack on High / Anti-Ice Off / 30 C.G.)

Initial Weight 36 000 LB		INITIAL PRESSURE ALTITUDE (100 FT)									
		230	250	270	290	310	330	350	370	390	410
ISA -10°C	Time(min)	38.1	41.6	43.5	45.3	46.8	48.3	49.6	51.3	53.0	54.4
	Dist(nam)	222	244	256	268	278	288	297	308	320	329
	Fuel(lb)	1205	1301	1348	1389	1424	1458	1480	1513	1547	1568
	Level Off(ft)	20389	20407	20418	20427	20434	20440	20446	20451	20456	20460
ISA	Time(min)	37.7	41.0	42.9	44.3	45.8	47.4	48.6	50.3	51.6	53.0
	Dist(nam)	225	245	258	267	277	288	297	308	317	327
	Fuel(lb)	1230	1319	1369	1398	1436	1472	1495	1531	1552	1576
	Level Off(ft)	20258	20275	20285	20294	20301	20306	20313	20318	20322	20326
ISA +10°C	Time(min)	37.3	40.2	42.2	44.1	45.2	46.7	48.0	49.3	50.6	52.0
	Dist(nam)	226	245	258	270	278	289	298	308	317	327
	Fuel(lb)	1247	1327	1382	1430	1454	1492	1517	1540	1564	1589
	Level Off(ft)	20113	20130	20139	20148	20154	20160	20166	20171	20176	20179
38 000 LB		230	250	270	290	310	330	350	370	390	410
ISA -10°C	Time(min)	39.6	42.9	44.9	46.7	48.2	49.7	51.0	52.7	54.0	55.4
	Dist(nam)	231	251	263	275	285	295	304	315	324	333
	Fuel(lb)	1266	1355	1404	1445	1481	1514	1536	1570	1591	1615
	Level Off(ft)	19987	20006	20017	20027	20034	20041	20048	20054	20059	20063
ISA	Time(min)	39.9	42.9	44.9	46.7	47.8	49.4	50.7	52.0	53.3	54.7
	Dist(nam)	237	255	268	280	288	298	308	317	326	335
	Fuel(lb)	1313	1394	1447	1492	1515	1551	1575	1598	1621	1647
	Level Off(ft)	19860	19879	19889	19899	19906	19912	19919	19925	19930	19934
ISA +10°C	Time(min)	40.3	42.9	44.9	46.3	47.9	49.0	50.3	51.6	53.0	54.4
	Dist(nam)	243	260	273	283	293	301	311	320	330	339
	Fuel(lb)	1359	1430	1486	1518	1558	1581	1607	1632	1657	1684
	Level Off(ft)	19712	19731	19741	19750	19757	19764	19770	19776	19781	19785

CL604_CL605_QRH_drift_260k_wgt3_imp_May09.ps

QR1_DXSE_010

HIGH SPEED DRIFTDOWN – MACH 0.72/260 KIAS**40,000 LB & 42,000 LB INITIAL WEIGHT****(Maximum Continuous Thrust / One Pack on High / Anti-Ice Off / 30 C.G.)**

Initial Weight 40 000 LB		INITIAL PRESSURE ALTITUDE (100 FT)									
		230	250	270	290	310	330	350	370	390	410
ISA -10°C	Time(min)	42.4	45.9	47.5	49.3	50.8	52.3	53.6	55.3	56.7	57.6
	Dist(nam)	246	266	276	288	298	308	317	329	338	344
	Fuel(lb)	1370	1466	1501	1544	1580	1614	1637	1673	1696	1706
	Level Off(ft)	19540	19559	19571	19581	19589	19596	19603	19609	19614	19619
ISA	Time(min)	42.1	45.2	46.8	48.6	50.2	51.3	53.0	54.3	55.7	56.7
	Dist(nam)	248	268	278	290	300	308	320	329	338	345
	Fuel(lb)	1400	1486	1525	1570	1608	1629	1669	1692	1717	1729
	Level Off(ft)	19415	19433	19445	19454	19462	19469	19476	19482	19487	19491
ISA +10°C	Time(min)	42.2	44.9	46.6	48.4	49.5	50.6	52.4	53.7	54.6	56.1
	Dist(nam)	253	271	281	294	302	310	322	331	338	348
	Fuel(lb)	1438	1513	1556	1603	1628	1651	1694	1718	1730	1759
	Level Off(ft)	19271	19289	19299	19309	19316	19323	19330	19336	19341	19345
42 000 LB		230	250	270	290	310	330	350	370	390	410
ISA -10°C	Time(min)	45.0	47.8	49.9	51.7	52.8	54.3	55.6	56.9	58.3	59.3
	Dist(nam)	259	276	289	300	308	318	327	336	345	352
	Fuel(lb)	1471	1543	1596	1640	1662	1697	1721	1743	1768	1781
	Level Off(ft)	19052	19072	19083	19094	19102	19110	19117	19124	19129	19134
ISA	Time(min)	44.7	47.5	49.3	50.6	52.2	53.3	54.6	56.0	57.4	58.4
	Dist(nam)	262	280	290	300	310	318	328	337	346	353
	Fuel(lb)	1503	1580	1623	1654	1693	1715	1741	1766	1793	1808
	Level Off(ft)	18929	18948	18959	18970	18978	18986	18993	19000	19005	19009
ISA +10°C	Time(min)	44.8	47.2	49.0	50.4	51.5	52.6	54.0	55.3	56.7	57.7
	Dist(nam)	267	283	294	304	312	320	329	339	349	356
	Fuel(lb)	1543	1609	1654	1688	1713	1737	1765	1791	1821	1837
	Level Off(ft)	18783	18801	18812	18822	18830	18838	18845	18852	18857	18861

CL604_CL605_QRH_drift_260k_wgt4_imp_May09.ps

QR1_DXSE_011

HIGH SPEED DRIFTDOWN – MACH 0.72/260 KIAS**44,000 LB & 46,000 LB INITIAL WEIGHT****(Maximum Continuous Thrust / One Pack on High / Anti-Ice Off / 30 C.G.)**

Initial Weight 44 000 LB		INITIAL PRESSURE ALTITUDE (100 FT)									
		230	250	270	290	310	330	350	370	390	410
ISA -10°C	Time(min)	47.7	50.1	51.8	53.7	54.8	56.3	57.7	59.0	59.9	61.0
	Dist(nam)	272	287	298	310	317	328	337	346	353	359
	Fuel(lb)	1575	1637	1679	1725	1747	1782	1807	1831	1844	1859
	Level Off(ft)	18528	18548	18559	18570	18579	18587	18595	18602	18608	18612
ISA	Time(min)	47.0	49.5	51.3	52.7	53.8	55.4	56.7	58.0	59.0	60.0
	Dist(nam)	274	289	300	310	318	328	338	347	354	361
	Fuel(lb)	1598	1664	1709	1741	1765	1804	1830	1857	1870	1887
	Level Off(ft)	18408	18427	18438	18449	18458	18465	18473	18479	18485	18489
ISA +10°C	Time(min)	46.7	48.8	50.6	52.0	53.2	54.3	55.7	57.0	58.0	59.0
	Dist(nam)	277	290	302	312	320	328	338	347	354	361
	Fuel(lb)	1627	1681	1729	1764	1790	1814	1843	1870	1886	1904
	Level Off(ft)	18266	18284	18295	18305	18313	18321	18328	18335	18340	18344
46 000 LB		230	250	270	290	310	330	350	370	390	410
ISA -10°C	Time(min)	49.2	51.7	53.5	55.4	56.5	57.6	58.9	60.3	61.3	62.3
	Dist(nam)	279	295	306	317	325	333	342	351	358	365
	Fuel(lb)	1643	1709	1753	1801	1824	1845	1871	1897	1911	1930
	Level Off(ft)	17976	17995	18007	18018	18027	18036	18044	18050	18056	18060
ISA	Time(min)	48.6	51.1	52.5	53.9	55.5	56.7	58.0	59.4	60.4	61.0
	Dist(nam)	281	297	306	315	326	334	343	352	359	364
	Fuel(lb)	1668	1740	1770	1804	1845	1868	1896	1924	1940	1944
	Level Off(ft)	17860	17878	17890	17901	17909	17917	17925	17932	17937	17942
ISA +10°C	Time(min)	48.3	50.5	51.9	53.4	54.5	55.7	57.0	58.0	59.4	60.0
	Dist(nam)	285	299	308	318	326	334	344	350	360	365
	Fuel(lb)	1702	1761	1794	1830	1857	1882	1912	1926	1960	1964
	Level Off(ft)	17724	17741	17752	17763	17771	17779	17787	17794	17799	17803

CL604_CL605_QRH_drift_260k_wgt5_imp_May09.ps

QR1_DXSE_012

HIGH SPEED DRIFTDOWN – MACH 0.72/260 KIAS**48,000 LB & 50,000 LB INITIAL WEIGHT****(Maximum Continuous Thrust / One Pack on High / Anti-Ice Off / 30 C.G.)**

Initial Weight 48 000 LB		INITIAL PRESSURE ALTITUDE (100 FT)									
		230	250	270	290	310	330	350	370	390	410
ISA -10°C	Time(min)	51.2	53.3	55.2	56.6	57.8	58.9	60.3	61.6	62.7	63.3
	Dist(nam)	288	302	313	322	330	338	347	356	363	368
	Fuel(lb)	1729	1785	1832	1865	1890	1912	1939	1967	1984	1991
	Level Off(ft)	17389	17407	17419	17430	17440	17448	17456	17463	17468	17472
ISA	Time(min)	50.5	52.8	54.2	55.7	56.8	58.0	59.3	60.3	61.3	62.5
	Dist(nam)	290	304	313	323	331	339	349	355	363	370
	Fuel(lb)	1757	1816	1851	1886	1913	1936	1966	1980	1998	2022
	Level Off(ft)	17275	17294	17305	17316	17325	17334	17341	17348	17354	17357
ISA +10°C	Time(min)	49.9	51.7	53.2	54.7	55.9	57.0	58.4	59.3	60.4	61.1
	Dist(nam)	292	304	313	323	331	340	349	356	364	369
	Fuel(lb)	1778	1824	1861	1899	1927	1952	1985	1999	2019	2028
	Level Off(ft)	17145	17163	17174	17185	17193	17201	17209	17216	17221	17225
50 000 LB		230	250	270	290	310	330	350	370	390	410
ISA -10°C	Time(min)	53.4	55.7	57.1	58.6	59.8	61.0	62.4	63.3	64.3	65.1
	Dist(nam)	299	313	322	331	339	347	356	363	370	375
	Fuel(lb)	1828	1888	1923	1957	1984	2007	2036	2050	2069	2080
	Level Off(ft)	16770	16788	16800	16812	16820	16829	16837	16844	16850	16853
ISA	Time(min)	52.8	54.7	56.2	57.7	58.9	60.0	61.0	62.4	63.0	63.7
	Dist(nam)	301	313	322	332	340	348	355	365	369	374
	Fuel(lb)	1860	1906	1944	1981	2009	2034	2048	2081	2084	2096
	Level Off(ft)	16656	16674	16686	16697	16706	16714	16722	16729	16734	16738
ISA +10°C	Time(min)	51.8	53.7	55.2	56.7	57.5	58.6	60.0	61.0	62.1	62.8
	Dist(nam)	301	313	322	333	338	347	356	363	371	376
	Fuel(lb)	1866	1917	1956	1996	2008	2035	2069	2085	2108	2121
	Level Off(ft)	16529	16547	16558	16568	16577	16586	16593	16600	16605	16608

CL604_CL605_QRH_drift_260k_wgt6_imp_May09.ps

QR1_DXSE_013

HIGH SPEED DRIFTDOWN – MACH 0.72/300 KIAS

28,000 LB & 30,000 LB INITIAL WEIGHT
(Maximum Continuous Thrust / One Pack on High / Anti-Ice Off / 30 % C.G.)

Initial Weight 28 000 LB		INITIAL PRESSURE ALTITUDE (100 FT)									
		230	250	270	290	310	330	350	370	390	410
ISA -10°C	Time(min)	45.3	46.4	47.7	48.7	50.4	51.7	53.4	54.6	56.3	57.6
	Dist(nam)	276	283	292	299	311	320	331	340	351	360
	Fuel(lb)	1742	1772	1811	1830	1876	1902	1938	1954	1986	2000
	Level Off(ft)	13350	13352	13353	13355	13357	13359	13360	13362	13363	13365
ISA	Time(min)	44.4	45.4	46.7	47.7	49.0	50.3	52.0	53.3	55.0	56.3
	Dist(nam)	275	282	292	299	308	317	329	338	350	359
	Fuel(lb)	1752	1783	1824	1845	1877	1905	1945	1964	1998	2016
	Level Off(ft)	13193	13195	13196	13198	13200	13202	13203	13205	13207	13208
ISA +10°C	Time(min)	43.4	44.4	45.4	46.7	48.0	49.4	50.7	52.0	53.7	55.0
	Dist(nam)	273	281	288	298	307	317	326	335	347	357
	Fuel(lb)	1755	1787	1814	1853	1887	1917	1944	1964	2002	2021
	Level Off(ft)	13045	13046	13048	13050	13051	13053	13055	13057	13058	13059
30 000 LB		230	250	270	290	310	330	350	370	390	410
ISA -10°C	Time(min)	47.0	48.1	49.4	50.7	52.0	53.3	55.0	56.7	58.0	59.7
	Dist(nam)	286	293	302	312	321	330	341	352	361	373
	Fuel(lb)	1810	1839	1877	1911	1940	1965	2000	2033	2049	2081
	Level Off(ft)	13238	13240	13242	13244	13246	13249	13251	13252	13254	13255
ISA	Time(min)	46.0	47.1	48.4	49.3	51.0	52.4	53.7	55.3	56.6	58.4
	Dist(nam)	285	292	302	309	321	330	339	350	360	371
	Fuel(lb)	1821	1851	1892	1911	1959	1986	2009	2044	2062	2096
	Level Off(ft)	13083	13085	13087	13089	13091	13093	13095	13097	13099	13100
ISA +10°C	Time(min)	45.8	46.4	47.7	48.7	50.0	51.7	53.0	54.3	55.7	57.4
	Dist(nam)	288	293	303	310	319	331	341	350	360	371
	Fuel(lb)	1856	1871	1913	1934	1968	2014	2040	2060	2081	2118
	Level Off(ft)	12933	12935	12937	12940	12942	12943	12945	12947	12949	12950

CL604_CL605_QRH_drift_300k_wgt1_imp_May09.ps

QR1_DXSE_014

HIGH SPEED DRIFTDOWN – MACH 0.72/300 KIAS**32,000 LB & 34,000 LB INITIAL WEIGHT****(Maximum Continuous Thrust / One Pack on High / Anti-Ice Off / 30 % C.G.)**

Initial Weight 32 000 LB		INITIAL PRESSURE ALTITUDE (100 FT)									
		230	250	270	290	310	330	350	370	390	410
ISA -10°C	Time(min)	48.7	49.7	51.0	52.3	54.0	55.3	57.0	58.7	60.0	61.3
	Dist(nam)	296	303	312	321	333	342	353	364	373	382
	Fuel(lb)	1879	1905	1942	1975	2020	2044	2080	2113	2130	2147
	Level Off(ft)	13110	13113	13115	13118	13119	13122	13124	13126	13128	13129
ISA	Time(min)	48.0	49.0	50.3	51.7	53.0	54.7	56.0	57.7	59.0	60.3
	Dist(nam)	297	304	313	323	332	344	353	365	374	383
	Fuel(lb)	1905	1934	1973	2009	2039	2082	2105	2140	2159	2179
	Level Off(ft)	12958	12960	12962	12964	12967	12969	12971	12973	12974	12976
ISA +10°C	Time(min)	47.7	48.7	50.1	51.0	52.3	54.0	55.4	56.7	58.4	59.7
	Dist(nam)	300	307	317	324	334	346	355	364	376	386
	Fuel(lb)	1942	1971	2013	2033	2066	2111	2137	2157	2195	2218
	Level Off(ft)	12806	12809	12811	12813	12815	12817	12819	12821	12823	12824
34 000 LB		230	250	270	290	310	330	350	370	390	410
ISA -10°C	Time(min)	49.4	50.7	52.0	53.4	54.6	56.3	58.0	59.7	61.0	62.3
	Dist(nam)	300	309	318	327	336	348	359	370	379	388
	Fuel(lb)	1908	1950	1986	2018	2045	2086	2122	2154	2172	2191
	Level Off(ft)	12971	12973	12977	12980	12983	12986	12988	12990	12993	12994
ISA	Time(min)	49.1	50.1	51.4	52.7	54.0	55.7	57.4	58.6	60.3	61.7
	Dist(nam)	303	310	320	329	338	350	361	370	382	391
	Fuel(lb)	1952	1979	2017	2051	2080	2123	2161	2180	2216	2237
	Level Off(ft)	12814	12817	12820	12824	12827	12829	12832	12834	12836	12838
ISA +10°C	Time(min)	48.5	49.4	50.3	52.1	53.4	54.7	56.4	57.6	59.4	60.7
	Dist(nam)	304	311	319	331	340	350	361	371	382	392
	Fuel(lb)	1974	2003	2026	2078	2110	2138	2179	2200	2239	2263
	Level Off(ft)	12665	12667	12671	12673	12676	12679	12681	12684	12685	12687

CL604_CL605_QRH_drift_300k_wgt2_imp_May09.ps

QR1_DXSE_015

HIGH SPEED DRIFTDOWN – MACH 0.72/300 KIAS**36,000 LB & 38,000 LB INITIAL WEIGHT****(Maximum Continuous Thrust / One Pack on High / Anti-Ice Off / 30 C.G.)**

Initial Weight 36 000 LB		INITIAL PRESSURE ALTITUDE (100 FT)									
		230	250	270	290	310	330	350	370	390	410
ISA -10°C	Time(min)	51.4	52.4	53.7	55.4	56.7	58.0	59.6	61.3	62.6	64.0
	Dist(nam)	311	318	327	339	348	357	368	380	389	398
	Fuel(lb)	1995	2019	2055	2103	2130	2154	2191	2225	2244	2266
	Level Off(ft)	12791	12795	12799	12802	12806	12809	12812	12814	12817	12819
ISA	Time(min)	50.4	51.7	53.0	54.4	55.7	57.4	58.7	60.0	61.3	62.7
	Dist(nam)	311	320	329	339	348	360	369	378	387	397
	Fuel(lb)	2010	2052	2090	2124	2153	2196	2219	2239	2261	2284
	Level Off(ft)	12636	12639	12642	12646	12649	12652	12655	12658	12660	12662
ISA +10°C	Time(min)	49.8	50.7	52.0	53.4	54.7	56.0	57.3	59.0	60.4	61.3
	Dist(nam)	312	319	329	338	348	357	367	379	388	395
	Fuel(lb)	2034	2062	2102	2138	2169	2197	2223	2262	2286	2295
	Level Off(ft)	12488	12491	12494	12497	12501	12504	12507	12509	12512	12514
38 000 LB		230	250	270	290	310	330	350	370	390	410
ISA -10°C	Time(min)	52.1	53.4	54.7	56.0	57.6	59.3	60.6	62.3	63.6	65.0
	Dist(nam)	315	324	333	342	354	365	374	385	394	403
	Fuel(lb)	2029	2067	2101	2132	2174	2215	2236	2271	2291	2315
	Level Off(ft)	12588	12593	12597	12601	12605	12609	12612	12615	12618	12620
ISA	Time(min)	51.1	52.4	53.7	55.4	56.7	58.4	59.7	61.4	62.7	63.7
	Dist(nam)	314	323	333	344	354	365	375	386	395	402
	Fuel(lb)	2044	2085	2121	2170	2199	2242	2265	2304	2327	2335
	Level Off(ft)	12435	12439	12443	12447	12451	12454	12458	12460	12463	12465
ISA +10°C	Time(min)	50.5	51.8	53.1	54.4	55.7	57.0	58.7	60.0	61.4	62.3
	Dist(nam)	316	325	335	344	354	363	375	384	394	401
	Fuel(lb)	2069	2112	2150	2185	2216	2244	2287	2310	2336	2346
	Level Off(ft)	12289	12293	12297	12301	12305	12308	12311	12314	12317	12319

CL604_CL605_QRH_drift_300k_wgt3_imp_May09.ps

QR1_DXSE_016

HIGH SPEED DRIFTDOWN – MACH 0.72/300 KIAS**40,000 LB & 42,000 LB INITIAL WEIGHT****(Maximum Continuous Thrust / One Pack on High / Anti-Ice Off / 30 C.G.)**

Initial Weight 40 000 LB		INITIAL PRESSURE ALTITUDE (100 FT)									
		230	250	270	290	310	330	350	370	390	410
ISA -10°C	Time(min)	53.8	55.1	56.4	57.6	59.4	60.6	62.4	63.6	65.0	66.0
	Dist(nam)	324	333	342	351	363	372	384	392	401	408
	Fuel(lb)	2103	2141	2176	2206	2250	2274	2313	2333	2356	2367
	Level Off(ft)	12358	12362	12366	12371	12375	12379	12382	12385	12388	12390
ISA	Time(min)	52.8	54.1	55.4	56.7	58.0	59.3	61.0	62.3	63.7	64.7
	Dist(nam)	324	333	342	352	361	371	382	391	401	408
	Fuel(lb)	2122	2163	2199	2231	2261	2287	2329	2352	2378	2389
	Level Off(ft)	12207	12211	12216	12220	12225	12229	12232	12235	12237	12240
ISA +10°C	Time(min)	51.8	52.7	54.0	55.3	56.7	58.4	59.7	61.0	62.0	63.4
	Dist(nam)	323	330	340	350	359	371	381	390	397	407
	Fuel(lb)	2134	2157	2196	2231	2263	2309	2336	2361	2371	2402
	Level Off(ft)	12065	12070	12074	12079	12083	12086	12090	12093	12096	12097
42 000 LB		230	250	270	290	310	330	350	370	390	410
ISA -10°C	Time(min)	54.4	56.1	57.3	58.6	60.3	61.6	63.4	64.7	66.0	67.0
	Dist(nam)	327	338	347	357	368	377	389	398	407	414
	Fuel(lb)	2136	2190	2223	2253	2298	2322	2362	2384	2410	2422
	Level Off(ft)	12112	12116	12122	12127	12131	12136	12139	12142	12145	12147
ISA	Time(min)	53.8	55.1	56.4	57.7	59.4	60.7	62.0	63.3	64.7	65.7
	Dist(nam)	329	338	348	357	369	378	387	397	406	413
	Fuel(lb)	2172	2211	2247	2280	2326	2353	2377	2403	2430	2444
	Level Off(ft)	11966	11970	11975	11980	11984	11988	11992	11995	11998	12000
ISA +10°C	Time(min)	52.8	54.1	55.4	56.7	58.0	59.7	61.0	62.4	63.3	64.4
	Dist(nam)	329	338	347	357	367	379	388	398	405	412
	Fuel(lb)	2182	2224	2261	2296	2327	2374	2401	2428	2440	2456
	Level Off(ft)	11826	11831	11835	11840	11845	11848	11852	11855	11858	11860

CL604_CL605_QRH_drift_300k_wgt4_imp_May09.ps

QR1_DXSE_017

HIGH SPEED DRIFTDOWN – MACH 0.72/300 KIAS

44,000 LB & 46,000 LB INITIAL WEIGHT
(Maximum Continuous Thrust / One Pack on High / Anti-Ice Off / 30 C.G.)

Initial Weight 44 000 LB		INITIAL PRESSURE ALTITUDE (100 FT)									
		230	250	270	290	310	330	350	370	390	410
ISA -10°C	Time(min)	55.8	57.0	58.7	60.0	61.3	63.0	64.4	65.7	66.6	67.7
	Dist(nam)	334	343	355	364	373	385	394	403	410	416
	Fuel(lb)	2201	2237	2288	2318	2346	2389	2414	2438	2448	2464
	Level Off(ft)	11845	11850	11855	11861	11866	11870	11874	11877	11881	11883
ISA	Time(min)	54.8	56.0	57.3	58.6	60.4	61.7	63.0	64.3	65.3	66.4
	Dist(nam)	334	343	353	362	374	384	393	402	409	416
	Fuel(lb)	2221	2260	2295	2329	2376	2404	2430	2457	2470	2487
	Level Off(ft)	11700	11705	11711	11716	11720	11725	11729	11732	11735	11737
ISA +10°C	Time(min)	53.8	55.1	56.4	57.7	59.0	60.3	61.7	63.0	64.0	65.1
	Dist(nam)	334	343	353	363	372	382	391	401	408	415
	Fuel(lb)	2234	2275	2313	2347	2379	2409	2438	2467	2480	2500
	Level Off(ft)	11563	11568	11573	11578	11583	11587	11591	11595	11598	11600
46 000 LB		230	250	270	290	310	330	350	370	390	410
ISA -10°C	Time(min)	57.1	58.3	60.0	61.3	63.0	64.3	65.7	67.0	68.0	69.1
	Dist(nam)	341	350	362	371	383	392	401	410	416	423
	Fuel(lb)	2266	2302	2352	2383	2428	2454	2480	2506	2520	2539
	Level Off(ft)	11559	11564	11570	11575	11580	11585	11589	11593	11595	11598
ISA	Time(min)	56.1	57.4	58.7	60.0	61.7	63.0	64.4	65.3	66.7	67.4
	Dist(nam)	342	351	360	369	381	391	400	407	416	421
	Fuel(lb)	2288	2327	2362	2395	2443	2471	2499	2510	2543	2546
	Level Off(ft)	11416	11422	11427	11433	11438	11442	11446	11450	11452	11455
ISA +10°C	Time(min)	55.1	56.4	57.7	59.0	60.3	61.7	63.0	64.0	65.4	66.0
	Dist(nam)	342	351	360	370	379	389	399	405	415	420
	Fuel(lb)	2302	2343	2380	2415	2447	2478	2508	2521	2556	2560
	Level Off(ft)	11281	11286	11292	11298	11303	11307	11311	11314	11317	11319

CL604_CL605_QRH_drift_300k_wgt5_imp_May09.ps

QR1_DXSE_018

HIGH SPEED DRIFTDOWN – MACH 0.72/300 KIAS**48,000 LB & 50,000 LB INITIAL WEIGHT****(Maximum Continuous Thrust / One Pack on High / Anti-Ice Off / 30 C.G.)**

Initial Weight 48 000 LB		INITIAL PRESSURE ALTITUDE (100 FT)									
		230	250	270	290	310	330	350	370	390	410
ISA -10°C	Time(min)	58.2	59.4	60.7	62.0	63.3	65.0	66.4	67.3	68.3	69.4
	Dist(nam)	347	355	365	374	383	395	404	410	417	424
	Fuel(lb)	2323	2359	2391	2421	2450	2496	2524	2534	2550	2573
	Level Off(ft)	11251	11257	11264	11270	11276	11281	11285	11289	11292	11294
ISA	Time(min)	56.8	58.0	59.3	60.6	62.4	63.7	64.6	66.0	67.0	67.7
	Dist(nam)	345	354	363	372	384	394	401	410	417	422
	Fuel(lb)	2328	2366	2401	2435	2484	2514	2525	2555	2573	2580
	Level Off(ft)	11112	11118	11124	11130	11136	11141	11145	11149	11152	11154
ISA +10°C	Time(min)	55.8	57.1	58.4	59.7	61.0	62.4	63.7	64.7	65.7	66.4
	Dist(nam)	345	354	363	373	383	392	402	409	416	421
	Fuel(lb)	2342	2383	2420	2456	2489	2520	2553	2566	2585	2593
	Level Off(ft)	10980	10985	10992	10998	11003	11008	11012	11016	11019	11021
50 000 LB		230	250	270	290	310	330	350	370	390	410
ISA -10°C	Time(min)	59.5	60.7	62.0	63.3	64.6	66.0	67.3	68.7	69.3	70.0
	Dist(nam)	353	362	371	380	390	399	408	417	422	426
	Fuel(lb)	2392	2428	2460	2491	2521	2549	2579	2610	2612	2622
	Level Off(ft)	10916	10922	10930	10936	10942	10948	10952	10955	10959	10961
ISA	Time(min)	58.5	59.8	61.0	62.4	63.7	65.0	66.0	67.4	68.0	68.7
	Dist(nam)	354	363	372	382	391	400	407	417	421	426
	Fuel(lb)	2416	2454	2489	2523	2554	2585	2597	2632	2633	2645
	Level Off(ft)	10776	10782	10789	10795	10801	10806	10811	10815	10818	10820
ISA +10°C	Time(min)	57.5	58.4	59.7	61.0	62.3	63.7	65.1	66.0	66.7	67.4
	Dist(nam)	354	360	370	380	389	399	409	416	420	425
	Fuel(lb)	2433	2453	2490	2526	2559	2593	2627	2643	2646	2659
	Level Off(ft)	10642	10648	10655	10662	10668	10673	10677	10681	10684	10686

CL604_CL605_QRH_drift_300k_wgt6_imp_May09.ps

QR1_DXSE_019

BOMBARDIER CHALLENGER 605	<i>PERF-08-20</i>
	<i>REV 11A, May 25/09</i>

THIS PAGE INTENTIONALLY LEFT BLANK

TRAINING PURPOSES ONLY

<i>QUICK REFERENCE HANDBOOK</i> <i>PSP 605-15</i>	<i>SINGLE ENGINE DATA</i>
--	----------------------------------

CONTENTS**PAGE****Cold Wx Ops**

Preparation for Deicing/Anti-Icing	SUPP-01-1
Deicing/Anti-Icing	SUPP-01-2
Deicing Fluid Holdover Time	SUPP-01-4
Ice Pellet Allowance Time	SUPP-01-15

Steep Approach

Steep Approach	SUPP-02-1
----------------------	-----------

Steep Approach from 4.5° to 5.5° – Landing Speeds and Distances

Altitude – Sea Level	SUPP-02-2
Altitude – Sea Level – Wet-Grooved Runway	SUPP-02-3
Altitude – 500 Feet	SUPP-02-4
Altitude – 500 Feet – Wet-Grooved Runway	SUPP-02-5
Altitude – 1,000 Feet	SUPP-02-6
Altitude – 1,000 Feet – Wet-Grooved Runway	SUPP-02-7
Altitude – 2,000 Feet	SUPP-02-8
Altitude – 2,000 Feet – Wet-Grooved Runway	SUPP-02-9
Altitude – 4,000 Feet	SUPP-02-10
Altitude – 4,000 Feet – Wet-Grooved Runway	SUPP-02-11
Altitude – 5,000 Feet	SUPP-02-12
Altitude – 5,000 Feet – Wet-Grooved Runway	SUPP-02-13

**FAA Steep Approach into London City Airport –
Landing Speeds and Distances**

Altitude – Sea Level	SUPP-02-14
Altitude – Sea Level – Wet-Grooved Runway	SUPP-02-15
Altitude – 500 Feet	SUPP-02-16
Altitude – 500 Feet – Wet-Grooved Runway	SUPP-02-17
Altitude – 1,000 Feet	SUPP-02-18
Altitude – 1,000 Feet – Wet-Grooved Runway	SUPP-02-19
Altitude – 2,000 Feet	SUPP-02-20
Altitude – 2,000 Feet – Wet-Grooved Runway	SUPP-02-21

CONTENTS**PAGE****Contaminated Runway**

Contaminated Runway Corrections	SUPP-03-1
Take-Off Corrections – Wet Runway	SUPP-03-1
Take-Off Corrections – 0.125 In. Water or Equivalent	SUPP-03-1
Take-Off Corrections – 0.25 In. Water or Equivalent	SUPP-03-1
Take-Off Corrections – Runway Covered with Ice	SUPP-03-1
Take-Off Corrections – Runway Covered by Compacted Snow	SUPP-03-1
Landing Corrections	SUPP-03-2

Volcanic Ash

Operation in Volcanic Ash	SUPP-04-1
---------------------------------	-----------

Extended MTOW

Maximum Allowable Take-Off Weight	SUPP-05-1
Maximum Take-Off Weight Limited by Brake Energy	SUPP-05-2
Maximum Take-Off Weight Limited by Tire Speed	SUPP-05-3

ACN Data

Aircraft Classification Number (ACN)	SUPP-06-1
Rigid Pavement	SUPP-06-1
Flexible Pavement	SUPP-06-1

Wet-Grooved Runway

Wet-Grooved Runway	SUPP-07-1
--------------------------	-----------

Landing Speeds and Distances

Altitude – Sea Level	SUPP-07-2
Altitude – 500 Feet	SUPP-07-4
Altitude – 1,000 Feet	SUPP-07-6
Altitude – 2,000 Feet	SUPP-07-8
Altitude – 4,000 Feet	SUPP-07-10
Altitude – 6,000 Feet	SUPP-07-12
Altitude – 8,000 Feet	SUPP-07-14
Altitude – 10,000 Feet	SUPP-07-16
Altitude – 12,000 Feet	SUPP-07-18
Altitude – 14,000 Feet	SUPP-07-20

PREPARATION FOR DEICING/ANTI-ICING

Before fluid is applied:

If engines/APU are off:

(1) Proceed to step (7).

If engines/APU are operating:

- (2) Thrust levers.....IDLE
- (3) PACKs..... OFF
- (4) 10TH STAGE bleeds.....CLOSED
- (5) WING and COWL ANTI-ICE OFF
- (6) 14TH STAGE bleeds.....CLOSED
- (7) Stabilizer trim.....AS REQUIRED
- (8) Flaps.....AS REQUIRED
- (9) Airplane HEAD INTO WIND
if possible.
- (10) Deicing operator ADVISE

to avoid direct spraying on:

- Windshields, side windows and cabin windows;
- Pitot/static and TAT probes;
- AOA vanes;
- Static pressure ports;
- Engine air intake and exhaust;
- APU inlet and exhaust;
- Antennas;
- Vents and drains;
- Winglets;
- Wheels and brakes.



Application of deicing/anti-icing fluid on wheel brake assemblies will seriously degrade braking performance.

DEICING/ANTI-ICING

1. Under no circumstances can an airplane that has been anti-iced receive another coat of Type II or Type IV fluid on top of the existing film. If the holdover time is exceeded, surfaces must first be deiced with a mixture of hot water and deicing fluid, before another application of Type II or Type IV fluid is made.
2. Type II, III and IV fluid must never be applied to the windshields and side windows.
3. Application of deicing/anti-icing fluid on wheel brake assemblies will seriously degrade braking performance.
4. With the APU operating, ingestion of deicing fluid will contaminate the air-conditioning system, and cause objectionable fumes (causing throat irritation) and odours to enter the airplane. This may also cause erratic operation and possible damage to the APU.
5. Under no circumstances should spray be directed at the trailing edges of control surfaces. Such spray may force partially melted contamination into hinge mechanisms, and under control shrouds, with risk of later re-freezing.

(1) Fluid APPLY
in the following sequence:

- Horizontal stabilizer
- Vertical stabilizer
- Top of fuselage
- Sides of fuselage
- Wings.

After Deicing/Anti-icing Spraying:

(2) Deicing INSPECT
areas listed below, to confirm complete deicing:

- Wings – leading edges, upper and lower surfaces;
- Upper fuselage;
- Vertical and horizontal stabilizers – leading edges, upper/lower surfaces and side panels;
- Flaps, flap tracks and flap drives;
- Ailerons, elevators, rudder and spoilers;
- Air data probes/sensors, AOA vanes;
- Antennas;
- Fuel drains and NACA vent scoops;
- Engine and APU intakes; APU exhaust;
- Landing gear and landing gear bays;
- Windshield, windows; door sills and surrounds.

DEICING/ANTI-ICING

If engines/APU are operating:

- (3) Thrust 60% N₁
for 20 seconds.
- (4) 14TH STAGE bleeds AS REQUIRED
- (5) WING and COWL ANTI-ICE AS REQUIRED
- (6) 10TH STAGE bleeds OPEN
- (7) PACKs ON
- (8) Take-off configuration RECHECK

TRAINING PURPOSES ONLY

DEICING FLUID HOLDOVER TIME**NOTE**

1. Use Snowfall Intensity as a Function of Visibility table to determine snowfall intensity (including for snow grains and snow pellets).
2. When using SAE Type III and IV fluids, use the ice pellet and small hail allowance times for slats/flaps retracted or deployed prior to deicing/anti-icing as applicable.
3. Guidelines for holdover times and deicing fluid application are revised every year according to the Transport Canada TP 14052 and associated holdover time guidelines document. The following tables contain Generic Holdover Time (HOT) and Fluids Application Procedures for the SAE Type I/II/III/IV deicing/anti-icing fluids. For the fluid specific Holdover Time (HOT), use the table that is available at the following Transport Canada and Federal Aviation Administration web sites:

www.tc.gc.ca/eng/civilaviation/standards/commerce-holdovertime-menu-1877.htm

www.faa.gov/other_visit/aviation_industry/airline_operators/airline_safety/deicing/

CAUTION

1. Takeoff after the longest applicable holdover time has been exceeded is not permitted for Type I fluids.
2. The only acceptable decision-making criteria for takeoff without a pre-takeoff contamination inspection, is the shortest time within the applicable holdover timetable cell.
3. For all types of deicing fluid, the time of protection will be shortened in heavy weather conditions, heavy precipitation rates or high moisture content. High wind velocity or jet blast may reduce holdover time below the lowest time stated in the range. Holdover time may also be reduced when airplane skin temperature is lower than OAT.
4. Fluids used during ground deicing/anti-icing do not provide in-flight icing protection.

DEICING FLUID HOLDOVER TIME

SNOWFALL INTENSITY AS A FUNCTION OF VISIBILITY						
Lighting	Temperature Range		Visibility in Snow in Statute Miles (Meters)			
	°C	°F	Heavy	Moderate	Light	Very Light
Darkness	-1 and above	30 and above	≤ 1 (≤ 1600)	> 1 to 2 1/2 (> 1600 to 4000)	> 2 1/2 to 4 (> 4000 to 6400)	> 4 (> 6400)
	below -1	below 30	≤ 3/4 (≤ 1200)	> 3/4 to 1 1/2 (> 1200 to 2400)	> 1 1/2 to 3 (> 2400 to 4800)	> 3 (> 4800)
Daylight	-1 and above	30 and above	≤ 1/2 (≤ 800)	> 1/2 to 1 1/2 (> 800 to 2400)	> 1 1/2 to 3 (> 2400 to 4800)	> 3 (> 4800)
	below -1	below 30	≤ 3/8 (≤ 600)	> 3/8 to 7/8 (> 600 to 1400)	> 7/8 to 2 (> 1400 to 3200)	> 2 (> 3200)

DF01_0612_014D

Snowfall Intensity as a Function of Visibility
Table 1

SAE TYPE I FLUIDS – FLAPS RETRACTED PRIOR TO DEICING/ANTI-ICING APPROXIMATE HOLDOVER TIMES ANTICIPATED UNDER VARIOUS WEATHER CONDITIONS								
OAT [1], [2]		Holdover Times (minutes)						
°C	°F	Freezing Fog, Freezing Mist ^[7] or Ice Crystals	Snow, Snow Grains or Snow Pellets ^[8]			Freezing Drizzle ^[4]	Light Freezing Rain	Rain on Cold Soaked Wing ^[5]
			Very Light ^[3]	Light ^[3]	Moderate			
-3 and above	27 and above	11 – 17	18 – 22	11 – 18	6 – 11	9 – 13	4 – 6	2 – 5
below -3 to -6	below 27 to 21	8 – 13	14 – 17	8 – 14	5 – 8	5 – 9	4 – 6	No holdover time guidelines exist
below -6 to -10	below 21 to 14	6 – 10	11 – 13	6 – 11	4 – 6	4 – 7	2 – 5	
below -10	below 14	5 – 9	7 – 8	4 – 7	2 – 4			

[1] Type I fluid/water mixture must be selected so that the freezing point of the mixture is at least 10°C (18°F) below outside air temperature.

[2] Ensure that the lowest operational use temperature (LOUT) is respected.

[3] Use light freezing rain holdover times in conditions of very light or light snow mixed with light rain or drizzle.

[4] Includes light, moderate and heavy freezing drizzle. Use light freezing rain holdover times if positive identification of freezing drizzle is not possible.

[5] No holdover time guidelines exist for this condition for 0°C (32°F) and below.

[6] Heavy snow, ice pellets, moderate and heavy freezing rain, small hail and hail.

[7] Freezing Mist is best confirmed by observation. It is never reported by METAR however it can occur when mist is present at 0°C (32°F) and below.

[8] To determine snowfall intensity, the Snowfall Intensities as a Function of Visibility table is required.

GF0701_040C

Type I Fluid Holdover Times –
Flaps Retracted Prior to Deicing/Anti-Icing
Table 2

DEICING FLUID HOLDOVER TIME

SAE TYPE I FLUIDS – FLAPS DEPLOYED PRIOR TO DEICING/ANTI-ICING APPROXIMATE HOLDOVER TIMES ANTICIPATED UNDER VARIOUS WEATHER CONDITIONS									
OAT [1], [2]		Holdover Times (minutes)							
°C	°F	Freezing Fog, Freezing Mist ^[7] or Ice Crystals	Snow, Snow Grains or Snow Pellets ^[8]			Freezing Drizzle ^[4]	Light Freezing Rain	Rain on Cold Soaked Wing ^[5]	Other ^[6]
			Very Light ^[3]	Light ^[3]	Moderate				
–3 and above	27 and above	8 – 13	14 – 17	8 – 14	5 – 8	7 – 10	3 – 5	2 – 4	No holdover time guidelines exist
below –3 to –6	below 27 to 21	6 – 10	11 – 13	6 – 11	4 – 6	4 – 7	3 – 5		
below –6 to –10	below 21 to 14	5 – 8	8 – 10	5 – 8	3 – 5	3 – 5	2 – 4		
below –10	below 14	4 – 7	5 – 6	3 – 5	2 – 3				
[1] Type I fluid/water mixture must be selected so that the freezing point of the mixture is at least 10°C (18°F) below outside air temperature. [2] Ensure that the lowest operational use temperature (LOUT) is respected. [3] Use light freezing rain holdover times in conditions of very light or light snow mixed with light rain or drizzle. [4] Includes light, moderate and heavy freezing drizzle. Use light freezing rain holdover times if positive identification of freezing drizzle is not possible. [5] No holdover time guidelines exist for this condition for 0°C (32°F) and below. [6] Heavy snow, ice pellets, moderate and heavy freezing rain, small hail and hail. [7] Freezing Mist is best confirmed by observation. It is never reported by METAR however it can occur when mist is present at 0° C (32° F) and below. [8] To determine snowfall intensity, the Snowfall Intensities as a Function of Visibility table is required.									

GF0701_037D

Type I Fluid Holdover Times –
Flaps Deployed Prior to Deicing/Anti-Icing
Table 3

DEICING FLUID HOLDOVER TIME

SAE TYPE II FLUIDS – FLAPS RETRACTED PRIOR TO DEICING/ANTI-ICING APPROXIMATE HOLDOVER TIMES ANTICIPATED UNDER VARIOUS WEATHER CONDITIONS									
OAT ^[1]		Type II Fluid Concentration	Holdover Times (minutes)						
°C	°F	Fluid/Water (% by Volume)	Freezing Fog, Freezing Mist ^[7] or Ice Crystals	Snow, Snow Grains or Snow Pellets ^{[2][9]}	Freezing Drizzle ^[3]	Light Freezing Rain	Rain on Cold Soaked Wing ^[4]	Other ^[5]	
-3 and above	27 and above	100 / 0	55 – 110	25 – 50	30 – 60	20 – 35	7 – 45	No holdover time guidelines exist	
		75 / 25	25 – 55	15 – 25	15 – 40	10 – 20	4 – 25		
		50 / 50	15 – 25	5 – 10	8 – 15	6 – 9			
below -3 to -8	below 27 to 18	100 / 0	30 – 45	20 – 35	20 – 45	15 – 20			
		75 / 25	25 – 50	10 – 20	15 – 25	8 – 15			
below -8 to -14	below 18 to 7	100 / 0	30 – 45	15 – 30	20 – 45 ^[8]	15 – 20 ^[8]			
		75 / 25	25 – 50	8 – 20	15 – 25 ^[8]	8 – 15 ^[8]			
below -14 to -18	below 7 to 0	100 / 0	15 – 20	2 – 7	No holdover time guidelines exist				
below -18 to -25	below 0 to -13	100 / 0	15 – 20 ^[6]	1 – 3 ^[6]					
below -25 to LOUT	below -13 to LOUT	100 / 0	15 – 20 ^[6]	0 – 1 ^[6]					
[1] Ensure that the lowest operational use temperature (LOUT) is respected. Consider use of Type I when Type II fluid cannot be used. [2] Use light freezing rain holdover times in conditions of very light or light snow mixed with light rain or drizzle. [3] Includes light, moderate and heavy freezing drizzle. Use light freezing rain holdover times if positive identification of freezing drizzle is not possible. [4] No holdover time guidelines exist for this condition for 0°C (32°F) and below. [5] Heavy snow, ice pellets, moderate and heavy freezing rain, small hail and hail. [6] If the LOUT is unknown, no holdover time guidelines exist below -25°C (-13°F). [7] Freezing Mist is best confirmed by observation. It is never reported by METAR however it can occur when mist is present at 0°C (32°F) and below. [8] No holdover time guidelines exist for this condition below -10°C (14°F). [9] To determine snowfall intensity, the Snowfall Intensities as a Function of Visibility table is required.									

GF0701_02/E

Type II Fluid Holdover Times –
Flaps Retracted Prior to Deicing/Anti-Icing
Table 4

DEICING FLUID HOLDOVER TIME

SAE TYPE II FLUIDS – FLAPS DEPLOYED PRIOR TO DEICING/ANTI-ICING APPROXIMATE HOLDOVER TIMES ANTICIPATED UNDER VARIOUS WEATHER CONDITIONS									
OAT ^[1]		Type II Fluid Concentration	Holdover Times (minutes)						
°C	°F	Fluid/Water (% by Volume)	Freezing Fog, Freezing Mist ^[7] or Ice Crystals	Snow, Snow Grains or Snow Pellets ^{[2][9]}	Freezing Drizzle ^[3]	Light Freezing Rain	Rain on Cold Soaked Wing ^[4]	Other ^[5]	
-3 and above	27 and above	100 / 0	42 – 84	19 – 38	23 – 46	15 – 27	5 – 34	No holdover time guidelines exist	
		75 / 25	19 – 42	11 – 19	11 – 30	8 – 15	3 – 19		
		50 / 50	11 – 19	4 – 8	6 – 11	5 – 7			
below -3 to -8	below 27 to 18	100 / 0	23 – 34	15 – 27	15 – 34	11 – 15			
		75 / 25	19 – 38	8 – 15	11 – 19	6 – 11			
below -8 to -14	below 18 to 7	100 / 0	23 – 34	11 – 23	15 – 34 ^[8]	11 – 15 ^[8]			
		75 / 25	19 – 38	6 – 15	11 – 19 ^[8]	6 – 11 ^[8]			
below -14 to -18	below 7 to 0	100 / 0	11 – 15	2 – 5	No holdover time guidelines exist				
below -18 to -25	below 0 to -13	100 / 0	11 – 15 ^[6]	1 – 2 ^[6]					
below -25 to LOUT	below -13 to LOUT	100 / 0	11 – 15 ^[6]	0 – 1 ^[6]					
[1] Ensure that the lowest operational use temperature (LOUT) is respected. Consider use of Type I when Type II fluid cannot be used. [2] Use light freezing rain holdover times in conditions of very light or light snow mixed with light rain or drizzle. [3] Includes light, moderate and heavy freezing drizzle. Use light freezing rain holdover times if positive identification of freezing drizzle is not possible. [4] No holdover time guidelines exist for this condition for 0° C (32° F) and below. [5] Heavy snow, ice pellets, moderate and heavy freezing rain, small hail and hail. [6] If the LOUT is unknown, no holdover time guidelines exist below -25° C (-13° F). [7] Freezing Mist is best confirmed by observation. It is never reported by METAR however it can occur when mist is present at 0° C (32° F) and below. [8] No holdover time guidelines exist for this condition below -10° C (14° F). [9] To determine snowfall intensity, the Snowfall Intensities as a Function of Visibility table is required.									

GF0701_028E

Type II Fluid Holdover Times –
Flaps Deployed Prior to Deicing/Anti-Icing
Table 5

DEICING FLUID HOLDOVER TIME

ALLCLEAR AEROCLEAR MAX HIGH SPEED TYPE III FLUID – APPLIED UNHEATED
FLAPS RETRACTED PRIOR TO DEICING/ANTI-ICING
APPROXIMATE HOLDOVER TIMES ANTICIPATED UNDER VARIOUS WEATHER CONDITIONS

OAT [2]		Type III Fluid Concentration	Holdover Times (minutes) [1]							
°C	°F	Fluid/Water (% by Volume)	Freezing Fog, Freezing Mist ^[7] or Ice Crystals	Snow, Snow Grains or Snow Pellets ^[8]			Freezing Drizzle ^[4]	Light Freezing Rain	Rain on Cold Soaked Wing ^[5]	Other ^[6]
				Very Light ^[3]	Light ^[3]	Moderate				
−3 and above	27 and above	100 / 0	45 – 115	80 – 105	40 – 80	18 – 40	25 – 50	14 – 25	5 – 40	No holdover time guidelines exist
below −3 to −10	below 27 to 14	100 / 0	50 – 100	80 – 105	40 – 80	18 – 40	25 – 45	15 – 25		
below −10 to −25	below 14 to −13	100 / 0	40 – 105	80 – 105	40 – 80	18 – 40				
below −25 to −35	below −13 to −31	100 / 0	25 – 60	45 – 60	20 – 45	10 – 20				

[1] Fluid must be applied unheated. No holdover time guidelines exist for this fluid applied heated.

[2] Ensure that the lowest operational use temperature (LOUT) is respected.
Consider use of Type I when Type III fluid cannot be used.

[3] Use light freezing rain holdover times in conditions of very light or light snow mixed with light rain or drizzle.

[4] Includes light, moderate and heavy freezing drizzle. Use light freezing rain holdover times if positive identification of freezing drizzle is not possible.

[5] No holdover time guidelines exist for this condition for 0° C (32° F) and below.

[6] Heavy snow, ice pellets, moderate and heavy freezing rain, small hail and hail.

[7] Freezing Mist is best confirmed by observation. It is never reported by METAR however it can occur when mist is present at 0° C (32° F) and below.

[8] To determine snowfall intensity, the Snowfall Intensities as a Function of Visibility table is required.

GF0701_031D

AllClear Unheated Type III Fluid Holdover Times –
Flaps Retracted Prior to Deicing/Anti-Icing
Table 6

DEICING FLUID HOLDOVER TIME

ALLCLEAR AEROCLEAR MAX HIGH SPEED TYPE III FLUID – APPLIED UNHEATED FLAPS DEPLOYED PRIOR TO DEICING/ANTI-ICING APPROXIMATE HOLDOVER TIMES ANTICIPATED UNDER VARIOUS WEATHER CONDITIONS										
OAT ^[2]		Type III Fluid Concentration	Holdover Times (minutes) ^[1]							
°C	°F	Fluid/Water (% by Volume)	Freezing Fog, Freezing Mist ^[7] or Ice Crystals	Snow, Snow Grains or Snow Pellets ^[8]			Freezing Drizzle ^[4]	Light Freezing Rain	Rain on Cold Soaked Wing ^[5]	Other ^[6]
				Very Light ^[3]	Light ^[3]	Moderate				
–3 and above	27 and above	100 / 0	34 – 87	61 – 80	30 – 61	14 – 30	19 – 38	11 – 19	4 – 30	No holdover time guidelines exist
below –3 to –10	below 27 to 14	100 / 0	38 – 76	61 – 80	30 – 61	14 – 30	19 – 34	11 – 19		
below –10 to –25	below 14 to –13	100 / 0	30 – 80	61 – 80	30 – 61	14 – 30				
below –25 to –35	below –13 to –31	100 / 0	19 – 46	34 – 46	15 – 34	8 – 15				
[1] Fluid must be applied unheated. No holdover time guidelines exist for this fluid applied heated.										
[2] Ensure that the lowest operational use temperature (LOUT) is respected. Consider use of Type I when Type III fluid cannot be used.										
[3] Use light freezing rain holdover times in conditions of very light or light snow mixed with light rain or drizzle.										
[4] Includes light, moderate and heavy freezing drizzle. Use light freezing rain holdover times if positive identification of freezing drizzle is not possible.										
[5] No holdover time guidelines exist for this condition for 0°C (32°F) and below.										
[6] Heavy snow, ice pellets, moderate and heavy freezing rain, small hail and hail.										
[7] Freezing Mist is best confirmed by observation. It is never reported by METAR however it can occur when mist is present at 0°C (32°F) and below.										
[8] To determine snowfall intensity, the Snowfall Intensities as a Function of Visibility table is required.										

GF0701_032D

AllClear Unheated Type III Fluid Holdover Times –
Flaps Deployed Prior to Deicing/Anti-Icing
Table 7

DEICING FLUID HOLDOVER TIME

SAE TYPE IV FLUIDS – FLAPS RETRACTED PRIOR TO DEICING/ANTI-ICING APPROXIMATE HOLDOVER TIMES ANTICIPATED UNDER VARIOUS WEATHER CONDITIONS											
OAT [1]		Type IV Fluid Concentration	Holdover Times (minutes)								
°C	°F	Fluid/Water (% by Volume)	Freezing Fog, Freezing Mist ^[7] or Ice Crystals	Snow, Snow Grains or Snow Pellets ^[9]			Freezing Drizzle ^[3]	Light Freezing Rain	Rain on Cold Soaked Wing ^[4]	Other ^[5]	
				Very Light ^[2]	Light ^[2]	Moderate					
-3 and above	27 and above	100 / 0	75 – 160	115 – 120	60 – 115	30 – 60	40 – 70	20 – 35	8 – 65	No holdover time guidelines exist	
		75 / 25	85 – 160	120	75 – 120	40 – 75	50 – 80	30 – 45	9 – 75		
		50 / 50	30 – 55	60 – 70	25 – 60	10 – 25	15 – 40	9 – 20			
below -3 to -8	below 27 to 18	100 / 0	20 – 95	105 – 120	55 – 105	25 – 55	25 – 70	20 – 25			
		75 / 25	30 – 80	110 – 120	60 – 110	30 – 60	20 – 65	15 – 25			
below -8 to -14	below 18 to 7	100 / 0	20 – 95	80 – 100	45 – 80	25 – 45	25 – 70 ^[8]	20 – 25 ^[8]			
		75 / 25	30 – 80	100 – 120	45 – 100	20 – 45	20 – 65 ^[8]	15 – 25 ^[8]			
below -14 to -18	below 7 to 0	100 / 0	20 – 35	30 – 45	9 – 30	2 – 9	No holdover time guidelines exist				
below -18 to -25	below 0 to -13	100 / 0	20 – 35 ^[6]	10 – 20 ^[6]	3 – 10 ^[6]	1 – 3 ^[6]					
below -25 to LOUT	below -13 to LOUT	100 / 0	20 – 35 ^[6]	7 – 10 ^[6]	2 – 7 ^[6]	0 – 2 ^[6]					
[1] Ensure that the lowest operational use temperature (LOUT) is respected. Consider use of Type I when Type IV fluid cannot be used. [2] Use light freezing rain holdover times in conditions of very light or light snow mixed with light rain or drizzle. [3] Includes light, moderate and heavy freezing drizzle. Use light freezing rain holdover times if positive identification of freezing drizzle is not possible. [4] No holdover time guidelines exist for this condition for 0°C (32°F) and below. [5] Heavy snow, ice pellets, moderate and heavy freezing rain, small hail and hail. [6] If the LOUT is unknown, no holdover time guidelines exist below -23.5°C (-10°F) [7] Freezing Mist is best confirmed by observation. It is never reported by METAR however it can occur when mist is present at 0°C (32°F) and below. [8] No holdover time guidelines exist for this condition below -10°C (14°F). [9] To determine snowfall intensity, the Snowfall Intensities as a Function of Visibility table is required.											

GF0701_041D

Type IV Fluid Holdover Times –
Flaps Retracted Prior to Deicing/Anti-Icing
Table 8

DEICING FLUID HOLDOVER TIME

SAE TYPE IV FLUIDS – FLAPS DEPLOYED PRIOR TO DEICING/ANTI-ICING APPROXIMATE HOLDOVER TIMES ANTICIPATED UNDER VARIOUS WEATHER CONDITIONS											
OAT [1]		Type IV Fluid Concentration	Holdover Times (minutes)								
°C	°F	Fluid/Water (% by Volume)	Freezing Fog, Freezing Mist ^[7] or Ice Crystals	Snow, Snow Grains or Snow Pellets ^[9]			Freezing Drizzle ^[3]	Light Freezing Rain	Rain on Cold Soaked Wing ^[4]	Other ^[5]	
				Very Light ^[2]	Light ^[2]	Moderate					
-3 and above	27 and above	100 / 0	57 – 122	87 – 106	46 – 87	23 – 46	30 – 53	15 – 27	6 – 49	No holdover time guidelines exist	
		75 / 25	65 – 122	95 – 110	57 – 95	30 – 57	38 – 61	23 – 34	7 – 57		
		50 / 50	23 – 42	46 – 53	19 – 46	8 – 19	11 – 30	7 – 15			
below -3 to -8	below 27 to 18	100 / 0	15 – 72	80 – 95	42 – 80	19 – 42	19 – 53	15 – 19			
		75 / 25	23 – 61	84 – 99	46 – 84	23 – 46	15 – 49	11 – 19			
below -8 to -14	below 18 to 7	100 / 0	15 – 72	61 – 76	34 – 61	19 – 34	19 – 53 ^[8]	15 – 19 ^[8]			
		75 / 25	23 – 61	76 – 91	34 – 76	15 – 34	15 – 49 ^[8]	11 – 19 ^[8]			
below -14 to -18	below 7 to 0	100 / 0	15 – 27	23 – 34	7 – 23	2 – 7	No holdover time guidelines exist				
below -18 to -25	below 0 to -13	100 / 0	15 – 27 ^[6]	8 – 15 ^[6]	2 – 8 ^[6]	1 – 2 ^[6]					
below -25 to LOUT	below -13 to LOUT	100 / 0	15 – 27 ^[6]	5 – 8 ^[6]	2 – 5 ^[6]	0 – 2 ^[6]					

[1] Ensure that the lowest operational use temperature (LOUT) is respected. Consider use of Type I when Type IV fluid cannot be used.

[2] Use light freezing rain holdover times in conditions of very light or light snow mixed with light rain or drizzle.

[3] Includes light, moderate and heavy freezing drizzle. Use light freezing rain holdover times if positive identification of freezing drizzle is not possible.

[4] No holdover time guidelines exist for this condition for 0°C (32°F) and below.

[5] Heavy snow, ice pellets, moderate and heavy freezing rain, small hail and hail.

[6] If the LOUT is unknown, no holdover time guidelines exist below -23.5°C (-10°F)

[7] Freezing Mist is best confirmed by observation. It is never reported by METAR however it can occur when mist is present at 0°C (32°F) and below.

[8] No holdover time guidelines exist for this condition below -10°C (14°F).

[9] To determine snowfall intensity, the Snowfall Intensities as a Function of Visibility table is required.

GF0701_033E

Type IV Fluid Holdover Times –
Flaps Deployed Prior to Deicing/Anti-Icing
Table 9

DEICING FLUID HOLDOVER TIME

ACTIVE FROST – TYPE I FLUID FLAPS RETRACTED			ACTIVE FROST – TYPE II, III AND IV FLUIDS FLAPS RETRACTED						
OAT [1], [2], [3]		Approximate Holdover Times (hours:minutes) Type I	OAT [2], [3]		Fluid Concentration Fluid/Water (% by Volume)	Approximate Holdover Times (hours:minutes)			
°C	°F		°C	°F		Type II	Type III [4]	Type IV	
–1 and above	30 and above	0:45	–1 and above	30 and above	100 / 0	8:00	2:00	12:00	
					75 / 25	5:00	1:00	5:00	
					50 / 50	2:00	0:30	3:00	
below –1 to –3	below 30 to 27		below –1 to –3	below 30 to 27	100 / 0	8:00	2:00	12:00	
					75 / 25	5:00	1:00	5:00	
					50 / 50	1:30	0:30	3:00	
below –3 to –10	below 27 to 14		below –3 to –10	below 27 to 14	100 / 0	8:00	2:00	10:00	
					75 / 25	4:00	1:00	5:00	
below –10 to –14	below 14 to 7		below –10 to –14	below 14 to 7	100 / 0	6:00	2:00	6:00	
					75 / 25	1:00	1:00	1:00	
below –14 to –21	below 7 to –6		below –14 to –21	below 7 to –6	100 / 0	3:00	2:00	6:00	
below –21 to –25	below –6 to –13		below –21 to –25	below –6 to –13	100 / 0	2:00	2:00	4:00	
below –25 to LOU	below –13 to LOU		below –25	below –13	100 / 0	No holdover time guidelines exist			
[1] Type I fluid/water mixture must be selected so that the freezing point of the mixture is at least 10°C (18°F) below outside air temperature.									
[2] Ensure that the lowest operational use temperature (LOU) is respected.									
[3] Changes in outside air temperature (OAT) over the course of longer frost events can be significant; the appropriate holdover time to use is the one provided for the coldest OAT that has occurred in the time between the deicing/anti-icing fluid application and takeoff.									
[4] To use Type III fluid frost holdover times, the fluid brand being used must be known. AllClear AeroClear MAX must be applied unheated.									

GF0701_038A

Active Frost Holdover Times –
Flaps Retracted Prior to Deicing/Anti-Icing
Table 10

DEICING FLUID HOLDOVER TIME

ACTIVE FROST – TYPE I FLUID FLAPS DEPLOYED			ACTIVE FROST – TYPE II, III AND IV FLUIDS FLAPS DEPLOYED						
OAT [1], [2], [3]		Approximate Holdover Times (hours:minutes)	OAT [2], [3]		Fluid Concentration	Approximate Holdover Times (hours:minutes)			
°C	°F	Type I	°C	°F	Fluid/Water (% by Volume)	Type II	Type III [4]	Type IV	
–1 and above	30 and above	0:34	–1 and above	30 and above	100 / 0	6:05	1:31	9:07	
					75 / 25	3:48	0:46	3:48	
					50 / 50	1:31	0:23	2:17	
below –1 to –3	below 30 to 27		below –1 to –3	below 30 to 27	100 / 0	6:05	1:31	9:07	
					75 / 25	3:48	0:46	3:48	
					50 / 50	1:08	0:23	2:17	
below –3 to –10	below 27 to 14		below –3 to –10	below 27 to 14	100 / 0	6:05	1:31	7:36	
					75 / 25	3:02	0:46	3:48	
below –10 to –14	below 14 to 7		below –10 to –14	below 14 to 7	100 / 0	4:34	1:31	4:34	
					75 / 25	0:46	0:46	0:46	
below –14 to –21	below 7 to –6		below –14 to –21	below 7 to –6	100 / 0	2:17	1:31	4:34	
below –21 to –25	below –6 to –13		below –21 to –25	below –6 to –13	100 / 0	1:31	1:31	3:02	
below –25 to LOUT	below –13 to LOUT		below –25	below –13	100 / 0	No holdover time guidelines exist			
[1] Type I fluid/water mixture must be selected so that the freezing point of the mixture is at least 10°C (18°F) below outside air temperature.									
[2] Ensure that the lowest operational use temperature (LOUT) is respected.									
[3] Changes in outside air temperature (OAT) over the course of longer frost events can be significant; the appropriate holdover time to use is the one provided for the coldest OAT that has occurred in the time between the deicing/anti-icing fluid application and takeoff.									
[4] To use Type III fluid frost holdover times, the fluid brand being used must be known. AllClear AeroClear MAX must be applied unheated.									

GF0701_039B

Active Frost Holdover Times –
Flaps Deployed Prior to Deicing/Anti-Icing
Table 11

ICE PELLET ALLOWANCE TIME



1. Allowance time can not be extended by an inspection of the aircraft critical surfaces.
2. Take off is allowed up to 90 minutes after start of the fluid application if the precipitation stops at or before the allowance time expires and does not restart. The OAT must not decrease during the 90 minutes to use this guidance in conditions of light ice pellets mixed with either freezing drizzle, freezing rain or rain.

Precipitation Types or Combinations	Applicable METAR Codes	Outside Air Temperature		
		-5 °C and above (23 °F and above)	Below -5 to -10 °C (Below 23 to 14 °F)	Below -10 °C ^[1] (Below 14 °F) ^[1]
Light Ice Pellets	-PL	10 minutes	10 minutes	Caution: No allowance times currently exist
Light Ice Pellets Mixed with Light Snow	-PLSN, -SNPL	10 minutes	10 minutes	
Light Ice Pellets Mixed with Light Freezing Drizzle or Moderate Freezing Drizzle	-PLFZDZ, -FZDZPL, FZDZPL	7 minutes	5 minutes	
Light Ice Pellets Mixed with Light Freezing Rain	-PLFZRA, -FZRAPL	7 minutes	5 minutes	
Light Ice Pellets Mixed with Light Rain	-PLRA, -RAPL	7 minutes ^[2]		
Moderate Ice Pellets (or Small Hail ^[3])	PL, GS	5 minutes	5 minutes	

[1] Ensure that the lowest operational use temperature (LOUT) is respected.

[2] No allowance times exist in this condition for temperatures of 0 °C (32 °F) and below; consider use of light ice pellets mixed with light freezing rain.

[3] In Canada (and outside the US) the code GS is used when hail is less than 5 mm and GR when it is 5mm or greater. In the US, small hail is included with regular hail and the remarks section is used saying "GR LESS THAN ¼". If no intensity is reported with small hail, use the "moderate ice pellets or small hail" allowance times. If an intensity is reported with small hail, the ice pellet condition with the equivalent intensity can be used, e.g. if light small hail is reported, the "light ice pellets" allowance times can be used. This also applies in mixed conditions, e.g. if light small hail mixed with light snow is reported, use the "light ice pellets mixed with light snow" allowance times.

Type III Ice Pellet and Small Hail Allowance Times –
Flaps Retracted Prior to Deicing/Anti-Icing
Table 12

ICE PELLET ALLOWANCE TIME

Precipitation Types or Combinations	Applicable METAR Codes	Outside Air Temperature		
		-5 °C and above (23 °F and above)	Below -5 to -10 °C (Below 23 to 14 °F)	Below -10 °C ^[1] (Below 14 °F) ^[1]
Light Ice Pellets	-PL	8 minutes	8 minutes	Caution: No allowance times currently exist
Light Ice Pellets Mixed with Light Snow	-PLSN, -SNPL	8 minutes	8 minutes	
Light Ice Pellets Mixed with Light Freezing Drizzle or Moderate Freezing Drizzle	-PLFZDZ, -FZDZPL, FZDZPL	5 minutes	4 minutes	
Light Ice Pellets Mixed with Light Freezing Rain	-PLFZRA, -FZRAPL	5 minutes	4 minutes	
Light Ice Pellets Mixed with Light Rain	-PLRA, -RAPL	5 minutes ^[2]		
Moderate Ice Pellets (or Small Hail ^[3])	PL, GS	4 minutes	4 minutes	

[1] Ensure that the lowest operational use temperature (LOUT) is respected.

[2] No allowance times exist in this condition for temperatures of 0 °C (32 °F) and below; consider use of light ice pellets mixed with light freezing rain.

[3] In Canada (and outside the US) the code GS is used when hail is less than 5 mm and GR when it is 5mm or greater. In the US, small hail is included with regular hail and the remarks section is used saying "GR LESS THAN ¼". If no intensity is reported with small hail, use the "moderate ice pellets or small hail" allowance times. If an intensity is reported with small hail, the ice pellet condition with the equivalent intensity can be used, e.g. if light small hail is reported, the "light ice pellets" allowance times can be used. This also applies in mixed conditions, e.g. if light small hail mixed with light snow is reported, use the "light ice pellets mixed with light snow" allowance times.

Type III Ice Pellet and Small Hail Allowance Times –
Flaps Deployed Prior to Deicing/Anti-Icing
Table 13

ICE PELLET ALLOWANCE TIME

Precipitation Types or Combinations	Applicable METAR Codes	Outside Air Temperature			
		-5 °C and above (23 °F and above)	Below -5 to -10 °C (Below 23 to 14 °F)	Below -10 to -16 °C (Below 14 to 3.2 °F)	Below -16 to -22 °C ^[1] (Below 3 to -7.6 °F) ^[1]
Light Ice Pellets	-PL	70 minutes	50 minutes	30 minutes	30 minutes
Light Ice Pellets Mixed with Light Snow	-PLSN, -SNPL	50 minutes	30 minutes	15 minutes	Caution: No allowance times currently exist
Light Ice Pellets Mixed with Light Freezing Drizzle or Moderate Freezing Drizzle	-PLFZDZ, -FZDZPL, FZDZPL	40 minutes	30 minutes		
Light Ice Pellets Mixed with Light Freezing Rain	-PLFZRA, -FZRAPL	40 minutes	30 minutes		
Light Ice Pellets Mixed with Light Rain	-PLRA, -RAPL	40 minutes ^[2]			
Moderate Ice Pellets (or Small Hail) ^[3]	PL, GS	35 minutes	25 minutes	10 minutes	10 minutes
Moderate Ice Pellets (or Small Hail) ^[3] Mixed with Moderate Freezing Drizzle	PLFZDZ, GSFZDZ,	20 minutes	10 minutes		Caution: No allowance times currently exist
Moderate Ice Pellets (or Small Hail) ^[3] Mixed with Moderate Rain	PLRA, GSRA, RAPL, RAGS	15 minutes ^[4]			

[1] Ensure that the lowest operational use temperature (LOUT) is respected.

[2] No allowance times exist in this condition for temperatures of 0 °C (32 °F) and below; consider use of light ice pellets mixed with light freezing rain.

[3] In Canada (and outside the US) the code GS is used when hail is less than 5 mm and GR when it is 5mm or greater. In the US, small hail is included with regular hail and the remarks section is used saying "GR LESS THAN ¼". If no intensity is reported with small hail, use the "moderate ice pellets or small hail" allowance times. If an intensity is reported with small hail, the ice pellet condition with the equivalent intensity can be used, e.g. if light small hail is reported, the "light ice pellets" allowance times can be used. This also applies in mixed conditions, e.g. if light small hail mixed with light snow is reported, use the "light ice pellets mixed with light snow" allowance times.

[4] No allowance times exist in this condition for temperatures of 0 °C (32 °F) and below.

[5] If the glycol type is unknown, the allowance times for SAE Type IV Propylene Glycol (PG) fluids should be used.

GF0701_049

Type IV Fluids Ethylene Glycol (EG) Fluids Ice Pellet and Small Hail Allowance Times Slats/Flaps Retracted Prior to Deicing/Anti-Icing Table 14

ICE PELLET ALLOWANCE TIME

Precipitation Types or Combinations	Applicable METAR Codes	Outside Air Temperature			
		-5 °C and above (23 °F and above)	Below -5 to -10 °C (Below 23 to 14 °F)	Below -10 to -16 °C (Below 14 to 3.2 °F)	Below -16 to -22 °C ^[1] (Below 3 to -7.6 °F) ^[1]
Light Ice Pellets	-PL	53 minutes	38 minutes	23 minutes	23 minutes
Light Ice Pellets Mixed with Light Snow	-PLSN, -SNPL	38 minutes	23 minutes	11 minutes	Caution: No allowance times currently exist
Light Ice Pellets Mixed with Light Freezing Drizzle or Moderate Freezing Drizzle	-PLFZDZ, -FZDZPL, FZDZPL	30 minutes	23 minutes		
Light Ice Pellets Mixed with Light Freezing Rain	-PLFZRA, -FZRAPL	30 minutes	23 minutes		
Light Ice Pellets Mixed with Light Rain	-PLRA, -RAPL	30 minutes ^[2]			
Moderate Ice Pellets (or Small Hail ^[3])	PL, GS	27 minutes	19 minutes	8 minutes	8 minutes
Moderate Ice Pellets (or Small Hail ^[3]) Mixed with Moderate Freezing Drizzle	PLFZDZ, GSFZDZ,	15 minutes	8 minutes	Caution: No allowance times currently exist	
Moderate Ice Pellets (or Small Hail ^[3]) Mixed with Moderate Rain	PLRA, GSRA, RAPL, RAGS	11 minutes ^[4]			

[1] Ensure that the lowest operational use temperature (LOUT) is respected.

[2] No allowance times exist in this condition for temperatures of 0 °C (32 °F) and below; consider use of light ice pellets mixed with light freezing rain.

[3] In Canada (and outside the US) the code GS is used when hail is less than 5 mm and GR when it is 5mm or greater. In the US, small hail is included with regular hail and the remarks section is used saying "GR LESS THAN ¼". If no intensity is reported with small hail, use the "moderate ice pellets or small hail" allowance times. If an intensity is reported with small hail, the ice pellet condition with the equivalent intensity can be used, e.g. if light small hail is reported, the "light ice pellets" allowance times can be used. This also applies in mixed conditions, e.g. if light small hail mixed with light snow is reported, use the "light ice pellets mixed with light snow" allowance times.

[4] No allowance times exist in this condition for temperatures of 0 °C (32 °F) and below.

[5] If the glycol type is unknown, the allowance times for SAE Type IV Propylene Glycol (PG) fluids should be used.

Type IV Fluids Ethylene Glycol (EG) Fluids Ice Pellet and Small Hail Allowance Times Slats/Flaps Deployed Prior to Deicing/Anti-Icing Table 15

ICE PELLET ALLOWANCE TIME

Precipitation Types or Combinations	Applicable METAR Codes	Outside Air Temperature			
		-5 °C and above (23 °F and above)	Below -5 to -10 °C (Below 23 to 14 °F)	Below -10 to -16 °C (Below 14 to 3.2 °F)	Below -16 to -22 °C ^[1] (Below 3 to -7.6 °F) ^[1]
Light Ice Pellets	-PL	50 minutes	30 minutes	30 minutes ^[2]	30 minutes ^[2]
Light Ice Pellets Mixed with Light Snow	-PLSN, -SNPL	40 minutes	15 minutes	15 minutes ^[2]	Caution: No allowance times currently exist
Light Ice Pellets Mixed with Light Freezing Drizzle or Moderate Freezing Drizzle	-PLFZDZ, -FZDZPL, FZDZPL	25 minutes	10 minutes		
Light Ice Pellets Mixed with Light Freezing Rain	-PLFZRA, -FZRAPL	25 minutes	10 minutes		
Light Ice Pellets Mixed with Light Rain	-PLRA, -RAPL	25 minutes ^[3]			
Moderate Ice Pellets (or Small Hail) ^[4]	PL, GS	15 minutes	10 minutes	10 minutes ^[2]	Caution: No allowance times currently exist
Moderate Ice Pellets (or Small Hail) ^[4] Mixed with Moderate Freezing Drizzle	PLFZDZ, GSFZDZ	10 minutes	7 minutes		
Moderate Ice Pellets (or Small Hail) ^[4] Mixed with Moderate Rain	PLRA, GSRA, RAPL, RAGS	10 minutes ^[5]			

[1] Ensure that the lowest operational use temperature (LOUT) is respected.

[2] No allowance times exist for propylene glycol (PG) fluids when used on aircraft with rotation speeds less than 115 knots.

[3] No allowance times exist in this condition for temperatures of 0 °C (32 °F) and below; consider use of light ice pellets mixed with light freezing rain.

[4] In Canada (and outside the US) the code GS is used when hail is less than 5 mm and GR when it is 5mm or greater. In the US, small hail is included with regular hail and the remarks section is used saying "GR LESS THAN ¼". If no intensity is reported with small hail, use the "moderate ice pellets or small hail" allowance times. If an intensity is reported with small hail, the ice pellet condition with the equivalent intensity can be used, e.g. if light small hail is reported, the "light ice pellets" allowance times can be used. This also applies in mixed conditions, e.g. if light small hail mixed with light snow is reported, use the "light ice pellets mixed with light snow" allowance times.

[5] No allowance times exist in this condition for temperatures of 0 °C (32 °F) and below.

[6] If the glycol type is unknown, the allowance times for SAE Type IV Propylene Glycol (PG) fluids should be used.

Type IV Fluids Propylene Glycol (PG) Fluids Ice Pellet and Small Hail Allowance Times Slats/Flaps Retracted Prior to Deicing/Anti-Icing

Table 16

ICE PELLET ALLOWANCE TIME

Precipitation Types or Combinations	Applicable METAR Codes	Outside Air Temperature			
		-5 °C and above (23 °F and above)	Below -5 to -10 °C (Below 23 to 14 °F)	Below -10 to -16 °C (Below 14 to 3.2 °F)	Below -16 to -22 °C ^[1] (Below 3 to -7.6 °F) ^[1]
Light Ice Pellets	-PL	38 minutes	23 minutes	23 minutes ^[2]	23 minutes ^[2]
Light Ice Pellets Mixed with Light Snow	-PLSN, -SNPL	30 minutes	11 minutes	11 minutes ^[2]	Caution: No allowance times currently exist
Light Ice Pellets Mixed with Light Freezing Drizzle or Moderate Freezing Drizzle	-PLFZDZ, -FZDZPL, FZDZPL	19 minutes	8 minutes		
Light Ice Pellets Mixed with Light Freezing Rain	-PLFZRA, -FZRAPL	19 minutes	8 minutes		
Light Ice Pellets Mixed with Light Rain	-PLRA, -RAPL	19 minutes ^[3]			
Moderate Ice Pellets (or Small Hail ^[4])	PL, GS	14 minutes	8 minutes	8 minutes ^[2]	Caution: No allowance times currently exist
Moderate Ice Pellets (or Small Hail ^[4]) Mixed with Moderate Freezing Drizzle	PLFZDZ, GSFZDZ	8 minutes	5 minutes		
Moderate Ice Pellets (or Small Hail ^[4]) Mixed with Moderate Rain	PLRA, GSRA, RAPL, RAGS	8 minutes ^[5]			

[1] Ensure that the lowest operational use temperature (LOUT) is respected.

[2] No allowance times exist for propylene glycol (PG) fluids when used on aircraft with rotation speeds less than 115 knots.

[3] No allowance times exist in this condition for temperatures of 0 °C (32 °F) and below; consider use of light ice pellets mixed with light freezing rain.

[4] In Canada (and outside the US) the code GS is used when hail is less than 5 mm and GR when it is 5mm or greater. In the US, small hail is included with regular hail and the remarks section is used saying "GR LESS THAN ¼". If no intensity is reported with small hail, use the "moderate ice pellets or small hail" allowance times. If an intensity is reported with small hail, the ice pellet condition with the equivalent intensity can be used, e.g. if light small hail is reported, the "light ice pellets" allowance times can be used. This also applies in mixed conditions, e.g. if light small hail mixed with light snow is reported, use the "light ice pellets mixed with light snow" allowance times.

[5] No allowance times exist in this condition for temperatures of 0 °C (32 °F) and below.

[6] If the glycol type is unknown, the allowance times for SAE Type IV Propylene Glycol (PG) fluids should be used.

Type IV Fluids Propylene Glycol (PG) Fluids Ice Pellet and Small Hail Allowance Times Slats/Flaps Deployed Prior to Deicing/Anti-Icing
Table 17

BOMBARDIER CHALLENGER 605	<i>SUPP-02-1</i>
	<i>REV 49, Nov 19/18</i>

STEEP APPROACH

This supplement is divided into two sections and provides steep approach data for the following:

- Steep Approach from 4.5 Degrees to 5.5 Degrees (TC and EASA only) (See Page SUPP–02–2)
- FAA Steep Approach into London City Airport (See Page SUPP–02–14)

TRAINING PURPOSES ONLY

STEEP APPROACH FROM 4.5 DEGREES TO 5.5 DEGREES

Landing Speeds and Distances

ALTITUDE - SEA LEVEL

V_{REF} = Speed at 50 ft screen height – KIAS
 V_{AC} = Approach climb speed (Flap 20°) – KIAS
 V_{FTO} = Final segment speed (Flap 0°) – KIAS
LFL = Landing Field Length – Feet – Zero wind
ALD = Actual Landing Distance – Feet – Zero wind and zero runway gradient

Corrected Landing Distance

Gradient Correction: No correction for UPHILL gradient
Increase by 300 ft for every 1% DOWNHILL

Wind Correction: No TAILWIND allowed
Decrease by 10 ft for every knot
HEADWIND (refer to PERF-07-3 for wind component conversions)

Landing Speed Correction: Increase distance by 12% for every 10 knots above V_{REF}
(maximum correction is +10 KIAS)

Shaded area indicates landing data above maximum landing weight for steep approach operations.

WT LB	V_{REF} V_{AC} V_{FTO}	LFL		ALD TEMPERATURE - °C											
				-40	-10	0	10	15	20	25	30	35	40	45	50
28000	116	3620	DRY	2170	2170	2170	2170	2170	2200	2220	2250	2280	2300	2330	2360
	129	4160	WET	3220	3220	3220	3220	3220	3270	3310	3360	3400	3450	3490	3540
	145														
30000	117	3660	DRY	2200	2200	2200	2200	2200	2220	2250	2280	2300	2330	2360	2380
	129	4210	WET	3270	3270	3270	3270	3270	3320	3370	3410	3460	3500	3550	3590
	145														
32000	121	3820	DRY	2290	2290	2290	2290	2290	2320	2350	2380	2410	2440	2460	2490
	129	4390	WET	3430	3430	3430	3430	3430	3480	3530	3580	3620	3670	3720	3770
	145														
34000	125	3980	DRY	2390	2390	2390	2390	2390	2420	2450	2480	2510	2540	2570	2600
	129	4580	WET	3590	3590	3590	3590	3590	3640	3690	3740	3790	3850	3900	3950
	149														
35000	127	4060	DRY	2440	2440	2440	2440	2440	2470	2500	2530	2560	2590	2630	2660
	129	4670	WET	3670	3670	3670	3670	3670	3720	3770	3830	3880	3930	3980	4030
	152														
36000	128	4150	DRY	2490	2490	2490	2490	2490	2520	2550	2590	2620	2650	2680	2710
	129	4770	WET	3750	3750	3750	3750	3750	3800	3860	3910	3960	4020	4070	4120
	154														
38000	132	4310	DRY	2590	2590	2590	2590	2590	2620	2650	2690	2720	2750	2790	2820
	132	4950	WET	3910	3910	3910	3910	3910	3960	4020	4080	4130	4190	4250	4300
	158														

QRH_WETSALDATAL_F45_IMP_CL604_19MAR07

QR1_DX_001

STEEP APPROACH FROM 4.5 DEGREES TO 5.5 DEGREES**Landing Speeds and Distances (Cont'd)****ALTITUDE - SEA LEVEL - WET-GROOVED RUNWAY** V_{REF} = Speed at 50 ft screen height – KIAS V_{AC} = Approach climb speed (Flap 20°) – KIAS V_{FTO} = Final segment speed (Flap 0°) – KIAS

Uncorrected distances presented are based on zero wind and zero runway gradient conditions.

Corrected Landing Distance

Gradient Correction: No correction for UPHILL gradient
Increase by 350 ft for every
1% DOWNHILL

Wind Correction: No TAILWIND allowed
Decrease by 25 ft for every knot
HEADWIND (refer to PERF-07-3 for
wind component conversions)

Landing Speed Correction: Increase distance by 12% for every
10 knots above V_{REF}
(maximum correction is +10 KIAS)

If the landing field length on a dry runway is greater than the corrected landing distance on a wet grooved runway, use the landing field length.

Shaded area indicates landing data above maximum landing weight for steep approach operations.

WT LB	V_{REF} V_{AC} V_{FTO}	UNCORRECTED LANDING DISTANCE ON WET-GROOVED RUNWAY											
		TEMPERATURE – °C											
		-40	-10	0	10	15	20	25	30	35	40	45	50
28000	116												
	129	2920	3200	3290	3390	3430	3480	3520	3570	3610	3660	3700	3750
	145												
30000	117												
	129	2970	3250	3340	3440	3480	3530	3580	3620	3670	3710	3760	3800
	145												
32000	121												
	129	3100	3400	3500	3590	3640	3690	3740	3790	3840	3890	3940	3980
	145												
34000	125												
	129	3230	3540	3650	3750	3810	3860	3910	3960	4010	4060	4110	4160
	149												
35000	127												
	129	3300	3620	3720	3830	3890	3940	3990	4050	4100	4150	4200	4250
	152												
36000	128												
	129	3360	3690	3800	3910	3970	4020	4080	4130	4180	4240	4290	4340
	154												
38000	132												
	132	3490	3840	3950	4070	4130	4190	4240	4300	4360	4410	4470	4520
	158												

QRH_WETGROOVED_SAL_DATA_SL_F45_IMP_CL650_TC_EASA_26JAN17

QR1_DX_033

STEEP APPROACH FROM 4.5 DEGREES TO 5.5 DEGREES**Landing Speeds and Distances (Cont'd)****ALTITUDE - 500 FEET** V_{REF} = Speed at 50 ft screen height – KIAS V_{AC} = Approach climb speed (Flap 20°) – KIAS V_{FTO} = Final segment speed (Flap 0°) – KIAS

LFL = Landing Field Length – Feet – Zero wind

ALD = Actual Landing Distance – Feet – Zero wind and zero runway gradient

Corrected Landing Distance

Gradient Correction: No correction for UPHILL gradient
Increase by 300 ft for every
1% DOWNHILL

Wind Correction: No TAILWIND allowed
Decrease by 10 ft for every knot
HEADWIND (refer to PERF-07-3 for
wind component conversions)

Landing Speed Correction: Increase distance by 12% for every
10 knots above V_{REF}
(maximum correction is +10 KIAS)

Shaded area indicates landing data above maximum landing weight
for steep approach operations.

WT LB	V_{REF} V_{AC} V_{FTO}	LFL		ALD TEMPERATURE – °C											
				-40	-10	0	10	15	20	25	30	35	40	45	49
28000	116	3650	DRY	2170	2170	2170	2170	2200	2220	2250	2280	2300	2330	2360	2380
	129	4200	WET	3220	3220	3220	3220	3270	3310	3360	3400	3450	3490	3540	3570
	145														
30000	117	3690	DRY	2200	2200	2200	2200	2220	2250	2280	2310	2330	2360	2390	2410
	129	4250	WET	3270	3270	3270	3270	3320	3360	3410	3460	3500	3550	3590	3630
	145														
32000	121	3860	DRY	2290	2290	2290	2290	2320	2350	2380	2410	2440	2470	2500	2520
	129	4440	WET	3430	3430	3430	3430	3480	3530	3580	3630	3670	3720	3770	3810
	145														
34000	125	4020	DRY	2390	2390	2390	2390	2420	2450	2480	2510	2540	2570	2600	2630
	129	4630	WET	3590	3590	3590	3590	3640	3690	3740	3790	3850	3900	3950	3990
	149														
35000	127	4110	DRY	2440	2440	2440	2440	2470	2500	2530	2570	2600	2630	2660	2680
	129	4720	WET	3670	3670	3670	3670	3720	3770	3830	3880	3930	3990	4040	4080
	152														
36000	128	4190	DRY	2490	2490	2490	2490	2520	2550	2590	2620	2650	2680	2710	2740
	129	4820	WET	3740	3740	3740	3740	3800	3860	3910	3970	4020	4080	4130	4170
	154														
38000	132	4350	DRY	2590	2590	2590	2590	2620	2650	2690	2720	2760	2790	2820	2850
	132	5010	WET	3900	3900	3900	3900	3960	4020	4080	4140	4190	4250	4310	4350
	158														

QR1_WET_SALDA1A0.5K_F45_IMP_CL604_19MAR07

QR1_DX_002

STEEP APPROACH FROM 4.5 DEGREES TO 5.5 DEGREES**Landing Speeds and Distances (Cont'd)****ALTITUDE - 500 FEET - WET-GROOVED RUNWAY** V_{REF} = Speed at 50 ft screen height – KIAS V_{AC} = Approach climb speed (Flap 20°) – KIAS V_{FTO} = Final segment speed (Flap 0°) – KIAS

Uncorrected distances presented are based on zero wind and zero runway gradient conditions.

Corrected Landing Distance

Gradient Correction: No correction for UPHILL gradient
Increase by 350 ft for every
1% DOWNHILL

Wind Correction: No TAILWIND allowed
Decrease by 25 ft for every knot
HEADWIND (refer to PERF-07-3 for
wind component conversions)

Landing Speed Correction: Increase distance by 12% for every
10 knots above V_{REF}
(maximum correction is +10 KIAS)

If the landing field length on a dry runway is greater than the corrected landing distance on a wet grooved runway, use the landing field length.

Shaded area indicates landing data above maximum landing weight for steep approach operations.

WT LB	V_{REF} V_{AC} V_{FTO}	UNCORRECTED LANDING DISTANCE ON WET-GROOVED RUNWAY											
		TEMPERATURE – °C											
		-40	-10	0	10	15	20	25	30	35	40	45	49
28000	116												
	129	2960	3240	3330	3430	3480	3520	3570	3610	3660	3710	3750	3790
	145												
30000	117												
	129	3000	3290	3380	3480	3530	3580	3620	3670	3720	3760	3810	3850
	145												
32000	121												
	129	3140	3440	3540	3640	3690	3740	3790	3840	3890	3940	3990	4030
	145												
34000	125												
	129	3270	3590	3700	3800	3860	3910	3960	4010	4070	4120	4170	4210
	149												
35000	127												
	129	3340	3660	3770	3880	3940	3990	4050	4100	4150	4210	4260	4300
	152												
36000	128												
	129	3410	3740	3850	3960	4020	4080	4130	4190	4240	4300	4350	4390
	154												
38000	132												
	132	3540	3890	4010	4130	4180	4240	4300	4360	4420	4470	4530	4580
	158												

QRH_WETGROOVED_SAL_DATA_0.5K_F45_IMP_CL650_TC_EASA_26JAN17

QR1_DX_034

STEEP APPROACH FROM 4.5 DEGREES TO 5.5 DEGREES**Landing Speeds and Distances (Cont'd)****ALTITUDE - 1,000 FEET** V_{REF} = Speed at 50 ft screen height – KIAS V_{AC} = Approach climb speed (Flap 20°) – KIAS V_{FTO} = Final segment speed (Flap 0°) – KIAS

LFL = Landing Field Length – Feet – Zero wind

ALD = Actual Landing Distance – Feet – Zero wind and zero runway gradient

Corrected Landing Distance

Gradient Correction: No correction for UPHILL gradient
Increase by 300 ft for every
1% DOWNHILL

Wind Correction: No TAILWIND allowed
Decrease by 10 ft for every knot
HEADWIND (refer to PERF-07-3 for
wind component conversions)

Landing Speed Correction: Increase distance by 12% for every
10 knots above V_{REF}
(maximum correction is +10 KIAS)

Shaded area indicates landing data above maximum landing weight
for steep approach operations.

WT LB	V _{REF} V _{AC} V _{FTO}	LFL		ALD TEMPERATURE – °C											
				-40	-10	0	10	15	20	25	30	35	40	45	48
28000	116	3690	DRY	2200	2200	2200	2200	2220	2250	2280	2310	2330	2360	2390	2400
	129														
	145	4240	WET	3260	3260	3260	3260	3310	3360	3400	3450	3490	3540	3590	3610
30000	118	3750	DRY	2230	2230	2230	2230	2260	2290	2320	2340	2370	2400	2430	2440
	129														
	145	4310	WET	3330	3330	3330	3330	3380	3420	3470	3520	3570	3610	3660	3690
32000	121	3910	DRY	2330	2330	2330	2330	2360	2390	2420	2450	2480	2510	2540	2560
	129														
	145	4500	WET	3490	3490	3490	3490	3540	3590	3640	3690	3740	3790	3840	3870
34000	125	4060	DRY	2430	2430	2430	2430	2460	2490	2530	2560	2590	2620	2650	2670
	129														
	149	4690	WET	3650	3650	3650	3650	3710	3760	3810	3870	3920	3970	4020	4060
35000	127	4170	DRY	2480	2480	2480	2480	2510	2550	2580	2610	2640	2680	2710	2730
	129														
	152	4790	WET	3730	3730	3730	3730	3790	3840	3900	3950	4010	4060	4120	4150
36000	129	4250	DRY	2530	2530	2530	2530	2570	2600	2630	2660	2700	2730	2760	2780
	129														
	154	4890	WET	3810	3810	3810	3810	3870	3930	3980	4040	4100	4150	4210	4240
38000	132	4420	DRY	2630	2630	2630	2630	2670	2700	2740	2770	2810	2840	2880	2900
	133														
	158	5080	WET	3980	3980	3980	3980	4040	4100	4160	4210	4270	4330	4390	4430

QRH_WETSA1DATA1K_F45_IMP_CL604_19MAR07

QR1_DX_003

STEEP APPROACH FROM 4.5 DEGREES TO 5.5 DEGREES**Landing Speeds and Distances (Cont'd)****ALTITUDE - 1,000 FEET - WET-GROOVED RUNWAY****V_{REF}** = Speed at 50 ft screen height – KIAS**V_{AC}** = Approach climb speed (Flap 20°) – KIAS**V_{FTO}** = Final segment speed (Flap 0°) – KIAS

Uncorrected distances presented are based on zero wind and zero runway gradient conditions.

Corrected Landing Distance

Gradient Correction: No correction for UPHILL gradient
Increase by 350 ft for every
1% DOWNHILL

Wind Correction: No TAILWIND allowed
Decrease by 25 ft for every knot
HEADWIND (refer to PERF-07-3 for
wind component conversions)

Landing Speed Correction: Increase distance by 12% for every
10 knots above V_{REF}
(maximum correction is +10 KIAS)

If the landing field length on a dry runway is greater than the corrected landing distance on a wet grooved runway, use the landing field length.

Shaded area indicates landing data above maximum landing weight for steep approach operations.

WT LB	V _{REF} V _{AC} V _{FTO}	UNCORRECTED LANDING DISTANCE ON WET-GROOVED RUNWAY											
		TEMPERATURE – °C											
		-40	-10	0	10	15	20	25	30	35	40	45	48
28000	116												
	129	3000	3280	3380	3470	3520	3570	3610	3660	3710	3750	3800	3830
	145												
30000	118												
	129	3050	3340	3440	3540	3590	3640	3680	3730	3780	3830	3870	3900
	145												
32000	121												
	129	3190	3500	3600	3700	3730	3810	3860	3910	3960	4010	4060	4090
	145												
34000	125												
	129	3330	3650	3760	3870	3920	3980	4030	4080	4140	4190	4240	4280
	149												
35000	127												
	129	3400	3730	3840	3950	4010	4060	4120	4170	4230	4280	4340	4370
	152												
36000	129												
	129	3460	3800	3920	4030	4090	4150	4200	4260	4320	4370	4430	4460
	154												
38000	132												
	133	3600	3960	4080	4200	4250	4320	4380	4440	4500	4550	4610	4650
	158												

QRH_WETGROOVED_SAL_DATA1K_F45_IMP_CL650_TC_EASA_26JAN17

QR1_DX_035

STEEP APPROACH FROM 4.5 DEGREES TO 5.5 DEGREES**Landing Speeds and Distances (Cont'd)****ALTITUDE - 2,000 FEET** V_{REF} = Speed at 50 ft screen height – KIAS V_{AC} = Approach climb speed (Flap 20°) – KIAS V_{FTO} = Final segment speed (Flap 0°) – KIAS

LFL = Landing Field Length – Feet – Zero wind

ALD = Actual Landing Distance – Feet – Zero wind and zero runway gradient

Corrected Landing Distance

Gradient Correction: No correction for UPHILL gradient
Increase by 300 ft for every
1% DOWNHILL

Wind Correction: No TAILWIND allowed
Decrease by 10 ft for every knot
HEADWIND (refer to PERF-07-3 for
wind component conversions)

Landing Speed Correction: Increase distance by 12% for every
10 knots above V_{REF}
(maximum correction is +10 KIAS)

Shaded area indicates landing data above maximum landing weight
for steep approach operations.

WT LB	V _{REF} V _{AC} V _{FTO}	LFL		ALD TEMPERATURE – °C											
				-40	-10	0	10	15	20	25	30	35	40	45	46
28000	116	3760	DRY	225C	2250	2250	2250	2280	2310	2340	2360	2390	2420	2450	2450
	129														
	145	4320	WET	335C	3350	3350	3350	3400	3450	3490	3540	3590	3640	3680	3690
30000	118	3850	DRY	231C	2310	2310	2310	2340	2370	2400	2420	2450	2480	2510	2520
	129														
	145	4430	WET	345C	3450	3450	3450	3500	3550	3600	3650	3700	3750	3800	3810
32000	122	4030	DRY	241C	2410	2410	2410	2440	2470	2510	2540	2570	2600	2630	2640
	129														
	145	4630	WET	362C	3620	3620	3620	3670	3720	3780	3830	3880	3930	3990	4000
34000	126	4200	DRY	252C	2520	2520	2520	2550	2580	2620	2650	2680	2710	2750	2750
	129														
	149	4830	WET	379C	3790	3790	3790	3840	3900	3960	4010	4070	4120	4180	4190
35000	128	4290	DRY	257C	2570	2570	2570	2600	2640	2670	2710	2740	2770	2810	2810
	129														
	152	4940	WET	387C	3870	3870	3870	3930	3990	4050	4100	4160	4220	4270	4290
36000	130	4380	DRY	262C	2620	2620	2620	2660	2690	2730	2760	2800	2830	2870	2870
	130														
	154	5040	WET	396C	3960	3960	3960	4020	4080	4140	4190	4250	4310	4370	4380
38000	133	4560	DRY	273C	2730	2730	2730	2780	2800	2840	2870	2910	2950	2980	2990
	133														
	158	5240	WET	413C	4130	4130	4130	4190	4250	4320	4380	4440	4500	4560	4580

QR1 WETSAI.DAT2K_F45_IMP_CL604_19MAR07

QR1_DX_004

STEEP APPROACH FROM 4.5 DEGREES TO 5.5 DEGREES**Landing Speeds and Distances (Cont'd)****ALTITUDE - 2,000 FEET - WET-GROOVED RUNWAY****V_{REF}** = Speed at 50 ft screen height – KIAS**V_{AC}** = Approach climb speed (Flap 20°) – KIAS**V_{FTO}** = Final segment speed (Flap 0°) – KIAS

Uncorrected distances presented are based on zero wind and zero runway gradient conditions.

Corrected Landing Distance

Gradient Correction: No correction for UPHILL gradient
Increase by 350 ft for every
1% DOWNHILL

Wind Correction: No TAILWIND allowed
Decrease by 25 ft for every knot
HEADWIND (refer to PERF-07-3 for
wind component conversions)

Landing Speed Correction: Increase distance by 12% for every
10 knots above V_{REF}
(maximum correction is +10 KIAS)

If the landing field length on a dry runway is greater than the corrected landing distance on a wet grooved runway, use the landing field length.

Shaded area indicates landing data above maximum landing weight for steep approach operations.

WT LB	V _{REF} V _{AC} V _{FTO}	UNCORRECTED LANDING DISTANCE ON WET-GROOVED RUNWAY											
		TEMPERATURE – °C											
		-40	-10	0	10	15	20	25	30	35	40	45	46
28000	116												
	129	3070	3360	3460	3560	3610	3660	3710	3760	3800	3850	3900	3910
	145												
30000	118												
	129	3150	3460	3560	3660	3710	3760	3810	3860	3910	3960	4010	4020
	145												
32000	122												
	129	3300	3620	3730	3830	3890	3940	3990	4050	4100	4150	4210	4220
	145												
34000	126												
	129	3440	3780	3890	4010	4060	4120	4180	4230	4290	4340	4400	4410
	149												
35000	128												
	129	3510	3860	3980	4090	4150	4210	4270	4320	4380	4440	4500	4510
	152												
36000	130												
	130	3580	3940	4060	4180	4240	4300	4360	4420	4480	4530	4590	4600
	154												
38000	133												
	133	3730	4100	4230	4350	4420	4480	4540	4600	4660	4720	4790	4800
	158												

QRH_WETGROOVED_SAL_DATA2K_F45_IMP_CL650_TC_EASA_26JAN17

QR1_DX_036

STEEP APPROACH FROM 4.5 DEGREES TO 5.5 DEGREES**Landing Speeds and Distances (Cont'd)****ALTITUDE - 4,000 FEET** V_{REF} = Speed at 50 ft screen height – KIAS V_{AC} = Approach climb speed (Flap 20°) – KIAS V_{FTO} = Final segment speed (Flap 0°) – KIAS

LFL = Landing Field Length – Feet – Zero wind

ALD = Actual Landing Distance – Feet – Zero wind and zero runway gradient

Corrected Landing Distance

Gradient Correction: No correction for UPHILL gradient
Increase by 300 ft for every
1% DOWNHILL

Wind Correction: No TAILWIND allowed
Decrease by 10 ft for every knot
HEADWIND (refer to PERF-07-3 for
wind component conversions)

Landing Speed Correction: Increase distance by 12% for every
10 knots above V_{REF}
(maximum correction is +10 KIAS)

Shaded area indicates landing data above maximum landing weight
for steep approach operations.

WT LB	V_{REF} V_{AC} V_{FTO}	LFL		ALD TEMPERATURE – °C											
				-40	-10	0	10	15	20	25	30	35	40	42	
28000	116	3910	DRY	2310	2310	2310	2370	2400	2430	2460	2490	2520	2550	2560	
	129	4500	WET	3430	3430	3430	3540	3590	3640	3690	3740	3790	3850	3870	
	145														
30000	120	4090	DRY	2410	2410	2410	2470	2500	2540	2570	2600	2630	2670	2680	
	129	4700	WET	3600	3600	3600	3710	3760	3820	3870	3930	3980	4040	4060	
	145														
32000	124	4280	DRY	2520	2520	2520	2590	2620	2660	2690	2720	2760	2790	2810	
	129	4920	WET	3780	3780	3780	3900	3960	4010	4070	4130	4190	4240	4270	
	147														
34000	127	4470	DRY	2630	2630	2630	2700	2740	2780	2810	2850	2880	2920	2940	
	129	5140	WET	3960	3960	3960	4080	4150	4210	4270	4330	4390	4450	4480	
	152														
35000	129	4560	DRY	2690	2690	2690	2760	2800	2840	2870	2910	2950	2990	3000	
	130	5250	WET	4050	4050	4050	4180	4240	4310	4370	4430	4500	4560	4580	
	154														
36000	131	4660	DRY	2740	2740	2740	2820	2860	2900	2930	2970	3010	3050	3060	
	132	5360	WET	4140	4140	4140	4270	4340	4400	4470	4530	4600	4660	4690	
	156														
38000	135	4850	DRY	2850	2850	2850	2940	2980	3020	3060	3100	3140	3180	3190	
	135	5580	WET	4320	4320	4320	4460	4530	4600	4670	4740	4810	4870	4900	
	161														

QR1_WETSALDATA4K_F45_IMP_CL604_19MAR07

QR1_DX_005

STEEP APPROACH FROM 4.5 DEGREES TO 5.5 DEGREES**Landing Speeds and Distances (Cont'd)****ALTITUDE - 4,000 FEET - WET-GROOVED RUNWAY****V_{REF}** = Speed at 50 ft screen height – KIAS**V_{AC}** = Approach climb speed (Flap 20°) – KIAS**V_{FTO}** = Final segment speed (Flap 0°) – KIAS

Uncorrected distances presented are based on zero wind and zero runway gradient conditions.

Corrected Landing Distance

Gradient Correction: No correction for UPHILL gradient
Increase by 350 ft for every
1% DOWNHILL

Wind Correction: No TAILWIND allowed
Decrease by 25 ft for every knot
HEADWIND (refer to PERF-07-3 for
wind component conversions)

Landing Speed Correction: Increase distance by 12% for every
10 knots above V_{REF}
(maximum correction is +10 KIAS)

If the landing field length on a dry runway is greater than the corrected landing distance on a wet grooved runway, use the landing field length.

Shaded area indicates landing data above maximum landing weight for steep approach operations.

WT LB	V _{REF} V _{AC} V _{FTO}	UNCORRECTED LANDING DISTANCE ON WET-GROOVED RUNWAY										
		TEMPERATURE – °C										
		-40	-10	0	10	15	20	25	30	35	40	42
28000	116											
	129	3230	3540	3650	3750	3810	3860	3910	3960	4010	4060	4080
	145											
30000	120											
	129	3370	3710	3820	3930	3980	4040	4090	4150	4200	4260	4280
	145											
32000	124											
	129	3530	3880	4000	4120	4180	4230	4290	4350	4410	4470	4490
	147											
34000	127											
	129	3690	4060	4180	4310	4370	4430	4490	4550	4610	4670	4700
	152											
35000	129											
	130	3770	4150	4270	4400	4470	4530	4590	4650	4720	4780	4800
	154											
36000	131											
	132	3850	4240	4370	4500	4560	4630	4690	4760	4820	4880	4910
	156											
38000	135											
	135	4000	4410	4550	4690	4750	4820	4890	4960	5020	5090	5120
	161											

QRH_WETGROOVED_SAL_DATA4K_F45_IMP_CL650_TC_EASA_26JAN17

QR1_DX_037

STEEP APPROACH FROM 4.5 DEGREES TO 5.5 DEGREES**Landing Speeds and Distances (Cont'd)****ALTITUDE - 5,000 FEET** V_{REF} = Speed at 50 ft screen height – KIAS V_{AC} = Approach climb speed (Flap 20°) – KIAS V_{FTO} = Final segment speed (Flap 0°) – KIAS

LFL = Landing Field Length – Feet – Zero wind

ALD = Actual Landing Distance – Feet – Zero wind and zero runway gradient

Corrected Landing Distance

Gradient Correction: No correction for UPHILL gradient
Increase by 300 ft for every
1% DOWNHILL

Wind Correction: No TAILWIND allowed
Decrease by 10 ft for every knot
HEADWIND (refer to PERF-07-3 for
wind component conversions)

Landing Speed Correction: Increase distance by 12% for every
10 knots above V_{REF}
(maximum correction is +10 KIAS)

Shaded area indicates landing data above maximum landing weight
for steep approach operations.

WT LB	V_{REF} V_{AC} V_{FTO}	LFL		ALD TEMPERATURE – °C										
				-40	-10	0	10	15	20	25	30	35	40	
28000	116	4020	DRY	2380	2380	2380	2440	2480	2510	2540	2570	2600	2630	
	129	4620	WET	3560	3560	3560	3670	3720	3770	3830	3880	3930	3990	
	145													
30000	120	4220	DRY	2500	2500	2500	2570	2600	2630	2670	2700	2730	2770	
	129	4850	WET	3750	3750	3750	3860	3920	3980	4030	4090	4150	4200	
	145													
32000	124	4420	DRY	2620	2620	2620	2690	2720	2760	2790	2830	2870	2900	
	129	5080	WET	3940	3940	3940	4060	4120	4180	4240	4300	4360	4420	
	149													
34000	128	4620	DRY	2730	2730	2730	2810	2850	2880	2920	2960	3000	3040	
	129	5310	WET	4130	4130	4130	4260	4320	4390	4450	4520	4580	4640	
	153													
35000	130	4720	DRY	2790	2790	2790	2870	2910	2950	2990	3030	3060	3100	
	131	5420	WET	4220	4220	4220	4360	4420	4490	4560	4620	4690	4750	
	155													
36000	132	4820	DRY	2850	2850	2850	2930	2970	3010	3050	3090	3130	3170	
	133	5540	WET	4320	4320	4320	4460	4520	4590	4660	4730	4800	4860	
	158													
38000	138	5010	DRY	2970	2970	2970	3050	3090	3140	3180	3220	3260	3310	
	136	5770	WET	4510	4510	4510	4660	4730	4800	4870	4940	5010	5090	
	162													

QRH_WETSALDATA5K_F45_IMP_CL604_19MAY07

QR1_DX_006

STEEP APPROACH FROM 4.5 DEGREES TO 5.5 DEGREES**Landing Speeds and Distances (Cont'd)****ALTITUDE - 5,000 FEET - WET-GROOVED RUNWAY****V_{REF}** = Speed at 50 ft screen height – KIAS**V_{AC}** = Approach climb speed (Flap 20°) – KIAS**V_{FTO}** = Final segment speed (Flap 0°) – KIAS

Uncorrected distances presented are based on zero wind and zero runway gradient conditions.

Corrected Landing Distance

Gradient Correction: No correction for UPHILL gradient
Increase by 350 ft for every
1% DOWNHILL

Wind Correction: No TAILWIND allowed
Decrease by 25 ft for every knot
HEADWIND (refer to PERF-07-3 for
wind component conversions)

Landing Speed Correction: Increase distance by 12% for every
10 knots above V_{REF}
(maximum correction is +10 KIAS)

If the landing field length on a dry runway is greater than the corrected landing distance on a wet grooved runway, use the landing field length.

Shaded area indicates landing data above maximum landing weight for steep approach operations.

WT LB	V _{REF} V _{AC} V _{FTO}	UNCORRECTED LANDING DISTANCE ON WET-GROOVED RUNWAY											
		TEMPERATURE – °C											
		-40	-10	0	10	15	20	25	30	35	40		
28000	116												
	129	3340	3670	3770	3880	3940	3990	4050	4100	4150	4210		
	145												
30000	120												
	129	3500	3850	3970	4080	4140	4200	4250	4310	4370	4420		
	145												
32000	124												
	129	3670	4040	4160	4280	4340	4400	4460	4520	4580	4640		
	149												
34000	128												
	129	3830	4220	4350	4480	4540	4610	4670	4740	4800	4860		
	153												
35000	130												
	131	3920	4310	4450	4580	4650	4710	4780	4840	4910	4970		
	155												
36000	132												
	133	4000	4410	4540	4680	4750	4810	4880	4950	5010	5080		
	158												
38000	136												
	136	4160	4590	4730	4880	4950	5020	5090	5160	5230	5300		
	162												

QRH_WETGROOVED_SAL_DATA5K_F45_IMP_CL650_TC_EASA_26JAN17

QR1_DX_038

FAA STEEP APPROACH INTO LONDON CITY AIRPORT

Landing Speeds and Distances

ALTITUDE - SEA LEVEL

 V_{REF} = Speed at 60 ft screen height – KIAS V_{AC} = Approach climb speed (Flap 20°) – KIAS V_{FTO} = Final segment speed (Flap 0°) – KIAS

LFL = Landing Field Length – Feet – Zero wind

ALD = Actual Landing Distance – Feet – Zero wind and zero runway gradient

Corrected Landing Distance

Gradient Correction: No correction for UPHILL gradient
Increase by 300 ft for every
1% DOWNHILL

Wind Correction: No TAILWIND allowed
Decrease by 10 ft for every knot
HEADWIND (refer to PERF-07-3 for
wind component conversions)

Landing Speed Correction: Increase distance by 12% for every
10 knots above V_{REF}
(maximum correction is +10 KIAS)

Shaded area indicates landing data above maximum landing weight
for steep approach operations.

WT LB	V _{REF} V _{VAC} V _{FTO}	LFL		ALD TEMPERATURE – °C											
				–40	–10	0	10	15	20	25	30	35	40	45	50
28000	116	3840	DRY	2300	2300	2300	2330	2300	2330	2360	2380	2410	2440	2460	2490
	129														
	145	4410	WET	3360	3360	3360	3360	3360	3400	3450	3490	3540	3580	3620	3670
30000	117	3880	DRY	2330	2330	2330	2330	2330	2360	2380	2410	2440	2460	2490	2520
	129														
	145	4460	WET	3410	3410	3410	3410	3410	3450	3500	3540	3590	3630	3680	3720
32000	121	4040	DRY	2430	2430	2430	2430	2430	2460	2480	2510	2540	2570	2600	2630
	129														
	145	4650	WET	3560	3560	3560	3560	3560	3610	3660	3710	3760	3810	3850	3900
32500	122	4080	DRY	2450	2450	2450	2450	2450	2480	2510	2540	2570	2600	2620	2650
	129														
	146	4690	WET	3600	3600	3600	3600	3600	3650	3700	3750	3800	3850	3900	3950
34000	125	4210	DRY	2520	2520	2520	2520	2520	2560	2590	2620	2650	2680	2710	2740
	129														
	149	4840	WET	3720	3720	3720	3720	3720	3770	3830	3880	3930	3980	4030	4080
35000	127	4290	DRY	2570	2570	2570	2570	2570	2610	2640	2670	2700	2730	2760	2790
	129														
	152	4930	WET	3800	3800	3800	3800	3800	3860	3910	3960	4010	4070	4120	4170

QRH_WETSALDATASL_F45_IMP_CL604_605_650_FAA_25JAN17

QR1_DX_032

FAA STEEP APPROACH INTO LONDON CITY AIRPORT**Landing Speeds and Distances (Cont'd)****ALTITUDE - SEA LEVEL - WET-GROOVED RUNWAY** V_{REF} = Speed at 60 ft screen height – KIAS V_{AC} = Approach climb speed (Flap 20°) – KIAS V_{FTO} = Final segment speed (Flap 0°) – KIAS

Uncorrected distances presented are based on zero wind and zero runway gradient conditions.

Corrected Landing Distance

Gradient Correction: No correction for UPHILL gradient
Increase by 350 ft for every
1% DOWNHILL

Wind Correction: No TAILWIND allowed
Decrease by 25 ft for every knot
HEADWIND (refer to PERF-07-3 for
wind component conversions)

Landing Speed Correction: Increase distance by 11% for every
10 knots above V_{REF}
(maximum correction is +10 KIAS)

If the landing field length on a dry runway is greater than the corrected landing distance on a wet grooved runway, use the landing field length.

Shaded area indicates landing data above maximum landing weight for steep approach operations.

WT LB	V_{REF} V_{AC} V_{FTO}	UNCORRECTED LANDING DISTANCE ON WET-GROOVED RUNWAY											
		TEMPERATURE – °C											
		-40	-10	0	10	15	20	25	30	35	40	45	50
28000	116												
	129	3090	3370	3460	3550	3600	3650	3690	3740	3780	3830	3870	3920
	145												
30000	117												
	129	3130	3420	3510	3610	3650	3700	3750	3790	3840	3880	3930	3970
	145												
32000	121												
	129	3270	3560	3660	3760	3810	3860	3910	3960	4010	4060	4110	4160
	145												
32500	122												
	129	3300	3600	3700	3800	3850	3900	3950	4000	4050	4100	4150	4200
	146												
34000	125												
	129	3400	3710	3820	3920	3980	4030	4080	4130	4180	4230	4290	4340
	149												
35000	127												
	129	3460	3790	3890	4000	4060	4110	4160	4220	4270	4320	4370	4430
	152												

QRH_WETGROOVED_SAL_DATA_SL_F45_IMP_CL650_FAA_26JAN17

QR1_DX_039

FAA STEEP APPROACH INTO LONDON CITY AIRPORT

Landing Speeds and Distances (Cont'd)

ALTITUDE - 500 FEET

 V_{REF} = Speed at 60 ft screen height – KIAS V_{AC} = Approach climb speed (Flap 20°) – KIAS V_{FTO} = Final segment speed (Flap 0°) – KIAS

LFL = Landing Field Length – Feet – Zero wind

ALD = Actual Landing Distance – Feet – Zero wind and zero runway gradient

Corrected Landing Distance

Gradient Correction: No correction for UPHILL gradient
Increase by 300 ft for every
1% DOWNHILL

Wind Correction: No TAILWIND allowed
Decrease by 10 ft for every knot
HEADWIND (refer to PERF-07-3 for
wind component conversions)

Landing Speed Correction: Increase distance by 12% for every
10 knots above V_{REF}
(maximum correction is +10 KIAS)

Shaded area indicates landing data above maximum landing weight for steep approach operations.

WT LB	V _{REF} V _{AC} V _{FTO}	LFL		ALD TEMPERATURE – °C											
				–40	–10	0	10	15	20	25	30	35	40	45	49
28000	116	3870	DRY	2300	2300	2300	2300	2830	2360	2380	2410	2440	2460	2490	2510
	129														
	145	4450	WET	3350	3350	3350	3350	3400	3440	3490	3540	3580	3630	3670	3710
30000	117	3910	DRY	2330	2330	2330	2330	2360	2380	2410	2440	2460	2490	2520	2540
	129														
	145	4500	WET	3400	3400	3400	3400	3450	3500	3540	3590	3640	3680	3730	3760
32000	121	4080	DRY	2430	2430	2430	2430	2460	2480	2510	2540	2570	2600	2630	2650
	129														
	145	4690	WET	3560	3560	3560	3560	3610	3660	3710	3760	3810	3860	3910	3950
32500	122	4120	DRY	2450	2450	2450	2450	2480	2510	2540	2570	2600	2630	2660	2680
	129														
	146	4740	WET	3600	3600	3600	3600	3650	3700	3750	3800	3850	3900	3950	3990
34000	125	4250	DRY	2520	2520	2520	2520	2560	2590	2620	2650	2680	2710	2740	2760
	129														
	149	4880	WET	3720	3720	3720	3720	3770	3820	3880	3930	3980	4030	4090	4130
35000	127	4330	DRY	2570	2570	2570	2570	2610	2640	2670	2700	2730	2760	2800	2820
	129														
	152	4980	WET	3800	3800	3800	3800	3850	3910	3960	4010	4070	4120	4180	4220

QRH_WETSALDATA05K_F45_IMP_CL604_605_650_FAA_25JAN17

QR1_DX_029

FAA STEEP APPROACH INTO LONDON CITY AIRPORT

Landing Speeds and Distances (Cont'd)

ALTITUDE - 500 FEET - WET-GROOVED RUNWAY

 V_{REF} = Speed at 60 ft screen height – KIAS V_{AC} = Approach climb speed (Flap 20°) – KIAS V_{FTO} = Final segment speed (Flap 0°) – KIAS

Uncorrected distances presented are based on zero wind and zero runway gradient conditions.

Corrected Landing Distance

Gradient Correction: No correction for UPHILL gradient
Increase by 350 ft for every
1% DOWNHILL

Wind Correction: No TAILWIND allowed
Decrease by 25 ft for every knot
HEADWIND (refer to PERF-07-3 for
wind component conversions)

Landing Speed Correction: Increase distance by 11% for every
10 knots above V_{REF}
(maximum correction is +10 KIAS)

If the landing field length on a dry runway is greater than the corrected landing distance on a wet grooved runway, use the landing field length.

Shaded area indicates landing data above maximum landing weight for steep approach operations.

WT LB	V_{REF} V_{AC} V_{FTO}	UNCORRECTED LANDING DISTANCE ON WET-GROOVED RUNWAY											
		TEMPERATURE – °C											
		-40	-10	0	10	15	20	25	30	35	40	45	49
28000	116												
	129	3130	3410	3500	3600	3640	3690	3740	3780	3830	3880	3920	3960
	145												
30000	117												
	129	3170	3460	3550	3650	3700	3740	3790	3840	3890	3930	3980	4020
	145												
32000	121												
	129	3310	3610	3710	3810	3860	3910	3960	4010	4060	4110	4160	4200
	145												
32500	122												
	129	3340	3650	3750	3850	3900	3950	4000	4050	4110	4160	4210	4240
	146												
34000	125												
	129	3440	3760	3870	3970	4030	4080	4130	4180	4240	4290	4340	4380
	149												
35000	127												
	129	3510	3830	3940	4050	4110	4160	4220	4270	4320	4380	4430	4470
	152												

QRH_WETGROOVED_SAL_DATA_0.5K_F45_IMP_CL650_FAA_26JAN17

QR1_DX_040

FAA STEEP APPROACH INTO LONDON CITY AIRPORT

Landing Speeds and Distances (Cont'd)

ALTITUDE - 1,000 FEET

 V_{REF} = Speed at 60 ft screen height – KIAS V_{AC} = Approach climb speed (Flap 20°) – KIAS V_{FTO} = Final segment speed (Flap 0°) – KIAS

LFL = Landing Field Length – Feet – Zero wind

ALD = Actual Landing Distance – Feet – Zero wind and zero runway gradient

Corrected Landing Distance

Gradient Correction: No correction for UPHILL gradient
Increase by 300 ft for every
1% DOWNHILLWind Correction: No TAILWIND allowed
Decrease by 10 ft for every knot
HEADWIND (refer to PERF-07-3 for
wind component conversions)Landing Speed Correction: Increase distance by 12% for every
10 knots above V_{REF}
(maximum correction is +10 KIAS)Shaded area indicates landing data above maximum landing weight
for steep approach operations.

WT LB	V_{REF} V_{AC} V_{FTO}	LFL		ALD TEMPERATURE – °C											
				-40	-10	0	10	15	20	25	30	35	40	45	48
28000	116	3910	DRY	2330	2330	2330	2330	2360	2380	2410	2440	2470	2490	2520	2540
	129														
	145	4490	WET	3390	3390	3390	3390	3440	3490	3530	3580	3630	3670	3720	3750
30000	118	3970	DRY	2360	2360	2360	2360	2390	2420	2450	2480	2500	2530	2560	2580
	129														
	145	4560	WET	3460	3460	3460	3460	3510	3560	3600	3650	3700	3750	3790	3820
32000	121	4140	DRY	2460	2460	2460	2460	2500	2520	2550	2580	2610	2640	2670	2690
	129														
	145	4750	WET	3620	3620	3620	3620	3670	3720	3770	3830	3880	3930	3980	4010
32500	122	4180	DRY	2490	2490	2490	2490	2520	2550	2580	2610	2640	2670	2700	2720
	129														
	146	4800	WET	3660	3660	3660	3660	3710	3770	3820	3870	3920	3970	4020	4050
34000	125	4310	DRY	2570	2570	2570	2570	2600	2630	2660	2690	2720	2760	2790	2810
	129														
	149	4950	WET	3780	3780	3780	3780	3840	3890	3950	4000	4050	4110	4160	4190
35000	127	4390	DRY	2620	2620	2620	2620	2650	2680	2710	2750	2780	2810	2840	2860
	129														
	152	5050	WET	3870	3870	3870	3870	3920	3980	4030	4090	4140	4200	4250	4280

QRH_WETSALDATA1K_F45_IMP_CL604_605_650_FAA_25JAN17

QR1_DX_030

FAA STEEP APPROACH INTO LONDON CITY AIRPORT

Landing Speeds and Distances (Cont'd)

ALTITUDE - 1,000 FEET - WET-GROOVED RUNWAY

 V_{REF} = Speed at 60 ft screen height – KIAS V_{AC} = Approach climb speed (Flap 20°) – KIAS V_{FTO} = Final segment speed (Flap 0°) – KIAS

Uncorrected distances presented are based on zero wind and zero runway gradient conditions.

Corrected Landing Distance

Gradient Correction: No correction for UPHILL gradient
Increase by 350 ft for every
1% DOWNHILL

Wind Correction: No TAILWIND allowed
Decrease by 25 ft for every knot
HEADWIND (refer to PERF-07-3 for
wind component conversions)

Landing Speed Correction: Increase distance by 11% for every
10 knots above V_{REF}
(maximum correction is +10 KIAS)

If the landing field length on a dry runway is greater than the corrected landing distance on a wet grooved runway, use the landing field length.

Shaded area indicates landing data above maximum landing weight for steep approach operations.

WT LB	V_{REF} V_{AC} V_{FTO}	UNCORRECTED LANDING DISTANCE ON WET-GROOVED RUNWAY											
		TEMPERATURE – °C											
		-40	-10	0	10	15	20	25	30	35	40	45	48
28000	116												
	129	3160	3450	3550	3640	3690	3740	3780	3830	3880	3920	3970	4000
	145												
30000	118												
	129	3220	3510	3610	3710	3760	3810	3850	3900	3950	4000	4050	4070
	145												
32000	121												
	129	3360	3670	3770	3870	3930	3980	4030	4080	4130	4180	4230	4260
	145												
32500	122												
	129	3390	3710	3810	3920	3970	4020	4070	4120	4170	4230	4280	4310
	146												
34000	125												
	129	3500	3820	3930	4040	4090	4150	4200	4260	4310	4360	4420	4450
	149												
35000	127												
	129	3560	3900	4010	4120	4180	4230	4290	4340	4400	4450	4510	4540
	152												

QRH_WETGROOVED_SAL_DATA1K_F45_IMP_CL650_FAA_26JAN17

QR1_DX_041

FAA STEEP APPROACH INTO LONDON CITY AIRPORT**Landing Speeds and Distances (Cont'd)****ALTITUDE - 2,000 FEET** V_{REF} = Speed at 60 ft screen height – KIAS V_{AC} = Approach climb speed (Flap 20°) – KIAS V_{FTO} = Final segment speed (Flap 0°) – KIAS

LFL = Landing Field Length – Feet – Zero wind

ALD = Actual Landing Distance – Feet – Zero wind and zero runway gradient

Corrected Landing Distance

Gradient Correction: No correction for UPHILL gradient
Increase by 300 ft for every
1% DOWNHILL

Wind Correction: No TAILWIND allowed
Decrease by 10 ft for every knot
HEADWIND (refer to PERF-07-3 for
wind component conversions)

Landing Speed Correction: Increase distance by 12% for every
10 knots above V_{REF}
(maximum correction is +10 KIAS)

Shaded area indicates landing data above maximum landing weight
for steep approach operations.

WT LB	V_{REF} V_{AC} V_{FTO}	LFL		ALD TEMPERATURE – °C											
				-40	-10	0	10	15	20	25	30	35	40	45	46
28000	116	3980	DRY	2380	2380	2380	2380	2410	2440	2470	2500	2530	2550	2580	2590
	129														
	145	4570	WET	3480	3480	3480	3480	3530	3580	3630	3670	3720	3770	3820	3830
30000	118	4070	DRY	2440	2440	2440	2440	2470	2500	2530	2560	2590	2620	2650	2650
	129														
	145	4680	WET	3580	3580	3580	3580	3630	3680	3730	3780	3830	3880	3930	3940
32000	122	4250	DRY	2550	2550	2550	2550	2580	2610	2640	2670	2700	2730	2760	2770
	129														
	145	4890	WET	3750	3750	3750	3750	3800	3860	3910	3960	4020	4070	4120	4130
32500	123	4300	DRY	2570	2570	2570	2570	2600	2640	2670	2700	2730	2760	2790	2800
	129														
	146	4940	WET	3790	3790	3790	3790	3850	3900	3960	4010	4060	4120	4170	4180
34000	126	4430	DRY	2650	2650	2650	2650	2690	2720	2750	2780	2820	2850	2880	2890
	129														
	149	5090	WET	3920	3920	3920	3920	3980	4030	4090	4150	4200	4260	4310	4330
35000	128	4520	DRY	2700	2700	2700	2700	2740	2770	2810	2840	2870	2910	2940	2950
	129														
	152	5190	WET	4010	4010	4010	4010	4070	4120	4180	4240	4300	4350	4410	4420

QRH_WETSALDATA2K_F45_IMP_CL604_605_650_FAA_25JAN17

QR1_DX_031

FAA STEEP APPROACH INTO LONDON CITY AIRPORT

Landing Speeds and Distances (Cont'd)

ALTITUDE - 2,000 FEET - WET-GROOVED RUNWAY

 V_{REF} = Speed at 60 ft screen height – KIAS V_{AC} = Approach climb speed (Flap 20°) – KIAS V_{FTO} = Final segment speed (Flap 0°) – KIAS

Uncorrected distances presented are based on zero wind and zero runway gradient conditions.

Corrected Landing Distance

Gradient Correction: No correction for UPHILL gradient
Increase by 350 ft for every
1% DOWNHILL

Wind Correction: No TAILWIND allowed
Decrease by 25 ft for every knot
HEADWIND (refer to PERF-07-3 for
wind component conversions)

Landing Speed Correction: Increase distance by 11% for every
10 knots above V_{REF}
(maximum correction is +10 KIAS)

If the landing field length on a dry runway is greater than the corrected landing distance on a wet grooved runway, use the landing field length.

Shaded area indicates landing data above maximum landing weight for steep approach operations.

WT LB	V_{REF} V_{AC} V_{FTO}	UNCORRECTED LANDING DISTANCE ON WET-GROOVED RUNWAY											
		TEMPERATURE – °C											
		-40	-10	0	10	15	20	25	30	35	40	45	46
28000	116												
	129	3240	3530	3630	3730	3780	3830	3880	3930	3970	4020	4070	4080
	145												
30000	118												
	129	3320	3630	3730	3830	3880	3930	3980	4030	4080	4130	4180	4190
	145												
32000	122												
	129	3470	3790	3900	4010	4060	4110	4170	4220	4270	4320	4380	4390
	145												
32500	123												
	129	3500	3830	3940	4050	4100	4160	4210	4260	4320	4370	4430	4440
	146												
34000	126												
	129	3610	3950	4060	4180	4240	4290	4350	4400	4460	4520	4570	4580
	149												
35000	128												
	129	3680	4030	4150	4260	4320	4380	4440	4500	4550	4610	4670	4680
	152												

QRH_WETGROOVED_SAL_DATA2K_F45_IMP_CL650_FAA_26JAN17

QR1_DX_042

BOMBARDIER CHALLENGER 605	<i>SUPP-02-22</i>
	<i>REV 49, Nov 19/18</i>

THIS PAGE INTENTIONALLY LEFT BLANK

TRAINING PURPOSES ONLY

<i>QUICK REFERENCE HANDBOOK</i> <i>PSP 605-15</i>	<i>STEEP APPROACH</i>
--	------------------------------

CONTAMINATED RUNWAY CORRECTIONS**TAKE-OFF CORRECTIONS – WET RUNWAY**

V ₁ DRY	110	115	120	125	130	135	140	145	150	155	160
V ₁ WET	113	113	113	117	122	127	133	138	146	152	158
Distance	1.22	1.22	1.07	1.07	1.07	1.07	1.07	1.07	1.07	1.07	1.07

DISPATCH WITH ONE THRUST REVERSER INOPERATIVE
 FOR V₁ < 115 KIAS, Δ Distance = 660 ft and Δ V₁ = 0 KIAS
 FOR V₁ ≥ 115 KIAS, Δ Distance = 660 ft and Δ V₁ = -2.0 KIAS

TAKE-OFF CORRECTIONS – 0.125 IN. WATER OR EQUIVALENT

V ₁ DRY	110	115	120	125	130	135	140	145	150	155	160
V ₁ 0.125IN	113	113	113	114	119	124	130	136	142	148	155
Distance	1.58	1.58	1.58	1.38	1.38	1.38	1.38	1.38	1.38	1.38	1.38

EQUIVALENT: 0.125 IN SLUSH, 0.25 IN WET SNOW, 0.60 IN DRY SNOW

DISPATCH WITH ONE THRUST REVERSER INOPERATIVE
 FOR V₁ < 117 KIAS, Δ Distance = 2300 ft and Δ V₁ = 0 KIAS
 FOR V₁ ≥ 117 KIAS, Δ Distance = 1970 ft and Δ V₁ = -6.0 KIAS

TAKE-OFF CORRECTIONS – 0.25 IN. WATER OR EQUIVALENT

V ₁ DRY	110	115	120	125	130	135	140	145	150	155	160
V ₁ 0.25IN	110	114	118	122	127	132	136	141	146	151	156
Distance	1.56	1.56	1.56	1.56	1.56	1.56	1.56	1.56	1.56	1.52	1.48

EQUIVALENT: 0.25 IN SLUSH, 0.50 IN WET SNOW, 1.20 IN DRY SNOW

DISPATCH WITH ONE THRUST REVERSER INOPERATIVE
 FOR V₁ < 115 KIAS, Δ Distance = 1640 ft and Δ V₁ = 0 KIAS
 FOR V₁ ≥ 115 KIAS, Δ Distance = 1970 ft and Δ V₁ = -3.0 KIAS

TAKE-OFF CORRECTIONS – RUNWAY COVERED WITH ICE

V ₁ DRY	110	115	120	125	130	135	140	145	150	155	160
V ₁ ICE	113	113	111	111	111	111	111	119	129	140	151
Distance	2.05	2.05	1.92	1.78	1.64	1.50	1.50	1.50	1.50	1.50	1.50

DO NOT DISPATCH WITH ONE THRUST REVERSER INOPERATIVE

TAKE-OFF CORRECTIONS – RUNWAY COVERED BY COMPACTED SNOW

V ₁ DRY	110	115	120	125	130	135	140	145	150	155	160
V ₁ SNOW	113	113	110	114	119	125	130	136	143	150	157
Distance	1.32	1.32	1.12	1.12	1.12	1.12	1.12	1.12	1.12	1.12	1.12

DISPATCH WITH ONE THRUST REVERSER INOPERATIVE
 FOR V₁ < 116 KIAS, Δ Distance = 980 ft and Δ V₁ = 0 KIAS
 FOR V₁ ≥ 116 KIAS, Δ Distance = 980 ft and Δ V₁ = -4.0 KIAS

CONTAMINATED RUNWAY CORRECTIONS

LANDING CORRECTIONS

CONTAMINANT	TWO THRUST REVERSERS	ONE THRUST REVERSER
ICE	2.30	2.90
COMPACTED SNOW	1.54	1.64
LOOSE SNOW	1.82	2.06
SLUSH STANDING WATER	1.92	2.24

TRAINING PURPOSES ONLY

OPERATION IN VOLCANIC ASH

The best course of action to take is avoidance. However, volcanic ash/dust clouds may sometimes extend for hundreds of miles and an encounter could be unavoidable. Volcanic ash/dust can cause engine malfunctions and the need to exit the area as quickly as possible cannot be overemphasized.

If an inadvertent encounter is experienced, the following procedures are recommended:

If altitude permits:

- (1) Thrust levers IDLE
 - (2) COWL ANTI-ICE ON
 - (3) WING ANTI-ICE NORM
 - (4) ITT MONITOR
- to ensure that limits are not exceeded.

If ITT continues to increase:

Affected engine:

- (5) In-Flight Engine Failure/Shutdown ACCOMPLISH
- (See Page ABNORM 1–3)

NOTE

- 1. If it becomes necessary to shutdown an engine to prevent exceeding ITT limits, restart engine once it has cooled down.
- 2. If the engine fails to start, repeated attempts within starter limits should be made immediately.
- 3. A successful start may not be possible until the airplane is clear of the volcanic ash/dust, and the airspeed and altitude is within the airstart envelope. The engines can be very slow to accelerate to idle at high altitude, and this could be interpreted as a failure to start, or as an engine malfunction.

After exiting area of volcanic ash/dust cloud and engine(s) restarted:

- (6) Affected systems RESTORE
- (7) ATC NOTIFY

BOMBARDIER CHALLENGER 605	SUPP-04-2
	<i>REV 15, Jun 28/10</i>

THIS PAGE INTENTIONALLY LEFT BLANK

TRAINING PURPOSES ONLY

QUICK REFERENCE HANDBOOK <i>PSP 605-15</i>	VOLCANIC ASH
--	---------------------

BOMBARDIER CHALLENGER 605	SUPP-05-1
	REV 27, Jan 06/14

MAXIMUM ALLOWABLE TAKE-OFF WEIGHT

This supplement provides expanded brake energy and tire speed data to use for the derivation of the maximum allowable take-off weight.

The additional information allows the airplane to be operated to its fullest capabilities in situations where the resulting take-off weight is either limited by brake energy or maximum tire speed.

NOTE

A CHECK TAKEOFF PERF message can be expected to be posted on the FMS along with the weight limited by AFM PERFORMANCE, indicated in amber at higher weights contained in this supplement.

The remaining take-off performance (take-off speeds, take-off distance, take-off weight limited by climb requirements, maximum allowable brake temperature for take-off, and adjustments for extended second segment climb) contained in the AFM; PERFORMANCE – TAKE-OFF PERFORMANCE must be used.

Take-off Vspeeds (V_1 , V_R , V_2 and V_{FTO}) from the AFM must be manually entered and selected for view on the displays.

MAXIMUM TAKE-OFF WEIGHT LIMITED BY BRAKE ENERGY

Bleed Correction: Decrease by 176 lb with bleeds open and packs on

Anti-Ice Correction: Decrease by 221 lb with cowl anti-ice on
Decrease by 794 lb with cowl and wing anti-ice on

APR Correction: Decrease by 705 lb with APR off

Gradient Correction: Increase by 90 lb for every 1% DOWNHILL
Decrease by 180 lb for every 1% UPHILL

Wind Correction: Increase by 120 lb for every knot HEADWIND
Decrease by 400 lb for every knot TAILWIND
(refer to PERF-07-3 for wind component conversions)

Temp (°C)	Airport Pressure altitude (ft)							
	SL	2000	4000	6000	8000	10000	12000	14000
-40	55000	55000	55000	53412	50723	47851	45047	42524
-15	55000	55000	53676	51174	48402	45650	42979	40753
5	55000	54444	52171	49474	46771	44084	41670	39400
7	55000	54304	52020	49314	46620	43933	41525	39222
10	55000	54093	51785	49076	46393	43707	41259	38954
21	55000	53396	50921	48070	45278	42618	40281	37937
22	55000	53333	50842	47946	45161	42519	40186	37839
24	55000	53208	50573	47697	44927	42320	39991	
26	55000	53082	50299	47448	44693	42127	39797	
30	54798	52530	49752	46950	44228	41758		
31	54675	52391	49615	46826	44116			
34	54305	51974	49204	46457	43778			
38	53813	51418	48666	45978				
42	53320	50864	48161					
46	52811	50314						
50	52252							

QR1_DX_014

MAXIMUM TAKE-OFF WEIGHT LIMITED BY TIRE SPEED

APR Correction:
Wind Correction:

Decrease by 440 lb with APR off
Increase by 240 lb for every knot HEADWIND
Decrease by 750 lb for every knot TAILWIND
(refer to PERF-07-3 for wind component conversions)

Temp (°C)	Airport Pressure altitude (ft)					
	2000 and Below	4000	6000	8000	10000	12000
-40	55000	55000	55000	55000	54862	48480
-29	55000	55000	55000	55000	52335	45947
-25	55000	55000	55000	55000	51352	45100
-15	55000	55000	55000	55000	48977	43022
-5	55000	55000	55000	53115	46773	41071
5	55000	55000	55000	50976	44869	39370
7	55000	55000	55000	50543	44483	39091
10	55000	55000	55000	49899	43903	38715
21	55000	55000	53886	47677	42030	37387
22	55000	55000	53712	47496	41865	37271
24	55000	55000	53346	47134	41537	37042
26	55000	55000	52960	46772	41208	36814
30	55000	55000	52187	46058	40551	
31	55000	55000	51993	45889		
34	55000	55000	51411	45381		
38	55000	55000	50628			
42	55000	55000				
46	55000					

QR1_DX_015

BOMBARDIER CHALLENGER 605	<i>SUPP-05-4</i>
	<i>REV 27, Jan 06/14</i>

THIS PAGE INTENTIONALLY LEFT BLANK

TRAINING PURPOSES ONLY

<i>QUICK REFERENCE HANDBOOK</i> <i>PSP 605-15</i>	<i>EXTENDED MTOW</i>
--	-----------------------------

BOMBARDIER CHALLENGER 605	SUPP-06-1
	<i>REV 29, Jul 11/14</i>

AIRCRAFT CLASSIFICATION NUMBER (ACN)

An aircraft with an ACN equal to or less than the reported aerodrome pavement classification number (PCN) within the allowable tire inflation limit may operate at the aerodrome without restrictions.

RIGID PAVEMENT

Main tires H27 x 8.5-14, 16 pr with unloaded pressure of 177 psi

Weight (lb)	ACN			
	Ultra Low 20 / D	Low 40 / C	Medium 80 / B	High 150 / A
48,300	16.70	16.30	15.80	15.30
48,200	16.60	16.20	15.80	15.30
43,500	14.80	14.40	14.00	13.50
43,000	14.60	14.20	13.80	13.30
38,000	12.70	12.30	11.90	11.50
32,000	10.40	10.10	9.80	9.40
26,000	8.20	8.00	7.70	7.40

FLEXIBLE PAVEMENT

Main tires H27 x 8.5-14, 16 pr with unloaded pressure of 177 psi

Weight (lb)	ACN			
	Ultra Low 3 / D	Low 6 / C	Medium 10 / B	High 15 / A
48,300	14.35	13.04	11.97	11.64
48,200	14.32	13.01	11.94	11.62
43,500	12.74	11.54	10.62	10.30
43,000	12.57	11.39	10.48	10.20
38,000	10.91	9.85	9.08	8.86
32,000	8.95	8.05	7.43	7.30
26,000	7.03	6.31	5.86	5.79

THIS PAGE INTENTIONALLY LEFT BLANK

TRAINING PURPOSES ONLY

BOMBARDIER CHALLENGER 605	SUPP-07-1
	<i>REV 49, Nov 19/18</i>

WET GROOVED RUNWAY

This supplement provides landing speeds and distances on wet grooved runways.

For steep approaches on wet grooved runways refer to STEEP APPROACH (See Page SUPP-02-1).

TRAINING PURPOSES ONLY

BOMBARDIER CHALLENGER 605	SUPP-07-2
	REV 49, Nov 19/18

WET GROOVED RUNWAY

Landing Speeds and Distances

ALTITUDE - SEA LEVEL

- V_{REF} = Speed at 50 ft screen height – KIAS
- V_{AC} = Approach climb speed (Flap 20°) – KIAS
- V_{FTO} = Final segment speed (Flap 0°) – KIAS

Uncorrected distances presented are based on zero wind and zero runway gradient conditions.

Corrected Landing Distance

- Gradient Correction:
 - For up to 1% DOWNHILL, increase distance by 20%
 - For between 1 and 1.49% DOWNHILL, increase distance by 35%
 - For between 1.5 and 2% DOWNHILL, increase distance by 50%
 - Decrease distance by 10% for every 1% UPHILL
- Wind Correction:
 - Increase distance by 140 ft for every knot TAILWIND
 - Decrease distance by 30 ft for every knot HEADWIND
 - (refer to PERF-07-3 for wind component conversions)
- Landing Speed Correction:
 - Increase distance by 12% for every 10 knots above V_{REF}
 - (maximum correction is +10 KIAS)

If the landing field length on a dry runway is greater than the corrected landing distance on a wet grooved runway, use the landing field length.

Shaded area indicates landing data above maximum landing weight.

WET GROOVED RUNWAY

Landing Speeds and Distances (Cont'd)

ALTITUDE - SEA LEVEL (CONT'D)

WT LB	V _{REF} V _{AC} V _{FTO}	UNCORRECTED LANDING DISTANCE ON WET-GROOVED RUNWAY											
		TEMPERATURE – °C											
		-40	-10	0	10	15	20	25	30	35	40	45	50
28000	116												
	129	3470	3830	3950	4070	4130	4180	4240	4300	4360	4410	4470	4530
	145												
30000	117												
	129	3530	3890	4010	4130	4190	4250	4310	4370	4430	4490	4540	4600
	145												
32000	121												
	129	3700	4090	4210	4340	4400	4460	4530	4590	4650	4710	4770	4830
	145												
34000	125												
	129	3880	4280	4410	4540	4610	4680	4740	4810	4870	4940	5000	5060
	149												
36000	128												
	129	4050	4470	4610	4750	4820	4890	4950	5020	5090	5160	5220	5290
	154												
38000	132												
	132	4220	4660	4810	4950	5020	5090	5170	5240	5310	5380	5450	5520
	158												
40000	136												
	136	4420	4880	5040	5190	5270	5340	5420	5490	5570	5640	5710	5790
	162												
42000	139												
	139	4590	5070	5230	5390	5470	5550	5630	5710	5780	5860	5940	6010
	166												
44000	143												
	143	4760	5260	5430	5590	5680	5760	5840	5920	6000	6080	6160	6240
	170												
46000	146												
	146	4910	5430	5600	5770	5860	5940	6030	6110	6190	6280	6360	6440
	173												

QRH_WETGROOVED_DATA_SL_F45_IMP_CL604_605_650_07FEB17

QR1_DXWGR_002

BOMBARDIER CHALLENGER 605	SUPP-07-4
	REV 49, Nov 19/18

WET GROOVED RUNWAY

Landing Speeds and Distances (Cont'd)

ALTITUDE - 500 FEET

- V_{REF} = Speed at 50 ft screen height – KIAS
- V_{AC} = Approach climb speed (Flap 20°) – KIAS
- V_{FTO} = Final segment speed (Flap 0°) – KIAS

Uncorrected distances presented are based on zero wind and zero runway gradient conditions.

Corrected Landing Distance

- Gradient Correction:
 - For up to 1% DOWNHILL, increase distance by 20%
 - For between 1 and 1.49% DOWNHILL, increase distance by 35%
 - For between 1.5 and 2% DOWNHILL, increase distance by 50%
 - Decrease distance by 10% for every 1% UPHILL
- Wind Correction:
 - Increase distance by 140 ft for every knot TAILWIND
 - Decrease distance by 30 ft for every knot HEADWIND
 - (refer to PERF-07-3 for wind component conversions)
- Landing Speed Correction: Increase distance by 12% for every 10 knots above V_{REF} (maximum correction is +10 KIAS)

If the landing field length on a dry runway is greater than the corrected landing distance on a wet grooved runway, use the landing field length.

Shaded area indicates landing data above maximum landing weight.

WET GROOVED RUNWAY**Landing Speeds and Distances (Cont'd)****ALTITUDE - 500 FEET (CONT'D)**

WT LB	V _{REF} V _{AC} V _{FTO}	UNCORRECTED LANDING DISTANCE ON WET-GROOVED RUNWAY											
		TEMPERATURE – °C											
		-40	-10	0	10	15	20	25	30	35	40	45	49
28000	116												
	129	3520	3880	4000	4120	4180	4240	4300	4360	4420	4470	4530	4580
	145												
30000	117												
	129	3580	3950	4070	4190	4250	4310	4370	4430	4490	4550	4610	4650
	145												
32000	121												
	129	3760	4140	4270	4400	4460	4530	4590	4650	4720	4780	4840	4890
	145												
34000	125												
	129	3930	4340	4470	4610	4680	4740	4810	4870	4940	5000	5070	5120
	149												
36000	128												
	129	4110	4530	4670	4820	4890	4960	5020	5090	5160	5230	5300	5350
	154												
38000	132												
	132	4280	4730	4870	5020	5090	5170	5240	5310	5380	5460	5530	5580
	158												
40000	136												
	136	4490	4950	5110	5260	5340	5420	5490	5570	5650	5720	5800	5860
	162												
42000	139												
	139	4660	5150	5310	5470	5550	5630	5710	5790	5870	5950	6020	6090
	166												
44000	143												
	143	4830	5340	5510	5670	5750	5840	5920	6000	6090	6170	6250	6310
	170												
46000	146												
	146	4990	5510	5680	5860	5940	6030	6110	6200	6280	6370	6450	6520
	173												

QRH_WETGROOVED_DATA_0.5K_F45_IMP_CL604_605_650_07FEB17

QR1_DXWGR_001

BOMBARDIER CHALLENGER 605	SUPP-07-6
	REV 49, Nov 19/18

WET GROOVED RUNWAY

Landing Speeds and Distances (Cont'd)

ALTITUDE - 1,000 FEET

- V_{REF} = Speed at 50 ft screen height – KIAS
- V_{AC} = Approach climb speed (Flap 20°) – KIAS
- V_{FTO} = Final segment speed (Flap 0°) – KIAS

Uncorrected distances presented are based on zero wind and zero runway gradient conditions.

Corrected Landing Distance

- Gradient Correction:
 - For up to 1% DOWNHILL, increase distance by 20%
 - For between 1 and 1.49% DOWNHILL, increase distance by 35%
 - For between 1.5 and 2% DOWNHILL, increase distance by 50%
 - Decrease distance by 10% for every 1% UPHILL
- Wind Correction:
 - Increase distance by 140 ft for every knot TAILWIND
 - Decrease distance by 30 ft for every knot HEADWIND
 - (refer to PERF-07-3 for wind component conversions)
- Landing Speed Correction: Increase distance by 12% for every 10 knots above V_{REF} (maximum correction is +10 KIAS)

If the landing field length on a dry runway is greater than the corrected landing distance on a wet grooved runway, use the landing field length.

Shaded area indicates landing data above maximum landing weight.

WET GROOVED RUNWAY

Landing Speeds and Distances (Cont'd)

ALTITUDE - 1,000 FEET (CONT'D)

WT LB	V _{REF} V _{AC} V _{FTO}	UNCORRECTED LANDING DISTANCE ON WET-GROOVED RUNWAY											
		TEMPERATURE – °C											
		–40	–10	0	10	15	20	25	30	35	40	45	48
28000	116												
	129	3570	3930	4060	4180	4240	4300	4360	4420	4480	4540	4590	4630
	145												
30000	118												
	129	3640	4020	4140	4270	4330	4390	4450	4510	4570	4630	4690	4730
	145												
32000	121												
	129	3820	4220	4350	4480	4550	4610	4670	4740	4800	4870	4930	4970
	145												
34000	125												
	129	4000	4420	4560	4690	4760	4830	4900	4960	5030	5100	5160	5200
	149												
36000	129												
	129	4180	4620	4760	4900	4980	5050	5120	5190	5260	5330	5400	5440
	154												
38000	132												
	133	4360	4810	4960	5110	5190	5260	5340	5410	5480	5560	5630	5670
	158												
40000	136												
	137	4570	5050	5210	5360	5440	5520	5600	5680	5750	5830	5910	5950
	162												
42000	140												
	140	4750	5240	5410	5570	5650	5740	5820	5900	5980	6060	6140	6190
	166												
44000	143												
	143	4920	5440	5610	5780	5870	5950	6030	6120	6200	6290	6370	6420
	170												
46000	146												
	146	5080	5610	5790	5970	6060	6140	6230	6320	6400	6490	6580	6630
	173												

QRH_WETGROOVED_DATA1K_F45_IMP_CL604_605_650_07FEB17

QR1_DXWGR_003

BOMBARDIER CHALLENGER 605	SUPP-07-8
	REV 49, Nov 19/18

WET GROOVED RUNWAY

Landing Speeds and Distances (Cont'd)

ALTITUDE - 2,000 FEET

- V_{REF} = Speed at 50 ft screen height – KIAS
 V_{AC} = Approach climb speed (Flap 20°) – KIAS
 V_{FTO} = Final segment speed (Flap 0°) – KIAS

Uncorrected distances presented are based on zero wind and zero runway gradient conditions.

Corrected Landing Distance

- Gradient Correction:

For up to 1% DOWNHILL, increase distance by 20%
For between 1 and 1.49% DOWNHILL, increase distance by 35%
For between 1.5 and 2% DOWNHILL, increase distance by 50%
Decrease distance by 10% for every 1% UPHILL
- Wind Correction:

Increase distance by 140 ft for every knot TAILWIND
Decrease distance by 30 ft for every knot HEADWIND
(refer to PERF-07-3 for wind component conversions)
- Landing Speed Correction:

Increase distance by 12% for every 10 knots above V_{REF}
(maximum correction is +10 KIAS)

If the landing field length on a dry runway is greater than the corrected landing distance on a wet grooved runway, use the landing field length.

Shaded area indicates landing data above maximum landing weight.

WET GROOVED RUNWAY

Landing Speeds and Distances (Cont'd)

ALTITUDE - 2,000 FEET (CONT'D)

WT LB	V _{REF} V _{AC} V _{FTO}	UNCORRECTED LANDING DISTANCE ON WET-GROOVED RUNWAY											
		TEMPERATURE – °C											
		–40	–10	0	10	15	20	25	30	35	40	45	46
28000	116												
	129	3670	4040	4170	4290	4360	4420	4480	4540	4600	4660	4720	4740
	145												
30000	118												
	129	3780	4170	4300	4430	4490	4550	4620	4680	4740	4810	4870	4880
	145												
32000	122												
	129	3970	4380	4510	4650	4720	4780	4850	4920	4980	5050	5120	5130
	145												
34000	126												
	129	4150	4580	4730	4870	4940	5010	5080	5150	5220	5290	5360	5370
	149												
36000	130												
	130	4340	4790	4940	5090	5170	5240	5310	5390	5460	5530	5600	5620
	154												
38000	133												
	133	4520	5000	5150	5310	5390	5460	5540	5620	5690	5770	5850	5860
	158												
40000	137												
	138	4740	5240	5400	5570	5650	5730	5810	5890	5970	6050	6130	6150
	162												
42000	141												
	141	4930	5440	5620	5790	5870	5960	6040	6120	6210	6290	6380	6390
	166												
44000	144												
	144	5110	5650	5830	6000	6090	6180	6270	6360	6440	6530	6620	6630
	170												
46000	147												
	147	5270	5830	6010	6200	6290	6380	6470	6560	6650	6740	6830	6850
	173												

QRH_WETGROOVED_DATA2K_F45_IMP_CL604_605_650_07FEB17

QR1_DXWGR_004

BOMBARDIER CHALLENGER 605	SUPP-07-10
	REV 49, Nov 19/18

WET GROOVED RUNWAY

Landing Speeds and Distances (Cont'd)

ALTITUDE - 4,000 FEET

- V_{REF} = Speed at 50 ft screen height – KIAS
- V_{AC} = Approach climb speed (Flap 20°) – KIAS
- V_{FTO} = Final segment speed (Flap 0°) – KIAS

Uncorrected distances presented are based on zero wind and zero runway gradient conditions.

Corrected Landing Distance

- Gradient Correction:
 - For up to 1% DOWNHILL, increase distance by 20%
 - For between 1 and 1.49% DOWNHILL, increase distance by 35%
 - For between 1.5 and 2% DOWNHILL, increase distance by 50%
 - Decrease distance by 10% for every 1% UPHILL
- Wind Correction:
 - Increase distance by 140 ft for every knot TAILWIND
 - Decrease distance by 30 ft for every knot HEADWIND
 - (refer to PERF-07-3 for wind component conversions)
- Landing Speed Correction:
 - Increase distance by 12% for every 10 knots above V_{REF}
 - (maximum correction is +10 KIAS)

If the landing field length on a dry runway is greater than the corrected landing distance on a wet grooved runway, use the landing field length.

Shaded area indicates landing data above maximum landing weight.

WET GROOVED RUNWAY

Landing Speeds and Distances (Cont'd)

ALTITUDE - 4,000 FEET (CONT'D)

WT LB	V _{REF} V _{AC} V _{FTO}	UNCORRECTED LANDING DISTANCE ON WET-GROOVED RUNWAY											
		TEMPERATURE – °C											
		-40	-10	0	10	15	20	25	30	35	40	42	
28000	116												
	129	3870	4280	4410	4540	4610	4670	4740	4800	4870	4930	4960	
	145												
30000	120												
	129	4070	4490	4630	4770	4840	4910	4980	5040	5110	5180	5210	
	145												
32000	124												
	129	4270	4710	4860	5010	5080	5160	5230	5300	5370	5440	5470	
	147												
34000	127												
	129	4470	4940	5100	5250	5330	5410	5480	5560	5630	5710	5740	
	152												
36000	131												
	132	4680	5170	5330	5490	5570	5650	5730	5810	5890	5970	6000	
	156												
38000	135												
	135	4880	5390	5560	5730	5810	5900	5980	6060	6150	6230	6260	
	161												
40000	139												
	139	5120	5650	5830	6010	6100	6190	6280	6360	6450	6540	6570	
	164												
42000	142												
	143	5320	5880	6060	6250	6340	6430	6520	6620	6710	6800	6830	
	168												
44000	146												
	146	5510	6100	6290	6480	6580	6680	6770	6870	6960	7060	7090	
	172												
46000	149												
	149	5690	6300	6500	6700	6800	6890	6990	7090	7190	7290	7330	
	176												

QR1_DXWGR_005

QRH_WETGROOVED_DATA4K_F45_IMP_CLB04_605_650_07FEB17

BOMBARDIER CHALLENGER 605	SUPP-07-12
	REV 49, Nov 19/18

WET GROOVED RUNWAY

Landing Speeds and Distances (Cont'd)

ALTITUDE - 6,000 FEET

- V_{REF} = Speed at 50 ft screen height – KIAS

V_{AC} = Approach climb speed (Flap 20°) – KIAS

V_{FTO} = Final segment speed (Flap 0°) – KIAS

Uncorrected distances presented are based on zero wind and zero runway gradient conditions.

Corrected Landing Distance

- Gradient Correction:

For up to 1% DOWNHILL, increase distance by 20%

For between 1 and 1.49% DOWNHILL, increase distance by 35%

For between 1.5 and 2% DOWNHILL, increase distance by 50%

Decrease distance by 10% for every 1% UPHILL

Wind Correction:

Increase distance by 140 ft for every knot TAILWIND

Decrease distance by 30 ft for every knot HEADWIND

(refer to PERF-07-3 for wind component conversions)

Landing Speed Correction:

Increase distance by 12% for every 10 knots above V_{REF}
(maximum correction is +10 KIAS)

If the landing field length on a dry runway is greater than the corrected landing distance on a wet grooved runway, use the landing field length.

Shaded area indicates landing data above maximum landing weight.

WET GROOVED RUNWAY

Landing Speeds and Distances (Cont'd)

ALTITUDE - 6,000 FEET (CONT'D)

WT LB	V _{REF} V _{AC} V _{FTO}	UNCORRECTED LANDING DISTANCE ON WET-GROOVED RUNWAY									
		TEMPERATURE – °C									
		-40	-10	0	10	15	20	25	30	35	38
28000	117										
	129	4180	4620	4760	4900	4970	5040	5110	5180	5250	5290
	145										
30000	121										
	129	4410	4860	5020	5170	5240	5320	5390	5460	5540	5580
	145										
32000	125										
	129	4630	5110	5270	5430	5510	5590	5670	5740	5820	5870
	150										
34000	129										
	130	4850	5360	5530	5690	5780	5860	5940	6020	6110	6150
	154										
36000	133										
	134	5070	5600	5780	5950	6040	6130	6210	6300	6390	6440
	159										
38000	136										
	137	5290	5850	6030	6210	6300	6390	6480	6580	6670	6720
	163										
40000	141										
	141	5550	6130	6330	6520	6620	6710	6810	6900	7000	7050
	167										
42000	144										
	145	5770	6380	6580	6780	6880	6980	7080	7180	7270	7330
	171										
44000	148										
	148	5980	6620	6830	7030	7140	7240	7350	7450	7550	7610
	175										
46000	151										
	151	6180	6830	7050	7270	7370	7480	7590	7690	7800	7860
	179										

QRH_WETGROOVED_DATA6K_F45_IMP_CL604_605_650_07FEB17

QR1_DXWGR_006

BOMBARDIER CHALLENGER 605	SUPP-07-14
	<i>REV 49, Nov 19/18</i>

WET GROOVED RUNWAY

Landing Speeds and Distances (Cont'd)

ALTITUDE - 8,000 FEET

V_{REF} = Speed at 50 ft screen height – KIAS

V_{AC} = Approach climb speed (Flap 20°) – KIAS

V_{FTO} = Final segment speed (Flap 0°) – KIAS

Uncorrected distances presented are based on zero wind and zero runway gradient conditions.

Corrected Landing Distance

Gradient Correction: For up to 1% DOWNHILL, increase distance by 20%
 For between 1 and 1.49% DOWNHILL, increase distance by 35%
 For between 1.5 and 2% DOWNHILL, increase distance by 50%
 Decrease distance by 10% for every 1% UPHILL

Wind Correction: Increase distance by 140 ft for every knot TAILWIND
 Decrease distance by 30 ft for every knot HEADWIND
 (refer to PERF-07-3 for wind component conversions)

Landing Speed Correction: Increase distance by 12% for every 10 knots above V_{REF}
 (maximum correction is +10 KIAS)

If the landing field length on a dry runway is greater than the corrected landing distance on a wet grooved runway, use the landing field length.

Shaded area indicates landing data above maximum landing weight.

WET GROOVED RUNWAY

Landing Speeds and Distances (Cont'd)

ALTITUDE - 8,000 FEET (CONT'D)

WT LB	V _{REF} V _{AC} V _{FTO}	UNCORRECTED LANDING DISTANCE ON WET-GROOVED RUNWAY									
		TEMPERATURE – °C									
		–40	–10	0	10	15	20	25	30	34	
28000	119										
	129	4560	5020	5170	5320	5400	5470	5550	5630	5690	
	145										
30000	123										
	129	4800	5290	5450	5610	5690	5770	5860	5940	6000	
	148										
32000	127										
	129	5040	5560	5730	5900	5980	6070	6160	6240	6310	
	152										
34000	131										
	132	5280	5830	6010	6190	6270	6360	6460	6550	6620	
	157										
36000	135										
	136	5520	6090	6280	6470	6560	6660	6750	6850	6920	
	161										
38000	138										
	139	5760	6360	6550	6750	6850	6950	7050	7150	7230	
	165										
40000	143										
	144	6040	6670	6880	7090	7190	7290	7400	7500	7590	
	169										
42000	146										
	147	6280	6940	7150	7370	7480	7580	7690	7800	7890	
	174										
44000	149										
	150	6510	7200	7420	7650	7760	7870	7990	8100	8190	
	178										
46000	152										
	153	6730	7430	7670	7900	8020	8130	8250	8370	8460	
	182										

QRH_WETGROOVED_DATA8K_F45_IMP_CL604_605_650_07FEB17

QR1_DXWGR_007

BOMBARDIER CHALLENGER 605	SUPP-07-16
	REV 49, Nov 19/18

WET GROOVED RUNWAY

Landing Speeds and Distances (Cont'd)

ALTITUDE - 10,000 FEET

- V_{REF} = Speed at 50 ft screen height – KIAS
- V_{AC} = Approach climb speed (Flap 20°) – KIAS
- V_{FTO} = Final segment speed (Flap 0°) – KIAS

Uncorrected distances presented are based on zero wind and zero runway gradient conditions.

Corrected Landing Distance

- Gradient Correction:
 - For up to 1% DOWNHILL, increase distance by 20%
 - For between 1 and 1.49% DOWNHILL, increase distance by 35%
 - For between 1.5 and 2% DOWNHILL, increase distance by 50%
 - Decrease distance by 10% for every 1% UPHILL
- Wind Correction:
 - Increase distance by 140 ft for every knot TAILWIND
 - Decrease distance by 30 ft for every knot HEADWIND
 - (refer to PERF-07-3 for wind component conversions)
- Landing Speed Correction:
 - Increase distance by 12% for every 10 knots above V_{REF}
 - (maximum correction is +10 KIAS)

If the landing field length on a dry runway is greater than the corrected landing distance on a wet grooved runway, use the landing field length.

Shaded area indicates landing data above maximum landing weight.

WET GROOVED RUNWAY

Landing Speeds and Distances (Cont'd)

ALTITUDE - 10,000 FEET (CONT'D)

WT LB	V _{REF} V _{AC} V _{FTO}	UNCORRECTED LANDING DISTANCE ON WET-GROOVED RUNWAY									
		TEMPERATURE – °C									
		-40	-10	0	10	15	20	25	30		
28000	120										
	129	4990	5490	5650	5820	5900	5990	6070	6150		
	145										
30000	124										
	129	5260	5780	5950	6130	6220	6310	6400	6490		
	150										
32000	129										
	130	5520	6070	6260	6440	6540	6630	6730	6820		
	155										
34000	133										
	134	5780	6370	6560	6760	6850	6960	7050	7150		
	159										
36000	136										
	138	6040	6660	6860	7070	7170	7280	7380	7480		
	164										
38000	140										
	141	6300	6940	7160	7370	7480	7590	7700	7810		
	168										
40000	144										
	146	6610	7290	7510	7740	7850	7970	8080	8200		
	173										
42000	148										
	149	6870	7570	7810	8050	8170	8290	8410	8520		
	177										
44000	151										
	152	7120	7860	8100	8350	8480	8600	8730	8850		
	181										
46000	154										
	155	7350	8120	8370	8630	8780	8890	9010	9140		
	185										

QRH_WETGROOVED_DATA10K_F45_IMP_CL604_605_650_07FEB17

QR1_DXWGR_008

BOMBARDIER CHALLENGER 605	SUPP-07-18
	REV 49, Nov 19/18

WET GROOVED RUNWAY

Landing Speeds and Distances (Cont'd)

ALTITUDE - 12,000 FEET

V_{REF} = Speed at 50 ft screen height – KIAS

V_{AC} = Approach climb speed (Flap 20°) – KIAS

V_{FTO} = Final segment speed (Flap 0°) – KIAS

Uncorrected distances presented are based on zero wind and zero runway gradient conditions.

Corrected Landing Distance

Gradient Correction: For up to 1% DOWNHILL, increase distance by 20%
 For between 1 and 1.49% DOWNHILL, increase distance by 35%
 For between 1.5 and 2% DOWNHILL, increase distance by 50%
 Decrease distance by 10% for every 1% UPHILL

Wind Correction: Increase distance by 140 ft for every knot TAILWIND
 Decrease distance by 30 ft for every knot HEADWIND
 (refer to PERF-07-3 for wind component conversions)

Landing Speed Correction: Increase distance by 12% for every 10 knots above V_{REF}
 (maximum correction is +10 KIAS)

If the landing field length on a dry runway is greater than the corrected landing distance on a wet grooved runway, use the landing field length.

Shaded area indicates landing data above maximum landing weight.

WET GROOVED RUNWAY

Landing Speeds and Distances (Cont'd)

ALTITUDE - 12,000 FEET (CONT'D)

WT LB	V _{REF} V _{AC} V _{FTO}	UNCORRECTED LANDING DISTANCE ON WET-GROOVED RUNWAY							
		TEMPERATURE – °C							
		-40	-10	0	10	15	20	21	
28000	122								
	129	5500	6030	6200	6380	6470	6560	6580	
	147								
30000	126								
	129	5790	6350	6540	6730	6820	6920	6940	
	152								
32000	130								
	132	6080	6670	6870	7070	7170	7270	7290	
	157								
34000	134								
	136	6360	6990	7200	7410	7520	7620	7640	
	162								
36000	138								
	140	6650	7300	7520	7750	7860	7970	7990	
	167								
38000	142								
	143	6930	7620	7850	8080	8200	8320	8340	
	171								
40000	146								
	148	7260	7990	8240	8480	8610	8730	8750	
	176								
42000	149								
	151	7540	8310	8560	8820	8950	9070	9100	
	180								
44000	153								
	155	7820	8620	8890	9150	9290	9420	9450	
	185								
46000	156								
	158	8080	8900	9180	9450	9590	9730	9760	
	189								

QRH_WETGROOVED_DATA12K_F45_IMP_CL604_605_650_07FEB17

QR1_DXWGR_009

BOMBARDIER CHALLENGER 605	SUPP-07-20
	REV 49, Nov 19/18

WET GROOVED RUNWAY

Landing Speeds and Distances (Cont'd)

ALTITUDE - 14,000 FEET

- V_{REF} = Speed at 50 ft screen height – KIAS
- V_{AC} = Approach climb speed (Flap 20°) – KIAS
- V_{FTO} = Final segment speed (Flap 0°) – KIAS

Uncorrected distances presented are based on zero wind and zero runway gradient conditions.

Corrected Landing Distance

- Gradient Correction:
 - For up to 1% DOWNHILL, increase distance by 20%
 - For between 1 and 1.49% DOWNHILL, increase distance by 35%
 - For between 1.5 and 2% DOWNHILL, increase distance by 50%
 - Decrease distance by 10% for every 1% UPHILL
- Wind Correction:
 - Increase distance by 140 ft for every knot TAILWIND
 - Decrease distance by 30 ft for every knot HEADWIND
 - (refer to PERF-07-3 for wind component conversions)
- Landing Speed Correction: Increase distance by 12% for every 10 knots above V_{REF} (maximum correction is +10 KIAS)

If the landing field length on a dry runway is greater than the corrected landing distance on a wet grooved runway, use the landing field length.

Shaded area indicates landing data above maximum landing weight.

WET GROOVED RUNWAY

Landing Speeds and Distances (Cont'd)

ALTITUDE - 14,000 FEET (CONT'D)

WT LB	V _{REF} V _{AC} V _{FTO}	UNCORRECTED LANDING DISTANCE ON WET-GROOVED RUNWAY									
		TEMPERATURE – °C									
		-40	-10	0	10	15	17				
28000	123										
	129	6040	6620	6800	6990	7080	7120				
	150										
30000	128										
	129	6360	6960	7160	7360	7460	7510				
	155										
32000	132										
	133	6670	7310	7520	7730	7840	7880				
	160										
34000	135										
	137	6970	7660	7880	8100	8220	8260				
	165										
36000	139										
	141	7280	8000	8240	8470	8590	8640				
	170										
38000	143										
	145	7590	8340	8590	8830	8960	9010				
	175										
40000	147										
	149	7950	8750	9010	9270	9400	9460				
	180										
42000	151										
	153	8260	9090	9360	9630	9770	9830				
	184										
44000	154										
	157	8560	9430	9710	10000	10140	10200				
	188										
46000	157										
	160	8830	9730	10030	10330	10480	10540				
	193										

QRH_WETGROOVED_DATA14K_F45_IMP_CL604_605_650_07FEB17

QR1_DXWGR_010

BOMBARDIER CHALLENGER 605	<i>SUPP-07-22</i>
	<i>REV 49, Nov 19/18</i>

THIS PAGE INTENTIONALLY LEFT BLANK

TRAINING PURPOSES ONLY

<i>QUICK REFERENCE HANDBOOK</i> <i>PSP 605-15</i>	<i>WET GROOVED RUNWAY</i>
--	----------------------------------