



Caution

This bag contains

MOISTURE-SENSITIVE DEVICES

If blank. See adjacent bar code label

LEVEL

5

1. Calculated shelf life in sealed bag: **12 months at <40°C and <90% relative humidity(RH)**
If blank. See adjacent bar code label
2. Peak package body temperature: **N/A °C** If blank. See adjacent bar code label
3. After bag is opened, devices that will be subjected to reflow solder or other high temperature process must be
 - a) Mounted within: **48** hours of factory conditions **≤30°C/60% RH,or**
 - b) Stored per J-STD-033 If blank. See adjacent bar code label
4. Devices require bake, before mounting, if:
 - a) Humidity indicator Card reads>10% for level 2a-5a devices or >60% for level 2 devices when read at 23+ 5°C
 - b) 3a or 3b are not met
- 5.If baking is required, refer to IPC/JEDEC J-STD-033 for bake procedure

Bag Seal Date: 14/02/2024

If blank. See adjacent bar code label

Note: Level and body temperature defined by IPC/JEDEC J-STD-020

HHPN : CAP47-5177



BU Code : Polight-DPBU

Min PKG no : L3K7194550AB



Version no.: BA-C



C P/N : 821-05104-01



Q'ty : 1080 Pcs.



Bare Flex D/C : 344



SMT D/C : 20240214



Expire date : 20240812



FJK name : RGPZ-469ML-0A



NSCM FCCLNSCN FCCL RoHS Halogen Free CFM