

Test Execution Report

EVEREST Demo E2E Tests

Donnerstag, 27. November 2025

Test Summary

5

Total Tests

<div></div> Passed:	1
<div></div> Failed:	4
<div></div> Broken:	0
<div></div> Skipped:	0

Test Details

Test Name	Suite	Status	Duration	0
Car Simulation mit AC Diode Fail und AC 3ph 16A, dann Pause/Resume Laden sollte gestartet sein - kW sollte > 0 sein: expected 0 to be above 0	Car Simulation und Pause/Resume Test	FAILED	34s	
Car Simulation mit AC RCD Error und Pause/Resume Timed out retrying after 10000ms: expected '<md-select-value#select_value_label_0.md-select-value>' to be 'visible' This element '<md-select-value#select_value_label_0.md-select-value>' is not visible because its content is being clipped by one of its parent elements, which has a CSS property of overflow: 'hidden', 'clip', 'scroll' or 'auto' See screenshots on next pages	Car Simulation und Pause/Resume Test	FAILED	12s	1
AC Diode Fail verursacht Temperatur-Störung und verhindert Laden Timed out retrying after 10000ms: expected '<md-select-value#select_value_label_0.md-select-value>' to be 'visible' This element '<md-select-value#select_value_label_0.md-select-value>' is not visible because its content is being clipped by one of its parent elements, which has a CSS property of overflow: 'hidden', 'clip', 'scroll' or 'auto' See screenshots on next pages	AC Diode Fail Test mit Temperatur-Überwachung	FAILED	12s	1
Vollständiger Ladezyklus - Plugin anschließen und ausstecken Timed out retrying after 10000ms: Expected to find element: '//div[@id='gauge_204']///*[name()='svg']///*[name()='text']', but never found it. ! See screenshots on next pages	Car Plugin Ladevorgang-Test	FAILED	22s	1
Energy Charged erhöht sich nach dem Ladestart	Energy Charged Validierung	PASSED	7s	

Screenshots

Car Simulation mit AC RCD Error und Pause/Resume

FAILED

ac-rcd-error-pause-resume.feature:2025-11-27T10:02:31.893Z (1/1)

The screenshot displays an Allure Test Report for a failed test case. The left pane shows the test steps and a failed assertion. The right pane shows a screenshot of a car simulation UI.

Test Steps:

- wait 2000
- (xhr) GET 200 /ui/css/app.min.less
- (xhr) GET 200 /ui/socket.io/?EIO=4&transport=polling&t=9lke4lkf
- (xhr) GET 404 /ui/loading.html
- (xhr) POST 200 /ui/socket.io/?EIO=4&transport=polling&t=9lkexbom&sid=fC4L2gDGJug1M3wYAAAS
- (xhr) GET 200 /ui/socket.io/?EIO=4&transport=polling&t=9lkexuja&sid=fC4L2gDGJug1M3wYAAAS
- (xhr) GET 200 /ui/socket.io/?EIO=4&transport=polling&t=9lkf9tIs&sid=fC4L2gDGJug1M3wYAAAS
- (xhr) POST 200 /ui/socket.io/?EIO=4&transport=polling&t=9lkf9zm4&sid=fC4L2gDGJug1M3wYAAAS
- (new url) http://localhost:1880/ui/#!/0?socketid=KGQWiEexr3pT6MrIAAAT

Failed Assertion:

```
When der Benutzer wählt Car Simulation "AC RCD Error" aus
```

```
-assert expected <md-select-value#select_value_label_0.md-select-value> to be visible
```

Car Simulation UI Screenshot:

The UI shows a "Connector" section with "PAUSE" and "RESUME" buttons. Below these, "Max Current" is 32.0 and "Energy Charged" is 0.02 kWh. A gauge shows "Idle" and "0 kW". At the bottom, there are "CAR PLUG IN" and "STOP & UNPLUG" buttons. A temperature indicator shows "Temperature: 25".

Screenshots

AC Diode Fail verursacht Temperatur-Störung und verhindert Laden

FAILED

ac-diode-fail-temperature.feature:2025-11-27T10:02:17.583Z (1/1)

The screenshot displays the Allure Test Report interface. The left pane shows the test steps for the feature "ac-diode-fail-temperature.feature". The test steps include several HTTP requests and a failed assertion.

The right pane shows a screenshot of the application under test, which is a car simulation UI. The UI displays the following information:

- Connector: PAUSE, RESUME
- Max Current: 32.0
- Energy Charged: 0.02 kWh
- Idle
- 0 kW
- Temperature: 25
- CAR PLUG IN, STOP & UNPLUG

The failed assertion is highlighted in red in the left pane:

```
-assert expected <md-select-value#select_value_label_0.md-select-value> to be visible
```


Screenshots

Vollständiger Ladezyklus - Plugin anschließen und ausstecken

FAILED

car-plugin-charge-cycle.feature:2025-11-27T10:02:56.090Z (1/1)

The screenshot displays an Allure Test Report for a failed test case. The left pane shows the test steps and assertions, while the right pane shows a screenshot of the application under test.

Test Steps and Assertions:

- 10 When der Benutzer das Car Plugin aktiviert
 - 11 **-assert** expected <button.md-raised.md-button.md-ink-ripple> to be visible
 - 12 **-assert** expected <button.md-raised.md-button.md-ink-ripple> not to be disabled
 - 13 `-xpath //button[@aria-label='buttonCar Plugin']`
 - 14 `-click {force: true}`
- 15 And der Benutzer wartet 10 Sekunden
 - 16 `wait 10000`
- 17 Then sollte der kW-Wert nicht mehr "0 kW" sein
 - 18 **-assert** expected `//div[@id='gauge_204']/**[name()='svg']/**[name()='text']` to exist in the DOM

Application Screenshot:

The application interface shows a "Connector" section with "PAUSE" and "RESUME" buttons. The "Max Current" is 32.0. The "Energy Charged" is 0.02 kWh. The status is "Idle" with a gauge showing 0 kW. The temperature is 25. At the bottom, there are buttons for "CAR PLUG IN" and "STOP & UNPLUG".

