

Book Store QA

Testing manual — unit, API and UI


Generated 28 August 2026, 09:59 · commit 4d8d9d3
Vitest · Karate · Playwright · GitHub Actions

Executive test metrics

Every figure below was produced by executing the suites at commit `523ad20`, not by counting source. Regenerate with `python scripts/collect_test_metrics.py`.



Smoke gate by layer



Test suite / layer	Tool	Total	Passed	Failed	Result	Coverage / scope
Unit	Vitest	7	7	0	100%	Pure logic in src/ - 100% of the covered surface
API (smoke)	Karate	2	2	0	100%	@smoke scenarios - the deployment gate
UI (smoke)	Playwright	5	5	0	100%	@smoke journeys on chromium
API (regression)	Karate	23	23	0	100%	Every scenario, all tags
UI (regression)	Playwright	7	7	0	100%	Every spec on chromium

The smoke gate is the first three rows: what a pull request runs and what verifies a production deployment. The regression rows are shown apart from it deliberately — quoting the API layer as 2 cases without saying *smoke* would misrepresent a suite that has 23.

1. Testing architecture

Three layers, run in a strict sequence. Each is cheaper and more certain than the one after it, so the pipeline learns the cheapest thing first and stops as soon as it knows enough.

Layer	Tool	Scope	Needs a target URL?	Fails the stage below it
Unit	Vitest	Pure logic in <code>playwright/src</code> — no browser, no network	No	Skips API and UI
API	Karate (Java 17 + Maven)	Book Store REST contract, per scenario	Yes	Skips UI
UI	Playwright	Browser journeys, one leg per browser	Yes	—

```
0. unit (Vitest) → api (Karate) → ui (Playwright, one leg per browser)
```

Why unit tests run once, not per environment. Unit tests assert pure logic — they never open a browser, never make a request, never touch `demoqa.com`. Their answer therefore *cannot* differ between dev, release and production. Running them inside each stage bought three identical answers to the same question, and made the API suite wait behind a redundant `npm ci` every time. They now run once, straight after the run configuration is resolved, as job `0. Unit tests (Vitest)`.

Because they run once, they have to gate *every* way into the chain. `dev` inherits that through ordinary job dependencies, but `release` and `production` are entry points in their own right and their conditions use a status function, which opts out of the implicit "all dependencies succeeded" rule. Both therefore name the result explicitly — without that, starting a run from `release` would walk straight past the gate.

2. Local execution

Three parameters run through everything: **environment** (which host), **suite** (smoke or regression) and **browser**.

Windows PowerShell. Run the lines in each block one at a time. PowerShell 5.1 has no `&&`, so joining them fails with `"'&&' is not a valid statement separator"`. Use `;` to chain, or `; if ($?) { ... }` to stop on the first failure. Git Bash and PowerShell 7+ accept `&&` as written. PowerShell also has no inline `VAR=value` command prefix — use `$env:VAR='...'` on its own statement.

Quote Playwright's tags on PowerShell too. `@` is the splatting operator, so a bare `--grep @smoke` expands the undefined variable `$smoke` to nothing and the argument silently disappears — Playwright then reports `"option '-g, --grep' argument missing"`. Write `--grep '@smoke'`.

Unit tests and coverage (Vitest)

```
cd playwright
npm ci
npm run test:unit           # tests only
npm run test:unit -- --coverage # tests + coverage gate
npm run test:unit:watch     # re-run on save while developing
```

Coverage is scoped to the code unit tests are responsible for. `src/pages/**` and `src/utls/api-client.ts` are excluded by rule, because the Playwright suite and the live API are what exercise them — counting them

here would measure the absence of Playwright rather than the quality of these tests.

Metric	Covered	Total	%	Floor
Statements	2	2	100%	80%
Branches	1	1	100%	80%
Functions	1	1	100%	80%
Lines	2	2	100%	80%

Vitest fails the run itself when any metric drops below the floor, so the gate is the runner's and not a later script's reading of a report. Read the figure as "*the pure logic is covered*", not "*the project is covered*" — the covered surface is deliberately small.

```
playwright - npm

$ npm run test:unit -- --coverage

> bookstore-web-automation@1.0.0 test:unit
> vitest run --coverage
RUN v4.1.11 C:/Users/g6k78/qa-assessment/playwright
  Coverage enabled with v8
✓ src/utils/test-data.test.ts (7 tests) 18ms
Test Files  1 passed (1)
Tests       7 passed (7)
Start at   13:56:39
Duration   469ms (transform 66ms, setup 0ms, import 105ms, tests 18ms, environment 0ms)
JUNIT report written to C:/Users/g6k78/qa-assessment/playwright/test-results/unit-junit.xml
% Coverage report from v8
===== Coverage summary =====
Statements : 100% ( 2/2 )
Branches   : 100% ( 1/1 )
Functions  : 100% ( 1/1 )
Lines      : 100% ( 2/2 )
=====
exit 0 - passed · 1.9s
```

API tests (Karate)

Requires **Java 17** and Maven 3.8+. Karate's GraalJS engine does not support JDK 18+ — on a newer JDK the suite hangs silently instead of failing, so check `java -version` first.

```
cd karate
```

Quote any `-D` containing a dot on PowerShell: it ends a parameter name at the first `.`, so `-Dkarate.env=dev` arrives at Maven split in two and fails with "*Unknown lifecycle phase '.env=dev'*".

Dev — smoke:

```
mvn test -Dtest=SmokeTest -Dkarate.env=dev
```

```
mvn test '-Dtest=SmokeTest' '-Dkarate.env=dev'
```

```
karate - mvn

$ mvn test -Dtest=SmokeTest -Dkarate.env=dev

[INFO] Scanning for projects...
[INFO] -----< com.assessment.qa:bookstore-api-automation >-----
[INFO] Building Book Store API Automation (Karate) 1.0.0
[INFO]   from pom.xml
[INFO] -----[ jar ]-----
[INFO] --- resources:3.4.0:resources (default-resources) @ bookstore-api-automation ---
[INFO] skip non existing resourceDirectory C:\Users\g6k78\qa-assessment\karate\src\main\resources
[INFO] --- compiler:3.15.0:compile (default-compile) @ bookstore-api-automation ---
[INFO] No sources to compile
[INFO] --- resources:3.4.0:testResources (default-testResources) @ bookstore-api-automation ---
[INFO] Copying 8 resources from src\test\java to target\test-classes
... 140 lines omitted ...
feature: classpath:bookstore/account/account.feature
scenarios: 1 | passed: 1 | failed: 0 | time: 9,2930
-----
13:57:07.309 [pool-3-thread-1] INFO  c.i.k.Suite - <<pass>> feature 1 of 5 (4 remaining) classpath:bookstore/account/account.feature
-----
feature: classpath:bookstore/books/books.feature
scenarios: 1 | passed: 1 | failed: 0 | time: 5,4620
-----
13:57:07.788 [pool-3-thread-1] INFO  c.i.k.Suite - <<pass>> feature 2 of 5 (3 remaining) classpath:bookstore/books/books.feature
Karate version: 1.4.1 | env: dev
=====
elapsed: 14,86 | threads: 3 | thread time: 14,76
features: 2 | skipped: 3 | efficiency: 0,33
scenarios: 2 | passed: 2 | failed: 0
=====
HTML report: (paste into browser to view) | Karate version: 1.4.1 | env: dev
file:///C:/Users/g6k78/qa-assessment/karate/target/karate-reports/karate-summary.html
=====
[INFO] Tests run: 1, Failures: 0, Errors: 0, Skipped: 0, Time elapsed: 15.87 s -- in bookstore.SmokeTest
[INFO]
[INFO] Results:
[INFO]
[INFO] Tests run: 1, Failures: 0, Errors: 0, Skipped: 0
[INFO]
[INFO] -----
[INFO] BUILD SUCCESS
[INFO] -----
[INFO] Total time: 22.314 s
[INFO] Finished at: 2026-08-27T13:57:08+03:00
[INFO] -----

exit 0 - passed - 26.1s
```

Release — full regression:

```
mvn test -Dtest=BookStoreApiTest -Dkarate.env=release -DbaseUrl=https://demoqa.com
```

```
mvn test '-Dtest=BookStoreApiTest' '-Dkarate.env=release' '-DbaseUrl=https://demoqa.com'
```

```
karate - mvn

$ mvn test -Dtest=BookStoreApiTest -Dkarate.env=release -DbaseUrl=https://demoqa.com

[INFO] Scanning for projects...
[INFO]
[INFO] -----< com.assessment.qa:bookstore-api-automation >-----
[INFO] Building Book Store API Automation (Karate) 1.0.0
[INFO]   from pom.xml
[INFO] -----[ jar ]-----
[INFO]
[INFO] --- resources:3.4.0:resources (default-resources) @ bookstore-api-automation ---
[INFO] skip non existing resourceDirectory C:\Users\g6k78\qa-assessment\karate\src\main\resources
[INFO]
[INFO] --- compiler:3.15.0:compile (default-compile) @ bookstore-api-automation ---
[INFO] No sources to compile
[INFO]
[INFO] --- resources:3.4.0:testResources (default-testResources) @ bookstore-api-automation ---
[INFO] Copying 8 resources from src\test\java to target\test-classes
... 1617 lines omitted ...
9 < Connection: keep-alive
9 < X-Powered-By: Express
9 < ETag: W/"2b-hLPYyb0m8IpHH/aFjmp8VZrYXGw"
{"code":"1207","message":"User not found!"}
-----
feature: classpath:bookstore/e2e/bookstore-collection.feature
scenarios: 1 | passed: 1 | failed: 0 | time: 16,0475
-----
13:58:10.083 [pool-3-thread-1] INFO  c.i.k.Suite - <<pass>> feature 5 of 5 (0 remaining) classpath:bookstore/e2e/bookstore-collection.feature
Karate version: 1.4.1 | env: release
=====
elapsed: 51,07 | threads: 5 | thread time: 193,43
features: 3 | skipped: 2 | efficiency: 0,76
scenarios: 23 | passed: 23 | failed: 0
=====
HTML report: (paste into browser to view) | Karate version: 1.4.1 | env: release
file:///C:/Users/g6k78/qa-assessment/karate/target/karate-reports/karate-summary.html
=====
[INFO] Tests run: 1, Failures: 0, Errors: 0, Skipped: 0, Time elapsed: 51.93 s -- in bookstore.BookStoreApiTest
[INFO]
[INFO] Results:
[INFO]
[INFO] Tests run: 1, Failures: 0, Errors: 0, Skipped: 0
[INFO]
[INFO] -----
[INFO] BUILD SUCCESS
[INFO] -----
[INFO] Total time: 56.159 s
[INFO] Finished at: 2026-08-27T13:58:10+03:00
[INFO] -----

exit 0 - passed · 59.7s
```

Production — smoke, with an explicit host:

```
mvn test -Dtest=SmokeTest -Dkarate.env=production -DbaseUrl=https://demoqa.com
```

```
mvn test '-Dtest=SmokeTest' '-Dkarate.env=production' '-DbaseUrl=https://demoqa.com'
```

```
karate - mvn

$ mvn test -Dtest=SmokeTest -Dkarate.env=production -DbaseUrl=https://demoqa.com

[INFO] Scanning for projects...
[INFO] -----< com.assessment.qa:bookstore-api-automation >-----
[INFO] Building Book Store API Automation (Karate) 1.0.0
[INFO] from pom.xml
[INFO] -----[ jar ]-----
[INFO] --- resources:3.4.0:resources (default-resources) @ bookstore-api-automation ---
[INFO] skip non existing resourceDirectory C:\Users\g6k78\qa-assessment\karate\src\main\resources
[INFO] --- compiler:3.15.0:compile (default-compile) @ bookstore-api-automation ---
[INFO] No sources to compile
[INFO] --- resources:3.4.0:testResources (default-testResources) @ bookstore-api-automation ---
[INFO] Copying 8 resources from src\test\java to target\test-classes
... 140 lines omitted ...
feature: classpath:bookstore/account/account.feature
scenarios: 1 | passed: 1 | failed: 0 | time: 5,7354
-----
13:58:30.105 [pool-3-thread-1] INFO c.i.k.Suite - <<pass>> feature 1 of 5 (4 remaining) classpath:bookstore/account/account.feature
-----
feature: classpath:bookstore/books/books.feature
scenarios: 1 | passed: 1 | failed: 0 | time: 5,6522
-----
13:58:30.549 [pool-3-thread-1] INFO c.i.k.Suite - <<pass>> feature 2 of 5 (3 remaining) classpath:bookstore/books/books.feature
Karate version: 1.4.1 | env: production
=====
elapsed: 10,24 | threads: 3 | thread time: 11,39
features: 2 | skipped: 3 | efficiency: 0,37
scenarios: 2 | passed: 2 | failed: 0
=====
HTML report: (paste into browser to view) | Karate version: 1.4.1 | env: production
file:///C:/Users/g6k78/qa-assessment/karate/target/karate-reports/karate-summary.html
=====
[INFO] Tests run: 1, Failures: 0, Errors: 0, Skipped: 0, Time elapsed: 11.07 s -- in bookstore.SmokeTest
[INFO]
[INFO] Results:
[INFO]
[INFO] Tests run: 1, Failures: 0, Errors: 0, Skipped: 0
[INFO]
[INFO] -----
[INFO] BUILD SUCCESS
[INFO] -----
[INFO] Total time: 15.185 s
[INFO] Finished at: 2026-08-27T13:58:31+03:00
[INFO] -----

exit 0 - passed - 18.6s
```

`-Dtest` picks the runner class and therefore the tag set: `SmokeTest` runs `@smoke`, `BookStoreApiTest` runs everything.

`release` and `production` both need `-DbaseUrl` locally. `dev` defaults to the demo site, but `release` falls back to a placeholder host that does not resolve, so the command would fail with a connection error rather than a test failure. In CI the host comes from the `RELEASE_BASE_URL` repository variable instead. Reports land in `karate/target/karate-reports/karate-summary.html`.

UI tests (Playwright)

```
cd playwright
npx playwright install chromium # or: firefox webkit msedge
```

Dev — smoke on chromium:

```
BASE_URL=https://demoqa.com npx playwright test --project=chromium --grep @smoke
```

```
$env:BASE_URL='https://demoqa.com'; npx playwright test --project=chromium --grep '@smoke'
```

playwright - npx

```
$ BASE_URL=https://demoqa.com npx playwright test --project=chromium --grep @smoke
```

Running 5 tests using 4 workers

```
ok 3 [chromium] > tests\login.spec.ts:27:7 > Login @smoke > protects the profile page from anonymous access (6.9s)
ok 5 [chromium] > tests\registration.spec.ts:32:7 > Registration @smoke > the API rejects a password that violates the documented policy (279ms)
ok 4 [chromium] > tests\registration.spec.ts:11:7 > Registration @smoke > the registration form is reachable from login and is captcha-protected (7.2s)
ok 1 [chromium] > tests\login.spec.ts:4:7 > Login @smoke > rejects unknown credentials with a visible error and no session (8.7s)
ok 2 [chromium] > tests\login.spec.ts:19:7 > Login @smoke > rejects a valid username with the wrong password (10.9s)
5 passed (12.4s)
```

```
exit 0 - passed · 15.0s
```

Release — regression across every browser:

```
BASE_URL=https://demoqa.com npx playwright test --project=chromium --project=firefox --project=webkit --project=msedge
```

```
$env:BASE_URL='https://demoqa.com'; npx playwright test --project=chromium --project=firefox --project=webkit --project=msedge
```

playwright - npx

```
$ BASE_URL=https://demoqa.com npx playwright test --project=chromium --project=firefox --project=webkit --project=msedge
```


Running 28 tests using 4 workers

```
ok 4 [chromium] > tests\login.spec.ts:4:7 > Login @smoke > rejects unknown credentials with a visible error and no session (7.8s)
ok 5 [chromium] > tests\login.spec.ts:27:7 > Login @smoke > protects the profile page from anonymous access (1.5s)
ok 6 [chromium] > tests\registration.spec.ts:11:7 > Registration @smoke > the registration form is reachable from login and is captcha-protected (2.4s)
ok 7 [chromium] > tests\registration.spec.ts:32:7 > Registration @smoke > the API rejects a password that violates the documented policy (282ms)
ok 2 [chromium] > tests\login.spec.ts:19:7 > Login @smoke > rejects a valid username with the wrong password (14.9s)
ok 3 [chromium] > tests\bookstore-collection.spec.ts:80:7 > Book Store - my collection @e2e > cancelling the delete dialog keeps the book in the collection @regression (18.7s)
ok 1 [chromium] > tests\bookstore-collection.spec.ts:15:7 > Book Store - my collection @e2e > a user can register, add a book to their collection, remove it and log out (21.1s)
ok 10 [firefox] > tests\login.spec.ts:4:7 > Login @smoke > rejects unknown credentials with a visible error and no session (16.2s)
ok 12 [firefox] > tests\login.spec.ts:27:7 > Login @smoke > protects the profile page from anonymous access (3.6s)
ok 11 [firefox] > tests\login.spec.ts:19:7 > Login @smoke > rejects a valid username with the wrong password (18.6s)
ok 14 [firefox] > tests\registration.spec.ts:32:7 > Registration @smoke > the API rejects a password that violates the documented policy (155ms)
ok 9 [firefox] > tests\bookstore-collection.spec.ts:80:7 > Book Store - my collection @e2e > cancelling the delete dialog keeps the book in the collection @regression (25.1s)
ok 13 [firefox] > tests\registration.spec.ts:11:7 > Registration @smoke > the registration form is reachable from login and is captcha-protected (4.5s)
ok 8 [firefox] > tests\bookstore-collection.spec.ts:15:7 > Book Store - my collection @e2e > a user can register, add a book to their collection, remove it and log out (36.7s)
ok 17 [webkit] > tests\login.spec.ts:4:7 > Login @smoke > rejects unknown credentials with a visible error and no session (8.2s)
ok 19 [webkit] > tests\login.spec.ts:27:7 > Login @smoke > protects the profile page from anonymous access (3.5s)
ok 20 [webkit] > tests\registration.spec.ts:11:7 > Registration @smoke > the registration form is reachable from login and is captcha-protected (3.9s)
ok 21 [webkit] > tests\registration.spec.ts:32:7 > Registration @smoke > the API rejects a password that violates the documented policy (281ms)
ok 18 [webkit] > tests\login.spec.ts:19:7 > Login @smoke > rejects a valid username with the wrong password (14.1s)
ok 15 [webkit] > tests\bookstore-collection.spec.ts:15:7 > Book Store - my collection @e2e > a user can register, add a book to their collection, remove it and log out (24.3s)
ok 16 [webkit] > tests\bookstore-collection.spec.ts:80:7 > Book Store - my collection @e2e > cancelling the delete dialog keeps the book in the collection @regression (23.8s)
ok 24 [msedge] > tests\login.spec.ts:4:7 > Login @smoke > rejects unknown credentials with a visible error and no session (9.9s)
ok 25 [msedge] > tests\login.spec.ts:19:7 > Login @smoke > rejects a valid username with the wrong password (12.7s)
ok 26 [msedge] > tests\login.spec.ts:27:7 > Login @smoke > protects the profile page from anonymous access (3.7s)
ok 28 [msedge] > tests\registration.spec.ts:32:7 > Registration @smoke > the API rejects a password that violates the documented policy (366ms)
ok 23 [msedge] > tests\bookstore-collection.spec.ts:80:7 > Book Store - my collection @e2e > cancelling the delete dialog keeps the book in the collection @regression (19.2s)
```


Production — smoke on Edge:

```
BASE_URL=https://demoqa.com npx playwright test --project=msedge --grep @smoke
```

```
$env:BASE_URL='https://demoqa.com'; npx playwright test --project=msedge --grep '@smoke'
```



```
playwright - npx
$ BASE_URL=https://demoqa.com npx playwright test --project=msedge --grep @smoke

Running 5 tests using 4 workers
ok 4 [msedge] > tests\registration.spec.ts:11:7 > Registration @smoke > the registration form is reachable from login and is captcha-protected (12.5s)
ok 1 [msedge] > tests\login.spec.ts:27:7 > Login @smoke > protects the profile page from anonymous access (12.7s)
ok 5 [msedge] > tests\registration.spec.ts:32:7 > Registration @smoke > the API rejects a password that violates the documented policy (690ms)
ok 2 [msedge] > tests\login.spec.ts:4:7 > Login @smoke > rejects unknown credentials with a visible error and no session (14.0s)
ok 3 [msedge] > tests\login.spec.ts:19:7 > Login @smoke > rejects a valid username with the wrong password (10.7s)
5 passed (17.9s)

exit 0 - passed · 21.0s
```

UI mode — pick and re-run tests interactively:

```
npx playwright test --ui
npm run test:headed      # or just watch chromium drive
npm run report           # open the last HTML report
```

Edge is a branded channel rather than a bundled engine, so `npx playwright install` alone does not fetch it — it has to be named. `playwright test` has no `--channel` flag either, so the config models Edge as a project pinning channel: `'msedge'`; one `--project` argument then selects any of the four.

The whole sequence in one line

Unit → API → UI, stopping at the first failure:

```
cd playwright && npm run test:unit -- --coverage && cd ../karate && mvn test -Dtest=SmokeTest -Dkarate.env=dev && cd ../playwright && BASE_URL=https://demoqa.com npx playwright test --project=chromium --grep @smoke
```

```
cd playwright; if ($?) { npm run test:unit -- --coverage }; if ($?) { cd ../karate }; if ($?) { mvn test '-Dtest=SmokeTest' '-Dkarate.env=dev' }; if ($?) { cd ../playwright }; if ($?) { $env:BASE_URL='https://demoqa.com'; npx playwright test --project=chromium --grep '@smoke' }
```

3. GitHub Actions pipeline

Run it from **Actions** → **QA Automation** → **Run workflow**. Four things decide what happens, and the first of them is the branch:

Input	Options	Effect
Use workflow from	eyter_dev , release , main	Chooses the entry stage — this is why there is no environment dropdown
Test suite	smoke , regression	-Dtest=SmokeTest / BookStoreApiTest , and --grep @smoke
Playwright browser	chromium , firefox , webkit , msedge , all browsers	One matrix leg each; all browsers runs four in parallel
Promote	checkbox, off by default	Whether the run continues past its entry stage

Scenario A — running from eyter_dev

The full chain. Unit tests gate everything; the dev stage runs against the dev host; if it is green and *Promote* is ticked, the tested commit is fast-forwarded onto `release`, the release stage runs, and the same happens onto `main` before production is deployed and verified.

```
0. unit → 1. dev → promote → 2. release → promote → 3. deploy → verify
```

With *Promote* unticked the run stops after the dev stage: nothing is promoted, no branch moves, nothing is deployed.

Run workflow ▼

Use workflow from

Branch: eyter_dev ▼

Test suite

regression

Playwright browser

chromium

☒ Promote onward if tests pass (eyter_dev only; fails elsewhere)

Run workflow

Scenario B — running from release or main

The branch is the entry point, so earlier stages are skipped and the run starts where you pointed it. **Promotion is bound to eyter_dev**: ticking *Promote* on a run started from `release`, `main` or a feature branch fails the run

in seconds, before any suite starts, with

Promotion is only allowed when triggered from the eyter_dev branch.

That guard matters most in the case that looks harmless — a feature branch enters at the dev stage exactly like `eyter_dev` does, so without it a green feature-branch run would push its own commit straight at `release`.

Two things to know before running from `main`: entering at stage 3 **deploys**, promote or not, because `main` has nowhere further to promote to; and a `Pipeline result` job fails the run if production was deployed but its verification did not pass, so a deploy can never report green unverified.

The screenshot displays the QA Automation interface for a pipeline run. At the top, a red error icon and the text "[MANUAL: release] - Promote onward from this branch if its tests pass - smoke on chromium #68" are visible. A "Re-run jobs" button is in the top right. The left sidebar contains a "Summary" section with a list of jobs: "All jobs", "Resolve run configuration", "1. Dev", "1b. Promote to release", "2. Release", "2b. Promote to main", "3. Deploy to production", "3b. Production", and "Pipeline result". The main content area shows a summary of the run: "Manually triggered yesterday", "Eyter-Higuera", "ed4d879", "release", "Failure", "8s", and "Artifacts". Below this is a "ci.yml" workflow diagram showing a sequence of jobs: "resolve run configuration", "1. Dev / opt", "Waiting for pending jobs", "1b. Promote to release", "1. Release / opt", "Waiting for pending jobs", "2b. Promote to main", "3. Deploy to production", "production verify / opt", "Waiting for pending jobs", and "Pipeline result". The "Pipeline result" job is highlighted in red, indicating failure. Below the diagram, the "Annotations" section shows two errors: "Resolve run configuration" (Process completed with exit code 1.) and "Promotion not allowed from this branch" (Promotion is only allowed when triggered from the eyter_dev branch.).

What the run summary shows

Every job writes its results to the run summary page, so a failure is readable without downloading an artifact: the Vitest coverage table with a tick or cross per metric, then a Karate table and a Playwright table per stage — totals, a row per suite with pass/fail/skip counts and durations, and, when something fails, a second table naming each failing test with the first line of its error.

Summary

All jobs

Resolve run configuration

0. Unit tests (Vitest)

1. Dev

1b. Promote to release

2. Release

2b. Promote to main

3. Deploy to production

3b. Production smoke

Pipeline result

Run details

Usage

Workflow file

Resolve run configuration summary

Run configuration

Suites: [API + UI] - Karate then Playwright at every stage.

Commit: 46acaf4

Triggered by workflow_dispatch on eytar_dev, entering at dev.

The dev -> release -> production chain runs only from eytar_dev.

A manual run from release or main tests that stage and stops; ticking promote there fails the run before any suite starts.

Promotion is off: this run tests its entry stage and stops.

Stage	Runs
1. dev	entry point - smoke on ["chromium"] - https://demoqa.com
2. release	skipped - promotion is off
3. production	skipped - promotion is off

Job summary generated at run-time

0. Unit tests (Vitest) summary

Unit (Vitest)

passed - 7 tests in 0.0s: 7 passed, 0 failed, 0 skipped

Suite	Passed	Failed	Skipped	Duration
src/utills/test-data.test.ts	7	0	0	0.0s

Unit test coverage

Metric	Covered	Total	%	Threshold 80%
Statements	2	2	100.0%	✔
Branches	1	1	100.0%	✔
Functions	1	1	100.0%	✔
Lines	2	2	100.0%	✔

► Per file (1)

Job summary generated at run-time

1. Dev / API (Karate) - dev - smoke summary

Karate - dev - smoke

passed - 2 tests in 17.2s: 2 passed, 0 failed, 0 skipped

Suite	Passed	Failed	Skipped	Duration
bookstore/account/account.feature	1	0	0	10.1s
bookstore/books/books.feature	1	0	0	7.1s

Job summary generated at run-time

1. Dev / Web (Playwright) - dev - smoke - chromium summary

Playwright - dev - smoke - chromium

passed - 5 tests in 14.6s: 5 passed, 0 failed, 0 skipped

Suite	Passed	Failed	Skipped	Duration
login.spec.ts	3	0	0	12.6s
registration.spec.ts	2	0	0	2.1s

Book Store QA — testing manual

12

/

12