🇺🇸 **English**

MAHARISHI INTERNATIONAL UNIVERSITY • USA
MS in Computer Science
COMPUTER PROFESSIONALS PROGRAM℠

Computer Professionals
Master's Program Sample Test

You will be asked to complete a real test as part of your application process.

The purpose of this short test is to assess your ability to solve elementary programming problems in a language of your choice.

Write your solutions in Java if you are familiar with that language; otherwise use one of these languages: C, C++, or C#. For each of the problems below, write the simplest, clearest solution you can, in the form of a short program.

SAMPLE TEST

1. An array with an odd number of elements is said to be centered if all elements (except the middle one) are strictly greater than the value of the middle element. Note that only arrays with an odd number of elements have a middle element. Write a function that accepts an integer array and returns 1 if it is a centered array, otherwise it returns 0.

Examples:

if the input array is	return

🇺🇸 English

MAHARISHI INTERNATIONAL UNIVERSITY • USA

MS in Computer Science

COMPUTER PROFESSIONALS PROGRAM℠

{1, 2, 3, 4}	0 (no middle element)
{}	0 (no middle element)
{10}	1 (the middle element 10 is strictly less than all other elements)

See correct answers to sample questions.

2. **Write a function that takes an array of integers as an argument and returns a value based on the sums of the even and odd numbers in the array.** Let X = the sum of the odd numbers in the array and let Y = the sum of the even numbers. The function should return X – Y

The signature of the function is:
int f(int[ ] a)

Examples

if input array is	return
{1}	1
{1, 2}	-1
{1, 2, 3}	2
{1, 2, 3, 4}	-2
{3, 3, 4, 4}	-2
{3, 2, 3, 4}	0

CHAT with us

Chat is offline. Send email.

🇺🇸 English

MAHARISHI INTERNATIONAL UNIVERSITY • USA

MS in Computer Science

COMPUTER PROFESSIONALS PROGRAM℠

<u>**See correct answers to sample questions.**</u>

3. Write a function that accepts a character array, a zero-based start position and a length. It should return a character array containing containing *length*characters starting with the *start*character of the **input array.** The function should do error checking on the start position and the length and return null if the either value is not legal.
   The function signature is:
   char[ ] f(char[ ] a, int start, int len)

Examples

if input parameters are	return
{'a', 'b', 'c'}, 0, 4	null
{'a', 'b', 'c'}, 0, 3	{'a', 'b', 'c'}
{'a', 'b', 'c'}, 0, 2	{'a', 'b'}
{'a', 'b', 'c'}, 0, 1	{'a'}
{'a', 'b', 'c'}, 1, 3	null
{'a', 'b', 'c'}, 1, 2	{'b', 'c'}
{'a', 'b', 'c'}, 1, 1	{'b'}
{'a', 'b', 'c'}, 2, 2	null
{'a', 'b', 'c'}, 2, 1	{'c'}
{'a', 'b', 'c'}, 3, 1	null
{'a', 'b', 'c'}, 1, 0	

CHAT with us

Chat is offline. Send email.

{'a', 'b', 'c'}, -1, 2

🇺🇸 English

MAHARISHI INTERNATIONAL UNIVERSITY • USA

MS in Computer Science

COMPUTER PROFESSIONALS PROGRAM℠

See correct answers to sample questions.

4. Write a function to reverse an integer using numeric operators and
   without using any arrays or other data structures.
   The signature of the function is:
   int f(int n)

Examples

if the input integer is	return
1234	4321
12005	50021
1	1
1000	1
0	0
-12345	-54321

See correct answers to sample questions.

5. Write a function to return an array containing all elements common
   to two given arrays containing distinct positive integers. You should
   not use any inbuilt methods. You are allowed to use any number
   arrays.

CHAT with us

Chat is offline. Send email.

The signature of the function is:

int[] f(int[] first, int[] second)

Examples

if input parameters are	return
{1, 8, 3, 2}, {4, 2, 6, 1}	{1, 2}
{1, 8, 3, 2, 6}, {2, 6, 1}	{2, 6, 1}
{1, 3, 7, 9}, {7, 1, 9, 3}	{1, 3, 7, 9}
{1, 2}, {3, 4}	{}
{}, {1, 2, 3}	{}
{1, 2}, {}	{}
{1, 2}, null	null
null, {}	null
null, null	null

<u>**See correct answers to sample questions.**</u>

6. **Consider an array A with n of positive integers. An integer idx is called a POE (point of equilibrium) of A, if A[0] + A[1] + … + A[idx – 1] is equal to A[idx + 1] + A[idx + 2] + … + A[n – 1]. Write a function to return POE of an array, if it exists and -1 otherwise.**
   The signature of the function is:
   int f(int[] a)

Examples

if input arrays are	return
{1, 8, 3, 7, 10, 2}	3 Reason: a[0] + a[1] + a[2] is

CHAT with us

Chat is offline. Send email.

English

| {1, 2, 10, 3, 4} | -1 Reason: No POE. |

See correct answers to sample questions.

Note: Please read the <u>list of common programming errors</u> that students have committed on our test.

START APPLICATION NOW

Application Links:

Application Checklist

Sample Test

Personal Information Form

Recommendation Form

Online Application

Check Application Status

CHAT with us

Chat is offline. Send email.

Entry Dates:

MS in Computer Science

- April

- August

- October

U.S. CITIZENS & PERMANENT RESIDENTS:

- January

- August

English

Chat is offline. Send email.