# DATA SHEET

**PRODUCT: Coated Flag Textile**

**FEATURES:**

Coated Flag Textile is a light and soft flag with release paper, it have excellent double penetration effect and does not fade under strong light feature after solvent or eco-solvent printing by all kinds of printer.

**APPLICATIONS:**



| SPECIFICATIONS | METRIC | TEST METHOD |
|---|---|---|
| Material | 100% polyester | DIN 60001,ASTM D7641 |
| Yarn Dtex | 55DX55D | GB/T16604 |
| Fabric Weight | 110±120 g/sq.m | GB/T4669 |
| Release liner | Non woven fabric | GB/T4669 |
| Product Weight | 210±10 g/sq.m | GB/T1040 |
| Tensile Strength MD/ CD | ≥300 N/5cm | GB/T1040 |
| Tearing Strength MD/ CD | ≥10 N/5cm | GB/T16578 |
| Temperature Range | -20 ~ +70 ℃ | |
| Width | 1.52m/3.2M | DIN EN ISO 3759,ASTM D751-2006 |
| Standard Length | 50m/ 100m | DIN EN ISO 3759,ASTM D751-2006 |
| Compatible Inks | Latex, UV, Solvent, Eco- | |
| Storage Time | 1 year | Sealed storage, horizontal place, avoid direct sunlight and direct contact with heat. Storage temperature 25±5℃, relative humidity 50±15% |
| Application | Flags, Banners | |

| Applications | Flag | Display | Backdrop | Roll up | Backlit | Light Box | Indoor | Outdoor |
|---|---|---|---|---|---|---|---|---|
| | ● | ● | | | | | ● | ● |

The information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. A legally binding guarantee of specific properties is not to be inferred from our specifications. They are given without guaranty and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)
Backdrop Roll