Sectioning commands with critical notes in parallel colums

This file provides examples of using sectioning commands with reledpar. The section titles are in the line numbering, and have critical notes.

The left and right sides are put in columns. We use `\eledsectnotoc{L}` to say we want the right titles be added to the table of contents, and not the left titles. We also use `\eledsectmark{R}` to use the right side to add LaTeX marks for headers.

We use the `\reledxxx` commands, each of them in their own `\pstart . . . \pend` group.

Page clearings are manually added before chapter with `\beforeeledchapter`.

Contents

1 Right chapter **5**

1.1 Right section 5

1.1.1 Right subsection 5

1.2 Right section 5

2 Right chapter **7**

2.1 Right section 7

2.1.1 Right subsection 7

2.2 Right section 7

Chapter 1

Left chapter

I use git to manage some packages. I would like to add a pre-commit hook, to check if I have forgotten For now, I have a minimal pre-commit, which tests only the blank spaces at ends of lines, but not the forgotten..

1.1 Left section

1.1.1 Left subsection

Left subsubsection

I use git to manage some packages. I would like to add a pre-commit hook, to check if I have forgotten For now, I have a minimal pre-commit, which tests only the blank spaces at ends of lines, but not the forgotten.

1.2 Left section

Chapter 1

Right chapter

I use git to manage some packages. I would like to add a pre-commit hook, to check if I have forgotten For now, I have a minimal pre-commit, which tests only the blank spaces at ends of lines, but not the forgotten..

1.1 Right section

1.1.1 Right subsection

Right subsubsection

I use git to manage some packages. I would like to add a pre-commit hook, to check if I have forgotten For now, I have a minimal pre-commit, which tests only the blank spaces at ends of lines, but not the forgotten.

1.2 Right section

1 chapter] chapitre
1 chapter] chapitre
9 subsection] sous-section
9 subsection] sous-section
10 subsubsection] sous-sous-section
10 subsubsection] sous-sous-section

I use git to manage some packages. I would like to add a pre-commit hook, to check if I have forgotten For now, I have a minimal pre-commit, which tests only the blank spaces at ends of lines, but not the forgotten.

I use git to manage some packages. I would like to add a pre-commit hook, to check if I have forgotten For now, I have a minimal pre-commit, which tests only the blank spaces at ends of lines, but not the forgotten.

Chapter 2

Left chapter

I use git to manage some packages. I would like to add a pre-commit hook, to check if I have forgotten For now, I have a minimal pre-commit, which tests only the blank spaces at ends of lines, but not the forgotten..

2.1 Left section

2.1.1 Left subsection

Left subsubsection

I use git to manage some packages. I would like to add a pre-commit hook, to check if I have forgotten For now, I have a minimal pre-commit, which tests only the blank spaces at ends of lines, but not the forgotten.

2.2 Left section

Chapter 2

Right chapter

I use git to manage some packages. I would like to add a pre-commit hook, to check if I have forgotten For now, I have a minimal pre-commit, which tests only the blank spaces at ends of lines, but not the forgotten..

2.1 Right section

2.1.1 Right subsection

Right subsubsection

I use git to manage some packages. I would like to add a pre-commit hook, to check if I have forgotten For now, I have a minimal pre-commit, which tests only the blank spaces at ends of lines, but not the forgotten.

2.2 Right section

1 chapter] chapitre
1 chapter] chapitre
9 subsection] sous-section
9 subsection] sous-section
10 subsubsection] sous-sous-section
10 subsubsection] sous-sous-section

I use git to manage some packages. I would like to add a pre-commit hook, to check if I have forgotten For now, I have a minimal pre-commit, which tests only the blank spaces at ends of lines, but not the forgotten.

I use git to manage some packages. I would like to add a pre-commit hook, to check if I have forgotten For now, I have a minimal pre-commit, which tests only the blank spaces at ends of lines, but not the forgotten.