# HIGH PERFORMANCE COMPUTING: TOWARDS BETTER PERFORMANCE PREDICTIONS AND EXPERIMENTS

Tom Cornebize 2 June 2021, PhD defense







#### No science without computing



Arithmometer (1851)



ENIAC (1945)



Fugaku (2021)

#### No science without computing







Arithmometer (1851)


ENIAC (1945)

Fugaku (2021)

#### Last decades:

- Exponential performance improvements (e.g. sequencing an entire human genome costed \$100,000,000 in 2001, \$1000 now)
- At the price of complexity (both software and hardware)

#### EXPERIMENTAL STUDY OF COMPUTER PERFORMANCE




Similar to natural sciences

Complexity ⇒ Variability and Opacity

 $\Rightarrow$  No perfect model

 $\Rightarrow \text{Need for experiments}$ 

#### EXPERIMENTAL STUDY OF COMPUTER PERFORMANCE



Similar to natural sciences

Complexity ⇒ Variability and Opacity

 $\Rightarrow$  No perfect model

⇒ Need for experiments


Experiments can be carried in reality or in simulation

**Typical Performance Evaluation Questions** (Given my application and a supercomputer)




- · Before running
  - How many nodes?
  - For how long?
  - · Which parameters?

### **Typical Performance Evaluation Questions** (Given my application and a supercomputer)



- · Before running
  - How many nodes?
  - For how long?
  - · Which parameters?
- After running
  - Performance as "expected"?
  - Problem in the app or the platform?


### **Typical Performance Evaluation Questions** (Given my application and a supercomputer)



- · Before running
  - · How many nodes?
  - For how long?
  - Which parameters?
- After running
  - Performance as "expected"?
  - Problem in the app or the platform?

So many large-scale runs, solely to tune performance?!?

**Typical Performance Evaluation Questions** (Given my application and a supercomputer)



- · Before running
  - · How many nodes?
  - For how long?
  - Which parameters?
- After running
  - Performance as "expected"?
  - Problem in the app or the platform?

So many large-scale runs, solely to tune performance?!?

Holy Grail: Predictive Simulation on a "Laptop"

Capture the whole application and platform complexity

#### SIM(EM)ULATION: THE SMPI APPROACH



### Full reimplementation of MPI on top of SIM

- · C/C++/F77/F90 codes run unmodified out of the box
- Simply replace mpicc/mpirun by smpicc/smpirun



#### SIM(EM)ULATION: THE SMPI APPROACH



### Full reimplementation of MPI on top of

- · C/C++/F77/F90 codes run unmodified out of the box
- Simply replace mpicc/mpirun by smpicc/smpirun



#### Emulation: how?

- · Computations run for real on a laptop
- · Communications are faked, good fluid network models
- · Performance model for the target platform

#### Thesis contributions (towards this goal)

- · Case study: High Performance Linpack (HPL)
- Skip the expensive computations (mostly dgemm) and replace them by a performance model
- Extensive (in)validation, comparing simulations with reality

#### Thesis contributions (towards this goal)

- · Case study: High Performance Linpack (HPL)
- Skip the expensive computations (mostly dgemm) and replace them by a performance model
- Extensive (in)validation, comparing simulations with reality

#### Thesis contributions (made on the way)

- · Automation (of experiments, statistical analyzes, etc.)
- · Experiment methodology, to bias or not to bias
- Performance tests, to detect eventual platform changes

#### Thesis contributions (towards this goal)

- · Case study: High Performance Linpack (HPL)
- Skip the expensive computations (mostly dgemm) and replace them by a performance model
- Extensive (in)validation, comparing simulations with reality

#### Thesis contributions (made on the way)

- Automation (of experiments, statistical analyzes, etc.)
- Experiment methodology, to bias or not to bias
- Performance tests, to detect eventual platform changes