

Urovo

CT48C

Enterprise Mobile Computer

Octa-core 2.0 GHz Processor and Android 12 O.S.

The device scores 250,000 Antutu benchmark points, 80% improved than the previous generation, giving a faster user experience.

High-Precision Scanning Engine

Equipped with a million-pixel image sensor, captures and reads various QR or barcodes -- 1D/2D/stained/distorted/DPM -- in lightning-fast response and pinpoint accuracy.

Zero-handoff Roaming over Wi-Fi

Enables seamless roaming among APs, ensuring uninterrupted and rapid data transmission.

Ergonomic Design with Keypads

Enhanced key spacing for flexible operation even with gloves and easily operated in one hand with ergonomic design.

High-Volume 2W Power Speaker

With the optimized 2W power speaker, delivers a volume of 100dB+ for clear feedback even in noisy environments.



IP67
Sealing



5000mAh
Battery



BT5.0



Screen
Protector



Charging
Cradle



Protective
Shell



Hand Strap



4-Slot Battery
Charging Cradle

CT48C Enterprise Mobile Computer

UROVO

Specification

Processor

Octa-core 2.0 GHz

O.S.

Android 12

Memory

RAM: 4GB ROM: 64GB
Micro SD card, Up to 256 GB

Display

4.0-inch touch screen
480×800

Touch Screen

Ultra sensitive capacitive touch panel, support multi-touch, works with gloves and wet fingers

Dimensions

Size: 165.7*66*18mm
Weight: 268g

Scanning

Professional scan engine
Supports standard 1D/2D barcodes

Voice

2 W speaker;
Microphone

Battery

5000mAh
removable battery

Camera

Front default none (2MP optional)
Rear 13MP Autofocus
Flash LED

Buttons

Power button
Scan button*3
Fn key
Direction key*4
Function key*2

Card slot

Nano-SIM x 1
or Micro SD x 1 up to 256GB

Communication

4G, 3G, 2G
BT5.0 + BR/EDR + BLE
2.4G/5G dual band,
IEEE 802.11a/b/g/n/ac/d/h/i/k/r/v/w
Fast roaming: PMKID caching;
Cisco CCKM 802.11r (Over-The-Air); OKC

Positioning

GPS, A-GPS, BEIDOU
GLONASS, Galileo

Protection

IP67 dustproof and waterproof
1.5-meter drop resistance

NFC(optional)

Support ISO15693, ISO14443
A/B, Mifare, Felica

Environment

Operating temperature: -20 ~ +60°C
Storage temperature: -40 ~ +70°C
Humidity: 5%RH ~ 95%RH (non-condensing)

UROVO PTE. LIMITED

Website: en.urovo.com

Email: urovo@urovo.com

Address: 1 Raffles Place, #21-01 One Raffles Place Tower 1,
Singapore 048616

Urovo Europe

Website: europe.urovo.com

Email: sales-europe@urovo-emea.com

Address: de Maas 9, 5684PL, Best, the Netherlands

Urovo North America

Website: us.urovo.com

Email: urovo@urovo.com

Address: 1990 Main Street, Suite 750, Sarasota,
Florida 34236

*This page is subject to change
without prior notice