



Series	D8100PLUS	
Printer type	Thermal transfer desktop printer	
Model	D8120PLUS	D8130PLUS
Resolution/DPI	203	300
Instruction Mode	TSPL, EPL, ZPL, ZPL II, DPL	TSPL, EPL, ZPL, ZPL II, DPL
Paper type	Continuous paper, gap paper, black mark paper, perforated paper, fanfold paper	Continuous paper, gap paper, black mark paper, perforated paper, fanfold paper
One-dimensional code	Code 11, Code 39, Code 93, Code 128 (subsets A, B, C), UPC-A, UPC-E, UCC-128, Codabar, EAN/JAN-8, EAN/JAN-13, Interleaved 2 of 5, ITF14, MSI Pleassy, PostCode, Telepen	Code 11, Code 39, Code 93, Code 128 (subsets A, B, C), UPC-A, UPC-E, UCC-128, Codabar, EAN/JAN-8, EAN/JAN-13, Interleaved 2 of 5, ITF14, MSI Pleassy, PostCode, Telepen
QR code	QR Code, Micro QR Code, PDF417, Micro PDF417, MaxiCode, Aztec Code, Data Matrix	QR Code, Micro QR Code, PDF417, Micro PDF417, MaxiCode, Aztec Code, Data Matrix
Font Collection	• 8 dot matrix alphanumeric vector font engines, need to download vector glyph (TTF) files	• 8 dot matrix alphanumeric vector font engines, need to download vector glyph (TTF) files
RAM (memory)/M	128	128
Flash (font)/M	128	128

Print speed	200mm/s	150mm/S
Effective printing (width) / MM	104	108
Minimum paper width supported/MM	20	20
Maximum paper width supported: MM	120	120
Paper outer diameter/MM	127	127
Minimum support (height) / MM	15	15
Supported paper thickness/MM	0.06-0.26	0.06-0.26
Paper roll aperture/MM	25~76	25~76
Paper loading direction	middle	middle
Carbon ribbon specification/MM	110	110
Carbon ribbon outer diameter/MM	67	67
Ribbon length/M	300	300
Carbon ribbon aperture/MM	25	25
Cover open sensor	have	have
Ribbon sensor	have	have
Distance sensor	have	have
Black mark sensor	have	have
Paper pick sensor (for cutter and peeler)	have	have
Power Input	DC 24V, 2.5A, 60w	
Operating environment (no condensation)	5 ~ 40°C, 25 ~ 85%	
Storage environment (no condensation)	-40 ~ 60°C, 10 ~ 90%	
Printer size/MM (length x width x height)	280×190×198	
PID	0x0512	0x0512
VID	0x1080	0x1081
Standard interface	USB+USB Host+Ethernet port+Serial port	USB+USB Host+Ethernet port+Serial port
Optional interface	WIFI/Bluetooth	WIFI/Bluetooth
Whether to support cutter (optional)	Full cut	Full cut
Whether to support stripping (optional)	yes	yes
CPU Specifications	400 MHZ, 32 bits, ARM9	400 MHZ, 32 bits, ARM9
buzzer	have	have