



UROVO D81R Series

Specifications



UROVO PTE. LIMITED

Specifications

	D81R Series	
Model	D812R	D813R
Resolution	203 DPI	300 DPI
Max. print width	104mm	108.4mm
Max. print length	1,000mm	1,000mm
Print Method	Thermal Transfer & Direct Thermal	
CPU	500 MHZ, 32 bits, COTEXT-M7	
RAM	8 MB PSRAM	
ROM	16 MB Flash Memory	
Interface	Built-in BT wireless transmission: 4.2 dual-mode BT, support iOS, Android, Windows and other systems connection (optional) Built-in wireless network: 2.4G or 5G (optional)	
Sensors	Head open sensor; Ribbon end sensor; Reflective sensor(moveable); Transmissive sensor(moveable);	
Power	Ex ternal universal switching power sup ply ; Inp ut: AC 100-240V, 2.5A, 50-60Hz. Output: DC 24V, 2.5A, 60W	
User Interface	power switch*1; button (Feed)*1; LED *5(Online blue, Error red, Ribbon green, Communication orange, Press-key white);	
Built-in fonts	8 dot matrix alphanumeric fonts. Vector font engine, need to download Vector Fonts (TTF) file.	
1 D Barcode	Code 11, Code 39, Code 93, Code 128 (subsets A, B, C), UPC-A, UPC-E, UCC-128, Codabar, EAN/JAN-8, EAN/JAN-13, Interleaved 2 of 5	
2D Barcode	QR Code, PDF417, Data Matrix	
Buzzer	Standard	
Rotation	Font and barcode support 0, 90, 180, 270 degree	
Printer language	Compatible to TSPL, EPL, ZPL, ZPL II	
Ribbon	Up to 300 m, OD 67 mm, 1" shaft (outer reel ribbon)	
Ribbon width	30 mm ~ 110 mm (1.18 inch ~ 4.3 inch)	
Media type	Continuous, die-cut, black mark, fan-fold (outside wound), On-metal tag support	
Media width	20~ 118 mm (0.7" ~ 4.6")	
Media thickness	0.06-1.3mm (2.36 ~ 10 mil)	
Media core diameter	25.4 mm (1")	

Label roll capacity	127 mm (5") OD
Label length	5 ~ 1,000 mm (0.2" ~ 40")
Physical dimension	190mm(W) * 198.3mm(H) * 280mm(D)
Operation Environment	+5 ~ +40°C, 25 ~ 85%(non-condensing)
Storage Environment	-40 ~ +60°C, 10 ~ 90%(non-condensing)

RFID (UHF)

RFID	读/写(UHF)
RFID	ISO18000-6C/EPC C1G2
	The minimum pitch length for On-Pitch labels is 15mm (0.625 inches)
	Optional compatibility with flexible anti-metal tags, with a thickness not exceeding 1.3mm
	Maximum RFID print speed: 4inch/s (print and write at the same time)
	Support UHF tag reading and writing, support chip type Ucode 7、UCODE 7xm-2k、UCODE 8、UCODE 9、Higgs9、Monza4E、M4i、MonzaR6-P、Monza4QT、MonzaM730、MonzaR6、MonzaR6-P、KM4Q、ONLY2, etc.
	Support one-click calibration or tool calibration, and automatically obtain the read and write power and position after calibration, which is convenient and effective.
	Support saving RFID configuration parameters. Replace calibrated labels on the same machine, and save the RFID configuration parameter settings without repeated calibration, saving time.
MODE	Support printing, reading and writing data at the same time, support only printing, support reading and writing different working modes
	Support reading the TID, EPC, TID+EPC data of the labels
	Support RFID password Lock/Unlock configuration
	Bad label automatically remarked during printing, support re-writing label quantity, re-writing chip times

Accessories

Accessories	Type
Standard accessories	Windows labeling software CD disk; Quick start guide; USB cable; Power cord; 1" ribbon spindle x 2 for 300M ribbon; External universal switching power supply