

DT610 Pro

Ultra-Rugged Mobile Computer



ARCore

Qualcomm



Meet the DT610 Pro

*The Next Generation
of Frontline Power*

DT610 Pro combines cutting-edge technology with enterprise-grade durability, purpose-built for mission-critical frontline operations. It integrates edge AI, next-generation connectivity, and rugged design to enable faster, smarter, and more efficient workflows.

Powered by the Qualcomm® Q-6690, its octa-core CPU is upgradeable up to 2.9 GHz, delivering high-performance edge AI for real-time tasks like OCR, speech, and computer vision—while ensuring future-ready scalability to protect your long-term investment.

With 5G, Wi-Fi 7, and 2x2 MU-MIMO, the DT610 Pro achieves up to 4.8x faster speeds, 4x lower latency, and 5x greater capacity compared to Wi-Fi 6. With Bluetooth 6.0 for short-range connectivity and CBRS support for private cellular networks, it ensures seamless, low-latency, multi-network connectivity for always-on operations.

Engineered for real-world use, it features a lightweight yet rugged design with IP68 protection, a high-brightness display, hot-swappable batteries, and advanced data capture capabilities, delivering uninterrupted productivity across every shift across industries such as logistics, warehousing, field service, and retail.

DT610 Pro — the next evolution of frontline productivity.

Product Highlights

Slim Design, Superior Protection

Featuring enhanced raised-edge protection (Higher Wall Protection) in a sleek form factor. At just 270g, it delivers effortless portability without compromising durability.

Purpose-Built for Extreme Conditions

With an IP68 rating for full dust and water protection, the device performs reliably in heavy rain and harsh industrial environments. Built for real-world durability, it withstands drops of up to 1.8 m across the full operating temperature range without a case, and is validated through 1,000 consecutive 1.0 m tumbles for exceptional shock resilience.

Breakthrough Enterprise Processor

Powered by the world’s first enterprise mobile processor with fully integrated UHF (RAIN) RFID capabilities, the DT610 Pro features an octa-core CPU up to 2.9GHz, 6 INT8 TOPS of on-device AI performance, and comes with Android 15 out of the box—delivering exceptional responsiveness for demanding workflows.

Next-Gen Wireless

Powered by 5G and Wi-Fi 7 (2×2 MU-MIMO) with 6 GHz support, the DT610 Pro delivers up to 4.8× faster speeds and expanded bandwidth for superior throughput. By comparison with Wi-Fi 6, it achieves 4× lower latency and 5× greater capacity, ensuring ultra-responsive performance in high-density environments.

Combined with Bluetooth 6.0 , it enables low-latency, multi-device connectivity with optimized power efficiency—keeping mission-critical operations running in real time.

Brilliant FHD+ Display

The 6-inch FHD+ screen (1080×2160) delivers sharp details, vibrant colors, and wide viewing angles. A 600-nit high-brightness panel ensures clear visibility even in bright sunlight, such as in a truck cab, with excellent readability in both portrait and landscape orientations.

Advanced Scan Camera with 3D Sensing Capabilities

DT610 Pro features a 50MP rear autofocus camera (PDAF) that captures clear, detailed images even in low light—ideal for visual documentation in logistics workflows. It enables accurate recording of package conditions upon arrival, including damage, moisture exposure, and deformation.

With ARCore support, it enables fast autofocus and multi-barcode scanning, while optional 3D sensing allows accurate volume measurement for inventory and shipping, enhancing warehouse efficiency and accuracy.

Choose Standard or Advanced Scanning

The FlexRange scan engine has a flexible working range -from 5cm to 10 m. Its impressive reading range and speed enable users to read barcodes without having to bend, stretch, or climb ladders, making scanning safer and more efficient.

The standard 1D/2D scan engine delivers fast, accurate barcode capture with stable performance in all lighting conditions, including bright sunlight.

AI-Powered Smart Battery Management Featuring Hot-Swap Flexibility

DT610 Pro features a 5500 mAh battery, delivering reliable full-shift endurance. AI-powered battery management dynamically optimizes efficiency.

Hot-swap support ensures uninterrupted operation, while its wide-temperature design guarantees stable performance in extreme conditions.

Dual-sided NFC

Supports dual-sided NFC reading, enabling fast and flexible interactions from any angle—ideal for logistics and warehouse operations, including quick payments, ID verification, and card emulation, while improving workflow efficiency and reducing handling time.

Biometric Security

A fingerprint sensor integrated into the power button enables instant, secure user authentication with a single touch.

Loud & Clear with Noise Cancellation

DT610 Pro is equipped with powerful front-facing stereo speakers delivering over 100dB loud output, ensuring clear communication even in noisy industrial environments. Combined with advanced noise reduction technology, it enables crystal-clear push-to-talk interactions for seamless coordination across teams and scenarios.

Integrated RFID

Equipped with Impinj Gen2X RFID, the DT610 Pro reads 50+ tags per second at distances up to 1.5 meters, enabling fast and accurate inventory and asset tracking. Ideal for warehouse management, retail stocktaking, and asset tracking, it streamlines operations with greater efficiency and reliability.

Visualized Fleet Management

UROVO UMS (Unified Management System) provides visualized management, enabling IT administrators to centrally manage multiple mobile devices from a single dashboard across different device types and operating systems. It supports shared device access control, application whitelisting and blacklisting, as well as granular user and device group permissions. From deployment to decommissioning, UMS streamlines device and smart battery lifecycle management, remote data wipe, and password policy enforcement—helping enterprises protect critical data while improving workforce productivity.

Streamlined Device Setup & Enterprise Management

UROVO U-Stage is designed to make device setup faster and simpler, helping customers get all their devices ready for use with minimal effort. By creating a staging file with the required configurations, settings, and applications, devices can be automatically set up through remote deployment, local file import, or QR code scanning—without manual procedures.

OEMConfig also integrates with enterprise EMM platforms, enabling customized policy deployment, permission control, and compliance management across devices.

Specifications

PERFORMANCE CHARACTERISTICS

CPU	Octa-core 2.0GHz/2.9GHz Antutu Score 1,114,080
Operating System	Android 15.0, Upgradable to Android 19
Memory	8 GB RAM / 128 GB UFS 12GB RAM / 256GB UFS(Optional)

PHYSICAL CHARACTERISTICS

Dimensions	169 mm L x 78.2 mm W x 15.8 mm D
Weight	270g
Display	6.0 inches 1080 x 2160, LCD,600 nits
Touchpanel	Multi-mode capacitive touch with bare or gloved fingertip input or stylus (sold separately), Corning Gorilla Glass; Water droplet rejection; Fingerprint resistant anti-smudge coating
Power	User replaceable battery Standard capacity 3.85V 5500mAh / 21.175Wh;Smart Battery Management
Hot swap	Support
Quick Charging	Optional
Expansion Slot	User-accessible microSD card up to 2 TB
SIM / SAM	Hybrid Dual SIM Slot (2 Nano SIM or 1 Nano SIM/1 Micro SD) - 2'nd Nano SIM is supported by micro SD Card Slot 2 Nano SIM or 1 Nano SIM and 1 e-SIM Dual SIM/Dual Standby
Interface	Rear: 8-pin communication I/O; Bottom: USB-C 3.1(support OTG,DP), 2-pin Charging Connector, 2-pin communication I/O
Notification	Audible tone ; Vibration; LED
Keypad & Button	On-screen keypad and Enterprise Keyboard; Power button; Volume up/down buttons; Dual-action side scan buttons; Programmable action button: Default to PTT
Voice and Audio	Two noise-canceling microphones; High-quality Single speaker phone; PTT headset USB-C support; Bluetooth wireless headset support, SWB & FB audio; cellular circuit switch voice; HD voice
PTT Hot Key	Programmable action buttons: Default to PTT

WIRELESS WAN DATA AND VOICE COMMUNICATION

Radio Frequency Band	Rest of World: 2G: 850/900/1800/1900 3G: B1/B2/B4/B5/B8 4G: B1/2/3/4/5/7/8/13/17/18/19/20/26/28/34/38/39/40/41/42/43; 5G:n1/2/3/5/7/8/20/28/38/40/41/77/78/79; North America: 3G: B2/4/5; 4G: B2/4/5/7/12/13/14/17/25/26/29/30/38/41/43/48/66/71; 5G FR1:n2/5/7/12/13/14/25/26/29/30/38/41/48/66/71/77/78; Dual SIM/Dual Standby, VoLTE, Gigabit LTE-A, 5G NR Sub-6 (NSA, SA), LTE/NR Carrier Aggregation, Supports CBRS, Private LTE
GPS	GPS, A-GPS, GLONASS, Galileo, BeiDou, QZSS, NavIC; Concurrent L1/G1/E1/B1 (GPS/QZSS, GLO, GAL, BeiDou) + L5/E5a/BDS B2a (GPS/QZSS, GAL, BeiDou); A-GPS; Supports XTRA ;SBAS

WIRELESS LAN

Radio	IEEE 802.11 a/b/g/n/ac/d/h/i/r/k/v/w/mc/ax/be; 2x2 MU-MIMO; Wi-Fi™ 7 (801.11be); Dual Band Simultaneous; IPv4, IPv6
Data Rates	6 GHz: 802.11ax/be—20 MHz, 40 MHz, 80 MHz, 160 MHz,320 MHz—up to 5764.7 Mbps; 5 GHz: 802.11a/n/ac/ax/be—20 MHz, 40 MHz, 80 MHz, 160 MHz—up to 2882.35 Mbps; 2.4 GHz: 802.11b/g/n/ax/be—20 MHz, 40 MHz up to 688.24 Mbps
Security and Encryption	WEP (40 or 104 bit); WPA/WPA2 Personal (TKIP, and AES); WPA3 Personal (SAE); WPA/WPA2 Enterprise (TKIP and AES); WPA3 Enterprise (AES),EAP- TTLS (PAP, MSCHAP,MSCHAPv2),EAP-TLS, PEAPv0-MSCHAPv2, PEAPv1- EAP-GTC , LEAP and EAP-PWD; WPA3 Enterprise 192-bit mode (GCMP-256)—EAP-TLS; Enhanced Open (OWE); WPA3-FT, SCV (Server Certificates Validation)

SENSOR

Light Sensor	Ambient Light
Other Sensors	Accelerator+ Proximity + Geomagnetic + Gyro

WIRELESS PAN

Bluetooth	Configurable Class 1 and 2, Bluetooth v6.0; Classic Bluetooth(BR/EDR) and Bluetooth LE
-----------	---

DATA CAPTURE

Scanning	Standard Range 1D/2D scan engine; FlexRange 1D/2D scan engine (Optional).
Camera	Rear: 50MP autofocus; Flash LED, PDAF; Torch mode; Front : 8MP Fixed, FF; AR Core Certification
NFC	ISO 14443 Type A and B; Sony FeliCa and ISO 15693 cards; Card Emulation via Host; Contactless payment support; MIFARE 1K/4K, MIFARE DESFire, ISO/IEC 18092 (Type F); Host Card Emulation ;Peer-to-Peer; Reader/Writer, ECP1.0 and ECP2.0 polling support; Apple VAS certified;
RFID	Built-In UHF RFID - Read Range : Up to 1.5 m - Read Rate : 50 tags/s
Biometrics	Fingerprint sensor integrated into the power button

USER ENVIRONMENT

Operating Temp	-20°C to 60°C / -4°F to 140°F
Storage Temp	-40°C to 70°C/ -40°F to 158°F
Humidity	5% to 95% non-condensing
Drop Spec	1.8 m/5.9 ft. drops to tile over concrete over operating temp (-20°C to 60°C/-4°F to 140°F) per MIL-STD 810H
Tumble Spec	1000 1.6 ft./0.5 meter tumbles at room temperature without Rugged boot 1000 1.6 ft./1 meter tumbles at room temperature with Rugged boot
Sealing	IP68
Vibration	12.2 g PK Sine (10 Hz to 55 Hz); 2.0 mm Double Amplitude (Constant Displacement); 60 minute duration per axis, 3 axis;
Thermal Shock	-40°C to 70°C(-40°F to 158°F)thermal shock; 12 cycles (1 cycle = 1 hour at -40°C and 1 hour at 70°C); 2-hour recovery at room temperature before inspection;
ElectrostaticDisch arge (ESD)	+/-15kVdc air discharge +/-8kVdc direct discharge +/-8kVdc indirect discharge

SOFTWARE SOLUTIONS

UEE Software Solutions	-Enterprise Management: Unified Management System (UMS) UStage Provisioning OEMConfig UTalk 2.0 PTT platform OTA / Firmware Update Management App Market -Device Productivity: ScanWedge RFIDWedge OCRWedge Key Mapping U-Browser Enterprise Launcher -Diagnostics & Maintenance: Log Capture WiFi Diagnostics Smart Battery Management -AI & Smart Tools: OCR Text Recognition AI Vision- Multibarcode AI Voice - Translingo/ Control
---------------------------	---

3rd Party Solutions Integration	EMM: SOTI Omniissa Workspace ONE(Airwatch) 42Gears safeUEM Industry Solutions: SAP Velocity (TE) P3finder TeamViewer
---------------------------------------	---

ACCESSORIES

Accessories	• RFID Sled • Charging cradle for DT610 PRO and RFG91 (1 DT610 PRO device with/without rugged case & 1 RFG91 device) • 5-slot charging cradle (4 DT610 PRO devices with/without rugged case & 4 RFG91 devices, with 4 DT610 batteries charging) • Single-slot charging cradle (1 DT610 PRO device with/without rugged case & 1 spare battery charging) • Single-slot Ethernet cradle (1 DT610 PRO device with/without rugged case & 1 spare battery charging) • Single-slot Ethernet and display cradle (1 DT610 PRO device with/without rugged case & 1 spare battery charging) • 5-slot charging cradle (5 DT610 PRO devices with/without rugged case) • 5-slot charging cradle (4 DT610 PRO devices with/without rugged case & 4 spare batteries charging) • 4-slot battery charger (4 DT610 PRO batteries) • Trigger Handle • Standard battery(5500mAh) • Rugged case • Wrist strap • Shoulder strap • Glass protective film • 18W(9V-2A) wall adapter + USB 2.0 Type C cable • 10W(5V/2A) wall adapter + USB 2.0 Type C cable
-------------	--

Industry & Applications



Retail

- Price and stock checks
- Order pickup handling
- Find in-store items
- Mobile checkout
- Customer assistance
- Shelf restocking
- Tag updates
- Inventory counts
- Staff scheduling
- Display planning
- Promotion checks
- Merchandising
- Backroom management



Field Service

- Asset tracking
- Parts inventory
- On-site billing
- Job scheduling



Delivery Staff

- Asset tracking
- Mobile billing
- Location tracking



Warehouse

- Sorting
- Loading
- Pickup

FOR MORE INFORMATION

UROVO PTE.LIMITED

urovo@urovo.com

en.urovo.com

1 Raffles Place, #21-01 One Raffles Place Tower
1, Singapore 048616

Urovo Europe

urovo@urovo.com

europe.urovo.com

de Maas 9, 5684 PL, Best, the Netherlands

Urovo North America

urovo@urovo.com

us.urovo.com

1990 Main Street, Suite 750, Sarasota, Florida
34236