



UROVO FR1000

Specifications



UROVO PTE. LIMITED



Specifications

Performance	Model	UROVO FR1000
	O.S.	Android 10.0
	Processor	Octa-core 1.6GHz
	Memory	RAM: 4GB ROM: 64GB
Basic specifications	Dimensions	180*128*28mm
	Display output	HDMI D Type interface; support 1920x1080P HD video output
	Interface	GPS antenna, main and auxiliary antenna for 4G communication, Wi-Fi/Bluetooth antenna, 4G communication Mini-SIM card slot, power interface DC JACK, USB interface, HDMI interface, TCPIP network interface RJ45(PoE+ supply mode), serial communication interface RS232 (DB9 Female), GPIO interface, debugging/download Micro-USB interface, USB interface * 2, system RESET button, SMA antenna interface ANT1~ANT8
Network Connections	Positioning	GPS + GLONASS or GPS + BeiDou
	Wi-Fi	Support 2.4G/5G dual-band Wi-Fi Wi-Fi network protocol: 802.11 a/b/g/n/ac Support WAPI & SMS4 encryption Support manual change of IPv6 addresses
	Bluetooth	Support BT5.0
Environment	Operating Temp.	-30 ~ +70°C
	Storage Temp.	-40 ~ +85°C
	Humidity	<95% (no condensation)
	Supply voltage	9 ~ 24V, typical value: 13.6V
	Working current	3A

Data Capture Specifications

RFID(UHF)

RFID	Read-write (UHF)
Frequency	840 ~ 960MHz (adjustable based on the requirements of different countries or regions)
Protocol	Support ISO18000-6C
RF output	Maximum: 33dBm
Receiving sensitivity	Minimum: -85dBm

Network Connections

GPS positioning

Positioning	Positioning parameters
Support mode	GPS + GLONASS or GPS + BeiDou

Frequency	GPS 1575.42 $\pm$ 1.023MHZ; GLONASS 1597.5~1605.8 MHZ; BDS 1561.098 $\pm$ 2.046MHZ;
Sensitivity	-163dBm

Wireless communication function

Wi-Fi	WLAN
Protocol	IEEE 802.11 b/g/n/a (2.4G/5G dual-band Wi-Fi)
Frequency	2.4G and 5G
Security and Encryption	Support WAPI & SMS4 encryption
Transmitting power	Pmax <20dBm

Bluetooth

Standard	Bluetooth parameters
Bluetooth features	BT5.0
Receiving sensitivity	DH5 -92dBm, 2-DH5 -91dBm, 3-DH5 -85dBm

Accessories

	Type
Optional accessories	4dBi - 12dBi Antenna