

K388Pro

Mobile Labeling Printer

*Support UHF
RFID Tag
Encoding
(Optional)

- **Ultra-compact 4-in-1 Design**
Integrated scanning, printing, peeling & labeling in a single device.
Achieve full labeling process in just 1.5 seconds for unmatched speed and precision
- **Professional-grade scanning engine with millisecond decoding speed**
Support 1D/2D codes scanning and printing, effortlessly replacing damaged or creased labels with greater speed and accuracy
- **High-performance data terminal**
Equipped with an Octa-core 2.4GHz Android terminal and a 5.5-inch large screen display for seamless and convenient operation
- **Precision narrow-width printing**
Providing 2" (50.8mm) professional printing width with 120mm/s ultra-fast speed. Quick-release paper magazine for forward/reverse label rolls



1D/2D Barcodes
Scanning



Print Speed - Up to
120 mm/s



Resolution: 203dpi
(8 pm / mm)



Automatic Label
Peeling



5.5-inch
Display



10.8V/3000mAh
(32.4Wh), support
hot-swap

K388Pro Mobile Labeling Printer

Specifications

UROVO

Printing Features

Printing Method: Thermal Direct
Print Width: ≤ 58 mm
Paper Thickness: 50–180 μm
Maximum Printing Speed: Up to 120 mm/s
Supply Roll Diameter: ≤ 60 mm
Supply Roll Thickness: 50–180 μm

Scanning

Professional scan engine,
support international standard 1D/2D
barcodes

CPU

Octa-core 2.4 GHz

Dimensions

Size: 185mm×85mm×137mm
Weight: 800g

Command Set

CPCL, ZPL, TSPL

O.S.

Android 14.0

Memory

RAM: 4GB, ROM: 64GB

Display

5.5 inch display
720*1440

Power Supply

Battery: 32.4 Wh (3000 mAh) / 10.8 V
rechargeable lithium-ion battery
Charging Method: Supports direct
charging or battery-only charging
Print Capacity per Charge: Up to 200
meters (at 12.5% black coverage)
Power Adapter: 5 V / 2 A
Support Hot-swap

Communication

Bluetooth: Class 2, Bluetooth v5.3 with
secondary BLE
Wi-Fi: Dual-band 2.4 GHz / 5 GHz
WLAN Standards: IEEE 802.11
a/b/g/n/ac/d/h/i/k/r/v/w/mc/ax
Wi-Fi Features: Supports Wi-Fi 6E, 2x2
MU-MIMO
Audio: 1 × Microphone, 1 × Speaker
Camera: Front 5 MP; Rear 13 MP with
flash

Environmental

Operating Temperature: -20°C to
+60°C
Storage Temperature: -40°C to
+70°C
Operating Humidity: 5% to 95% RH
(non-condensing)
Drop Specification: Multiple drops
from 1.5 m (5 ft.) to concrete at room
temperature
ESD Protection: ±15 kV (Air
discharge), ±8 kV (Contact
discharge)

RFID(UHF)

Support UHF RFID Tag
Encoding(Optional)

UROVO PTE. LIMITED

Website: en.urovo.com
Email: urovo@urovo.com
Address: 1 Raffles Place, #21-01 One Raffles Place Tower 1,
Singapore 048616

Urovo Europe

Website: europe.urovo.com
Email: sales-europe@urovo-emea.com
Address: de Maas 9, 5684PL, Best, the Netherlands

Urovo North America

Website: us.urovo.com
Email: urovo@urovo.com
Address: 1990 Main Street, Suite 750, Sarasota,
Florida 34236

*This page is subject to change
without prior notice