

K389

3-inch Mobile Printer



Meet the K389

*Engineered for Endurance,
Designed for Mobility.*

Built for demanding industrial and mobile environments, the K389 3-inch portable printer features an exclusive rugged casing that withstands 2-meter drops onto concrete, ensuring reliable performance in warehouse and manufacturing operations.

Designed for enterprise-grade workflows, it delivers consistent printing even under intensive daily use across logistics, field service, and industrial applications. Equipped with IEEE 802.11 a/b/g/n/ac (Wi-Fi 5) dual-band connectivity (2.4 GHz / 5 GHz), it enables fast, stable, and low-latency wireless communication for seamless system integration and uninterrupted printing.

A high-capacity 3200mAh battery provides up to double the runtime of previous models, supporting extended shifts with ease.

With robust durability, long-lasting power, and advanced wireless performance, the K389 ensures continuous connectivity and maximized productivity where it matters most.

Product Highlights

Engineered for Endurance: The Rugged Mobile Printer

The K389 sets a new standard for resilience, purpose-built for the toughest manufacturing and warehouse environments. Featuring an exclusive protective casing, it withstands 2-meter drops onto concrete from any angle, ensuring reliable operation through the most demanding shifts.

Compact Design for On-the-Spot Printing

Maximize efficiency with true mobility. The K389, weighing only 390g, is engineered for portability. Carry it effortlessly throughout your shift to instantly print labels where and when you need them—eliminating unnecessary movement between picking locations and printers, and accelerating workflows in fast-paced warehouse environments.

Double the Shift, Single Charge

Maximize productivity with uninterrupted power. The K389 houses a high-capacity 3200mAh battery paired with intelligent power management, delivering up to double the runtime of previous models. It powers the longest workday without fail.

Seamless Connectivity for a Mobile Workforce

Stay connected and in sync. The K389 delivers robust, reliable wireless connectivity tailored for industrial environments, supporting 802.11ac dual-band Wi-Fi (2.4GHz/5GHz), WPA/WPA2 security—ensuring a stable, secure connection as your team moves seamlessly across the facility.

High-Speed Mobile Printing with Precision

Delivering fast and reliable output for high-demand mobile printing scenarios, the device achieves a maximum print speed of up to 100 mm/s enabling efficient processing of labels and receipts in time-critical operations. Combined with 203 dpi (8 dots/mm) high-resolution printing, it ensures sharp, legible barcodes, text, and graphics even at high throughput.

Specifications

PERFORMANCE CHARACTERISTICS

CPU(MCU)	Single-core 32-bit LX7 microprocessor, up to 240 MHz
Memory	2/16 MB(SPI RAM), 128MB ROM(NAND FLASH)

PHYSICAL CHARACTERISTICS

Dimensions	115 mm L x 115 mm W x 58 mm D
Weight	390g(Including battery, excluding paper roll)
Display	0.91 inches, 128 × 32, OLED (passive matrix), 150 nits
Power	User replaceable battery standard capacity 7.2V 3200mAh / 23.04Wh
Hot swap	Support
Charging Time	2.5 hours(with 5V/2A)
Standby Time	200~ 260 hours(only BT communication)
Interface	USB-C 2.0*1
Notification	Audible tone ; LED
Keypad & Button	Power button; Setting buttons; Paper feed button
Voice and Audio	High-quality single buzzer

PRINTER CHARACTERISTICS

Maimum Printing Length	Over 130m(12.5% print density)
Minimum Print Width	72mm
Maimum Printing Speed	100mm/s (12.5% print density)
Resolution	203 dpi (8 dots/mm)
Printhead Life	150 km (at 12.5% or lower dot density) / per dot: 100 million pulses (at 25°C)

BARCODE SYMBOLOGIES

Barcode Symbologies	1D barcode: CodaBar, Code39, Code128, Code93, ITF, EAN-8, EAN-13, UPC-A, UPC-E 2D barcode: QRCode, PDF417, and DataMatrixFonts and Graphics
---------------------	--

PROGRAMMING LANGUAGES

Programming Languages	CPCL , ZPL , EPL , TSPL , ESC-POS
-----------------------	-----------------------------------

FONTS

Bitmap Fonts	3 bitmap fonts(SimSun)
Scalable Fonts	3 scalable fonts(Terminus, Source Han Serif, Source Han Sans)

WIRELESS LAN

Radio	IEEE 802.11 a/b/g/n/ac; Wi-Fi 5; Dual Band (2.4GHz/5GHz); Support 802.11r roaming
Data Rates	5 GHz: 802.11a/n/ac—20 MHz, 40 MHz, 80 MHz—up to 866.7 Mbps; 2.4 GHz: 802.11b/g/n—20 MHz, 40 MHz up to 300 Mbps
Security and Encryption	WEP (64 or 128 bit); WPA-PSK (TKIP, and AES); WPA2-PSK (TKIP, and AES); IPv4, TCP/UDP/FTP/HTTP, WebSocket/MQTT

WIRELESS PAN

Bluetooth	Configurable class 2, Bluetooth V2.1+4.0(BLE); Classic Bluetooth(BR/EDR) and Bluetooth LE
-----------	---

SENSOR

Sensors	Black mark & gap media sensor; Printhead temperature sensor; Cover open sensor(hall sensor)
---------	---

MEDIA CHARACTERISTICS

Media Width	25mm-80mm
Maimum Media Roll Size	50mm OD
Thickness	50~180μm
Media Types	Liner labels, receipt paper

USER ENVIRONMENT

Operating Temp	-10°C to 50°C / 14°F to 122°F
Storage Temp (Ecept Battery)	-20°C to 70°C / -4°F to 158°F
Storage Temp(Battery)	-5°C to 35°C / 23°F to 95°F
Humidity(Operati ng)	20%-85% non-condensing
Humidity(Storage)	5%-95% non-condensing
Drop Spec	2.0 m/6.6 ft. drops to tile over concrete over operating temp (-10°C to 50°C/14°F to 122°F) per MIL-STD 810H
Electrostatic Discharge (ESD)	+/-15kVdc air discharge(Level C) +/-8kVdc direct discharge(Level C) +/-8kVdc indirect discharge(Level C)

OTHER CHARACTERISTICS

Charging Method	Charge while in standby (supports charging during operation)
Paper Loading	Clamshell paper loading
Cover Opening	One-touch cover opening
Cutting Method	Manual tear-off
Status Indication	OLED display: communication mode, printing status, out of paper, cover open, low battery, sleep mode
Power Saving Mode	Auto-sleep & Auto-wake

ACCESSORIES

Accessories	• Belt clip • Shoulder strap • Printhead • Standard battery(3200mAh) • 10W(5V/2A) wall adapter + USB 2.0 Type C cable
-------------	---

Industry & Applications



Retail

Shelf Labeling
Relabeling
Return Labels



Manufacturing

Pick and Pack Labels
Raw Materials
Finished Goods



Warehouse

Shipping/Receiving
Put Away
Inventory Management
Cycle Count
Picking
Staging
Packing
Reverse Logistics



Transportation and logistics

Shipping/Receiving
Cross-Docking

FOR MORE INFORMATION

UROVO PTE.LIMITED

urovo@urovo.com

en.urovo.com

1 Raffles Place, #21-01 One Raffles Place Tower
1, Singapore 048616

Urovo Europe

urovo@urovo.com

europe.urovo.com

de Maas 9, 5684 PL, Best, the Netherlands

Urovo North America

urovo@urovo.com

us.urovo.com

1990 Main Street, Suite 750, Sarasota, Florida
34236