

RFG91

Handheld UHF RFID Sled



RFG91 Stand Alone



Magnetic Version



Universal Version



DT610 Version



Meet the RFG91

*Lighter, Smarter, Faster –
Power in Your Hands*

Urovo RFG91 is a high-performance UHF RFID sled that transforms smartphones and mobile computers into professional-grade RFID readers. Powered by the Impinj E710 chip and supporting Impinj Gen2X, it delivers fast and accurate data capture for applications such as cycle counting, asset tracking, and inventory management.

Weighing just 390g, the RFG91 features a lightweight, ergonomic design for efficient mobile use, with seamless connectivity across PDAs, smartphones, and computers. The RFG91 Series offers four flexible form factors—Standard, Magnetic, POGO PIN, and Universal—supporting multi-platform compatibility (Android, iOS, Windows) and fast pairing via NFC, Bluetooth, and QR codes.

With versatile mounting options and high-performance RFID capabilities—up to 1300+ tags/sec and 15m+ read range—it provides a scalable and efficient solution for modern mobile data collection.

It is ideally suited for industries such as retail, warehousing and logistics, manufacturing, healthcare, and asset-intensive enterprises, enabling faster, more accurate, and more efficient field data operations.

Product Highlights

Professional and Versatile Data Collection

All-in-one RFID reading and barcode scanning, three data collection modes, one-click to switch, transforming your phone into a professional data collection device.

Outstanding RFID Performance

Equipped with the Impinj E710 chip and supporting Impinj Gen2X, it delivers a faster RFID reading rate of 1300+ tags per second and a longer reading range of over 15 meters, enabling fast and accurate inventory and asset tracking. Ideal for large-scale cycle counting scenarios such as high-bay warehouses, apparel distribution centers, and e-commerce logistics hubs.

Versatile Compatibility

The RFG91 seamlessly connects with devices running Android, iOS, Windows, and more. It supports three fast pairing modes – NFC tap-to-pair, Bluetooth search, and barcode scanning, ensuring quick and effortless setup.

Multiple Versions for Flexibility

The RFG91 Series offers four versatile form factors to adapt to diverse field scenarios.

Standard – RFID + barcode scanning with quick NFC/Bluetooth/QR pairing.

Magnetic – Strong magnetic mount for fast, tool-free attach/detach.

POGO PIN – RFG91 with DT610 extends RFID from short to long range, With 1,300+ tags/sec and 15m+ range.

Universal – Adjustable telescopic design for wide device compatibility. Efficient. Versatile. Built for the field.

Lightweight & Ergonomic

Weighing just 390g, it is designed for all users. The ergonomic design ensures comfort during extended use, reducing physical fatigue by 35% during long shifts and minimizing errors caused by worker fatigue.

Industrial-Grade Durability

Built with industrial-grade durability, the RFG91 is IP54 rated for dust and water resistance (upgradable to IP67) and designed to withstand 1.5m drop resistance, 0.5m tumble tests, 1 million scan button presses, and 10 million handle trigger operations. It is well-suited for harsh environments such as dusty or humid warehouses, outdoor logistics, and sorting operations, ensuring reliable performance in demanding field conditions.

Extended Battery Life

The RFG91 features flexible battery options, including a standard 4900mAh removable battery and an optional 6700mAh high-capacity battery, supporting up to 8-12 hours of continuous operation.

Comes with 1-slot cradle and 4-slot cradle which enable you to charge the RFG91 by itself, the mobile computer by itself, and both simultaneously.

AI-Powered Smart Battery Management Featuring Secure Battery Locking Foot

Equipped with AI-powered battery management for real-time monitoring, improved lifespan, and enhanced safety, combined with a low power consumption design for extended field use. A secure battery locking system ensures stable and reliable attachment during operation, delivering consistent and efficient power support for demanding mobile and industrial applications.

RFIDWedge

RFIDWedge is a no-code RFID input tool that delivers tag data into any application without integration, enabling fast deployment and flexible data control.

Specifications

PHYSICAL CHARACTERISTICS

Dimensions	147.7 mm L x 141.7 mm W x 80 mm D
Weight	390g
Power	User replaceable battery Standard capacity 3.6V 4900mAh / 18Wh;option : 6700mAh / 25.2Wh; Smart Battery Management
Notification	Audible tone ; Vibration; LED
Keypad & Button	Trigger, Power button; BT button; Mode button(or self-definition)
Voice and Audio	Bottom Buzzer; 1*Power, 2*Decode Status, 1* Bluetooth status, 1* Mode Indication

WIRELESS PAN

Bluetooth	BT5.0+ BLE. Supports NFC tap-to-pair for quick Bluetooth pairing with a single tap
-----------	--

SENSOR

Scanning	Default: Y3010 1D/2D Scan Engine Optional: Configuration without scan engine
----------	---

RFID PERFORMANCE

Standards Supported	EPC Class 1 Gen 2 EPC GEN2 V2, Gen2 X
Fastest Read Rate	1,300+ Tags/sec
Nominal Read Range	49+ ft./ 15+ m
Frequency Range / RF Output	US: 902-928MHz; 0 — 30 dBm EU: 865-868MHz; 0 — 30 dBm EU: 915-921MHz; 0 — 30 dBm Japan: 916-921MHz; 0 — 30 dBm
RFID Chipset	Impinj E710

USER ENVIRONMENT

Operating Temp	-20°C to 50°C / -4°F to 122°F
Storage Temp	-40°C to 70°C / -40°F to 158°F
Humidity	5% to 95% non-condensing
Drop Spec	1.5 m/6 ft. drops to tile over concrete over operating temp (-20°C to 50°C/-4°F to 122°F)
Tumble Spec	1000 1.6 ft./0.5 meter tumbles at room temperature without Rugged boot
Sealing	IP54 (upgradable to IP67)
ElectrostaticDischarge (ESD)	+/-15kVdc air discharge +/-8kVdc direct discharge +/-8kVdc indirect discharge

ACCESSORIES

Accessories	• Single-slot charging cradle (1 RFG91 device or 1 RFG91 device & 1 DT610 with rugged case or DT610 Pro without rugged case). • 4-slot battery charger (standard batteries or extended batteries). • 5-slot charging cradle (5 RFG91 devices or 5 RFG91 devices & 5 DT610 with rugged case or DT610 Pro without rugged case) • 5-slot charging cradle (4 RFG91 devices or 4 RFG91 devices & 1 DT610 with rugged case or DT610 Pro without rugged case & 4 spare RFG91 standard or extended batteries charging) • 5-slot charging cradle (3 RFG91 devices or 3 RFG91 devices and 3 DT610 with rugged case or 3 DT610 Pro without rugged case, and 4 spare RFG91 standard or extended batteries, and 4 spare DT610/DT610 Pro standard or extended batteries) • Magnetic universal Bluetooth adaptor • Universal Bluetooth adaptor • Adaptor for use with DT610 with rugged case (connect by pogopin) • Adaptor for use with DT610 Pro without rugged case (connect by pogopin) • Wrist strip • Standard battery(4900mAh) • Extended capacity battery(6700mAh) • 5V/2A (10W)wall adapter + USB 2.0 Type C cable
-------------	--

Industry & Applications



Retail

Cycle Counting
Item Finding / Locationing
Returns
Back-of-store
Backroom Management
Receiving
Food Safety and Traceability



Healthcare

Medication Administration
Pharmacy Management and Tracking
Hospital Asset Management and Tracking



Warehouse

Inventory Cycle Counting
Item Tracking/Locationing
Receiving/Shrink Control



Transportation and logistics

Inventory cycle count
Loading verification
Inbound/outbound validation



Manufacturing

Product and component tracking
Semi-finished product

FOR MORE INFORMATION

UROVO PTE.LIMITED

urovo@urovo.com

en.urovo.com

1 Raffles Place, #21-01 One Raffles Place Tower
1, Singapore 048616

Urovo Europe

urovo@urovo.com

europe.urovo.com

de Maas 9, 5684 PL, Best, the Netherlands

Urovo North America

urovo@urovo.com

us.urovo.com

1990 Main Street, Suite 750, Sarasota, Florida
34236