



UROVO S710

2D Barcode Scanner

Specifications



UROVO Technology Co., Ltd.



Specifications

Basic characteristics	Operation System	Compatible with Windows, Android and Linux systems
	Processor	32bit ARM processor
	Camera	640(H) x 480(V) CMOS
	Viewing Angle	Horizontal 31°
	Skew/Pitch/Roll	Roll 360°, Skew±55°, Pitch±55°
	Decode Ability	Support mainstream 1D/2D barcodes, including EAN, QR, GS1...etc.
		Support barcodes on tags, monitors and mobile devices
	Reading Distance	Support all payment codes, electronic tags, coupons, and color barcodes on the mobile devices
		EAN13: 4.0~20.0cm(13mil)
		Code128: 4.5 ~ 25.0cm(15mil)
		Code39: 4.5~9.5cm(5mil)
		QR Code: 4.0 ~ 18cm (15mil)
	Operating Voltage	USB 5V
	Operating Current	125mA, standby current 25mA
	Weight	185g (including USB cable)
Interfaces	Cable Length	1.8M
	Dimension	110mm(L) x 71mm(W) x 158mm(H)
Environmental	Material	ABS
	Interfaces	Support USB-HID, USB Virtual Serial Port, USB HID-KBW(default)
	Operating Temperature	-20°C ~ 60°C
	Storage Temperature	-40°C ~ 70°C
	Humidity	5%RH~95%RH (non-condensing)
	Vibration	5~200Hz, 10G rms, 3-axes, 1.5Hr
	Drop	1.5M drops on concrete