

Fuzzy rho-calculus: a quantale-graded interaction, and its lift to ci GSLTs with binding

A working note

June 4, 2026

Abstract

We present a concise axiomatization of a fuzzy rho-calculus and a minimal model: the comm rule transmits not Q but $(u \circ x) * Q$, where $u \circ x$ is a quantale element measuring the match between the two interaction surfaces and $a * (-)$ is its action on terms. We compute the model in full, show that the order axiom is a *theorem* there (modulo one congruence side-condition isolated as a lemma), and observe that the model commits to an *accumulator* reading of $\circ$, with a dual *attenuator* reading available. We then sketch the intended payoff: this is the binding-free, asymmetric, single-surface instance of a general construction — a quantale-graded interaction in a continued-interactive GSLT — and identify what each ingredient must become once continuations carry binding, in both the asymmetric (“usual suspects”) and the symmetric (unification/fusion) cases. The slogan that emerges: the comparison $\circ$ is *imposed* in flat rho but *generated* by unification in the symmetric lift, where A is (a quotient of) the substitution lattice and $\circ$ is mgu.

1 Recap: rho and its fuzzification

Recall the reflective syntax of the rho-calculus [1], with processes P and names x mutually defined, and the single structural reduction (comm):

$$P, Q ::= \mathbf{0} \mid \text{for}(y \leftarrow x)P \mid x!(Q) \mid P \mid Q \mid *x, \quad x, y ::= @P,$$

$$\text{for}(y \leftarrow x)P \mid x!(Q) \longrightarrow P\{ @Q/y \}.$$

Here $@P$ quotes a process to a name and $*x$ drops a name back to a process; we write $\bar{x}$ for the dereference, or unquote (also written $\#x$), so $@\bar{P} = P$ and $@\bar{x} = x$.

The fuzzy data. Fuzzification is purely semantic. One adds

$$(-*-): A \times \text{Proc} \rightarrow \text{Proc} \quad (\text{action of grades on processes}), \quad (-\circ-): \mathbf{N} \times \mathbf{N} \rightarrow A \quad (\text{surface comparison}),$$

and replaces strict channel equality in comm by a graded comm in which the transmitted term is modulated by how well the two channels match:

$$\text{for}(y \leftarrow x)P \mid u!(Q) \longrightarrow P\{ @((u \circ x) * Q) / y \}. \quad (1)$$

Read $u \circ x$ as “how closely u and x match” and $(u \circ x) * Q$ as “the part of (the information in) Q that gets through.” Classical rho is the special case where $\circ$ returns a unit grade on a perfect match and $a * (-)$ is then the identity.

The grade structure. We demand that A carries a quantale structure [5, 6] $(A, \leq, \otimes, \mathbf{1})$ — a complete lattice with an associative product $\otimes$ that distributes over arbitrary joins — and a *measure*

$$\mu: \text{Proc} \rightarrow A,$$

subject to the

$$\text{Order axiom. } a_1 \leq a_2 \implies \mu(a_1 * P) \leq \mu(a_2 * P).$$

A bigger match grade must read off as at least as much transmitted information.

2 The model

The minimal model takes grades to be names themselves and realises every piece through quote/par/dereference:

$$\begin{aligned} A &= \mathbf{N}, & x_1 \circ x_2 &= @(\overline{x_1} \mid \overline{x_2}), \\ \mu(P) &= @P, & a * P &= P\{ (a \circ z)/z : z \in \text{FN}(P) \}. \end{aligned} \quad (2)$$

The product is par-under-quote, the unit is $@\mathbf{0}$ (since $P \mid \mathbf{0} \equiv P$), the order is sub-multiset inclusion of par-components, and joins are componentwise suprema of multiplicities. Par is the *product*, not the join; that distribution of $+$ over $\max$ is exactly what makes this a quantale rather than a mere monoid.

2.1 Unfolding the action

Fix u, x and Q with $\text{FN}(Q) = \{z_1, \dots, z_k\}$. Put $a = u \circ x = @(\overline{u} \mid \overline{x})$, so $\overline{a} = \overline{u} \mid \overline{x}$. For each z_j ,

$$a \circ z_j = @(\overline{a} \mid \overline{z_j}) = @(\overline{u} \mid \overline{x} \mid \overline{z_j}).$$

Hence the action is a uniform *re-channelling*, never a deletion:

$$(u \circ x) * Q = Q\{ @(\overline{u} \mid \overline{x} \mid \overline{z})/z : z \in \text{FN}(Q) \}. \quad (3)$$

Every channel z on which Q acts is stamped with the *match signature* $\overline{u} \mid \overline{x}$ of the redex; the whole term structure of Q survives intact.

2.2 The two redexes

With the example's orientation (input on u_i , output on x_i ; commutativity of $\circ$ makes the orientation immaterial, since $@(\overline{u} \mid \overline{x}) \equiv @(\overline{x} \mid \overline{u})$), equation (3) gives

$$\begin{aligned} \text{for}(y \Leftarrow u_1)P \mid x_1!(Q) &\longrightarrow P\{ @(\overline{Q}\{ @(\overline{u_1} \mid \overline{x_1} \mid \overline{z})/z \})/y \}, \\ \text{for}(y \Leftarrow u_2)P \mid x_2!(Q) &\longrightarrow P\{ @(\overline{Q}\{ @(\overline{u_2} \mid \overline{x_2} \mid \overline{z})/z \})/y \}. \end{aligned}$$

The two residuals differ in exactly one place: the signature $\overline{u_1} \mid \overline{x_1}$ versus $\overline{u_2} \mid \overline{x_2}$ stamped into every channel of Q .

2.3 The order axiom is a theorem here

Lemma 1 (Congruence side-condition). *Let the order $\leq$ on $A = \mathbf{N}$ be the least pre-congruence for the rho operators with $@\mathbf{0}$ as bottom (equivalently: sub-multiset inclusion at the top level, propagated through prefixes $\text{for}(\cdot)$, par , output , and quote). Then name-substitution into a fixed context is monotone: $a \leq a'$ implies $C[a] \leq C[a']$ for every term context C .*

The point of Lemma 1 is that a prefix $\text{for}(y \Leftarrow x)P$ is a single molecule; sub-multiset comparison at the top level alone does *not* push through it, and without congruent propagation the monotonicity below leaks precisely at the binders.

Proposition 1 (Grade monotonicity). *In the model (2) with the order of Lemma 1, the order axiom holds. Consequently, if $\bar{u}_1 \mid \bar{x}_1 \sqsubseteq \bar{u}_2 \mid \bar{x}_2$ then $\mu((u_1 \circ x_1) * Q) \leq \mu((u_2 \circ x_2) * Q)$, i.e. the redex with the larger match signature carries at least as much information into the residual.*

Proof. $\circ$ is $+$ on multisets, hence monotone in each argument; by Lemma 1 substitution of a $\leq$ -larger grade into the fixed context $Q\{(-)/z\}$ yields a $\leq$ -larger term, so $(u_1 \circ x_1) * Q \sqsubseteq (u_2 \circ x_2) * Q$. Applying $\mu = @(-)$, which is monotone by construction, gives the claim. The order axiom is the same statement with $u \circ x$ abstracted to a free grade a . $\square$

So in this model monotonicity is not an extra demand but a consequence of $\circ$ being the (monotone) quantale product and μ a monotone reading of it.

2.4 What kind of “fuzzy” is this? Accumulator vs. attenuator

Remark 1 (The model commits to an accumulator). With $\circ = @(\bar{u} \mid \bar{x})$ the construction is an *accumulator*, not an *attenuator*:

- it never deletes any of Q — by (3) the action only renames channels, so all term structure of Q always survives;
- $u \circ x$ grows when *either* side is large, regardless of overlap, so it measures combined bulk, not similarity;
- even a perfect match $u = x$ gives $u \circ x = @(\bar{x} \mid \bar{x})$, a doubling — a *watermark*, not the identity. Classical rho is recovered only at $u = x = @\mathbf{0}$.

If one wants the literal “distance/attenuation” reading — perfect match transmits cleanly, mismatch transmits less — the natural swap is the multiset *meet* $u \circ x = @(\bar{u} \wedge \bar{x})$, the shared sub-process. Then $u \circ x$ grows with genuine overlap, and because *meet* can map distinct channels $@Z_j$ to a common stamped name, channels can *collapse*: attenuation as lost distinguishability rather than lost terms. Meet over multisets is still a (frame-like) quantale and $\mu = @(-)$ stays monotone, so nothing breaks.

Remark 2 (A foretaste of the lift: mgu vs. lgg). The fork in Remark 1 is not ad hoc. In the subsumption order on terms, the accumulator (“keep everything from both surfaces”) is aligned with *unification* [7] — the most general common *instance*, mgu — while the attenuator (“keep only what is shared”) is aligned with *anti-unification* [8, 9] — the least general common *generalization*, lgg. These are dual operations in the same lattice. Section 3 takes this seriously: when continuations carry binding and interaction is symmetric, the comparison $\circ$ is a (anti-)unifier and need not be invented.

3 Lifting to ci GSLTs with binding

Flat rho is convenient because $\text{FN}(P)$ is a bare set of names and the action (2) is just a name-substitution over that set. In a continued-interactive GSLT a *language* is presented by a grammar (sorts/operations, some of which bind), equations (structural congruence), and rewrites (reduction) [2, 3, 4], and the continuation in an interaction redex *carries binding structure*. The whole graded apparatus must be reread inside the category of terms-with-binding — nominal sets / a presheaf category over name-contexts, or de Bruijn families [14, 15, 16]. We list what each of the three ingredients becomes.

3.1 (i) The action becomes a graded action respecting binders

$a * (-)$ is no longer a flat substitution but an A -graded, capture-avoiding endofunctor on the term presheaf. The defining law is that it commutes with the binding (context-extension) functor: for any binder $\nu y. P$,

$$a * (\nu y. P) = \nu y. (a' * P),$$

where a' is a transported across the binder (in nominal terms, a taken with support away from y , α -renaming as needed). This transport law is the precise content of “continuations have binding structure.” The order axiom lifts unchanged in statement: $*$ is a lax action of the quantale (functorial and monotone in A), in the sense of graded monads [17], and μ a lax monotone measure, whence *fuzzy reduction is grade-monotone* — now internal to the presheaf category.

3.2 (ii) The comparison $\circ$: subject-matching vs. unification

Asymmetric case (the usual suspects: λ [11], π [10], rho). There is a privileged binding surface. The surfaces are a subject pair (the input channel x , the output channel u); $\circ$ compares subjects, $u \circ x \in A$; and the action modulates the transmitted term before a *one-directional* graded substitution into the binder body, exactly as in (1). This is a near-verbatim lift: only the substitution becomes the presheaf’s capture-avoiding one, and the action must be transported under any binders occurring inside the transmitted term.

Symmetric case (fusion/solos via unification). There is no privileged binder. Both surfaces present terms with (meta)variables, and the reaction is a *fusion* [12, 13]: it computes a unifier $\sigma = \text{mgu}(\text{surface}_1, \text{surface}_2)$ and applies σ to *all* continuations in scope, each application a graded action. The grade is read off the unifier,

$$\circ(\text{surface}_1, \text{surface}_2) = \text{grade}(\sigma) \in A,$$

with natural choices ranging from the crudest two-element quantale $\{\top \text{ if unifiable, } \perp \text{ otherwise}\}$ (“fuzzy” = “does it react at all”) to a rich quantale built from the *substitution lattice* — substitutions ordered by instantiation, mgu as its meet/join — with $\text{grade}(\sigma)$ a monotone invariant such as the number of equations discharged, the term-size of σ , or μ of the substituted material.

This is the conceptual payoff. In flat rho the comparison $\circ$ had to be *imposed* as extra structure (par-under-quote). Under symmetric interaction it is *generated*: the substitution lattice already is the requisite ordered structure, mgu already is its meet/join, so A may be taken to be (a quotient of) that lattice and $\circ$ to be mgu itself. The intuition “how far apart u and x are” then becomes literal — the *unification distance*: how much the mgu had to do to make the surfaces agree, or whether they agree at all. Dually (Remark 2), the attenuator/meet variant is realised by anti-unification: $\circ = \text{lgg}$ keeps the shared skeleton of the two surfaces, the symmetric surface of the $@(\bar{u} \wedge \bar{x})$ swap.

3.3 (iii) Side conditions: scope extrusion as a precongruence law

Fusion extrudes scope: a fused name may sit under a restriction, and σ must respect it (the classical fusion side-condition — do not fuse names trapped under conflicting binders; push the restriction outward instead). The graded version adds a stability requirement that is the symmetric analogue of Lemma 1:

$\text{grade}(\sigma)$ must be stable under α -conversion and scope extrusion,

i.e. computing the grade before and after pushing a ν outward must agree (up to the action’s transport law). Equivalently, the order on A must be a pre-congruence for the binders, not merely for par; otherwise grade-monotonicity leaks exactly at the binders — the same failure Lemma 1 forecloses in the flat, top-level case.

4 Summary and open ends

Summary. Fuzzy rho is the binding-free, asymmetric, single-surface, par-quote instance of one construction: a quantale-graded interaction in a ciGSLT, with the grade obtained by comparing interaction surfaces (subject-matching when asymmetric, (anti-)unification when symmetric), acting capture-avoidingly on continuations, and grade-monotonicity guaranteed by a precongruent order. The two warm-up redexes of §2 are the shadow this construction casts when binding is trivial and the comparison is par.

Open ends.

1. Which monotone invariant of the mgu yields a μ for which grade-monotonicity says something about *genuinely transmitted* information, rather than mere substitution bulk?
2. Make the mgu/lgg duality of Remark 2 a precise adjunction between the accumulator and attenuator gradings, internal to the substitution lattice.
3. Reading the grade as a potential on the reduction graph (the energetics picture), is grade-monotonicity along reduction a second-law-flavoured statement, and does the precongruence condition correspond to a conservation law at the binders?

References

- [1] L. G. Meredith and M. Radestock. A reflective higher-order calculus. *Electronic Notes in Theoretical Computer Science*, 141(5):49–67, 2005. DOI: 10.1016/j.entcs.2005.05.016.
- [2] L. G. Meredith and M. Radestock. Namespace logic: A logic for a reflective higher-order calculus. In *Trustworthy Global Computing (TGC 2005)*, volume 3705 of *LNCS*, pages 353–369. Springer, 2005.
- [3] C. Williams and M. Stay. Native type theory. In *Applied Category Theory (ACT 2021)*, volume 372 of *EPTCS*, pages 116–132, 2022. DOI: 10.4204/EPTCS.372.9. Derives a type system from a language’s presentation by passing to its presheaf topos (rho among the worked examples).
- [4] L. G. Meredith. Generative spatial logic types (GSLT) and METTAIL: languages as types, equations, and rewrites. Working notes / preprint, F1R3FLY.io. *[author to supply final reference]*.

- [5] C. J. Mulvey. &. *Rendiconti del Circolo Matematico di Palermo*, Series II, Supplement 12:99–104, 1986.
- [6] K. I. Rosenthal. *Quantales and Their Applications*. Volume 234 of Pitman Research Notes in Mathematics. Longman Scientific & Technical, 1990.
- [7] J. A. Robinson. A machine-oriented logic based on the resolution principle. *Journal of the ACM*, 12(1):23–41, 1965.
- [8] G. D. Plotkin. A note on inductive generalization. *Machine Intelligence*, 5:153–163, 1970.
- [9] J. C. Reynolds. Transformational systems and the algebraic structure of atomic formulas. *Machine Intelligence*, 5:135–151, 1970.
- [10] R. Milner, J. Parrow, and D. Walker. A calculus of mobile processes, I and II. *Information and Computation*, 100(1):1–77, 1992.
- [11] H. P. Barendregt. *The Lambda Calculus: Its Syntax and Semantics*. Volume 103 of Studies in Logic. North-Holland, revised edition, 1984.
- [12] J. Parrow and B. Victor. The fusion calculus: Expressiveness and symmetry in mobile processes. In *LICS 1998*, pages 176–185. IEEE, 1998.
- [13] C. Laneve and B. Victor. Solos in concert. *Mathematical Structures in Computer Science*, 13(5):657–683, 2003.
- [14] M. J. Gabbay and A. M. Pitts. A new approach to abstract syntax with variable binding. *Formal Aspects of Computing*, 13(3–5):341–363, 2002.
- [15] A. M. Pitts. *Nominal Sets: Names and Symmetry in Computer Science*. Volume 57 of Cambridge Tracts in Theoretical Computer Science. Cambridge University Press, 2013.
- [16] M. Fiore, G. Plotkin, and D. Turi. Abstract syntax and variable binding. In *LICS 1999*, pages 193–202. IEEE, 1999.
- [17] S. Katsumata. Parametric effect monads and semantics of effect systems. In *POPL 2014*, pages 633–645. ACM, 2014.