Breaking the Validator Stall Loop

Cost-accounted order-then-execute, built on the cost-accounting papers: analysis, design, throughput model, and the path to a working branch

F1R3FLY.io — design document, revision 6

October 29, 2026

Repository	`F1R3FLY-io/f1r3node-rust`
Code basis	`dev` at `252a86d1d` (Oct 28, 2026); Track A on `fix/finality-stall-track-a`, `fix/finalizer-forward-progress` and `fix/stall-track-a-rest`; `integration/cost-accounted-ote-b1d866e45` at `d1f3ab5e1`, which carries Track A and the B4 work through patch 0035
Design basis	The cost-accounting papers in `F1R3FLY-io/publications` at `37915af` (Oct 28, 2026), read directly (§C); the annotation syntax on `feature/cost-accounted-rho` at `1b5a92f13` and `F1R3FLY-io/rholang-rs` at `02cef80`; `dev`'s cost schedule at `252a86d1d`
Revision 6	Adds the second charge. A COMM costs one phlo and pays the block's proposer. All other work done under a signed term `{%P%}[s]` is priced in phlo by `dev`'s existing cost schedule and debited from the wallet at s at the deployment's `phloPrice`; that REV goes to one shard-wide compute wallet held under the hook authority named at genesis. A send or receive left unmatched in the tuplespace pays its storage the same way; recurring rent is left to a later revision. File I/O and pattern matching stay uncharged for now. Conservation now runs over wallets, validator channels and the compute wallet. The plan adds the port of the annotation syntax to phase 2, keys wallets by REV address so that genesis can read `wallets.txt`, and records that DR-27's pegging of phlo to REV is superseded. Appendix B lists the cost schedule.
Revision 5	Records the answers to Q-14 to Q-17 and the decisions that followed. REV is conserved and minted only at genesis from `wallets.txt`. Phlo is a rate, not a token: nothing is minted per deployment and there is no escrow; the gate records a commitment against the wallet. Behaviour beyond the core enters through hooks that default to no-ops, under a multi-signature authority named at genesis. Box-car batching of debits is a node parameter, and a canonical settled form keeps it out of the state root. There is no legacy chain to preserve. Adds the path to a working branch (§8): current `dev`, a reduced Track A, and three phases, in place of the S1–S7 series. Corrects revision 4, which listed Track A as delivered on `dev`; it is not.
Revision 4	Recorded the agreed relationship between REV and the token stacks. Wallets are disaggregated from the vault: REV lives in located stacks on its owners' channels, and moving REV is a native operation. Phlo is what a COMM spends, minted per deployment at the deployment's stated price. The system is linear: REV changes hands, and is never created or destroyed by computation. Consumed REV moves to the proposer that the block names. Revision 3 treated the vault as permanent and REV payments as a later track; that part is withdrawn.
Revision 3	Rebuilt the cost-accounting design on the papers and added a measured throughput model. The stall analysis, the consensus seam and the finalizer design of revision 2 stand.
Method	Code reading, and measurements on a 2-vCPU host (Intel Xeon at 2.1 GHz, release build). Absolute times are host-specific. The ratios carry the argument.

Abstract

Validators stall as they come under sustained load. The stall analysis of revisions 1 and 2 stands: a feedback loop through the finality lag, closed by two hard limits, with run-to-completion execution and the merge it forces at its root. This revision builds the cost-accounting half of the design on the papers. Wallets are disaggregated from the vault: each wallet is a stack of REV located on its owner's own channel, so moving REV is a native operation on two channels, with no shared contract on its path. A deployment states a phlo limit and a phlo price. A validator accepts or rejects it on that price. Phlo is the rate at which REV is spent: the gate checks that the wallet covers the overestimate at that price and records a commitment, and nothing leaves the wallet until work is done. Work is charged in two ways. Each COMM costs one phlo, and that REV goes to the block's proposer. All other work done under a signed term `{%P%}[s]` (arithmetic, method calls, substitution, and the storage of a send or receive left unmatched) is priced in phlo by `dev`'s existing cost schedule, and that REV goes to a shard-wide compute wallet held under the multi-signature hook authority named at genesis. The system is linear: REV is created once, at genesis, every unit of work happens because REV changes hands, and nothing is burned. The implementation today keeps money in the SystemVault, reads it through Rholang contracts, and settles every deploy through one shared vault contract that burns the charge. Measured on the integration branch, settlement takes 83–94 % of block execution, and a one-line deploy spends 1.2 ms interpreting its term and about 675 ms on funding and settlement. The throughput model projects a 12–105-fold reduction of per-envelope work on the measured workloads, about 100-fold for REV transfers, and near-linear scaling with cores for envelopes with independent signers. That is two to three orders of magnitude over today's measured 0.44–1.24 envelopes per second for small deploys and transfers, and one to two orders for heavier deploys. The model also identifies where the gains stop: deploys dominated by their own computation, application-level hot channels, the consensus cap of envelopes per block, and multi-core RSpace efficiency, which is not yet measured. The quickest path to a working branch starts from current `dev`, adds the part of Track A that `dev` lacks, ports the consensus seam, and builds the native REV layer and the annotation syntax on it: about five and a half to seven engineer-weeks to a mergeable branch with the core of the design.

Contents

1 Summary **6**

2 What revisions 3 to 6 change, and why **7**

3 The stall: analysis **8**

3.1 The core loop 9

3.2 Costs that grow with the lag, and the starvation paths 9

3.3 Soak evidence 9

4 The blueprint: what the papers specify **10**

4.1 Signatures are names; token stacks are located terms 10

4.2 Payment is the communication 10

4.3 Acceptance by linear proof is the concurrency control 10

4.4 Overcharge and refund 10

4.5 Located purses make the proof local . . . 11
4.6 Chains and antichains: where hot spots come from . . . 11
4.7 Fees, minting, sponsors and multi-signature . . . 11
4.8 Wallets disaggregated from the vault . . . 12
4.9 Linearity: work happens because REV changes hands . . . 12
4.10 Internalisation . . . 13

5 The gap, measured **13**
5.1 How the funding path works today . . . 13
5.2 Measurements . . . 14

6 Design: cost-accounted order-then-execute on REV stacks **15**
6.1 Principles . . . 15
6.2 Price and acceptance . . . 16
6.3 The two charges . . . 16
6.4 The annotation syntax . . . 18
6.5 The life of an envelope . . . 18
6.6 Box-car batching and the canonical form . . . 19
6.7 REV transfers . . . 20
6.8 Supply and hooks . . . 20
6.9 Owners, sponsors and grants . . . 20
6.10 Block execution . . . 20
6.11 Records . . . 21
6.12 What leaves the execution path . . . 21

7 Throughput analysis **22**
7.1 Model . . . 22
7.2 Per-envelope work . . . 22
7.3 Node throughput . . . 23
7.4 Where the anticipated gains do not appear . . . 23
7.5 Validation . . . 24

8 The path to a working branch **24**
8.1 Where the code stands (October 29, 2026) . . . 25
8.2 Trial merges . . . 25
8.3 The choice of base . . . 26
8.4 Phases . . . 27
8.5 What carries over . . . 28

8.6 Other tracks 29

9 Decisions, risks and open questions **29**

9.1 Decisions 29

9.2 Risks 31

9.3 Questions 32

A Detailed stall findings **32**

B The cost schedule for non-COMM compute **34**

B.1 Process evaluation and the deployment 34

B.2 Arithmetic and logic 35

B.3 Strings, bytes and collection operators 35

B.4 Methods 36

B.5 Storage 37

B.6 Known gaps 38

C Sources **39**

1 Summary

The stall. Under sustained deploy load the unfinalized region of the DAG grows. Proposal preparation, merging, the deploy lifecycle register and the finality oracle all do work that grows with that region, which slows blocks and finality, which grows the region. Two limits turn the slowdown into a stop: a 15-second finalizer timeout that discards all work, and a merge cap at 256 blocks of floor distance (§3). Track A holds the fixes for the finality half of the loop. It has not reached `dev`, which has meanwhile landed its own versions of several of them (§8).

The cause underneath. Each deploy runs to completion against committed state, so concurrently produced blocks hold divergent post-states, and the node must merge them. The cost-accounting papers remove the reason for the merge: every interaction is gated by a token of the signatures involved, so potential conflicts are visible as shared signatures, and deploys can run at any time.

The two central points of the design.

1. **No hot spots.** Wallets are disaggregated from the vault. Each wallet is a stack of REV located on its owner's own channel. A deploy touches only the wallets and stacks that its own signatures name. Two deploys with different signers touch disjoint state and cannot contend. A shared structure on the payment path would put every deploy on one causal chain, and that is what the papers rule out.
2. **Concurrent deploys, little merge logic.** Acceptance by linear proof is the concurrency control. Competing deploys are competing proof obligations over the same linear hypotheses, and at most one succeeds before any step runs. Independent deploys then run concurrently. The only conflicts left are races on shared data channels, which the runner decides and records.

REV and phlo. REV is the quantity held in wallets. Phlo is the unit in which work is measured. A deployment states a `phloLimit` and a `phloPrice`, and a validator accepts or rejects it on that price. Phlo is not minted: once the deployment is accepted, its `phloPrice` is the rate at which wallet REV is spent per phlo. At acceptance, the gate checks that the wallet covers the overestimate at the deployment's price and records a commitment; nothing moves. At settlement the commitment is released. The system is linear: REV is minted only at genesis, from `wallets.txt`, work happens because REV changes hands, REV is never created or destroyed by computation, and the counterparty of every payment is a name that the block or the genesis configuration fixes (§4.9).

Two charges. Work done under a signed term `{%P%}[s]` is paid from the wallet at s in two ways (§6.3):

- **A COMM costs one phlo.** Its `phloPrice` REV goes to the channel of the block's proposer.
- **All other work** is priced in phlo by `dev`'s existing cost schedule (Appendix B): arithmetic, method calls, substitution, `new`, `match`, and the storage of a send or receive that is left in the tuplespace unmatched. That REV goes to the compute wallet, one per shard, held under the multi-signature hook authority named at genesis.

File I/O and pattern matching stay uncharged for now, and recurring rent on stored data is left to a later revision.

Where the implementation stands. The consensus seam is largely in place: order-then-execute, structural validity, the linearizer, records, attestation, inclusion checks and pruning (patches 0028–0035). The funding path departs from the papers. Money stays in the SystemVault. Each deploy reads vault balances through Rholang (44.5 ms per read), and after its run one vault contract

reserves, validates, apportions, burns the charge, pays a shared fee vault and refunds. That play runs with an unlimited budget and writes about 1,000 events into the record. A user REV transfer through the vault costs 81.6 ms of contract code on its own. Every settlement touches the same vault map, fee vault and cost cursors, so settlements form one causal chain. The measured consequence: settlement is 83–94 % of block execution, and the branch executes 0.44–1.24 envelopes per second on the measurement host (§5).

Projected throughput. Per-envelope work falls 12- to 105-fold on the measured workloads and about 100-fold for REV transfers, and independent envelopes scale with cores. For one-line deploys and transfers the projection is about 160–280 envelopes per second on the 2-vCPU measurement host and 1,300–2,250 on 16 cores, against 0.44–1.24 today. Where gains are smaller, §7.4 explains why, item by item.

Decisions (§9.1). Items 1 to 5 are agreed; item 6 is proposed.

(1) Wallets are located REV stacks on their owners' channels, disaggregated from the vault. Moving REV is native.

(2) REV is conserved and minted only at genesis. Phlo is a rate, not a token, and there is no escrow. The shard minimum price is a validity floor; the validator's price is a fixed node price behind a hook.

(3) A COMM costs one phlo, and its REV moves to the proposer that the block names. All other work is priced by `dev`'s cost schedule, and its REV moves to the shard's compute wallet. Nothing is burned.

(4) Hooks and the compute wallet are held by one multi-signature authority of addresses named at genesis. Box-car batching is a node parameter that never changes the state root.

(5) Unmatched sends and receives pay their storage once; rent, file I/O and pattern matching are left to later revisions.

(6) The base is current `dev` with a reduced Track A, then the seam, the native REV layer and the annotation syntax in three phases (§8).

2 What revisions 3 to 6 change, and why

Revision 2 stated in its sources that it "did not read the papers directly", and took them as the branch's proposal quoted them. It got the signature-marking argument right: different signatures cannot conflict on funding, and agreement reduces to the race winners of each block and the order of conflicting blocks. It missed what the papers say about money. It does not mention token stacks. It adopted the branch's settlement as a library to port. It kept the vault's contention patch as a requirement ("`SystemVault.rho` bucket locks (DR-119): Keep"). It defined the record to include "settlements, system work", so the vault's event logs entered consensus.

The work of the week of October 26 traced each of these to a defect:

- **Record size.** Records came to about 100 KB per envelope, 93 % logs, and 92 KB of that was the vault settlement log. A block of more than about 80 envelopes produced a record that no block could carry (patch 0035).

- **Unbounded system work.** Settlement runs with `Cost::unsafe_max()`, the gate's estimator cannot bound the vault contracts, and system plays never draw on the meter: a test measured 0 phlo under any budget.
- **The vault as a hot spot.** A precharge-and-refund design built on the vault measured worse than the code it replaced: 118 KB per one-source send. That design is withdrawn.

Revision 3 started from the papers and measured the gap. It still treated the vault as the permanent custodian of REV, with tokens bought from it at a boundary, and it put REV payments in a later track. Revision 4 corrects that. The papers' abstraction is a disaggregation of wallets from the vault: REV itself lives in located stacks, and every payment is REV changing hands in a linear system. Revision 5 takes the last two steps of that correction. Phlo is not a token at all, so there is nothing to mint and nothing to hold in escrow: it is the rate at which REV in the wallet is spent. And REV itself is minted once, at genesis. With custody, escrow, cursors and the legacy path gone, the implementation no longer needs most of the integration branch, and the quickest path to it starts from current `dev`.

Revision 6 settles the unit of cost and closes the gaps that a review of revision 5 against the papers and the branch found:

- **The unit of cost.** Revision 5 said that a COMM costs one phlo but planned to meter with `dev`'s per-runtime meter, which counts operations and bytes, not COMMs. Revision 6 keeps both, with distinct roles: the COMM count pays the proposer, and `dev`'s schedule prices the rest of the work, which pays the compute wallet (§6.3).
- **Payload size.** With one phlo per COMM, a COMM carrying 1 KB cost the same as one carrying a byte, and a send that never matched was never charged. Charging the storage of unmatched sends and receives by size closes that gap.
- **The annotation syntax.** The design pays from the wallet at s for work under `{%P%}[s]`, but revision 5's plan never brought that syntax onto the new branch. Revision 6 ports it in phase 2 (§6.4).
- **Genesis from `wallets.txt`.** `wallets.txt` lists REV addresses, not public keys, and an address cannot be inverted to a key. Wallet channels are therefore keyed by REV address, which is still a function of the owner's signature (§6).
- **DR-27 superseded.** The branch's DR-27 (June 15) pegged phlo to REV as one token. Phlo as a rate priced by `phloPrice` replaces it.

Everything in revision 5 that the second charge does not touch stands. Everything in revision 2 that does not depend on the funding path stands: the stall analysis, the consensus seam, the canonical order, records and attestation, the finalizer design, backpressure, Track A and the hook points.

3 The stall: analysis

This section restates revision 2 in brief. The evidence and line references are unchanged, and Appendix A lists the detailed findings.

3.1 The core loop

Under sustained load three quantities grow together: the pending deploy pool, the set of deploys included in blocks but not yet settled, and the unfinalized DAG cone. Each grows with the finality lag D, and each carries costs that scale with it (Figure 1).




Figure 1: The feedback loop. Every cost in the middle column grows with the finality lag. The two traps (outlined) turn the slowdown into a stop.

3.2 Costs that grow with the lag, and the starvation paths

- **Deploy pool.** About $8N$ signature checks per proposal for a pool of N, re-read under a lock.
- **Lineage walks.** Quadratic in load: open signatures times segment length times deploys per block.
- **Rejection-option search.** Exponential in conflicting pairs per group. Vault and PoS channels collapse groups into one, so the vault is a hot spot for the merge as well.
- **Hot channels in RSpace.** $O(n)$ per touch and $O(n^2)$ over a run for a channel that accumulates n datums. Replay scans its COMM list with a copy per step, $O(n^2)$ in COMMs (clone audit, finding 0.2).
- **Finality walks.** $O(P \cdot V^2LD)$ warm per block.
- **Starvation.** A serial proposer queue, synchronous locks in async code, and CPU-bound consensus work on the async workers that also serve the network.

3.3 Soak evidence

The branch's proposal records two soaks. In August one merge call averaged 2.16 s, 92 % of it settled-signature probes. In October no single stage separated failing sessions from passing ones, and the binding constraint had moved toward finality and Casper bookkeeping. The production high-phase replay targets recorded in `cost_accounting_perf_spec.rs` attribute about 229 ms

per deploy to precharge, 189 ms to refund and 32 ms to evaluation. That is, 93 % of replay time per deploy is spent moving money through the vault.

4 The blueprint: what the papers specify

This section reads the design from the papers. Each point ends with its consequence for the implementation.

4.1 Signatures are names; token stacks are located terms

The cost-accounted rho calculus extends names to $x, y ::= \lceil T \rceil \mid s$: signatures are channel names. Token stacks $S ::= () \mid s : S$ are first-class terms. Each layer is a balance cell of one signature. The companion paper refines the stack to a *located* stack $S(I, s : S')$, a stack indexed by the surface I that may draw on it. In rho this is a token stack sitting on a specific channel: only processes holding a matching channel name can consume from it. Unforgeable channels make that a genuine capability.

Consequence. A signer's funds for computation are a stack on the signer's own channel in RSpace. They are not a balance in a shared contract.

4.2 Payment is the communication

The five rewrite rules are the COMM rule gated by token consumption. For a single signature,

$$\{\, \texttt{for}(y \leftarrow x)\, T \mid x!(U)\, \}_s \;\mid\; s : S \;\longrightarrow\; T\{\lceil U \rceil / y\} \;\mid\; S.$$

The other four rules cover compound signatures and split or combined tokens. Joins follow one schema quantified over partitions, and conservation of authority holds across all of them: a join consumes exactly one receiver authority and one sender authority per channel.

Consequence. The reducer charges by popping cells from located stacks. There is no separate settlement step that converts usage into money after the fact.

4.3 Acceptance by linear proof is the concurrency control

A deployment is accepted if and only if a linear proof of its resource use exists: for every signature s it names, the supply Σ_s meets the demand Δ_s. The check runs before any step executes, and it is linear in the size of the AST. In the papers' words, two deployments competing for the same tokens are "two proof obligations competing for the same linear hypotheses. At most one can succeed." Duplicate and simultaneous arrivals are resolved by the same rule, "without locks, priority queues, or rollback mechanisms".

Consequence. Admission needs only the stacks of the envelope's own signers. Group decisions, later holds and shared cursors are unnecessary: committing tokens to an accepted deployment removes them from the supply that the next proof sees.

4.4 Overcharge and refund

Where control flow is data-dependent, the validator computes a conservative demand $\Delta_c^{\max}$, the maximum over reachable branches, and accepts if $\Sigma_c \geq \Delta_c^{\max}$. Execution consumes only the tokens

it forces, and "the residual $\Delta_c^{\max} - \kappa$ is returned to the client's token stack as part of the deployment's settlement". The refund is safe because the number of tokens consumed equals the number of forced redexes, which the runtime counts exactly.

Consequence. Settlement is a return of unused cells to the client's own stack. It is not a vault transaction.

4.5 Located purses make the proof local

Locating stacks decomposes the global resource obligation into one local linear proof per purse. The global proof is the separating conjunction of the local ones (companion paper, "Local sufficiency composes"). Location also quarantines data-dependence to the surfaces that need a conservative bound.

Consequence. The gate checks each signer's stack independently, and independent signers' checks can run concurrently.

4.6 Chains and antichains: where hot spots come from

The spacetime paper maps a cost-accounted computation to a measured causal set. Events are COMM firings, the order is enabling, and concurrency is Bernstein independence of footprints: no write-write and no read-write overlap. Two of its results bear directly on throughput:

- **Time from the stack.** The firings that draw on a single located stack form a chain, ordered by stack depth. A shared stack, or any shared resource that every deploy writes, serializes every deploy that touches it.
- **Space from the surfaces.** Firings that draw on distinct stacks at non-near surfaces are concurrent: they form an antichain.
- **Number is volume.** The phlogiston spent equals the number of events, and discrete proper time is the longest chain.

With W the total work and L the longest chain, a scheduler on P cores completes the work in at most $W/P + L$ (Brent's bound). Throughput therefore depends on keeping L short: no state that every deploy writes.

Consequence. A design meets the papers' throughput promise only if nothing on the payment path is shared across signers. A shared vault map, fee vault or cursor puts every settlement on one chain, and L grows with W.

4.7 Fees, minting, sponsors and multi-signature

- **Fees.** In the worked example, the validator handler takes one token from the client's address A_c and keeps it on its own fee channel F_v. The fee lands on a per-validator channel.
- **Minting.** Minting is constructing a token stack and sending it on a signature channel. Epoch phlogiston for validators, slush funds and fee-to-stake conversion use the same primitive.
- **Funding slots.** A contract creates an unforgeable channel and lets any funder deposit tokens on it. This decouples who authorizes, who pays and what runs. A sponsor funds a new user through a slot.

- **Multi-signature.** A compound signature $s_1 \otimes s_2$ needs tokens from every component. Weakening is forbidden, so a compound token must be spent in full or explicitly split.

Consequence. Sponsors, grants and owners are funding slots and located stacks, not post-run vault debits.

4.8 Wallets disaggregated from the vault

The located stack is how value is held, not only how fuel is held. A wallet is a stack of REV located on its owner's channel. The channel is a function of the owner's signature: a public key, an unforgeable name, or a compound signature for a multi-signature wallet. Finding a wallet is therefore a computation, not a lookup in a shared map. Only a term signed by the owner can draw on the stack. Anyone can deposit to it, as anyone can fund a funding slot.

Cells carry amounts. A balance is a count on a cell, not a list of unit cells, so spending splits a cell and receiving adds one. Deposits land as separate datums on the payee's channel and are combined only when the payee spends. Payments to one payee therefore commute: two deposits never conflict, and only spends from one wallet form a chain.

Consequence. Moving REV is a COMM on the payer's and payee's channels. It needs no registry lookup, no map walk, no purse split through a shared mint and no settlement afterwards.

4.9 Linearity: work happens because REV changes hands

In the calculus, linearity means that every token is consumed exactly once: forcing a signed redex pops one cell from a located stack, and the cell is gone. The monad paper reads that stack as the temporal monoid, a clock whose consumed prefix counts the steps run. Conservation of REV is an economic rule layered on top. The two fit together as two sorts:

- **Phlo is time.** It is ordered and consumed, and it is never commutative. It lives in the record, as the count κ of work an envelope performed.
- **REV is value.** It is spatial: deposits commute, nothing is lost, and the REV behind each consumed phlo moves to a counterparty. This is the paper's fee extraction, generalised so that all spending is payment for work.

Computation never creates or destroys REV, so the destination of consumed REV is not left open: the block or the genesis configuration names it.

Phlo is not a second currency. It is the rate at which REV in a wallet is spent: one phlo is `phloPrice` REV. Each COMM costs one phlo, and the schedule of Appendix B prices all other work in phlo. Nothing is minted per deployment and nothing is held in escrow. The REV stays in the wallet until work spends it.

A minimal example: client c holds r REV in its wallet W_c. Its deployment is one COMM, so $\Delta = 1$ phlo, at price p. Validator v proposes the block that includes it.

```
D  =  { x!(5) | for(y <- x) Nil }_c           -- one COMM, signed by c

block b, sender v, at D's canonical position:

  W_c!(r) | D                                 -- c's wallet: r REV
```

```
gate:   r >= Delta * p = p                    -- accept; commit p against W_c
                                              -- (bookkeeping, nothing moves)

-> Rule 1, at price p (k = 1):
  { x!(5) | for(y <- x) Nil }_c | W_c!(r)
    ->  Nil | W_c!(r - p) | F_v!(p)           -- the COMM moves p REV from W_c to F_v

-> release the commitment (Delta - k = 0 unspent: nothing to return)

conservation:  (r - p) at W_c  +  p at F_v  =  r
```

The recipient is a name in the term, F_v, and v is the block's sender. The term is fixed when v proposes the block. Whoever reduces it, the runner or any replaying validator, reaches the same post-state, and appears nowhere in the term. Paying the runner would make executed state depend on who produced the record, not on the ordered blocks. So consumed REV moves to $F_{\mathrm{sender}(b)}$, and running and replaying are the work every validator does as a member of the shard.

Overcharge and refund keep their meaning without an escrow. The gate commits $\Delta^{\max} \times p$ against the wallet, and execution spends $\kappa \times p$. The residual $(\Delta^{\max} - \kappa) \times p$ never left the wallet, so the "refund" is the release of the commitment.

The second charge has the same shape. Work that is not a COMM (an addition, a method call, a substitution, the bytes of a send left in the tuplespace) is still work done under a signature, so it still moves REV. Its counterparty is not the proposer but the shard: a compute wallet named at genesis.

Consequence. Conservation is an invariant of every block, and of the shard: the sum over wallets, validator channels and the compute wallet equals the genesis supply. There is no burn, no fixed fee and no mint after genesis.

4.10 Internalisation

The papers give a source-to-source translation of the cost-accounted calculus into pure Rholang 1.1, with splitter and joiner infrastructure. This gives cost-accounted semantics on today's runtime while the native implementation is built. The history-and-cost note adds that such an internalisation is lax: it carries an overhead grade. The native implementation is therefore the throughput path, and the translation is a bridge.

5 The gap, measured

5.1 How the funding path works today

The branch already has the papers' mechanism, but the v6 path does not use it:

- **Located stacks exist.** The reducer evaluates a token stack term by producing a `CostStack` datum on the signature channel of its head cell (`reduce.rs`, `eval_cost_stack`). The supply module models purse stacks and their inventory (`costacc/supply.rs`). Stack pops are accounted natively (`accounting/authority.rs`, `stack_pops`).
- **v6 offers bypass them.** An owner-direct offer funds "every class of the signer's own principal lane" from the signer's vault (`owner_offer.rs`). The gate's supply "counts SystemVault

balances only" (`gate.rs`). Fresh usage is bought from REV at the signed price on every deploy.

Blueprint	Implementation (v6 path)	Measured effect
Supply is the depth of the signer's located stack.	Supply is read from SystemVault balances through Rholang queries.	44.5 ms per balance query. The run phase spends 110–160 ms beyond interpreting the term.
Payment is the COMM popping a cell.	The run is metered natively. The charge is then converted to REV and settled by `applyPhloCost`.	560–600 ms and about 1,000 events per envelope, under `Cost::unsafe_max()`.
Refund returns $\Delta^{\max} - \kappa$ to the client's stack.	`reserveAll`, `validateSettlement` and `settleReserved` run together after the run.	The reserve-and-refund happens, collapsed into one play after the run.
The linear proof is the concurrency control.	Holds that move no funds, plus `decide_groups`, `LaterHolds`, a held-capacity guard and the DR-28 cursors.	Settlement runs sequentially in block order.
Consumed REV moves to the counterparty; the system is linear.	`settleReserved` burns the resource charge, leaving it in a purse that nobody can reach. Only the fee moves.	REV is destroyed by computation, which breaks conservation.
A wallet is a located stack; moving REV is a COMM.	Wallets are purses in the vault's tree map, reached by registry lookup; a transfer runs the mint's split and deposit.	81.6 ms of contract code per user transfer.
The fee goes to the validator's own channel.	One fee vault, reached through `findOrCreate` by every settlement.	One write target shared by every envelope.
Distinct signers form an antichain.	Every settlement touches the vault map, the fee vault and the cursor map.	Settlement time per envelope grows with block size (Table 2).
The record carries the COMM log with charges.	The record also carries the wallet and receipt logs of the vault contracts.	About 92 KB of a 100 KB entry.

5.2 Measurements

All figures come from release builds on the 2-vCPU host named on the first page, using tests in `casper/tests/v6_executor_spec.rs` and `casper/tests/util/rholang/cost_accounting_perf_spec.rs`.

Legacy `dev` pays the same cost. The legacy precharge and refund system deploys, which also move REV through the vault, take 364 ms and 291 ms per deploy on the play path, against 0.3 ms of

Envelopes	Runs	Settlement	Settlement share	Settlement per envelope	Envelopes/s
1	0.14 s	0.67 s	83 %	0.67 s	1.24
4	0.51 s	2.73 s	84 %	0.68 s	1.24
16	1.84 s	14.2 s	88 %	0.89 s	1.00
64	8.13 s	136.6 s	94 %	2.14 s	0.44

Table 2: Block execution on the integration branch by block size (one-line sends from distinct payers; `phase_timings_by_block_size`). Settlement per envelope grows with block size, which is the mark of shared state.

Workload (one envelope)	Interpret term	v6 run phase	v6 settlement	Useful share
One send	1.2 ms	112 ms	563 ms	0.17 %
256 sends	29.7 ms	192 ms	605 ms	3.7 %
300 recursive COMMs	32.5 ms	184 ms	572 ms	4.3 %
128 COMMs carrying 1 KB each	52.3 ms	211 ms	602 ms	6.4 %
REV transfer through the SystemVault	81.6 ms	—	—	—

Table 3: Where the time of one envelope goes (`cost_breakdown_of_one_envelope`, `a_user_vault_transfer_costs`). "Interpret term" is an unmetered exploratory run of the same term. Spawning a runtime costs 3.6 ms and is subtracted.

evaluation. On replay, a block of seven deploys spends 106 ms on precharge, 70 ms on refund and 0.5 ms on evaluation per deploy. The vault-centred payment path is the dominant per-deploy cost on both the legacy and the v6 path.

System work is invisible to the meter. The vault plays measured on October 28 report 0 phlo used under any budget. Work under the system signature is never drawn from a budget, so no allowance can bound it. Its event count is deterministic and linear in the number of sources: about 157 events (16 KB) per source per play.

6 Design: cost-accounted order-then-execute on REV stacks

6.1 Principles

P1. **Wallets are located REV stacks.** REV lives on its owners' channels, disaggregated from the vault. A wallet's channel is computed from its owner's signature, so finding it needs no lookup. For a public key the channel is keyed by the key's REV address, which is what `wallets.txt` lists; an address cannot be inverted to a key, while a key always yields its address. Moving REV is a native operation on the payer's and payee's channels.

P2. **REV is conserved.** REV is created once, at genesis, from the `wallets.txt` given to the shard. No later operation creates or destroys it.

P3. **Phlo is a rate.** Work costs phlo, and a deployment's `phloPrice` says how much REV one phlo is. Phlo is never minted or held. Work moves REV from the paying wallet at that price.

P4. **Two charges, two counterparties.** A COMM costs one phlo, which moves to the block's proposer. All other work under a signed term is priced by `dev`'s cost schedule, and moves to

the shard's compute wallet.

P5. **No shared state on a deploy's payment path.** Everything a deploy reads or writes to pay for itself is named by its own signatures: its wallets and its funding slots. The two exceptions are the proposer's channel and the compute wallet, where deposits commute and are combined once per block.

P6. **Concurrency from independence.** Envelopes whose footprints are Bernstein-independent run concurrently. Conflicts are races on shared data channels, decided by the runner and recorded.

P7. **Extension by hook, not by fork.** Behaviour beyond the core (rewards, staking shares, pricing policy) enters through hooks that default to no-ops and are replaced by contracts, under a multi-signature authority named at genesis.

P8. **The consensus seam stays.** Order-then-execute, structural validity, the linearizer, records, attestation, inclusion checks, the finalizer design and backpressure are those of revision 2, as delivered in patches 0028–0035.

6.2 Price and acceptance

A deployment states `phloLimit`, the most phlo it may spend, and `phloPrice`, the REV it pays per phlo. These keep their meaning from `dev`, as D-12 requires.

- **The shard floor is a validity rule.** A block that includes a deployment priced below the shard's minimum price is invalid (block-validity step 8, preserved by D-12). The floor sits in the genesis policy.
- **The validator's price is its own.** Above the floor, each validator decides the price at which it accepts deployments. A deployment below that price is simply not included by that validator. This is a market, not a consensus rule.
- **The first version is a fixed price.** The node reads its acceptance price through a price hook. The first version of the hook returns a fixed price from the node's configuration. Making pricing programmable is a later change to the hook, with no change to consensus.
- **One price for both charges.** The deployment's `phloPrice` prices COMMs and the rest of its work alike.

6.3 The two charges

Work done under a signed term `{%P%}[s]` is paid from the wallet at s, at the deployment's `phloPrice`, in two ways.

Charge	What it covers	Phlo	REV goes to
COMM	A redex that fires: a send meets a receive, or a join fires on all its channels	1 per COMM	The block's proposer, $F_{\text{sender}(b)}$
Compute	Everything else P does: evaluation of sends, receives, variables, `new`, `match` and `if`; arithmetic; method calls; substitution; and the storage of a send or receive left unmatched	`dev`'s cost schedule (Appendix B)	The shard's compute wallet, W_{compute}

Why two counterparties. A COMM is the interaction that the block fixes, and its counterparty is the proposer that the block names (§4.9). Compute work has no such counterparty in the term: it is the cost to the shard of evaluating and storing what the term does. Its REV therefore goes to a wallet the shard holds. One compute wallet serves the whole shard; how its REV is later used (rewards, a share for stakers, a treasury) is a matter for the REV hook, which can move it but cannot create or destroy it.

The compute wallet. Genesis creates W_{compute} with a zero balance and places it under the hook authority: the same set of genesis addresses and the same threshold that replace hooks (§6.8). It is the one shared write target on the payment path. Deposits to it commute, and settlement combines each block's compute charges into one deposit, so it adds one datum per block, not one per envelope.

Storage is charged once, when it is left. `dev` charges a send or receive its storage size up front and refunds it when a COMM consumes it. The design keeps the sizes and nets the timing within the run:

- A send and a receive that meet within the envelope's run cost one phlo for the COMM and no storage.
- A send or receive that the run leaves in the tuplespace, unmatched or persistent, pays its storage as compute: for a send, the bytes of its channel and data; for a receive, the bytes of its channels, patterns and continuation; and in both cases the event storage of $32 + 32k$ for k channels. These are `dev`'s formulas (Appendix B).
- When a later envelope consumes stored data, its COMM costs one phlo, and nothing is refunded. On `dev`, the consuming deploy is credited with the producer's storage refund. Here the producer's payment has already gone to the compute wallet, and a credit to another wallet would have to come from somewhere; so there is no cross-envelope refund.
- `dev`'s COMM event-storage charge is replaced by the one phlo of the COMM.

This closes the payload-size gap: a send that carries a kilobyte and is left in the tuplespace pays for the kilobyte. Charging stored data again over time, in units of block time, is rent; it is left to a later revision.

What stays uncharged. File I/O (`rho:io:fs:native:*`), whose weights `dev` defines but discards, and the spatial matcher, which `dev` never charged, stay uncharged in this revision. Appendix B lists them with the other flat-priced operations as known gaps.

Who pays. The wallet at the signature of the signed term whose work it is:

- A deployment with no explicit wrapper is `{%D%}[deployer]`. Parsing the deployment's source happens outside any wrapper and is charged to the deployer.

- Uniform signing, `{% for(y <- x) P %}[s]`, charges both the COMM and the continuation's compute to s.
- The linear transfer `{% for(y <- x) P %}[s1 -o s2]` charges the COMM to s_1 and the continuation's compute to s_2.
- Nested wrappers flatten to the compound s_1 `(*)` s_2, as the cost monad's multiplication requires; a compound signature's charge is discharged in full by its components, never by one alone.

Phase 2 admits only the deployer's own signature in the signed terms of a deployment (§8); funding slots, owners and compound signatures follow in phase 3.

6.4 The annotation syntax

The surface syntax is the paper's concrete syntax (Appendix C of the cost-accounted rho paper), already implemented in two places:

- **Parser.** `F1R3FLY-io/rholang-rs`, branch `feature/cost-accounting-transpiler` at `02cef80`: the forms `{% P %}[s]`, `s :: S`, `# P`, `s1 (*) s2`, `s1 -o s2` and the per-clause signed bind, with an AST, a corpus and golden tests. It is not on `rholang-rs` master; `dev` pins `527af8a`, which has none of it.
- **Normalizer.** `feature/cost-accounted-rho`, `compiler/normalizer/cost_accounting/` (about 450 lines): recognition of signed terms and stacks, the uniform-signing and lollipop desugarings, flattening of nested signatures to a compound, and the guard against cost syntax in patterns. It lowers signed terms to `CostSignedTerm` and stacks to `CostStack` in the protobuf model.

The design ports the parser and the normalizer as they are, and re-implements the reducer's part on the native REV layer rather than porting the branch's 4,952-line `authority.rs`:

- A signed term opens a funding region for its signature; COMMs and compute inside it are charged to that region's wallet.
- A stack literal `s :: S` is a native transfer from the writer's wallet onto the signature channel, never a mint. This is what the branch's `eval_cost_stack` does, and conservation requires it.

6.5 The life of an envelope

```
gate(e, R, C):                      -- in block order, at the block pre-state R
  Delta = demand of e in phlo: COMMs + compute (Delta_max where data-dependent),
          <= phloLimit
  for each wallet w that e's signers fund it from:
    need_w = w's share of Delta * phloPrice
    have_w = REV on w's located stack at R  -  C[w]      (native read)
  accept iff have_w >= need_w for every w               (one local proof per purse)
  on accept: C[w] += need_w                             (commitment: bookkeeping)
run(e):                             -- concurrent with the other envelopes
  per wallet w, count k_comm[w]: one phlo per COMM, under rules 1-5 and joins
  per wallet w, count k_compute[w]: phlo of the cost schedule, including the
                storage of what the run leaves in the tuplespace
```

```
settle(e):                          -- in block order, after the merge
  debit each w by (k_comm[w] + k_compute[w]) * phloPrice, in canonical form
  credit F_sender(block) with sum k_comm * phloPrice
  credit W_compute       with sum k_compute * phloPrice
  release C[w] for e's wallets    (the unspent (Delta - k) * phloPrice never left)
  exhausted (signed limit reached): k = phloLimit, so the whole commitment
                is spent, each phlo to the counterparty of its work
end of block:  combine the block's credits into one deposit on F_sender(block)
               and one on W_compute; run the REV hook; check conservation
```

- **Native, not Rholang.** The wallet read, the commitment, the debits and the deposit are runtime operations on signature channels. They run no contract code and leave no Rholang event log.
- **The commitment is the reservation.** The commitment table C belongs to the block's execution, not to RSpace. Gating runs in block order, so a later envelope that draws on the same wallet sees the earlier commitments, and the sum of commitments on a wallet never exceeds its balance. Every block settles all of its envelopes, so no commitment outlives its block. Replay reproduces C from the gate verdicts in the record.
- **The overestimate bounds the commitment.** With a complete proof the commitment is $\Delta\times$ `phloPrice`, often far below `phloLimit` $\times$ `phloPrice`. With an incomplete proof it is the signed limit, exactly as in `dev`. The linear proof bounds the COMM part of Δ; until a static estimate of the compute part exists, the compute part is bounded only by `phloLimit`, so $\Delta =$ `phloLimit` in practice.
- **Exhaustion.** An envelope that reaches its signed limit stops. It has then spent its whole commitment, and each phlo has already gone to the counterparty of the work it paid for. Revision 5's rule that an exhausted envelope's full commitment goes to the proposer is no longer needed.

6.6 Box-car batching and the canonical form

Writing a wallet debit for every COMM is wasteful when an envelope makes thousands of them. Each node may therefore batch its debits, with a box-car size set in the node's configuration. Batching is a matter of how one node schedules its writes, so it must not change the state that consensus sees. Two nodes with different box-car sizes must reach the same state root. The design guarantees that with one rule:

> **Canonical settled form.** After a block settles, each wallet that paid holds one combined datum, its balance less $(\kappa_w^{\text{comm}} + \kappa_w^{\text{compute}})\times$ `phloPrice` summed over the block's envelopes; the proposer's channel holds one new deposit datum for the block's COMM charges; and the compute wallet holds one new deposit datum for the block's compute charges. Intermediate debits are not part of the state. A term that reads its own wallet during its run sees the pre-state balance less the commitments recorded against that wallet up to and including its own gate position, which is also independent of the box-car size.

The record carries κ_w^{comm} and $\kappa_w^{\text{compute}}$ per wallet, so replay checks the settled form, not the write schedule. The box-car size is a per-node parameter, as decided. It affects how fast a node runs, and it never affects the state.

6.7 REV transfers

A transfer from wallet A to wallet B is a deployment signed by A. Its few COMMs cost phlo like any other deployment's. The movement of REV is one native debit of A's stack and one native deposit on B's channel. Deposits land as separate datums, so transfers to one payee never conflict, and transfers between disjoint pairs run concurrently. Only spends from one wallet form a chain, and the linear proof already orders those.

The SystemVault stops being the custodian of REV. At most it remains as a compatibility facade: `find` returns the wallet channel, and `transfer` is the native transfer.

6.8 Supply and hooks

- **Genesis.** Genesis creates one located stack per line of `wallets.txt`, keyed by that line's REV address, with that balance, and an empty compute wallet. This is the only creation of REV. Every block's executor checks that the sum over wallets, validator channels and the compute wallet equals the genesis supply. The check is incremental: each block's debits and credits sum to zero, with an occasional full audit.
- **The REV hook.** Genesis installs a hook that is called at fixed points (after each block's settlement, and at epoch boundaries) and does nothing. Rewards, sharing a proposer's receipts with its stakers or delegators, or any other policy are contracts that replace the no-op. A hook can move REV but cannot create it, because conservation is checked after it runs.
- **The price hook.** As above: the first version returns the node's fixed price.
- **Hook authority.** Genesis names a set of addresses and a threshold. Replacing a hook is a deployment signed by at least the threshold of those addresses (a compound signature over them). No other signer can change a hook.
- **The compute wallet's authority.** The same addresses and threshold hold the compute wallet. Spending from it is a deployment with that compound signature, or the work of a hook they installed. A single compute wallet per shard is the default; splitting it (per epoch, or per proposer) is a change to the REV hook, not to consensus.

6.9 Owners, sponsors and grants

- **Owners** (DR-135) pay for the regions of their stored processes at their own price, from their own REV wallets. An owner without the REV refuses the introduction, as the branch's region refusal already does.
- **Sponsors** use funding slots: an unforgeable channel holding deposited REV, named by the deploy that it funds.
- **Grants** are funding slots with a validity window that the gate checks at block time.

6.10 Block execution

1. **Gate** every envelope at R_0, in block order, accumulating commitments. The wallet reads are independent per wallet and run concurrently. The commitment accumulation is a pass over a table in memory.

2. **Run** every admitted envelope concurrently from R_0.
3. **Merge** in block order. A conflicting envelope is rolled back and keeps its charge for the run, as decided on October 25.
4. **Settle** in block order, natively, in the canonical form of §6.6: debit the wallets, then make one deposit to the proposer and one to the compute wallet. Run the REV hook. Check conservation.

The ordered steps (1 and 4) are cheap. The expensive step, the run, is the concurrent one.

6.11 Records

A record entry carries the gate verdict and commitment, the outcome, the COMM phlo and the compute phlo spent per wallet, the REV moved to the proposer and to the compute wallet, the budget recording and operation journal needed for replay, and the user COMM log. It carries no system log. With the 0035a analysis of 1.25 bytes of user log per phlo (0.1 measured), an entry is at most $1.25\,\Delta + r_0$ bytes, with r_0 under 4 KB measured. A per-block demand cap D with $1.25\,D + E\,r_0 \leq$ `block-record-bytes` then guarantees that every record can be cited. That closes the liveness hole of 0035 by arithmetic alone, and citing records in pieces (0035b) is no longer needed. The 1.25 bytes per phlo was measured under the old units; with storage now priced by the byte, a large payload costs phlo in proportion to its size, which can only lower the bytes of log per phlo, but the ratio is re-measured in phase 2 before the cap is fixed.

6.12 What leaves the execution path

- The SystemVault as custodian of REV, its tree map of purses, its registry lookup and its mint-based purse split.
- The precharge and refund system deploys, the settlement call `applyPhloCost`, its unlimited budget, its burn of the charge, and its logs in the record.
- Vault reads in the gate. Supply becomes a wallet balance read natively.
- Holds as fit checks, `decide_groups`, `LaterHolds` and the held-capacity guard.
- The DR-28 monetary cursors and their vault validation, and with them the reason for the DR-119 bucket locks.
- The shared fee vault and the fixed fee. The compute wallet is not a fee vault: it receives one deposit per block, at settlement, and no envelope reads it.
- `dev`'s cross-deploy storage refunds and its COMM event-storage charge (§6.3).
- The vault-based precharge and refund of October 28 (withdrawn before merge).

There is no legacy chain to preserve. This is software from which others build blockchains, and no deployed shard depends on the vault-based path. The rule of revisions 2 to 4, that legacy paths stay byte-identical to `dev`, is relaxed. Code on the old path is removed where removing it is simpler than keeping it. There is no migration of balances.

7 Throughput analysis

7.1 Model

Let an envelope's core time be the sum of four parts: its interpretation u, the metering overhead factor m on that interpretation, its funding work f (wallet read, commitment, debits and the proposer deposit), and its share c of the block's checkpoint and merge. On P cores with parallel efficiency η, and with the longest chain L short relative to the work, node throughput is

$$X \;\approx\; \frac{\eta\, P}{m\, u + f + c}.$$

Every validator executes or replays every block, so shard throughput equals the throughput of one node. Adding validators adds safety, not throughput.

Today. f is the run-phase funding overhead (110–160 ms) plus settlement (560–600 ms), and settlement is one chain. The parallel term does not apply to it, and its per-envelope cost grows with block size. A REV transfer adds 81.6 ms of vault contract code on top.

Design. $m = 1.2$, from the branch's own profiles (15–23 % more CPU in the reducer). The funding work f covers a native wallet read, the commitment, the debits in canonical form, the proposer deposit and the gate's linear estimate. The checkpoint share is $c \approx 0.5$ ms (31 ms per 64-envelope block measured). Together $f + c$ is taken as 2 to 8 ms, with 5 ms as the middle value. A REV transfer adds one native debit and one native deposit, taken as 0.5 to 2 ms. These ranges are estimates until phase 2 measures them. Without the escrow moves and the mint of revision 4, f should sit in the lower half of its range.

The second charge. Pricing compute adds no interpreter work: `dev`'s meter already evaluates the schedule on every operation, and m includes it. It adds two counters per paying wallet, and one deposit to the compute wallet per block rather than per envelope, so its share of f is negligible. The figures below are unchanged from revision 5.

7.2 Per-envelope work

Workload	Today	Design (range)	Gain, middle	Gain, range
One send	675 ms	6.4 ms (3.4–9.4)	105×	72–198×
REV transfer	756 ms	7.4 ms (3.9–11.4)	102×	66–194×
256 sends	796 ms	40.6 ms (37.6–43.6)	20×	18–21×
300 recursive COMMs	756 ms	44.0 ms (41.0–47.0)	17×	16–18×
128 COMMs carrying 1 KB	813 ms	67.8 ms (64.8–70.8)	12×	11–13×

Table 4: Core time per envelope, today (run phase plus settlement, single-envelope block; for the transfer, plus the measured 81.6 ms of vault code) and projected. A transfer's own COMMs are taken as a one-send deployment. The gain is largest where the deploy does least, because today's cost is almost all funding overhead.

Workload	2 cores	8 cores	16 cores	32 cores
One send	187–281	750–1,124	1,499–2,249	2,998–4,497
REV transfer	162–243	648–972	1,297–1,945	2,593–3,890
256 sends	30–44	118–177	236–354	472–709
300 recursive COMMs	27–41	109–164	218–327	436–655
128 COMMs carrying 1 KB	18–27	71–106	142–213	283–425

Table 5: Projected envelopes per second for one node, with parallel efficiency η from 0.6 to 0.9, for envelopes with independent signers and no shared data channel. Today's measured rate on the same 2-core host is 0.44 (64-envelope blocks) to 1.24 (single-envelope blocks). Absolute values are for the measurement host. Faster hosts scale all figures alike, today's included.

7.3 Node throughput

Reading the tables. On 2 cores, the design projects 150–640 times today's measured rate for one-line deploys, and 130–550 times for REV transfers, against 1.24 envelopes per second for single-envelope blocks and 0.44 for 64-envelope blocks. For the heavier workloads it projects 14–36 times their single-envelope rate of 1.2–1.3 per second. On 16 cores, with independent signers, the factors become about 1,050–5,100 for small deploys and transfers, and 110–290 for the heavier ones. The gain has two sources that multiply: removing fixed funding overhead and the vault (Table 4), and replacing one causal chain with an antichain, so that cores apply (Table 5).

7.4 Where the anticipated gains do not appear

The model supports large gains for overhead, payments and concurrency. It does not support them unconditionally. These are the cases where it projects less, and why.

1. **Deploys dominated by their own computation.** The gain is $(m\,u + f_{\text{today}})/(m\,u + f)$. For a deploy that interprets for 50 ms it is about 12, and it falls toward 1 for very heavy deploys. Against the unmetered legacy path it falls toward $1/m$, below 1. The design removes overhead. It does not make Rholang faster, and the metering factor $m = 1.2$ is a real cost. The interpreter's own defects (clone audit, Tier 0: quadratic `Env::put`, quadratic replay scan, quadratic `eval_match`) are separate wins of 2.7–273 times on the patterns they affect.
2. **Application hot channels.** Two deploys that write the same data channel, such as a popular contract's state or a liquidity pool kept in one contract, form a chain. If a fraction h of the work lies on one chain, Amdahl's law limits the speedup on P cores to $1/(h + (1-h)/P)$. On 16 cores, h of 1, 5, 10 and 25 % gives 13.9, 9.1, 6.4 and 3.4. The design removes the system's hot spots, including the vault. Applications can still create their own.
3. **One busy wallet.** All spends from one wallet form a chain, by the papers' own result. A single account that submits most of the load is serialized at its precharge. The precharge is cheap, but the order is fixed. Deposits to one wallet do not have this limit, because they commute.
4. **The consensus cap.** A block carries at most $E = 256$ envelopes, and blocks execute in canonical order. Shard throughput is at most $E \cdot V \cdot r$ for V validators proposing r blocks per second: 768 per second for three validators at one block per second, 1,536 for six. For small deploys and transfers this cap binds before 16 cores do. Raising it means a larger E (bounded

by the record arithmetic above), faster proposals, or executing blocks with disjoint footprints concurrently (refinement R1).

5. **Replication.** Every node executes or replays every block, so validators add no throughput. Replay is cheaper than execution, with no matching search, but still proportional to the work.
6. **Multi-core efficiency is not measured.** The range $\eta = 0.6$–0.9 is an assumption. On today's code, the run phase's core time per envelope grows from 140 ms alone to 254 ms in a 64-envelope block on 2 cores. Part of that is vault reads in the gate, which the design removes, and part may be contention in RSpace's hot store. Until the phase 2 scaling run measures it, the 8- to 32-core columns are projections, not results.
7. **The funding work estimate.** The 2–8 ms for native funding work and the checkpoint share is an estimate from RSpace operation costs. If native stack operations cost as much as Rholang COMMs (about 1 ms each, measured in the legacy reducer breakdown), f approaches the top of its range and the one-send gain falls toward 72 times.

7.5 Validation

These measurements turn the projections into exit criteria:

- **Funding microbenchmark (phase 2).** The gate, commitment, debits and settlement for one envelope funded from one to four wallets. Target: under 8 ms on the measurement host.
- **Transfer benchmark (phase 2).** A REV transfer between two wallets as a deployment, end to end. Target: under 12 ms per transfer on the measurement host, and at least 150 transfers per second on 2 cores with independent payers.
- **Block benchmark (phase 2).** `phase_timings_by_block_size` and `cost_breakdown_of_one_envelope` rerun on the new path. Targets: settlement under 5 % of block time, settlement per envelope flat in block size (within 20 % from 1 to 64 envelopes), and one-send throughput of at least 150 per second on 2 cores.
- **Scaling run (phase 2).** The same block benchmark on 8 and 16 cores. Target: $\eta \geq 0.6$. A lower result points to RSpace contention and opens a work item.
- **Conservation.** Every executor and benchmark run checks that the sum over wallets, validator channels and the compute wallet equals the genesis supply after each block, and that replay reaches the same root for different box-car sizes.
- **The compute charge (phase 2).** On a corpus that exercises every row of Appendix B, the compute phlo recorded per wallet equals the schedule's figure, in play and in replay; matched sends pay no storage, unmatched and persistent ones pay theirs once.
- **B7 soak.** Sustained throughput against a legacy soak on the same hardware, with the hot-channel workloads of item 2 above as a separate profile.

8 The path to a working branch

This section answers one question: what is the quickest path to a working branch that carries the full implementation and can be merged back to `dev`? It reviews current `dev`, the Track A changes and the integration branch against the design of §6, and proposes a base and a sequence of phases.

8.1 Where the code stands (October 29, 2026)

Line of work	State
`dev`	At `252a86d1d` (October 28), 583 commits past the point where Track A forked on October 16. It has landed its own versions of several Track A fixes: oracle verdicts shared within a floor derivation with the validated floor kept (near A1a), a reused pool snapshot during block creation and mutex-free pool storage (near A4), the unfinalized cone walked over cached block facts (near A5), the finalizer as the single writer of the LFB with one finalizer task per Casper instance, and the re-fetch rate limit (equivalent to A7).
Track A (A1a–A9)	Not on `dev`. Three branches in series: `fix/finality-stall-track-a` (A1a, A2, A3), `fix/finalizer-forward-progress` (A1b, A1c) and `fix/stall-track-a-rest` (A4–A9), 67 files, about 4,100 lines added.
Integration branch	`integration/cost-accounted-ote-b1d866e45` at `d1f3ab5e1`: Track A, the cost-accounting work of `feature/cost-accounted-rho`, and the v6 seam through patch 0035. About 230,000 lines added, 534 commits behind `dev`, with 105 files that `dev` has also changed.
v6 seam	Canonical order, structural validity, the linearizer, records, attestation, the executor, pruning, the lag gate, inclusion checks and A-LIN: about 6,400 lines on the integration branch, mostly self-contained. Eight of its 21 files import from `costacc`, one or two lines each: the genesis resource policy (five uses), the executor's run types from `direct_wallet_funding`, the owner offer in proposal, and the close-block deploy. Only `rho_settlement.rs` is wholly tied to the old funding path. Its original form, `feature/cost-accounted-ote`, is 2,600 lines on an older `dev`.
P1 (vault precharge and refund)	Withdrawn, uncommitted, not to ship.
Annotation syntax	Parser on `rholang-rs` `feature/cost-accounting-transpiler` at `02cef80`, not on its master; `dev` pins `527af8a`, without it. Normalizer, protobuf messages and reducer support on `feature/cost-accounted-rho` only. Not on `dev`, `feature/cost-accounted-ote` or the v6 seam.
Cost schedule	On `dev`, in `accounting/costs.rs` and the reducer (Appendix B). File-I/O weights defined but discarded by `NoopMetering`.

8.2 Trial merges

Trial	Result
All of Track A into current `dev`	Conflicts in 15 files. The heaviest are `block_creator.rs` (9 hunks) and `finalization_runner.rs` (7). The rest are `casper.rs`, `block_admission.rs`, `types.rs`, `deploy_lifecycle.rs`, the Casper buffer store, metrics constants, five API and bonding tests, `test_node.rs` and `supply-chain/policy.toml`.
Track A one commit at a time	A2, the `commit_lfb` part of A1c, A6 and A8 apply cleanly, in that order: A8's tests use `commit_lfb`, so A8 conflicts if applied before A1c. A1a, A1b, the floor cursor, A3, A4, A5, A7 and A9 conflict. Most of those conflicts come from `dev`'s overlapping fixes, not from logic that disagrees.
`feature/cost-accounted-ote` into current `dev`	Conflicts in 9 files: `casper.rs`, `finalization_runner.rs`, four API tests, the bonding spec, `test_node.rs` and `supply-chain/policy.toml`. These are mostly constructor and test-harness signatures.
Integration branch into current `dev`	Not attempted in full. With 105 files changed on both sides and 534 commits of drift, the conflicts would fall largely in code that this design deletes.

8.3 The choice of base

	Current `dev` + reduced Track A	Continue the integration branch
Drift from `dev`	None at the start; each phase rebases cheaply.	534 commits; 105 files changed on both sides.
Code carried	Track A's fixes that `dev` lacks, then the v6 seam, then only what the design needs.	230,000 lines, of which at least 45,000 (`monetary_allocation`, `phlo_execution`, `owner_funding`, the controls) and most of the 28,000 in `costacc` are REV-funding machinery the design removes.
Conflict work	On code that stays.	Largely on code that is about to be deleted.
Review	Phases of a size a reviewer can read.	One very large merge.
What is lost	Nothing: the integration branch stays as a reference, and phase 3 takes pieces from it on purpose.	—

The simpler design is what makes the first column possible. Revisions 2 to 4 needed most of the branch's machinery: vault custody, holds, cursors, apportionment, and a byte-identical legacy path

beside the new one. This design needs the consensus seam and a small native layer: wallets, transfer, gate, settlement, prices and hooks. That fits on current `dev` directly.

> **Recommendation.** A new branch from current `dev`. Track A goes onto it first, reduced to what `dev` lacks, as its own pull request. The design is then built on top in three phases. The integration branch is frozen as a reference, not merged.

8.4 Phases

Ph.	Work	Exit criterion	Estimate
0	**Reduced Track A onto `dev`.** Drop A7, which `dev` has. Reconcile A1a, A4 and A5 with `dev`'s versions, keeping only what `dev` lacks, and listing what is kept and what is dropped before any code changes. Port A1b, A1c, A2, A3, A6, A8 and A9, starting with the four that apply cleanly.	The stall and finalizer tests pass on `dev`; its own pull request.	1–1.5 weeks
1	**The v6 seam.** Start from `feature/cost-accounted-ote` and add the improvements of patches 0028–0035: contracts and persistent executor state, the v6 body field, the execution-lag gate, deferred inclusion checks, the A-LIN switch, pruning, configuration and record packing. Separate it from `costacc` (a slim resource policy and run types replace its imports), and replace `rho_settlement.rs`. Deployments are plain signed `DeployData` carrying `phloLimit` and `phloPrice`. The executor runs one runtime session per envelope from the block pre-state, with a COMM counter beside `dev`'s per-runtime meter, which supplies the compute phlo.	v6 blocks are ordered, executed, replayed and attested on a test shard; COMM and compute phlo are recorded.	1.5–2 weeks

Ph.	Work	Exit criterion	Estimate
2	**Native REV and the two charges.** Wallets as located stacks keyed by REV address, created from `wallets.txt` at genesis; the native transfer with deposits as separate datums; the gate with its commitment table; the COMM charge to $F_{\mathrm{sender}(b)}$ and the compute charge to the compute wallet, in the canonical form, with the box-car node parameter; the storage rule for unmatched sends and receives; the compute wallet at genesis under the hook authority; the shard price floor in validity and the fixed node price behind the price hook; the no-op REV hook and the multi-signature hook authority from genesis; records without system logs; the conservation check over wallets, validator channels and the compute wallet; removal of what §6 takes off the path; the benchmarks of §7.5. **The annotation syntax** (§6.4): the `rholang-rs` branch merged to its master and `dev`'s pin moved; the normalizer ported; signed terms and stacks in the protobuf model; regions and stack literals in the reducer on the native layer. Signed terms may name only the deployer's own signature in this phase.	Conservation holds on every block; replay equality across box-car sizes; compute charges match the schedule on a test corpus; the transfer and one-send targets are met; the syntax corpus parses and normalizes.	2.5–3.5 weeks
3	**More signatures, and selective port from the integration branch.** Funding slots, sponsors and grants (signed terms naming an unforgeable name); owners (DR-135); compound signatures charged per component, with multi-signature wallets; `delta_sigma` (a tighter COMM part of Δ); footprints; each as its own change.	Multi-signer deploys charged exactly; the DR-135 owner tests; sponsored deploys; footprint-based concurrency.	2–3 weeks, overlapping phase 2

For one engineer, phases 0 to 2 give a working, mergeable branch with the core of the design in about five and a half to seven weeks; the syntax port adds about half a week to phase 2, and the compute charge little, since `dev`'s meter already computes it. With phase 3 overlapping, full scope takes about seven and a half to nine and a half weeks. Phase 0 can go to `dev` as soon as it is ready. Phases 1 and 2 can go as one pull request or two. Each phase rebases onto `dev` as it closes, rather than once at the end.

8.5 What carries over

- **Patches 0028–0035** carry over in phase 1, as the improvements on the seam.

- **The measurement tests** (`phase_timings_by_block_size`, `cost_breakdown_of_one_envelope`, `a_user_vault_transfer_costs`) carry over as the baseline for the phase 2 benchmarks.
- **From `feature/cost-accounted-rho`**, phase 2 takes the annotation syntax's normalizer and the semantics of its signed-term regions and stack literals.
- **From the integration branch**, phase 3 takes `delta_sigma`, per-signature metering, owners, multi-signature and footprints. The REV-funding machinery stays behind.
- **From `dev`**, the cost schedule carries over unchanged as the price list of the compute charge (Appendix B).
- **P1** stays withdrawn.

8.6 Other tracks

- **B5–B7** stand as in revision 2 (records and evidence, epochs, the soak and activation), with the throughput targets added to B7.
- **Interpreter defects** (clone audit, Tier 0): quadratic environment copying, the quadratic replay scan, quadratic match fall-through and quadratic stream reassembly. These are independent of cost accounting, low risk, and they help every path. They should land on `dev` beside phase 0.
- **The D-12 mapping.** `phloLimit` and `phloPrice` keep their `dev` meaning (§6). The mapping is written up as the normative text D-12 asked for, and ratified before phase 2 lands.

9 Decisions, risks and open questions

9.1 Decisions

	Decision	State
1	Wallets are located REV stacks on their owners' channels, disaggregated from the vault. Moving REV is native.	Agreed.
2	REV is conserved and minted only at genesis from `wallets.txt`. Further behaviour enters through a hook that defaults to a no-op.	Agreed (Q-14).
3	Phlo is the rate at which wallet REV is spent. It is not minted, and there is no escrow: the gate records a commitment.	Agreed (Q-16).
4	REV consumed by COMMs moves to the proposer that the block names. No burn, no fixed fee.	Agreed.
5	The shard minimum price is a validity floor. The validator's acceptance price is a fixed node price behind an updatable hook.	Agreed (Q-17).
6	Box-car batching of debits is a per-node configuration parameter.	Agreed.

	Decision	State
7	Hook updates require a multi-signature from addresses named at genesis.	Agreed.
8	No legacy chain and no migration; the byte-identical legacy rule is relaxed.	Agreed (Q-15).
9	The canonical settled form of §6.6, so that box-car size never changes the state root.	Proposed.
10	Base: a new branch from current `dev` with a reduced Track A, then phases 1 to 3. The integration branch is frozen as a reference.	Proposed.
11	Phase 0 goes to `dev` as its own pull request.	Proposed.
12	The throughput targets of §7.5 become exit criteria.	Proposed.
13	The clone-audit Tier 0 fixes land on `dev` beside phase 0.	Proposed.
14	A COMM costs one phlo. An accepted deployment's `phloPrice` is the rate at which its REV is spent per phlo, for both charges.	Agreed (Oct 29).
15	All non-COMM work under `{%P%}[s]` is priced by `dev`'s cost schedule and debited from the wallet at s at `phloPrice`.	Agreed (Oct 29).
16	The compute charge goes to one compute wallet per shard, held by the hook authority (the same genesis addresses and threshold). Splitting it is a matter for the REV hook.	Agreed (Oct 29).
17	A send or receive left unmatched in the tuplespace pays its storage as compute. Rent over block time is deferred to a later revision.	Agreed (Oct 29).
18	File I/O and pattern matching stay uncharged in this revision.	Agreed (Oct 29).
19	Storage is charged on what a run leaves in the tuplespace; there is no cross-envelope storage refund, and `dev`'s COMM event-storage charge is replaced by the COMM's one phlo.	Proposed.
20	The annotation syntax is ported in phase 2: the `rholang-rs` parser as it is, the branch's normalizer as it is, and the reducer's regions and stack literals re-implemented on the native layer.	Proposed.
21	Wallet channels for public keys are keyed by REV address, so that genesis can read `wallets.txt`.	Proposed.
22	Phlo as a rate priced by `phloPrice` supersedes DR-27's pegging of phlo to REV on `feature/cost-accounted-rho`.	Proposed.

9.2 Risks

Risk	Mitigation
Box-car size leaks into the state root	The canonical settled form (§6.6); a replay-equality test across box-car sizes is a phase 2 exit criterion.
Cost per signature	Phase 2 admits only the deployer's signature in signed terms, so all of an envelope's charges fall on one wallet and are exact. Charging by region for other signatures waits for phase 3.
The compute meter diverges between validators	The schedule is `dev`'s, already consensus-critical on the legacy path; its constants are pinned by golden tests. Replay checks the recorded compute phlo per wallet.
The storage rule differs from `dev`	`dev` refunds a producer's storage to whichever deploy consumes it; the design does not. The difference is deliberate (§6.3) and is tested against a corpus of matched, unmatched and persistent sends.
The compute wallet becomes a hot spot	Deposits commute and are combined into one per block; no envelope reads it.
The syntax depends on another repository	The `rholang-rs` branch must merge to its master before `dev`'s pin moves; this is the first item of the syntax work, so a delay shows early.
Known gaps in the schedule	Flat-priced operations, pattern matching, system processes and file I/O are listed in Appendix B; each is a later change to the schedule, not to the design.
`dev` keeps moving	Rebase at the close of each phase; land phase 0 early.
Reconciling A1a, A4 and A5 with `dev`'s versions drops a fix that `dev` lacks	Phase 0 begins with a written reconciliation list, reviewed before code changes; the Track A tests run against the result.
Multi-core efficiency is low (RSpace contention)	The phase 2 scaling run measures it early. RSpace hot-store contention becomes a work item if $\eta < 0.6$.
Client changes	The deployment contract (`phloLimit`, `phloPrice`) is unchanged. Wallet queries and transfers change behind the vault facade; tooling changes (`node deploy`, Embers, the gateway) follow phase 2.
Applications build their own hot channels	Document the chain rule for contract authors, and that deposits commute while spends from one wallet do not.
The consensus cap binds before cores do	Raise E within the record arithmetic, tune the proposal rate, and pursue refinement R1.
Conservation broken by a defect or a hook	Conservation is checked on every block, in play and replay, after the hooks run.
Risks of revision 2	A-LIN, the finalizer commit, the charge model and host-work determinism stand as listed there and are mitigated as delivered.

9.3 Questions

Q-1 to Q-12 of revision 2 stand. Q-2 (evidence penalties) and Q-7 (fallback distance, record cap, retention) have been decided. Q-13 is answered by §6. Q-14 to Q-17 of revision 4 are answered:

ID	Question	Answer
Q-14	How REV is minted after genesis, and whether a proposer's receipts are shared with stakers.	REV is conserved and minted only at genesis from `wallets.txt`. Further behaviour comes through a hook that defaults to a no-op and is replaced by a contract.
Q-15	How existing balances move to stacks.	There is no legacy to preserve and no migration.
Q-16	Where the escrow lives.	There is no escrow. REV stays in the wallet; phlo only marks the rate at which it is spent.
Q-17	The form of a validator's acceptance price.	A fixed price for now, behind a hook that can be updated.

Open:

ID	Question
Q-18	Confirm the canonical settled form of §6.6: one combined datum per paying wallet, one deposit per block on the proposer's channel and one on the compute wallet, with a term's reads of its own wallet seeing the pre-state balance less the commitments against it up to its own gate position. (Revision 5 had one proposer deposit per envelope, and only the envelope's own commitment subtracted.)
Q-19	The multi-signature threshold for hook updates: a fixed k of n at genesis, or a threshold that the hook authority can itself change.
Q-20	The points at which the REV hook is called: after every block's settlement, at epoch boundaries, or both.
Q-21	How a compound signature's compute charge is divided among its components: equally, in a fixed ratio named in the term, or by a rule of the funding slot.
Q-22	Whether a signed term may name the hash of a process, `# P`, so that a contract pays for its own work from the wallet at its hash, and who may fund that wallet.
Q-23	Whether contracts may create token stacks for tokens other than REV, as the paper's minting primitive allows, or whether every stack is REV.
Q-24	A static estimate of the compute part of Δ, so that the gate can commit less than `phloLimit`.

A Detailed stall findings

The table lists the findings of the stall review beyond those in Section 3, by subsystem, with the lines at which each was located on `master` at `7264c98`. Severity is the review's estimate of the contribution to a stall that worsens under load.

Subsystem	Finding	Location	Sev.
Proposer	Unfinalized cone walked once per parent with full block decodes.	`block_creator.rs:1497-1725, 2085-2131`	High
Proposer	Whole pool sorted and encoded per selection, three times.	`block_creator.rs: 269-279,349-415`	Med
Proposer	Per-deploy WARN logged for every in-scope deploy on every proposal.	`block_creator.rs:1380-1440`	Med
Merge	Retry loop rebuilds branches and conflict map each pass.	`dag_merger.rs: 705-752`	High
Merge	Stale-diff expansion runs one DAG search per block pair.	`dag_merger.rs: 1855-1915`	Med
Merge	Dependency ordering cubic in branch size; `depends` allocates sets per call.	`dag_merger.rs: 82-120,1456-1502`	Med
Merge	`ChannelChange::combine` quadratic on hot channels.	`channel_change.rs:17-55`	Med
Merge	Block-index cache returns deep clones; bypasses its FIFO bound.	`interpreter_util.rs: 1316-1342`	Med
Finality	Uncached LMDB metadata lookups inside `block_in_place`.	`block_dag_key_value_storage.rs:144-151`	High
Finality	FT propagation rescans up to 50,000 blocks under both write locks.	`block_dag_key_value_storage.rs:1699-1727`	Med
Finality	Estimator scoring walks $O(V \times (\text{tip} - \text{LCA}))$.	`estimator.rs: 232-378`	Med
Finality	Redundant fault-tolerance oracle run after each LFB advance.	`finalization_runner.rs: 571-576`	Med
Block processing	DAG membership via full representation per gossip message.	`block_admission.rs:34-67`	High
Block processing	Pendant full scan every 32 blocks with block decodes.	`buffer_resolver.rs:59-109`	Med
Block processing	Retriever sends serially, one hash at a time.	`block_retriever.rs:1032-1139`	Med
Block processing	Full snapshot computed per incoming block; cache keyed on DAG generation.	`block_processor.rs:548-553`	Med
RSpace	`put_continuation` formats a `Debug` string per waiting continuation.	`hot_store.rs: 528-559,1000`	Med
RSpace	Checkpoint CPU and LMDB writes on tokio workers.	`ispace_impl.rs: 41-78`	Med

Subsystem	Finding	Location	Sev.
RSpace	History caches cleared in bulk; radix cache evicts arbitrary nodes.	`hot_store.rs: 1091–1117`, `radix_tree.rs: 875–890`	Med
Node	gRPC `find_deploy` server-side retry loop.	`deploy_grpc_ service_v1.rs: 570–643`	Med
Node	HTTP offload without an admission limit.	`shared_handlers. rs:626–640`	Low

B The cost schedule for non-COMM compute

This appendix lists the price list of the compute charge (§6.3). It is `dev`'s existing cost schedule at `252a86d1d`, unchanged: the base weights are in `rholang/src/rust/interpreter/accounting/costs.rs`, and the charges are applied in `reduce.rs` unless a row says otherwise. Costs are in phlo; under `{%P%}[s]` each phlo costs the wallet at s the deployment's `phloPrice` in REV.

Sizes are byte lengths of the protobuf encoding unless a row says otherwise ($|t|$ is the encoded size of term t). Every method call `e.m(...)` pays the method-call charge of 10 in addition to the method's own row. A COMM is not in this schedule: it costs one phlo and pays the proposer.

B.1 Process evaluation and the deployment

Construct	Cost (phlo)	Charged at
Send `x!(...)` evaluated	11	`reduce.rs:1242`
Receive `for(...)` evaluated	11	`reduce.rs:1285`
Variable evaluated	10	`reduce.rs:1356`
`match`	12, once per match (not per case)	`reduce.rs:1391`
`if` / `else`	12	`reduce.rs:1446`
`new` $x_1, \ldots, x_n$	$2n + 10$	`reduce.rs:1602`
Method call `e.m(...)`	10, plus the method's own row	`reduce.rs: 1646,2996`
Substitution into a term	$\lvert t\rvert$ of the substituted term; on failure, of the original	`substitute.rs: 91–98`
Parsing the deployment's source	length of the source text	`interpreter.rs: 59,93`

B.2 Arithmetic and logic

For BigInt, ℓ_a, ℓ_b are the byte lengths of the operands. For BigRat, n_a, d_a, n_b, d_b are the byte lengths of the numerators and denominators, and m is the largest of them.

Construct	Cost (phlo)	Charged at
`a + b` (fixed-width numbers)	3	`reduce.rs: 2259–2283`
`a - b`	3	`reduce.rs: 2371–2395`
`a * b`	9	`reduce.rs: 1957–1985`
`a / b`	9	`reduce.rs: 2047–2079`
`a % b`	9	`reduce.rs: 2152–2161`
<, <=, >, >= (Bool, Int, Int32, Uint*, String, Double, Float32)	3, whatever the operand size	`reduce.rs: 1684–1758`
==, !=	$\min(\|a\|, \|b\|)$	`reduce.rs: 2537,2554`
`and`, `or`	2	`reduce.rs: 2569,2579`
BigInt +, −	$\max(\max(\ell_a, \ell_b) + 1,\ 3)$	`reduce.rs: 2291–2426`
BigInt *, /, %	$\max(\ell_a \ell_b,\ 9)$	`reduce.rs: 1993–2214`
BigInt negation	$\max(\ell_a, 1)$	`reduce.rs: 1920,1935`
BigInt comparison	$\max(\max(\ell_a, \ell_b),\ 3)$	`reduce.rs: 1777,1798`
BigRat +, −	$\max(4m^2 + m,\ 3)$	`reduce.rs: 2296,2409`
BigRat *	$\max(n_a n_b + d_a d_b + m,\ 9)$	`reduce.rs:1997`
BigRat /	$\max(n_a d_b + d_a n_b + m,\ 9)$	`reduce.rs:2095`
BigRat negation	$\max(n_a, 1)$	`reduce.rs:1925`
BigRat comparison	$\max(\max(n_a d_b,\ n_b d_a),\ 3)$	`reduce.rs:1785`

B.3 Strings, bytes and collection operators

Construct	Cost (phlo)	Charged at
`string % map` (interpolation)	$10 +$ length $\times$ map size	`reduce.rs: 2673,2692`
`s1 ++ s2` (String)	$10 + \lvert s_1 \rvert + \lvert s_2 \rvert$ in characters	`reduce.rs: 2726,2733`
`b1 ++ b2` (ByteArray)	$10 + \lfloor \log_{10} \lvert b_1 \rvert \rfloor$; 10 if b_1 is empty	`reduce.rs: 2726,2740`
`l1 ++ l2` (List)	$10+$ elements of l_1	`reduce.rs: 2726,2749`
`set + e`	$10 + 3$	`reduce.rs: 2325,6337`
`set - e`, `map - k`	$10 + 3$	`reduce.rs: 2443,2459`
`set1 -- set2`	$10 + 3 \lvert set_2 \rvert$	`reduce.rs: 2828,3588`

B.4 Methods

Each row is in addition to the method-call charge of 10.

Method	Cost (phlo)	Charged at
`.nth(i)`	10	`reduce.rs:3059`
`.toByteArray()`	$\lvert t \rvert$	`reduce.rs:3120`
`.hexToBytes()`	length of the string	`reduce.rs:3154`
`.bytesToHex()`	length of the byte array	`reduce.rs:3201`
`.concatBytes()`	total bytes concatenated	`reduce.rs:3270`
`.validUtf8PrefixLen()`, `.decodeUtf8()`	length of the byte array	`reduce.rs: 3322,3374`
`.toUtf8Bytes()`	length of the string	`reduce.rs:3417`
`.length()`	10	`reduce.rs:6838`
`.slice(from, to)`	`to`	`reduce.rs:6973`
`.take(n)`	n	`reduce.rs:7035`
`.union(other)` (Set, Map, PathMap)	$3\times$ size of `other`	`reduce.rs: 3463-3518`
`.diff(other)`	$3\times$ size of `other`	`reduce.rs: 3588-3642`
`.add(e)`, `.set(k, v)`	3	`reduce.rs: 6337,6663`
`.delete(e)`	3	`reduce.rs:6421`
`.contains(e)`, `.get(k)`, `.getOrElse(k, d)`	3	`reduce.rs: 6486-6600`

Method	Cost (phlo)	Charged at
`.keys()`	10, whatever the map size	`reduce.rs:6722`
`.size()`	number of elements	`reduce.rs:6785`
`.toList()` (Set, Map, Tuple)	number of elements	`reduce.rs: 7062-7104`
PathMap `.intersection`, `.restriction`, `.joinInto`	$3\times$ size of the argument	`reduce.rs:3716, 3791,5145-5231`
PathMap `.dropHead(n)`	$3n$	`reduce.rs:3857`
PathMap `.getLeaf`, `.getSubtrie`	3	`reduce.rs: 4376,4457`
PathMap `.setLeaf`	3	`reduce.rs:4514`
PathMap `.removeLeaf`, `.removeBranches`, `.prunePath`	3	`reduce.rs: 4894,4995,5601`
PathMap `.run`, `.readZipper`, `.readZipperAt`, `.writeZipper`, `.writeZipperAt`, `.descendTo`, `.setSubtrie`, `.graft`, `.atPath`, `.pathExists`, `.createPath`	3 each	`reduce.rs: 3954-5511`
Zipper `.reset`, `.ascendOne`, `.ascend`, `.childCount`, `.descendFirst`, `.descendIndexedBranch`, `.toNextSibling`, `.toPrevSibling`	3 each	`reduce.rs: 5649-6271`

B.5 Storage

`dev` charges these sizes up front and refunds them when a COMM consumes the datum (`storage/charging_rspace.rs`). Under this design only what the run leaves in the tuplespace pays, once (§6.3). For a join, k is its number of channels.

Left in the tuplespace	Cost (phlo)	`dev` source
A send	$\lvert\text{channel}\rvert + \sum \lvert\text{data}\rvert + (32 + 32k)$, with $k = 1$	`charging_rspace.rs:111,304`
A receive	$\sum \lvert\text{channels}\rvert + \sum \lvert\text{patterns}\rvert + \lvert\text{continuation}\rvert + (32 + 32k)$	`charging_rspace.rs:79,304`
A persistent send or receive	as above, once, when it is introduced	`charging_rspace.rs:279-325`

Left in the tuplespace	Cost (phlo)	`dev` source
Replaced. `dev`'s COMM event storage, $(32+32k)+64k$ (128 for one channel), is replaced by the one phlo of the COMM. `dev`'s refund to a consuming deploy of the producer's storage does not exist here.		

B.6 Known gaps

These are charged at a flat rate, or not at all, on `dev`. They stay as they are in this revision and are candidates for later changes to the schedule.

Item	On `dev`	Consequence
Pattern matching (the spatial matcher)	Not charged; `match` pays a flat 12 and a receive 11	A complex pattern against a large term costs the same as a trivial one.
File I/O, `rho:io:fs:native:*`	Weights defined in `io/costs.rs` (100 per call, 200 per path mutation, $+1$ per byte read, $+2$ per byte written, $+32$ per directory entry) but discarded by `NoopMetering` (`rho_runtime.rs:1309`)	File I/O is free.
System processes (hashing, signature verification, registry)	Not charged beyond the COMM that invokes them	Hashing or verifying a large input is free at the compute level.
`.toSet()`, `.toMap()`, `.toString()`, `.toBigInt()`	Only the method-call charge of 10	Converting or rendering a large term is flat-priced.
Comparisons <, <=, >, >=	Flat 3	Comparing long strings is flat-priced.
`.keys()`	Flat 10	Building the key set of a large map is flat-priced.
`l1 ++ l2`	Charges the length of l_1	`costs.rs` documents the length of l_2; the call site passes l_1.
`channel_eval_cost` (11)	Defined, never charged	Unused weight.
Parallel composition, quote, dequote, bundles	No charge of their own	Their cost appears only through substitution and storage.
Rent	Not charged over time	Stored data pays once; recurring rent is a later revision.

C Sources

Papers, read directly, in `F1R3FLY-io/publications` at `37915af`:

- `cost-accounting/cost-accounted-rho.tex`: signatures as names, token stacks, the five rules, the join schema, object capabilities and located stacks, funding slots, the RSpace and Casper implications, the transaction analysis, the linear resource proof, overcharge and refund, the acceptance protocol, deployment boundaries, the translation to pure rho, and the validator fee example.
- `cost-accounting-as-monad/continued-gslt-cost-v2.tex`: the cost endofunctor, the two monoids, located resource stacks, and local sufficiency of per-purse proofs.
- `cost-spacetime/spacetime-functor.tex`: footprints and Bernstein independence; time from the stack and space from the surfaces; number as volume; proper time as the longest chain.
- `virtual-tokens/virtual-token.tex`: the virtual token as a unit of account.
- `history-and-cost/two-erasures.tex`: internalisation as a lax algebra with an overhead grade.
- `f1r3node-profiling/clone-audit.tex`: the interpreter's asymptotic copy defects and their microbenchmarks.
- `cost-accounting/stall-loop-design-5-10-1-response.tex`: the Casper Working Group's finalizer design.

Code, `F1R3FLY-io/f1r3node-rust`, branch `integration/cost-accounted-ote-b1d866e45` at `d1f3ab5e1`:

- in `rholang/src/rust/interpreter/`: `reduce.rs`, `accounting/authority.rs` and `accounting/delta_sigma/estimate.rs`;
- in `casper/src/rust/util/rholang/costacc/`: `supply.rs`, `owner_offer.rs` and `direct_wallet_funding/execution/`;
- `casper/src/main/resources/SystemVaultV6.rho` and `casper/src/rust/v6/`.

Code, `F1R3FLY-io/f1r3node-rust`, branch `dev` at `252a86d1d`, for the cost schedule:

- in `rholang/src/rust/interpreter/`: `accounting/costs.rs`, `reduce.rs`, `substitute.rs`, `interpreter.rs`, `storage/charging_rspace.rs`, `io/costs.rs` and `rho_runtime.rs`.

Code, the annotation syntax:

- `F1R3FLY-io/rholang-rs`, branch `feature/cost-accounting-transpiler` at `02cef80`: `docs/cost-accounting/parser-syntax.md` and the `cost_*` corpus;
- `F1R3FLY-io/f1r3node-rust`, branch `feature/cost-accounted-rho` at `1b5a92f13`: `compiler/normalizer/cost_accounting/`, `eval_cost_signed_term` and `eval_cost_stack` in `reduce.rs`, and `docs/casper/theory/cost-accounting-as-monad-correspondence.md` (DR-27).

Measurements, on the host named on the first page: `v6_executor_spec::phase_timings_by_block_size`, `cost_breakdown_of_one_envelope`, `a_user_vault_transfer_costs`, the record measurements of patch 0035, the vault-play measurements of October 28, and `cost_accounting_perf_spec` (legacy precharge, refund and replay).

Branches compared in §8: `dev` at `252a86d1d`; `fix/finality-stall-track-a`, `fix/finalizer-forward-progress` and `fix/stall-track-a-rest`; `feature/cost-accounted-ote`; the integration branch above. Trial merges were made in a scratch clone.

Earlier designs: revisions 1 to 5 of this document (October 16 to 29, 2026); D-12 (deploy cost limits, rejected September 16, 2026).