PRODUCT
CATALOGUE

PT. Taurus Sampai Tuntas

Solving Your IT Problem

MIKROTIK

Indoor Access Point

hAP mini
- 3 port Fast Ethernet
- Build-in Wireless 2.4Ghz
- RouterOS level 4

hAP ac lite
- 5 Port Fast Ethernet
- Dual-Concurrent 2.4/5GHz AP
- USB for 3G/4G support

hAP lite TC
- 4 port Fast Ethernet
- Build-in Wireless 2.4Ghz
- Antenna internal Dual-Chain 2 x 1.5dbi

RB951Ui-2HnD
- 2.4GHz AP with 5 Ethernet ports
- 600MHz CPU & 128MB RAM
- USB for 3G/4G support

cAP ac
- Ceiling Mount Design
- Support PoE in 802.3at/at
- High-Gain Ceiling Antenna

cAP lite
- 650 MHz CPU, 64 MB RAM
- 1.5 dBi 2.4 GHz antenna
- 1 port Fast Ethernet

Ethernet Routers

hEX Lite
- 5 port Fast Ethernet
- 850MHz CPU, 64MB RAM
- RouterOS level 4

hEX
- 5 x Gigabit Ethernet
- Dual Core 880MHz CPU
- RouterOS level 4

hEX PoE
- 5 Gigabit Ethernet +1 SFP
- 800MHz CPU, 128MB RAM
- RouterOS level 4

hEX S
- 5 Gigabit Ethernet +1 SFP
- Dual Core 880MHz CPU
- RouterOS level 4

Cloud Router Switch

CRS326-24G-2S+RM

- 24 Gigabit Ethernet ports
- 2 SFP+ ports for 10 Gigabit connectivity
- Powered by SwOS
- 1U rackmount case

CRS312-4C+8XG-RM

- 8 x 10G Ethernet ports
- 4 Combo 10G Ethernet/SFP+ ports
- Dual Power Supply & 1U Rackmount Case

CRS326-24S+2Q+RM

- 2 x 40 Gbps QSFP+ ports
- 24 SFP+ ports for 10 Gigabit connectivity
- Dual Power Supply & 1U rackmount case

CRS354-48G-4S+2Q+RM

- 2 x 40 Gbps QSFP+ ports
- 48 Gigabit Ethernet ports & 4 SFP+ ports for 10 Gigabit connectivity
- Dual Power Supply & 1U Rackmount Case

Outdoor Wireless Antenna

SXTsq Lite2

- Antenna gain 10dBi
- Protocols 802.11b/g/n
- Wireless bands 2.4 GHz

LDF 5 ac

- Dual chain 5GHz
- Supports 802.11ac
- RouterOS level 3

LHG XL 2

- 21 dBi grid Antenna
- Dual Chain 2.4GHz
- RouterOS level 3

DISC Lite5

- Dual Chain 802.11n CPE
- 600MHz CPU, 64MB RAM
- RouterOS level 3

UBIQUITI
NETWORKS

Indoor Access Point

UAP-AC-SHD
- WiFi 5 Dual-Radio
- 8 Spatial Streams
- 140 m² Coverage
- 1,000+ connected devices

U6-Pro
WiFi 6
- 140 m² coverage
- 350+ connected devices
- WiFi 6 (4x4 MIMO)
- Powered using PoE+

U7-Pro
WiFi 7
- WiFi 7 Tri-Radio with 6 GHz
- 6 Spatial Streams
- 140 m² coverage
- 300+ connected devices

U6-LR
WiFi 6
- 185 m² coverage
- 350+ connected devices
- WiFi 6 (4x4 MIMO)
- Powered using PoE+

Outdoor Access Point

U6 Mesh
- 140 m² coverage
- 250+ connected devices
- WiFi 5 (2x2 MIMO)
- Powered using PoE
- Versatile wall or pole mounting

UAP-AC-M-PRO
- 185 m² coverage
- 250+ connected devices
- WiFi 5 (3x3 MIMO)
- Powered using PoE
- Versatile wall or pole mounting

UAP-AC-M
- 140 m² coverage
- 250+ connected devices
- WiFi 5 (2x2 MIMO)
- Powered using PoE
- Versatile wall or pole mounting

UK-Ultra
- 115 m² coverage with internal antenna
- 200+ connected devices
- WiFi 5 (3x3 MIMO)
- Powered using PoE
- Versatile wall or pole mounting

UBIQUITI
NETWORKS

UniFi Switching

USW-24 (Non PoE)

- 24 Gigabit Ethernet ports
- 2 SFP ports for 1 Gigabit connectivity
- Layer 2 switch with a silent, fanless cooling system.

USW-48 (Non PoE)

- 48 Gigabit Ethernet ports
- 4 SFP ports for 1 Gigabit connectivity
- Layer 2 switch with a silent, fanless cooling system.

USW-16-POE (42W)

- 16 Gigabit Ethernet ports
- 2 SFP ports for 1 Gigabit connectivity
- Layer 2 PoE switch with a silent, fanless cooling system.

USW-24-POE (95W)

- 24 Gigabit Ethernet ports
- 2 SFP ports for 1 Gigabit connectivity
- Layer 2 PoE switch with a silent, fanless cooling system.

USW-48-POE (195W)

- 48 Gigabit Ethernet ports
- 4 SFP ports for 1 Gigabit connectivity
- Layer 2 PoE switch with a silent, fanless cooling system.

USW-Aggregation

- 8 SFP+ ports for 10 Gigabit connectivity
- Layer 2 switch with a silent, fanless cooling system.

Indoor Access Point

RG-AP720-L
Wi-Fi 5 Dual-Radio Indoor AP

- 2 Port Gigabit Ethernet
- Wi-Fi 5 Wireless 1167 Mbps
- Built-in Omni-directional
- Wall / Ceiling mounting

RG-RAP2260(G)
Wi-Fi 6 AX1800 Indoor AP

- 2 Port Gigabit Ethernet
- Wi-Fi 6 Wireless 1775Mbps
- Built-in Omni-directional
- Client connections over 500

RG-RAP2200(F)
Wi-Fi 5 1267Mbps Indoor AP

- 2 Port Gigabit Ethernet
- Wi-Fi 5 Wireless 1267 Mbps
- Built-in Omni-directional
- Recomended Clients : 48 Clients

RG-RAP2200(E)
Wi-Fi 5 1267Mbps Indoor AP

- 2 Port Gigabit Ethernet
- Wi-Fi 5 Wireless 1267 Mbps
- Built-in Omni-directional
- Recomended Clients : 80 Clients

RG-AP840-L
Wi-Fi 6 Dual-Radio Indoor AP

- 5 Gbps SFP & RJ45 Combo Port
- Wi-Fi 6 Wireless 1775Mbps
- Built-in Omni-directional
- Maximum 1024 Client connections

RG-AP820-L(V3)
Wi-Fi 6 AX3000 Indoor AP

- 1 Port Gigabit + 1 SFP Port
- Wi-Fi 6 Wireless 2975 Mbps
- Wall/Ceiling mounting
- Auto MDI/MDIX Crossover

Outdoor Access Point & Wireless Bridge

RG-EST310 V2
- Wi-Fi 5 867Mbps (5Ghz)
- Distance up to 1 KM
- Antenna Directional 10 dBi
- 1 Port Fast Ethernet

RG-RAP6202(G)
Wi-Fi 5 AC1300 Outdoor AP

- 2 Port Gigabit Ethernet
- Wi-Fi 5 Wireless 1267 Mbps
- Recomended Clients : 48

RG-RAP6262(G)
Wi-Fi 6 AX1800 Outdoor AP

- 2 Port Gigabit Ethernet
- Wi-Fi 6 Wireless 1775Mbps
- Recomended Clients : 100

RG-EST350 V2
- Wi-Fi 5 867Mbps (5Ghz)
- Distance up to 5 KM
- Antenna Directional 15 dBi
- 2 Port Gigabit Ethernet

Unmanaged Switch

RG-ES05G
- 5 Port Gigabit Ethernet
- Plug and Play Energy Saving
- Support auto MDI/MDIX
- Mac Address 2K

RG-ES08G
- 8 Port Gigabit Ethernet
- Plug and Play Energy Saving
- Support auto MDI/MDIX
- Mac Address 4K

RG-ES105D
- 5 Port Fast Ethernet
- High Network Reliability
- Plug and Play Energy Saving
- Port surge 6 kV

RG-ES108GD
- 8 Port Gigabit Ethernet
- High Network Reliability
- Plug and Play Energy Saving
- Port surge 6 kV

RG-ES116G
- 16 Port Gigabit Ethernet
- Plug and Play Energy Saving
- Fanfree and quiet design
- Mac Address 8K

RG-ES124GD
- 24 Port Gigabit Ethernet
- Plug and Play Energy Saving
- Fanfree and quiet design
- Mac Address 8K

Smart Cloud Managed Switch

RG-ES205GC
- 5 Port Gigabit Ethernet
- IP Camera Recognition
- Automatic Loop Prevention
- Fanless, Quiet and Compact

RG-ES205GC-P
- 5 Port Gigabit (4 PoE+ ports)
- Maximum VLAN 16
- IP Camera Recognition
- Automatic Loop Prevention

RG-ES208GC
- 8 Port Gigabit Ethernet
- IP Camera Recognition
- Automatic Loop Prevention
- Fanless, Quiet and Compact

RG-ES206GS-P
- 5 Port Gigabit + 1 Combo Port
- IP Camera Recognition
- Automatic Loop Prevention
- Maximum VLAN 16

RG-ES216GC
- 16 Port Gigabit Ethernet
- Maximum VLAN 16
- IP Camera Recognition
- Automatic Loop Prevention

RG-ES209GC-P
- 9 Port Gigabit (8 PoE+ ports)
- IP Camera Recognition
- Automatic Loop Prevention
- Fanless, Quiet and Compact

RG-ES224GC
- 24 Port Gigabit Ethernet
- Maximum VLAN 16
- IP Camera Recognition
- Automatic Loop Prevention

RG-ES218GC-P
- 16 Port Gigabit + 2 SFP Port
- Max PoE budget 240W
- Maximum VLAN 16
- Automatic Loop Prevention

Layer 2 Cloud Managed Switch

RG-NBS3100-8GT2SFP-P

- 24 Gigabit Ethernet ports
- 2 SFP ports for 1 Gigabit connectivity
- Layer 2 switch with a silent, fanless cooling system.

RG-NBS3100-24GT4SFP-P

- 24 Gigabit Ethernet ports
- 2 SFP ports for 1 Gigabit connectivity
- Layer 2 switch with a silent, fanless cooling system.

RG-NBS3200-24GT4XS

- 24 Gigabit Ethernet ports
- 2 SFP ports for 1 Gigabit connectivity
- Layer 2 switch with a silent, fanless cooling system.

RG-NBS3200-48GT4XS

- 24 Gigabit Ethernet ports
- 2 SFP ports for 1 Gigabit connectivity
- Layer 2 switch with a silent, fanless cooling system.

Cloud Managed Router

RG-EG105G-P V2
- 5 Port Gigabit Ethernet
- 100 Concurrent Users
- Dual-WAN Load Balancing
- IPSec, OpenVPN, PPTP, L2TP
- Free Cloud Management

RG-EG209GS
- 8 Port Gigabit + 1 SFP Port
- 200 Concurrent Users
- Seamless Failover
- Max. 4 WAN Load Balancing
- Free Cloud Management

RG-EG210G-P
- 10 Port Gigabit Ethernet
- 200 Concurrent Users
- Seamless Failover
- Dual-WAN Load Balancing
- Free Cloud Management

RG-EG310GH-P-E
- 10 Port Gigabit Ethernet
- 300 Concurrent Users
- 64 VPN Tunnels
- OpenVPN, IPSec, L2TP, PPTP
- Free Cloud Management

Wi-Fi Mesh Router

RG-EW1200G PRO

- 4 Port Gigabit Ethernet
- Wi-Fi 5 Wireless 1300 Mbps
- Recomended Clients : 32

RG-EW1800GX PRO

Wi-Fi 6

- 4 Port Gigabit Ethernet
- Wi-Fi 6 Wireless 1800 Mbps
- VPN, Beamforming, OFDMA

RG-M18 **Wi-Fi 6**

- Wi-Fi 6 1800 Mbps (4 dBi)
- 4 Internal Antennas
- Up to 48 Users Connected
- Support WIFI Mesh

RG-M32 **Wi-Fi 6**

- Wi-Fi 6 3200 Mbps (4 dBi)
- 4 Internal Antennas
- Up to 64 Users Connected
- Support WIFI Mesh

RG-EW1200

- Wi-Fi 5 Wireless 1167 Mbps
- Recomended Clients : 24
- 4 Omnidirectional Antennas

RG-EW3000GX PRO

Wi-Fi 6

- Wi-Fi 6 Wireless 3000 Mbps
- 5 External Antennas
- Recomended Clients : 60

RG-EW3200GX PRO

Wi-Fi 6

- Wi-Fi 6 Wireless 3200 Mbps
- Recomended Clients : 60
- Support WIFI Mesh

Accessories

RG-POE-AF15
1 Port PoE Injector
(52 V, 15.6 W)

RG-POE-AT30
1 Port PoE Injector
(52 V, 31.2 W)

RG-E-120(GE)
1-port Gigabit PoE
Adaptor (802.3af)

RG-E-130(GE)
1-port Gigabit PoE
Adaptor (802.3at)

Indoor Access Point

WiFi 6 — GWN7664

- 3.55Gbps Wired Throughput
- Up to 175m Coverage Range
- Client Devices Up to 750
- Dual-Band (4x4 MIMO)

WiFi 6 — GWN7660

- 1.77Gbps Wireless Throughput
- Up to 175m Coverage Range
- Client Devices Up to 256
- Dual-Band (2x2 MIMO)

GWN7630

- 2.33Gbps Wired Throughput
- Up to 175m Coverage Range
- Client Devices Up to 200
- Dual-Band (4x4 MIMO)

WiFi 6 — GWN7661

- 1.77Gbps Wireless Throughput
- Up to 100m Coverage Range
- Client Devices Up to 500
- Dual-Band (2x2 MIMO)

GWN7602

- 1.17Gbps Wireless Throughput
- Up to 100m Coverage Range
- Client Devices Up to 80
- Dual-Band (2x2 MIMO)

GWN7624

- 2.03 Gbps Wireless Throughput
- Up to 175m Coverage Range
- Client Devices Up to 200
- Dual-Band (4x4 MIMO)

Outdoor Access Point

GWN7602

- 1.27Gbps Wireless Throughput
- Up to 300m Coverage Range
- Client Devices Up to 450
- Dual-Band (2x2 MIMO)

WiFi 6 — GWN7664LR

- 3.55Gbps Wireless Throughput
- Up to 300m Coverage Range
- Client Devices Up to 750
- Dual-Band (4x4 MIMO)

WiFi 6 — GWN7660LR

- 1.77Gbps Wireless Throughput
- Up to 250m Coverage Range
- Client Devices Up to 500
- Dual-Band (2x2 MIMO)

GWN7605LR

- 1.27Gbps Wireless Throughput
- Up to 250m Coverage Range
- Client Devices Up to 100
- Dual-Band (2x2 MIMO)

![Grandstream - Connecting The World]

Gigabit Routers

GWN7062

- 1.77Gbps Wireless Throughput
- Client Devices concurrent 256
- Dual-Band (2x2 MIMO)
- Secure Cloud Provisioning Through GWN.Cloud

Wi-Fi 6

GWN7052(F)

- 1.27Gbps Wireless Throughput
- Up to 175m Coverage Range
- 100 Concurrent Client Devices
- Dual-Band (2x2 MIMO)

GWN7001

Multi-WAN Gigabit VPN Routers

- 6 Port Gigabit Ethernet Ports
- Max. VPN Tunnels Up to 50
- Multiple WAN Ports Load Balancing
- Network Management up to 100 GWN

GWN7002

Multi-WAN Gigabit VPN Routers

- 4x Gigabit Ethernet Ports
- 2x 2.5 Gigabit SFP Ports
- Max. VPN Tunnels Up to 50
- Network Management up to 100 GWN

GWN7003

Multi-WAN Gigabit VPN Routers

- 9x Gigabit Ethernet ports
- 2x 2.5 Gigabit SFP ports
- Max. VPN Tunnels Up to 100
- Network Management up to 150 GWN

Network Switches

Layer 2+ managed

Unmanaged Switches

Layer 3 managed

Aggregation Switches

NETGEAR®

Indoor Access Point

WAX615
WiFi 6 Dual-Band PoE
- 1 x 2.5GbE Port Gigabit Ethernet
- Wi-Fi 6 Wireless 3 Gbps
- Concurrent Users : 60 Clients
- Dual-Band (2x2 MIMO)

WAX610
Wi-Fi 6 AX1800 Access Point
- 1x2.5G Port Gigabit Ethernet
- Wi-Fi 6 Wireless Up to 1.8 Gbps
- Concurrent Users : 50 Clients
- Dual-Band (2x2 MIMO)

WAX630
WiFi 6 AX6000 Access Point
- 1 x 2.5G & 1 x 1G Port Ethernet
- Wi-Fi 6 Wireless Up to 6 Gbps
- Concurrent Users : 100 Clients
- Tri-Band (4x4 MIMO)

WAX620
Wi-Fi 6 AX3600 Access Point
- 2 Port Gigabit Ethernet
- Wi-Fi 6 Wireless Up to 3.6 Gbps
- Recomended Clients : 75 Clients
- Dual-Band (4x4 MIMO)

WAC540
Wi-Fi 5 AC3000 Access Point
- 1 x 2.5G & 1 x 1G Port Gigabit Ethernet
- Wi-Fi 5 Wireless Up to 3 Gbps
- Max Users : Up to 600 Clients
- Tri-Band (4x4 MIMO)

WAX620
Wi-Fi 6 AX3600 Access Point
- 2 Port Gigabit Ethernet
- Wi-Fi 6 Wireless Up to 3.6 Gbps
- Recomended Clients : 75 Clients
- Dual-Band (4x4 MIMO)

Outdoor Access Point

WAX610Y
Wi-Fi 6 AX1800 Outdoor AP
- 1x2.5G 1x1G Port Gigabit Ethernet
- Wi-Fi 5 Wireless Up to 3 Gbps
- Max Users : Up to 600 Clients
- Dual-Band (2x2 MIMO)

WND930
Wi-Fi 5 Outdoor Access Point
- 1x2.5G 1x1G Port Gigabit Ethernet
- Wi-Fi 5 Wireless Up to 3 Gbps
- Max Users : Up to 600 Clients
- Dual-Band (2x2 MIMO)

Accessories

ANT24501B
- Wireless Mode 802.11 a/b/g/n
- Gain 5 dBi and 7 dBi
- Compatible with WND930
- Built-in Omni-Directional

PAV12V
Compatible with the following models:WNDAP350-100NAS / WNDAP360-100NAS / WNDAP620-100NAS / WNDAP660-100NAS/WAC720-100NAS / WAC730-100NAS and Others

NETGEAR®

Unmanaged Network Switch

GS308V3
- 8 Port Gigabit Ethernet
- Bandwidth 16 Gbps
- Support auto MDI/MDIX
- Mac Address 8K

GS324
- 24 Port Gigabit Ethernet
- Metal Case Flexible Mounting
- Plug and Play Energy Saving
- Mac Address 8K

GS348
- 48 Port Gigabit Ethernet
- Bandwidth 96 Gbps
- Energy-efficient Technology
- Mac Address 8K

JGS516
- 16 Port Gigabit Ethernet
- Switching Bandwidth 32Gbps
- Jumbo frame support Up to 9K
- Mac Address 8K

JGS524
- 24 Port Gigabit Ethernet
- Switching Bandwidth 48Gbps
- Jumbo frame support Up to 9K
- Mac Address 8K

GS116
- 16 Port Gigabit Ethernet
- Bandwidth 32 Gbps
- Jumbo frame support Up to 9K
- Mac Address 8K

Smart Switch Series

GS108T
- 8 Port Gigabit Ethernet
- Bandwidth 16 Gbps
- Dynamic VLAN Assignment
- Mac Address 4K

GS724T
- 24 Port Gigabit Ethernet + 2 SFP Port
- Bandwidth 52 Gbps
- Dynamic VLAN Assignment
- Mac Address 16K

GS716T
- 16 Port Gigabit Ethernet + 2 SFP Port
- Bandwidth 36 Gbps
- Dynamic VLAN Assignment
- Mac Address 16K

GS748Tv5
- 48 Port Gigabit Ethernet + 4 SFP port
- Bandwidth 100 Gbps, MAC Address 16K
- 256 VLAN Supported, VLAN Routing

M4300-52G
- 48 Port Gigabit Ethernet + 2 SFP+ port
- Advanced IPv4/IPv6 security
- Layer 3 (static, policy-based & RIP OSPF dynamic routing)

Yealink

IP Phone Series

SIP-T31
Dual Line Entry Level IP Phone
- Yealink HD Voice
- Smart Noise Filtering Technology
- Opus Codec Support
- Up to 2 SIP accounts

SIP-T31P
Dual Line Entry Level IP Phone
- Yealink HD Voice, PoE Support
- Smart Noise Filtering Technology
- Opus Codec Support
- Up to 2 SIP accounts

SIP-T31W
Entry-level IP Phone with WiFi
- Supports 2.4G/5G built-in WiFi
- Up to 2 SIP accounts
- Support EHS Wireless Headset
- Yealink HD Voice

SIP-T33G
Gigabit Color Screen IP Phone
- 2 port Gigabit Ethernet
- PoE support, Support YDMP/YMCS
- Up to 4 SIP accounts
- Opus Codec Support

SIP-T43U
Feature-rich SIP Phone
- Optima HD voice, PoE support
- Up to 12 SIP accounts
- T4U firmware unified
- Dual-port Gigabit Ethernet

SIP-T46U
Productivity Enhance SIP Phone
- 2 port Gigabit Ethernet
- PoE support, Support YDMP/YMCS
- Up to 16 SIP accounts
- Opus Codec Support

MP56
Certified for Microsoft Teams
Teams Edition Mid level IP Phone
- Android 12 OS Desk Phone
- Optimal HD Audio, Supports Office 365
- Supports Module EXP50

MP58
Certified for Microsoft Teams
Smart Business IP Phone
- Android 9.0 OS, Optimal HD Audio
- Supports Office 365, PoE support
- Dual-port Gigabit Ethernet
- Built-in Wi-Fi Dual Band 2.4G/5G

Accessories

EXP43
LCD Expansion Module

EXP50
LCD Expansion Module

WF40
Wi-Fi USB Dongle

W60B
DECT IP Base Station

CPN10
PSTN box Connector

Yeastar

P-Series IP PBX

IP PBX P550

- Base Users / Max Users : 50
- Max Concurrent Calls : 25
- Max FXS Ports : 8
- Max FXO/BRI Ports : 8
- Max GSM/3G/4G Ports : 4
- Max E1/T1/J1 Ports : -

IP PBX P560

- Base Users / Max Users : 100/200
- Max Concurrent Calls : 30/60
- Max FXS Ports : 8
- Max FXO/BRI Ports : 8
- Max GSM/3G/4G Ports : 4
- Max E1/T1/J1 Ports : 1

IP PBX P570

- Base Users / Max Users : 300/500
- Max Concurrent Calls : 60/120
- Max FXS Ports : 16
- Max FXO/BRI Ports : 16
- Max GSM/3G/4G Ports : 6
- Max E1/T1/J1 Ports : 2

S-Series IP PBX

IP PBX S20

- Users : 20
- Max Concurrent Calls: 10
- Max Analog Ports : 4
- Expansion Boards : N/A
- External Storage : TF Card

IP PBX S50

- Users: 50
- Max Concurrent Calls : 25
- Max Analog Ports : 8
- Expansion Board : N/A
- External Storage : SD Card

IP PBX S100

- Users: 100 (up to 200)
- Max Concurrent Calls: 30 (up to 60)
- Max Analog Ports: 16
- Max E1/T1/J1 Ports: 2
- Expand Boards: 2*EX30/EX08+1*D30
- External Storage: SD Card

Expansion Boards & Modules

D30
Add 100 VoIP users + 30 concurrent calls

O2
Module with 2 FXO ports to terminate 2 analog PSTN (POTS) lines

S2
Module with 2 FXS ports to terminate 2 analog telephone.

SO
Module with 1 FXS and 1 FXO ports

EX08
Add 100 VoIP users + 30 concurrent calls

EX30
Expand E1/T1 interfaces

HIKVISION®

Indoor Camera

DS-2CD1323G2
- High quality imaging with 2 MP resolution
- Support Human and Vehicle Detection
- Efficient H.265+ compression technology

ColorVu

DS-2CD2147G2
- High quality imaging with 4 MP resolution
- Clear imaging against strong back light due to 130 dB WDR technology
- Water and dust resistant (IP67)

ColorVu

DS-2CD1147G2H
- High quality imaging with 4 MP resolution
- Support Human and Vehicle Detection
- Smart Hybrid Light: advanced technology with long range

DS-2CD2386G2
- High quality imaging with 8 MP resolution
- Built-in microphone for real-time audio security(-U)
- Water and dust resistant (IP67)

AcuSense

DS-2CD2546G2
- High quality imaging with 4 MP resolution
- Excellent low-light performance
- Water and dust resistant IP67
- Efficient H.265+ compression technology

AcuSense

DS-2CD2563G2
- High quality imaging with 6 MP resolution
- Clear imaging against strong back light due to 120 dB WDR technology
- Water and dust resistant (IP67)

Outdoor Camera

DS-2CD2043G2-I
- High quality imaging with 4 MP resolution
- Clear imaging against strong backlight due to 120 dB WDR technology
- Efficient H.265+ compression technology

DS-2CD2T63G2
- High quality imaging with 6 MP resolution
- Efficient H.265+ compression technology
- Clear imaging against strong backlight due to 120 dB WDR technology

DS-2CD2087G2
- High quality imaging with 8 MP resolution
- Efficient H.265+ compression technology
- 24/7 colorful imaging
- Built-in microphone for real-time audio security (-U)

DS-2CD1T27G2H
- High quality imaging with 2 MP resolution
- Support Human and Vehicle Detection
- Support on-board storage up to 512 GB
- Water Dust resistant (IP67)

DS-2DE4215IW
- High quality imaging with 2 MP resolution
- 15x optical zoom & Pan and tilt Camera
- Excellent low-light performance

DS-2SE4C225MWG
- High quality imaging with 2 MP resolution
- 25× optical zoom and 16× digital zoom
- Supports WDR, HLC, BLC, 3D DNR
- Night view with up to 100 m IR distance & 30 m white light

Network Video Recorders

DS-7608NI-Q2
8 Channel 1U 4K NVR

- Up to 8 Channel IP camera inputs
- Up to 80 Mbps incoming bandwidth
- 2 SATA Interfaces, Up to 8 TB capacity for each HDD

DS-7616NI-K1
16 Channel 1U 4K NVR

- Up to 16 Channel IP camera inputs
- Up to 160 Mbps incoming bandwidth
- 1 SATA interface, Up to 8TB capacity for each HDD

DS-7732NI-K4
32 Channel 1.5U 4K NVR

- Up to 32 Channel IP camera inputs
- Up to 256 Mbps incoming bandwidth
- 4 SATA interfaces, Up to 10 TB capacity for each HDD

DS-7716NI-I4
16 Channel 1.5U 4K NVR

- Up to 16 channel IP cameras inputs
- Up to 1-ch@32 MP/2-ch@12 MP/16-ch@1080p decoding capacity
- 4 SATA interfaces, Up to 10 TB capacity for each HDD

DS-7732NXI-I4/S
32 Channel 1U AcuSense 4K NVR

- Intelligent analytics based on deep learning algorithm
- Up to 32-ch IP camera inputs
- Up to 4-ch perimeter protection
- 4 SATA interfaces supporting hot-plug, Up to 10 TB capacity for each HDD

DS-7104NI-Q1/M
4 Channel Mini 1U NVR

- Up to 40 Mbps incoming bandwidth, and 60 Mbps outgoing bandwidth
- Up to 4-ch network camera inputs
- 1 SATA interface, Up to 6TB capacity for each HDD

Network PoE Switch

DS-3E0105P-E/M
- 5 Port Fast Ethernet
- Up to 300 m Range PoE
- PoE Power Budget 35 W
- 2K MAC Address Table

DS-3E0510P-E/M
- 8 Port Gigabit + 1 SFP Port
- 4K MAC Address Table
- PoE Power Budget 58 W
- 6 KV Surge Protection

DS-3E0318P-E
- 16 Port Fast Ether + 1 SFP Port
- 4K MAC Address Table
- PoE Power Budget 130 W
- 6KV Surge Protection

DS-3E0510HP-E
- 8 Port Gigabit + 1 SFP Port
- Up to 300 m Range PoE
- PoE Power Budget 110 W
- 4K MAC Address Table

DS-3E0528HP-E
- 24 Port Gigabit + 2 SFP Port
- 370 W PoE Power Budget
- 8K MAC Address Table
- Up to 300 m Range PoE

DS-3E1518P-SI
- 16 Port Gigabit + 2 SFP Port
- 8K MAC Address Table
- PoE Power Budget 225 W
- 6 KV Surge Protection

TAURUS

Solving Your IT Problems

Selain produk dengan brand di atas, **PT. Taurus Sampai Tuntas** juga provide produk-produk dari brand berikut :

tp-link · D-Link Building Networks for People · Tenda · DELL

hp HEWLETT PACKARD · logitech · EZVIZ Creating Easy Smart Homes · BiO FINGER

Canon · EPSON · INDORACK NETWORK CABINET · ICA UPS & Stabilizer

COMMSCOPE · BELDEN · Zimm LINK · ZKTeco

FORTINET · Ruckus · poly · APC

SEAGATE · aruba · Synology · alhua TECHNOLOGY

HELIX EDUKIT · Cambium Networks · ASUS · infocus

Microsoft · CISCO · LS Cable System Optical Fiber Cables · WD Western Digital

McAfee · QNAP · Lenovo · eset

OUR CUSTOMER

KOMINFO

SIDOMUNCUL

CIPUTRA WORLD
SURABAYA

INTEGRA
GROUP

premierplace

Avian
BRANDS

PT. AGRINDO

TANRISE
PROPERTY

HARRIS
HOTEL & CONVENTIONS
Gubeng • Surabaya

jiipe
INDONESIA
SEZ

Tanobel

SKN

UBAYA
UNIVERSITAS SURABAYA

PT. INDOSPRING Tbk.
Member of Indoprima Group

ADHIWANGSA

BIS
PT. BUMINDO SAKTI

PT. ALIM AMPUH JAYA STEEL

BPSDM
Jatim

intiland

OneMed
HEALTH CARE

SAMSUNG SDS

PARAHITA
DIAGNOSTIC CENTER

PRAMITA Lab

Pfi
PRIMARASA FOOD
INDUSTRI

PLATINUM
HOTEL
TUNJUNGAN - SURABAYA

KOLABORA
COFFEE GEEKS & LIFESTYLE

OUR PROJECT

ICA

- Instalasi Rack Server di Gereja ICA Surabaya -

KOLLABORA
COFFEE GEEKS & LIFESTYLE

- Instalasi & Konfigurasi CCTV di Kollabora Coffee Surabaya -

VITA SCHOOL

- Project Instalasi, Konfigurasi CCTV di VITA School Surabaya -

WISATA Bukit Mas
hunian sejuta pesona

- Instalasi dan Konfigurasi CCTV di Wisata Bukit Mas Surabaya -

OUR PROJECT

HELIX EDUKIT

Project Helix EDUKIT- Paket Network Trainer KIT   SMK Muhammadiyah 6 Rogojampi

Project Helix EDUKIT- Paket Network Trainer KIT   SMK Negeri 1 Mojokerto

Project Helix EDUKIT- Paket Network Trainer KIT   SMK Ma'arif NU Kencong Jember

0821-5200-6060   @taurus.sby   sales@taurus.co.id   www.taurus.co.id

CONNECT WITH US

📞 : 0821-5200-6060

✉️ : sales@taurus.co.id

🌐 : www.taurus.co.id

📍 : Surabaya - East Java

📷 : @taurus.sby

f : Taurus

♪ : @taurus.sby

▶️ : Tech HITMAN

SIPLah blibli.com   **e**catalogue **LKPP**   : PT. Taurus Sampai Tuntas