

Index

Note: Page numbers with “F” denote figures; “t” tables.

A

A3967SLB bipolar stepper motor, 609
Ab function, 47
Access methods, Ethernet, 510–513
 e-mail, 512
 using custom application, 512
 using HyperTerminal, 511
 using web browser on PC, 511, 511f
Acos function, 48
Action commands, 339
Active RFID tags, 370
ADC_Get_Sample function, 504, 535
ADC_Init function, 503–504
Adc_Read(0) function, 131–136, 144–146
Alarm clock, real-time, 436–439, 436f–438f, 440f
Altimeter display on GLCDs, 490–501, 491f, 493f, 495f–496f, 501f
Arbitrary waveform generation, 229–234, 232f–233f, 235f
Arrays, 12–13
 character, 12–13
Asin function, 48
Assembly language
 instructions, 45
Assembly program, 2
Atan function, 48
Atan2 function, 48
Automotive project *see* CAN bus;
 Local interconnect network (LIN) bus

B

Barometer display on GLCDs, 490–501, 491f, 493f, 495f–496f, 501f
Baud rate, 290, 303–304
BEGIN–END, 52, 52f
Biased split termination of CAN bus, 552–553
Bipolar A/D converter, 216
Bipolar stepper motors, 600
 drive, 608–611, 609f–612f, 614f
 driving sequence, 601f
 windings, 600f
Bit stuffing in CAN bus, 556
Bluetooth, 5f
 master mode, serial communication in, 361–369, 362f, 364f, 368f
 program testing, 368–369
 slave mode, serial communication in, 333–361, 335f–336f, 338f–339f, 343f–348f, 353f–354f, 356f
 making connection, 342
 manual connection, 342–346
 modifications, 355
 program testing, 352–355
 RN41 module, 334–335, 334f
BusyXLCD function, 149
BusyxUSART function, 299
Buzzer, 156

C

C, <address> command, 341
Calculator
 with keypad and liquid crystal display, 190–201, 190f–194f, 202f

 program using built-in keypad function, 195f, 198–201, 199f
 PC-based, 304–306, 305f, 307f, 310f
CAN bus, 535–536, 550–577, 551f
 bit stuffing, 556
 configuration mode, 561
 data frame, 553–555
 disable mode, 561
 error frame, 555
 error recognition mode, 562
 listen-only mode, 561
 logic states, 552f
 loop-back mode, 561
 message reception, 562–563
 message transmission, 562
 nominal bit timing, 556–558
 normal operation mode, 561
 overload frame, 555–556
PIC microcontroller interface, 558–559, 558f–559f
PIC18F258 microcontroller, 559–561
remote frame, 555
temperature sensor and display project, 568, 569f–570f, 577f
COLLECTOR processor, 569
COLLECTOR program, 574–577, 575f
DISPLAY processor, 569–570
DISPLAY program, 570–574, 571f
termination methods, 553f

- CAN bus (*Continued*)
 - timing parameters calculation, 563–564
 - CAN_Initialize function, 565, 574
 - CANGetOperationMode function, 565
 - CANRead function, 567
 - CANSetBaudRate function, 566
 - CANSetFilter function, 566
 - CANSetMask function, 566
 - CANSetOperationMode function, 565
 - CANWrite function, 567
 - Card Identification Register (CID), 450
 - Card Specific Data Register (CSD), 450
 - Carrier Sense Multiple Access with Collision Detection (CSMA/CD) protocol, 509
 - with Arbitration on Message Priority (CSMA/CD + AMP), 550
 - Case sensitivity, 11
 - CCS C compiler, 10, 581
 - Change commands, 339
 - Character arrays, 12–13
 - Click boards, 310–311
 - RFID, 372f
 - Clock
 - real-time, 414–435, 421f–422f, 426f, 428f, 430f
 - alarm clock, 436–439, 436f–438f, 440f
 - Clock edge mode, 401
 - Clock polarity (CP), 404, 404f
 - Closed-loop DC motor speed
 - control, 616, 616f, 624–630, 627f–628f
 - ClosexUSART function, 299
 - CMX-Tiny+, 581
 - Command frame identifiers, 538
 - Comments, 11
 - Common-anode7-segment display, 109, 116f
 - Common-cathode7-segment display, 109, 115f
 - Complex instruction set computer *see* CISC
 - Configuration
 - bits, specifying, 45
 - mode of CAN module, 561
 - Constants, 12, 44–45
 - Contact debouncing, 194–198
 - Contact noise, 194–198
 - Control flow, 15–19
 - iteration statements, 17
 - selection statements, 15
 - Control register, 405
 - Controller area network *see* CAN bus
 - Controller chips, Ethernet, 510
 - CONV function, 55
 - Convert_Date_Time function, 429, 434
 - Cooperative scheduling, 579, 579f
 - multitasking, 581–589, 582f–584f, 586f
 - Cos function, 47
 - Cosh function, 47
 - CR95HF, 385f
 - operational modes, 374
 - startup sequence, 374
 - CustomChar function, 164–168
- D**
- D command, 340
 - basic settings with, 341f
 - Data clock rate, 400
 - Data frame in CAN bus, 553–555
 - ACK field, 555
 - arbitration field, 554
 - control field, 554, 555t
 - CRC field, 555
 - data field, 554
 - start of frame, 554
 - Data memory, 6
 - DataRdyxUSART function, 299
 - DC motors control, 613–619, 617f–619f
 - closed-loop transfer function, 616f
 - electrical circuit, 615f
 - open-loop transfer function, 616f
 - _delay function, 46–47
 - _delay3 function, 46–47
 - Delay_ms function, 76–77, 92–93
 - _delay_ms function, 46–47, 74
 - _delay_ms(5) function, 149
 - _delay_ms(15) function, 149
 - Delay_Seconds function, 74, 80, 94, 160
 - _delay_us function, 46–47
 - Diagnostic frames, 538
 - Dice, LED, 85–94, 90f–92f, 92t, 93f, 95f
 - two-dice project, 94–98, 100f–102f, 104f
 - using random number generator, 94, 97f, 99f
 - Digital signal processing (DSP), 522–535, 528f–532f
 - filter structure, 525–527, 530f
 - Digital thermometer, 168–171, 168f–170f
 - Digital-to-analog converter (DAC), 214–216, 215f
 - Direct current (DC) motor control system, 3–4, 6f
 - Disable mode of CAN module, 561
 - Display function, 123, 127
 - Display_Date_Time function, 429, 435
 - Display_PTA function, 501
 - Display_Temperature function, 412
 - DISPLY function, 55–57
 - Do statement, 19
 - DO-ENDO, 54, 54f
 - DO-FOREVER, 54, 54f
- E**
- EasyPIC V7 development board, 39–42
 - _EEPROM_DATA function, 47
 - Electronic stadiometer, 248
 - EM4100 RFID tag, 375–376, 375f
 - data format, 376f
 - E-mail, 512, 512f
 - Embedded controller *see* Microcontrollers
 - ENC28J6 Ethernet controller chip, 510
 - ENC28J60 Ethernet controller chip, 510–511, 510f, 513, 515
 - Error frame in CAN bus, 555
 - Error function, 501

Error recognition mode of CAN module, 562
 Ethernet, 550
 UDP-based control, 521–522, 522f–523f, 526f
 web browser-based control, 508–521, 513f–517f, 519f
 connectivity, 509
 embedded access methods, 510–513
 embedded controller chips, 510, 510f
 packet format, 509f
 External interrupt, four-digit multiplexed 7-segment event LED counter using, 175–186, 178f–180f, 183f, 186f–187f

F

FloatToStr function, 294–296
 Flowcharts, 51–57
 representing for loops in, 36
 Fluid level control system, 3, 3f, 5f
 with Bluetooth, 5f
 with keypad and LCD, 4f
 Fonts, LCD, 160–168, 164f–167f
 For statement, 17–18, 84–85, 116–118, 123, 127–128, 131–136, 144–146, 289, 504, 574
 loop, 92–93, 107–109, 125–126, 194, 219–220, 475, 602
 representing in flow charts, 63
 Format_Temperature function, 412–413
 4 × 4 keypad *see* Keypad
 Four-digit multiplexed 7-segment LED counter, 125–128, 127f–130f, 132f
 using external interrupt, 175–186, 178f–180f, 183f, 186f–187f
 FreeRTOS, 581
 Frequency counter with LCD, 262–268, 262f–265f
 FSfclose function, 465–466
 FSfopen function, 465–466
 FSfopenpgm function, 465–466

FSInit function, 465–466
 FSread function, 465
 FSremove function, 466
 FSremovepgm function, 466
 FSwrite function, 465
 Functions, 20
 library, 20, 21t

G

Get commands, 339
 Getkeypad function, 192–198
 Get_Response function, 546–550
 GetsxUSART function, 300
 Get_Temperature function, 469, 475
 Glcd_Box function, 484
 Glcd_Circle function, 485
 Glcd_Circle_Fill function, 485
 Glcd_Dot function, 482–483
 Glcd_Fill function, 482
 Glcd_H_Line function, 483
 Glcd_Image function, 487
 Glcd_Init function, 481–482, 503
 Glcd_Line function, 483, 504–507
 Glcd_Rectangle function, 483–484
 Glcd_Rectangle_Round_Edges function, 484
 Glcd_Rectangle_Round_Edges_Fill function, 484
 Glcd_Set_Font function, 485
 Glcd_Set_Font_Adv function, 486
 Glcd_Set_Page function, 482
 Glcd_Set_Slide function, 482
 Glcd_Set_X function, 482
 Glcd_V_Line function, 483
 Glcd_Write_Char function, 485–486
 Glcd_Write_Char_Adv function, 486
 Glcd_Write_Const_Text_Adv function, 487
 Glcd_Write_Data function, 482
 Glcd_Write_Text function, 485–486
 Glcd_Write_Text_Adv function, 486–487
 Global positioning system (GPS) with LCD output, 306–317, 310f–314f, 317f
 Goto statement, 19

GPIO commands, 339
 Graphical User Interface (GUI), 521
 Graphics LCD displays (GLCDs), 477–490, 488f–489f
 barometer, thermometer, and altimeter display on, 490–501, 491f, 493f, 495f–496f, 501f
 display coordinates, 481f
 128 × 64 pixel, 478–479
 operation, 480
 plotting temperature variation on, 501–508, 502f–505f, 508f
 shapes drawn on, 490f
 structure, 480f

H

#pragma config statement, 74
 HD44780 LCD controller module, 141–142
 pin configuration of, 142t
 High-level languages, 2
 High/Low game, 206–214, 208f–210f, 213f–214f
 generating random number, 207
 HTTP, 511
 Human height measurement, 248–258, 249f–251f, 253f, 255f
 HyperTerminal, 297, 298f, 511

I

I, <value 1>, <value 2> command, 341
 I/O pins
 accessing individual, 45
 two-dice project using fewer pins, 98–109, 105t, 106f, 106t, 107f, 107t, 108f, 110f, 111t, 112f–113f
 I²C bus, 396, 420, 421f, 422, 435, 491, 493
 If statement, 15–17
 IF–THEN–ELSE–ENDIF, 52, 53f
 IF–THEN–ENDIF, 52, 53f
 Init_LCD function, 407
 Init_Pressure function, 494
 Init_SPI function, 407
 Initialize_CR95HF function, 379
 InitTask function, 590

Internal registers of TC72, 404t
 Internet, 508
 Interrupt isr function, 160
 Interrupt service routines (ISRs),
 46, 56–57, 175–177, 179,
 182–186, 235–236, 242,
 244, 352, 363–367,
 590–591, 627
 Iteration statements, 17
 Itoa function, 48, 152

K

K command, 341
 Keypad
 calculator, 190–201, 190f–195f,
 199f, 202f
 High/Low game, 206–214,
 208f–210f, 213f–214f
 structure, 191f
 Keypad_Init function, 198
 Keypad_Key_Click function,
 198
 Keypad_Key_Press function,
 198

L

Labs function, 47
 Lcd_Chr function, 435
 Lcd_Out function, 164–168
 Led_Out function, 146
 Library functions, 20, 21t
 peripheral libraries, 49
 software, 46–49
 Light emitting diodes (LEDs)
 chasing, 70–76, 72f–75f
 current sinking mode, 70–71,
 71f
 current sourcing mode, 71–72,
 72f
 complex flashing, 76–77,
 77f–79f
 dice, 85–98, 90f–92f, 92t, 93f,
 95f, 97f, 99f
 random flashing, 78–80,
 80f–82f
 7-segment LED counter,
 109–118, 114f–117f, 117t,
 118f–119f
 voltmeter, 129–140, 133f–135f,
 137f

Liquid crystal display (LCD)
 calculator, 190–201, 190f–195f,
 199f, 202f
 custom fonts, 160–168,
 164f–167f
 frequency counter with,
 262–268, 262f–265f
 GLCDs, 477–490, 478t,
 479f–481f, 488f–490f
 High/Low game, 206–214,
 208f–210f, 213f–214f
 output, GPS with, 306–317,
 310f–314f, 317f
 voltmeter, 140–152, 143f–145f,
 147t, 148f, 151t, 152f–153f
 connecting LCD to
 microcontroller, 142–143
 HD44780 LCD module,
 141–142, 142t
 Listen-only mode of CAN module,
 561
 LM35DZ temperature sensor, 469,
 501–502, 538
 LMD18200T motor controller chip,
 619, 619f
 Local interconnect network (LIN)
 bus, 535–550, 539f, 540f,
 542f, 543f, 547f–549f
 Get_Response function,
 546–550
 MASTER node, 541
 with one master and three slaves,
 536f
 protocol, 536–538, 537f
 Send_Header function,
 541–546
 SLAVE node, 546–550
 Lock, RFID, 387–389, 388f,
 390f–391f
 Log function, 48
 Log10 function, 48
 Logic probe, 81–85, 83f–84f,
 86f–87f, 87t, 88f–89f
 LongToStr function, 146, 193, 306,
 469
 Loop-back mode of CAN module,
 561
 Looping, 63f–65f, 63
 Low pass FIR digital filter,
 522–535, 528f–532f

coefficients, 530f
 structure, 525–527
 LPS331AP sensor, 490–501
 registers, 492t
 LSB register, 405
 LTrim function, 146, 306

M

Main Program function, 412
 Manufacturer ID, 405
 Master mode, 361–369
 Bluetooth serial communication,
 361–369, 362f, 364f, 368f
 Master Synchronous Serial Port
 (MSSP) module, 389–396
 configuration for SPI master
 mode, 400
 in SPI mode, 396–397, 397f
 MAX232, 291–292
 pin configuration, 292f
 MCP 201 LIN bus, 538–539
 Measure function, 289–290
 Mechanical stadiometer, 248f
 Memcmp function, 48
 Memory organization *see* Data
 memory, organization;
 Program memory,
 organization
 Message reception in CAN bus,
 562–563, 562f
 Message transmission in CAN bus,
 562
 MF1ICS50 RFID tag, 376–377
 memory organization, 377f
 MicroC/OS-II, 581
 Microcomputer, defined, 1
 Microcontrollers
 defined, 1
 fluid level control system, 3f
 program development, 51
 PDL and flowcharts, 52–57
 Microprocessor, 2
 mikroBUS, 311
 mikroC Pro, 9
 arrays, 12–13
 functions, 20
 library, 20, 21t
 modifying flow of control, 15–19
 operators, 15
 pointers, 13–14

program structure, 10–12, 10f
 structures, 14
 variable types, 11t
 Minielectronic organ, 258–261,
 259f–261f
 Mmc_Fat_Activate function,
 455–456
 Mmc_Fat_Append function, 455,
 475
 Mmc_Fat_Assign function, 455
 Mmc_Fat_Close function,
 456–457
 Mmc_Fat_Delete function, 455
 Mmc_Fat_EOF function, 456
 Mmc_Fat_Exists function, 455
 Mmc_Fat_Get_File_Dat function,
 455
 Mmc_Fat_Get_File_Size function,
 455
 Mmc_Fat_Init function, 455
 Mmc_Fat_MakeDir function, 455
 Mmc_Fat_Open function,
 456–457, 456t
 Mmc_Fat_QuickFormat function,
 455–456
 Mmc_Fat_Read function, 455–457,
 475
 Mmc_Fat_ReadN function, 456
 Mmc_Fat_Rename function, 455
 Mmc_Fat_Reset function,
 455, 475
 Mmc_Fat_Rewrite function,
 455–457
 Mmc_Fat_Seek function, 455
 Mmc_Fat_Tell function, 455
 Mmc_Fat_Write function,
 455–457, 475
 Mmc_Set_File_Date function, 455
 Motor speed
 control, closed-loop, 624–630,
 627f–628f
 measurement, 619–624,
 620f–622f
 MPLAB C18 C compiler, 10
 MPLAB X IDE, 29
 MPLAB XC8 C compiler, 10
 MPLAB XC8 C compiler, 10,
 29–49
 MDD library functions, 463,
 463t–464t

programming other boards,
 39–42
 XC8 language features, 42–49
 accessing individual bits of
 variable, 45
 accessing individual I/O pins,
 45
 assembly language
 instructions, 45
 constants, 44–45
 interrupt service routines, 46
 peripheral libraries, 49
 persistent qualifier, 45
 program startup, 46
 program template, 43–44,
 43f
 software library functions,
 46–49
 specifying configuration bits,
 45
 variable types, 44, 44t
 MSB register, 405
 Mult function, 20
 Multitasking, 578–581
 cooperative scheduling, 579,
 579f, 581–589, 582f–584f,
 586f
 preemptive scheduling,
 580–581, 580f
 round-robin scheduling,
 579–580, 579f, 590–594,
 590f, 592f, 595f

N

Negative temperatures, displaying,
 413–414
 Newline function, 294–296, 469
 NMEA sentences, 310, 312,
 316–317
 Nominal bit timing in CAN bus,
 556–558
 Normal operation mode of CAN
 module, 561
 Number function, 94
 Numbers function, 98, 105–106

O

100Base-T, 509–510
 128 × 64 pixel, 478–479, 479f
 pin configuration, 478t

One-phase full-step sequencing,
 598, 599t
 ON–OFF temperature control,
 317–325, 317f
 OpenADC function, 136
 Open-loop transfer function of DC
 motor, 616, 616f
 OpenSPIx function, 226
 OpenXLCD function, 149–150
 OpenxUSART function, 300
 Operation Control Register (OCR),
 450
 Operators in C, 15
 Optical encoders, 619–624,
 620f–622f
 Organ, minielectronic, 258–261,
 259f–261f
 OSA-RTOS, 581
 Overload frame in CAN bus,
 555–556

P

Parallel LCDs, 141
 Passive RFID tags, 370, 370f,
 375–377
 PCF8583 RTC chip, 414–435
 pin layout, 425f
 registers, 424f
 hours, 424f
 weekday–month, 424f
 year–date, 424f
 PCSGU250, 525, 528f
 Peripheral libraries, 49
 Persistent qualifier, 45
 Personal computer (PC)
 -based calculator, 304–306,
 305f, 307f, 310f
 Ethernet access using web
 browser on, 511, 511f
 PIC18F258 microcontroller,
 559–561
 see also CAN bus
 PICC18 C compiler, 9–10
 PICDEM PIC18 Explorer
 development board, 26–29,
 26f
 block diagram, 28f
 module connections, 28–29
 programming and debugging, 29
 Piconet, 333

PICos18, 581
 PICtail Daughter Board,
 457f–458f, 462
 PlotAxis function, 503–504
 Pointers, 13–14
 Preemptive scheduling, 580–581,
 580f
 Pressure_Read function, 494
 Pressure_Write function, 494
 Program
 startup, 46
 template, 43–44, 43f
 Program description languages
 (PDLs), 51–57
 Program memory, 6
 Pseudorandom number generator
 function, 94
 Pulse width modulated (PWM)
 modules, 156, 244, 247,
 624–627
 PutcXLCD function, 150
 PutrsXLCD function, 150
 PutrsxUSART function, 303
 PutsXLCD function, 150

R

R,1 command, 341
 Radiofrequency identification
 (RFID), 369–387,
 370f–371f, 373f, 375f,
 375t, 376f–380f, 385f, 387f
 click board, 372f
 CR95HF
 operational modes, 374
 startup sequence, 374
 lock, 387–389, 388f, 390f–391f
 passive tags, 375–377
 UART communication, 374–375
 Rand function, 48, 207, 212
 Random access memory *see* RAM
 Random flashing light emitting
 diodes, 78–80
 Random number generator, 94
 Reaction timer, 268–276,
 269f–271f, 273f
 Read only memory *see* ROM
 Read_Alarm_Flag function, 439
 Read_Altimeter_Value function,
 501
 Read_Date_Time function, 429

Reading data in SD cards, 451
 Read_Pressure_Value function, 494
 Read_Temperature function, 407
 Read_Temperature_Value function,
 494
 ReadxUSART function, 303
 Real-time clock (RTC), 414–435,
 421f–422f, 426f, 428f, 430f
 alarm clock, 436–439,
 436f–438f, 440f
 Real-time operating system
 (RTOS), 578, 580
 Reduced instruction set computer
 see RISC
 Registers
 alarm control, 437f
 LPS331AP sensor, 492t
 PCF8583 RTC chip, 424f
 SPI mode, 397–398
 Relative humidity measurement,
 277–290, 277f, 279t, 281t,
 282f–285f, 290f
 acknowledgment, 279
 conversion command, 279
 conversion of signal output,
 280–281
 RESET, 277–278
 Status register, 279–280
 transmission start sequence, 278
 Remote frame in CAN bus, 555
 Remote Transmit Request (RTR),
 551, 553–554
 REPEAT–UNTIL, 55, 55f
 Request_Short_Info function, 379
 Reset_Sequence function,
 289–290
 Return statement, 147
 RN41 Bluetooth module, 334–335,
 334f
 Round function, 49
 Round-robin scheduling, 579–580,
 579f
 multitasking with variable CPU
 time allocation, 590–594,
 590f, 592f, 595f
 RS232, 304
 serial output, thermometer with,
 290–304, 291f, 291t,
 292f–295f, 298f–301f
 RTOS.C, 590

S

SA, <value> command, 339
 Salvo, 580–581
 Sawtooth waveform generation,
 217–219, 218f–223f, 225f,
 227f
 Sbit statements, 164–171
 ScopeFIR program, 525, 529f
 SD cards, 446f, 452f–454f,
 457f–461f, 466f–467f
 -based temperature data logger,
 466–476, 468f, 470f,
 476f–477f
 deleting existing file, 466
 holder, 451f
 MPLAB XC8
 library options, 464, 464t
 MDD library functions, 463,
 463t–464t
 microcontroller memory
 usage, 464–465, 465t
 operation in SPI mode,
 449–450
 reading data, 451
 reading from existing file, 465
 sequence of function calls,
 465
 setting configuration files, 462
 specifications, 447t
 standard card
 pin definitions, 449t
 pin layout, 448f
 writing data, 451
 writing to existing file, 465
 SD Configuration Register (SCR),
 450
 Select_Protocol_14443 function,
 385–386
 Selection statements, 15
 Semipassive RFID tags, 370
 Send_Command function, 363
 Send_Header function, 541–546
 Send_To_TC72 function, 407
 Sequencing, 52, 53f
 SerDDRamAddr function, 151
 Serial clock polarity, 404f
 Serial communication
 Bluetooth
 master mode, 361–369, 362f,
 364f, 368f

- slave mode, 333–361,
 - 334f–336f, 338f–339f,
 - 343f–348f, 353f–354f, 356f
 - pins required for, 291t
 - RS232 serial output, thermometer
 - with, 290–304, 291f–295f,
 - 298f–299f, 301f
 - using USB-RS232 converter
 - cable, 297
 - using USB-UART port,
 - 299–304, 300f
 - Serial Ethernet board, 515f
 - Serial LCDs, 141
 - Set commands, 339
 - Set_Date_Time function, 429, 439
 - Set_RTC_Alarm function, 439
 - SetSpeed function, 630
 - 7-segment LED counter, 109–118,
 - 114f–117f, 117t,
 - 118f–119f
 - four-digit multiplexed, 125–128,
 - 127f–130f, 132f
 - two-digit multiplexed, 120–125,
 - 120f–121f, 121t,
 - 122f–124f, 126f
 - SHT11 temperature and relative
 - humidity sensor, 277f
 - Sin function, 47, 234–235
 - Sine waveform, 234–239, 237f,
 - 239f–240f
 - Sinh function, 47
 - Slave mode Bluetooth serial
 - communication, 333–361,
 - 334f–336f, 338f–339f,
 - 343f–348f, 353f–354f, 356f
 - Sleep function, 49
 - SM, <value> command, 340
 - SN, <value> command, 340
 - SO, <value> command, 340
 - Software library functions, 46–49
 - Sound generation, 156–160,
 - 156f–159f, 161f
 - Sound_Play function, 157
 - SP, <string> command, 340
 - SP11_Write function, 535
 - SPI bus, 216–217, 217f, 447–448
 - complex bus project, 389–414,
 - 406f, 408f, 415f
 - clock edge mode, 401
 - control register, 405
 - data clock rate, 400
 - displaying fractional part, 414
 - displaying negative
 - temperatures, 413–414
 - enabling SPI mode, 401–402
 - LSB and MSB registers, 405
 - manufacturer ID, 405
 - MSSP configuration for SPI
 - master mode, 400
 - MSSP in SPI mode, 396–397,
 - 397f
 - MSSP module, 389–396
 - operation in SPI mode, 398,
 - 399f
 - receiving data from slave, 400
 - sending data to slave, 400
 - SPI mode registers, 397–398,
 - 398f–399f
 - TC72 internal registers, 404t,
 - 405
 - TC72 read/write operations,
 - 404–405
 - TC72 temperature sensor,
 - 402–403
 - SPI_Ethernet_doPacket function,
 - 519
 - SPI_Ethernet_Init function, 516
 - SPI_Ethernet_UserTCP function,
 - 522
 - SPI_Ethernet_UserUDP function,
 - 522
 - SPI_Init function, 219–220, 516
 - SPI_Set_Active function, 222
 - SPIx_Init function, 220
 - SPIx_Init_Advanced function, 220
 - SPIx_Read function, 220
 - SPIx_Write function, 220
 - Split termination of CAN bus,
 - 552–553
 - Sqrt function, 49
 - Square waveform, 239–247,
 - 243f–247f
 - SR,, 341–346
 - Srand function, 207, 212
 - SSPxCON1 register, 398, 399f
 - SSPxSTAT register, 398, 398f
 - Stadiometer, 248
 - mechanical, 248f
 - Standard termination of CAN bus,
 - 552–553
 - StartTasks function, 590, 594
 - Statements
 - iteration, 17
 - selection, 15
 - Stepper motor control
 - bipolar motor drive, 608–611,
 - 609f–612f, 614f
 - complex control of unipolar
 - motor, 604–608,
 - 605f–606f
 - unipolar motor drive, 598–602,
 - 601f–603f
 - Stepper_Motor function, 608
 - Strchr function, 296
 - String functions, 49
 - Structures, 14
 - SU, <value> command, 340
 - Subprograms, 55, 56f
 - structure, 56–57, 56f
 - SwapTask function, 594
 - Switch statement, 16, 193, 582
- ## T
- Tan function, 47
 - Tanh function, 47
 - TC72 temperature sensor,
 - 402–403
 - internal registers, 404t, 405
 - pin configuration, 402f
 - read/write operations,
 - 404–405
 - TCP protocol, 509, 512, 512t, 519
 - Telnet interface, 511
 - Temperature
 - data logger, SD card-based,
 - 466–476, 468f, 470f,
 - 476f–477f
 - measurement, 277–290, 277f,
 - 279t, 281t, 282f, 282t,
 - 283f–285f, 290f
 - acknowledgment, 279
 - conversion command, 279
 - conversion of signal output,
 - 280–281
 - RESET, 277–278
 - Status register, 279–280
 - transmission start sequence,
 - 278
 - ON–OFF control, 317–325,
 - 317f–320f, 324f, 825

Temperature (*Continued*)

- sensor and display using CAN, 568, 569f–570f, 577f
 - COLLECTOR processor, 569
 - COLLECTOR program, 574–577, 575f
 - DISPLAY processor, 569–570
 - DISPLAY program, 570–574, 571f
 - TC72 temperature sensor, 402–403
 - variation plotting on GLCDs, 501–508, 502f–505f, 508f
- Terminal emulator software, 297
- Thermometer
- digital, 168–171, 168f–170f
 - display on GLCDs, 490–501, 491f, 493f, 495f–496f, 501f
 - with RS232 serial output, 290–304, 291f, 291t, 292f–295f, 298f–301f
- 39HS02 bipolar stepper motor, 611f
- Timing parameters calculation in CAN bus, 563–564
- Toascii function, 49
- Tolower function, 49
- Toupper function, 49
- Transducers, ultrasonic, 249f
- Transmission_Start_Sequence function, 289–290
- Triangle waveform generation, 229, 230f–231f
- Trunc function, 49
- Two-dice project, 94–98, 100f–102f, 104f
- using fewer I/O pins, 98–109, 105t, 106f, 106t, 107f, 107t, 108f, 110f, 111t, 112f–113f
- Two-digit multiplexed 7-segment LED, 120–125, 120f–121f, 121t, 122f–124f, 126f
- Two-dimensional arrays, 13
- Two-phase full-step sequencing, 598, 599t
- Two-phase half-step sequencing, 599, 600t

U

- UAG2 stepper motor, 601–602
- UART communication, 374–375
- UART_Set_Active function, 297
- Uart1_Data_Ready function, 306
- Uart1_Read function, 306
- Uart1_Read_Text function, 316
- UARTx_Data_Ready function, 296
- UARTx_Init function, 296
- UARTx_Read function, 296
- UARTx_Read_Text function, 296
- UARTx_Tx_Idle function, 296
- UARTx_Write function, 297
- UARTx_Write_Text function, 297
- UCN5804B stepper motor, 604
- UDP protocol, 512, 512t, 519
 - based Ethernet control, 521–522, 522f–523f, 526f
- Ultrasonic human height measurement, 248–258, 249f–251f, 253f, 255f
- Unconditional frame identifiers, 538
- Unipolar A/D converter, 216
- Unipolar stepper motors, 598–599
 - complex control of, 604–608, 605f–606f
 - drive, 598–602, 601f–603f
 - windings, 599f
- Universal serial bus (USB)
 - USB-RS232 converter cable, 297
 - USB-UART port, 299–304, 300f
- Universal Synchronous—
 - Asynchronous Receiver—Transmitter (UDART), 292
- Universal Synchronous—
 - Asynchronous Receiver—Transmitter (USART), 306
- Unsigned long, 144–146

V

- Variable
- accessing individual bits of, 45
 - names, 11
 - types, 11t, 44, 44t
- Void functions, 20
- Voltmeter
- LCD, 140–152, 143f–145f, 147t, 148f, 151t, 152f–153f
 - LED, 129–140, 133f–135f, 137f

W

- Waveform generation, 214–247, 215f
- arbitrary waveform, 229–234, 232f–233f, 235f
 - DAC, 215–216, 215f
 - sawtooth waveform, 217–219, 218f–223f, 225f, 227f
 - sine waveform, 234–239, 237f, 239f–240f
 - SPI bus, 216–217, 217f
 - square waveform, 239–247
 - triangle waveform, 229, 230f–231f
- Web browser-based control of Ethernet, 508–521, 509f–517f, 519f
- While statement, 18, 389, 541, 546
- loop, 193–194
- WriteCmdXLCD function, 151
- WriteSPI function, 226
- WritexUSART function, 303
- Writing data in SD cards, 451

X

- XC8. *see* MPLAB XC8 compiler, XC8 language features