

FactDev

0.1

Generated by Doxygen 1.8.6

Sun Apr 5 2015 23:04:36

Contents

1	FactDev documentation	1
2	README	3
3	QTestRunner	5
4	Namespace Index	7
4.1	Namespace List	7
5	Hierarchical Index	9
5.1	Class Hierarchy	9
6	Class Index	13
6.1	Class List	13
7	Namespace Documentation	17
7.1	Databases Namespace Reference	17
7.1.1	Detailed Description	17
7.2	Gui Namespace Reference	17
7.2.1	Detailed Description	18
7.3	Gui::Widgets Namespace Reference	18
7.3.1	Detailed Description	18
7.4	Models Namespace Reference	18
7.4.1	Detailed Description	19
8	Class Documentation	21
8.1	Databases::AccessDatabase Class Reference	21
8.2	Gui::Dialogs::AddProjectDialog Class Reference	21
8.2.1	Detailed Description	22
8.2.2	Constructor & Destructor Documentation	22
8.2.2.1	AddProjectDialog	22
8.3	Gui::Dialogs::AddQuoteDialog Class Reference	22
8.3.1	Detailed Description	23
8.3.2	Constructor & Destructor Documentation	23

8.3.2.1	AddQuoteDialog	23
8.3.3	Member Function Documentation	24
8.3.3.1	fillQuoteBilling	24
8.3.3.2	getCopy	24
8.3.3.3	getIdCustomer	24
8.3.3.4	getNumber	24
8.3.3.5	setCopy	24
8.3.3.6	setQuoteIdNumber	25
8.4	Models::Billing Class Reference	25
8.4.1	Detailed Description	27
8.4.2	Constructor & Destructor Documentation	27
8.4.2.1	Billing	27
8.4.3	Member Function Documentation	27
8.4.3.1	addContributory	27
8.4.3.2	getContributories	27
8.4.3.3	getDataMap	27
8.4.3.4	getDate	27
8.4.3.5	getDescription	28
8.4.3.6	getFilename	28
8.4.3.7	getFolder	28
8.4.3.8	getItem	28
8.4.3.9	getNumber	28
8.4.3.10	getPath	28
8.4.3.11	getPrice	29
8.4.3.12	getSumQuantity	29
8.4.3.13	getTitle	29
8.4.3.14	hydrat	29
8.4.3.15	isBilling	29
8.4.3.16	isPaid	29
8.4.3.17	operator!=	29
8.4.3.18	operator<	30
8.4.3.19	operator==	30
8.4.3.20	setDate	30
8.4.3.21	setDescription	30
8.4.3.22	setIsBilling	30
8.4.3.23	setIsPaid	31
8.4.3.24	setNumber	31
8.4.3.25	setTitle	31
8.5	Databases::BillingDatabase Class Reference	31
8.5.1	Detailed Description	33

8.5.2	Member Function Documentation	33
8.5.2.1	addBilling	33
8.5.2.2	addBillingProject	33
8.5.2.3	getAllBillingsOfProject	33
8.5.2.4	getBilling	33
8.5.2.5	getBilling	34
8.5.2.6	getBillingsTable	35
8.5.2.7	getBills	35
8.5.2.8	getBillsBetweenDates	35
8.5.2.9	getBillsPaid	35
8.5.2.10	getMaxBillingNumber	36
8.5.2.11	getMaxBillingNumberOfCustomer	36
8.5.2.12	getMaxQuoteNumber	36
8.5.2.13	getMaxQuoteNumberOfCustomer	36
8.5.2.14	getNbBills	36
8.5.2.15	getNbBillsPaid	37
8.5.2.16	getNbDocs	37
8.5.2.17	getNbQuotes	37
8.5.2.18	instance	37
8.5.2.19	isBillingPaid	38
8.5.2.20	removeBilling	39
8.5.2.21	removeBillingProject	39
8.6	BillingDatabaseTest Class Reference	39
8.7	BillingModelTest Class Reference	39
8.8	Gui::Widgets::WdgModels::BillingsTableModel Class Reference	40
8.8.1	Detailed Description	41
8.8.2	Constructor & Destructor Documentation	41
8.8.2.1	BillingsTableModel	41
8.8.3	Member Function Documentation	41
8.8.3.1	append	41
8.8.3.2	columnCount	41
8.8.3.3	count	41
8.8.3.4	data	41
8.8.3.5	flags	42
8.8.3.6	getBillings	42
8.8.3.7	headerData	42
8.8.3.8	remove	42
8.8.3.9	rowCount	43
8.8.3.10	setData	43
8.9	Gui::Widgets::BrowseImageWidget Class Reference	43

8.9.1	Detailed Description	44
8.9.2	Constructor & Destructor Documentation	44
8.9.2.1	BrowseImageWidget	44
8.9.3	Member Function Documentation	44
8.9.3.1	getExtension	44
8.9.3.2	getImage	44
8.9.3.3	setImage	44
8.9.3.4	setImageScaled	44
8.10	Models::Calculable Class Reference	45
8.10.1	Detailed Description	45
8.10.2	Member Function Documentation	45
8.10.2.1	getPrice	45
8.10.2.2	getSumQuantity	45
8.11	Gui::Widgets::CheckFields::CheckCity Class Reference	46
8.11.1	Detailed Description	46
8.11.2	Constructor & Destructor Documentation	46
8.11.2.1	CheckCity	46
8.12	Gui::Widgets::CheckFields::CheckCountry Class Reference	47
8.12.1	Detailed Description	47
8.12.2	Constructor & Destructor Documentation	47
8.12.2.1	CheckCountry	47
8.13	Gui::Widgets::CheckFields::CheckEmail Class Reference	47
8.13.1	Detailed Description	48
8.13.2	Constructor & Destructor Documentation	48
8.13.2.1	CheckEmail	48
8.13.3	Member Function Documentation	48
8.13.3.1	check	48
8.14	Gui::Widgets::CheckFields::CheckFieldsLetters Class Reference	49
8.14.1	Detailed Description	49
8.14.2	Constructor & Destructor Documentation	49
8.14.2.1	CheckFieldsLetters	49
8.14.3	Member Function Documentation	50
8.14.3.1	check	50
8.15	Gui::Widgets::CheckFields::CheckFieldsNumbers Class Reference	51
8.15.1	Detailed Description	51
8.15.2	Constructor & Destructor Documentation	52
8.15.2.1	CheckFieldsNumbers	52
8.15.3	Member Function Documentation	53
8.15.3.1	check	53
8.16	Gui::Widgets::CheckFields::CheckIpAddress Class Reference	53

8.16.1 Detailed Description	53
8.16.2 Constructor & Destructor Documentation	54
8.16.2.1 CheckIpAddress	54
8.16.3 Member Function Documentation	54
8.16.3.1 check	54
8.17 Gui::Widgets::CheckFields::CheckLogin Class Reference	54
8.17.1 Detailed Description	55
8.17.2 Constructor & Destructor Documentation	55
8.17.2.1 CheckLogin	55
8.17.3 Member Function Documentation	55
8.17.3.1 check	55
8.18 Gui::Widgets::CheckFields::CheckName Class Reference	56
8.18.1 Detailed Description	56
8.18.2 Constructor & Destructor Documentation	56
8.18.2.1 CheckName	56
8.19 Gui::Widgets::CheckFields::CheckPhone Class Reference	56
8.19.1 Detailed Description	57
8.19.2 Constructor & Destructor Documentation	57
8.19.2.1 CheckPhone	57
8.19.3 Member Function Documentation	57
8.19.3.1 check	57
8.19.3.2 getCountry	58
8.19.3.3 setCountry	58
8.20 Gui::Widgets::CheckFields::CheckPortNumber Class Reference	58
8.20.1 Detailed Description	58
8.20.2 Constructor & Destructor Documentation	59
8.20.2.1 CheckPortNumber	59
8.20.3 Member Function Documentation	59
8.20.3.1 check	59
8.21 Gui::Widgets::CheckFields::CheckPostalCode Class Reference	59
8.21.1 Detailed Description	60
8.21.2 Constructor & Destructor Documentation	60
8.21.2.1 CheckPostalCode	60
8.21.3 Member Function Documentation	60
8.21.3.1 check	60
8.21.3.2 getCountry	60
8.21.3.3 setCountry	60
8.22 Gui::Widgets::CheckFields::CheckQLineEdit Class Reference	61
8.22.1 Detailed Description	61
8.22.2 Constructor & Destructor Documentation	61

8.22.2.1	CheckQLineEdit	61
8.22.3	Member Function Documentation	62
8.22.3.1	getBtnValid	62
8.22.3.2	isValid	62
8.22.3.3	setBtnValid	62
8.23	Gui::Widgets::CheckFields::CheckSiretNumber Class Reference	62
8.23.1	Detailed Description	63
8.23.2	Constructor & Destructor Documentation	63
8.23.2.1	CheckSiretNumber	63
8.23.3	Member Function Documentation	63
8.23.3.1	check	63
8.24	Gui::Widgets::CheckFields::CheckUntilField Class Reference	63
8.24.1	Detailed Description	64
8.24.2	Constructor & Destructor Documentation	64
8.24.2.1	CheckUntilField	64
8.24.3	Member Function Documentation	64
8.24.3.1	check	64
8.25	Gui::Widgets::CheckFields::CheckValidField Class Reference	64
8.25.1	Detailed Description	65
8.25.2	Constructor & Destructor Documentation	65
8.25.2.1	CheckValidField	65
8.25.3	Member Function Documentation	65
8.25.3.1	check	65
8.26	Gui::Widgets::CheckFields::CheckWebsite Class Reference	66
8.26.1	Detailed Description	66
8.26.2	Constructor & Destructor Documentation	66
8.26.2.1	CheckWebsite	66
8.26.3	Member Function Documentation	66
8.26.3.1	check	66
8.27	Gui::Widgets::Path::ChoseDirectoryWidget Class Reference	67
8.27.1	Detailed Description	67
8.27.2	Constructor & Destructor Documentation	67
8.27.2.1	ChoseDirectoryWidget	67
8.28	Gui::Widgets::Path::ChoseFileWidget Class Reference	68
8.28.1	Detailed Description	68
8.28.2	Constructor & Destructor Documentation	68
8.28.2.1	ChoseFileWidget	68
8.28.3	Member Function Documentation	69
8.28.3.1	getTypeFiles	69
8.28.3.2	setTypeFiles	69

8.29	Gui::Widgets::Path::ChosePathWidget Class Reference	69
8.29.1	Detailed Description	70
8.29.2	Constructor & Destructor Documentation	70
8.29.2.1	ChosePathWidget	70
8.29.3	Member Function Documentation	70
8.29.3.1	getDefaultLocation	70
8.29.3.2	getField	70
8.29.3.3	setField	70
8.30	Gui::Widgets::Delegates::ComboBoxDelegate Class Reference	71
8.30.1	Detailed Description	71
8.30.2	Constructor & Destructor Documentation	72
8.30.2.1	ComboBoxDelegate	72
8.30.3	Member Function Documentation	72
8.30.3.1	createEditor	72
8.30.3.2	paint	72
8.30.3.3	setEditorData	72
8.30.3.4	setModelData	73
8.30.3.5	updateEditorGeometry	74
8.31	Gui::Widgets::ComboBoxModelWidget Class Reference	74
8.31.1	Detailed Description	74
8.31.2	Constructor & Destructor Documentation	74
8.31.2.1	ComboBoxModelWidget	74
8.32	Gui::Dialogs::ComputeTurnoverDialog Class Reference	75
8.32.1	Detailed Description	75
8.32.2	Member Function Documentation	75
8.32.2.1	beginDateControl	75
8.32.2.2	endDateControl	76
8.32.2.3	fillLabels	76
8.33	Mustache::Context Class Reference	76
8.33.1	Detailed Description	77
8.33.2	Constructor & Destructor Documentation	77
8.33.2.1	Context	77
8.33.3	Member Function Documentation	77
8.33.3.1	canEval	77
8.33.3.2	eval	77
8.33.3.3	isFalse	77
8.33.3.4	listCount	77
8.33.3.5	partialResolver	77
8.33.3.6	partialValue	77
8.33.3.7	pop	78

8.33.3.8	push	78
8.33.3.9	stringValue	78
8.34	ContributoriesDatabaseTest Class Reference	78
8.35	Models::ContributoriesList Class Reference	78
8.35.1	Detailed Description	79
8.35.2	Member Function Documentation	80
8.35.2.1	addContributory	80
8.35.2.2	addProject	81
8.35.2.3	getAllContributories	81
8.35.2.4	getContributories	81
8.35.2.5	getCustomer	81
8.35.2.6	getDataMap	81
8.35.2.7	getIdBilling	81
8.35.2.8	getNbProjects	82
8.35.2.9	getPrice	82
8.35.2.10	getPrice	82
8.35.2.11	getProjects	82
8.35.2.12	getRate	82
8.35.2.13	getSumQuantity	82
8.35.2.14	getSumQuantity	83
8.35.2.15	isInsert	83
8.35.2.16	setAllIdContributories	83
8.35.2.17	setIdBilling	83
8.35.2.18	setInsert	83
8.36	Gui::Widgets::WdgModels::ContributoriesTableModel Class Reference	83
8.36.1	Detailed Description	84
8.36.2	Constructor & Destructor Documentation	84
8.36.2.1	ContributoriesTableModel	84
8.36.3	Member Function Documentation	85
8.36.3.1	append	85
8.36.3.2	columnCount	85
8.36.3.3	count	85
8.36.3.4	data	85
8.36.3.5	flags	85
8.36.3.6	getContributories	86
8.36.3.7	getSumQuantity	86
8.36.3.8	headerData	86
8.36.3.9	remove	86
8.36.3.10	rowCount	86
8.36.3.11	setData	86

8.37	Gui::Widgets::ContributoriesWidget Class Reference	87
8.37.1	Detailed Description	88
8.37.2	Constructor & Destructor Documentation	88
8.37.2.1	ContributoriesWidget	88
8.37.3	Member Function Documentation	88
8.37.3.1	add	88
8.37.3.2	addProject	88
8.37.3.3	count	88
8.37.3.4	getContributories	89
8.38	Models::Contributory Class Reference	89
8.38.1	Detailed Description	90
8.38.2	Constructor & Destructor Documentation	90
8.38.2.1	Contributory	90
8.38.3	Member Function Documentation	90
8.38.3.1	getDataMap	90
8.38.3.2	getDescription	91
8.38.3.3	getHourlyRate	91
8.38.3.4	getLongDescription	91
8.38.3.5	getPrice	91
8.38.3.6	getProject	91
8.38.3.7	getQuantity	91
8.38.3.8	getSumQuantity	92
8.38.3.9	getUnit	92
8.38.3.10	hydrat	92
8.38.3.11	operator!=	92
8.38.3.12	operator==	92
8.38.3.13	setDescription	92
8.38.3.14	setHourlyRate	93
8.38.3.15	setLongDescription	93
8.38.3.16	setProject	93
8.38.3.17	setQuantity	93
8.38.3.18	setUnit	93
8.39	Databases::ContributoryDatabase Class Reference	93
8.39.1	Detailed Description	94
8.39.2	Member Function Documentation	94
8.39.2.1	addContributory	94
8.39.2.2	getContributoriesByBilling	95
8.39.2.3	getContributoriesByBillingAndProject	95
8.39.2.4	getContributory	95
8.39.2.5	getContributory	95

8.39.2.6	instance	95
8.39.2.7	removeContributory	96
8.40	ContributoryListTest Class Reference	96
8.41	ContributoryModelTest Class Reference	96
8.42	CounterContext Class Reference	97
8.42.1	Member Function Documentation	97
8.42.1.1	canEval	97
8.42.1.2	canEval	97
8.42.1.3	eval	98
8.42.1.4	eval	98
8.42.1.5	stringValue	98
8.42.1.6	stringValue	98
8.43	Models::Customer Class Reference	98
8.43.1	Detailed Description	99
8.43.2	Constructor & Destructor Documentation	99
8.43.2.1	Customer	99
8.43.3	Member Function Documentation	99
8.43.3.1	commit	99
8.43.3.2	getDataMap	100
8.43.3.3	getImage	100
8.43.3.4	getNameFolder	100
8.43.3.5	getPath	100
8.43.3.6	getTurnover	100
8.43.3.7	hydrat	100
8.43.3.8	isArchived	101
8.43.3.9	setImage	101
8.43.3.10	setIsArchived	101
8.44	Gui::Widgets::CustomerContextualMenu Class Reference	101
8.44.1	Detailed Description	102
8.44.2	Constructor & Destructor Documentation	102
8.44.2.1	CustomerContextualMenu	102
8.45	Databases::CustomerDatabase Class Reference	102
8.45.1	Detailed Description	103
8.45.2	Member Function Documentation	103
8.45.2.1	addCustomer	103
8.45.2.2	getCustomer	103
8.45.2.3	getCustomer	104
8.45.2.4	getCustomerImage	104
8.45.2.5	getCustomers	104
8.45.2.6	getCustomersTable	104

8.45.2.7	getItemCustomer	105
8.45.2.8	getItemProject	106
8.45.2.9	getItemRoot	106
8.45.2.10	getNbCustomers	106
8.45.2.11	getTree	106
8.45.2.12	instance	107
8.45.2.13	removeCustomer	107
8.45.2.14	setCustomerImage	107
8.45.2.15	updateCustomer	107
8.46	CustomerDatabaseTest Class Reference	107
8.47	Gui::Widgets::CustomerDataWidget Class Reference	108
8.47.1	Detailed Description	108
8.47.2	Constructor & Destructor Documentation	108
8.47.2.1	CustomerDataWidget	108
8.47.3	Member Function Documentation	108
8.47.3.1	printInformations	108
8.48	CustomerModelTest Class Reference	109
8.49	Gui::Widgets::WdgModels::CustomersTableModel Class Reference	109
8.49.1	Detailed Description	110
8.49.2	Constructor & Destructor Documentation	110
8.49.2.1	CustomersTableModel	110
8.49.3	Member Function Documentation	110
8.49.3.1	append	110
8.49.3.2	columnCount	110
8.49.3.3	count	110
8.49.3.4	data	111
8.49.3.5	flags	112
8.49.3.6	getCustomers	112
8.49.3.7	headerData	112
8.49.3.8	remove	112
8.49.3.9	rowCount	113
8.49.3.10	setData	113
8.50	Databases::Database Class Reference	113
8.50.1	Detailed Description	114
8.50.2	Member Function Documentation	115
8.50.2.1	changeDatabase	115
8.50.2.2	executeFile	115
8.50.2.3	instance	115
8.50.2.4	lastError	115
8.50.2.5	setDatabase	115

8.50.2.6	value	115
8.51	Gui::Widgets::DatabaseSettingsWidget Class Reference	116
8.51.1	Detailed Description	117
8.51.2	Constructor & Destructor Documentation	117
8.51.2.1	DatabaseSettingsWidget	117
8.51.3	Member Function Documentation	117
8.51.3.1	getDatabaseName	117
8.51.3.2	getDomainNameOrIP	117
8.51.3.3	getLogin	117
8.51.3.4	getPassword	118
8.51.3.5	getPort	118
8.51.3.6	isValid	118
8.52	Exceptions::DbException Class Reference	118
8.52.1	Detailed Description	119
8.52.2	Constructor & Destructor Documentation	119
8.52.2.1	DbException	119
8.52.3	Member Function Documentation	119
8.52.3.1	popupMessage	119
8.53	Gui::Dialogs::DialogAddCustomer Class Reference	119
8.53.1	Detailed Description	120
8.53.2	Constructor & Destructor Documentation	120
8.53.2.1	DialogAddCustomer	120
8.54	Utils::Directories Class Reference	120
8.54.1	Member Function Documentation	120
8.54.1.1	makeDirectory	120
8.55	Utils::Double Class Reference	121
8.55.1	Detailed Description	121
8.55.2	Member Function Documentation	121
8.55.2.1	round	121
8.56	Gui::Widgets::Delegates::DoubleSpinBoxDelegate Class Reference	122
8.56.1	Detailed Description	122
8.56.2	Constructor & Destructor Documentation	122
8.56.2.1	DoubleSpinBoxDelegate	122
8.56.3	Member Function Documentation	123
8.56.3.1	createEditor	123
8.56.3.2	setEditorData	124
8.56.3.3	setModelData	124
8.56.3.4	updateEditorGeometry	124
8.57	FileChoseWidget Class Reference	124
8.58	Exceptions::FileException Class Reference	125

8.58.1 Detailed Description	125
8.58.2 Constructor & Destructor Documentation	125
8.58.2.1 FileException	125
8.58.3 Member Function Documentation	126
8.58.3.1 popupMessage	126
8.59 Generation Class Reference	126
8.60 Utils::HierarchicalSystem Class Reference	126
8.60.1 Detailed Description	127
8.60.2 Member Function Documentation	127
8.60.2.1 addBillingToProject	127
8.60.2.2 addProjectToCustomer	127
8.60.2.3 getCustomers	127
8.60.2.4 getProjects	127
8.61 Gui::Widgets::CheckFields::!CheckField Class Reference	128
8.61.1 Detailed Description	128
8.61.2 Member Function Documentation	128
8.61.2.1 check	128
8.62 Gui::Utils::Image Class Reference	128
8.62.1 Detailed Description	129
8.62.2 Member Function Documentation	129
8.62.2.1 bytesToPixmap	129
8.62.2.2 imageToBytes	129
8.62.2.3 pixmapToBytes	129
8.62.2.4 pixmapToImage	130
8.63 Models::IModel Class Reference	130
8.63.1 Detailed Description	131
8.63.2 Member Function Documentation	131
8.63.2.1 getDataMap	131
8.63.2.2 getId	131
8.63.2.3 hydrat	131
8.63.2.4 isToRemoved	132
8.63.2.5 setId	132
8.63.2.6 setToRemoved	132
8.64 Utils::ItemType Class Reference	132
8.64.1 Detailed Description	133
8.64.2 Constructor & Destructor Documentation	133
8.64.2.1 ItemType	133
8.64.3 Member Function Documentation	133
8.64.3.1 getModel	133
8.64.3.2 getName	133

8.64.3.3	getType	133
8.64.3.4	setName	134
8.64.3.5	setType	134
8.65	ItemTypeTest Class Reference	134
8.66	Utils::Log Class Reference	134
8.66.1	Detailed Description	135
8.66.2	Member Function Documentation	135
8.66.2.1	instance	135
8.66.2.2	write	135
8.66.3	Friends And Related Function Documentation	135
8.66.3.1	operator<<	135
8.67	Gui::MainWindow Class Reference	135
8.67.1	Detailed Description	137
8.67.2	Constructor & Destructor Documentation	137
8.67.2.1	MainWindow	137
8.67.3	Member Function Documentation	138
8.67.3.1	addBill	138
8.67.3.2	addDoc	138
8.67.3.3	addProject	138
8.67.3.4	addQuote	138
8.67.3.5	editUser	138
8.67.3.6	getCurrentCustomerId	139
8.67.3.7	getCurrentCustomerName	139
8.67.3.8	getCurrentProjectId	139
8.67.3.9	getCurrentProjectName	139
8.67.3.10	getCurrentQuoteId	139
8.67.3.11	resizeEvent	139
8.67.3.12	rootTree	139
8.67.3.13	search	140
8.67.3.14	treeLevel	141
8.68	Gui::Dialogs::MessageBox Class Reference	141
8.68.1	Detailed Description	142
8.68.2	Constructor & Destructor Documentation	142
8.68.2.1	MessageBox	142
8.68.3	Member Function Documentation	142
8.68.3.1	setImage	142
8.68.3.2	setText	142
8.69	Parameters Class Reference	142
8.69.1	Detailed Description	143
8.69.2	Member Data Documentation	143

8.69.2.1	DB_FILENAME	143
8.69.2.2	VERSION	143
8.70	Mustache::PartialFileLoader Class Reference	143
8.70.1	Detailed Description	143
8.70.2	Member Function Documentation	143
8.70.2.1	getPartial	143
8.71	Mustache::PartialMap Class Reference	144
8.71.1	Detailed Description	144
8.71.2	Member Function Documentation	144
8.71.2.1	getPartial	144
8.72	Mustache::PartialResolver Class Reference	144
8.72.1	Detailed Description	145
8.72.2	Member Function Documentation	145
8.72.2.1	getPartial	145
8.73	Generator::PdfGenerator Class Reference	145
8.73.1	Detailed Description	145
8.73.2	Constructor & Destructor Documentation	145
8.73.2.1	PdfGenerator	145
8.73.3	Member Function Documentation	145
8.73.3.1	generate	145
8.74	Models::People Class Reference	146
8.74.1	Detailed Description	148
8.74.2	Member Function Documentation	148
8.74.2.1	getAddress	148
8.74.2.2	getAddressComplement	148
8.74.2.3	getCity	148
8.74.2.4	getCompany	148
8.74.2.5	getCountry	148
8.74.2.6	getEmail	148
8.74.2.7	getExtensionImage	149
8.74.2.8	getFax	149
8.74.2.9	getFirstname	149
8.74.2.10	getImage	149
8.74.2.11	getLastname	149
8.74.2.12	getMobilePhone	149
8.74.2.13	getPhone	149
8.74.2.14	getPostalCode	150
8.74.2.15	getWebsite	150
8.74.2.16	operator!=	150
8.74.2.17	operator==	150

8.74.2.18 setAddress	150
8.74.2.19 setAddressComplement	150
8.74.2.20 setCity	151
8.74.2.21 setCompany	151
8.74.2.22 setCountry	151
8.74.2.23 setEmail	151
8.74.2.24 setExtensionImage	151
8.74.2.25 setFax	151
8.74.2.26 setFirstname	152
8.74.2.27 setImage	152
8.74.2.28 setLastname	152
8.74.2.29 setMobilePhone	152
8.74.2.30 setPhone	152
8.74.2.31 setPostalCode	152
8.74.2.32 setWebsite	153
8.75 Utils::pointers Class Reference	154
8.75.1 Detailed Description	154
8.75.2 Member Function Documentation	154
8.75.2.1 deleteIfNotNull	154
8.76 PointersTest Class Reference	154
8.77 Gui::Widgets::Popup Class Reference	155
8.77.1 Detailed Description	155
8.78 Models::Project Class Reference	155
8.78.1 Detailed Description	156
8.78.2 Constructor & Destructor Documentation	157
8.78.2.1 Project	157
8.78.3 Member Function Documentation	157
8.78.3.1 getBeginDate	157
8.78.3.2 getCost	157
8.78.3.3 getCustomer	157
8.78.3.4 getDailyRate	157
8.78.3.5 getDataMap	157
8.78.3.6 getDescription	158
8.78.3.7 getEndDate	158
8.78.3.8 getName	158
8.78.3.9 hydrat	158
8.78.3.10 operator!=	158
8.78.3.11 operator<	158
8.78.3.12 operator==	159
8.78.3.13 setBeginDate	159

8.78.3.14	setCustomer	159
8.78.3.15	setDailyRate	159
8.78.3.16	setDescription	159
8.78.3.17	setEndDate	159
8.78.3.18	setName	160
8.79	Gui::Widgets::Delegates::ProjectComboDelegate Class Reference	160
8.79.1	Detailed Description	161
8.79.2	Constructor & Destructor Documentation	161
8.79.2.1	ProjectComboDelegate	161
8.79.3	Member Function Documentation	161
8.79.3.1	createEditor	161
8.79.3.2	getProjects	161
8.79.3.3	isLocked	161
8.79.3.4	paint	161
8.79.3.5	setLocked	162
8.80	Gui::Widgets::WdgModels::ProjectContributoriesTableModel Class Reference	162
8.80.1	Detailed Description	163
8.80.2	Constructor & Destructor Documentation	163
8.80.2.1	ProjectContributoriesTableModel	163
8.80.3	Member Function Documentation	163
8.80.3.1	allProjectsChosen	163
8.80.3.2	append	163
8.80.3.3	columnCount	164
8.80.3.4	data	164
8.80.3.5	flags	164
8.80.3.6	getProject	164
8.80.3.7	getProjects	164
8.80.3.8	getSelectedProjects	165
8.80.3.9	headerData	165
8.80.3.10	remove	165
8.80.3.11	rowCount	165
8.80.3.12	setData	165
8.81	Databases::ProjectDatabase Class Reference	166
8.81.1	Detailed Description	167
8.81.2	Member Function Documentation	167
8.81.2.1	addProject	167
8.81.2.2	getAllProjects	167
8.81.2.3	getCostProjects	167
8.81.2.4	getNbProjects	167
8.81.2.5	getNbProjects	167

8.81.2.6	getProject	168
8.81.2.7	getProject	168
8.81.2.8	getProjects	168
8.81.2.9	getProjectsOfCustomer	168
8.81.2.10	getProjectsTable	169
8.81.2.11	instance	170
8.81.2.12	removeProject	170
8.81.2.13	updateProject	170
8.82	ProjectDatabaseTest Class Reference	170
8.83	ProjectModelTest Class Reference	171
8.84	Gui::Widgets::WdgModels::ProjectsTableModel Class Reference	171
8.84.1	Detailed Description	172
8.84.2	Constructor & Destructor Documentation	172
8.84.2.1	ProjectsTableModel	172
8.84.3	Member Function Documentation	172
8.84.3.1	append	172
8.84.3.2	columnCount	172
8.84.3.3	count	172
8.84.3.4	data	172
8.84.3.5	flags	173
8.84.3.6	getProjects	173
8.84.3.7	headerData	173
8.84.3.8	remove	173
8.84.3.9	rowCount	174
8.84.3.10	setData	174
8.85	Gui::Widgets::ProjectsWidget Class Reference	174
8.85.1	Detailed Description	175
8.85.2	Constructor & Destructor Documentation	175
8.85.2.1	ProjectsWidget	175
8.85.3	Member Function Documentation	175
8.85.3.1	updateBtn	175
8.86	Mustache::QtVariantContext Class Reference	175
8.86.1	Detailed Description	176
8.86.2	Member Typedef Documentation	176
8.86.2.1	fn_t	176
8.86.3	Member Function Documentation	176
8.86.3.1	canEval	176
8.86.3.2	eval	176
8.86.3.3	isFalse	177
8.86.3.4	listCount	177

8.86.3.5	pop	177
8.86.3.6	push	177
8.86.3.7	stringValue	177
8.87	Models::Rate Class Reference	177
8.87.1	Detailed Description	178
8.87.2	Constructor & Destructor Documentation	178
8.87.2.1	Rate	178
8.87.2.2	Rate	178
8.87.3	Member Function Documentation	178
8.87.3.1	getDailyRate	178
8.87.3.2	getHourlyRate	179
8.87.3.3	getLegalRate	179
8.87.3.4	getNbDailyHours	179
8.88	Databases::RateDatabase Class Reference	179
8.88.1	Member Function Documentation	180
8.88.1.1	addRateProject	180
8.88.1.2	getRate	180
8.88.1.3	instance	180
8.88.1.4	updateRateProject	180
8.89	RateModelTest Class Reference	181
8.90	Gui::Widgets::RateWidget Class Reference	181
8.90.1	Detailed Description	182
8.90.2	Constructor & Destructor Documentation	182
8.90.2.1	RateWidget	182
8.90.3	Member Function Documentation	182
8.90.3.1	getDailyRate	182
8.90.3.2	getHourlyRate	182
8.90.3.3	setDailyRate	182
8.90.3.4	setHourlyRate	182
8.90.3.5	setWidgetDailyRateValue	182
8.90.3.6	setWidgetHourlyRateValue	183
8.91	Mustache::Renderer Class Reference	183
8.91.1	Detailed Description	183
8.91.2	Member Function Documentation	183
8.91.2.1	error	183
8.91.2.2	errorPartial	183
8.91.2.3	errorPos	183
8.91.2.4	render	184
8.91.2.5	setTagMarkers	184
8.92	Models::Search Class Reference	184

8.92.1	Detailed Description	185
8.92.2	Member Function Documentation	185
8.92.2.1	filterOnBillsOrQuotes	185
8.92.2.2	filterOnCompany	185
8.92.2.3	filterOnContributories	185
8.92.2.4	filterOnCustomersWithoutProject	186
8.92.2.5	filterOnNumberElements	186
8.92.2.6	filterOnProjects	186
8.92.2.7	filterOnReferentLastname	186
8.92.2.8	filterOnVarcharElements	186
8.92.2.9	getFilter	187
8.92.2.10	getGroupFilter	187
8.92.2.11	getSearchInBillsQuotes	187
8.92.2.12	getSearchInCompanies	187
8.92.2.13	getSearchInProjects	187
8.92.2.14	getSearchInReferentLastname	187
8.92.2.15	getText	187
8.92.2.16	searchInContributories	188
8.92.2.17	setGroupFilter	188
8.92.2.18	setSearchInBillsQuotes	188
8.92.2.19	setSearchInCompanies	188
8.92.2.20	setSearchInContributories	188
8.92.2.21	setSearchInProjects	188
8.92.2.22	setSearchInReferentLastname	188
8.92.2.23	setText	189
8.93	Gui::Docks::SearchDock Class Reference	189
8.93.1	Detailed Description	189
8.93.2	Constructor & Destructor Documentation	190
8.93.2.1	SearchDock	190
8.93.3	Member Function Documentation	191
8.93.3.1	search	191
8.93.3.2	textChanged	191
8.94	searchTest Class Reference	191
8.95	Gui::Widgets::searchWidget Class Reference	191
8.95.1	Detailed Description	192
8.95.2	Constructor & Destructor Documentation	192
8.95.2.1	searchWidget	192
8.95.3	Member Function Documentation	193
8.95.3.1	getCurrentCustomerId	193
8.95.3.2	getCustomerId	193

8.95.3.3	isCustomerSelected	193
8.95.3.4	search	193
8.95.3.5	selectCustomer	193
8.95.3.6	setIdCustomer	193
8.96	Gui::Dialogs::StartedWindowsDialog Class Reference	194
8.96.1	Detailed Description	195
8.96.2	Constructor & Destructor Documentation	195
8.96.2.1	StartedWindowsDialog	195
8.96.3	Member Function Documentation	195
8.96.3.1	databaseTypeChanged	195
8.96.3.2	getImage	195
8.96.3.3	isDatabaseCentralized	196
8.96.3.4	isDatabaseTypeValid	196
8.97	StatisticModelTest Class Reference	196
8.98	Models::Statistics Class Reference	196
8.98.1	Member Function Documentation	196
8.98.1.1	getGlobalTurnover	196
8.98.1.2	getTurnoverBetweenDates	197
8.99	Gui::Dialogs::StatisticsDialog Class Reference	197
8.99.1	Detailed Description	197
8.99.2	Constructor & Destructor Documentation	198
8.99.2.1	StatisticsDialog	198
8.99.3	Member Function Documentation	199
8.99.3.1	singularPlural	199
8.99.3.2	updateUi	199
8.100	Utils::String Class Reference	199
8.100.1	Detailed Description	199
8.100.2	Member Function Documentation	200
8.100.2.1	firstLetterToUpper	200
8.100.2.2	getExtensionFile	201
8.101	StringTest Class Reference	201
8.102	Mustache::Tag Struct Reference	201
8.102.1	Detailed Description	202
8.102.2	Member Enumeration Documentation	202
8.102.2.1	Type	202
8.103	testadder Class Reference	202
8.104	TestAdder< T > Class Template Reference	202
8.105	TestMustache Class Reference	203
8.106	TestRunner Class Reference	203
8.107	Generator::TexGenerator Class Reference	203

8.107.1 Detailed Description	203
8.107.2 Constructor & Destructor Documentation	204
8.107.2.1 TexGenerator	204
8.107.3 Member Function Documentation	205
8.107.3.1 generate	205
8.108Gui::Widgets::Delegates::TextareaDelegate Class Reference	205
8.108.1 Detailed Description	205
8.108.2 Constructor & Destructor Documentation	206
8.108.2.1 TextareaDelegate	206
8.108.3 Member Function Documentation	206
8.108.3.1 createEditor	206
8.108.3.2 setEditorData	206
8.108.3.3 setModelData	206
8.108.3.4 updateEditorGeometry	207
8.109Models::Unit Class Reference	208
8.109.1 Detailed Description	208
8.109.2 Constructor & Destructor Documentation	208
8.109.2.1 Unit	208
8.109.3 Member Function Documentation	208
8.109.3.1 gettype	208
8.109.3.2 operator!=	209
8.109.3.3 operator==	209
8.109.3.4 setType	209
8.109.3.5 toString	209
8.110Gui::Widgets::Delegates::UnitComboDelegate Class Reference	209
8.110.1 Detailed Description	210
8.110.2 Constructor & Destructor Documentation	210
8.110.2.1 UnitComboDelegate	210
8.110.3 Member Function Documentation	210
8.110.3.1 createEditor	210
8.110.3.2 paint	211
8.111Models::User Class Reference	211
8.111.1 Detailed Description	212
8.111.2 Constructor & Destructor Documentation	212
8.111.2.1 User	212
8.111.3 Member Function Documentation	213
8.111.3.1 getDataMap	213
8.111.3.2 getImage	213
8.111.3.3 getNbDaysPerMonths	213
8.111.3.4 getNbHoursPerDays	213

8.111.3.5 getNoSiret	213
8.111.3.6 getPdflatexPath	213
8.111.3.7 setTitle	214
8.111.3.8 getWorkspaceName	214
8.111.3.9 getWorkspacePath	214
8.111.3.10 hydrat	214
8.111.3.11 operator!=	214
8.111.3.12 operator==	214
8.111.3.13 setImage	215
8.111.3.14 setNoSiret	215
8.111.3.15 setPdflatexPath	215
8.111.3.16 setTitle	215
8.111.3.17 setWorkspaceName	215
8.111.3.18 setWorkspacePath	215
8.111.3.19 updateFolders	216
8.112 Databases::UserDatabase Class Reference	216
8.112.1 Detailed Description	217
8.112.2 Member Function Documentation	217
8.112.2.1 getUser	217
8.112.2.2 getUserImage	217
8.112.2.3 instance	217
8.112.2.4 setUserImage	217
8.113 UserDatabaseTest Class Reference	218
8.114 Gui::Dialogs::UserDataDialog Class Reference	218
8.114.1 Detailed Description	219
8.114.2 Constructor & Destructor Documentation	219
8.114.2.1 UserDataDialog	219
8.115 UserModelTest Class Reference	219
8.116 Gui::Utils::WindowSettings Class Reference	219
8.116.1 Detailed Description	220
8.116.2 Member Function Documentation	220
8.116.2.1 setMaximumSize	220
8.116.2.2 setPositionToCenter	220

Chapter 1

FactDev documentation

This website contains the documentation of FactDev, a billings and quotes software.

Team

FACT team is a team for University Project. Members of this team are :

- Florent Berbie ([KraTuX31](#))
- Antoine de Roquemaurel ([aroquemaurel](#))
- Cédric Rohaut ([Oxynos](#))
- Manantsoa Andriamihary Razanajatovo ([manantsoa](#))

For more informations, you can go to <http://fact-team.github.io>.

What is FactDev ?

FactDev is a software for quotes and billings developped by FACT team for university project in Toulouse III University – Paul Sabatier.

This software is developed with C++ and Qt framework, and there is differents features :

- Customers database
- Differents projects for customers
- Quotes
- Billings

Documentation

You can access to the documentation generated by Doxygen here :

- [HTML Documentation](#)
- [PDF Documentation](#)

Installation and using

- [User Manual](#)

Chapter 2

README

! [Build Status] (<https://travis-ci.org/robertknight/qt-mustache.svg?branch=master>)

Qt Mustache

qt-mustache is a simple library for rendering **Mustache templates**.

Example Usage

```
““cpp #include "mustache.h"
```

```
QVariantHash contact; contact["name"] = "John Smith"; contact["email"] = "john.smith@gmail.com";
```

```
QString contactTemplate = "<b>{{name}}</b> <a href=\"mailto:{{email}}\">{{email}}\"";
```

```
Mustache::Renderer renderer; Mustache::QtVariantContext context(contact);
```

```
QTextStream output(stdout); output << renderer.render(contactTemplate, &context); ““
```

Outputs: John Smith john.smith@gmail.com

For further examples, see the tests in `test_mustache.cpp`

Building

- To build the tests, run `qmake` followed by `make`
- To use qt-mustache in your project, just add the `mustache.h` and `mustache.cpp` files to your project.

License

qt-mustache is licensed under the BSD license.

Dependencies

qt-mustache depends on the QtCore library. It is compatible with Qt 4 and Qt 5.

Usage

Syntax

qt-mustache uses the standard Mustache syntax. See the [Mustache manual](#) for details.

Data Sources

qt-mustache expands Mustache tags using values from a `Mustache::Context`. `Mustache::QtVariantContext` is a simple context implementation which wraps a `QVariantHash` or `QVariantMap`. If you want to render a template using a custom data source, you can either create a `QVariantHash` which mirrors the data source or you can re-implement `Mustache::Context`.

Partials

When a `{{>partial}}` Mustache tag is encountered, qt-mustache will attempt to load the partial using a `Mustache::PartialResolver` provided by the context. `Mustache::PartialMap` is a simple resolver which takes a `QHash<QString,QString>` map of partial names to values and looks up partials in that map. `Mustache::PartialFileLoader` is another simple resolver which fetches partials from `<partial name>.mustache` files in a specified directory.

You can re-implement the `Mustache::PartialResolver` interface if you want to load partials from a custom source (eg. a database).

Error Handling

If an error occurs when rendering a template, `Mustache::Renderer::errorPosition()` is set to non-negative value and template rendering stops. If the error occurs whilst rendering a partial template, `errorPartial()` contains the name of the partial.

Lambdas

The [Mustache manual](#) provides a mechanism to customize rendering of template sections by setting the value for a tag to a callable object (eg. a lambda in Ruby or Javascript), which takes the unrendered block of text for a template section and renders it itself. qt-mustache supports this via the `Context::canEval()` and `Context::eval()` methods.

Chapter 3

QTestRunner

A repo for Increase QTest productivity

Thanks to <https://marcoarena.wordpress.com/2012/06/23/increase-your-qtest-productivity/>!

The QTestLib framework is a tool for unit testing Qt based applications and libraries. I find it precious and simple to use, though it lacks some important features, supported, for example, by GTest. I'm not talking about mocking – for this you generally need an out-and-out framework (like GMock) – instead, I'm referring to simple things like fast deploying. Suppose you have written a test class like this:

This repo contains only the code in this article.

Chapter 4

Namespace Index

4.1 Namespace List

Here is a list of all documented namespaces with brief descriptions:

Databases		
	Class for Database , contains queries	??
Gui	??
Gui::Widgets		
	Contains Widgets classes	??
Models		
	Models classes	??

Chapter 5

Hierarchical Index

5.1 Class Hierarchy

This inheritance list is sorted roughly, but not completely, alphabetically:

Databases::AccessDatabase	??
Models::Calculable	??
Models::Billing	??
Models::ContributoriesList	??
Models::Contributory	??
Mustache::Context	??
Mustache::QtVariantContext	??
CounterContext	??
CounterContext	??
Databases::Database	??
Databases::BillingDatabase	??
Databases::ContributoryDatabase	??
Databases::CustomerDatabase	??
Databases::ProjectDatabase	??
Databases::RateDatabase	??
Databases::UserDatabase	??
Utils::Directories	??
Utils::Double	??
exception	
Exceptions::DbException	??
Exceptions::FileException	??
Utils::HierarchicalSystem	??
Gui::Widgets::CheckFields::ICheckField	??
Gui::Widgets::CheckFields::CheckQLineEdit	??
Gui::Widgets::CheckFields::CheckEmail	??
Gui::Widgets::CheckFields::CheckPortNumber	??
Gui::Widgets::CheckFields::CheckSiretNumber	??
Gui::Widgets::CheckFields::CheckUntilField	??
Gui::Widgets::CheckFields::CheckFieldsLetters	??
Gui::Widgets::CheckFields::CheckCity	??
Gui::Widgets::CheckFields::CheckCountry	??
Gui::Widgets::CheckFields::CheckName	??
Gui::Widgets::CheckFields::CheckFieldsNumbers	??
Gui::Widgets::CheckFields::CheckIpAddress	??
Gui::Widgets::CheckFields::CheckLogin	??
Gui::Widgets::CheckFields::CheckPhone	??
Gui::Widgets::CheckFields::CheckPostalCode	??

Gui::Widgets::CheckFields::CheckValidField	??
Gui::Widgets::CheckFields::CheckWebsite	??
Gui::Utils::Image	??
Models::IModel	??
Models::Billing	??
Models::Contributory	??
Models::People	??
Models::Customer	??
Models::User	??
Models::Project	??
Utils::ItemType	??
Utils::Log	??
Parameters	??
Mustache::PartialResolver	??
Mustache::PartialFileLoader	??
Mustache::PartialMap	??
Generator::PdfGenerator	??
Utils::pointers	??
Gui::Widgets::Popup	??
QAbstractTableModel	
Gui::Widgets::WdgModels::BillingsTableModel	??
Gui::Widgets::WdgModels::ContributoriesTableModel	??
Gui::Widgets::WdgModels::CustomersTableModel	??
Gui::Widgets::WdgModels::ProjectContributoriesTableModel	??
Gui::Widgets::WdgModels::ProjectsTableModel	??
QDialog	
Gui::Dialogs::AddProjectDialog	??
Gui::Dialogs::AddQuoteDialog	??
Gui::Dialogs::ComputeTurnoverDialog	??
Gui::Dialogs::DialogAddCustomer	??
Gui::Dialogs::MessageBox	??
Gui::Dialogs::StartedWindowsDialog	??
Gui::Dialogs::StatisticsDialog	??
Gui::Dialogs::UserDataDialog	??
QDockWidget	
Gui::Docks::SearchDock	??
QItemDelegate	
Gui::Widgets::Delegates::ComboBoxDelegate	??
Gui::Widgets::Delegates::ProjectComboDelegate	??
Gui::Widgets::Delegates::UnitComboDelegate	??
Gui::Widgets::Delegates::DoubleSpinBoxDelegate	??
Gui::Widgets::Delegates::TextareaDelegate	??
QLineEdit	
Gui::Widgets::CheckFields::CheckQLineEdit	??
QMainWindow	
Gui::MainWindow	??
QMap	
Models::ContributoriesList	??
QMenu	
Gui::Widgets::CustomerContextualMenu	??
QObject	
BillingDatabaseTest	??
BillingModelTest	??
ContributoriesDatabaseTest	??
ContributoryListTest	??
ContributoryModelTest	??
CustomerDatabaseTest	??

CustomerModelTest	??
Generation	??
ItemTypeTest	??
PointersTest	??
ProjectDatabaseTest	??
ProjectModelTest	??
RateModelTest	??
searchTest	??
StatisticModelTest	??
StringTest	??
TestMustache	??
TestMustache	??
UserDatabaseTest	??
UserModelTest	??
QWidget	
FileChoseWidget	??
Gui::Widgets::BrowseImageWidget	??
Gui::Widgets::ComboBoxModelWidget	??
Gui::Widgets::ContributoriesWidget	??
Gui::Widgets::CustomerDataWidget	??
Gui::Widgets::DatabaseSettingsWidget	??
Gui::Widgets::Path::ChosePathWidget	??
Gui::Widgets::Path::ChoseDirectoryWidget	??
Gui::Widgets::Path::ChoseFileWidget	??
Gui::Widgets::ProjectsWidget	??
Gui::Widgets::RateWidget	??
Gui::Widgets::searchWidget	??
Models::Rate	??
Mustache::Renderer	??
Models::Search	??
Models::Statistics	??
Utils::String	??
Mustache::Tag	??
testadder	??
TestAdder< T >	??
TestRunner	??
Generator::TexGenerator	??
Models::Unit	??
Gui::Utils::WindowSettings	??

Chapter 6

Class Index

6.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

Databases::AccessDatabase	??
Gui::Dialogs::AddProjectDialog	
Windows to add a new Project	??
Gui::Dialogs::AddQuoteDialog	
Window to add or modify a Quote	??
Models::Billing	
: Billing or Quote of a Customer	??
Databases::BillingDatabase	
The BillingDatabase class Billing (or Quote) table database	??
BillingDatabaseTest	??
BillingModelTest	??
Gui::Widgets::WdgModels::BillingsTableModel	
For a Billing table	??
Gui::Widgets::BrowseImageWidget	
Widget to add a new BrowseImageWidget	??
Models::Calculable	
The Calculable interface Models who are calculable	??
Gui::Widgets::CheckFields::CheckCity	
Line Edit of City with a check icon	??
Gui::Widgets::CheckFields::CheckCountry	
CheckCountry::CheckCountry Line Edit of country with a check icon	??
Gui::Widgets::CheckFields::CheckEmail	
Line Edit of email with a check icon	??
Gui::Widgets::CheckFields::CheckFieldsLetters	
Field with only letters (no numbers)	??
Gui::Widgets::CheckFields::CheckFieldsNumbers	
Line Edit of number with a check icon	??
Gui::Widgets::CheckFields::CheckIpAddress	
Line Edit of IP address with a check icon	??
Gui::Widgets::CheckFields::CheckLogin	
Line Edit of login with a check icon	??
Gui::Widgets::CheckFields::CheckName	
Line edit of name with a check icon	??
Gui::Widgets::CheckFields::CheckPhone	
Line Edit of Phone number with a check icon	??
Gui::Widgets::CheckFields::CheckPortNumber	
The CheckFieldsNumbers class Line Edit of number with a check icon	??

Gui::Widgets::CheckFields::CheckPostalCode	
Line Edit of postal code with a check icon	??
Gui::Widgets::CheckFields::CheckQLineEdit	
LineEdit custom with a check of text inputed	??
Gui::Widgets::CheckFields::CheckSiretNumber	
Line Edit with a check icon	??
Gui::Widgets::CheckFields::CheckUntilField	
The CheckUntilField class	??
Gui::Widgets::CheckFields::CheckValidField	
Check field not required	??
Gui::Widgets::CheckFields::CheckWebsite	
Line Edit of website with a check icon	??
Gui::Widgets::Path::ChoseDirectoryWidget	
Open a QFileDialog.and display path in textfield	??
Gui::Widgets::Path::ChoseFileWidget	
Chose a File in computer	??
Gui::Widgets::Path::ChosePathWidget	
The ChoseDirectoryWidget class Open a QFileDialog.and display path in textfield	??
Gui::Widgets::Delegates::ComboBoxDelegate	
The ComboBoxDelegate class	??
Gui::Widgets::ComboBoxModelWidget	
Model of ComboBox	??
Gui::Dialogs::ComputeTurnoverDialog	
Window to compute a turnover with a period	??
Mustache::Context	??
ContributoriesDatabaseTest	??
Models::ContributoriesList	
List of contributories	??
Gui::Widgets::WdgModels::ContributoriesTableModel	
For a custom table for contributories widget	??
Gui::Widgets::ContributoriesWidget	
Widget of Contributories	??
Models::Contributory	
The Unit enum Unity of work : hour or day	??
Databases::ContributoryDatabase	
The ContributoryDatabase class Contributory (or Quote) table database	??
ContributoryListTest	??
ContributoryModelTest	??
CounterContext	??
Models::Customer	
Customer	??
Gui::Widgets::CustomerContextualMenu	
Display contextual menu on a customer	??
Databases::CustomerDatabase	
The CustomerDatabase class Customer table database	??
CustomerDatabaseTest	??
Gui::Widgets::CustomerDataWidget	
Class for display info of a customer	??
CustomerModelTest	??
Gui::Widgets::WdgModels::CustomersTableModel	
For a customer table	??
Databases::Database	
The Database class Master class for all database access	??
Gui::Widgets::DatabaseSettingsWidget	
Windows of database settings	??
Exceptions::DbException	
For database exception : queries, db file,	??

Gui::Dialogs::DialogAddCustomer	
Window to add or modify a Customer	??
Utils::Directories	??
Utils::Double	
Utils functions for Double calculs	??
Gui::Widgets::Delegates::DoubleSpinBoxDelegate	
The DoubleSpinBoxDelegate class	??
FileChoseWidget	??
Exceptions::FileException	
For file/access file exception	??
Generation	??
Utils::HierarchicalSystem	
Create class which contains hierarchical system of FactDev	??
Gui::Widgets::CheckFields::ICheckField	
Interface to check fields validity	??
Gui::Utils::Image	
Contains generic methods on image formats	??
Models::IModel	
The IModel class	??
Utils::ItemType	
Item type model	??
ItemTypeTest	??
Utils::Log	
For Simple management of log	??
Gui::MainWindow	
Main Window of the software	??
Gui::Dialogs::MessageBox	
Information window with message	??
Parameters	
Class for simple user parameters	??
Mustache::PartialFileLoader	??
Mustache::PartialMap	??
Mustache::PartialResolver	??
Generator::PdfGenerator	
Generator of PDF files	??
Models::People	
People	??
Utils::pointers	
The pointers class	??
PointersTest	??
Gui::Widgets::Popup	
Class for display popup quickly	??
Models::Project	
: Project linked to a Customer	??
Gui::Widgets::Delegates::ProjectComboDelegate	
The ProjectComboDelegate class	??
Gui::Widgets::WdgModels::ProjectContributoriesTableModel	
Table model of contributories linked to projets	??
Databases::ProjectDatabase	
Project table database	??
ProjectDatabaseTest	??
ProjectModelTest	??
Gui::Widgets::WdgModels::ProjectsTableModel	
For a Project table	??
Gui::Widgets::ProjectsWidget	
Actions on Project	??
Mustache::QtVariantContext	??

Models::Rate	
Rate of a prestation	??
Databases::RateDatabase	??
RateModelTest	??
Gui::Widgets::RateWidget	
Class for display Rate	??
Mustache::Renderer	??
Models::Search	
The Search class	??
Gui::Docks::SearchDock	
Dock which contains search bar	??
searchTest	??
Gui::Widgets::searchWidget	
Class for search in database	??
Gui::Dialogs::StartedWindowsDialog	
Construct a Windows for the first begin	??
StatisticModelTest	??
Models::Statistics	??
Gui::Dialogs::StatisticsDialog	
Window to have global informations or about a customer	??
Utils::String	
The Utils class	??
StringTest	??
Mustache::Tag	??
testadder	??
TestAdder< T >	??
TestMustache	??
TestRunner	??
Generator::TexGenerator	
Generate a LaTeX file	??
Gui::Widgets::Delegates::TextareaDelegate	
The TextareaDelegate class	??
Models::Unit	
An unity for billing calculs	??
Gui::Widgets::Delegates::UnitComboDelegate	
The UnitComboDelegate class	??
Models::User	
User of it application	??
Databases::UserDatabase	
Access to User data in the the table User of the Database	??
UserDatabaseTest	??
Gui::Dialogs::UserDataDialog	
Window to fill user data	??
UserModelTest	??
Gui::Utils::WindowSettings	
Utils function on windows	??

Chapter 7

Namespace Documentation

7.1 Databases Namespace Reference

Class for [Database](#), contains queries.

Classes

- class [AccessDatabase](#)
- class [BillingDatabase](#)
*The **BillingDatabase** class Billing (or Quote) table database.*
- class [ContributoryDatabase](#)
*The **ContributoryDatabase** class Contributory (or Quote) table database.*
- class [CustomerDatabase](#)
*The **CustomerDatabase** class Customer table database.*
- class [Database](#)
*The **Database** class Master class for all database access.*
- class [ProjectDatabase](#)
*The **ProjectDatabase** class Project table database.*
- class [RateDatabase](#)
- class [UserDatabase](#)
*The **UserDatabase** class Access to User data in the the table User of the **Database***

Enumerations

- enum **DbType** { [SQLITE](#), [MYSQL](#) }

7.1.1 Detailed Description

Class for [Database](#), contains queries.

7.2 Gui Namespace Reference

Namespaces

- [Widgets](#)
Contains [Widgets](#) classes.

Classes

- class [MainWindow](#)

The [MainWindow](#) class Main Window of the software.

7.2.1 Detailed Description

Classes for Graphical User Interface

7.3 Gui::Widgets Namespace Reference

Contains [Widgets](#) classes.

Classes

- class [BrowseImageWidget](#)

The [BrowseImageWidget](#) class Widget to add a new [BrowseImageWidget](#).

- class [ComboBoxModelWidget](#)

The [ComboBoxModelWidget](#) class Model of ComboBox.

- class [ContributoriesWidget](#)

The [ContributoriesWidget](#) class Widget of Contributories.

- class [CustomerContextualMenu](#)

Display contextual menu on a customer.

- class [CustomerDataWidget](#)

Class for display info of a customer.

- class [DatabaseSettingsWidget](#)

The [DatabaseSettingsWidget](#) class Windows of database settings.

- class [Popup](#)

Class for display popup quickly.

- class [ProjectsWidget](#)

The [ProjectsWidget](#) class Actions on Project.

- class [RateWidget](#)

Class for display Rate.

- class [searchWidget](#)

Class for search in database.

7.3.1 Detailed Description

Contains [Widgets](#) classes.

7.4 Models Namespace Reference

[Models](#) classes.

Classes

- class [Billing](#)
The [Billing](#) class : [Billing](#) or Quote of a [Customer](#).
- class [Calculable](#)
The [Calculable](#) interface [Models](#) who are calculable.
- class [ContributoriesList](#)
The [ContributoriesList](#) class List of contributories.
- class [Contributory](#)
The [Unit](#) enum Unity of work : hour or day.
- class [Customer](#)
The [Customer](#) class [Customer](#).
- class [IModel](#)
The [IModel](#) class.
- class [People](#)
The [People](#) class [People](#).
- class [Project](#)
The [Project](#) class : [Project](#) linked to a [Customer](#).
- class [Rate](#)
The [Rate](#) class [Rate](#) of a prestation.
- class [Search](#)
The [Search](#) class.
- class [Statistics](#)
- class [Unit](#)
The [Unit](#) class An unity for billing calculs.
- class [User](#)
The [User](#) class [User](#) of it application.

Enumerations

- enum [TypeUnit](#) { **HOURLY**, **DAILY**, **MONTHLY** }
The [TypeUnit](#) enum Type Unit : hour or days.

7.4.1 Detailed Description

[Models](#) classes.

Chapter 8

Class Documentation

8.1 Databases::AccessDatabase Class Reference

Static Public Member Functions

- static void **init** ()
- static void **commit** ()

Static Public Attributes

- static QString **_address**
- static int **_port**
- static QString **_userDb**
- static QString **_password**
- static QString **_dbName**
- static Databases::DbType **_dbType**
- static bool **_exists**

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/database/accessdatabase.h
- /home/travis/build/FACT-Team/FactDev/src/database/accessdatabase.cpp

8.2 Gui::Dialogs::AddProjectDialog Class Reference

The [AddProjectDialog](#) class Windows to add a new Project.

```
#include <addprojectdialog.h>
```

Inheritance diagram for Gui::Dialogs::AddProjectDialog:



Public Slots

- void [checkFields](#) ()
AddProjectDialog::checkFields Check if fields are valid.

Public Member Functions

- [AddProjectDialog](#) (int idProject=0, int noRowCustomer=0, QWidget *parent=0)
AddProjectDialogAddProjectDialog Construct a windows according an idCustomer and, optionnaly, an idProject
- void [accept](#) ()
AddProjectDialog::accept Valid data inputed by user and add these data in Database.
- void [reject](#) ()
AddProjectDialog::reject Cancel the operation and close the windows.
- void [fillFields](#) ()
AddProjectDialog::fillFields Fill the differents fields of the current windows according the Project data existing As a project requires to be linked to a Customer, the Customer selection part may be disable.

8.2.1 Detailed Description

The [AddProjectDialog](#) class Windows to add a new Project.

Author

Florent Berbie

See Also

[Project](#)

8.2.2 Constructor & Destructor Documentation

8.2.2.1 [Gui::Dialogs::AddProjectDialog::AddProjectDialog](#) (int *idProject* = 0, int *noRowCustomer* = 0, QWidget * *parent* = 0) [explicit]

[AddProjectDialogAddProjectDialog](#) Construct a windows according an *idCustomer* and, optionnaly, an *idProject*

Parameters

<i>noRowCustomer</i>	Row number of the Customer
<i>idProject</i>	Project identify
<i>parent</i>	QWidget of the current windows

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/dialogs/addprojectdialog.h
- /home/travis/build/FACT-Team/FactDev/src/gui/dialogs/addprojectdialog.cpp

8.3 [Gui::Dialogs::AddQuoteDialog](#) Class Reference

The [AddQuoteDialog](#) class Window to add or modify a Quote.

```
#include <addquotedialog.h>
```

Inheritance diagram for [Gui::Dialogs::AddQuoteDialog](#):



Public Slots

- void **updateBtn** (void)
- void **changeDocType** ()

Public Member Functions

- [AddQuoteDialog](#) (bool isBilling, int idCustomer=0, int id=0, bool copy=false, QWidget *parent=0)
[AddQuoteDialog::AddQuoteDialog](#) Construct a windows [AddQuoteDialog](#).
- void [fillFields](#) ()
[AddQuoteDialog::fillFields](#) Fill line edits with the data of the quote.
- int [getNumber](#) ()
[AddQuoteDialog::getNumber](#) return the number of bill or quote.
- void [accept](#) ()
[AddQuoteDialog::accept](#) Valid data inputed by user and add these data in Database.
- bool [getCopy](#) () const
[AddQuoteDialog::getCopy](#) return if [AddQuoteDialog](#) is an add by copy of Billing/quote or if it's edition or add of Billing/quote.
- void [setCopy](#) (bool copy)
[AddQuoteDialog::setCopy](#) Change the _copy value to define if it's a copy of a Billing/quote or if it's a new Billing or a Billing edition.
- int [getIdCustomer](#) () const
[AddQuoteDialog::getIdCustomer](#) get the id of the customer changing his quote/billing.
- void [fillQuoteBilling](#) (bool isBilling)
[AddQuoteDialog::fillQuoteBilling](#) fill fields for a Billing or a quote.
- void [fillQuoteBillingCopy](#) (bool isBilling)
[AddQuoteDialog::fillQuoteBilling](#) fill fields if it's a Billing or a quote for a copy.
- void [setQuoteIdNumber](#) (int id, int idCustomer, bool isBilling)
[AddQuoteDialog::setQuoteIdNumber](#) set id and number of the _quote

8.3.1 Detailed Description

The [AddQuoteDialog](#) class Window to add or modify a Quote.

Author

8.3.2 Constructor & Destructor Documentation

- 8.3.2.1 [Gui::Dialogs::AddQuoteDialog::AddQuoteDialog](#) (bool *isBilling*, int *idCustomer* = 0, int *id* = 0, bool *copy* = false, QWidget * *parent* = 0) [explicit]

[AddQuoteDialog::AddQuoteDialog](#) Construct a windows [AddQuoteDialog](#).

Parameters

<i>isBilling</i>	displaying of a quote or a Billing
<i>idCustomer</i>	the id of the Customer
<i>id</i>	the id of the quote or the billing of the Customer's Project
<i>edit</i>	if it's an edition or a copy of a quote/Billing
<i>parent</i>	QWidget of the current windows

8.3.3 Member Function Documentation

8.3.3.1 void Gui::Dialogs::AddQuoteDialog::fillQuoteBilling (bool *isBilling*)

[AddQuoteDialog::fillQuoteBilling](#) fill fields for a Billing or a quote.

Parameters

<i>isBilling</i>	if it's a quote or a Billing
------------------	------------------------------

8.3.3.2 bool Gui::Dialogs::AddQuoteDialog::getCopy () const

[AddQuoteDialog::getCopy](#) return if [AddQuoteDialog](#) is an add by copy of Billing/quote or if it's edition or add of Billing/quote.

Returns

if it's a copy or not

8.3.3.3 int Gui::Dialogs::AddQuoteDialog::getIdCustomer () const

[AddQuoteDialog::getIdCustomer](#) get the id of the customer changing his quote/billing.

Returns

the id of the customer

8.3.3.4 int Gui::Dialogs::AddQuoteDialog::getNumber ()

[AddQuoteDialog::getNumber](#) return the number of bill or quote.

Returns

int

8.3.3.5 void Gui::Dialogs::AddQuoteDialog::setCopy (bool *copy*)

[AddQuoteDialog::setCopy](#) Change the `_copy` value to define if it's a copy of a Billing/quote or if it's a new Billing or a Billing edition.

Parameters

<i>copy</i>	
-------------	--

8.3.3.6 void Gui::Dialogs::AddQuoteDialog::setQuotedIdNumber (int *id*, int *idCustomer*, bool *isBilling*)

AddQuoteDialog::setQuotedIdNumber set id and number of the *_quote*

Parameters

<i>id</i>	the id of the Billing
<i>idCustomer</i>	the id of the customer to set the <i>number</i>
<i>isBilling</i>	if it's a quote or a Billing

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/dialogs/addquotedialog.h
- /home/travis/build/FACT-Team/FactDev/src/gui/dialogs/addquotedialog.cpp

8.4 Models::Billing Class Reference

The **Billing** class : **Billing** or Quote of a **Customer**.

```
#include <billing.h>
```

Inheritance diagram for Models::Billing:



Public Member Functions

- **Billing** ()
Billing::Billing. Construct a **Billing**.
- **Billing** (int *id*)
Billing::Billing. Construct a **Billing** or quote.
- **~Billing** ()
destruct a billing object
- void **commit** ()
Billing::commit. Insert a modification in **Billing** table on the database.
- void **hydrat** (int *getId*)
Billing::hydrat. Update of the **Billing** which is specified by *getId*
- void **remove** ()
Billing::remove. Remove a **Billing**.
- QVariantHash **getDataMap** ()
Billing::getDataMap Get all data of model with a HashMap key/value.
- double **getPrice** (bool *paied*=false)
getPrice Return the price of a calculable object
- double **getSumQuantity** ()
ContributoriesList::getSumQuantity Return the sum of quantity (number of days) of the Contributories.
- void **generateTex** ()

- Billing::generateTex* Generate a .tex file for the billing.
- void **generatePdf** ()
 - Billing::generatePdf* Generate a .pdf file for the billing.
- QString **getPath** ()
 - Billing::getPath* Return the path of billing filename (without extension)
- QString **getFolder** ()
 - Billing::getFolder* Return the directory of billing.
- QString **getFilename** ()
 - Billing::getFilename* Return the filename of billing (without extension)
- **ContributoriesList** & **getContributories** ()
 - Billing::getContributories.* Return a map of **Contributory** for each **Project** of the **Billing**
- void **addContributory** (**Contributory** &c)
 - Billing::addContributories* Add a new contributory for project p.
- QString **getTitle** () const
 - Billing::getTitle.* return title of **Billing**
- void **setTitle** (const QString &**getTitle**)
 - Billing::setTitle.* Modify the title of **Billing**
- QString **getDescription** () const
 - Billing::getDescription.* return description of **Billing**
- void **setDescription** (const QString &**getDescription**)
 - Billing::setDescription.* Modify the description of **Billing**
- int **getNumber** () const
 - Billing::getNumber.* Return number of the **Billing**.
- void **setNumber** (int **getNumber**)
 - Billing::setNumber.* Modify _number of **Billing**.
- bool **isBilling** () const
 - Billing::isBilling.* Return if it's a billing or a quote.
- void **setIsBilling** (bool **isBilling**)
 - Billing::setIsBilling.* Modify isBilling of **Billing**.
- QDate **getDate** () const
 - Billing::getDate.* return date of the **Billing**
- void **setDate** (const QDate &**getDate**)
 - Billing::setDate.* Modify date of the **Billing**
- bool **isPaid** () const
 - Billing::isPaid* Return TRUE if thee current billing is paid else return FALSE.
- void **setIsPaid** (bool **isPaid**)
 - Billing::setIsPaid* Define the current billing according the argument isPaid
- bool **operator==** (const **Billing** &b)
 - Billing::operator ==* define the operator "==" to compare two billings and to see if they are the same.
- bool **operator!=** (const **Billing** &b)
 - Billing::operator !=* defines the operator "!=" to compare two **Billing** and to see if they are different.
- void **setContributories** (const **ContributoriesList** &contributories)
- bool **operator<** (const **Billing** &b) const
 - Billing::operator <* defines the operator "<" to compare two **Billing** and to see if the first is anterior to the second.
- QStandardItem * **getItem** ()
 - Billing::getItem* Return the bill/quote item.

Additional Inherited Members

8.4.1 Detailed Description

The [Billing](#) class : [Billing](#) or Quote of a [Customer](#).

Author

Antoine de Roquemaurel
Florent Berbie

8.4.2 Constructor & Destructor Documentation

8.4.2.1 Models::Billing::Billing (int *id*)

[Billing::Billing](#). Construct a [Billing](#) or quote.

Parameters

<i>int</i>	id
------------	----

8.4.3 Member Function Documentation

8.4.3.1 void Models::Billing::addContributory (Contributory & *c*)

[Billing::addContributories](#) Add a new contributory for project p.

Parameters

<i>p</i>	The Project who contain Contributory
<i>c</i>	The new Contributory

8.4.3.2 ContributoriesList & Models::Billing::getContributories ()

[Billing::getContributories](#). Return a map of [Contributory](#) for each [Project](#) of the [Billing](#)

Returns

QMap<[Project](#), QList<Contributory>>

8.4.3.3 QVariantHash Models::Billing::getDataMap () [virtual]

[Billing::getDataMap](#) Get all data of model with a HashMap key/value.

Returns

Model's data

Implements [Models::IModel](#).

8.4.3.4 QDate Models::Billing::getDate () const

[Billing::getDate](#). return date of the [Billing](#)

Returns

date of [Billing](#)

8.4.3.5 QString Models::Billing::getDescription () const

[Billing::getDescription](#). return description of [Billing](#)

Returns

description of [Billing](#)

8.4.3.6 QString Models::Billing::getFilename ()

[Billing::getFilename](#) Return the filename of billing (without extension)

Returns

Filename of Billing

8.4.3.7 QString Models::Billing::getFolder ()

[Billing::getFolder](#) Return the directory of billing.

Returns

[Billing](#) directory

8.4.3.8 QList<QStandardItem> * Models::Billing::getItem ()

[Billing::getItem](#) Return the bill/quote item.

Returns

QStandardItem an item for QTree (level/depth 3)

8.4.3.9 int Models::Billing::getNumber () const

[Billing::getNumber](#). Return number of the [Billing](#).

Returns

_number of [Billing](#)

8.4.3.10 QString Models::Billing::getPath ()

[Billing::getPath](#) Return the path of billing filename (without extension)

Returns

billing path

8.4.3.11 `double Models::Billing::getPrice (bool paied = false) [virtual]`

`getPrice` Return the price of a calculable object

Returns

The price

Implements [Models::Calculable](#).

8.4.3.12 `double Models::Billing::getSumQuantity () [virtual]`

[ContributoriesList::getSumQuantity](#) Return the sum of quantity (number of days) of the Contributories.

Returns

sum of quantity in days

Implements [Models::Calculable](#).

8.4.3.13 `QString Models::Billing::getTitle () const`

[Billing::getTitle](#). return title of [Billing](#)

Returns

title of [Billing](#)

8.4.3.14 `void Models::Billing::hydrat (int getId) [virtual]`

[Billing::hydrat](#). Update of the [Billing](#) which is specified by *getId*

Parameters

<i>getId</i>	
--------------	--

Implements [Models::IModel](#).

8.4.3.15 `bool Models::Billing::isBilling () const`

[Billing::isBilling](#). Return if it's a billing or a quote.

Returns

if it's billing or a quote

8.4.3.16 `bool Models::Billing::isPaid () const`

[Billing::isPaid](#) Return TRUE if thee current billing is paid else return FALSE.

Returns

Boolean

8.4.3.17 `bool Models::Billing::operator!= (const Billing & b)`

[Billing::operator !=](#) defines the operator "!=" to compare two [Billing](#) and to see if they are different.

Parameters

<i>b</i>	the Billing to compare with the current Billing
----------	---

Returns

true if the **Billing** are different else false

8.4.3.18 bool Models::Billing::operator< (const **Billing** & *b*) const

Billing::operator < defines the operator "<" to compare two **Billing** and to see if the first is anterior to the second.

Parameters

<i>b</i>	the Billing to compare with the current Billing
----------	---

Returns

true if the **Billing** are different else false

8.4.3.19 bool Models::Billing::operator== (const **Billing** & *b*)

Billing::operator == define the operator "==" to compare two billings and to see if they are the same.

Parameters

<i>b</i>	the Billing to compare with the current Billing
----------	---

Returns

true if they are the same billings else false

8.4.3.20 void Models::Billing::setDate (const QDate & *getDate*)

Billing::setDate. Modify *date* of the **Billing**

Parameters

<i>getDate</i>	the new date of the Billing
----------------	------------------------------------

8.4.3.21 void Models::Billing::setDescription (const QString & *getDescription*)

Billing::setDescription. Modify the description of **Billing**

Parameters

<i>getDescription</i>	Modify the description with <i>getDescription</i>
-----------------------	---

8.4.3.22 void Models::Billing::setIsBilling (bool *isBilling*)

Billing::setIsBilling. Modify *isBilling* of **Billing**.

Parameters

<i>isBilling</i>	
------------------	--

8.4.3.23 void Models::Billing::setIsPaid (bool *isPaid*)

[Billing::setIsPaid](#) Define the current billing according the argument *isPaid*

Parameters

<i>isPaid</i>	Boolean
---------------	---------

8.4.3.24 void Models::Billing::setNumber (int *getNumber*)

[Billing::setNumber](#). Modify *_number* of [Billing](#).

Parameters

<i>getNumber</i>	the new number of the Billing
------------------	---

8.4.3.25 void Models::Billing::setTitle (const QString & *getTitle*)

[Billing::setTitle](#). Modify the title of [Billing](#)

Parameters

<i>getTitle</i>	Modify the title with <i>getTitle</i>
-----------------	---------------------------------------

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/models/billing.h
- /home/travis/build/FACT-Team/FactDev/src/models/billing.cpp

8.5 Databases::BillingDatabase Class Reference

The [BillingDatabase](#) class Billing (or Quote) table database.

```
#include <billingdatabase.h>
```

Inheritance diagram for Databases::BillingDatabase:



Public Member Functions

- [Models::Billing * getBilling](#) (const int pld)
[BillingDatabase::getBilling](#) get informations about the billing identified by pld
- [WdgModels::BillingsTableModel * getBillingsTable](#) (const int idProject) throw (DbException*)
[BillingDatabase::getBillingsTable](#) Return an item model of billings for QTableView.
- int [addBilling](#) (const [Models::Billing](#) &)

- BillingDatabase::addBilling* Add the billing pBilling to the database.
- void **updateBilling** (const **Models::Billing** &)

BillingDatabase::updateCustomer Update informations about the billing pCustomer
- void **removeBilling** (const int pld)

BillingDatabase::removeCustomer Remove the billing with the id pld
- void **addBillingProject** (const int idProject, const int idBilling, const int idContributory)

BillingDatabase::addBillingProject Link a project, a billing and a contributory in the table BillingProject.
- bool **isBillingPaid** (const int pld)

BillingDatabase::isBillingPaid Return TRUE if the id pld correspond to a Billing and not quote (isBilling = 1) and if this billing is paid (isPaid = 1) else return FALSE.
- void **removeBillingProject** (const int idProject, const int idBilling, const int idContributory)

BillingDatabase::removeBillingProject remove a link between a project, a billing and a contributory in the table Billing-Project.
- int **getMaxBillingNumber** ()

getMaxBillingNumber Get the last number of a billing
- int **getMaxQuoteNumber** ()

getMaxQuoteNumber Get the last number of a quote
- int **getMaxBillingNumberOfCustomer** (const int idCustomer)

BillingDatabase::getMaxBillingNumberOfCustomer Get the last number of a **Customer's** Billing.
- int **getMaxQuoteNumberOfCustomer** (const int idCustomer)

BillingDatabase::getMaxQuoteNumberOfCustomer Get the last number of a **Customer's** quote.
- QSharedPointer< **Models::Billing** > **getBilling** (QStringQuery &q)

BillingDatabase::getBilling Add the element of the q request and return their.
- QMap< **Project** *, **Billing** * > **getAllBillingsOfProject** ()

BillingDatabase::getAllBillingsOfProject Return a map with the project id as key linked to the billing.
- QList< **Billing** > **getBillsBetweenDates** (QDate begin, QDate end)

Get the bills between begin and end dates.
- QList< **Billing** > **getBills** (const int projectId=0)

Get the bills.
- QList< **Billing** > **getBillsPaid** (const int projectId=0)

Get the bills paid.
- int **getNbBills** (const int customerId=0)

Get the number of bills.
- int **getNbBillsPaid** (const int customerId=0)

Get the number of bills paid.
- int **getNbQuotes** (const int customerId=0)

Get the number of quotes.
- int **getNbDocs** (const int customerId=0)

Get the number of documents.

Static Public Member Functions

- static **BillingDatabase** * **instance** () throw (DbException*)

BillingDatabase::getInstance Return an instance of **BillingDatabase**

Additional Inherited Members

8.5.1 Detailed Description

The [BillingDatabase](#) class Billing (or Quote) table database.

Author

See Also

[Database](#)
Billing/Quote

8.5.2 Member Function Documentation

8.5.2.1 `int Databases::BillingDatabase::addBilling (const Models::Billing & pBilling)`

[BillingDatabase::addBilling](#) Add the billing *pBilling* to the database.

Returns

billing id

8.5.2.2 `void Databases::BillingDatabase::addBillingProject (const int idProject, const int idBilling, const int idContributory)`

[BillingDatabase::addBillingProject](#) Link a project, a billing and a contributory in the table BillingProject.

Parameters

<i>idProject</i>	Project id
<i>idBilling</i>	Billing id
<i>idContributory</i>	Contributory id

8.5.2.3 `QMap< Project *, Billing * > Databases::BillingDatabase::getAllBillingsOfProject ()`

[BillingDatabase::getAllBillingsOfProject](#) Return a map with the project id as key linked to the billing.

Returns

Map with projects and Billing

8.5.2.4 `Models::Billing * Databases::BillingDatabase::getBilling (const int pId)`

[BillingDatabase::getBilling](#) get informations about the billing identified by *pId*

Parameters

<i>pId</i>	billing id
------------	------------

Returns

the Billing

8.5.2.5 QSharedPointer< Billing > Databases::BillingDatabase::getBilling (QSqlQuery & *q*)

[BillingDatabase::getBilling](#) Add the element of the *q* request and return their.

Parameters

<i>q</i>	SQL request
----------	-------------

Returns

a billing formed according to QSharedPointer

8.5.2.6 `WdgModels::BillingsTableModel * Databases::BillingDatabase::getBillingsTable (const int idProject) throw DbException *`

[BillingDatabase::getBillingsTable](#) Return an item model of billings for QTableView.

Parameters

<i>pld</i>	the project id of the billings returned
------------	---

Exceptions

<i>DbException</i>	
--------------------	--

Returns

QStandardItemModel an item model for QTableView

8.5.2.7 `QList< Billing > Databases::BillingDatabase::getBills (const int projectId = 0)`

Get the bills.

Parameters

<i>projectId</i>	Get the specified project bills
------------------	---------------------------------

Returns

The list of bills

8.5.2.8 `QList< Billing > Databases::BillingDatabase::getBillsBetweenDates (QDate begin, QDate end)`

Get the bills between *begin* and *end* dates.

Parameters

<i>begin</i>	
<i>end</i>	

Returns

the list of **Bills**

8.5.2.9 `QList< Billing > Databases::BillingDatabase::getBillsPaid (const int projectId = 0)`

Get the bills paid.

Parameters

<i>projectId</i>	Get the specified project bills paid
------------------	--------------------------------------

Returns

The list of bills paid

8.5.2.10 `int Databases::BillingDatabase::getMaxBillingNumber ()`

`getMaxBillingNumber` Get the last number of a billing

Returns

The max number

8.5.2.11 `int Databases::BillingDatabase::getMaxBillingNumberOfCustomer (const int idCustomer)`

[BillingDatabase::getMaxBillingNumberOfCustomer](#) Get the last number of a **Customer's** Billing.

Parameters

<i>idCustomer</i>	Customer id
-------------------	-------------

Returns

the last number of the **Customer's** Billing

8.5.2.12 `int Databases::BillingDatabase::getMaxQuoteNumber ()`

`getMaxQuoteNumber` Get the last number of a quote

Returns

The last number

8.5.2.13 `int Databases::BillingDatabase::getMaxQuoteNumberOfCustomer (const int idCustomer)`

[BillingDatabase::getMaxQuoteNumberOfCustomer](#) Get the last number of a **Customer's** quote.

Parameters

<i>idCustomer</i>	Customer id
-------------------	-------------

Returns

the last number of the **Customer's** quote

8.5.2.14 `int Databases::BillingDatabase::getNbBills (const int customerId = 0)`

Get the number of bills.

Parameters

<i>customerId</i>	If customerId isn't specified or if it's not valid, get all bills else get the specified customer bills
-------------------	---

Returns

Number of bills in the database for all or for a customer

8.5.2.15 `int Databases::BillingDatabase::getNbBillsPaid (const int customerId = 0)`

Get the number of bills paid.

Parameters

<i>customerId</i>	If customerId isn't specified if it's not valid, get all bills paid else get the specified customer bills paid
-------------------	--

Returns

Number of bills paid in the database for all or for a customer

8.5.2.16 `int Databases::BillingDatabase::getNbDocs (const int customerId = 0)`

Get the number of documents.

Parameters

<i>customerId</i>	If customerId isn't specified or if it's not valid, get all documents else get the specified customer documents
-------------------	---

Returns

Number of quotes in the database for all or for a customer

8.5.2.17 `int Databases::BillingDatabase::getNbQuotes (const int customerId = 0)`

Get the number of quotes.

Parameters

<i>customerId</i>	If customerId isn't specified or if it's not valid, get all quotes else get the specified customer quotes
-------------------	---

Returns

Number of quotes in the database for all or for a customer

8.5.2.18 `BillingDatabase * Databases::BillingDatabase::instance () throw DbException *` [static]

BillingDatabase::getInstance Return an instance of [BillingDatabase](#)

See Also

[DbException](#)

Returns

Instance of [BillingDatabase](#)

8.5.2.19 `bool Databases::BillingDatabase::isBillingPaid (const int pId)`

[BillingDatabase::isBillingPaid](#) Return TRUE if the id *pId* correspond to a Billing and not quote (isBilling = 1) and if this billing is paid (isPaid = 1) else return FALSE.

Parameters

<i>pld</i>	Billing id
------------	------------

Returns

TRUE if billing is paid

8.5.2.20 void Databases::BillingDatabase::removeBilling (const int *pld*)

BillingDatabase::removeCustomer Remove the billing with the id *pld*

Parameters

<i>pld</i>	billing id
------------	------------

8.5.2.21 void Databases::BillingDatabase::removeBillingProject (const int *idProject*, const int *idBilling*, const int *idContributory*)

[BillingDatabase::removeBillingProject](#) remove a link between a project, a billing and a contributory in the table BillingProject.

Parameters

<i>idProject</i>	Project id
<i>idBilling</i>	Billing id
<i>idContributory</i>	Contributory id

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/database/billingdatabase.h
- /home/travis/build/FACT-Team/FactDev/src/database/billingdatabase.cpp

8.6 BillingDatabaseTest Class Reference

Inheritance diagram for BillingDatabaseTest:



The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/tests/database/billingdatabasetest.h
- /home/travis/build/FACT-Team/FactDev/tests/database/billingdatabasetest.cpp

8.7 BillingModelTest Class Reference

Inheritance diagram for BillingModelTest:



The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/tests/models/billingmodeltest.h
- /home/travis/build/FACT-Team/FactDev/tests/models/billingmodeltest.cpp

8.8 Gui::Widgets::WdgModels::BillingsTableModel Class Reference

The [BillingsTableModel](#) class for a Billing table.

```
#include <billingstablemodel.h>
```

Inheritance diagram for Gui::Widgets::WdgModels::BillingsTableModel:



Public Member Functions

- [BillingsTableModel](#) ()
BillingsTableModel::BillingsTableModel Construct a *BillingsTableModel*.
- int [rowCount](#) (const QModelIndex &) const
BillingsTableModel::rowCount Number of billings row.
- int [columnCount](#) (const QModelIndex &) const
BillingsTableModel::columnCount Number of column of a Billing.
- QVariant [data](#) (const QModelIndex &index, int role=Qt::DisplayRole) const
BillingsTableModel::data Obtains data of a specify cell.
- QVariant [headerData](#) (int section, Qt::Orientation orientation, int role=Qt::DisplayRole) const
BillingsTableModel::headerData Obtains header title of table.
- bool [setData](#) (const QModelIndex &index, const QVariant &value, int role=Qt::EditRole)
BillingsTableModel::setData Change data of a cell.
- void [append](#) (const [Billing](#) &billing)
BillingsTableModel::append Add a new line in table.
- void [remove](#) (const int i)
BillingsTableModel::remove Remove a line.
- Qt::ItemFlags [flags](#) (const QModelIndex &index) const
BillingsTableModel::flags Differents table flags.
- int [count](#) ()
BillingsTableModel::count Number of billings in table.
- QList< [Billing](#) > [getBillings](#) () const
BillingsTableModel::getbillings Return the list of billings.

8.8.1 Detailed Description

The [BillingsTableModel](#) class for a Billing table.

Author

Florent Berbie

See Also

[Billing](#)

8.8.2 Constructor & Destructor Documentation

8.8.2.1 Gui::Widgets::WdgModels::BillingsTableModel::BillingsTableModel ()

[BillingsTableModel::BillingsTableModel](#) Construct a [BillingsTableModel](#).

Parameters

<i>parent</i>	Parent widget
---------------	---------------

8.8.3 Member Function Documentation

8.8.3.1 void Gui::Widgets::WdgModels::BillingsTableModel::append (const Billing & *billing*)

[BillingsTableModel::append](#) Add a new line in table.

Parameters

<i>Billing</i>	The new Billing
----------------	-----------------

8.8.3.2 int Gui::Widgets::WdgModels::BillingsTableModel::columnCount (const QModelIndex &) const

[BillingsTableModel::columnCount](#) Number of column of a Billing.

Returns

The number of column

8.8.3.3 int Gui::Widgets::WdgModels::BillingsTableModel::count ()

[BillingsTableModel::count](#) Number of billings in table.

Returns

The number of billings

8.8.3.4 QVariant Gui::Widgets::WdgModels::BillingsTableModel::data (const QModelIndex & *index*, int *role* = Qt::DisplayRole) const

[BillingsTableModel::data](#) Obtains data of a specify cell.

Parameters

<i>index</i>	The cell who we want data
<i>role</i>	The role of set

Returns

The data of cell

8.8.3.5 `Qt::ItemFlags Gui::Widgets::WdgModels::BillingsTableModel::flags (const QModelIndex & index) const`

[BillingsTableModel::flags](#) Differents table flags.

Parameters

<i>index</i>	The cell who we want to know flags
--------------	------------------------------------

Returns

Flags

8.8.3.6 `QList< Billing > Gui::Widgets::WdgModels::BillingsTableModel::getBillings () const`

[BillingsTableModel::getbillings](#) Return the list of billings.

Returns

list of billings

8.8.3.7 `QVariant Gui::Widgets::WdgModels::BillingsTableModel::headerData (int section, Qt::Orientation orientation, int role = Qt::DisplayRole) const`

[BillingsTableModel::headerData](#) Obtains header title of table.

Parameters

<i>section</i>	The number of column
<i>orientation</i>	The table orientation
<i>role</i>	

Returns

The Title header of column

8.8.3.8 `void Gui::Widgets::WdgModels::BillingsTableModel::remove (const int i)`

[BillingsTableModel::remove](#) Remove a line.

Parameters

<i>i</i>	The number of line to remove
----------	------------------------------

8.8.3.9 `int Gui::Widgets::WdgModels::BillingsTableModel::rowCount (const QModelIndex &) const`

[BillingsTableModel::rowCount](#) Number of billings row.

Returns

The number of billings

8.8.3.10 `bool Gui::Widgets::WdgModels::BillingsTableModel::setData (const QModelIndex & index, const QVariant & value, int role = Qt::EditRole)`

[BillingsTableModel::setData](#) Change data of a cell.

Parameters

<i>index</i>	The cell to change data
<i>value</i>	The new value
<i>role</i>	The role of cell

Returns

True if we could edit

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/widgetmodels/billingstablemodel.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/widgetmodels/billingstablemodel.cpp

8.9 Gui::Widgets::BrowseImageWidget Class Reference

The [BrowseImageWidget](#) class Widget to add a new [BrowseImageWidget](#).

```
#include <browseimagewidget.h>
```

Inheritance diagram for Gui::Widgets::BrowseImageWidget:



Public Slots

- void [browseImagePath](#) ()
[BrowseImageWidget::browseImagePath\(\)](#) Open a new window to define the workspace path of the user.

Public Member Functions

- [BrowseImageWidget](#) (QWidget *parent=0)
[BrowseImageWidget::BrowseImageWidget](#) Construct a [BrowseImageWidget](#).
- void [setImageScaled](#) (QString path, int width=128, int height=128)
*[BrowseImageWidget::getImageScaled](#) Modify the current image to a scaled image from the icon specified by it path. The image has a resolution of width*height (default 128*128)*

- QPixmap * [getImage](#) ()
BrowseImageWidget::getIcon Return the icon selected.
- void [setImage](#) (QPixmap *img)
BrowseImageWidget::setImage Change the current image by the new *img*
- QString [getExtension](#) () const
BrowseImageWidgetextension::getExtension Return extension of the image file.

8.9.1 Detailed Description

The [BrowseImageWidget](#) class Widget to add a new [BrowseImageWidget](#).

Author

Florent Berbie

8.9.2 Constructor & Destructor Documentation

8.9.2.1 [Gui::Widgets::BrowseImageWidget::BrowseImageWidget \(QWidget * parent = 0 \)](#) [explicit]

[BrowseImageWidget::BrowseImageWidget](#) Cosntruct a [BrowseImageWidget](#).

Parameters

<i>parent</i>	QWidget parent
---------------	----------------

8.9.3 Member Function Documentation

8.9.3.1 [QString Gui::Widgets::BrowseImageWidget::getExtension \(\)](#) const

[BrowseImageWidgetextension::getExtension](#) Return extension of the image file.

Returns

Extension of image file

8.9.3.2 [QPixmap * Gui::Widgets::BrowseImageWidget::getImage \(\)](#)

[BrowseImageWidget::getIcon](#) Return the icon selected.

Returns

image

8.9.3.3 [void Gui::Widgets::BrowseImageWidget::setImage \(QPixmap * img \)](#)

[BrowseImageWidget::setImage](#) Change the current image by the new *img*

Parameters

<i>img</i>	New image
------------	-----------

8.9.3.4 [void Gui::Widgets::BrowseImageWidget::setImageScaled \(QString path, int width = 128, int height = 128 \)](#)

[BrowseImageWidget::getImageScaled](#) Modify the current image to a scaled image from the icon specified by it *path*. The image has a resolution of *width*height* (default 128*128)

Parameters

<i>path</i>	Icon path
<i>width</i>	Icon width
<i>height</i>	Icon height

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/browseimagewidget.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/browseimagewidget.cpp

8.10 Models::Calculable Class Reference

The [Calculable](#) interface [Models](#) who are calculable.

```
#include <calculable.h>
```

Inheritance diagram for Models::Calculable:



Public Member Functions

- virtual double [getPrice](#) (bool *paied*=false)=0
getPrice Return the price of a calculable object
- virtual double [getSumQuantity](#) ()=0
[ContributoriesList::getSumQuantity](#) Return the sum of quantity (number of days) of the Contributories.

8.10.1 Detailed Description

The [Calculable](#) interface [Models](#) who are calculable.

8.10.2 Member Function Documentation

8.10.2.1 virtual double Models::Calculable::getPrice (bool *paied* = false) [pure virtual]

getPrice Return the price of a calculable object

Returns

The price

Implemented in [Models::Billing](#), [Models::Contributory](#), and [Models::ContributoriesList](#).

8.10.2.2 virtual double Models::Calculable::getSumQuantity () [pure virtual]

[ContributoriesList::getSumQuantity](#) Return the sum of quantity (number of days) of the Contributories.

Returns

sum of quantity in days

Implemented in [Models::Billing](#), [Models::Contributory](#), and [Models::ContributoriesList](#).

The documentation for this class was generated from the following file:

- `/home/travis/build/FACT-Team/FactDev/src/models/calculable.h`

8.11 Gui::Widgets::CheckFields::CheckCity Class Reference

The [CheckCity](#) class Line Edit of City with a check icon.

```
#include <checkcity.h>
```

Inheritance diagram for Gui::Widgets::CheckFields::CheckCity:

**Public Member Functions**

- [CheckCity](#) (QWidget *w=0, QPushButton *btn=0)
[CheckCity::CheckCity](#) Construct a [CheckCity](#).

Additional Inherited Members

8.11.1 Detailed Description

The [CheckCity](#) class Line Edit of City with a check icon.

8.11.2 Constructor & Destructor Documentation

8.11.2.1 Gui::Widgets::CheckFields::CheckCity::CheckCity (QWidget * w = 0, QPushButton * btn = 0)

[CheckCity::CheckCity](#) Construct a [CheckCity](#).

Parameters

<i>w</i>	QWidget linked to CheckCity
----------	---

The documentation for this class was generated from the following files:

- `/home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkcity.h`
- `/home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkcity.cpp`

8.12 Gui::Widgets::CheckFields::CheckCountry Class Reference

[CheckCountry::CheckCountry](#) Line Edit of country with a check icon.

```
#include <checkcountry.h>
```

Inheritance diagram for Gui::Widgets::CheckFields::CheckCountry:



Public Member Functions

- [CheckCountry](#) (QWidget *w=0, QPushButton *btn=0)
[CheckCountry::CheckCountry](#) Construct a [CheckCountry](#).

Additional Inherited Members

8.12.1 Detailed Description

[CheckCountry::CheckCountry](#) Line Edit of country with a check icon.

8.12.2 Constructor & Destructor Documentation

8.12.2.1 [Gui::Widgets::CheckFields::CheckCountry::CheckCountry](#) ([QWidget](#) * *w* = 0, [QPushButton](#) * *btn* = 0)

[CheckCountry::CheckCountry](#) Construct a [CheckCountry](#).

Parameters

<i>w</i>	QWidget linked to CheckCountry
----------	--

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkcountry.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkcountry.cpp

8.13 Gui::Widgets::CheckFields::CheckEmail Class Reference

The [CheckEmail](#) class Line Edit of email with a check icon.

```
#include <checkemail.h>
```

Inheritance diagram for Gui::Widgets::CheckFields::CheckEmail:



Public Member Functions

- [CheckEmail](#) (QWidget *w=0, QPushButton *btn=0)
[CheckEmail::CheckEmail](#) Construct a CheckMail.
- bool [check](#) (const QString text)
[CheckEmail::check](#) Check if the field email is valid. To be valid, an email address should be under this form: *me@me. - xx* An email address need:

Additional Inherited Members

8.13.1 Detailed Description

The [CheckEmail](#) class Line Edit of email with a check icon.

8.13.2 Constructor & Destructor Documentation

8.13.2.1 [Gui::Widgets::CheckFields::CheckEmail::CheckEmail](#) ([QWidget](#) * *w* = 0, [QPushButton](#) * *btn* = 0)

[CheckEmail::CheckEmail](#) Construct a CheckMail.

Parameters

<i>w</i>	QWidget linked to CheckEmail
----------	--

8.13.3 Member Function Documentation

8.13.3.1 bool [Gui::Widgets::CheckFields::CheckEmail::check](#) (const [QString](#) *text*) [virtual]

[CheckEmail::check](#) Check if the field email is valid. To be valid, an email address should be under this form: *me@me. xx* An email address need:

- 1 character [A-Z] or [a-z] minimum before the character *</i>*
- the character '@'
- 1 character [A-Z] or [a-z] after the character *</i>* minimum and before the character .
- 1 character [A-Z] or [a-z] minimum afer the character . Return TRUE if email address is valid, else FALSE

Parameters

<i>text</i>	<i>Text to check</i>
-------------	----------------------

Returns

boolean Validity of the text

Implements [Gui::Widgets::CheckFields::ICheckField](#).

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkemail.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkemail.cpp

8.14 Gui::Widgets::CheckFields::CheckFieldsLetters Class Reference

The [CheckFieldsLetters](#) class Field with only letters (no numbers)

```
#include <checkfieldsletters.h>
```

Inheritance diagram for Gui::Widgets::CheckFields::CheckFieldsLetters:



Public Member Functions

- [CheckFieldsLetters](#) (QWidget *w=0, QPushButton *btn=0)
CheckFieldsLetters::CheckFieldsLetters Construct a [CheckFieldsLetters](#).
- bool [check](#) (QString text)
CheckFieldsLetters::check Check if the field contains only letters.

Additional Inherited Members

8.14.1 Detailed Description

The [CheckFieldsLetters](#) class Field with only letters (no numbers)

8.14.2 Constructor & Destructor Documentation

8.14.2.1 Gui::Widgets::CheckFields::CheckFieldsLetters::CheckFieldsLetters (QWidget * w = 0, QPushButton * btn = 0)

[CheckFieldsLetters::CheckFieldsLetters](#) Construct a [CheckFieldsLetters](#).

Parameters

<i>w</i>	QWidget linked to CheckFieldsLetters
----------	--

8.14.3 Member Function Documentation

8.14.3.1 `bool Gui::Widgets::CheckFields::CheckFieldsLetters::check (QString text)` `[virtual]`

[CheckFieldsLetters::check](#) Check if the field contains only letters.

Parameters

<i>text</i>	Text to check
-------------	---------------

Returns

boolean Validity of the text

Implements [Gui::Widgets::CheckFields::ICheckField](#).

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkfieldsletters.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkfieldsletters.cpp

8.15 Gui::Widgets::CheckFields::CheckFieldsNumbers Class Reference

The [CheckFieldsNumbers](#) class Line Edit of number with a check icon.

```
#include <checkfieldsnumbers.h>
```

Inheritance diagram for Gui::Widgets::CheckFields::CheckFieldsNumbers:



Public Member Functions

- [CheckFieldsNumbers](#) (QWidget *w=0, QPushButton *btn=0)
CheckFieldsNumbers::CheckFieldsNumbers Construct a *CheckFieldsNumbers*.
- bool [check](#) (QString text)
CheckFieldsNumbers::check Check if the field contains only numbers.

Additional Inherited Members

8.15.1 Detailed Description

The [CheckFieldsNumbers](#) class Line Edit of number with a check icon.

Author

Florent BERBIE

See Also

[CheckQLineEdit](#)
[CheckUntilField](#)

8.15.2 Constructor & Destructor Documentation

8.15.2.1 `Gui::Widgets::CheckFields::CheckFieldsNumbers::CheckFieldsNumbers (QWidget * w = 0, QPushButton * btn = 0)`

[CheckFieldsNumbers::CheckFieldsNumbers](#) Construct a [CheckFieldsNumbers](#).

Parameters

<i>w</i>	QWidget linked to CheckFieldsNumbers
----------	--

8.15.3 Member Function Documentation

8.15.3.1 bool Gui::Widgets::CheckFields::CheckFieldsNumbers::check (QString *text*) [virtual]

[CheckFieldsNumbers::check](#) Check if the field contains only numbers.

Parameters

<i>text</i>	Text to check
-------------	---------------

Returns

boolean Validity of the text

Implements [Gui::Widgets::CheckFields::ICheckField](#).

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkfieldsnumbers.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkfieldsnumbers.cpp

8.16 Gui::Widgets::CheckFields::CheckIpAddress Class Reference

The [CheckIpAddress](#) class Line Edit of IP address with a check icon.

```
#include <checkipaddress.h>
```

Inheritance diagram for Gui::Widgets::CheckFields::CheckIpAddress:



Public Member Functions

- [CheckIpAddress](#) (QWidget *w=0, QPushButton *btn=0)
[CheckIpAddress::CheckIpAddress](#) Construct a [CheckIpAddress](#).
- bool [check](#) (QString *text*)
[CheckIpAddress::check](#) Check if the field contains an IP address or domain name valid.

Additional Inherited Members

8.16.1 Detailed Description

The [CheckIpAddress](#) class Line Edit of IP address with a check icon.

Author

Florent BERBIE

See Also

[CheckQLineEdit](#)
[CheckUntilField](#)

8.16.2 Constructor & Destructor Documentation

8.16.2.1 `Gui::Widgets::CheckFields::CheckIpAddress::CheckIpAddress (QWidget * w = 0, QPushButton * btn = 0)`[CheckIpAddress::CheckIpAddress](#) Construct a [CheckIpAddress](#).

Parameters

<i>w</i>	QWidget linked to CheckIpAddress
----------	--

8.16.3 Member Function Documentation

8.16.3.1 `bool Gui::Widgets::CheckFields::CheckIpAddress::check (QString text) [virtual]`[CheckIpAddress::check](#) Check if the field contains an IP address or domain name valid.

Parameters

<i>text</i>	Text to check
-------------	---------------

Returns

boolean Validity of the text

Implements [Gui::Widgets::CheckFields::ICheckField](#).

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkipaddress.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkipaddress.cpp

8.17 Gui::Widgets::CheckFields::CheckLogin Class Reference

The [CheckLogin](#) class Line Edit of login with a check icon.

#include <checklogin.h>

Inheritance diagram for Gui::Widgets::CheckFields::CheckLogin:



Public Slots

- void [passwordPreviousInputed](#) (const QString &text)
[CheckLogin::fieldTextChanged](#) For each new characater inputed or removed, displays an icon to show if the field is valid or not.

Public Member Functions

- [CheckLogin](#) (QWidget *w=0, QPushButton *btn=0)
[CheckLogin::CheckLogin](#) Construct a [CheckLogin](#).
- bool [check](#) (QString text)
[CheckLogin::check](#) Check if the field contains only numbers.

8.17.1 Detailed Description

The [CheckLogin](#) class Line Edit of login with a check icon.

Author

Florent BERBIE

See Also

[CheckQLineEdit](#)
[CheckUntilField](#)

8.17.2 Constructor & Destructor Documentation

8.17.2.1 [Gui::Widgets::CheckFields::CheckLogin::CheckLogin](#) ([QWidget](#) * *w* = 0, [QPushButton](#) * *btn* = 0)

[CheckLogin::CheckLogin](#) Construct a [CheckLogin](#).

Parameters

<i>w</i>	QWidget linked to CheckIpAddress
----------	--

8.17.3 Member Function Documentation

8.17.3.1 bool [Gui::Widgets::CheckFields::CheckLogin::check](#) ([QString](#) *text*) [virtual]

[CheckLogin::check](#) Check if the field contains only numbers.

Parameters

<i>text</i>	Text to check
-------------	---------------

Returns

boolean Validity of the text

Implements [Gui::Widgets::CheckFields::ICheckField](#).

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checklogin.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checklogin.cpp

8.18 Gui::Widgets::CheckFields::CheckName Class Reference

The [CheckName](#) class Line edit of name with a check icon.

```
#include <checkname.h>
```

Inheritance diagram for Gui::Widgets::CheckFields::CheckName:



Public Member Functions

- [CheckName](#) (QWidget *w=0, QPushButton *btn=0)
CheckName::CheckName Construct a [CheckName](#).

Additional Inherited Members

8.18.1 Detailed Description

The [CheckName](#) class Line edit of name with a check icon.

8.18.2 Constructor & Destructor Documentation

8.18.2.1 Gui::Widgets::CheckFields::CheckName::CheckName (QWidget * w = 0, QPushButton * btn = 0)

[CheckName::CheckName](#) Construct a [CheckName](#).

Parameters

<i>w</i>	QWidget linked to CheckName
----------	---

The documentation for this class was generated from the following files:


- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkname.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkname.cpp

8.19 Gui::Widgets::CheckFields::CheckPhone Class Reference

The [CheckPhone](#) class Line Edit of Phone number with a check icon.

```
#include <checkphone.h>
```

Inheritance diagram for Gui::Widgets::CheckFields::CheckPhone:



Public Member Functions

- [CheckPhone](#) (QWidget *w=0, QPushButton *btn=0)
CheckPhone::CheckPhone Construct a [CheckPhone](#).
- bool [check](#) (QString text)
CheckPhone::check Check if the field is valid. To be valid, a name should be composed of a character.
- QString [getCountry](#) () const
CheckPhone::getCountry Return the country linked to current field.
- void [setCountry](#) (const QString &country)
CheckPhone::setCountry Modify the country linked to field.

Additional Inherited Members

8.19.1 Detailed Description

The [CheckPhone](#) class Line Edit of Phone number with a check icon.

8.19.2 Constructor & Destructor Documentation

8.19.2.1 [Gui::Widgets::CheckFields::CheckPhone::CheckPhone](#) ([QWidget](#) * *w* = 0, [QPushButton](#) * *btn* = 0)

[CheckPhone::CheckPhone](#) Construct a [CheckPhone](#).

Parameters

<i>w</i>	QWidget linked to CheckPhone
----------	--

8.19.3 Member Function Documentation

8.19.3.1 bool [Gui::Widgets::CheckFields::CheckPhone::check](#) ([QString](#) *text*) [virtual]

[CheckPhone::check](#) Check if the field is valid. To be valid, a name should be composed of a character.

Parameters

<i>text</i>	Text to check
-------------	---------------

Returns

boolean Validity of the text

Implements [Gui::Widgets::CheckFields::ICheckField](#).

8.19.3.2 QString Gui::Widgets::CheckFields::CheckPhone::getCountry () const

[CheckPhone::getCountry](#) Return the country linked to current field.

Returns

8.19.3.3 void Gui::Widgets::CheckFields::CheckPhone::setCountry (const QString & country)

[CheckPhone::setCountry](#) Modify the *country* linked to field.

Parameters

<i>country</i>	New country
----------------	-------------

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkphone.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkphone.cpp

8.20 Gui::Widgets::CheckFields::CheckPortNumber Class Reference

The [CheckFieldsNumbers](#) class Line Edit of number with a check icon.

```
#include <checkportnumber.h>
```

Inheritance diagram for Gui::Widgets::CheckFields::CheckPortNumber:



Public Member Functions

- [CheckPortNumber](#) (QWidget *w=0, QPushButton *btn=0)
[CheckPortNumber](#).
- bool [check](#) (QString text)
[CheckPortNumber::check](#) Check if the field contains only numbers or an empty text.

Additional Inherited Members

8.20.1 Detailed Description

The [CheckFieldsNumbers](#) class Line Edit of number with a check icon.

Author

Florent BERBIE

See Also

[CheckQLineEdit](#)
[CheckUntilField](#)

8.20.2 Constructor & Destructor Documentation

8.20.2.1 `Gui::Widgets::CheckFields::CheckPortNumber::CheckPortNumber (QWidget * w = 0, QPushButton * btn = 0)`

[CheckPortNumber.](#)

Parameters

<i>w</i>	Widget parent
<i>btn</i>	Button parretrn

8.20.3 Member Function Documentation

8.20.3.1 `bool Gui::Widgets::CheckFields::CheckPortNumber::check (QString text)` `[virtual]`

[CheckPortNumber::check](#) Check if the field contains only numbers or an empty text.

Parameters

<i>text</i>	Text to check
-------------	---------------

Returns

boolean Validity of the text

Implements [Gui::Widgets::CheckFields::ICheckField](#).

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkportnumber.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkportnumber.cpp

8.21 Gui::Widgets::CheckFields::CheckPostalCode Class Reference

The [CheckPostalCode](#) class Line Edit of postal code with a check icon.

```
#include <checkpostalcode.h>
```

Inheritance diagram for Gui::Widgets::CheckFields::CheckPostalCode:



Public Member Functions

- [CheckPostalCode](#) (QWidget *w=0, QPushButton *btn=0)
[CheckPostalCode::CheckPostalCode](#) Construct a [CheckPostalCode](#).
- bool [check](#) (QString text)
[CheckPostalCode::check](#) Check if the field is valid. To be valid, a name should be composed of a character.
- QString [getCountry](#) () const
[CheckPostalCode::getCountry](#) Return the country linked to current field.
- void [setCountry](#) (const QString &country)
[CheckPostalCode::setCountry](#) Modify the country linked to field.

Additional Inherited Members

8.21.1 Detailed Description

The [CheckPostalCode](#) class Line Edit of postal code with a check icon.

8.21.2 Constructor & Destructor Documentation

8.21.2.1 `Gui::Widgets::CheckFields::CheckPostalCode::CheckPostalCode (QWidget * w = 0, QPushButton * btn = 0)`

[CheckPostalCode::CheckPostalCode](#) Construct a [CheckPostalCode](#).

Parameters

<i>w</i>	QWidget linked to CheckPostalCode
----------	---

8.21.3 Member Function Documentation

8.21.3.1 `bool Gui::Widgets::CheckFields::CheckPostalCode::check (QString text) [virtual]`

[CheckPostalCode::check](#) Check if the field is valid. To be valid, a name should be composed of a character.

Parameters

<i>text</i>	Text to check
-------------	---------------

Returns

boolean Validity of the text

Implements [Gui::Widgets::CheckFields::ICheckField](#).

8.21.3.2 `QString Gui::Widgets::CheckFields::CheckPostalCode::getCountry () const`

[CheckPostalCode::getCountry](#) Return the country linked to current field.

Returns

country Country of the field

8.21.3.3 `void Gui::Widgets::CheckFields::CheckPostalCode::setCountry (const QString & country)`


[CheckPostalCode::setCountry](#) Modify the *country* linked to field.

<i>country</i>	New country
----------------	-------------

- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkpostalcode.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkpostalcode.cpp

The `CheckQLineEdit` class `LineEdit` custom with a check of text inputted.

Inheritance diagram for Gui::Widgets::CheckFields::CheckQLineEdit:



- void `fieldTextChanged` (const QString &text)
CheckQLineEdit::fieldTextChanged For each new character inputted or removed, displays an icon to show if the field is valid or not.

- [CheckQLineEdit](#) (QWidget *parent=0, QPushButton *btn=0)
CheckQLineEdit::CheckQLineEdit Construct a [CheckQLineEdit](#).
- void [displayCheckValidFieldIcon](#) ()
CheckQLineEdit::displayCheckValidFieldIcon Display a valid icon into the field.
- void [displayCheckNoValidFieldIcon](#) ()
CheckQLineEdit::displayCheckNoValidFieldIcon Display a "no valid" icon into the field.
- QPushButton * [getBtnValid](#) () const
CheckQLineEdit::getBtnValid.
- void [setBtnValid](#) (QPushButton *[getBtnValid](#))
CheckQLineEdit::setBtnValid.
- bool [isValid](#) ()
isValid Return true if the current field if valid

The `CheckQLineEdit` class `LineEdit` custom with a check of text inputed.

8.22.2.1 Gui::Widgets::CheckFields::CheckQLineEdit::CheckQLineEdit (QWidget * *parent* = 0, QPushButton * *btn* = 0)

Generated on Sun Apr 5 2015 23:04:36 for FactDev by Doxygen

Parameters

<i>parent</i>	
---------------	--

8.22.3 Member Function Documentation

8.22.3.1 `QPushButton * Gui::Widgets::CheckFields::CheckQLineEdit::getBtnValid () const`

[CheckQLineEdit::getBtnValid.](#)

Returns

a

8.22.3.2 `bool Gui::Widgets::CheckFields::CheckQLineEdit::isValid ()`

isValid Return true if the current field if valid

Returns

boolean

8.22.3.3 `void Gui::Widgets::CheckFields::CheckQLineEdit::setBtnValid (QPushButton * getBtnValid)`

[CheckQLineEdit::setBtnValid.](#)

Parameters

<i>getBtnValid</i>	
--------------------	--

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkqlineEdit.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkqlineEdit.cpp

8.23 Gui::Widgets::CheckFields::CheckSiretNumber Class Reference

The [CheckSiretNumber](#) class Line Edit with a check icon.

```
#include <checksiretnumber.h>
```

Inheritance diagram for Gui::Widgets::CheckFields::CheckSiretNumber:



Public Member Functions

- [CheckSiretNumber](#) (QWidget *w=0, QPushButton *btn=0)

[CheckSiretNumber::CheckSiretNumber](#) Construct a [CheckSiretNumber](#).

- bool [check](#) (QString text)

[CheckSiretNumber::check](#) Check if the field noSiret is valid. To be valid, a SIRET number should be composed of numbers.

Additional Inherited Members

8.23.1 Detailed Description

The [CheckSiretNumber](#) class Line Edit with a check icon.

8.23.2 Constructor & Destructor Documentation

8.23.2.1 [Gui::Widgets::CheckFields::CheckSiretNumber::CheckSiretNumber \(QWidget * w = 0, QPushButton * btn = 0 \)](#)

[CheckSiretNumber::CheckSiretNumber](#) Construct a [CheckSiretNumber](#).

Parameters

<i>w</i>	QWidget linked to CheckSiretNumber
----------	--

8.23.3 Member Function Documentation

8.23.3.1 [bool Gui::Widgets::CheckFields::CheckSiretNumber::check \(QString text \)](#) [virtual]

[CheckSiretNumber::check](#) Check if the field noSiret is valid. To be valid, a SIRET number should be composed of numbers.

Parameters

<i>text</i>	Text to check
-------------	---------------

Returns

boolean Validity of the text

Implements [Gui::Widgets::CheckFields::ICheckField](#).

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checksiretnumber.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checksiretnumber.cpp

8.24 Gui::Widgets::CheckFields::CheckUntilField Class Reference

The [CheckUntilField](#) class.

```
#include <checkuntilfield.h>
```

Inheritance diagram for [Gui::Widgets::CheckFields::CheckUntilField](#):



Public Member Functions

- [CheckUntilField](#) (QWidget *w=0, QPushButton *btn=0)
[CheckUntilField::CheckUntilField](#) Construct a [CheckUntilField](#).
- bool [check](#) (QString text)
[CheckUntilField::check](#) Check if the field is valid. To be valid, a name should be composed of a character.

Additional Inherited Members

8.24.1 Detailed Description

The [CheckUntilField](#) class.

8.24.2 Constructor & Destructor Documentation

8.24.2.1 [Gui::Widgets::CheckFields::CheckUntilField::CheckUntilField](#) ([QWidget](#) * *w* = 0, [QPushButton](#) * *btn* = 0)

[CheckUntilField::CheckUntilField](#) Construct a [CheckUntilField](#).

Parameters

<i>w</i>	QWidget linked to CheckUntilField
----------	---

8.24.3 Member Function Documentation

8.24.3.1 bool [Gui::Widgets::CheckFields::CheckUntilField::check](#) ([QString](#) *text*) [\[virtual\]](#)

[CheckUntilField::check](#) Check if the field is valid. To be valid, a name should be composed of a character.

Parameters

<i>text</i>	Text to check
-------------	---------------

Returns

boolean Validity of the text

Implements [Gui::Widgets::CheckFields::ICheckField](#).

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkuntilfield.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkuntilfield.cpp

8.25 Gui::Widgets::CheckFields::CheckValidField Class Reference

The [CheckValidField](#) class Check field not required.

```
#include <checkvalidfield.h>
```

Inheritance diagram for [Gui::Widgets::CheckFields::CheckValidField](#):



Public Member Functions

- [CheckValidField](#) (QWidget *w=0, QPushButton *btn=0)
[CheckValidField::CheckValidField](#).
- bool [check](#) (QString text)
[CheckValidField::check](#) Return TRUE : the field is not required.

Additional Inherited Members

8.25.1 Detailed Description

The [CheckValidField](#) class Check field not required.

8.25.2 Constructor & Destructor Documentation

8.25.2.1 [Gui::Widgets::CheckFields::CheckValidField::CheckValidField](#) (QWidget * w = 0, QPushButton * btn = 0)

[CheckValidField::CheckValidField](#).

Parameters

<i>w</i>	QWidget linked to CheckValidField
----------	---

8.25.3 Member Function Documentation

8.25.3.1 bool [Gui::Widgets::CheckFields::CheckValidField::check](#) (QString *text*) [virtual]

[CheckValidField::check](#) Return TRUE : the field is not required.

Parameters

<i>text</i>	Text to check
-------------	---------------

Returns

boolean Validity of the text

Implements [Gui::Widgets::CheckFields::ICheckField](#).

Reimplemented in [Gui::Widgets::CheckFields::CheckWebsite](#).

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkvalidfield.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkvalidfield.cpp

8.26 Gui::Widgets::CheckFields::CheckWebsite Class Reference

The [CheckWebsite](#) class Line Edit of website with a check icon.

```
#include <checkwebsite.h>
```

Inheritance diagram for Gui::Widgets::CheckFields::CheckWebsite:



Public Member Functions

- [CheckWebsite](#) (QWidget *w=0, QPushButton *btn=0)
[CheckWebsite::CheckWebsite](#) Construct a [CheckWebsite](#).
- bool [check](#) (QString text)
[CheckWebsite::check](#) Check if the field contains an website address.

Additional Inherited Members

8.26.1 Detailed Description

The [CheckWebsite](#) class Line Edit of website with a check icon.

See Also

[CheckQLineEdit](#)
[CheckUntilField](#)
[CheckIpAddress](#)

8.26.2 Constructor & Destructor Documentation

8.26.2.1 [Gui::Widgets::CheckFields::CheckWebsite::CheckWebsite](#) ([QWidget](#) * *w* = 0, [QPushButton](#) * *btn* = 0)

[CheckWebsite::CheckWebsite](#) Construct a [CheckWebsite](#).

Parameters

<i>w</i>	QWidget linked to CheckWebsite
----------	--

8.26.3 Member Function Documentation

8.26.3.1 bool [Gui::Widgets::CheckFields::CheckWebsite::check](#) ([QString](#) *text*) [virtual]

[CheckWebsite::check](#) Check if the field contains an website address.

Parameters

<i>text</i>	Text to check
-------------	---------------

Returns

boolean Validity of the text

Reimplemented from [Gui::Widgets::CheckFields::CheckValidField](#).

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkwebsite.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkwebsite.cpp

8.27 Gui::Widgets::Path::ChoseDirectoryWidget Class Reference

The [ChoseDirectoryWidget](#) class Open a QFileDialog.and display path in textfield.

```
#include <chosedirectorywidget.h>
```

Inheritance diagram for Gui::Widgets::Path::ChoseDirectoryWidget:



Public Slots

- void [fillField](#) ()
fillField Fill the textfield with path information

Public Member Functions

- [ChoseDirectoryWidget](#) (QWidget *parent=0)
ChoseDirectoryWidget Construct Widget.

Additional Inherited Members

8.27.1 Detailed Description

The [ChoseDirectoryWidget](#) class Open a QFileDialog.and display path in textfield.

8.27.2 Constructor & Destructor Documentation

8.27.2.1 [Gui::Widgets::Path::ChoseDirectoryWidget::ChoseDirectoryWidget](#) (QWidget * *parent* = 0) [explicit]

[ChoseDirectoryWidget](#) Construct Widget.

Parameters

<i>parent</i>	The parent widget
---------------	-------------------

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/path/chosedirectorywidget.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/path/chosedirectorywidget.cpp

8.28 Gui::Widgets::Path::ChoseFileWidget Class Reference

The [ChoseFileWidget](#) class Chose a File in computer.

```
#include <chosefilewidget.h>
```

Inheritance diagram for Gui::Widgets::Path::ChoseFileWidget:



Public Slots

- void [fillField](#) ()
fillField Fill the textfield with path information

Public Member Functions

- [ChoseFileWidget](#) (QWidget *parent=0)
ChoseFileWidget Construct a choseFileWidget.
- QString [gettypeFiles](#) () const
*gettypeFiles Return the types of files, by default it's **
- void [setTypeFiles](#) (const QString &[gettypeFiles](#))
*setTypeFiles Change the files types. By default it's **

Additional Inherited Members

8.28.1 Detailed Description

The [ChoseFileWidget](#) class Chose a File in computer.

8.28.2 Constructor & Destructor Documentation

8.28.2.1 [Gui::Widgets::Path::ChoseFileWidget::ChoseFileWidget \(QWidget * parent = 0 \)](#) [explicit]

[ChoseFileWidget](#) Construct a choseFileWidget.

Parameters

<i>parent</i>	The parent widget
---------------	-------------------

8.28.3 Member Function Documentation

8.28.3.1 QString Gui::Widgets::Path::ChoseFileWidget::getTypeFiles () const

getTypeFiles Return the types of files, by default it's *

Returns

The type of files

8.28.3.2 void Gui::Widgets::Path::ChoseFileWidget::setTypeFiles (const QString & *getTypeFiles*)

setTypeFiles Change the files types. By default it's *

Parameters

<i>getTypeFiles</i>	The new files types.
---------------------	----------------------

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/path/chosefilewidget.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/path/chosefilewidget.cpp

8.29 Gui::Widgets::Path::ChosePathWidget Class Reference

The [ChoseDirectoryWidget](#) class Open a QFileDialog.and display path in textfield.

```
#include <chosepathwidget.h>
```

Inheritance diagram for Gui::Widgets::Path::ChosePathWidget:



Public Slots

- virtual void [fillField](#) ()
fillField Fill the textfield with path information

Signals

- void [textChanged](#) ()
textChanged Signal is send when path changed.

Public Member Functions

- [ChosePathWidget](#) (QWidget *parent=0)
[ChoseFileWidget](#) Construct a choseFileWidget.
- void [setField](#) (QString text)
setField Change the path in textfield
- QString [getField](#) ()
getField The text in field
- virtual QString [getDefaultLocation](#) ()
getDefaultLocation The default location when we open popup. In default case, it's ~/Documents

Protected Attributes

- Ui::ChosePathWidget * **ui**

8.29.1 Detailed Description

The [ChoseDirectoryWidget](#) class Open a QFileDialog.and display path in textfield.

8.29.2 Constructor & Destructor Documentation

8.29.2.1 `Gui::Widgets::Path::ChosePathWidget::ChosePathWidget (QWidget * parent = 0) [explicit]`

[ChoseFileWidget](#) Construct a choseFileWidget.

Parameters

<i>parent</i>	The parent widget
---------------	-------------------

8.29.3 Member Function Documentation

8.29.3.1 `QString Gui::Widgets::Path::ChosePathWidget::getDefaultLocation () [virtual]`

getDefaultLocation The default location when we open popup. In default case, it's ~/Documents

Returns

The default location

8.29.3.2 `QString Gui::Widgets::Path::ChosePathWidget::getField (void)`

getField The text in field

Returns

The path text

8.29.3.3 `void Gui::Widgets::Path::ChosePathWidget::setField (QString text)`

setField Change the path in textfield

Parameters

<i>text</i>	The new text
-------------	--------------

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/path/chosepathwidget.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/path/chosepathwidget.cpp

8.30 Gui::Widgets::Delegates::ComboBoxDelegate Class Reference

The [ComboBoxDelegate](#) class.

```
#include <comboboxdelegate.h>
```

Inheritance diagram for Gui::Widgets::Delegates::ComboBoxDelegate:



Public Member Functions

- [ComboBoxDelegate](#) (QObject *parent=0)
ComboBoxDelegate::ComboBoxDelegate Construct a [ComboBoxDelegate](#).
- virtual QWidget * [createEditor](#) (QWidget *parent, const QStyleOptionViewItem &option, const QModelIndex &index) const =0
ComboBoxDelegate::createEditor Return a [ComboBox](#) specified by index item defined by the parent widget and style option which are used to control how the editor widgets appears.
- void [paint](#) (QPainter *painter, const QStyleOptionViewItem &option, const QModelIndex &index) const =0
ComboBoxDelegate::paint Renders the delegate using the given painter and style option for the item specified by index
- void [setEditorData](#) (QWidget *editor, const QModelIndex &index) const
ComboBoxDelegate::setEditorData Sets the data to be displayed and edited by the editor from the data model item specified by the model index
- void [setModelData](#) (QWidget *editor, QAbstractItemModel *model, const QModelIndex &index) const
ComboBoxDelegate::setModelData Gets data from the editor widget and stores it in the specified model at the item index
- void [updateEditorGeometry](#) (QWidget *editor, const QStyleOptionViewItem &option, const QModelIndex &index) const
ComboBoxDelegate::updateEditorGeometry Update the editor for the item specified by index according to the style option given.

8.30.1 Detailed Description

The [ComboBoxDelegate](#) class.

Author

Antoine de Roquemaurel

8.30.2 Constructor & Destructor Documentation

8.30.2.1 Gui::Widgets::Delegates::ComboBoxDelegate::ComboBoxDelegate (QObject * *parent* = 0)

[ComboBoxDelegate::ComboBoxDelegate](#) Construct a [ComboBoxDelegate](#).

Parameters

<i>parent</i>	Object parent
---------------	---------------

8.30.3 Member Function Documentation

8.30.3.1 virtual QWidget* Gui::Widgets::Delegates::ComboBoxDelegate::createEditor (QWidget * *parent*, const QStyleOptionViewItem & *option*, const QModelIndex & *index*) const [pure virtual]

[ComboBoxDelegate::createEditor](#) Return a ComboBox specified by *index* item defined by the *parent* widget and style *option* which are used to control how the editor widgets appears.

Parameters

<i>parent</i>	Widget parent
<i>option</i>	Option style
<i>index</i>	Index for editing

Returns

ComboBox

Implemented in [Gui::Widgets::Delegates::UnitComboDelegate](#), and [Gui::Widgets::Delegates::ProjectComboDelegate](#).

8.30.3.2 void Gui::Widgets::Delegates::ComboBoxDelegate::paint (QPainter * *painter*, const QStyleOptionViewItem & *option*, const QModelIndex & *index*) const [pure virtual]

[ComboBoxDelegate::paint](#) Renders the delegate using the given *painter* and style *option* for the item specified by *index*

Parameters

<i>parent</i>	Widget parent
<i>option</i>	Option style
<i>index</i>	Index for editing

Implemented in [Gui::Widgets::Delegates::UnitComboDelegate](#), and [Gui::Widgets::Delegates::ProjectComboDelegate](#).

8.30.3.3 void Gui::Widgets::Delegates::ComboBoxDelegate::setEditorData (QWidget * *editor*, const QModelIndex & *index*) const

[ComboBoxDelegate::setEditorData](#) Sets the data to be displayed and edited by the *editor* from the data model item specified by the model *index*

Parameters

<i>editor</i>	Data edited
---------------	-------------

<i>index</i>	Index of the model to edit
--------------	----------------------------

8.30.3.4 void Gui::Widgets::Delegates::ComboBoxDelegate::setModelData (QWidget * *editor*, QAbstractItemModel * *model*, const QModelIndex & *index*) const

[ComboBoxDelegate::setModelData](#) Gets data from the *editor* widget and stores it in the specified *model* at the item *index*

Parameters

<i>editor</i>	Editor Widget
<i>model</i>	Model to store data
<i>index</i>	Item index

8.30.3.5 void Gui::Widgets::Delegates::ComboBoxDelegate::updateEditorGeometry (QWidget * *editor*, const QStyleOptionViewItem & *option*, const QModelIndex & *index*) const

[ComboBoxDelegate::updateEditorGeometry](#) Update the *editor* for the item specified by *index* according to the style *option* given.

Parameters

<i>editor</i>	Editor widget to update
<i>option</i>	Style option
<i>index</i>	Item index

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/delegates/comboboxdelegate.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/delegates/comboboxdelegate.cpp

8.31 Gui::Widgets::ComboBoxModelWidget Class Reference

The [ComboBoxModelWidget](#) class Model of ComboBox.

```
#include <comboboxmodelwidget.h>
```

Inheritance diagram for Gui::Widgets::ComboBoxModelWidget:



Public Member Functions

- [ComboBoxModelWidget](#) (QWidget *parent=0)
[ComboBoxModelWidget::ComboBoxModelWidget](#) Construct a [ComboBoxModelWidget](#).

8.31.1 Detailed Description

The [ComboBoxModelWidget](#) class Model of ComboBox.

8.31.2 Constructor & Destructor Documentation

8.31.2.1 Gui::Widgets::ComboBoxModelWidget::ComboBoxModelWidget (QWidget * *parent* = 0) [explicit]

[ComboBoxModelWidget::ComboBoxModelWidget](#) Construct a [ComboBoxModelWidget](#).

Parameters

<i>parent</i>	QWidget parent
---------------	----------------

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/comboboxmodelwidget.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/comboboxmodelwidget.cpp

8.32 Gui::Dialogs::ComputeTurnoverDialog Class Reference

The [ComputeTurnoverDialog](#) class window to compute a turnover with a period.

```
#include <computeturnoverdialog.h>
```

Inheritance diagram for Gui::Dialogs::ComputeTurnoverDialog:



Public Slots

- void [computeTurnover](#) ()
ComputeTurnoverDialog::computeTurnover compute the turnover between chosen dates in the window.
- void [endDateControl](#) (const QDate end)
ComputeTurnoverDialog::endDateControl controls if the end date field is valid.
- void [beginDateControl](#) (const QDate begin)
ComputeTurnoverDialog::beginDateControl controls if the begin date field is valid.

Public Member Functions

- **ComputeTurnoverDialog** (QWidget *parent=0)
- void [fillLabels](#) (const int nbBillings, const int turnover)
ComputeTurnoverDialog::fillLabels Fills the labels with nbBillings and turnover

8.32.1 Detailed Description

The [ComputeTurnoverDialog](#) class window to compute a turnover with a period.

Author

Manantsoa Razanajatovo

8.32.2 Member Function Documentation

8.32.2.1 void Gui::Dialogs::ComputeTurnoverDialog::beginDateControl (const QDate *begin*) [slot]

[ComputeTurnoverDialog::beginDateControl](#) controls if the *begin* date field is valid.

Parameters

<i>begin</i>	
--------------	--

8.32.2.2 void Gui::Dialogs::ComputeTurnoverDialog::endDateControl (const QDate *end*) [slot]

[ComputeTurnoverDialog::endDateControl](#) controls if the *end* date field is valid.

Parameters

<i>end</i>	
------------	--

8.32.2.3 void Gui::Dialogs::ComputeTurnoverDialog::fillLabels (const int *nbBillings*, const int *turnover*)

[ComputeTurnoverDialog::fillLabels](#) Fills the labels with *nbBillings* and *turnover*

Parameters

<i>nbBillings</i>	the number of Billings
<i>turnover</i>	the turnover computed

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/dialogs/computeturnoverdialog.h
- /home/travis/build/FACT-Team/FactDev/src/gui/dialogs/computeturnoverdialog.cpp

8.33 Mustache::Context Class Reference

```
#include <mustache.h>
```

Inheritance diagram for Mustache::Context:



Public Member Functions

- [Context](#) ([PartialResolver](#) *resolver=0)
- virtual QString [stringValue](#) (const QString &key) const =0
- virtual bool [isFalse](#) (const QString &key) const =0
- virtual int [listCount](#) (const QString &key) const =0
- virtual void [push](#) (const QString &key, int index=-1)=0
- virtual void [pop](#) ()=0
- QString [partialValue](#) (const QString &key) const
- [PartialResolver](#) * [partialResolver](#) () const
- virtual bool [canEval](#) (const QString &key) const
- virtual QString [eval](#) (const QString &key, const QString &_template, [Renderer](#) *renderer)

8.33.1 Detailed Description

[Context](#) is an interface that [Mustache::Renderer::render\(\)](#) uses to fetch substitutions for template tags.

8.33.2 Constructor & Destructor Documentation

8.33.2.1 `Context::Context (PartialResolver * resolver = 0)` `[explicit]`

Create a context. `resolver` is used to fetch the expansions for any `{{>partial}}` tags which appear in a template.

8.33.3 Member Function Documentation

8.33.3.1 `bool Context::canEval (const QString & key) const` `[virtual]`

Returns true if `eval()` should be used to render section tags using `key`. If `canEval()` returns true for a key, the renderer will pass the literal, unrendered block of text for the section to `eval()` and replace the section with the result.

`canEval()` and `eval()` are equivalents for callable objects (eg. lambdas) in other Mustache implementations.

The default implementation always returns false.

Reimplemented in [CounterContext](#), [CounterContext](#), and [Mustache::QtVariantContext](#).

8.33.3.2 `QString Context::eval (const QString & key, const QString & _template, Renderer * renderer)` `[virtual]`

Callback used to render a template section with the given `key`. `renderer` will substitute the original section tag with the result of `eval()`.

The default implementation returns an empty string.

Reimplemented in [CounterContext](#), [CounterContext](#), and [Mustache::QtVariantContext](#).

8.33.3.3 `virtual bool Mustache::Context::isFalse (const QString & key) const` `[pure virtual]`

Returns true if the value for `key` is 'false' or an empty list. 'False' values typically include empty strings, the boolean value false etc.

When processing a section Mustache tag, the section is not rendered if the key is false, or for an inverted section tag, the section is only rendered if the key is false.

Implemented in [Mustache::QtVariantContext](#).

8.33.3.4 `virtual int Mustache::Context::listCount (const QString & key) const` `[pure virtual]`

Returns the number of items in the list value for `key` or 0 if the value for `key` is not a list.

Implemented in [Mustache::QtVariantContext](#).

8.33.3.5 `PartialResolver * Context::partialResolver () const`

Returns the partial resolver passed to the constructor.

8.33.3.6 `QString Context::partialValue (const QString & key) const`

Returns the partial template for a given `key`.

8.33.3.7 `virtual void Mustache::Context::pop () [pure virtual]`

Exit the current context.

Implemented in [Mustache::QtVariantContext](#).

8.33.3.8 `virtual void Mustache::Context::push (const QString & key, int index = -1) [pure virtual]`

Set the current context to the value for `key`. If `index` is ≥ 0 , set the current context to the `index`'th value in the list value for `key`.

Implemented in [Mustache::QtVariantContext](#).

8.33.3.9 `virtual QString Mustache::Context::stringValue (const QString & key) const [pure virtual]`

Returns a string representation of the value for `key` in the current context. This is used to replace a Mustache value tag.

Implemented in [CounterContext](#), [CounterContext](#), and [Mustache::QtVariantContext](#).

The documentation for this class was generated from the following files:

- `/home/travis/build/FACT-Team/FactDev/src/libs/qt-mustache/src/mustache.h`
- `/home/travis/build/FACT-Team/FactDev/src/libs/qt-mustache/src/mustache.cpp`

8.34 ContributoriesDatabaseTest Class Reference

Inheritance diagram for ContributoriesDatabaseTest:



The documentation for this class was generated from the following files:

- `/home/travis/build/FACT-Team/FactDev/tests/database/contributoriesdatabasetest.h`
- `/home/travis/build/FACT-Team/FactDev/tests/database/contributoriesdatabasetest.cpp`

8.35 Models::ContributoriesList Class Reference

The [ContributoriesList](#) class List of contributories.

```
#include <contributorieslist.h>
```

Inheritance diagram for Models::ContributoriesList:



Public Member Functions

- [ContributoriesList](#) ()
ContributoriesList::ContributoriesList Construct a [ContributoriesList](#).
- double [getPrice](#) (bool isPaied=false)
getPrice Return the price of a contributories list
- double [getPrice](#) ([Models::Project](#) *project)
getPrice Return price of project
- double [getSumQuantity](#) ()
ContributoriesList::getSumQuantity Return the sum of quantity (number of hours) of the Contributories.
- double [getSumQuantity](#) ([Models::Project](#) *project)
ContributoriesList::getSumQuantity Return the sum of quantity (number of hours) of the Contributories of project.
- [Models::Rate](#) [getRate](#) ([Models::Project](#) *project)
ContributoriesList::getRate.
- virtual void [commit](#) ()
ContributoriesList::commit Update or insert data into the database.
- void [addContributory](#) ([Models::Contributory](#) &contributory)
ContributoriesList::addContributory Add a new contributory
- void [addProject](#) ([Project](#) *p, [Models::Rate](#) rate)
ContributoriesList::addProject Add a [Project](#) p and it rate
- [QList](#)< [Contributory](#) > & [getContributories](#) ([Project](#) *p)
ContributoriesList::getContributories Return a list of Contributories for the [Project](#) p
- int [getIdBilling](#) () const
ContributoriesList::getIdBilling Return the [Billing](#) ID.
- void [setIdBilling](#) (int idBilling)
ContributoriesList::setIdBilling Change the [Billing](#) id by the new idBilling
- void [setAllIdContributories](#) (int idContributory)
ContributoriesList::setAllIdContributories Change all [Contributory](#) id with the same id.
- bool [isInsert](#) () const
ContributoriesList::isInsert Return TRUE if an element is inserting else FALSE.
- void [setInsert](#) (bool insert)
ContributoriesList::setInsert Change the state of insertion.
- int [getNbProjects](#) ()
ContributoriesList::getNbProjects Return the number of projects.
- [QSharedPointer](#)< [Customer](#) > [getCustomer](#) ()
ContributoriesList::getCustomer Return the Customers linked to theses contributories.
- [QList](#)< [Project](#) * > [getProjects](#) ()
ContributoriesList::getProjects List of Projects.
- [QList](#)< [Contributory](#) > * [getAllContributories](#) ()
ContributoriesList::getAllContributories List of all contributories (all contributories from all projects)
- [QVariantList](#) [getDataMap](#) ()
ContributoriesList::getDataMap Return a list of [Billing](#) and it value linked which indicates if it is inserting or not.

8.35.1 Detailed Description

The [ContributoriesList](#) class List of contributories.

Author

Antoine de Roquemaurel

8.35.2 Member Function Documentation

8.35.2.1 void Models::ContributoriesList::addContributory (Models::Contributory & *contributory*)

[ContributoriesList::addContributory](#) Add a new *contributory*

Parameters

<i>contributory</i>	Contributory to add
---------------------	-------------------------------------

8.35.2.2 void Models::ContributoriesList::addProject ([Project](#) * *p*, [Models::Rate](#) *rate*)

[ContributoriesList::addProject](#) Add a [Project](#) *p* and it *rate*

Parameters

<i>p</i>	Project to add
<i>rate</i>	Rate of the project

8.35.2.3 QList< [Contributory](#) > * Models::ContributoriesList::getAllContributories ()

[ContributoriesList::getAllContributories](#) List of all contributories (all contributories from all projects)

Returns

List of all contributories

8.35.2.4 QList< [Contributory](#) > & Models::ContributoriesList::getContributories ([Project](#) * *p*)

[ContributoriesList::getContributories](#) Return a list of Contributories for the [Project](#) *p*

Parameters

<i>p</i>	Project
----------	-------------------------

Returns

List of Contributories for a project

8.35.2.5 QSharedPointer< [Customer](#) > Models::ContributoriesList::getCustomer ()

[ContributoriesList::getCustomer](#) Return the Customers linked to theses contributories.

Returns

[Customer](#)

8.35.2.6 QVariantList Models::ContributoriesList::getDataMap ()

[ContributoriesList::getDataMap](#) Return a list of [Billing](#) and it value linked which indicates if it is inserting or not.

Returns

List of billing and value linked

8.35.2.7 int Models::ContributoriesList::getIldBilling () const

[ContributoriesList::getIldBilling](#) Return the [Billing](#) ID.

Returns

[Billing](#) id

8.35.2.8 `int Models::ContributoriesList::getNbProjects ()`

[ContributoriesList::getNbProjects](#) Return the number of projects.

Returns

Count number of project

8.35.2.9 `double Models::ContributoriesList::getPrice (bool isPaied = false) [virtual]`

`getPrice` Return the price of a contributories list

Returns

The price

Implements [Models::Calculable](#).

8.35.2.10 `double Models::ContributoriesList::getPrice (Models::Project * project)`

`getPrice` Return price of project

Parameters

<i>project</i>	The project
----------------	-------------

Returns

The price

8.35.2.11 `QList< Project * > Models::ContributoriesList::getProjects (void)`

[ContributoriesList::getProjects](#) List of Projects.

Returns

List of Projects

8.35.2.12 `Models::Rate Models::ContributoriesList::getRate (Models::Project * project)`

[ContributoriesList::getRate](#).

Parameters

<i>project</i>	
----------------	--

Returns**8.35.2.13** `double Models::ContributoriesList::getSumQuantity () [virtual]`

[ContributoriesList::getSumQuantity](#) Return the sum of quantity (number of hours) of the Contributories.

Returns

sum of quantity in days

Implements [Models::Calculable](#).

8.35.2.14 `double Models::ContributoriesList::getSumQuantity (Models::Project * project)`

[ContributoriesList::getSumQuantity](#) Return the sum of quantity (number of hours) of the Contributories of project.

Parameters

<i>project</i>	The project
----------------	-------------

Returns

sum of quantity in days

8.35.2.15 `bool Models::ContributoriesList::isInsert () const`

[ContributoriesList::isInsert](#) Return TRUE if an element is inserting else FALSE.

Returns

boolean

8.35.2.16 `void Models::ContributoriesList::setAllIdContributories (int idContributory)`

[ContributoriesList::setAllIdContributories](#) Change all [Contributory](#) id with the same id.

Parameters

<i>idContributory</i>	the new Contributory id
-----------------------	---

8.35.2.17 `void Models::ContributoriesList::setIdBilling (int idBilling)`

[ContributoriesList::setIdBilling](#) Change the [Billing](#) id by the new *idBilling*

Parameters

<i>idBilling</i>	Billind id
------------------	------------

8.35.2.18 `void Models::ContributoriesList::setInsert (bool insert)`

[ContributoriesList::setInsert](#) Change the state of insertion.

Parameters

<i>insert</i>	Boolean
---------------	---------

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/models/contributorieslist.h
- /home/travis/build/FACT-Team/FactDev/src/models/contributorieslist.cpp

8.36 Gui::Widgets::WdgModels::ContributoriesTableModel Class Reference

The [ContributoriesTableModel](#) class for a custom table for contributories widget.

```
#include <contributoriesstablemodel.h>
```

Inheritance diagram for Gui::Widgets::WdgModels::ContributoriesTableModel:



Public Member Functions

- [ContributoriesTableModel](#) (QObject *parent=0)
[ContributoriesTableModel::ContributoriesTableModel](#) Construct a [ContributoriesTableModel](#).
- int [rowCount](#) (const QModelIndex &) const
[ContributoriesTableModel::rowCount](#) Number of contributories row.
- int [columnCount](#) (const QModelIndex &) const
[ContributoriesTableModel::columnCount](#) Number of column of a contributory.
- QVariant [data](#) (const QModelIndex &index, int role) const
[ContributoriesTableModel::data](#) Obtains data of a specify cell.
- QVariant [headerData](#) (int section, Qt::Orientation orientation, int role) const
[ContributoriesTableModel::headerData](#) Obtains header title of table.
- bool [setData](#) (const QModelIndex &index, const QVariant &value, int role=Qt::EditRole)
[ContributoriesTableModel::setData](#) Change data of a cell.
- void [append](#) (const [Contributory](#) &contributory)
[ContributoriesTableModel::append](#) Add a new line in table.
- void [remove](#) (const int i)
[ContributoriesTableModel::remove](#) Remove a line.
- Qt::ItemFlags [flags](#) (const QModelIndex &index) const
[ContributoriesTableModel::flags](#) Differents table flags.
- QList< [Contributory](#) > [getContributories](#) ()
[ContributoriesTableModel::getContributories](#) Get all contributories of table.
- int [count](#) ()
[ContributoriesTableModel::count](#) Number of contributories in table.
- double [getSumQuantity](#) () const
[ContributoriesTableModel::getSumQuantity](#) Return the sum of the hours of all contriburoies added.
- void [clear](#) ()
[ContributoriesTableModel::clear](#) Remove all contributories.

8.36.1 Detailed Description

The [ContributoriesTableModel](#) class for a custom table for contributories widget.

Author

Antoine de Roquemaurel

See Also

[Contributory](#)

8.36.2 Constructor & Destructor Documentation

8.36.2.1 [Gui::Widgets::WdgModels::ContributoriesTableModel::ContributoriesTableModel](#) ([QObject](#) * *parent* = 0)

[ContributoriesTableModel::ContributoriesTableModel](#) Construct a [ContributoriesTableModel](#).

Parameters

<i>parent</i>	Parent widget
---------------	---------------

8.36.3 Member Function Documentation

8.36.3.1 void Gui::Widgets::WdgModels::ContributoriesTableModel::append (const Contributory & *contributory*)

[ContributoriesTableModel::append](#) Add a new line in table.

Parameters

<i>contributory</i>	The new contributory
---------------------	----------------------

8.36.3.2 int Gui::Widgets::WdgModels::ContributoriesTableModel::columnCount (const QModelIndex &) const

[ContributoriesTableModel::columnCount](#) Number of column of a contributory.

Returns

The number of column

8.36.3.3 int Gui::Widgets::WdgModels::ContributoriesTableModel::count ()

[ContributoriesTableModel::count](#) Number of contributories in table.

Returns

The number of contributories

8.36.3.4 QVariant Gui::Widgets::WdgModels::ContributoriesTableModel::data (const QModelIndex & *index*, int *role*) const

[ContributoriesTableModel::data](#) Obtains data of a specify cell.

Parameters

<i>index</i>	The cell who we want data
<i>role</i>	The role of set

Returns

The data of cell

8.36.3.5 Qt::ItemFlags Gui::Widgets::WdgModels::ContributoriesTableModel::flags (const QModelIndex & *index*) const

[ContributoriesTableModel::flags](#) Differents table flags.

Parameters

<i>index</i>	The cell who we want to know flags
--------------	------------------------------------

Returns

Flags

8.36.3.6 `QList< Contributory > Gui::Widgets::WdgModels::ContributoriesTableModel::getContributories ()`

[ContributoriesTableModel::getContributories](#) Get all contributories of table.

Returns

The contributory list

8.36.3.7 `double Gui::Widgets::WdgModels::ContributoriesTableModel::getSumQuantity () const`

[ContributoriesTableModel::getSumQuantity](#) Return the sum of the hours of all contriburoies added.

Returns

sum quantity

8.36.3.8 `QVariant Gui::Widgets::WdgModels::ContributoriesTableModel::headerData (int section, Qt::Orientation orientation, int role) const`

[ContributoriesTableModel::headerData](#) Obtains header title of table.

Parameters

<i>section</i>	The number of column
<i>orientation</i>	The table orientation
<i>role</i>	

Returns

The Title header of column

8.36.3.9 `void Gui::Widgets::WdgModels::ContributoriesTableModel::remove (const int i)`

[ContributoriesTableModel::remove](#) Remove a line.

Parameters

<i>i</i>	The number of line to remove
----------	------------------------------

8.36.3.10 `int Gui::Widgets::WdgModels::ContributoriesTableModel::rowCount (const QModelIndex &) const`

[ContributoriesTableModel::rowCount](#) Number of contributories row.

Returns

The number of contributories

8.36.3.11 `bool Gui::Widgets::WdgModels::ContributoriesTableModel::setData (const QModelIndex & index, const QVariant & value, int role = Qt::EditRole)`

[ContributoriesTableModel::setData](#) Change data of a cell.

Parameters

<i>index</i>	The cell to change data
<i>value</i>	The new value
<i>role</i>	The role of cell

Returns

True if we could edit

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/widgetmodels/contributoriesstablemodel.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/widgetmodels/contributoriesstablemodel.cpp

8.37 Gui::Widgets::ContributoriesWidget Class Reference

The [ContributoriesWidget](#) class Widget of Contributories.

```
#include <contributorieswidget.h>
```

Inheritance diagram for Gui::Widgets::ContributoriesWidget:



Public Slots

- void [add](#) (void)
ContributoriesWidget::add Add a new empty contributory.
- void [remove](#) (void)
ContributoriesWidget::remove Remove the current contributory.
- void [addProject](#) (QPair< [Project](#) *, [Rate](#) > *p=0)
ContributoriesWidget::addProject Add a Project and it rate p
- void [removeProject](#) (void)
ContributoriesWidget::removeProject Remove the current Project.
- void [changeProject](#) (void)
ContributoriesWidget::changeProject Change the current Project.
- void [editing](#) (void)
ContributoriesWidget::editing Remove the current Project in the combobox not used.
- void [updateUi](#) (void)
ContributoriesWidget::updateUi Update the User Interface.
- void [updatePrice](#) (void)
ContributoriesWidget::updatePrice Update total price.

Signals

- void [contributoryChanged](#) ()
ContributoriesWidget::contributoryChanged Signal that a contributory has changed.

Public Member Functions

- [ContributoriesWidget](#) (QSharedPointer< [Customer](#) > c, QWidget *parent=0)
ContributoriesWidget::ContributoriesWidget Construct a [ContributoriesWidget](#).
- [ContributoriesList](#) * [getContributories](#) () const
ContributoriesWidget::getContributories Get contributories List.
- int [count](#) ()
ContributoriesWidget::count Numbers of contributories.
- void [add](#) ([ContributoriesList](#) &list)
ContributoriesWidget::add Add contributorieslist list in the model.

8.37.1 Detailed Description

The [ContributoriesWidget](#) class Widget of Contributories.

8.37.2 Constructor & Destructor Documentation

8.37.2.1 `Gui::Widgets::ContributoriesWidget::ContributoriesWidget (QSharedPointer< Customer > c, QWidget * parent = 0) [explicit]`

[ContributoriesWidget::ContributoriesWidget](#) Construct a [ContributoriesWidget](#).

Parameters

<i>c</i>	Customer
<i>parent</i>	Widget parent

8.37.3 Member Function Documentation

8.37.3.1 `void Gui::Widgets::ContributoriesWidget::add (ContributoriesList & list)`

[ContributoriesWidget::add](#) Add contributorieslist *list* in the model.

Parameters

<i>list</i>	the ContributoriesList
-------------	-------------------------------

8.37.3.2 `void Gui::Widgets::ContributoriesWidget::addProject (QPair< Project *, Rate > * p = 0) [slot]`

[ContributoriesWidget::addProject](#) Add a Projet and it rate *p*

Parameters

<i>p</i>	Rate linked to Project
----------	------------------------

8.37.3.3 `int Gui::Widgets::ContributoriesWidget::count ()`

[ContributoriesWidget::count](#) Numbers of contributories.

Returns

Numbers of contributories

8.37.3.4 **ContributoriesList * Gui::Widgets::ContributoriesWidget::getContributories () const**

[ContributoriesWidget::getContributories](#) Get contributories List.

Returns

ContributoriesList

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/contributorieswidget.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/contributorieswidget.cpp

8.38 Models::Contributory Class Reference

The [Unit](#) enum Unity of work : hour or day.

```
#include <contributory.h>
```

Inheritance diagram for Models::Contributory:

**Public Member Functions**

- [Contributory](#) ()
Contributory::Contributory Construct a [Contributory](#).
- [Contributory](#) (int id)
Contributory::Contributory Construct a [Contributory](#) and get data in database.
- [~Contributory](#) ()
Destroy an contributory object.
- void [commit](#) ()
Contributory::commit Update or insert a contributory to the database.
- void [hydrat](#) (int id)
Contributory::hydrat Get data about the [Contributory](#) which is specified by the identify id
- void [remove](#) ()
Contributory::remove Remove the current [Contributory](#).
- double [getPrice](#) (const bool paied=false)
getPrice Return the price of a contributory
- double [getSumQuantity](#) ()
ContributoriesList::getSumQuantity Return the sum of quantity (number of hours) of the Contributories.
- QVariantHash [getDataMap](#) ()
getDataMap Get all data of model with a HashMap key/value
- [Project * getProject](#) () const
Contributory::getProject Return the project linked to this [Contributory](#).
- void [setProject](#) ([Project](#) *id)
Contributory::setProject Modify the identify id of the [Project](#) linked to this [Contributory](#).
- double [getQuantity](#) () const

- getNbHours* Number of work hour of a contributory
- void [setQuantity](#) (double value)
 - setNbHours* Change nbHours
- QString [getDescription](#) () const
 - getDescription* Description of a contributory
- void [setDescription](#) (const QString &[getDescription](#))
 - setDescription* Change the contributory description
- bool [operator==](#) (const [Contributory](#) &c)
 - operator ==* define the operator "==" to compare two [Contributory](#)
- bool [operator!=](#) (const [Contributory](#) &c)
 - operator !=* define the operator "!=" to compare two [Contributory](#)
- QString [getLongDescription](#) () const
 - getLongDescription* A contributory has a long description : display in tex appendix
- void [setLongDescription](#) (const QString &[getLongDescription](#))
 - setLongDescription* Change the long description
- [Unit](#) [getUnit](#) () const
 - getUnit* Return the unit (hour or day) of contributory
- void [setUnit](#) (const [Unit](#) &value)
 - setUnit* Change the unit
- double [getHourlyRate](#) () const
 - getHourlyRate* Hourly rate for this contributory
- void [setHourlyRate](#) (double value)
 - setHourlyRate* Change the hourly rate for this contributory

Additional Inherited Members

8.38.1 Detailed Description

The [Unit](#) enum Unity of work : hour or day.

Author

The [Contributory](#) class

8.38.2 Constructor & Destructor Documentation

8.38.2.1 Models::Contributory::Contributory (int *id*)

[Contributory::Contributory](#) Construct a [Contributory](#) and get data in database.

Parameters

<i>id</i>	Contributory 's id
-----------	------------------------------------

8.38.3 Member Function Documentation

8.38.3.1 QVariantHash Models::Contributory::getDataMap () [virtual]

[getDataMap](#) Get all data of model with a HashMap key/value

Returns

Model's data

Implements [Models::IModel](#).

8.38.3.2 `QString Models::Contributory::getDescription () const`

getDescription Description of a contributory

Returns

The description

8.38.3.3 `double Models::Contributory::getHourlyRate () const`

getHourlyRate Hourly rate for this contributory

Returns

The hourly rate

8.38.3.4 `QString Models::Contributory::getLongDescription () const`

getLongDescription A contributory has a long description : display in tex appendix

Returns

The long description

8.38.3.5 `double Models::Contributory::getPrice (const bool paied = false) [virtual]`

getPrice Return the price of a contributory

Returns

The price

Implements [Models::Calculable](#).

8.38.3.6 `Project * Models::Contributory::getProject () const`

[Contributory::getProject](#) Return the project linked to this [Contributory](#).

Returns

[Project](#) linked to this [Contributory](#)

8.38.3.7 `double Models::Contributory::getQuantity () const`

getNbHours Number of work hour of a contributory

Returns

Then number of hours

8.38.3.8 `double Models::Contributory::getSumQuantity () [virtual]`

[ContributoriesList::getSumQuantity](#) Return the sum of quantity (number of hours) of the Contributories.

Returns

sum of quantity in hours

Implements [Models::Calculable](#).

8.38.3.9 `Unit Models::Contributory::getUnit () const`

`getUnit` Return the unit (hour or day) of contributory

Returns

The unit

8.38.3.10 `void Models::Contributory::hydrat (int id) [virtual]`

[Contributory::hydrat](#) Get data about the [Contributory](#) which is specified by the identify *id*

Parameters

<i>id</i>	Contributory identify
-----------	---------------------------------------

Implements [Models::IModel](#).

8.38.3.11 `bool Models::Contributory::operator!= (const Contributory & c)`

`operator !=` define the operator "!=" to compare two [Contributory](#)

Parameters

<i>c</i>	the Contributory to compare with the current Contributory
----------	---

Returns

true if the [Contributory](#) are different else false

8.38.3.12 `bool Models::Contributory::operator== (const Contributory & c)`

`operator ==` define the operator "==" to compare two [Contributory](#)

Parameters

<i>c</i>	the Contributory to compare with the current Contributory
----------	---

Returns

true if the [Contributory](#) are equals else false

8.38.3.13 `void Models::Contributory::setDescription (const QString & getDescription)`

`setDescription` Change the contributory description

Parameters

<i>getDescription</i>	The new description
-----------------------	---------------------

8.38.3.14 void Models::Contributory::setHourlyRate (double *value*)

setHourlyRate Change the hourly rate for this contributory

Parameters

<i>value</i>	The hourly rate
--------------	-----------------

8.38.3.15 void Models::Contributory::setLongDescription (const QString & *getLongDescription*)

setLongDescription Change the long description

Parameters

<i>getLong-Description</i>	The new description
----------------------------	---------------------

8.38.3.16 void Models::Contributory::setProject (Project * *id*)

[Contributory::setProject](#) Modify the identify *id* of the [Project](#) linked to this [Contributory](#).

Parameters

<i>id</i>	Project Identify
-----------	----------------------------------

8.38.3.17 void Models::Contributory::setQuantity (double *value*)

setNbHours Change nbHours

Parameters

<i>value</i>	The new value of nbHours
--------------	--------------------------

8.38.3.18 void Models::Contributory::setUnit (const Unit & *value*)

setUnit Change the unit

Parameters

<i>value</i>	The new unit
--------------	--------------

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/models/contributory.h
- /home/travis/build/FACT-Team/FactDev/src/models/contributory.cpp

8.39 Databases::ContributoryDatabase Class Reference

The [ContributoryDatabase](#) class Contributory (or Quote) table database.

```
#include <contributorydatabase.h>
```

Inheritance diagram for Databases::ContributoryDatabase:



Public Member Functions

- [Models::Contributory](#) * [getContributory](#) (const int idContributory)
ContributoryDatabase::getCustomer get informations about the Contributory identified by pld
- [Models::ContributoriesList](#) [getContributoriesByBilling](#) (const int billingId)
ContributoryDatabase::getContributoriesByBilling get informations about the Contributory identified by Billing
- int [addContributory](#) (const [Models::Contributory](#) &)
ContributoryDatabase::addContributory Add the Contributory pContributory to the database.
- void [updateContributory](#) (const [Models::Contributory](#) &)
ContributoryDatabase::updateCustomer Update informations about the Contributory pCustomer
- void [removeContributory](#) (const int pld)
ContributoryDatabase::removeCustomer Remove the Contributory with the id pld
- [Models::Contributory](#) * [getContributory](#) (QString &q)
getContributory Obtain a contributory without new query
- [Models::ContributoriesList](#) [getContributoriesByBillingAndProject](#) (const int billingId, const int projectId)
getContributory Get contributories list by project and billing

Static Public Member Functions

- static [ContributoryDatabase](#) * [instance](#) () throw (DbException*)
ContributoryDatabase::getInstance Return an instance of [ContributoryDatabase](#)

Additional Inherited Members

8.39.1 Detailed Description

The [ContributoryDatabase](#) class Contributory (or Quote) table database.

Author

See Also

[Database](#)
[Contributory/Quote](#)

8.39.2 Member Function Documentation

8.39.2.1 int [Databases::ContributoryDatabase::addContributory](#) (const [Models::Contributory](#) & *pContributory*)

[ContributoryDatabase::addContributory](#) Add the Contributory *pContributory* to the database.

Returns

Contributory id

8.39.2.2 Models::ContributoriesList Databases::ContributoryDatabase::getContributoriesByBilling (const int *billingId*)

[ContributoryDatabase::getContributoriesByBilling](#) get informations about the Contributory identified by *Billing*

Parameters

<i>idBilling</i>	Contributory id
------------------	-----------------

Returns

the Contributory

8.39.2.3 Models::ContributoriesList Databases::ContributoryDatabase::getContributoriesByBillingAndProject (const int *billingId*, const int *projectId*)

getContributory Get contributories list by project and billing

Parameters

<i>billingId</i>	
<i>projectId</i>	

Returns

The contributories list by project and billing

8.39.2.4 Models::Contributory * Databases::ContributoryDatabase::getContributory (const int *idContributory*)

ContributoryDatabase::getCustomer get informations about the Contributory identified by *pId*

Parameters

<i>idContributory</i>	Contributory id
-----------------------	-----------------

Returns

the Contributory

8.39.2.5 Models::Contributory * Databases::ContributoryDatabase::getContributory (QSqlQuery & *q*)

getContributory Obtain a contributory without new query

Parameters

<i>q</i>	The query to use
----------	------------------

Returns

The contributory linked to q

8.39.2.6 ContributoryDatabase * Databases::ContributoryDatabase::instance () throw DbException *) [static]

ContributoryDatabase::getInstance Return an instance of [ContributoryDatabase](#)

See Also

DbException

Returns

Instance of [ContributoryDatabase](#)

8.39.2.7 void Databases::ContributoryDatabase::removeContributory (const int *pld*)

ContributoryDatabase::removeCustomer Remove the Contributory with the id *pld*

Parameters

<i>pld</i>	Contributory id
------------	-----------------

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/database/contributorydatabase.h
- /home/travis/build/FACT-Team/FactDev/src/database/contributorydatabase.cpp

8.40 ContributoryListTest Class Reference

Inheritance diagram for ContributoryListTest:




The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/tests/models/contributorylisttest.h
- /home/travis/build/FACT-Team/FactDev/tests/models/contributorylisttest.cpp

8.41 ContributoryModelTest Class Reference

Inheritance diagram for ContributoryModelTest:



The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/tests/models/contributorymodeltest.h
- /home/travis/build/FACT-Team/FactDev/tests/models/contributorymodeltest.cpp

8.42 CounterContext Class Reference

Inheritance diagram for CounterContext:



Public Member Functions

- **CounterContext** (const QVariantHash &map)
- virtual bool [canEval](#) (const QString &key) const
- virtual QString [eval](#) (const QString &key, const QString &_template, [Mustache::Renderer](#) *renderer)
- virtual QString [stringValue](#) (const QString &key) const
- **CounterContext** (const QVariantHash &map)
- virtual bool [canEval](#) (const QString &key) const
- virtual QString [eval](#) (const QString &key, const QString &_template, [Mustache::Renderer](#) *renderer)
- virtual QString [stringValue](#) (const QString &key) const

Public Attributes

- int **counter**

Additional Inherited Members

8.42.1 Member Function Documentation

8.42.1.1 virtual bool CounterContext::canEval (const QString & key) const [inline], [virtual]

Returns true if [eval\(\)](#) should be used to render section tags using *key*. If [canEval\(\)](#) returns true for a key, the renderer will pass the literal, unrendered block of text for the section to [eval\(\)](#) and replace the section with the result.

[canEval\(\)](#) and [eval\(\)](#) are equivalents for callable objects (eg. lambdas) in other Mustache implementations.

The default implementation always returns false.

Reimplemented from [Mustache::QtVariantContext](#).

8.42.1.2 virtual bool CounterContext::canEval (const QString & key) const [inline], [virtual]

Returns true if [eval\(\)](#) should be used to render section tags using *key*. If [canEval\(\)](#) returns true for a key, the renderer will pass the literal, unrendered block of text for the section to [eval\(\)](#) and replace the section with the result.

[canEval\(\)](#) and [eval\(\)](#) are equivalents for callable objects (eg. lambdas) in other Mustache implementations.

The default implementation always returns false.

Reimplemented from [Mustache::QtVariantContext](#).

8.42.1.3 `virtual QString CounterContext::eval (const QString & key, const QString & _template, Mustache::Renderer * renderer) [inline], [virtual]`

Callback used to render a template section with the given `key`. `renderer` will substitute the original section tag with the result of `eval()`.

The default implementation returns an empty string.

Reimplemented from [Mustache::QtVariantContext](#).

8.42.1.4 `virtual QString CounterContext::eval (const QString & key, const QString & _template, Mustache::Renderer * renderer) [inline], [virtual]`

Callback used to render a template section with the given `key`. `renderer` will substitute the original section tag with the result of `eval()`.

The default implementation returns an empty string.

Reimplemented from [Mustache::QtVariantContext](#).

8.42.1.5 `virtual QString CounterContext::stringValue (const QString & key) const [inline], [virtual]`

Returns a string representation of the value for `key` in the current context. This is used to replace a Mustache value tag.

Reimplemented from [Mustache::QtVariantContext](#).

8.42.1.6 `virtual QString CounterContext::stringValue (const QString & key) const [inline], [virtual]`

Returns a string representation of the value for `key` in the current context. This is used to replace a Mustache value tag.

Reimplemented from [Mustache::QtVariantContext](#).

The documentation for this class was generated from the following file:

- `/home/travis/build/FACT-Team/FactDev/src/libs/qt-mustache/tests/test_mustache.cpp`

8.43 Models::Customer Class Reference

The [Customer](#) class [Customer](#).

```
#include <customer.h>
```

Inheritance diagram for Models::Customer:



Public Member Functions

- [Customer](#) ()

- Customer::Customer* Construct a *Customer*.
- **Customer** (int id)
 - Customer::Customer* Construct a *Customer* who is specified by id
- void **commit** ()
 - Customer::Customer* Construct a *People* who is specified by id
- void **hydrat** (int id)
 - Customer::hydrat* Insert into database informations related to the *Customer* who is specified by id
- void **remove** ()
 - Customer::remove* Remove the current customer.
- QVariantHash **getDataMap** ()
 - getDataMap* Get all data of model with a HashMap key/value
- QString **getPath** () const
 - Customer::getPath* Return the path of the workspace for the current *Customer*.
- QString **getNameFolder** () const
 - Customer::getNameFolder* Return the name of the current *Customer*'s folder in the workspace.
- double **getTurnover** () const
 - Customer::getTurnover* Return the turnover of the customer money that customer pay, revenue sales.
- QPixmap * **getImage** ()
 - Customer::getImage* Return the compagny image.
- void **setImage** (QPixmap *image)
 - Customer::setImage* Change the current image by the new image
- bool **isArchived** () const
 - Customer::isArchived* Return if the *Customer* is archived.
- void **setIsArchived** (const bool isArchived)
 - Customer::setIsArchived* set the isArchived parameter.

Additional Inherited Members

8.43.1 Detailed Description

The *Customer* class *Customer*.

Author

Antoine de Roquemaurel
Florent Berbie

8.43.2 Constructor & Destructor Documentation

8.43.2.1 Models::Customer::Customer (int id)

Customer::Customer Construct a *Customer* who is specified by *id*

Parameters

<i>id</i>	<i>Customer</i> identify
-----------	--------------------------

8.43.3 Member Function Documentation

8.43.3.1 void Models::Customer::commit () [virtual]

Customer::Customer Construct a *People* who is specified by *id*

Parameters

<i>id</i>	Customer identify
-----------	-----------------------------------

Implements [Models::IModel](#).

8.43.3.2 QVariantHash Models::Customer::getDataMap () [virtual]

getDataMap Get all data of model with a HashMap key/value

Returns

Model's data

Implements [Models::IModel](#).

8.43.3.3 QPixmap * Models::Customer::getImage ()

[Customer::getImage](#) Return the compagny image.

Returns

compagny image

8.43.3.4 QString Models::Customer::getNameFolder () const

[Customer::getNameFolder](#) Return the name of the current [Customer](#)'s folder in the workspace.

Returns

name of the [Customer](#)'s folder

8.43.3.5 QString Models::Customer::getPath () const

[Customer::getPath](#) Return the path of the workspace for the current [Customer](#).

Returns

workspace path

8.43.3.6 double Models::Customer::getTurnover () const

[Customer::getTurnover](#) Return the turnover of the customer money that customer pay, revenue sales.

Returns

turnover

8.43.3.7 void Models::Customer::hydrat (int *id*) [virtual]

[Customer::hydrat](#) Insert into database informations related to the [Customer](#) who is specified by *id*

Parameters

<i>id</i>	Customer identify
-----------	-----------------------------------

Implements [Models::IModel](#).

8.43.3.8 bool Models::Customer::isArchived () const

[Customer::isArchived](#) Return if the [Customer](#) is archived.

Returns

true or false

8.43.3.9 void Models::Customer::setImage (QPixmap * *image*) [virtual]

[Customer::setImage](#) Change the current image by the new *image*

Parameters

<i>image</i>	New image
--------------	-----------

Reimplemented from [Models::People](#).

8.43.3.10 void Models::Customer::setIsArchived (const bool *isArchived*)

[Customer::setIsArchived](#) set the *isArchived* parameter.

Parameters

<i>isArchived</i>	
-------------------	--

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/models/customer.h
- /home/travis/build/FACT-Team/FactDev/src/models/customer.cpp

8.44 Gui::Widgets::CustomerContextualMenu Class Reference

Display contextual menu on a customer.

```
#include <customercontextualmenu.h>
```

Inheritance diagram for Gui::Widgets::CustomerContextualMenu:



Public Member Functions

- [CustomerContextualMenu](#) (QWidget *w=0)
[CustomerContextualMenu::CustomerContextualMenu](#) Construct a new contextual menu.
- [~CustomerContextualMenu](#) ()
[CustomerContextualMenu::~Destruct](#) the contextual menu.

8.44.1 Detailed Description

Display contextual menu on a customer.

Author

Antoine de Roquemaurel

8.44.2 Constructor & Destructor Documentation

8.44.2.1 Gui::Widgets::CustomerContextualMenu::CustomerContextualMenu (QWidget * w = 0)

[CustomerContextualMenu::CustomerContextualMenu](#) Construct a new contextual menu.

Parameters

<i>w</i>	Parent
----------	--------

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/customercontextualmenu.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/customercontextualmenu.cpp

8.45 Databases::CustomerDatabase Class Reference

The [CustomerDatabase](#) class Customer table database.

```
#include <customerdatabase.h>
```

Inheritance diagram for Databases::CustomerDatabase:



Public Member Functions

- [WdgModels::CustomersTableModel * getCustomersTable](#) (QString filter="") throw (DbException*)
[CustomerDatabase::getCustomersTable](#) Return an item model of customers for QTableView.
- [QStandardItemModel * getTree](#) (QString filter="") throw (DbException*)
[CustomerDatabase::getTree](#) Return an item model of customers for QTree.
- [QSharedPointer< Models::Customer > getCustomer](#) (const int pld)
[CustomerDatabase::getCustomer](#) get informations about the customer identified by pld
- [int addCustomer](#) (const [Models::Customer](#) &)
[CustomerDatabase::addCustomer](#) Add the customer pCustomer to the database.
- [void updateCustomer](#) ([Customer](#) &)
[CustomerDatabase::updateCustomer](#) Update informations about the customer pCustomer
- [void removeCustomer](#) (const int pld)
[CustomerDatabase::removeCustomer](#) Remove the customer with the id pld
- [int getNbCustomers](#) ()
[CustomerDatabase::getNbCustomers](#) Return the number of customers existing.
- [QStandardItem * getItemRoot](#) ()

- [CustomerDatabase::getItemRoot](#)* Return the first item for the *QStandardItemModel*.
- *QStandardItem* * [getItemCustomer](#) (*QSqlQuery* q1)
[CustomerDatabase::getItemCustomer](#) Return the customer item for the *QStandardItemModel*.
- *QStandardItem* * [getItemProject](#) (*QSqlQuery* q2)
[CustomerDatabase::getItemProject](#) Return the project item for the *QStandardItemModel*.
- *QSharedPointer*< [Models::Customer](#) > [getCustomer](#) (*QSqlQuery* &q)
[CustomerDatabase::getCustomer](#) Add the element of the q request and return their.
- void [updateCustomer](#) (*QSqlQuery* &q, [Customer](#) &pCustomer)
[CustomerDatabase::updateCustomer](#) Update customer data according to the request q
- *QPixmap* [getCustomerImage](#) (const int pld)
[CustomerDatabase::getCustomerImage](#) Return a Customer image.
- void [setCustomerImage](#) ([Customer](#) &pCustomer)
[CustomerDatabase::setCustomerImage](#) Change the image of the customer pCustomer
- *QList*< [Customer](#) > [getCustomers](#) ()
[CustomerDatabase::getCustomers](#) Return all the customers.

Static Public Member Functions

- static [CustomerDatabase](#) * [instance](#) () throw (DbException*)
[CustomerDatabase::instance](#) Return an instance of [CustomerDatabase](#)

Additional Inherited Members

8.45.1 Detailed Description

The [CustomerDatabase](#) class Customer table database.

Author

Antoine de Roquemaurel
Manantsoa Razanajatovo
Florent Berbie

See Also

[Database](#)
[Customer](#)

8.45.2 Member Function Documentation

8.45.2.1 int [Databases::CustomerDatabase::addCustomer](#) (const [Models::Customer](#) & pCustomer)

[CustomerDatabase::addCustomer](#) Add the customer pCustomer to the database.

Returns

customer id

8.45.2.2 *QSharedPointer*< [Models::Customer](#) > [Databases::CustomerDatabase::getCustomer](#) (const int pld)

[CustomerDatabase::getCustomer](#) get informations about the customer identified by pld

Parameters

<i>pld</i>	customer id
------------	-------------

Returns

the Customer

8.45.2.3 `QSharedPointer< Models::Customer > Databases::CustomerDatabase::getCustomer (QSqlQuery & q)`

[CustomerDatabase::getCustomer](#) Add the element of the *q* request and return their.

Parameters

<i>q</i>	SQL request
----------	-------------

Returns

a customer formed according to QSharedPointer

8.45.2.4 `QPixmap Databases::CustomerDatabase::getCustomerImage (const int pld)`

[CustomerDatabase::getCustomerImage](#) Return a Customer image.

Parameters

<i>pld</i>	Customer id
------------	-------------

Returns

Customer image

8.45.2.5 `QList< Customer > Databases::CustomerDatabase::getCustomers ()`

[CustomerDatabase::getCustomers](#) Return all the customers.

Returns

QList of customers

8.45.2.6 `WdgModels::CustomersTableModel * Databases::CustomerDatabase::getCustomersTable (QString filter = " ") throw DbException *`

[CustomerDatabase::getCustomersTable](#) Return an item model of customers for QTableView.

Parameters

<i>filter</i>	Select only customers who are specified by <i>filter</i>
---------------	--

Exceptions

<i>DbException</i>

Returns

QStandardItemModel an item model for QTableView

8.45.2.7 QStandardItem * Databases::CustomerDatabase::getItemCustomer (QSqlQuery *q1*)

[CustomerDatabase::getItemCustomer](#) Return the customer item for the QStandardItemModel.

Parameters

<i>q1</i>	the row of the sql query for customers
-----------	--

Returns

QStandardItem an item for QTree (level/depth 1)

8.45.2.8 QStandardItem * Databases::CustomerDatabase::getItemProject (QSqlQuery *q2*)

[CustomerDatabase::getItemProject](#) Return the project item for the QStandardItemModel.

Parameters

<i>q2</i>	the row of the sql query for projects
-----------	---------------------------------------

Returns

QStandardItem an item for QTree (level/depth 2)

8.45.2.9 QStandardItem * Databases::CustomerDatabase::getItemRoot ()

[CustomerDatabase::getItemRoot](#) Return the first item for the QStandardItemModel.

Returns

QStandardItem an item for QTree (level/depth 0)

8.45.2.10 int Databases::CustomerDatabase::getNbCustomers ()

[CustomerDatabase::getNbCustomers](#) Return the number of customers existing.

Returns

number of customers

8.45.2.11 QStandardItemModel * Databases::CustomerDatabase::getTree (QString *filter* = " ") throw DbException *)

[CustomerDatabase::getTree](#) Return an item model of customers for QTree.

Parameters

<i>filter</i>	Select only customers who are specified by <i>filter</i>
---------------	--

Exceptions

<i>DbException</i>	
--------------------	--

Returns

QStandardItemModel an item model for QTreeView

8.45.2.12 **CustomerDatabase * Databases::CustomerDatabase::instance () throw DbException *** [static]

[CustomerDatabase::instance](#) Return an instance of [CustomerDatabase](#)

See Also

[DbException](#)

Returns

Instance of [CustomerDatabase](#)

8.45.2.13 **void Databases::CustomerDatabase::removeCustomer (const int *pld*)**

[CustomerDatabase::removeCustomer](#) Remove the customer with the id *pld*

Parameters

<i>pld</i>	customer id
------------	-------------

8.45.2.14 **void Databases::CustomerDatabase::setCustomerImage (Models::Customer & *pCustomer*)**

[CustomerDatabase::setCustomerImage](#) Change the image of the customer *pCustomer*

Parameters

<i>pCustomer</i>	Customer
------------------	----------

8.45.2.15 **void Databases::CustomerDatabase::updateCustomer (QSqlQuery & *q*, Customer & *pCustomer*)**

[CustomerDatabase::updateCustomer](#) Update customer data according to the request *q*

Parameters

<i>q</i>	SQL request
----------	-------------

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/database/customerdatabase.h
- /home/travis/build/FACT-Team/FactDev/src/database/customerdatabase.cpp

8.46 CustomerDatabaseTest Class Reference

Inheritance diagram for CustomerDatabaseTest:



The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/tests/database/customerdatabasetest.h
- /home/travis/build/FACT-Team/FactDev/tests/database/customerdatabasetest.cpp

8.47 Gui::Widgets::CustomerDataWidget Class Reference

Class for display info of a customer.

```
#include <customerdatawidget.h>
```

Inheritance diagram for Gui::Widgets::CustomerDataWidget:



Public Member Functions

- [CustomerDataWidget](#) (QWidget *parent=0)
CustomerDataWidget::CustomerDataWidget Construct a [CustomerDataWidget](#).
- void [printUserData](#) ()
CustomerDataWidget::printUserData Print Data of current user.
- void [printInformations](#) (int id)
CustomerDataWidget::printInformations Print Data of customer id.

8.47.1 Detailed Description

Class for display info of a customer.

Author

8.47.2 Constructor & Destructor Documentation

8.47.2.1 [Gui::Widgets::CustomerDataWidget::CustomerDataWidget](#) ([QWidget](#) * *parent* = 0) [explicit]

[CustomerDataWidget::CustomerDataWidget](#) Construct a [CustomerDataWidget](#).

Parameters

<i>parent</i>	Widget parent
---------------	---------------

8.47.3 Member Function Documentation

8.47.3.1 void Gui::Widgets::CustomerDataWidget::printInformations (int *id*)

[CustomerDataWidget::printInformations](#) Print Data of customer id.

Parameters

<i>id</i>	of customer to print
-----------	----------------------

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/customerdatawidget.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/customerdatawidget.cpp

8.48 CustomerModelTest Class Reference

Inheritance diagram for CustomerModelTest:



Public Member Functions

- void **setup** ()

The documentation for this class was generated from the following files:


- /home/travis/build/FACT-Team/FactDev/tests/models/customermodeltest.h
- /home/travis/build/FACT-Team/FactDev/tests/models/customermodeltest.cpp

8.49 Gui::Widgets::WdgModels::CustomersTableModel Class Reference

The [CustomersTableModel](#) class for a customer table.

```
#include <customerstablemodel.h>
```

Inheritance diagram for Gui::Widgets::WdgModels::CustomersTableModel:



Public Member Functions

- [CustomersTableModel](#) (QObject *parent=0)
[CustomersTableModel::CustomersTableModel](#) Construct a [CustomersTableModel](#).
- int [rowCount](#) (const QModelIndex &) const
[CustomersTableModel::rowCount](#) Number of customers row.
- int [columnCount](#) (const QModelIndex &) const
[CustomersTableModel::columnCount](#) Number of column of a customer.
- QVariant [data](#) (const QModelIndex &index, int role=Qt::DisplayRole) const
[CustomersTableModel::data](#) Obtains data of a specify cell.
- QVariant [headerData](#) (int section, Qt::Orientation orientation, int role=Qt::DisplayRole) const
[CustomersTableModel::headerData](#) Obtains header title of table.
- bool [setData](#) (const QModelIndex &index, const QVariant &value, int role=Qt::EditRole)
[CustomersTableModel::setData](#) Change data of a cell.
- void [append](#) (const [Customer](#) &customer)
[CustomersTableModel::append](#) Add a new line in table.
- void [remove](#) (const int i)
[CustomersTableModel::remove](#) Remove a line.
- Qt::ItemFlags [flags](#) (const QModelIndex &index) const
[CustomersTableModel::flags](#) Differents table flags.
- int [count](#) ()
[CustomersTableModel::count](#) Number of customers in table.
- QList< [Customer](#) > [getCustomers](#) () const
[CustomersTableModel::getCustomers](#) Return the list of customers.

8.49.1 Detailed Description

The [CustomersTableModel](#) class for a customer table.

Author

Florent Berbie

See Also

[Customer](#)

8.49.2 Constructor & Destructor Documentation

8.49.2.1 Gui::Widgets::WdgModels::CustomersTableModel::CustomersTableModel (QObject * parent = 0)

[CustomersTableModel::CustomersTableModel](#) Construct a [CustomersTableModel](#).

Parameters

<i>parent</i>	Parent widget
---------------	---------------

8.49.3 Member Function Documentation

8.49.3.1 void Gui::Widgets::WdgModels::CustomersTableModel::append (const Customer & customer)

[CustomersTableModel::append](#) Add a new line in table.

Parameters

<i>Customer</i>	The new customer
-----------------	------------------

8.49.3.2 `int Gui::Widgets::WdgModels::CustomersTableModel::columnCount (const QModelIndex &) const`

[CustomersTableModel::columnCount](#) Number of column of a customer.

Returns

The number of column

8.49.3.3 `int Gui::Widgets::WdgModels::CustomersTableModel::count ()`

[CustomersTableModel::count](#) Number of customers in table.

Returns

The number of customers

8.49.3.4 `QVariant Gui::Widgets::WdgModels::CustomersTableModel::data (const QModelIndex & index, int role = Qt::DisplayRole) const`

[CustomersTableModel::data](#) Obtains data of a specify cell.

Parameters

<i>index</i>	The cell who we want data
<i>role</i>	The role of set

Returns

The data of cell

8.49.3.5 `Qt::ItemFlags Gui::Widgets::WdgModels::CustomersTableModel::flags (const QModelIndex & index) const`

[CustomersTableModel::flags](#) Differents table flags.

Parameters

<i>index</i>	The cell who we want to know flags
--------------	------------------------------------

Returns

Flags

8.49.3.6 `QList< Customer > Gui::Widgets::WdgModels::CustomersTableModel::getCustomers () const`

[CustomersTableModel::getCustomers](#) Return the list of customers.

Returns

list of Customers

8.49.3.7 QVariant Gui::Widgets::WdgModels::CustomersTableModel::headerData (int *section*, Qt::Orientation *orientation*, int *role* = Qt::DisplayRole) const

[CustomersTableModel::headerData](#) Obtains header title of table.

Parameters

<i>section</i>	The number of column
<i>orientation</i>	The table orientation
<i>role</i>	

Returns

The Title header of column

8.49.3.8 void Gui::Widgets::WdgModels::CustomersTableModel::remove (const int *i*)

[CustomersTableModel::remove](#) Remove a line.

Parameters

<i>i</i>	The number of line to remove
----------	------------------------------

8.49.3.9 int Gui::Widgets::WdgModels::CustomersTableModel::rowCount (const QModelIndex &) const

[CustomersTableModel::rowCount](#) Number of customers row.

Returns

The number of customers

8.49.3.10 bool Gui::Widgets::WdgModels::CustomersTableModel::setData (const QModelIndex & *index*, const QVariant & *value*, int *role* = Qt::EditRole)

[CustomersTableModel::setData](#) Change data of a cell.

Parameters

<i>index</i>	The cell to change data
<i>value</i>	The new value
<i>role</i>	The role of cell

Returns

True if we could edit

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/widgetmodels/customerstablemodel.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/widgetmodels/customerstablemodel.cpp

8.50 Databases::Database Class Reference

The [Database](#) class Master class for all database access.

```
#include <database.h>
```

Inheritance diagram for Databases::Database:



Public Member Functions

- QString [lastError](#) (const QSqlQuery &q) const
Database::lastError Return an error message on the last error occurred during the SQL request q
- void [testCases](#) ()
Database::testCases Realise a test cases.
- void [executeFile](#) (QString pName)
Database::executerFichier Exeute a specified file named pName
- void [openTransaction](#) ()
Database::openTransaction Open new transaction.
- void [closeTransaction](#) ()
Database::closeTransaction Close current transaction.
- void [close](#) ()
Database::close Close database access.
- void [open](#) ()
Database::open Open database.
- [~Database](#) ()
Database::~Database Suppression object, and close database access.
- void [setDatabase](#) (QSqlDatabase sql)
Database::setDatabase Set database.
- void [updateBillingNumber](#) ()
Database::updateBillingNumber Update the billing number.
- void [cleanDatabase](#) ()
Database::clearDatabase Drop alls tables of [Database](#) WARNING: We can't restore data after.
- void [changeDatabase](#) (Databases::DbType dbType)
changeDatabase Change the current database : mysql to sqlite or sqlite to mysql

Static Public Member Functions

- static [Database](#) * [instance](#) (bool tests=false) throw (DbException*)
Database::getInstance Return an instance of [Database](#).

Protected Member Functions

- [Database](#) (bool tests=false) throw (DbException*)
Database::Database [Database](#) is a singleton.
- QVariant [value](#) (const QSqlQuery &q, const QString &champ) const
Database::valeur Value of database field.

Protected Attributes

- QSettings * [_settings](#)
settings
- QSqlDatabase [mDatabase](#)
contains Database
- QList< [Database](#) * > [_instances](#)
List of instances.

Static Protected Attributes

- static [Database](#) * `_instance` = 0
Instance.
- static bool `_dbInstance` = 0
an instance of db is open
- static bool `isOpen` = false
[Database](#) is open.
- static bool `_isMysql` = false

8.50.1 Detailed Description

The [Database](#) class Master class for all database access.

Author

Antoine de Roquemaurel

8.50.2 Member Function Documentation

8.50.2.1 void `Databases::Database::changeDatabase (Databases::DbType dbType)`

`changeDatabase` Change the current database : mysql to sqlite or sqlite to mysql

Parameters

<i>dbType</i>	: The new database type, Sqlite or Mysql
---------------	--

8.50.2.2 void `Databases::Database::executeFile (QString pName)`

`Database::executerFichier` Exeute a specified file named *pName*

Parameters

<i>pNom</i>	File name
-------------	-----------

8.50.2.3 `Database * Databases::Database::instance (bool tests = false) throw DbException *` `[static]`

`Database::getInstance` Return an instance of [Database](#).

Returns

Instance of [Database](#)

8.50.2.4 `QString Databases::Database::lastError (const QSqlQuery & q) const` `[inline]`

`Database::lastError` Return an error message on the last error occurred during the SQL request *q*

Parameters

<i>q</i>	SQL request
----------	-------------

Returns

an error message

8.50.2.5 void Databases::Database::setDatabase (QSqlDatabase *sql*)

[Database::setDatabase](#) Set database.

Parameters

<i>sql</i>	The new database
------------	------------------

8.50.2.6 QVariant Databases::Database::value (const QSqlQuery & *q*, const QString & *champ*) const [protected]

Database::valeur Value of database field.

Parameters

<i>q</i>	Query
<i>champ</i>	Field

Returns

The value

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/database/database.h
- /home/travis/build/FACT-Team/FactDev/src/database/database.cpp

8.51 Gui::Widgets::DatabaseSettingsWidget Class Reference

The [DatabaseSettingsWidget](#) class Windows of database settings.

```
#include <databasesettingswidget.h>
```

Inheritance diagram for Gui::Widgets::DatabaseSettingsWidget:



Public Slots

- bool [isValid](#) ()
DatabaseSettingsWidget::isValid Return TRUE if all fields are correctly inputed else FALSE.
- void [checkRepeatPassword](#) (QString text)
DatabaseSettingsWidget::checkRepeatLogin Check if the second login field is the same than the first.
- void [userInterfaceChanged](#) ()
DatabaseSettingsWidget::userInterfaceChanged User interface has changed.

Signals

- void [textfieldChanged](#) ()
DatabaseSettingsWidget::textfieldChanged Signal which indicates if a fieldtext has changed.

Public Member Functions

- [DatabaseSettingsWidget](#) (QWidget *parent=0)
[DatabaseSettingsWidget::DatabaseSettingsWidget](#) Construct a [DatabaseSettingsWidget](#).
- void [fillFields](#) ()
[DatabaseSettingsWidget::fillFields](#) Complete fields with a default value for field Database name, Username, IP address and port.
- QString [getDatabaseName](#) ()
[DatabaseSettingsWidget::getDatabaseName](#) Return the database name.
- QString [getLogin](#) ()
[DatabaseSettingsWidget::getLogin](#) Return the login of the user.
- QString [getPassword](#) ()
[DatabaseSettingsWidget::getPassword](#) Return the password of the user.
- QString [getDomainNameOrIP](#) ()
[DatabaseSettingsWidget::getDomainNameOrIP](#) Return the domain name or IP address on the machine where is the database.
- QString [getPort](#) ()
[DatabaseSettingsWidget::getPort](#) Return the port of the database.

8.51.1 Detailed Description

The [DatabaseSettingsWidget](#) class Windows of database settings.

Author

8.51.2 Constructor & Destructor Documentation

8.51.2.1 [Gui::Widgets::DatabaseSettingsWidget::DatabaseSettingsWidget](#) ([QWidget](#) * *parent* = 0) [explicit]

[DatabaseSettingsWidget::DatabaseSettingsWidget](#) Construct a [DatabaseSettingsWidget](#).

Parameters

<i>parent</i>	Parent widget of this windows
---------------	-------------------------------

8.51.3 Member Function Documentation

8.51.3.1 [QString](#) [Gui::Widgets::DatabaseSettingsWidget::getDatabaseName](#) ()

[DatabaseSettingsWidget::getDatabaseName](#) Return the database name.

Returns

Database name

8.51.3.2 [QString](#) [Gui::Widgets::DatabaseSettingsWidget::getDomainNameOrIP](#) ()

[DatabaseSettingsWidget::getDomainNameOrIP](#) Return the domain name or IP address on the machine where is the database.

Returns

Domain name or IP address

8.51.3.3 QString Gui::Widgets::DatabaseSettingsWidget::getLogin ()

[DatabaseSettingsWidget::getLogin](#) Return the login of the user.

Returns

Login of the user

8.51.3.4 QString Gui::Widgets::DatabaseSettingsWidget::getPassword ()

[DatabaseSettingsWidget::getPassword](#) Return the password of the user.

Returns

User password

8.51.3.5 QString Gui::Widgets::DatabaseSettingsWidget::getPort ()

[DatabaseSettingsWidget::getPort](#) Return the port of the database.

Returns

Database port

8.51.3.6 bool Gui::Widgets::DatabaseSettingsWidget::isValid () [slot]

[DatabaseSettingsWidget::isValid](#) Return TRUE if all fields are correctly inputed else FALSE.

Returns

boolean

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/databasesettingswidget.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/databasesettingswidget.cpp

8.52 Exceptions::DbException Class Reference

The [DbException](#) class for database exception : queries, db file, ...

```
#include <dbexception.h>
```

Inheritance diagram for Exceptions::DbException:



Public Member Functions

- [DbException](#) (const QString fct, const QString fctName, const QString logError, float errorCode)
DbException::DbException. Construct a DbException.
- virtual [~DbException](#) () throw ()
~DbException
- void [popupMessage](#) (QWidget *parent)
DbException::popupMessage. Display a popup message with the message error.

8.52.1 Detailed Description

The [DbException](#) class for database exception : queries, db file, ...

Author

Antoine de Roquemaurel

8.52.2 Constructor & Destructor Documentation

8.52.2.1 Exceptions::DbException::DbException (const QString *fct*, const QString *fctName*, const QString *logError*, float *errorCode*)

[DbException::DbException](#). Construct a [DbException](#).

Parameters

<i>userError</i>	ClassName of error
<i>fctName</i>	Function name
<i>logError</i>	Message error
<i>errorCode</i>	Code of error

8.52.3 Member Function Documentation

8.52.3.1 void Exceptions::DbException::popupMessage (QWidget * *parent*)

[DbException::popupMessage](#). Display a popup message with the message error.

Parameters

<i>parent</i>	
---------------	--

The documentation for this class was generated from the following files:


- /home/travis/build/FACT-Team/FactDev/src/exceptions/dbexception.h
- /home/travis/build/FACT-Team/FactDev/src/exceptions/dbexception.cpp

8.53 Gui::Dialogs::DialogAddCustomer Class Reference

The [DialogAddCustomer](#) class Window to add or modify a Customer.

```
#include <dialogaddcustomer.h>
```

Inheritance diagram for Gui::Dialogs::DialogAddCustomer:



Public Slots

- void [checkFields](#) ()
[DialogAddCustomer::checkFields](#) Check if fields are valid.

Public Member Functions

- [DialogAddCustomer](#) (int id=0, QWidget *parent=0)
[DialogAddCustomer::DialogAddCustomer](#) Construct a window to add/modify a Customer.
- void [fillFields](#) ()
[DialogAddCustomer::fillFields](#) If the Customer exits, fill line edits with the data of the current Customer.
- void [accept](#) ()
[DialogAddCustomer::accept](#) Valid data inputed by user and add these data in Database.
- void [reject](#) ()
[DialogAddCustomer::reject](#) Cancel the operation and close the windows.

8.53.1 Detailed Description

The [DialogAddCustomer](#) class Window to add or modify a Customer.

Author

8.53.2 Constructor & Destructor Documentation

8.53.2.1 [Gui::Dialogs::DialogAddCustomer::DialogAddCustomer](#) (int *id* = 0, QWidget * *parent* = 0) [explicit]

[DialogAddCustomer::DialogAddCustomer](#) Construct a window to add/modify a Customer.

Parameters

<i>id</i>	Customer id
<i>parent</i>	QWidget parent

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/dialogs/dialogaddcustomer.h
- /home/travis/build/FACT-Team/FactDev/src/gui/dialogs/dialogaddcustomer.cpp

8.54 Utils::Directories Class Reference

Static Public Member Functions

- static QString [makeDirectory](#) (QDir &directory, const QString path, const QString folder) throw (Exceptions::FileException*)
[MainWindow::makeDirectory](#) If not exists make a new directory folder

8.54.1 Member Function Documentation

8.54.1.1 `QString Utils::Directories::makeDirectory (QDir & directory, const QString path, const QString folder) throw Exceptions::FileException *)` `[static]`

MainWindow::makeDirectory If not exists make a new directory *folder*

Parameters

<i>path</i>	Return the path of the folder just created
<i>folder</i>	Folder name to create

Returns

Path of the folder just created

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/Utils/directories.h
- /home/travis/build/FACT-Team/FactDev/src/Utils/directories.cpp

8.55 Utils::Double Class Reference

The `Double` class Utils functions for `Double` calculs.

```
#include <double.h>
```

Static Public Member Functions

- static double `round` (double *n*, unsigned int *d*)
round Roud a double value to d decimals
- static double `round` (double *n*, unsigned int *d*)

8.55.1 Detailed Description

The `Double` class Utils functions for `Double` calculs.

8.55.2 Member Function Documentation

8.55.2.1 `double Utils::Double::round (double n, unsigned int d)` `[static]`

`round` Roud a double value to d decimals

Parameters

<i>n</i>	The number
<i>d</i>	The number of decimals who you want

Returns

The rounded value

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/Utils/double.h
- /home/travis/build/FACT-Team/FactDev/src/Utils/double.cpp

8.56 Gui::Widgets::Delegates::DoubleSpinBoxDelegate Class Reference

The [DoubleSpinBoxDelegate](#) class.

```
#include <doublespinboxdelegate.h>
```

Inheritance diagram for Gui::Widgets::Delegates::DoubleSpinBoxDelegate:



Public Member Functions

- [DoubleSpinBoxDelegate](#) (QObject *parent=0)
[DoubleSpinBoxDelegate::DoubleSpinBoxDelegate.](#)
- QWidget * [createEditor](#) (QWidget *parent, const QStyleOptionViewItem &option, const QModelIndex &index) const
[DoubleSpinBoxDelegate::createEditor](#) Return a *ComboBox* specified by index item defined by the parent widget and style option which are used to control how the editor widgets appears.
- void [setEditorData](#) (QWidget *editor, const QModelIndex &index) const
[DoubleSpinBoxDelegate::setEditorData](#) Sets the data to be displayed and edited by the editor from the data model item specified by the model index
- void [setModelData](#) (QWidget *editor, QAbstractItemModel *model, const QModelIndex &index) const
[DoubleSpinBoxDelegate::setEditorData](#) Sets the data to be displayed and edited by the editor from the data model item specified by the model index
- void [updateEditorGeometry](#) (QWidget *editor, const QStyleOptionViewItem &option, const QModelIndex &index) const
[DoubleSpinBoxDelegate::updateEditorGeometry](#) Update the editor for the item specified by index according to the style option given.

8.56.1 Detailed Description

The [DoubleSpinBoxDelegate](#) class.

Author

Florent Berbie

8.56.2 Constructor & Destructor Documentation

8.56.2.1 Gui::Widgets::Delegates::DoubleSpinBoxDelegate::DoubleSpinBoxDelegate (QObject * parent = 0)

[DoubleSpinBoxDelegate::DoubleSpinBoxDelegate.](#)

Parameters

<i>parent</i>	
---------------	--

8.56.3 Member Function Documentation

8.56.3.1 `QWidget * Gui::Widgets::Delegates::DoubleSpinBoxDelegate::createEditor (QWidget * parent, const QStyleOptionViewItem & option, const QModelIndex & index) const`

[DoubleSpinBoxDelegate::createEditor](#) Return a ComboBox specified by *index* item defined by the *parent* widget and style *option* which are used to control how the editor widgets appears.

Parameters

<i>parent</i>	Widget parent
<i>option</i>	Option style
<i>index</i>	Index for editing

Returns

[DoubleSpinBoxDelegate](#)

8.56.3.2 `void Gui::Widgets::Delegates::DoubleSpinBoxDelegate::setEditorData (QWidget * editor, const QModelIndex & index) const`

[DoubleSpinBoxDelegate::setEditorData](#) Sets the data to be displayed and edited by the *editor* from the data model item specified by the model *index*

Parameters

<i>editor</i>	Data edited
<i>index</i>	Index of the model to edit

8.56.3.3 `void Gui::Widgets::Delegates::DoubleSpinBoxDelegate::setModelData (QWidget * editor, QAbstractItemModel * model, const QModelIndex & index) const`

[DoubleSpinBoxDelegate::setEditorData](#) Sets the data to be displayed and edited by the *editor* from the data model item specified by the model *index*

Parameters

<i>editor</i>	Data edited
<i>index</i>	Index of the model to edit

8.56.3.4 `void Gui::Widgets::Delegates::DoubleSpinBoxDelegate::updateEditorGeometry (QWidget * editor, const QStyleOptionViewItem & option, const QModelIndex & index) const`

[DoubleSpinBoxDelegate::updateEditorGeometry](#) Update the *editor* for the item specified by *index* according to the style *option* given.

Parameters

<i>editor</i>	Editor widget to update
<i>option</i>	Style option
<i>index</i>	Item index

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/delegates/doublespinboxdelegate.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/delegates/doublespinboxdelegate.cpp

8.57 FileChoseWidget Class Reference

Inheritance diagram for FileChoseWidget:



Public Member Functions

- **FileChoseWidget** (QWidget *parent=0)

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/filechosewidget.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/filechosewidget.cpp

8.58 Exceptions::FileException Class Reference

The [FileException](#) class for file/acess file exception.

```
#include <fileexception.h>
```

Public Member Functions

- [FileException](#) (const QString userError, const QString fctName, const QString logError, float errorCode)
[FileException::FileException](#). Construct a [FileException](#).
- void [popupMessage](#) (QWidget *parent)
[FileException::popupMessage](#). Display a popup message with the message error.

8.58.1 Detailed Description

The [FileException](#) class for file/acess file exception.

Author

Florent Berbie

8.58.2 Constructor & Destructor Documentation

8.58.2.1 Exceptions::FileException::FileException (const QString *userError*, const QString *fctName*, const QString *logError*, float *errorCode*)

[FileException::FileException](#). Construct a [FileException](#).

Parameters

<i>userError</i>	ClassName of error
<i>fctName</i>	Function name
<i>logError</i>	Message error

<i>errorCode</i>	Code of error
------------------	---------------

8.58.3 Member Function Documentation

8.58.3.1 void Exceptions::FileException::popupMessage (QWidget * *parent*)

[FileException::popupMessage](#). Display a popup message with the message error.

Parameters

<i>parent</i>	
---------------	--

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/exceptions/fileexception.h
- /home/travis/build/FACT-Team/FactDev/src/exceptions/fileexception.cpp

8.59 Generation Class Reference

Inheritance diagram for Generation:



The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/tests/generation.h
- /home/travis/build/FACT-Team/FactDev/tests/generation.cpp

8.60 Utils::HierarchicalSystem Class Reference

The [HierarchicalSystem](#) class Create class which contains hierarchical system of FactDev.

```
#include <hierarchichalsystem.h>
```

Public Member Functions

- [HierarchicalSystem](#) ()
HierarchicalSystem::HierarchicalSystem Construct a *HierarchicalSystem*.
- void [getAllProjects](#) ()
HierarchicalSystem::getAllProjects Get all projects and add each project to Customer linked.
- void [getAllBillings](#) ()
HierarchicalSystem::getAllBillings Get all billings and add each billing to Project linked.
- void [updateData](#) ()
HierarchicalSystem::updateData Update data on Customers, Projects, Billings.
- void [addProjectToCustomer](#) (Project *p, Customer c)
HierarchicalSystem::addProjectToCustomer Add the Project p to the Customer c
- void [addBillingToProject](#) (Billing *b, Project *p)

- [HierarchicalSystem::addBillingToProject](#) Add the Billing *b* to the Project *p*
- QMap< [Project *](#), [Customer](#) > [getCustomers](#) () const
[HierarchicalSystem::getCustomers](#) Return all customers and these projects linked.
- QMap< [Billing *](#), [Project *](#) > [getProjects](#) () const
[HierarchicalSystem::getProjects](#) Return all projects and these billing linked.

8.60.1 Detailed Description

The [HierarchicalSystem](#) class Create class which contains hierarchical system of FactDev.

Author

Florent Berbie

See Also

Customer
Project
Billing

8.60.2 Member Function Documentation

8.60.2.1 void Utils::HierarchicalSystem::addBillingToProject ([Billing *](#) *b*, [Project *](#) *p*)

[HierarchicalSystem::addBillingToProject](#) Add the Billing *b* to the Project *p*

Parameters

<i>b</i>	Billing
<i>p</i>	Project

8.60.2.2 void Utils::HierarchicalSystem::addProjectToCustomer ([Project *](#) *p*, [Customer](#) *c*)

[HierarchicalSystem::addProjectToCustomer](#) Add the Project *p* to the Customer *c*

Parameters

<i>p</i>	Project
<i>c</i>	Customer

8.60.2.3 QMap< [Project *](#), [Customer](#) > Utils::HierarchicalSystem::getCustomers () const

[HierarchicalSystem::getCustomers](#) Return all customers and these projects linked.

Returns

Projects linked to Customers

8.60.2.4 QMap< [Billing *](#), [Project *](#) > Utils::HierarchicalSystem::getProjects (void) const

[HierarchicalSystem::getProjects](#) Return all projects and these billing linked.

Returns

Billing linked to Projects

The documentation for this class was generated from the following files:


- /home/travis/build/FACT-Team/FactDev/src/utls/hierarchicalsystm.h
- /home/travis/build/FACT-Team/FactDev/src/utls/hierarchicalsystm.cpp

8.61 Gui::Widgets::CheckFields::ICheckField Class Reference

The [ICheckField](#) class Interface to check fields validity.

```
#include <icheckfield.h>
```

Inheritance diagram for Gui::Widgets::CheckFields::ICheckField:



Public Member Functions

- virtual bool [check](#) (QString text)=0
ICheckField::check Check if the field (line edit) is valid Return TRUE if the field is valid, else FALSE.

8.61.1 Detailed Description

The [ICheckField](#) class Interface to check fields validity.

8.61.2 Member Function Documentation

8.61.2.1 virtual bool Gui::Widgets::CheckFields::ICheckField::check (QString text) [pure virtual]

[ICheckField::check](#) Check if the field (line edit) is valid Return TRUE if the field is valid, else FALSE.

Returns

boolean Validity of the text

Implemented in [Gui::Widgets::CheckFields::CheckEmail](#), [Gui::Widgets::CheckFields::CheckPortNumber](#), [Gui::Widgets::CheckFields::CheckFieldsNumbers](#), [Gui::Widgets::CheckFields::CheckIpAddress](#), [Gui::Widgets::CheckFields::CheckWebsite](#), [Gui::Widgets::CheckFields::CheckLogin](#), [Gui::Widgets::CheckFields::CheckPhone](#), [Gui::Widgets::CheckFields::CheckPostalCode](#), [Gui::Widgets::CheckFields::CheckSiretNumber](#), [Gui::Widgets::CheckFields::CheckUntilField](#), [Gui::Widgets::CheckFields::CheckFieldsLetters](#), and [Gui::Widgets::CheckFields::CheckValidField](#).

The documentation for this class was generated from the following file:

- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/icheckfield.h

8.62 Gui::Utils::Image Class Reference

The [Image](#) class Contains generic methods on image formats.

```
#include <image.h>
```

Static Public Member Functions

- static QByteArray [imageToBytes](#) (QImage image, const QString ext="PNG")
Image::imageToBytes Return a QByteArray of the QImage image
- static QByteArray [pixmapToBytes](#) (const QPixmap pix, const QString ext="PNG")
Image::pixmapToBytes Return a QByteArray of the QPixmap image
- static QImage [pixmapToImage](#) (const QPixmap pix)
Image::pixmapToImage Return a QImage of QPixmap image
- static QPixmap [bytesToPixmap](#) (const QByteArray bytes)
Image::BytesToPixmap Return QPixmap from an array of bytes.

8.62.1 Detailed Description

The [Image](#) class Contains generic methods on image formats.

Author

8.62.2 Member Function Documentation

8.62.2.1 QPixmap Gui::Utils::Image::bytesToPixmap (const QByteArray bytes) [static]

Image::BytesToPixmap Return QPixmap from an array of bytes.

Parameters

<i>bytes</i>	Array of bytes
--------------	----------------

Returns

QPixmap from bytes

8.62.2.2 QByteArray Gui::Utils::Image::imageToBytes (QImage image, const QString ext = "PNG") [static]

[Image::imageToBytes](#) Return a QByteArray of the QImage image

Parameters

<i>image</i>	An image
<i>ext</i>	Extension file of the image (PNG as default value)

Returns

array of bytes from an **QImage** image

8.62.2.3 QByteArray Gui::Utils::Image::pixmapToBytes (const QPixmap pix, const QString ext = "PNG") [static]

[Image::pixmapToBytes](#) Return a QByteArray of the QPixmap image

Parameters

<i>pix</i>	An image
<i>ext</i>	Extension file of the image (PNG as default value)

Returns

array of bytes from an **QPixmap** image

8.62.2.4 QImage Gui::Utils::Image::pixmapToImage (const QPixmap *pix*) [static]

[Image::pixmapToImage](#) Return a QImage of QPixmap *image*

Parameters

<i>pix</i>	An image
------------	----------

Returns

QImage of pix

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/Utils/image.h
- /home/travis/build/FACT-Team/FactDev/src/gui/Utils/image.cpp

8.63 Models::IModel Class Reference

The [IModel](#) class.

```
#include <imodel.h>
```

Inheritance diagram for Models::IModel:



Public Member Functions

- virtual [~IModel](#) ()
~IModel Remove an instance of IModel
- virtual void [commit](#) ()=0
IModel::commit Update or insert data into the database.
- virtual void [hydrat](#) (int id)=0
IModel::hydrat Get data of the element which is specified by the identify id from the database.
- virtual void [remove](#) ()=0
IModel::remove Remove the current element in the database.
- virtual QVariantHash [getDataMap](#) ()=0
getDataMap Get all data of model with a HashMap key/value

- int [getId](#) () const
IModel::getId Return the identify of the element of the database.
- void [setId](#) (int id)
IModel::setId Replace the current identify by id
- bool [isToRemoved](#) () const
toRemoved return if object must be removed.
- void [setToRemoved](#) (bool toRemoved)
setToRemoved Change the flag for removed object

Protected Attributes

- int [_id](#)
Element identify.
- bool [_toRemoved](#)
Flag to know if the object must be removed.

8.63.1 Detailed Description

The [IModel](#) class.

Author

Antoine de Roquemaurel

8.63.2 Member Function Documentation

8.63.2.1 `virtual QVariantHash Models::IModel::getDataMap () [pure virtual]`

`getDataMap` Get all data of model with a HashMap key/value

Returns

Model's data

Implemented in [Models::Contributory](#), [Models::Billing](#), [Models::Project](#), [Models::User](#), and [Models::Customer](#).

8.63.2.2 `int Models::IModel::getId () const [inline]`

[IModel::getId](#) Return the identify of the element of the database.

Returns

identity

8.63.2.3 `virtual void Models::IModel::hydrat (int id) [pure virtual]`

[IModel::hydrat](#) Get data of the element which is specified by the identify *id* from the database.

Parameters

<i>id</i>	
-----------	--

Implemented in [Models::Billing](#), [Models::Project](#), [Models::Contributory](#), [Models::User](#), and [Models::Customer](#).

8.63.2.4 `bool Models::IModel::isToRemoved () const` [inline]

toRemoved return if object must be removed.

Returns

boolean

8.63.2.5 `void Models::IModel::setId (int id)` [inline]

[IModel::setId](#) Replace the current identify by *id*

Parameters

<i>id</i>	New identify
-----------	--------------

8.63.2.6 `void Models::IModel::setToRemoved (bool toRemoved)` [inline]

setToRemoved Change the flag for removed object

Parameters

<i>toRemoved</i>	The new flag
------------------	--------------

The documentation for this class was generated from the following file:

- /home/travis/build/FACT-Team/FactDev/src/models/imodel.h

8.64 Utils::ItemType Class Reference

The [ItemType](#) class Item type model.

```
#include <itemtype.h>
```

Public Member Functions

- [ItemType](#) (int type, QString name)
ItemType::ItemType Construct an Item type.
- QString [getName](#) () const
ItemType::getName Get item name.
- [Models::IModel](#) * [getModel](#) (int id)
ItemType::getModel Get the databasemodel of the [ItemType](#) according to this identity id
- void [setName](#) (const QString &name)
ItemType::setName Modify the item name.
- int [getType](#) () const
ItemType::getType Get the type of the current item.
- void [setType](#) (int type)
ItemType::setType Modify the type of the current item.

Static Public Attributes

- static const int [CUSTOMER](#) = 0
constant value assigned to Customer
- static const int [PROJECT](#) = 1
constant value assigned to Project
- static const int [BILLING](#) = 2
constant value assigned to Billing
- static const int [QUOTE](#) = 3
constant value assigned to Quote

8.64.1 Detailed Description

The [ItemType](#) class Item type model.

8.64.2 Constructor & Destructor Documentation

8.64.2.1 Utils::ItemType::ItemType (int *type*, QString *name*)

[ItemType::ItemType](#) Construct an Item type.

Parameters

<i>type</i>	Type of the item
<i>name</i>	Name of the item

8.64.3 Member Function Documentation

8.64.3.1 Models::IModel * Utils::ItemType::getModel (int *id*)

[ItemType::getModel](#) Get the databasemodel of the [ItemType](#) according to this identity *id*

Parameters

<i>id</i>	Item type identity
-----------	--------------------

Returns

database model

8.64.3.2 QString Utils::ItemType::getName () const

[ItemType::getName](#) Get item name.

Returns

item name

8.64.3.3 int Utils::ItemType::getType () const

[ItemType::getType](#) Get the type of the current item.

Returns

type of the current item

8.64.3.4 void Utils::ItemType::setName (const QString & name)

[ItemType::setName](#) Modify the item name.

Parameters

<i>name</i>	New Item name
-------------	---------------

8.64.3.5 void Utils::ItemType::setType (int type)

[ItemType::setType](#) Modify the type of the current item.

Parameters

<i>type</i>	New item type
-------------	---------------

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/utils/itemtype.h
- /home/travis/build/FACT-Team/FactDev/src/utils/itemtype.cpp

8.65 ItemTypeTest Class Reference

Inheritance diagram for ItemTypeTest:



The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/tests/utils/itemtypetest.h
- /home/travis/build/FACT-Team/FactDev/tests/utils/itemtypetest.cpp

8.66 Utils::Log Class Reference

The [Log](#) class for Simple management of log.

```
#include <log.h>
```

Public Member Functions

- void [write](#) (const QString text)
Log::write. Write log message in file.
- [Log](#) ()
Log::Log. *Log* is a singleton.

Static Public Member Functions

- static [Log](#) & [instance](#) (TypeLog type=INFO)
Log::instance. Return the instance of logger.

Friends

- [Log](#) & [operator<<](#) ([Log](#) &logger, const QString &text)
operator << for log writing

8.66.1 Detailed Description

The [Log](#) class for Simple management of log.

8.66.2 Member Function Documentation

8.66.2.1 [Log](#) & [Utils::Log::instance](#) ([TypeLog](#) *type* = INFO) [static]

[Log::instance](#). Return the instance of logger.

Parameters

<i>type</i>	Type of log : WARNING, INFO, ERROR
-------------	------------------------------------

Returns

Instance of logger.

8.66.2.2 void [Utils::Log::write](#) (const QString *text*)

[Log::write](#). Write log message in file.

Parameters

<i>text</i>	
-------------	--

8.66.3 Friends And Related Function Documentation

8.66.3.1 [Log](#) & [operator<<](#) ([Log](#) &*logger*, const QString &*text*) [friend]

[operator <<](#) for log writing

Parameters

<i>logger</i>	Instance of Logger
<i>text</i>	Text to write

Returns

New logger.

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/Utils/log.h
- /home/travis/build/FACT-Team/FactDev/src/Utils/log.cpp

8.67 Gui::MainWindow Class Reference

The [MainWindow](#) class Main Window of the software.

```
#include <mainwindow.h>
```

Inheritance diagram for Gui::MainWindow:



Public Slots

- void [addCustomer](#) ()
MainWindow::addCustomer open window to add a new customer.
- void [editCustomer](#) ()
MainWindow::editCustomer open window to modify a customer.
- void [removeCustomer](#) ()
MainWindow::removeCustomer open a popup to confirm the deletion of a customer, if ok remove the customer.
- void [archiveCustomer](#) ()
MainWindow::archiveCustomer open a pop-up to confirm the archiving of the customer, if ok archive the customer.
- void [addQuote](#) ()
MainWindow::addQuote open window to add a new quote.
- void [addBill](#) ()
MainWindow::addBill open window to add a new bill.
- void [billingsIsPaid](#) ()
MainWindow::billingsIsPaid Define the current billing as "paid".
- void [editUser](#) ()
MainWindow::editUser modify the user.
- void [search](#) (QString s)
MainWindow::search launch a new search.
- void [addProject](#) ()
MainWindow::addProject Create a new project for a customer.
- void [removeProject](#) ()
MainWindow::removeProject Remove a project for a customer.
- void [editProject](#) ()
MainWindow::editProject Modify the customer project.
- void [aboutQt](#) ()
MainWindow::aboutQt show Qt's details.
- void [aboutFact](#) ()
MainWindow::aboutFact show FACT's details (FACT team)
- void [aboutFactDev](#) ()
MainWindow::aboutFactDev() show FactDev's details (FactDev Software)
- void [aboutIcons](#) ()
MainWindow::aboutIcons() show icons's details.
- void [updateButtons](#) ()
updateButton Update all button to disable or enabled its
- void [editDoc](#) ()
MainWindow::editDoc Edit the quote or bill of the project.
- void [removeDoc](#) ()
MainWindow::removeDoc Remove the quote or bill of the project.
- void [copyDoc](#) ()

- [*MainWindow::copyDoc*](#) Copy all elements of a quote or a bill and Display these elements in a new quote or bill.
- void [`openPdf`](#) ()
[*MainWindow::openPdf*](#) Open the PDF file of the current Quote or Billing selected in the TableView.
- void [`computeTurnover`](#) ()
[*MainWindow::computeTurnover*](#) open window to allow computation of a period turnover.
- void [`globalStatistics`](#) ()
[*MainWindow::globalStatistics*](#).
- void [`customerStatistics`](#) ()
[*MainWindow::customerStatistics*](#).

Public Member Functions

- [`MainWindow`](#) (QWidget *parent=0)
[*MainWindow*](#): Construct a window.
- int [`getCurrentCustomerId`](#) ()
[*MainWindow::getCurrentCustomerId*](#) get the selected customer.
- int [`getCurrentProjectId`](#) ()
[*MainWindow::getCurrentProjectId*](#) get the selected project id.
- int [`getCurrentQuoteId`](#) ()
[*MainWindow::getCurrentQuoteId*](#) get the selected quote id.
- QString [`getCurrentCustomerName`](#) ()
[*MainWindow::getCurrentCustomerName*](#) get the selected customer name in the customers' table.
- QString [`getCurrentProjectName`](#) ()
[*MainWindow::getCurrentProjectName*](#) get the selected project name in the table of projects.
- int [`treeLevel`](#) ()
[*MainWindow::treeLevel*](#) return the level of the node selected in the tree.
- QModelIndex [`rootTree`](#) ()
[*MainWindow::rootTree*](#) return the root of the tree "Tous les clients".
- void [`addDoc`](#) (bool isBilling)
[*MainWindow::addDoc*](#) open window to add a new document.
- void [`resizeEvent`](#) (QResizeEvent *event)
[*MainWindow::resizeEvent*](#) Resize central TableView when you resize the [**MainWindow**](#)
- void [`responsiveCustomerTable`](#) ()
[*MainWindow::responsiveCustomerTable*](#) Resize the Customer TableView according it resolution.
- void [`responsiveProjectTable`](#) ()
[*MainWindow::responsiveProjectTable*](#) Resize the Project TableView according it resolution.
- void [`responsiveBillingTable`](#) ()
[*MainWindow::responsiveBillingTable*](#) Resize the Billing TableView according it resolution.

8.67.1 Detailed Description

The [`MainWindow`](#) class Main Window of the software.

Author

Everybody

8.67.2 Constructor & Destructor Documentation

8.67.2.1 Gui::MainWindow::MainWindow (QWidget *parent = 0) [explicit]

[*MainWindow*](#): Construct a window.

Parameters

<i>parent</i>	
---------------	--

8.67.3 Member Function Documentation

8.67.3.1 void Gui::MainWindow::addBill () [slot]

[MainWindow::addBill](#) open window to add a new bill.

See Also

AddQuoteDialog

8.67.3.2 void Gui::MainWindow::addDoc (bool *isBilling*)

[MainWindow::addDoc](#) open window to add a new document.

Parameters

<i>bool</i>	quote or bill
-------------	---------------

See Also

[addBill](#) [addQuote](#)

8.67.3.3 void Gui::MainWindow::addProject () [slot]

[MainWindow::addProject](#) Create a new project for a customer.

See Also

AddProjectDialog

8.67.3.4 void Gui::MainWindow::addQuote () [slot]

[MainWindow::addQuote](#) open window to add a new quote.

See Also

AddQuoteDialog

8.67.3.5 void Gui::MainWindow::editUser () [slot]

[MainWindow::editUser](#) modify the user.

See Also

UserDataDialog

8.67.3.6 `int Gui::MainWindow::getCurrentCustomerId ()`

[MainWindow::getCurrentCustomerId](#) get the selected customer.

Returns

id of the selected customer

8.67.3.7 `QString Gui::MainWindow::getCurrentCustomerName ()`

[MainWindow::getCurrentCustomerName](#) get the selected customer name in the customers' table.

Returns

name of the selected customer

8.67.3.8 `int Gui::MainWindow::getCurrentProjectId ()`

[MainWindow::getCurrentProjectId](#) get the selected project id.

Returns

id of the selected project

8.67.3.9 `QString Gui::MainWindow::getCurrentProjectName ()`

[MainWindow::getCurrentProjectName](#) get the selected project name in the table of projects.

Returns

name of the selected project

8.67.3.10 `int Gui::MainWindow::getCurrentQuoteId ()`

[MainWindow::getCurrentQuoteId](#) get the selected quote id.

Returns

id of the selected quote

8.67.3.11 `void Gui::MainWindow::resizeEvent (QResizeEvent * event)`

[MainWindow::resizeEvent](#) Resize central TableView when you resize the [MainWindow](#)

Parameters

<i>event</i>	Resize event
--------------	--------------

8.67.3.12 `QModelIndex Gui::MainWindow::rootTree ()`

[MainWindow::rootTree](#) return the root of the tree "Tous les clients".

Returns

QModelIndex

8.67.3.13 void Gui::MainWindow::search (QString *s*) [slot]

[MainWindow::search](#) launch a new search.

Parameters

<code>s</code>	text in field
----------------	---------------

8.67.3.14 `int Gui::MainWindow::treeLevel ()`

[MainWindow::treeLevel](#) return the level of the node selected in the tree.

Returns

integer, depth of the item in tree

The documentation for this class was generated from the following files:

- `/home/travis/build/FACT-Team/FactDev/src/gui/mainwindow/mainwindow.h`
- `/home/travis/build/FACT-Team/FactDev/src/gui/mainwindow/mainwindow.cpp`

8.68 Gui::Dialogs::MessageBox Class Reference

The [MessageBox](#) class Information window with message.

```
#include <messagebox.h>
```

Inheritance diagram for `Gui::Dialogs::MessageBox`:



Public Member Functions

- [MessageBox](#) (`QWidget *parent=0`)
[MessageBox::MessageBox](#) Construt a [MessageBox](#)
- void [aboutFact](#) ()
[MessageBox::aboutFact](#) Defines FACT team information.
- void [aboutFactDev](#) ()
[MessageBox::aboutFactDev](#) Defines FactDev software information.
- void [aboutIcons](#) ()
[MessageBox::aboutIcons](#) Defines icons theme information.
- void [setImage](#) (`QString img, int width=128, int height=128`)
[MessageBox::setImage](#) Add the icon img to the current window.
- void [setText](#) (`QString txt`)
[MessageBox::setText](#) Add the text txt to the current window.

Static Public Member Functions

- static void [showAboutFact](#) ()
[MessageBox::showAboutFact](#) Shows window about FACT team.
- static void [showAboutFactDev](#) ()
[MessageBox::showAboutFactDev](#) Shows window about FactDev software.
- static void [showAboutIcons](#) ()
[MessageBox::showAboutIcons](#) Shows about icons theme of FactDev software.

8.68.1 Detailed Description

The [MessageBox](#) class Information window with message.

Author

Florent Berbie

8.68.2 Constructor & Destructor Documentation

8.68.2.1 `Gui::Dialogs::MessageBox::MessageBox (QWidget * parent = 0) [explicit]`

[MessageBox::MessageBox](#) Construt a [MessageBox](#)

Parameters

<i>parent</i>	
---------------	--

8.68.3 Member Function Documentation

8.68.3.1 `void Gui::Dialogs::MessageBox::setImage (QString img, int width = 128, int height = 128)`

[MessageBox::setImage](#) Add the icon *img* to the current window.

Parameters

<i>img</i>	Icon
<i>width</i>	Icon width (default: 128)
<i>height</i>	Icon height (default: 128)

8.68.3.2 `void Gui::Dialogs::MessageBox::setText (QString txt)`

[MessageBox::setText](#) Add the text *txt* to the current window.

Parameters

<i>txt</i>	Text inside the current window
------------	--------------------------------

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/dialogs/messagebox.h
- /home/travis/build/FACT-Team/FactDev/src/gui/dialogs/messagebox.cpp

8.69 Parameters Class Reference

The [Parameters](#) class Class for simple user parameters.

```
#include <parameters.h>
```

Static Public Attributes

- static const QString [DB_FILENAME](#) = "database.db"
DB_FILENAME The database sqlite file name.
- static const double [VERSION](#) = 1.0
VERSION Version number of software.

8.69.1 Detailed Description

The [Parameters](#) class Class for simple user parameters.

Author

Antoine de Roquemaurel

8.69.2 Member Data Documentation

8.69.2.1 `const QString Parameters::DB_FILENAME = "database.db" [static]`

DB_FILENAME The database sqlite file name.

Database file name

8.69.2.2 `const double Parameters::VERSION = 1.0 [static]`

VERSION Version number of software.

Application version

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/parameters.h
- /home/travis/build/FACT-Team/FactDev/src/parameters.cpp

8.70 Mustache::PartialFileLoader Class Reference

```
#include <mustache.h>
```

Inheritance diagram for Mustache::PartialFileLoader:



Public Member Functions

- **PartialFileLoader** (const QString &basePath)
- virtual QString [getPartial](#) (const QString &name)

8.70.1 Detailed Description

A partial fetcher when loads templates from '<name>.mustache' files in a given directory.

Once a partial has been loaded, it is cached for future use.

8.70.2 Member Function Documentation

8.70.2.1 `QString PartialFileLoader::getPartial (const QString & name) [virtual]`

Returns the partial template with a given `name`.

Implements [Mustache::PartialResolver](#).

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/libs/qt-mustache/src/mustache.h
- /home/travis/build/FACT-Team/FactDev/src/libs/qt-mustache/src/mustache.cpp

8.71 Mustache::PartialMap Class Reference

```
#include <mustache.h>
```

Inheritance diagram for Mustache::PartialMap:



Public Member Functions

- **PartialMap** (const QHash< QString, QString > &partials)
- virtual QString [getPartial](#) (const QString &name)

8.71.1 Detailed Description

A simple partial fetcher which returns templates from a map of (partial name -> template)

8.71.2 Member Function Documentation

8.71.2.1 QString PartialMap::getPartial (const QString & name) [virtual]

Returns the partial template with a given `name`.

Implements [Mustache::PartialResolver](#).

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/libs/qt-mustache/src/mustache.h
- /home/travis/build/FACT-Team/FactDev/src/libs/qt-mustache/src/mustache.cpp

8.72 Mustache::PartialResolver Class Reference

```
#include <mustache.h>
```

Inheritance diagram for Mustache::PartialResolver:



Public Member Functions

- virtual QString [getPartial](#) (const QString &name)=0

8.72.1 Detailed Description

Interface for fetching template partials.

8.72.2 Member Function Documentation

8.72.2.1 virtual QString Mustache::PartialResolver::getPartial (const QString & *name*) [pure virtual]

Returns the partial template with a given *name*.

Implemented in [Mustache::PartialFileLoader](#), and [Mustache::PartialMap](#).

The documentation for this class was generated from the following file:

- /home/travis/build/FACT-Team/FactDev/src/libs/qt-mustache/src/mustache.h

8.73 Generator::PdfGenerator Class Reference

The [PdfGenerator](#) class Generator of PDF files.

```
#include <pdfgenerator.h>
```

Public Member Functions

- [PdfGenerator](#) (QString pdflatexPath="pdflatex")
PdfGenerator::PdfGenerator Construct a *PdfGenerator*.
- void [generate](#) (QString inputDir, QString filename)
PdfGenerator::generate Generate a PDF of the file named *filename* into the directory *inputDir*

8.73.1 Detailed Description

The [PdfGenerator](#) class Generator of PDF files.

8.73.2 Constructor & Destructor Documentation

8.73.2.1 Generator::PdfGenerator::PdfGenerator (QString *pdflatexPath* = "pdflatex")

[PdfGenerator::PdfGenerator](#) Construct a *PdfGenerator*.

Parameters

<i>pdflatexPath</i>	Path to the command to generate PDF file
---------------------	--

8.73.3 Member Function Documentation

8.73.3.1 void Generator::PdfGenerator::generate (QString *inputDir*, QString *filename*)

[PdfGenerator::generate](#) Generate a PDF of the file named *filename* into the directory *inputDir*

Parameters

<i>inputDir</i>	Directory where is store the PDF generated
<i>filename</i>	File name

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/generator/pdfgenerator.h
- /home/travis/build/FACT-Team/FactDev/src/generator/pdfgenerator.cpp

8.74 Models::People Class Reference

The [People](#) class [People](#).

```
#include <people.h>
```

Inheritance diagram for Models::People:



Public Member Functions

- [People](#) ()
People::People Construct a [People](#).
- [People](#) (int id)
People::People Construct a [People](#).
- QString [getFirstname](#) () const
People::getFirstname Return the [People](#) firstname.
- void [setFirstname](#) (const QString &firstname)
People::setFirstnament Modify the [People](#) firstname
- QString [getLastname](#) () const
People::getLastname Return the [People](#) lastname.
- void [setLastname](#) (const QString &lastname)
People::setLastname Modify the [People](#) lastname
- QString [getCompany](#) () const
People::getCompany Return the [People](#) company.
- void [setCompany](#) (const QString &company)
People::setCompany Modify the [People](#) company name.
- QString [getAddress](#) () const
People::getAddress Return the company address (Number and name of street)
- void [setAddress](#) (const QString &address)
People::setAddress Modify the [People](#) company address
- QString [getPostalCode](#) () const
People::getPostalCode Return the postal code.
- void [setPostalCode](#) (const QString &postalCode)
People::setPostalCode Modify the postal code postalCode

- QString [getCity](#) () const
People::getCity Return the city.
- void [setCity](#) (const QString &city)
People::setCity Modify the city
- QString [getCountry](#) () const
People::getCountry Return the country of the [People](#).
- void [setCountry](#) (const QString &country)
People::setCountry Replace the country of the [People](#) by country
- QString [getEmail](#) () const
People::getEmail Return the [People](#) professional email
- void [setEmail](#) (const QString &email)
People::setEmail Modify the [People](#) professional email
- QString [getPhone](#) () const
People::getPhone Return the number of the desktop phone.
- void [setPhone](#) (const QString &phone)
People::setPhone Modify the number of the desktop phone
- QString [getMobilePhone](#) () const
People::getMobilePhone Return the number of the professional mobile phone.
- void [setMobilePhone](#) (const QString &mobilePhone)
People::setMobilePhone Modify the number of the professional [People](#) mobile phone mobilePhone
- QString [getFax](#) () const
People::getFax Return the fax number.
- void [setFax](#) (const QString &fax)
People::setFax Replace the current fax number by fax
- virtual QPixmap * [getImage](#) () const
People::getImage Return the compagny image.
- virtual void [setImage](#) (QPixmap *image)
People::setImage Modify the current compagny image by image
- QString [getExtensionImage](#) () const
People::getExtensionImage Return the extension of the image file.
- void [setExtensionImage](#) (const QString &ext)
People::setExtensionImage Change the extension of the image file by the new ext
- QString [getAddressComplement](#) () const
getAddressComplement Return the address complement (Building, Appartment, ...)
- void [setAddressComplement](#) (const QString &addressComplement)
setAddressComplement Change the address complement
- QString [getWebsite](#) () const
getWebsite Website of [People](#)
- void [setWebsite](#) (const QString &website)
setWebsite Change the url of website
- bool [operator==](#) (const [People](#) &c)
People::operator == Re-define the operator "==" to compare if the current [People](#) is the same to the other [People](#) c
Return TRUE if both Peoples are the same, else FALSE.
- bool [operator!=](#) (const [People](#) &c)
People::operator != Re-define the operator "!=" to compare if the current [People](#) is differnt to the other [People](#) c
Return TRUE if both Peoples are different, else FALSE.

Protected Attributes

- QPixmap * [_image](#)
Compagny image.

8.74.1 Detailed Description

The [People](#) class [People](#).

8.74.2 Member Function Documentation

8.74.2.1 QString Models::People::getAddress () const

[People::getAddress](#) Return the company address (Number and name of street)

Returns

Address company

8.74.2.2 QString Models::People::getAddressComplement () const

[getAddressComplement](#) Return the address complement (Building, Appartment, ...)

Returns

The address complement

8.74.2.3 QString Models::People::getCity () const

[People::getCity](#) Return the city.

Returns

city

8.74.2.4 QString Models::People::getCompany () const

[People::getCompany](#) Return the [People](#) company.

Returns

New company name

8.74.2.5 QString Models::People::getCountry () const

[People::getCountry](#) Return the country of the [People](#).

Returns

country of the [People](#)

8.74.2.6 QString Models::People::getEmail () const

[People::getEmail](#) Return the [People](#) professional *email*

Returns

professional email

8.74.2.7 QString Models::People::getExtensionImage () const

[People::getExtensionImage](#) Return the extension of the image file.

Returns

Extension of image file

8.74.2.8 QString Models::People::getFax () const

[People::getFax](#) Return the fax number.

Returns

fax number

8.74.2.9 QString Models::People::getFirstname () const

[People::getFirstname](#) Return the [People](#) firstname.

Returns

[People](#) firstname

8.74.2.10 QPixmap * Models::People::getImage () const [virtual]

[People::getImage](#) Return the compagny image.

Returns

compagny image

8.74.2.11 QString Models::People::getLastname () const

[People::getLastname](#) Return the [People](#) lastname.

Returns

[People](#) lastname

8.74.2.12 QString Models::People::getMobilePhone () const

[People::getMobilePhone](#) Return the number of the professional mobile phone.

Returns

number of mobile phone

8.74.2.13 QString Models::People::getPhone () const

[People::getPhone](#) Return the number of the desktop phone.

Returns

number of the desktop phone

8.74.2.14 QString Models::People::getPostalCode () const

[People::getPostalCode](#) Return the postal code.

Returns

postal code

8.74.2.15 QString Models::People::getWebsite () const

[getWebsite](#) Website of [People](#)

Returns

The website url

8.74.2.16 bool Models::People::operator!= (const People & c)

[People::operator !=](#) Re-define the operator "!=" to compare if the current [People](#) is differnt to the other [People](#) c
Return TRUE if both Peoples are different, else FALSE.

Parameters

<i>c</i>	People to compare
----------	-----------------------------------

Returns

boolean

8.74.2.17 bool Models::People::operator== (const People & c)

[People::operator ==](#) Re-define the operator "==" to compare if the current [People](#) is the same to the other [People](#) c
Return TRUE if both Peoples are the same, else FALSE.

Parameters

<i>c</i>	People to compare
----------	-----------------------------------

Returns

boolean

8.74.2.18 void Models::People::setAddress (const QString & address)

[People::setAddress](#) Modify the [People](#) company *address*

Parameters

<i>address</i>	Company address (name and number of street)
----------------	---

8.74.2.19 void Models::People::setAddressComplement (const QString & addressComplement)

[setAddressComplement](#) Change the address complement

Parameters

<i>address-Complement</i>	The new complement
---------------------------	--------------------

8.74.2.20 void Models::People::setCity (const QString & *city*)

[People::setCity](#) Modify the *city*

Parameters

<i>city</i>	Company city address
-------------	----------------------

8.74.2.21 void Models::People::setCompany (const QString & *company*)

[People::setCompany](#) Modify the [People](#) *company* name.

Parameters

<i>company</i>	New People company name
----------------	---

8.74.2.22 void Models::People::setCountry (const QString & *country*)

[People::setCountry](#) Replace the country of the [People](#) by *country*

Parameters

<i>country</i>	New country of the People
----------------	---

8.74.2.23 void Models::People::setEmail (const QString & *email*)

[People::setEmail](#) Modify the [People](#) professional *email*

Parameters

<i>email</i>	The People professional email
--------------	---

8.74.2.24 void Models::People::setExtensionImage (const QString & *ext*)

[People::setExtensionImage](#) Change the extension of the image file by the new *ext*

Parameters

<i>ext</i>	Extension file
------------	----------------

8.74.2.25 void Models::People::setFax (const QString & *fax*)

[People::setFax](#) Replace the current fax number by *fax*

Parameters

<i>fax</i>	new fax number
------------	----------------

8.74.2.26 void Models::People::setFirstname (const QString & *firstname*)

People::setFirstname Modify the [People](#) *firstname*

Parameters

<i>firstname</i>	New People firstname
------------------	--------------------------------------

8.74.2.27 void Models::People::setImage (QPixmap * *image*) [virtual]

[People::setImage](#) Modify the current compagny image by *image*

Parameters

<i>image</i>	Compagny image
--------------	----------------

Reimplemented in [Models::User](#), and [Models::Customer](#).

8.74.2.28 void Models::People::setLastname (const QString & *lastname*)

[People::setLastname](#) Modify the [People](#) *lastname*

Parameters

<i>lastname</i>	New People lastname
-----------------	-------------------------------------

8.74.2.29 void Models::People::setMobilePhone (const QString & *mobilePhone*)

[People::setMobilePhone](#) Modify the number of the professional [People](#) mobile phone *mobilePhone*

Parameters

<i>mobilePhone</i>	Number of the professional mobile phone
--------------------	---

8.74.2.30 void Models::People::setPhone (const QString & *phone*)

[People::setPhone](#) Modify the number of the desktop *phone*

Parameters

<i>phone</i>	Number of the desktop phone
--------------	-----------------------------

8.74.2.31 void Models::People::setPostalCode (const QString & *postalCode*)

[People::setPostalCode](#) Modify the postal code *postalCode*

Parameters

<i>postalCode</i>	New postal code
-------------------	-----------------

8.74.2.32 void Models::People::setWebsite (const QString & *website*)

setWebsite Change the url of website

Parameters

<i>website</i>	The new URL
----------------	-------------

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/models/people.h
- /home/travis/build/FACT-Team/FactDev/src/models/people.cpp

8.75 Utils::pointers Class Reference

The pointers class.

```
#include <pointers.h>
```

Static Public Member Functions

- static void [deleteIfNotNull](#) (QObject *p)
*[pointers::deleteIfNotNull](#) Remove to the memory the object *p* if it is not null*

8.75.1 Detailed Description

The pointers class.

Author

Antoine de Roquemaurel

8.75.2 Member Function Documentation

8.75.2.1 void [Utils::pointers::deleteIfNotNull](#) (QObject * *p*) [static]

[pointers::deleteIfNotNull](#) Remove to the memory the object *p* if it is not null

Parameters

<i>p</i>	An object
----------	-----------

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/Utils/pointers.h
- /home/travis/build/FACT-Team/FactDev/src/Utils/pointers.cpp

8.76 PointersTest Class Reference

Inheritance diagram for PointersTest:



The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/tests/utis/pointerstest.h
- /home/travis/build/FACT-Team/FactDev/tests/utis/pointerstest.cpp

8.77 Gui::Widgets::Popup Class Reference

Class for display popup quickly.

```
#include <popup.h>
```

Static Public Member Functions

- static void [toImplement](#) (QString, QWidget *)
[Popup::toImplement](#) Method to display a critical message : feature is not implemented now.

8.77.1 Detailed Description

Class for display popup quickly.

Author

Antoine de Roquemaurel

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/popup.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/popup.cpp

8.78 Models::Project Class Reference

The [Project](#) class : [Project](#) linked to a [Customer](#).

```
#include <project.h>
```

Inheritance diagram for Models::Project:



Public Member Functions

- [Project](#) ()
[Project::Project](#) Construct a [Project](#).
- [Project](#) (QString name)
[Project::project](#) Construct a project with a name.
- [Project](#) (int id)
[Project::Project](#) Construct a [Project](#) which is specified by an id
- virtual [~Project](#) ()
[~Project](#) Desctruct project object
- void [commit](#) ()

- [*Project::commit*](#) Update project data in the database.
- void [hydrat](#) (int id)
 - [*Project::hydrat*](#) Insert project data which is specified by id in the database.
- void [remove](#) ()
 - [*Project::remove*](#) Remove the current project.
- QVariantHash [getDataMap](#) ()
 - [*getDataMap*](#) Get all data of model with a HashMap key/value
- QString [getName](#) () const
 - [*Project::getName*](#) Return the project name.
- void [setName](#) (const QString &name)
 - [*Project::setName*](#) Modify the project name
- QString [getDescription](#) () const
 - [*Project::getDescription*](#) Return a project description.
- void [setDescription](#) (const QString &description)
 - [*Project::setDescription*](#) Modify the project description
- QDate [getBeginDate](#) () const
 - [*Project::getBeginDate*](#) return the date of creation of the **Project**
- void [setBeginDate](#) (QDate beginDate)
 - [*Project::setBeginDate*](#) Modify beginDate of a **Project**
- QDate [getEndDate](#) () const
 - [*Project::getEndDate*](#) Return the endDate of the **Project**
- void [setEndDate](#) (QDate endDate)
 - [*Project::setEndDate*](#) Modify endDate of **Project**
- double [getCost](#) () const
 - [*Project::getCost*](#) Return the **Project** cost
- double [getDailyRate](#) () const
 - [*Project::getDailyRate*](#) Return the daily rate estimated for this project.
- void [setDailyRate](#) (double dailyRate)
 - [*Project::setDailyRate*](#) Modify the daily rate dailyRate of the current project.
- QSharedPointer< [Customer](#) > [getCustomer](#) () const
 - [*Project::getCustomer*](#) Return the reference to the customer linked to this project.
- void [setCustomer](#) (QSharedPointer< [Customer](#) > customer)
 - [*Project::setCustomer*](#) Modify the customer linked to this project.
- bool [operator==](#) (const [Project](#) &p)
 - [*Project::operator ==*](#) Re-define the operator "==" to compare if the current project is the same to the other **Project** p
Return TRUE if both projects are the same, else FALSE.
- bool [operator<](#) (const [Project](#) &p) const
 - [*Project::operator <*](#) defines the operator "<" to compare two **Project** and to see if the first is anterior to the second.
- bool [operator!=](#) (const [Project](#) &p)
 - [*Project::operator !=*](#) Re-define the operator "!=" to compare if the current project is different to the other **Project** p
Return TRUE if both projects are different, else FALSE.

Additional Inherited Members

8.78.1 Detailed Description

The [Project](#) class : [Project](#) linked to a [Customer](#).

Author

Florent Berbie

See Also

[IModel](#)

8.78.2 Constructor & Destructor Documentation

8.78.2.1 Models::Project::Project (int *id*)

[Project::Project](#) Construct a [Project](#) which is specified by an *id*

Parameters

<i>id</i>	
-----------	--

8.78.3 Member Function Documentation

8.78.3.1 QDate Models::Project::getBeginDate () const

[Project::getBeginDate](#) return the date of creation of the [Project](#)

Returns

the begin date of the [Project](#)

8.78.3.2 double Models::Project::getCost () const

[Project::getCost](#) Return the [Project](#) cost

Returns

the project cost

8.78.3.3 QSharedPointer< Customer > Models::Project::getCustomer () const

[Project::getCustomer](#) Return the reference to the customer linked to this project.

Returns

customer linked to this project

8.78.3.4 double Models::Project::getDailyRate () const

[Project::getDailyRate](#) Return the daily rate estimated for this project.

Returns

the daily rate linket to the current project

8.78.3.5 QVariantHash Models::Project::getDataMap () [virtual]

[getDataMap](#) Get all data of model with a HashMap key/value

Returns

Model's data

Implements [Models::IModel](#).

8.78.3.6 QString Models::Project::getDescription () const

[Project::getDescription](#) Return a project description.

Returns

project description

8.78.3.7 QDate Models::Project::getEndDate () const

[Project::getEndDate](#) Return the *endDate* of the **Project**

Returns

the end date of the project

8.78.3.8 QString Models::Project::getName () const

[Project::getName](#) Return the project name.

Returns

project name

8.78.3.9 void Models::Project::hydrat (int *id*) [virtual]

[Project::hydrat](#) Insert project data which is specified by *id* in the database.

Parameters

<i>id</i>	Project identify
-----------	----------------------------------

Implements [Models::IModel](#).

8.78.3.10 bool Models::Project::operator!= (const Project & *p*)

[Project::operator ==](#) Re-define the operator "!=" to compare if the current project is differnt to the other **Project** *p*
Return TRUE if both projects are different, else FALSE.

Parameters

<i>c</i>	Project to compare
----------	------------------------------------

Returns

boolean

8.78.3.11 bool Models::Project::operator< (const Project & *p*) const

[Project::operator <](#) defines the operator "<" to compare two **Project** and to see if the first is anterior to the second.

Parameters

<i>b</i>	the Project to compare with the current Project
----------	---

Returns

true if the [Project](#) are different else false

8.78.3.12 bool Models::Project::operator==(const Project & p)

[Project::operator ==](#) Re-define the operator "==" to compare if the current project is the same to the other [Project](#) *p*
Return TRUE if both projects are the same, else FALSE.

Parameters

<i>c</i>	Project to compare
----------	------------------------------------

Returns

boolean

8.78.3.13 void Models::Project::setBeginDate (QDate beginDate)

[Project::setBeginDate](#) Modify *beginDate* of a [Project](#)

Parameters

<i>beginDate</i>	the new date of creation of the project
------------------	---

8.78.3.14 void Models::Project::setCustomer (QSharedPointer< Customer > customer)

[Project::setCustomer](#) Modify the *customer* linked to this project.

Parameters

<i>customer</i>	New customer associated to this project
-----------------	---

8.78.3.15 void Models::Project::setDailyRate (double dailyRate)

[Project::setDailyRate](#) Modify the daily rate *dailyRate* of the current project.

Parameters

<i>dailyRate</i>	New daily rate associated to the current project
------------------	--

8.78.3.16 void Models::Project::setDescription (const QString & description)

[Project::setDescription](#) Modify the project *description*

Parameters

<i>description</i>	New project description
--------------------	-------------------------

8.78.3.17 void Models::Project::setEndDate (QDate *endDate*)

[Project::setEndDate](#) Modify *endDate* of [Project](#)

Parameters

<i>endDate</i>	the new end date of the project
----------------	---------------------------------

8.78.3.18 void Models::Project::setName (const QString & *name*)

[Project::setName](#) Modify the project *name*

Parameters

<i>name</i>	Project name
-------------	------------------------------

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/models/project.h
- /home/travis/build/FACT-Team/FactDev/src/models/project.cpp

8.79 Gui::Widgets::Delegates::ProjectComboDelegate Class Reference

The [ProjectComboDelegate](#) class.

```
#include <projectcombodelegate.h>
```

Inheritance diagram for Gui::Widgets::Delegates::ProjectComboDelegate:



Public Member Functions

- [ProjectComboDelegate](#) (QSharedPointer< [Models::Customer](#) > c, QObject *parent=0)
ProjectComboDelegate::ProjectComboDelegate.
- QWidget * [createEditor](#) (QWidget *parent, const QStyleOptionViewItem &option, const QModelIndex &index) const
ProjectComboDelegate::createEditor Return a *ComboBox* specified by *index* item defined by the parent widget and *style option* which are used to control how the editor widgets appears.
- void [paint](#) (QPainter *painter, const QStyleOptionViewItem &option, const QModelIndex &index) const
ProjectComboDelegate::paint Renders the delegate using the given painter and style option for the item specified by *index*
- void [removeInCombo](#) (QList< int > &l)
ProjectComboDelegate::removeInCombo Remove the items contained in the list *l* into the current *ComboBox*.
- QMap< int, [Models::Project](#) > [getProjects](#) () const

- [ProjectComboDelegate::getProjects](#) Return a list of projects linked to a Customer ID.
- bool [isLocked](#) () const
[ProjectComboDelegate::isLocked](#) Return TRUE if is locked else FALSE.
- void [setLocked](#) (bool locked)
[ProjectComboDelegate::setLocked](#) Change the state of the lock by a new value locked

8.79.1 Detailed Description

The [ProjectComboDelegate](#) class.

8.79.2 Constructor & Destructor Documentation

- 8.79.2.1 [Gui::Widgets::Delegates::ProjectComboDelegate::ProjectComboDelegate](#) ([QSharedPointer](#)< [Models::Customer](#) > *c*, [QObject](#) * *parent* = 0)

[ProjectComboDelegate::ProjectComboDelegate](#).

Parameters

<i>c</i>	
<i>parent</i>	

8.79.3 Member Function Documentation

- 8.79.3.1 [QWidget](#) * [Gui::Widgets::Delegates::ProjectComboDelegate::createEditor](#) ([QWidget](#) * *parent*, const [QStyleOptionViewItem](#) & *option*, const [QModelIndex](#) & *index*) const [virtual]

[ProjectComboDelegate::createEditor](#) Return a ComboBox specified by *index* item defined by the *parent* widget and style *option* which are used to control how the editor widgets appears.

Parameters

<i>parent</i>	Widget parent
<i>option</i>	Option style
<i>index</i>	Index for editing

Returns

ComboBox

Implements [Gui::Widgets::Delegates::ComboBoxDelegate](#).

- 8.79.3.2 [QMap](#)< int, [Models::Project](#) > [Gui::Widgets::Delegates::ProjectComboDelegate::getProjects](#) () const

[ProjectComboDelegate::getProjects](#) Return a list of projects linked to a Customer ID.

Returns

Projets of a Customer

- 8.79.3.3 bool [Gui::Widgets::Delegates::ProjectComboDelegate::isLocked](#) () const

[ProjectComboDelegate::isLocked](#) Return TRUE if is locked else FALSE.

Returns

boolean

8.79.3.4 void Gui::Widgets::Delegates::ProjectComboDelegate::paint (QPainter * *painter*, const QStyleOptionViewItem & *option*, const QModelIndex & *index*) const [virtual]

[ProjectComboDelegate::paint](#) Renders the delegate using the given *painter* and style *option* for the item specified by *index*

Parameters

<i>parent</i>	Widget parent
<i>option</i>	Option style
<i>index</i>	Index for editing

Implements [Gui::Widgets::Delegates::ComboBoxDelegate](#).

8.79.3.5 void Gui::Widgets::Delegates::ProjectComboDelegate::setLocked (bool *locked*)

[ProjectComboDelegate::setLocked](#) Change the state of the lock by a new value *locked*

Parameters

<i>locked</i>	
---------------	--

The documentation for this class was generated from the following files:


- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/delegates/projectcombodelegate.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/delegates/projectcombodelegate.cpp

8.80 Gui::Widgets::WdgModels::ProjectContributoriesTableModel Class Reference

The [ProjectContributoriesTableModel](#) class Table model of contributories linked to projects.

```
#include <projectcontributoriesstablemodel.h>
```

Inheritance diagram for Gui::Widgets::WdgModels::ProjectContributoriesTableModel:



Public Member Functions

- [ProjectContributoriesTableModel](#) (QObject *parent=0)
[ProjectContributoriesTableModel::ProjectContributoriesTableModel](#) Construct a [ProjectContributoriesTableModel](#).
- int [rowCount](#) (const QModelIndex &) const
[ProjectContributoriesTableModel::rowCount](#) Number of contributories row.
- int [columnCount](#) (const QModelIndex &) const
[ProjectContributoriesTableModel::columnCount](#) Number of column of a contributory.
- QVariant [data](#) (const QModelIndex &index, int role) const
[ProjectContributoriesTableModel::data](#) Obtains data of a specify cell.

- QVariant [headerData](#) (int section, Qt::Orientation orientation, int role) const
ProjectContributoriesTableModel::headerData Obtains header title of table.
- bool [setData](#) (const QModelIndex &index, const QVariant &value, int role=Qt::EditRole)
ProjectContributoriesTableModel::setData Change data of a cell.
- Qt::ItemFlags [flags](#) (const QModelIndex &index) const
ProjectContributoriesTableModel::flags Differents table flags.
- void [append](#) (QPair< [Models::Project](#) *, [Models::Rate](#) > p)
ProjectContributoriesTableModel::append Add a new rate p to a Project.
- void [append](#) ()
ProjectContributoriesTableModel::append Add the current element to the list.
- bool [allProjectsChosen](#) ()
ProjectContributoriesTableModel::allProjectsChosen Return TRUE if all projects have been selected else FALSE.
- QList< int > & [getSelectedProjects](#) ()
ProjectContributoriesTableModel::getSelectedProjects Return the list of the Project id which are selected.
- void [remove](#) (int index)
ProjectContributoriesTableModel::remove Remove the element to the index
- QPair< [Models::Project](#) *, [Models::Rate](#) > [getProject](#) (const int row)
ProjectContributoriesTableModel::getProject Return the project and it rate linked which correspond to the row
- QList< QPair< [Models::Project](#) *, [Models::Rate](#) > > [getProjects](#) (void)
ProjectContributoriesTableModel::getProjects Return a list of the set of projects and their rates linked.

8.80.1 Detailed Description

The [ProjectContributoriesTableModel](#) class Table model of contributories linked to projects.

Author

Antoine de Roquemaurel

8.80.2 Constructor & Destructor Documentation

8.80.2.1 [Gui::Widgets::WdgModels::ProjectContributoriesTableModel::ProjectContributoriesTableModel](#) ([QObject](#) * *parent* = 0)

[ProjectContributoriesTableModel::ProjectContributoriesTableModel](#) Construct a [ProjectContributoriesTableModel](#).

Parameters

<i>parent</i>	Parent widget
---------------	---------------

8.80.3 Member Function Documentation

8.80.3.1 [bool](#) [Gui::Widgets::WdgModels::ProjectContributoriesTableModel::allProjectsChosen](#) ()

[ProjectContributoriesTableModel::allProjectsChosen](#) Return TRUE if all projects have been selected else FALSE.

Returns

boolean All projects selected

8.80.3.2 void Gui::Widgets::WdgModels::ProjectContributoriesTableModel::append (QPair< Models::Project *,
Models::Rate > p)

[ProjectContributoriesTableModel::append](#) Add a new rate p to a Project.

Parameters

<i>p</i>	
----------	--

8.80.3.3 `int Gui::Widgets::WdgModels::ProjectContributoriesTableModel::columnCount (const QModelIndex &) const`

[ProjectContributoriesTableModel::columnCount](#) Number of column of a contributory.

Returns

The number of column

8.80.3.4 `QVariant Gui::Widgets::WdgModels::ProjectContributoriesTableModel::data (const QModelIndex & index, int role) const`

[ProjectContributoriesTableModel::data](#) Obtains data of a specify cell.

Parameters

<i>index</i>	The cell who we want data
<i>role</i>	The role of set

Returns

The data of cell

8.80.3.5 `Qt::ItemFlags Gui::Widgets::WdgModels::ProjectContributoriesTableModel::flags (const QModelIndex & index) const`

[ProjectContributoriesTableModel::flags](#) Differents table flags.

Parameters

<i>index</i>	The cell who we want to know flags
--------------	------------------------------------

Returns

Flags

8.80.3.6 `QPair< Models::Project *, Models::Rate > Gui::Widgets::WdgModels::ProjectContributoriesTableModel::getProject (const int row)`

[ProjectContributoriesTableModel::getProject](#) Return the project and it rate linked which correspond to the *row*

Parameters

<i>row</i>	Row of the project to get
------------	---------------------------

Returns

a Project and it rate

8.80.3.7 `QList< QPair< Models::Project *, Models::Rate > > Gui::Widgets::WdgModels::ProjectContributoriesTableModel::getProjects (void)`

[ProjectContributoriesTableModel::getProjects](#) Return a list of the set of projects and their rates linked.

Returns

List of Projects and Rates linked

8.80.3.8 `QList< int > & Gui::Widgets::WdgModels::ProjectContributoriesTableModel::getSelectedProjects ()`

[ProjectContributoriesTableModel::getSelectedProjects](#) Return the list of the Project id which are selected.

Returns

List of ID Project

8.80.3.9 `QVariant Gui::Widgets::WdgModels::ProjectContributoriesTableModel::headerData (int section, Qt::Orientation orientation, int role) const`

[ProjectContributoriesTableModel::headerData](#) Obtains header title of table.

Parameters

<i>section</i>	The number of column
<i>orientation</i>	The table orientation
<i>role</i>	

Returns

The Title header of column

8.80.3.10 `void Gui::Widgets::WdgModels::ProjectContributoriesTableModel::remove (int index)`

[ProjectContributoriesTableModel::remove](#) Remove the element to the *index*

Parameters

<i>index</i>	Index of the element to remove
--------------	--------------------------------

8.80.3.11 `int Gui::Widgets::WdgModels::ProjectContributoriesTableModel::rowCount (const QModelIndex &) const`

[ProjectContributoriesTableModel::rowCount](#) Number of contributories row.

Returns

The number of contributories

8.80.3.12 `bool Gui::Widgets::WdgModels::ProjectContributoriesTableModel::setData (const QModelIndex & index, const QVariant & value, int role = Qt::EditRole)`

[ProjectContributoriesTableModel::setData](#) Change data of a cell.

Parameters

<i>index</i>	The cell to change data
<i>value</i>	The new value
<i>role</i>	The role of cell

Returns

True if we could edit

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/widgetmodels/projectcontributoriestablemodel.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/widgetmodels/projectcontributoriestablemodel.cpp

8.81 Databases::ProjectDatabase Class Reference

The [ProjectDatabase](#) class Project table database.

```
#include <projectdatabase.h>
```

Inheritance diagram for Databases::ProjectDatabase:



Public Member Functions

- [Models::Project](#) * [getProject](#) (const int pld)
ProjectDatabase::getProject Get informations about the project identified by 'pld'.
- [Models::Project](#) * [getProject](#) (QSqlQuery &q)
ProjectDatabase::getProject.
- int [addProject](#) (const [Models::Project](#) &)
ProjectDatabase::addProject Add the project 'pProject' to the database.
- void [updateProject](#) (const [Models::Project](#) &)
ProjectDatabase::updateProject Update informations about the project.
- void [removeProject](#) (const int pld)
removeProject Remove the project with the id 'pld'
- int [getNbProjects](#) ()
ProjectDatabase::getNbProjects Return the number of projects existing.
- int [getNbProjects](#) (const int customerId)
Get the number of projects.
- QMap< int, [Models::Project](#) > [getProjectsOfCustomer](#) (QSharedPointer< [Models::Customer](#) > c)
getProjectsOfCustomer Return all projects of a customer
- QList< [Models::Project](#) > [getProjects](#) (const int customerId)
getProjects Return all projects of a customer
- [WdgModels::ProjectsTableModel](#) * [getProjectsTable](#) (const int pld) throw (DbException*)
getProjectsTable Return all projects of a customer in QStandardItemModel
- QSharedPointer< [Project](#) > [updateProject](#) (QSqlQuery &q)
getProject Obtain a project without new query

- `QList< Project * > getAllProjects ()`
`Project::getAllProjects` Return the list of projects.
- `double getCostProjects (QList< Project * > projects)`
`ProjectDatabase::getCostProjects` compute the cost of the project list given in parameter.

Static Public Member Functions

- `static ProjectDatabase * instance () throw (DbException*)`
`ProjectDatabase::getInstance` Return an instance of [ProjectDatabase](#).

Additional Inherited Members

8.81.1 Detailed Description

The [ProjectDatabase](#) class Project table database.

Author

Florent Berbie

See Also

[Database](#)
[Project](#)

8.81.2 Member Function Documentation

8.81.2.1 `int Databases::ProjectDatabase::addProject (const Models::Project & pProject)`

[ProjectDatabase::addProject](#) Add the project 'pProject' to the database.

Returns

project id

8.81.2.2 `QList< Project * > Databases::ProjectDatabase::getAllProjects ()`

`Project::getAllProjects` Return the list of projects.

Returns

Projects list

8.81.2.3 `double Databases::ProjectDatabase::getCostProjects (QList< Project * > projects)`

[ProjectDatabase::getCostProjects](#) compute the cost of the project list given in parameter.

Parameters

<i>projects</i>	the list of projects
-----------------	----------------------

Returns

the cost of the list given

8.81.2.4 `int Databases::ProjectDatabase::getNbProjects ()`

[ProjectDatabase::getNbProjects](#) Return the number of projects existing.

Returns

number of projects

8.81.2.5 `int Databases::ProjectDatabase::getNbProjects (const int customerId)`

Get the number of projects.

Parameters

<i>customerId</i>	If customerId isn't specified if it's not valid, get all projects else get the specified customer projects
-------------------	--

Returns

Number of projects in the database for all or for a customer

8.81.2.6 `Models::Project * Databases::ProjectDatabase::getProject (const int pld)`

[ProjectDatabase::getProject](#) Get informations about the project identified by 'pld'.

Parameters

<i>pld</i>	project
------------	---------

Returns

the project

8.81.2.7 `Models::Project * Databases::ProjectDatabase::getProject (QSqlQuery & q)`

[ProjectDatabase::getProject](#).

Parameters

<i>q</i>	
----------	--

Returns**8.81.2.8** `QList< Project > Databases::ProjectDatabase::getProjects (const int customerId)`

`getProjects` Return all projects of a customer

Parameters

<i>customerId</i>	The customer id
-------------------	-----------------

Returns

List with all projects of customer

8.81.2.9 `QMap< int, Models::Project > Databases::ProjectDatabase::getProjectsOfCustomer (QSharedPointer< Models::Customer > c)`

getProjectsOfCustomer Return all projects of a customer

Parameters

<i>c</i>	The customer
----------	--------------

Returns

All projects of *c* with id in key

8.81.2.10 `WdgModels::ProjectsTableModel * Databases::ProjectDatabase::getProjectsTable (const int pld) throw DbException *`

`getProjectsTable` Return all projects of a customer in `QStandardItemModel`

Parameters

<i>filter</i>	Select only projects who are specified by <i>filter</i>
---------------	---

Returns

`QStandardItemModel` an item model for `QTableView`

8.81.2.11 `ProjectDatabase * Databases::ProjectDatabase::instance () throw DbException *` `[static]`

`ProjectDatabase::getInstance` Return an instance of [ProjectDatabase](#).

Returns

Instance of [ProjectDatabase](#)

8.81.2.12 `void Databases::ProjectDatabase::removeProject (const int pld)`

`removeProject` Remove the project with the id '*pld*'

Parameters

<i>pld</i>	project id
------------	------------

8.81.2.13 `QSharedPointer< Models::Project > Databases::ProjectDatabase::updateProject (QSqlQuery & q)`

`getProject` Obtain a project without new query

Parameters

<i>q</i>	The query to use
----------	------------------

Returns

The project linked to *q*

The documentation for this class was generated from the following files:

- `/home/travis/build/FACT-Team/FactDev/src/database/projectdatabase.h`
- `/home/travis/build/FACT-Team/FactDev/src/database/projectdatabase.cpp`

8.82 ProjectDatabaseTest Class Reference

Inheritance diagram for ProjectDatabaseTest:



The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/tests/database/projectdatabasetest.h
- /home/travis/build/FACT-Team/FactDev/tests/database/projectdatabasetest.cpp

8.83 ProjectModelTest Class Reference

Inheritance diagram for ProjectModelTest:



The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/tests/models/projectmodeltest.h
- /home/travis/build/FACT-Team/FactDev/tests/models/projectmodeltest.cpp

8.84 Gui::Widgets::WdgModels::ProjectsTableModel Class Reference

The [ProjectsTableModel](#) class for a Project table.

```
#include <projectstablemodel.h>
```

Inheritance diagram for Gui::Widgets::WdgModels::ProjectsTableModel:



Public Member Functions

- [ProjectsTableModel](#) ()
ProjectsTableModel::ProjectsTableModel Construct a *ProjectsTableModel*.
- int [rowCount](#) (const QModelIndex &) const
ProjectsTableModel::rowCount Number of projects row.

- int [columnCount](#) (const QModelIndex &) const
ProjectsTableModel::columnCount Number of column of a Project.
- QVariant [data](#) (const QModelIndex &index, int role=Qt::DisplayRole) const
ProjectsTableModel::data Obtains data of a specify cell.
- QVariant [headerData](#) (int section, Qt::Orientation orientation, int role=Qt::DisplayRole) const
ProjectsTableModel::headerData Obtains header title of table.
- bool [setData](#) (const QModelIndex &index, const QVariant &value, int role=Qt::EditRole)
ProjectsTableModel::setData Change data of a cell.
- void [append](#) (const [Project](#) &project)
ProjectsTableModel::append Add a new line in table.
- void [remove](#) (const int i)
ProjectsTableModel::remove Remove a line.
- Qt::ItemFlags [flags](#) (const QModelIndex &index) const
ProjectsTableModel::flags Differents table flags.
- int [count](#) ()
ProjectsTableModel::count Number of projects in table.
- QList< [Project](#) > [getProjects](#) () const
ProjectsTableModel::getProjects Return the list of projects.

8.84.1 Detailed Description

The [ProjectsTableModel](#) class for a Project table.

Author

Florent Berbie

See Also

[Project](#)

8.84.2 Constructor & Destructor Documentation

8.84.2.1 Gui::Widgets::WdgModels::ProjectsTableModel::ProjectsTableModel ()

[ProjectsTableModel::ProjectsTableModel](#) Construct a [ProjectsTableModel](#).

Parameters

<i>parent</i>	Parent widget
---------------	---------------

8.84.3 Member Function Documentation

8.84.3.1 void Gui::Widgets::WdgModels::ProjectsTableModel::append (const [Project](#) & *project*)

[ProjectsTableModel::append](#) Add a new line in table.

Parameters

<i>Project</i>	The new Project
----------------	-----------------

8.84.3.2 `int Gui::Widgets::WdgModels::ProjectsTableModel::columnCount (const QModelIndex &) const`

[ProjectsTableModel::columnCount](#) Number of column of a Project.

Returns

The number of column

8.84.3.3 `int Gui::Widgets::WdgModels::ProjectsTableModel::count ()`

[ProjectsTableModel::count](#) Number of projects in table.

Returns

The number of projects

8.84.3.4 `QVariant Gui::Widgets::WdgModels::ProjectsTableModel::data (const QModelIndex & index, int role = Qt::DisplayRole) const`

[ProjectsTableModel::data](#) Obtains data of a specify cell.

Parameters

<i>index</i>	The cell who we want data
<i>role</i>	The role of set

Returns

The data of cell

8.84.3.5 `Qt::ItemFlags Gui::Widgets::WdgModels::ProjectsTableModel::flags (const QModelIndex & index) const`

[ProjectsTableModel::flags](#) Differents table flags.

Parameters

<i>index</i>	The cell who we want to know flags
--------------	------------------------------------

Returns

Flags

8.84.3.6 `QList< Project > Gui::Widgets::WdgModels::ProjectsTableModel::getProjects (void) const`

[ProjectsTableModel::getProjects](#) Return the list of projects.

Returns

list of projects

8.84.3.7 `QVariant Gui::Widgets::WdgModels::ProjectsTableModel::headerData (int section, Qt::Orientation orientation, int role = Qt::DisplayRole) const`

[ProjectsTableModel::headerData](#) Obtains header title of table.

Parameters

<i>section</i>	The number of column
<i>orientation</i>	The table orientation
<i>role</i>	

Returns

The Title header of column

8.84.3.8 void Gui::Widgets::WdgModels::ProjectsTableModel::remove (const int *i*)

[ProjectsTableModel::remove](#) Remove a line.

Parameters

<i>i</i>	The number of line to remove
----------	------------------------------

8.84.3.9 int Gui::Widgets::WdgModels::ProjectsTableModel::rowCount (const QModelIndex &) const

[ProjectsTableModel::rowCount](#) Number of projects row.

Returns

The number of projects

8.84.3.10 bool Gui::Widgets::WdgModels::ProjectsTableModel::setData (const QModelIndex & *index*, const QVariant & *value*, int *role* = Qt::EditRole)

[ProjectsTableModel::setData](#) Change data of a cell.

Parameters

<i>index</i>	The cell to change data
<i>value</i>	The new value
<i>role</i>	The role of cell

Returns

True if we could edit

The documentation for this class was generated from the following files:


- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/widgetmodels/projectstablemodel.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/widgetmodels/projectstablemodel.cpp

8.85 Gui::Widgets::ProjectsWidget Class Reference

The [ProjectsWidget](#) class Actions on Project.

```
#include <projectswidget.h>
```

Inheritance diagram for Gui::Widgets::ProjectsWidget:



Public Slots

- void [newProject](#) ()
ProjectsWidget::addProject Event which sends a signal to add a new project.
- void [editSelectedProject](#) ()
ProjectsWidget::editSelectedProject Event which sends a signal to edit the project selected.
- void [removeSelectedProject](#) ()
ProjectsWidget::removeSelectedProject Event which sends a signal to remove the project selected.
- void [updateBtn](#) (bool b)
ProjectsWidget::updateBtn Update the toolbar in tblProjects.

Signals

- void [addProject](#) ()
ProjectsWidget::addProject Add a new project to the current Customer.
- void [editProject](#) ()
ProjectsWidget::editProject Edit the current Customer selected.
- void [removeProject](#) ()
ProjectsWidget::removeProject Remove the current Customer selected.

Public Member Functions

- [ProjectsWidget](#) (QWidget *parent=0)
ProjectsWidget::ProjectsWidget Construct a [ProjectsWidget](#).

8.85.1 Detailed Description

The [ProjectsWidget](#) class Actions on Project.

Author

Florent Berbie

8.85.2 Constructor & Destructor Documentation

8.85.2.1 [Gui::Widgets::ProjectsWidget::ProjectsWidget](#) ([QWidget](#) * *parent* = 0) [explicit]

[ProjectsWidget::ProjectsWidget](#) Construct a [ProjectsWidget](#).

Parameters

<i>parent</i>	
---------------	--

8.85.3 Member Function Documentation

8.85.3.1 void Gui::Widgets::ProjectsWidget::updateBtn (bool *b*) [slot]

[ProjectsWidget::updateBtn](#) Update the toolbar in tblProjects.

Parameters

<i>boolean</i>	if a row is selected
----------------	----------------------

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/projectswidget.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/projectswidget.cpp

8.86 Mustache::QtVariantContext Class Reference

```
#include <mustache.h>
```

Inheritance diagram for Mustache::QtVariantContext:



Public Types

- typedef QString(* [fn_t](#))(const QString &, [Mustache::Renderer](#) *, [Mustache::Context](#) *)

Public Member Functions

- **QtVariantContext** (const QVariant &root, [PartialResolver](#) *resolver=0)
- virtual QString [stringValue](#) (const QString &key) const
- virtual bool [isFalse](#) (const QString &key) const
- virtual int [listCount](#) (const QString &key) const
- virtual void [push](#) (const QString &key, int index=-1)
- virtual void [pop](#) ()
- virtual bool [canEval](#) (const QString &key) const
- virtual QString [eval](#) (const QString &key, const QString &_template, [Mustache::Renderer](#) *renderer)

8.86.1 Detailed Description

A context implementation which wraps a QVariantHash or QVariantMap.

8.86.2 Member Typedef Documentation

- 8.86.2.1 typedef QString(* [Mustache::QtVariantContext::fn_t](#))(const QString &, [Mustache::Renderer](#) *, [Mustache::Context](#) *)

Construct a [QtVariantContext](#) which wraps a dictionary in a QVariantHash or a QVariantMap.

8.86.3 Member Function Documentation

8.86.3.1 `bool QtVariantContext::canEval (const QString & key) const` [virtual]

Returns true if `eval()` should be used to render section tags using `key`. If `canEval()` returns true for a key, the renderer will pass the literal, unrendered block of text for the section to `eval()` and replace the section with the result.

`canEval()` and `eval()` are equivalents for callable objects (eg. lambdas) in other Mustache implementations.

The default implementation always returns false.

Reimplemented from [Mustache::Context](#).

Reimplemented in [CounterContext](#), and [CounterContext](#).

8.86.3.2 `QString QtVariantContext::eval (const QString & key, const QString & _template, Mustache::Renderer * renderer)` [virtual]

Callback used to render a template section with the given `key`. `renderer` will substitute the original section tag with the result of `eval()`.

The default implementation returns an empty string.

Reimplemented from [Mustache::Context](#).

Reimplemented in [CounterContext](#), and [CounterContext](#).

8.86.3.3 `bool QtVariantContext::isFalse (const QString & key) const` [virtual]

Returns true if the value for `key` is 'false' or an empty list. 'False' values typically include empty strings, the boolean value false etc.

When processing a section Mustache tag, the section is not rendered if the key is false, or for an inverted section tag, the section is only rendered if the key is false.

Implements [Mustache::Context](#).

8.86.3.4 `int QtVariantContext::listCount (const QString & key) const` [virtual]

Returns the number of items in the list value for `key` or 0 if the value for `key` is not a list.

Implements [Mustache::Context](#).

8.86.3.5 `void QtVariantContext::pop ()` [virtual]

Exit the current context.

Implements [Mustache::Context](#).

8.86.3.6 `void QtVariantContext::push (const QString & key, int index = -1)` [virtual]

Set the current context to the value for `key`. If `index` is ≥ 0 , set the current context to the `index`'th value in the list value for `key`.

Implements [Mustache::Context](#).

8.86.3.7 `QString QtVariantContext::stringValue (const QString & key) const` [virtual]

Returns a string representation of the value for `key` in the current context. This is used to replace a Mustache value tag.

Implements [Mustache::Context](#).

Reimplemented in [CounterContext](#), and [CounterContext](#).

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/libs/qt-mustache/src/mustache.h
- /home/travis/build/FACT-Team/FactDev/src/libs/qt-mustache/src/mustache.cpp

8.87 Models::Rate Class Reference

The [Rate](#) class [Rate](#) of a prestation.

```
#include <rate.h>
```

Public Member Functions

- [Rate](#) ()
[Rate::Rate](#) Construct a [Rate](#).
- [Rate](#) (double hourly)
[Rate::Rate](#) Construct a [Rate](#) with an hourly rate.
- [Rate](#) (int idBilling, int idProject)
[Rate::Rate](#) Construct a [Rate](#) for the [Billing](#) with idBilling as identify and from the project identified by idProject
- void [setDailyRate](#) (const double &)
[Rate::setDailyRate](#) Modify the daily rate with the new value.
- void [setHourlyRate](#) (const double &)
[Rate::setHourlyRate](#) Modify the hourly rate with the new value.
- double [getDailyRate](#) () const
[Rate::getDailyRate](#) Return the daily rate.
- double [getHourlyRate](#) () const
[Rate::getHourlyRate](#) Return the hourly rate.
- int [getNbDailyHours](#) () const
[Rate::getNbDailyHours](#) Return the number of daily hours.
- double [getLegalRate](#) () const
[Rate::getLegalRate](#) Return the legal rate.

8.87.1 Detailed Description

The [Rate](#) class [Rate](#) of a prestation.

Author

Antoine de Roquemaurel

8.87.2 Constructor & Destructor Documentation

8.87.2.1 Models::Rate::Rate (double hourly)

[Rate::Rate](#) Construct a [Rate](#) with an hourly rate.

Parameters

<i>hourly</i>	Hourly rate
---------------	-------------

8.87.2.2 Models::Rate::Rate (int *idBilling*, int *idProject*)

[Rate::Rate](#) Construct a [Rate](#) for the [Billing](#) with *idBilling* as identify and from the project identified by *idProject*

Parameters

<i>idBilling</i>	Billing identify
<i>idProject</i>	Project identify

8.87.3 Member Function Documentation

8.87.3.1 double Models::Rate::getDailyRate () const

[Rate::getDailyRate](#) Return the daily rate.

Returns

8.87.3.2 double Models::Rate::getHourlyRate () const

[Rate::getHourlyRate](#) Return the hourly rate.

Returns

8.87.3.3 double Models::Rate::getLegalRate () const

[Rate::getLegalRate](#) Return the legal rate.

Returns

8.87.3.4 int Models::Rate::getNbDailyHours () const

[Rate::getNbDailyHours](#) Return the number of daily hours.

Returns

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/models/rate.h
- /home/travis/build/FACT-Team/FactDev/src/models/rate.cpp

8.88 Databases::RateDatabase Class Reference

Inheritance diagram for Databases::RateDatabase:



Public Member Functions

- void [addRateProject](#) (int idProject, int idBilling, double hourlyRate)
[RateDatabase::addRateProject](#) Add a new rate *hourlyRate* to the Project identified by *idProject* of the Billing with *idBilling* as identify.
- double [getRate](#) (const int idBilling, const int idProject) const
[RateDatabase::getRate](#) Return the rate of the Project identified by *idProject* of the Billing with *idBilling* as identify.
- void [updateRateProject](#) (int idProject, int idBilling, double hourlyRate)
[RateDatabase::updateRateProject](#) Update the current rate by the new *hourlyRate* of the Project identified by *idProject* of the Billing with *idBilling* as identify.

Static Public Member Functions

- static [RateDatabase](#) * [instance](#) () throw (DbException*)
[RateDatabase::getInstance](#) Return an instance of [RateDatabase](#).

Additional Inherited Members

8.88.1 Member Function Documentation

8.88.1.1 void Databases::RateDatabase::addRateProject (int *idProject*, int *idBilling*, double *hourlyRate*)

[RateDatabase::addRateProject](#) Add a new rate *hourlyRate* to the Project identified by *idProject* of the Billing with *idBilling* as identify.

Parameters

<i>idProject</i>	Project identify
<i>idBilling</i>	Billing identify
<i>hourlyRate</i>	New hourly rate

8.88.1.2 double Databases::RateDatabase::getRate (const int *idBilling*, const int *idProject*) const

[RateDatabase::getRate](#) Return the rate of the Project identified by *idProject* of the Billing with *idBilling* as identify.

Parameters

<i>idBilling</i>	Billing identify
<i>idProject</i>	Project identify

Returns

Rate of the Project of a Billing

8.88.1.3 `RateDatabase * Databases::RateDatabase::instance () throw DbException *` `[static]`

`RateDatabase::getInstance` Return an instance of [RateDatabase](#).

Returns

Instance of [RateDatabase](#)

8.88.1.4 `void Databases::RateDatabase::updateRateProject (int idProject, int idBilling, double hourlyRate)`

[RateDatabase::updateRateProject](#) Update the current rate by the new *hourlyRate* of the Project identified by *id-Project* of the Billing with *idBilling* as identify.

Parameters

<i>idProject</i>	Project identify
<i>idBilling</i>	Billing identify
<i>hourlyRate</i>	New hourly rate

The documentation for this class was generated from the following files:

- `/home/travis/build/FACT-Team/FactDev/src/database/ratedatabase.h`
- `/home/travis/build/FACT-Team/FactDev/src/database/ratedatabase.cpp`

8.89 RateModelTest Class Reference

Inheritance diagram for `RateModelTest`:



The documentation for this class was generated from the following files:

- `/home/travis/build/FACT-Team/FactDev/tests/models/ratemodeltest.h`
- `/home/travis/build/FACT-Team/FactDev/tests/models/ratemodeltest.cpp`

8.90 Gui::Widgets::RateWidget Class Reference

Class for display Rate.

```
#include <ratewidget.h>
```

Inheritance diagram for `Gui::Widgets::RateWidget`:



Public Slots

- void [setDailyRate](#) ()
setDailyRate Set a new value for the daily rate
- void [setHourlyRate](#) ()
setHourlyRate Set a new value for the hourly rate

Public Member Functions

- [RateWidget](#) (QWidget *parent=0)
RateWidget::RateWidget Construct a rate widget.
- void [initRate](#) ()
RateWidget::initRate Initialize the rate.
- void [setWidgetDailyRateValue](#) (double value)
RateWidget::setWidgetDailyRateValue Modify the value of the daily rate spin box component.
- double [getDailyRate](#) ()
RateWidget::getDailyRate Get the daily rate.
- double [getHourlyRate](#) ()
RateWidget::getHourlyRate Get the hourly rate.
- void [setWidgetHourlyRateValue](#) (double value)
RateWidget::setWidgetHourlyRateValue Modify the value of the hourly rate spin box component.
- void [updateConversionRate](#) ()
updateConversionRate Update daily rate or hourly rate

8.90.1 Detailed Description

Class for display Rate.

Author

Florent Berbie

8.90.2 Constructor & Destructor Documentation

8.90.2.1 [Gui::Widgets::RateWidget::RateWidget](#) ([QWidget](#) * *parent* = 0) [explicit]

[RateWidget::RateWidget](#) Construct a rate widget.

Parameters

<i>parent</i>	The QWidget parent
---------------	--------------------

8.90.3 Member Function Documentation

8.90.3.1 double [Gui::Widgets::RateWidget::getDailyRate](#) ()

[RateWidget::getDailyRate](#) Get the daily rate.

Returns

The daily rate

8.90.3.2 `double Gui::Widgets::RateWidget::getHourlyRate ()`

[RateWidget::getHourlyRate](#) Get the hourly rate.

Returns

The hourly rate

8.90.3.3 `void Gui::Widgets::RateWidget::setDailyRate () [slot]`

`setDailyRate` Set a new value for the daily rate

Parameters

<i>dailyRate</i>	The new daily rate
------------------	--------------------

8.90.3.4 `void Gui::Widgets::RateWidget::setHourlyRate () [slot]`

`setHourlyRate` Set a new value for the hourly rate

Parameters

<i>hourlyRate</i>	The new hourly rate
-------------------	---------------------

8.90.3.5 `void Gui::Widgets::RateWidget::setWidgetDailyRateValue (double value)`

[RateWidget::setWidgetDailyRateValue](#) Modify the *value* of the daily rate spin box component.

Parameters

<i>value</i>	New Value
--------------	-----------

8.90.3.6 `void Gui::Widgets::RateWidget::setWidgetHourlyRateValue (double value)`

[RateWidget::setWidgetHourlyRateValue](#) Modify the *value* of the hourly rate spin box component.

Parameters

<i>value</i>	New value
--------------	-----------

The documentation for this class was generated from the following files:

- `/home/travis/build/FACT-Team/FactDev/src/gui/widgets/ratewidget.h`
- `/home/travis/build/FACT-Team/FactDev/src/gui/widgets/ratewidget.cpp`

8.91 Mustache::Renderer Class Reference

```
#include <mustache.h>
```

Public Member Functions

- `QString render (const QString &_template, Context *context)`
- `QString error () const`
- `int errorPos () const`

- QString [errorPartial](#) () const
- void [setTagMarkers](#) (const QString &startMarker, const QString &endMarker)

8.91.1 Detailed Description

Renders Mustache templates, replacing mustache tags with values from a provided context.

8.91.2 Member Function Documentation

8.91.2.1 QString [Renderer::error](#) () const

Returns a message describing the last error encountered by the previous [render\(\)](#) call.

8.91.2.2 QString [Renderer::errorPartial](#) () const

Returns the name of the partial where the error occurred, or an empty string if the error occurred in the main template.

8.91.2.3 int [Renderer::errorPos](#) () const

Returns the position in the template where the last error occurred when rendering the template or -1 if no error occurred.

If the error occurred in a partial template, the returned position is the offset in the partial template.

8.91.2.4 QString [Renderer::render](#) (const QString &_template, Context * context)

Render a Mustache template, using `context` to fetch the values used to replace Mustache tags.

8.91.2.5 void [Renderer::setTagMarkers](#) (const QString &startMarker, const QString &endMarker)

Sets the default tag start and end markers. This can be overridden within a template.

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/libs/qt-mustache/src/mustache.h
- /home/travis/build/FACT-Team/FactDev/src/libs/qt-mustache/src/mustache.cpp

8.92 Models::Search Class Reference

The [Search](#) class.

```
#include <search.h>
```

Public Member Functions

- [Search](#) ()
[Search::Search](#) Construct a search.
- [~Search](#) ()
[Search::Search](#) Destruct a search.
- QString [getFilter](#) ()

- Search::getFilter* Return the search filter.
- void **filterOnVarcharElements** (QString &filter, const QStringList list, QString element)
 - Search::filterOnVarcharElements* Search, for each word of the list from the filter, if it corresponds to the element in the database.
 - void **filterOnNumberElements** (QString &filter, const QStringList list, QString element)
 - Search::filterOnNumberElements* Search, for each number of the list from the filter, if it corresponds to the element in the database.
 - void **filterOnCompany** (QString &filter, const QStringList list)
 - Search::filterOnCompany* Search all companies contained in the list of the filter
 - void **filterOnReferentLastname** (QString &filter, const QStringList list)
 - Search::filterOnReferentLastname* Search all referents last name contained in the list of the filter
 - void **filterOnProjects** (QString &filter, const QStringList list)
 - Search::filterOnProjects* Search all projects contained in the list of the filter
 - void **filterOnContributories** (QString &filter, const QStringList list)
 - Search::filterOnContributories* Search all contributories contained in the list of the filter
 - void **filterOnBillsOrQuotes** (QString &filter, const QStringList list)
 - Search::filterOnBillsOrQuotes* Search all bills or quotes which are contained in the list of the filter
 - void **filterOnCustomersWithoutProject** (QString &filter, const QStringList list)
 - Search::filterOnCustomersWithoutProject* Search all customers which are contained in the list of the filter
 - bool **getSearchInCompanies** () const
 - Search::getSearchInCompanies* Return if we search a company.
 - void **setSearchInCompanies** (bool searchInCompanies)
 - Search::setSearchInCompanies* Modify the filter of companies search.
 - bool **getSearchInReferentLastname** () const
 - Search::getSearchInReferentLastname* Return if we search a Last name referent.
 - void **setSearchInReferentLastname** (bool searchInReferentLastname)
 - Search::setSearchInReferentLastname* Modify the filter of referents last name search.
 - bool **getSearchInProjects** () const
 - Search::getSearchInProjects* Return TRUE if it exists one or more projets in database.
 - void **setSearchInProjects** (bool searchInProjects)
 - Search::setSearchInProjects* Modify the filter of projects search.
 - bool **searchInContributories** () const
 - Search::getSearchInContributories* Return TRUE if it exists one or more projets in database.
 - void **setSearchInContributories** (bool **searchInContributories**)
 - Search::setSearchInContributories* Modify the filter of contributories search.
 - bool **getSearchInBillsQuotes** () const
 - Search::searchInBillsQuotes* Return TRUE if it exists one or more bills or quotes in database.
 - void **setSearchInBillsQuotes** (bool searchInBillsQuotes)
 - Search::setSearchInBillsQuotes* Modify the filter of bills and quotes search.
 - bool **getGroupFilter** () const
 - Search::getGroupFilter* Return if the filter is activated.
 - void **setGroupFilter** (bool **getGroupFilter**)
 - Search::setGroupFilter* Modify if we active search filter.
 - QString **getText** () const
 - Search::getText* Return sql portion of filter.
 - void **setText** (const QString &**getText**)
 - Search::setText* Modify sql portion.

8.92.1 Detailed Description

The [Search](#) class.

Author

Antoine de Roquemaurel
Florent Berbie

8.92.2 Member Function Documentation

8.92.2.1 void Models::Search::filterOnBillsOrQuotes (QString & *filter*, const QStringList *list*)

[Search::filterOnBillsOrQuotes](#) [Search](#) all bills or quotes which are contained in the *list* of the *filter*

Parameters

<i>filter</i>	Text inputed in searchbar
<i>list</i>	List of bills or quotes

8.92.2.2 void Models::Search::filterOnCompany (QString & *filter*, const QStringList *list*)

[Search::filterOnCompany](#) [Search](#) all companies contained in the *list* of the *filter*

Parameters

<i>filter</i>	Text inputed in searchbar
<i>list</i>	List of companies

8.92.2.3 void Models::Search::filterOnContributories (QString & *filter*, const QStringList *list*)

[Search::filterOnContributories](#) [Search](#) all contributories contained in the *list* of the *filter*

Parameters

<i>filter</i>	Text inputed in searchbar
<i>list</i>	List of contributories

8.92.2.4 void Models::Search::filterOnCustomersWithoutProject (QString & *filter*, const QStringList *list*)

[Search::filterOnCustomersWithoutProject](#) [Search](#) all customers which are contained in the *list* of the *filter*

Parameters

<i>filter</i>	Text inputed in searchbar
<i>list</i>	List of bills or quotes

8.92.2.5 void Models::Search::filterOnNumberElements (QString & *filter*, const QStringList *list*, QString *element*)

[Search::filterOnNumberElements](#) [Search](#), for each number of the *list* from the *filter*, if it corresponds to the *element* in the database.

Parameters

<i>filter</i>	Text inputed in the searchbar
<i>list</i>	List of numbers from the <i>filter</i>
<i>element</i>	Attribute name into the database

8.92.2.6 void Models::Search::filterOnProjects (QString & *filter*, const QStringList *list*)

[Search::filterOnProjects](#) Search all projects contained in the *list* of the *filter*

Parameters

<i>filter</i>	Text inputed in searchbar
<i>list</i>	List of projects

8.92.2.7 void Models::Search::filterOnReferentLastname (QString & *filter*, const QStringList *list*)

[Search::filterOnReferentLastname](#) Search all referents last name contained in the *list* of the *filter*

Parameters

<i>filter</i>	Text inputed in searchbar
<i>list</i>	List of referent last name

8.92.2.8 void Models::Search::filterOnVarcharElements (QString & *filter*, const QStringList *list*, QString *element*)

[Search::filterOnVarcharElements](#) Search, for each word of the *list* from the *filter*, if it corresponds to the *element* in the database.

Parameters

<i>filter</i>	Text inputed in the searchbar
<i>list</i>	List of words from the <i>filter</i>
<i>element</i>	Attribute name into the database

8.92.2.9 QString Models::Search::getFilter ()

[Search::getFilter](#) Return the search filter.

Returns

filter selected (sql portion)

8.92.2.10 bool Models::Search::getGroupFilter () const

[Search::getGroupFilter](#) Return if the filter is activated.

Returns

boolean if search filter is activated

8.92.2.11 bool Models::Search::getSearchInBillsQuotes () const

[Search::searchInBillsQuotes](#) Return TRUE if it exists one or more bills or quotes in database.

Returns

boolean if bills or quotes are existing

8.92.2.12 `bool Models::Search::getSearchInCompanies () const`

[Search::getSearchInCompanies](#) Return if we search a company.

Returns

boolean if we search a company

8.92.2.13 `bool Models::Search::getSearchInProjects () const`

[Search::getSearchInProjects](#) Return TRUE if it exists one or more projets in database.

Returns

boolean if project are existing

8.92.2.14 `bool Models::Search::getSearchInReferentLastname () const`

[Search::getSearchInReferentLastname](#) Return if we search a Last name referent.

Returns

boolean if search concerns the last name of referent

8.92.2.15 `QString Models::Search::getText () const`

[Search::getText](#) Return sql portion of filter.

Returns

QString the sql portion

8.92.2.16 `bool Models::Search::searchInContributories () const`

[Search::getSearchInContributories](#) Return TRUE if it exists one or more projets in database.

Returns

boolean if contributories are existing

8.92.2.17 `void Models::Search::setGroupFilter (bool getGroupFilter)`

[Search::setGroupFilter](#) Modify if we active search filter.

Parameters

<i>getGroupFilter</i>	Get if filter is actived
-----------------------	--------------------------

8.92.2.18 void Models::Search::setSearchInBillsQuotes (bool *searchInBillsQuotes*)

[Search::setSearchInBillsQuotes](#) Modify the filter of bills and quotes search.

Parameters

<i>searchInBills-Quotes</i>	Search in bills or quotes which are concerned
-----------------------------	---

8.92.2.19 void Models::Search::setSearchInCompanies (bool *searchInCompanies*)

[Search::setSearchInCompanies](#) Modify the filter of companies search.

Parameters

<i>getSearchIn-Companies</i>	Search in companies is concerned
------------------------------	--

8.92.2.20 void Models::Search::setSearchInContributories (bool *searchInContributories*)

[Search::setSearchInContributories](#) Modify the filter of contributories search.

Parameters

<i>searchIn-Contributories</i>	Search in contributories which are concerned
--------------------------------	--

8.92.2.21 void Models::Search::setSearchInProjects (bool *searchInProjects*)

[Search::setSearchInProjects](#) Modify the filter of projects search.

Parameters

<i>searchInProjects</i>	Search in projects which are concerned
-------------------------	--

8.92.2.22 void Models::Search::setSearchInReferentLastname (bool *searchInReferentLastname*)

[Search::setSearchInReferentLastname](#) Modify the filter of referents last name search.

Parameters

<i>searchIn-Referent-Lastname</i>	Search in referents last name which are concerned
-----------------------------------	---

8.92.2.23 void Models::Search::setText (const QString & *getText*)

[Search::setText](#) Modify sql portion.

Parameters

<i>getText</i>	Get sql portion
----------------	-----------------

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/models/search.h
- /home/travis/build/FACT-Team/FactDev/src/models/search.cpp

8.93 Gui::Docks::SearchDock Class Reference

The [SearchDock](#) class Dock which contains search bar.

```
#include <searchdock.h>
```

Inheritance diagram for Gui::Docks::SearchDock:



Public Slots

- void [search](#) (QString text)
[SearchDock::search](#) Search elements in database which correspond to the text

Signals

- void [textChanged](#) (QString text)
[SearchDock::textChanged](#) Current text changed by text

Public Member Functions

- [SearchDock](#) (QWidget *parent=0, Qt::WindowFlags flags=0)
[SearchDock::SearchDock](#) Construct a [SearchDock](#).

8.93.1 Detailed Description

The [SearchDock](#) class Dock which contains search bar.

8.93.2 Constructor & Destructor Documentation

8.93.2.1 [Gui::Docks::SearchDock::SearchDock](#) ([QWidget](#) * *parent* = 0, [Qt::WindowFlags](#) *flags* = 0) [explicit]

[SearchDock::SearchDock](#) Construct a [SearchDock](#).

Parameters

<i>parent</i>	Widget Parent
<i>flags</i>	Window flag

8.93.3 Member Function Documentation

8.93.3.1 void Gui::Docks::SearchDock::search (QString *text*) [slot]

[SearchDock::search](#) Search elements in database which correspond to the *text*

Parameters

<i>text</i>	Element to search
-------------	-------------------

8.93.3.2 void Gui::Docks::SearchDock::textChanged (QString *text*) [signal]

[SearchDock::textChanged](#) Current text changed by *text*

Parameters

<i>text</i>	New text
-------------	----------

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/docks/searchdock.h
- /home/travis/build/FACT-Team/FactDev/src/gui/docks/searchdock.cpp

8.94 searchTest Class Reference

Inheritance diagram for searchTest:



The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/tests/models/searchtest.h
- /home/travis/build/FACT-Team/FactDev/tests/models/searchtest.cpp

8.95 Gui::Widgets::searchWidget Class Reference

Class for search in database.

```
#include <searchwidget.h>
```

Inheritance diagram for Gui::Widgets::searchWidget:



Public Slots

- void [search](#) (QString toSearch)
searchWidget::launch a search
- void [getCustomerData](#) ()
searchWidget::getCustomerData Return data on the customer selected in the QTableView and display this data (First-name, Lastname, Company)

Signals

- void [selectCustomer](#) ()
searchWidget::selectCustomer Signal that the Customer selected has changed

Public Member Functions

- [searchWidget](#) (QWidget *parent=0)
searchWidget::searchWidget Construct a search widget
- int [getCurrentCustomerId](#) ()
searchWidget::getCurrentCustomerId Return the id of the customer selected in the table
- bool [isCustomerSelected](#) () const
searchWidget::isCustomerSelected Return TRUE if a customer is selected, else FALSE
- void [selectCustomer](#) (int id)
searchWidget::selectCustomer Select the Customer with it id
- int [getIdCustomer](#) () const
searchWidget::getIdCustomer Return the Customer id of the Customer line selected
- void [setIdCustomer](#) (int idCustomer)
searchWidget::setIdCustomer Change the customer id by the new idCustomer

8.95.1 Detailed Description

Class for search in database.

Author

Antoine de Roquemaurel

8.95.2 Constructor & Destructor Documentation

8.95.2.1 Gui::Widgets::searchWidget::searchWidget (QWidget * parent = 0) [explicit]

[searchWidget::searchWidget](#) Construct a search widget

Parameters

<i>parent</i>	The QWidget parent
---------------	--------------------

8.95.3 Member Function Documentation

8.95.3.1 `int Gui::Widgets::searchWidget::getCurrentCustomerId ()`

[searchWidget::getCurrentCustomerId](#) Return the id of the customer selected in the table

Returns

id of the current customer

8.95.3.2 `int Gui::Widgets::searchWidget::getIdCustomer () const`

[searchWidget::getIdCustomer](#) Return the Customer id of the Customer line selected

Returns

The Customer ID

8.95.3.3 `bool Gui::Widgets::searchWidget::isCustomerSelected () const`

[searchWidget::isCustomerSelected](#) Return TRUE if a customer is selected, else FALSE

Returns

boolean

8.95.3.4 `void Gui::Widgets::searchWidget::search (QString toSearch) [slot]`

`searchWidget::launch` a search

Parameters

<i>toSearch</i>	The value to search
-----------------	---------------------

8.95.3.5 `void Gui::Widgets::searchWidget::selectCustomer (int id)`

[searchWidget::selectCustomer](#) Select the Customer with it *id*

Parameters

<i>id</i>	Customer ID
-----------	-------------

8.95.3.6 `void Gui::Widgets::searchWidget::setIdCustomer (int idCustomer)`

[searchWidget::setIdCustomer](#) Change the customer id by the new *idCustomer*

Parameters

<i>idCustomer</i>	Customer id
-------------------	-------------

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/searchwidget.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/searchwidget.cpp

8.96 Gui::Dialogs::StartedWindowsDialog Class Reference

The [StartedWindowsDialog](#) class Construct a Windows for the first begin.

```
#include <startedwindowsdialog.h>
```

Inheritance diagram for Gui::Dialogs::StartedWindowsDialog:



Public Slots

- void [checkFields](#) ()
StartedWindowsDialog::checkFields Check all fields of dialog components.
- void [backToPage2](#) ()
StartedWindowsDialog::backToPage2 Return to the second page.
- void [nextToPage2](#) ()
StartedWindowsDialog::nextToPage2 Go to the second page.
- void [nextToPage3](#) ()
StartedWindowsDialog::nextToPage3 Go to the third page.
- void [databaseTypeChanged](#) (const int index)
StartedWindowsDialog::databaseTypeChanged Listener on the Database type combobox.
- void [databaseTypeChanged](#) (void)
StartedWindowsDialog::databaseTypeChanged Listener on the Database type combobox.
- void [updateNextButton](#) ()
StartedWindowsDialog::updateNextButton Check if the next button is enabled.
- void [accept](#) ()
StartedWindowsDialog::accept Valid data inputed by user and add these data in Database.

Public Member Functions

- [StartedWindowsDialog](#) (QWidget *parent=0)
StartedWindowsDialog::StartedWindowsDialog Construct a [StartedWindowsDialog](#).
- void [fillFields](#) ()
StartedWindowsDialog::fillFields Fill line edits with the data of the user.
- QPixmap [getImage](#) (QString path, int width=256, int height=256)
StartedWindowsDialog::getImage Return a scaled image from the icon specified by it path. The image returned has a resolution of width*height (default 256*256)
- bool [isDatabaseTypeValid](#) ()

[*StartedWindowsDialog::isDatabaseTypeValid*](#) Return *TRUE* if settings of database type is valid else return *FALSE*.

- bool [*isDatabaseCentralized*](#) ()

[*StartedWindowsDialog::isDatabaseCentralized*](#) Return *TRUE* if the current type of database is centralized else *FALSE*.

8.96.1 Detailed Description

The [StartedWindowsDialog](#) class Construct a Windows for the first begin.

Author

Florent Berbie

See Also

[DatabaseSettingsWidget](#)

8.96.2 Constructor & Destructor Documentation

8.96.2.1 [Gui::Dialogs::StartedWindowsDialog::StartedWindowsDialog \(QWidget * *parent* = 0 \)](#) `[explicit]`

[StartedWindowsDialog::StartedWindowsDialog](#) Construct a [StartedWindowsDialog](#).

Parameters

<i>parent</i>	QWidget parent
---------------	----------------

8.96.3 Member Function Documentation

8.96.3.1 `void Gui::Dialogs::StartedWindowsDialog::databaseTypeChanged (const int index)` `[slot]`

[StartedWindowsDialog::databaseTypeChanged](#) Listener on the Database type combobox.

Parameters

<i>index</i>	Current index selected
--------------	------------------------

8.96.3.2 `QPixmap Gui::Dialogs::StartedWindowsDialog::getImage (QString path, int width = 256, int height = 256)`

[StartedWindowsDialog::getImage](#) Return a scaled image from the icon specified by it *path*. The image returned has a resolution of *width*height* (default 256*256)

Parameters

<i>path</i>	Icon path
<i>width</i>	Icon width
<i>height</i>	Icon height

Returns

Scaled image

8.96.3.3 bool Gui::Dialogs::StartedWindowsDialog::isDatabaseCentralized ()

[StartedWindowsDialog::isDatabaseCentralized](#) Return TRUE if the current type of database is centralized else FALSE.

Returns

boolean

8.96.3.4 bool Gui::Dialogs::StartedWindowsDialog::isDatabaseTypeValid ()

[StartedWindowsDialog::isDatabaseTypeValid](#) Return TRUE if settings of database type is valid else return FALSE.

Returns


boolean on the database type validity

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/dialogs/startedwindowsdialog.h
- /home/travis/build/FACT-Team/FactDev/src/gui/dialogs/startedwindowsdialog.cpp

8.97 StatisticModelTest Class Reference

Inheritance diagram for StatisticModelTest:



The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/tests/models/statisticmodeltest.h
- /home/travis/build/FACT-Team/FactDev/tests/models/statisticmodeltest.cpp

8.98 Models::Statistics Class Reference

Static Public Member Functions

- static QPair< int, double > [getTurnoverBetweenDates](#) (QDate begin, QDate end)
getTurnoverBetweenDates Compute the turnover between 2 dates
- static double [getGlobalTurnover](#) ()
Get the global turnover.

8.98.1 Member Function Documentation

8.98.1.1 double Statistics::getGlobalTurnover () [static]

Get the global turnover.

Returns

The global turnover

8.98.1.2 `QPair< int, double > Statistics::getTurnoverBetweenDates (QDate begin, QDate end)` `[static]`

getTurnoverBetweenDates Compute the turnover between 2 dates

Parameters

<i>begin</i>	The beginning date
<i>end</i>	The ending date

Returns

A Qpair who contains the number of billing and their costs

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/models/statistics.h
- /home/travis/build/FACT-Team/FactDev/src/models/statistics.cpp

8.99 Gui::Dialogs::StatisticsDialog Class Reference

The [StatisticsDialog](#) class window to have global informations or about a customer.

```
#include <statisticsdialog.h>
```

Inheritance diagram for Gui::Dialogs::StatisticsDialog:

**Public Member Functions**

- [StatisticsDialog](#) (bool global=true, int idCustomer=0, QWidget *parent=0)
Construct a windows [StatisticsDialog](#).
- void [updateUi](#) (int nbBills, int nbBillsPaid, int nbQuotes, int nbProjects)
Update interface (text)
- void [changeMainTitle](#) ()
Change the title of the windows if it's global stats or customer stats.
- QString [singularPlural](#) (int nb)
Get the correct terminaison.

8.99.1 Detailed Description

The [StatisticsDialog](#) class window to have global informations or about a customer.

8.99.2 Constructor & Destructor Documentation

8.99.2.1 `Gui::Dialogs::StatisticsDialog::StatisticsDialog (bool global = true, int idCustomer = 0, QWidget * parent = 0)`
[explicit]

Construct a windows [StatisticsDialog](#).

Parameters

<i>global</i>	if it's the global stats or customer stats
<i>idCustomer</i>	the id of the Customer

8.99.3 Member Function Documentation

8.99.3.1 QString Gui::Dialogs::StatisticsDialog::singularPlural (int *nb*)

Get the correct terminaison.

Parameters

<i>nb</i>	
-----------	--

8.99.3.2 void Gui::Dialogs::StatisticsDialog::updateUi (int *nbBills*, int *nbBillsPaid*, int *nbQuotes*, int *nbProjects*)

Update interface (text)

Parameters

<i>nbBills</i>	
<i>nbBillsPaid</i>	
<i>nbQuotes</i>	
<i>nbProjects</i>	

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/dialogs/statisticsdialog.h
- /home/travis/build/FACT-Team/FactDev/src/gui/dialogs/statisticsdialog.cpp

8.100 Utils::String Class Reference

The Utils class.

```
#include <string.h>
```

Static Public Member Functions

- static QString [firstLetterToUpper](#) (QString s)
String::firstLetterToUpper Put the first letter of a string in capslock.
- static QString [getExtensionFile](#) (QString fileName)
String::getExtensionFile Get the extension file of the file named fileName

8.100.1 Detailed Description

The Utils class.

Author

Antoine de Roquemaurel

8.100.2 Member Function Documentation

8.100.2.1 QString Utils::String::firstLetterToUpper (QString s) [static]

[String::firstLetterToUpper](#) Put the first letter of a string in capslock.

Parameters

<i>s</i>	The string to display
----------	-----------------------

Returns

The new string with caps

8.100.2.2 QString Utils::String::getExtensionFile (QString *fileName*) [static]

[String::getExtensionFile](#) Get the extension file of the file named *fileName*

Parameters

<i>file</i>	File name
-------------	-----------

Returns

extension of file

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/utils/string.h
- /home/travis/build/FACT-Team/FactDev/src/utils/string.cpp

8.101 StringTest Class Reference

Inheritance diagram for StringTest:



The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/tests/utils/stringtest.h
- /home/travis/build/FACT-Team/FactDev/tests/utils/stringtest.cpp

8.102 Mustache::Tag Struct Reference

```
#include <mustache.h>
```

Public Types

- enum [Type](#) { **Null**, **Value**, [SectionStart](#), [InvertedSectionStart](#), [SectionEnd](#), [Partial](#), [Comment](#), [SetDelimiter](#) }
- enum **EscapeMode** { **Escape**, **Unescape**, **Raw** }

Public Attributes

- [Type](#) **type**
- QString **key**
- int **start**
- int **end**
- EscapeMode **escapeMode**

8.102.1 Detailed Description

Holds properties of a tag in a mustache template.

8.102.2 Member Enumeration Documentation

8.102.2.1 enum Mustache::Tag::Type

Enumerator

SectionStart A {{key}} or {{{key}}} tag.

InvertedSectionStart A {{#section}} tag.

SectionEnd An {{^inverted-section}} tag.

Partial A {{/section}} tag.

Comment A {{^partial}} tag.

SetDelimiter A {{! comment }} tag. A {{=<% %>=}} tag

The documentation for this struct was generated from the following file:

- /home/travis/build/FACT-Team/FactDev/src/libs/qt-mustache/src/mustache.h

8.103 testadder Class Reference

The documentation for this class was generated from the following file:

- /home/travis/build/FACT-Team/FactDev/tests/QStringRunner/testadder.h

8.104 TestAdder< T > Class Template Reference

Public Member Functions

- **TestAdder** (const QString &name)

The documentation for this class was generated from the following file:

- /home/travis/build/FACT-Team/FactDev/tests/QStringRunner/testadder.cpp

8.105 TestMustache Class Reference

Inheritance diagram for TestMustache:



The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/libs/qt-mustache/tests/test_mustache.h
- /home/travis/build/FACT-Team/FactDev/src/libs/qt-mustache/tests/test_mustache.cpp

8.106 TestRunner Class Reference

Public Member Functions

- `template<typename T >`
char **RegisterTest** (QString name)
- int **RunAll** ()

Static Public Member Functions

- static [TestRunner](#) & **Instance** ()

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/tests/QTestRunner/testrunner.h
- /home/travis/build/FACT-Team/FactDev/tests/QTestRunner/testrunner.cpp

8.107 Generator::TexGenerator Class Reference

The [TexGenerator](#) class Generate a LaTeX file.

```
#include <texgenerator.h>
```

Public Member Functions

- [TexGenerator](#) (QString tpl)
[TexGenerator::TexGenerator](#) Construct a [TexGenerator](#).
- void [generate](#) (QVariantHash data, QString path)
[TexGenerator::generate](#) Generate a LaTeX file into a file specified by the path and which contains data

8.107.1 Detailed Description

The [TexGenerator](#) class Generate a LaTeX file.

8.107.2 Constructor & Destructor Documentation

8.107.2.1 Generator::TexGenerator::TexGenerator (QString *tpl*)

[TexGenerator::TexGenerator](#) Construct a [TexGenerator](#).

Parameters

<i>tpl</i>	Template LaTeX to apply
------------	-------------------------

8.107.3 Member Function Documentation

8.107.3.1 void Generator::TexGenerator::generate (QVariantHash *data*, QString *path*)

[TexGenerator::generate](#) Generate a LaTeX file into a file specified by the *path* and which contains *data*

Parameters

<i>data</i>	Data to integrate in the file
<i>path</i>	Path of the out file

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/generator/texgenerator.h
- /home/travis/build/FACT-Team/FactDev/src/generator/texgenerator.cpp

8.108 Gui::Widgets::Delegates::TextareaDelegate Class Reference

The [TextareaDelegate](#) class.

```
#include <textareadelegate.h>
```

Inheritance diagram for Gui::Widgets::Delegates::TextareaDelegate:



Public Member Functions

- [TextareaDelegate](#) (QWidget *parent=0)
[TextareaDelegate::TextareaDelegate](#).
- void [setModelData](#) (QWidget *editor, QAbstractItemModel *model, const QModelIndex &index) const
[TextareaDelegate::setModelData](#) Sets the data model from content in editor.
- void [updateEditorGeometry](#) (QWidget *editor, const QStyleOptionViewItem &option, const QModelIndex &) const
[TextareaDelegate::updateEditorGeometry](#) Update the editor for the item specified by index according to the style option given.
- QWidget * [createEditor](#) (QWidget *parent, const QStyleOptionViewItem &, const QModelIndex &) const
[TextareaDelegate::createEditor](#) Return a QTextEdit specified by index item defined by the parent widget and style option which are used to control how the editor widgets appears.
- void [setEditorData](#) (QWidget *editor, const QModelIndex &index) const
[TextareaDelegate::setEditorData](#) Sets the data to be displayed and edited by the editor from the data model item specified by the model index

8.108.1 Detailed Description

The [TextareaDelegate](#) class.

Author

Antoine de Roquemaurel

8.108.2 Constructor & Destructor Documentation

8.108.2.1 Gui::Widgets::Delegates::TextareaDelegate::TextareaDelegate (QWidget * *parent* = 0)[TextareaDelegate::TextareaDelegate.](#)

Parameters

<i>parent</i>	
---------------	--

8.108.3 Member Function Documentation

8.108.3.1 QWidget * Gui::Widgets::Delegates::TextareaDelegate::createEditor (QWidget * *parent*, const QStyleOptionViewItem & , const QModelIndex &) const

[TextareaDelegate::createEditor](#) Return a QTextEdit specified by *index* item defined by the *parent* widget and style *option* which are used to control how the editor widgets appears.

Parameters

<i>parent</i>	Widget parent
<i>option</i>	Option style
<i>index</i>	Index for editing

Returns

[TextareaDelegate](#)8.108.3.2 void Gui::Widgets::Delegates::TextareaDelegate::setEditorData (QWidget * *editor*, const QModelIndex & *index*) const

[TextareaDelegate::setEditorData](#) Sets the data to be displayed and edited by the *editor* from the data model item specified by the model *index*

Parameters

<i>editor</i>	Data edited
<i>index</i>	Index of the model to edit

8.108.3.3 void Gui::Widgets::Delegates::TextareaDelegate::setModelData (QWidget * *editor*, QAbstractItemModel * *model*, const QModelIndex & *index*) const

[TextareaDelegate::setModelData](#) Sets the data model from content in editor.

Parameters

<i>editor</i>	Data edited
<i>index</i>	Index of the model to edit

8.108.3.4 void Gui::Widgets::Delegates::TextareaDelegate::updateEditorGeometry (QWidget * *editor*, const QStyleOptionViewItem & *option*, const QModelIndex &) const

[TextareaDelegate::updateEditorGeometry](#) Update the *editor* for the item specified by *index* according to the style *option* given.

Parameters

<i>editor</i>	Editor widget to update
<i>option</i>	Style option
<i>index</i>	Item index

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/delegates/textareadelegate.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/delegates/textareadelegate.cpp

8.109 Models::Unit Class Reference

The [Unit](#) class An unity for billing calculs.

```
#include <unit.h>
```

Public Member Functions

- [Unit](#) ([TypeUnit](#) type)
Unit Construct an unit with init type.
- [Unit](#) ()
Unit Construct an unit.
- [QString](#) [toString](#) (const bool plural=false)
toString Return String for unit type.
- [TypeUnit](#) [gettype](#) () const
gettype The unit Type
- void [setType](#) (const [TypeUnit](#) &type)
setType Change the unit Type
- bool [operator==](#) (const [Unit](#) &u)
operator == define the operator "==" to compare two [Unit](#)
- bool [operator!=](#) (const [Unit](#) &u)
operator != define the operator "!=" to compare two [Unit](#)

8.109.1 Detailed Description

The [Unit](#) class An unity for billing calculs.

8.109.2 Constructor & Destructor Documentation

8.109.2.1 Models::Unit::Unit ([TypeUnit](#) type)

[Unit](#) Construct an unit with init type.

Parameters

<i>type</i>	The unit Type;
-------------	----------------

8.109.3 Member Function Documentation

8.109.3.1 [TypeUnit](#) Models::Unit::gettype () const

gettype The unit Type

Returns

The unit Type

8.109.3.2 bool Models::Unit::operator!= (const Unit & *u*)

operator != define the operator "!=" to compare two [Unit](#)

Parameters

<i>c</i>	the Unit to compare with the current Contributory
----------	---

Returns

true if the [Unit](#) are different else false

8.109.3.3 bool Models::Unit::operator== (const Unit & *u*)

operator == define the operator "==" to compare two [Unit](#)

Parameters

<i>c</i>	the Unit to compare with the current Contributory
----------	---

Returns

true if the [Unit](#) are equals else false

8.109.3.4 void Models::Unit::setType (const TypeUnit & *type*)

setType Change the unit Type

Parameters

<i>type</i>	The new unit type.
-------------	--------------------

8.109.3.5 QString Models::Unit::toString (const bool *plural* = false)

toString Return String for unit type.

Returns

The unit in String

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/models/unit.h
- /home/travis/build/FACT-Team/FactDev/src/models/unit.cpp

8.110 Gui::Widgets::Delegates::UnitComboDelegate Class Reference

The [UnitComboDelegate](#) class.

```
#include <unitcomodelegate.h>
```

Inheritance diagram for Gui::Widgets::Delegates::UnitComboDelegate:



Public Member Functions

- [UnitComboDelegate](#) (QObject *parent=0)
[UnitComboDelegate::UnitComboDelegate](#).
- QWidget * [createEditor](#) (QWidget *parent, const QStyleOptionViewItem &option, const QModelIndex &index) const
[UnitComboDelegate::createEditor](#) Return a ComboBox specified by *index* item defined by the *parent* widget and style *option* which are used to control how the editor widgets appears.
- void [paint](#) (QPainter *painter, const QStyleOptionViewItem &option, const QModelIndex &index) const
[UnitComboDelegate::paint](#) Renders the delegate using the given painter and style option for the item specified by *index*

8.110.1 Detailed Description

The [UnitComboDelegate](#) class.

8.110.2 Constructor & Destructor Documentation

8.110.2.1 [Gui::Widgets::Delegates::UnitComboDelegate::UnitComboDelegate \(QObject * *parent* = 0 \)](#)

[UnitComboDelegate::UnitComboDelegate](#).

Parameters

<i>parent</i>	
---------------	--

8.110.3 Member Function Documentation

8.110.3.1 [QWidget * Gui::Widgets::Delegates::UnitComboDelegate::createEditor \(QWidget * *parent*, const QStyleOptionViewItem & *option*, const QModelIndex & *index* \) const](#) [virtual]

[UnitComboDelegate::createEditor](#) Return a ComboBox specified by *index* item defined by the *parent* widget and style *option* which are used to control how the editor widgets appears.

Parameters

<i>parent</i>	Widget parent
<i>option</i>	Option style
<i>index</i>	Index for editing

Returns

ComboBox

Implements [Gui::Widgets::Delegates::ComboBoxDelegate](#).

8.110.3.2 void Gui::Widgets::Delegates::UnitComboDelegate::paint (QPainter * *painter*, const QStyleOptionViewItem & *option*, const QModelIndex & *index*) const [virtual]

[UnitComboDelegate::paint](#) Renders the delegate using the given *painter* and style *option* for the item specified by *index*

Parameters

<i>parent</i>	Widget parent
<i>option</i>	Option style
<i>index</i>	Index for editing

Implements [Gui::Widgets::Delegates::ComboBoxDelegate](#).

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/delegates/unitcombodelegate.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/delegates/unitcombodelegate.cpp

8.111 Models::User Class Reference

The [User](#) class [User](#) of it application.

```
#include <user.h>
```

Inheritance diagram for Models::User:



Public Member Functions

- [User](#) ()
User::User. Construct an [User](#).
- [User](#) (int id)
User::User. Construct a [User](#) with the identify *id*
- void [commit](#) ()
User::commit Update user data in [User](#) table on the database.
- void [hydrat](#) (int id=1)
User::hydrat Get data of the user who is specified by *id* from the database.
- void [remove](#) ()
remove Remove the current [User](#)
- QVariantHash [getDataMap](#) ()
getDataMap Get all data of model with a HashMap key/value
- void [updateFolders](#) (void)
MainWindow::updateFolders Make directories which contain quotes and billings. Directories are the same than theirs of the Tree organisation (without Projects).
- QString [getTitle](#) () const
User::getTitle Return a short description of [User](#) (company) activity.
- void [setTitle](#) (const QString &title)

- User::setTitle* Modify the user/company activities description
- QString **getNoSiret** () const
 - User::getNoSiret* Return the SIRET number (company registration number)
- void **setNoSiret** (const QString &noSiret)
 - User::setNoSiret* Modify the SIRET number (company registration number) noSiret
- QPixmap * **getImage** ()
 - User::getImage* Return the compagny image.
- void **setImage** (QPixmap *image)
 - User::setImage* Change the current image by the new image
- QString **getWorkspaceName** () const
 - User::getWorkspaceName* Return the name of the workspace user.
- void **setWorkspaceName** (const QString &workspaceName)
 - User::setWorkspaceName* Change the current workspace name by the new workspaceName
- QString **getWorkspacePath** () const
 - User::getWorkspacePath* Return the path of the workspace user.
- void **setWorkspacePath** (const QString &workspacePath)
 - User::setWorkspacePath* Change the current workspace path by the new workspacePath
- bool **operator==** (const **User** &u)
 - User::operator ==* Re-define the operator "==" to compare if the current **User** is the same to the other **User** c Return TRUE if both Users are the same, else FALSE.
- bool **operator!=** (const **User** &u)
 - User::operator !=* Re-define the operator "!=" to compare if the current **User** is differnt to the other **User** c Return TRUE if both Users are different, else FALSE.
- QString **getPdflatexPath** () const
 - getPdflatexPath* The path of pdflatex
- void **setPdflatexPath** (const QString &getPdflatexPath)
 - setPdflatexPath* Change the pdflatex command path.
- int **getNbHoursPerDays** ()
 - nbHoursPerDays* The number of hours per days who the user work.
- int **getNbDaysPerMonths** ()
 - getNbDaysPerMonths* The number of days per months who the user work.

Additional Inherited Members

8.111.1 Detailed Description

The **User** class **User** of it application.

Author

Florent Berbie

8.111.2 Constructor & Destructor Documentation

8.111.2.1 Models::User::User (int id)

User::User. Construct a **User** with the identify *id*

Parameters

<i>id</i>	User id
-----------	-------------------------

8.111.3 Member Function Documentation

8.111.3.1 QVariantHash Models::User::getDataMap () [virtual]

getDataMap Get all data of model with a HashMap key/value

Returns

Model's data

Implements [Models::IModel](#).

8.111.3.2 QPixmap * Models::User::getImage ()

[User::getImage](#) Return the compagny image.

Returns

compagny image

8.111.3.3 int Models::User::getNbDaysPerMonths ()

getNbDaysPerMonths The number of days per months who the user work.

Returns

The number of days per months

8.111.3.4 int Models::User::getNbHoursPerDays ()

nbHoursPerDays The number of hours per days who the user work.

Returns

The number of hours per days

8.111.3.5 QString Models::User::getNoSiret () const

[User::getNoSiret](#) Return the SIRET number (company registration number)

Returns

SIRET number

8.111.3.6 QString Models::User::getPdflatexPath () const

getPdflatexPath The path of pdflatex

Returns

The pdflatex path

8.111.3.7 QString Models::User::getTitle () const

[User::getTitle](#) Return a short description of [User](#) (company) activity.

Returns

a short description of user (company) activity

8.111.3.8 QString Models::User::getWorkspaceName () const

[User::getWorkspaceName](#) Return the name of the workspace user.

Returns

workspace name

8.111.3.9 QString Models::User::getWorkspacePath () const

[User::getWorkspacePath](#) Return the path of the workspace user.

Returns

workspace path

8.111.3.10 void Models::User::hydrat (int *id* = 1) [virtual]

[User::hydrat](#) Get data of the user who is specified by *id* from the database.

Parameters

<i>id</i>	User identify
-----------	-------------------------------

Implements [Models::IModel](#).

8.111.3.11 bool Models::User::operator!= (const [User](#) & *u*)

[User::operator !=](#) Re-define the operator "!=" to compare if the current [User](#) is differnt to the other [User](#) c Return TRUE if both Users are different, else FALSE.

Parameters

<i>u</i>	User to compare
----------	---------------------------------

Returns

boolean

8.111.3.12 bool Models::User::operator== (const [User](#) & *u*)

[User::operator ==](#) Re-define the operator "==" to compare if the current [User](#) is the same to the other [User](#) c Return TRUE if both Users are the same, else FALSE.

Parameters

<i>u</i>	User to compare
----------	---------------------------------

Returns

boolean

8.111.3.13 void Models::User::setImage (QPixmap * *image*) [virtual]

[User::setImage](#) Change the current image by the new *image*

Parameters

<i>image</i>	New image
--------------	-----------

Reimplemented from [Models::People](#).

8.111.3.14 void Models::User::setNoSiret (const QString & *noSiret*)

[User::setNoSiret](#) Modify the SIRET number (company registration number) *noSiret*

Parameters

<i>noSiret</i>	SIRET number
----------------	--------------

8.111.3.15 void Models::User::setPdflatexPath (const QString & *getPdflatexPath*)

setPdflatexPath Change the pdflatex command path.

Parameters

<i>getPdflatexPath</i>	The new command
------------------------	-----------------

8.111.3.16 void Models::User::setTitle (const QString & *title*)

[User::setTitle](#) Modify the user/company activities *description*

Parameters

<i>title</i>	Short description on activity(ies) of User company
--------------	--

8.111.3.17 void Models::User::setWorkspaceName (const QString & *workspaceName*)

[User::setWorkspaceName](#) Change the current workspace name by the new *workspaceName*

Parameters

<i>workspaceName</i>	
----------------------	--

8.111.3.18 void Models::User::setWorkspacePath (const QString & *workspacePath*)

[User::setWorkspacePath](#) Change the current workspace path by the new *workspacePath*

Parameters

<i>workspacePath</i>	
----------------------	--

8.111.3.19 void Models::User::updateFolders (void)

MainWindow::updateFolders Make directories which contain quotes and billings. Directories are the same than theirs of the Tree organisation (without Projects).

Organisation of folders are formed like this:

- COMPANY CustomerLastname CustomerFirstname/
 - Quotes/
 - * quote1 ...
 - Billings/
 - * billing1 ...

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/models/user.h
- /home/travis/build/FACT-Team/FactDev/src/models/user.cpp

8.112 Databases::UserDatabase Class Reference

The [UserDatabase](#) class Access to User data in the the table User of the [Database](#)

```
#include <userdatabase.h>
```

Inheritance diagram for Databases::UserDatabase:



Public Member Functions

- [Models::User](#) * [getUser](#) (const int pld=1)
 [UserDatabase::getUser](#) Get informations about the user (identified by 'pld')
- void [updateUser](#) (const [Models::User](#) &)
 [UserDatabase::updateUser](#) Update informations about the user.
- QPixmap [getUserImage](#) (const int pld=1)
 [UserDatabase::getUserImage](#) Return a User image.
- void [setUserImage](#) ([Models::User](#) &pUser)
 [UserDatabase::setUserImage](#) Change the image of the customer pCustomer

Static Public Member Functions

- static [UserDatabase](#) * [instance](#) () throw (DbException*)
 [UserDatabase::getInstance](#) Return an instance of [UserDatabase](#).

Additional Inherited Members

8.112.1 Detailed Description

The [UserDatabase](#) class Access to User data in the the table User of the [Database](#)

Author

Florent Berbie

See Also

[Database](#)
[User](#)

8.112.2 Member Function Documentation

8.112.2.1 `Models::User * Databases::UserDatabase::getUser (const int pld = 1)`

[UserDatabase::getUser](#) Get informations about the user (identified by 'pld')

Parameters

<i>pld</i>	user id (1 default)
------------	---------------------

Returns

the user

8.112.2.2 `QPixmap Databases::UserDatabase::getUserImage (const int pld = 1)`

[UserDatabase::getUserImage](#) Return a User image.

Parameters

<i>pld</i>	Customer id
------------	-------------

Returns

User image

8.112.2.3 `UserDatabase * Databases::UserDatabase::instance () throw DbException *` [static]

[UserDatabase::getInstance](#) Return an instance of [UserDatabase](#).

Returns

Instance of [UserDatabase](#)

8.112.2.4 `void Databases::UserDatabase::setUserImage (Models::User & pUser)`

[UserDatabase::setUserImage](#) Change the image of the customer *pCustomer*

Parameters

<i>pUser</i>	User
--------------	------

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/database/userdatabase.h
- /home/travis/build/FACT-Team/FactDev/src/database/userdatabase.cpp

8.113 UserDatabaseTest Class Reference

Inheritance diagram for UserDatabaseTest:



The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/tests/database/userdatabasetest.h
- /home/travis/build/FACT-Team/FactDev/tests/database/userdatabasetest.cpp

8.114 Gui::Dialogs::UserDataDialog Class Reference

The [UserDataDialog](#) class Window to fill user data.

```
#include <userdatadialog.h>
```

Inheritance diagram for Gui::Dialogs::UserDataDialog:



Public Slots

- void [checkFields](#) ()
[UserDataDialog::checkFields](#) Check all fields of dialog components.

Public Member Functions

- [UserDataDialog](#) (QWidget *parent=0)
[UserDataDialog::UserDataDialog](#) Construct a window with user data.
- void [fillFields](#) ()
[UserDataDialog::fillFields](#) Fill line edits with the data of the user.
- void [accept](#) ()
[UserDataDialog::accept](#) Valid data inputed by user and add these data in Database.

- void [reject](#) ()
[UserDataDialog::reject](#) Cancel the operation and close the windows.
- void **browseWorkspacePath** ()

8.114.1 Detailed Description

The [UserDataDialog](#) class Window to fill user data.

Author

Florent Berbie

See Also

Project

8.114.2 Constructor & Destructor Documentation

8.114.2.1 [Gui::Dialogs::UserDataDialog::UserDataDialog](#) ([QWidget](#) * *parent* = 0) [explicit]

[UserDataDialog::UserDataDialog](#) Construct a window with user data.

Parameters


<i>parent</i>	
---------------	--

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/dialogs/userdatadialog.h
- /home/travis/build/FACT-Team/FactDev/src/gui/dialogs/userdatadialog.cpp

8.115 UserModelTest Class Reference

Inheritance diagram for UserModelTest:



The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/tests/models/usermodeltest.h
- /home/travis/build/FACT-Team/FactDev/tests/models/usermodeltest.cpp

8.116 Gui::Utils::WindowSettings Class Reference

The [WindowSettings](#) class Utils function on windows.

```
#include <windowsettings.h>
```

Static Public Member Functions

- static void [setMaximumSize](#) (QWidget &w)
*[WindowSettings::setMaximumSize](#) Adapt the resolution of the window *w* to take all screen.*
- static void [setPositionToCenter](#) (QWidget &w)
*[WindowSettings::setPositionToCenter](#) Place the current window *w* to the center of the screen.*

8.116.1 Detailed Description

The [WindowSettings](#) class Utils function on windows.

Author

Florent Berbie

8.116.2 Member Function Documentation

8.116.2.1 void Gui::Utils::WindowSettings::setMaximumSize (QWidget & *w*) [static]

[WindowSettings::setMaximumSize](#) Adapt the resolution of the window *w* to take all screen.

Parameters

<i>w</i>	Current Window
----------	----------------

8.116.2.2 void Gui::Utils::WindowSettings::setPositionToCenter (QWidget & *w*) [static]

[WindowSettings::setPositionToCenter](#) Place the current window *w* to the center of the screen.

Parameters

<i>w</i>	Current Window
----------	----------------

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/Utils/windowsettings.h
- /home/travis/build/FACT-Team/FactDev/src/gui/Utils/windowsettings.cpp

Index

- add
 - Gui::Widgets::ContributoriesWidget, 88
- addBill
 - Gui::MainWindow, 138
- addBilling
 - Databases::BillingDatabase, 33
- addBillingProject
 - Databases::BillingDatabase, 33
- addBillingToProject
 - Utils::HierarchicalSystem, 127
- addContributory
 - Databases::ContributoryDatabase, 94
 - Models::Billing, 27
 - Models::ContributoriesList, 80
- addCustomer
 - Databases::CustomerDatabase, 103
- addDoc
 - Gui::MainWindow, 138
- addProject
 - Databases::ProjectDatabase, 167
 - Gui::MainWindow, 138
 - Gui::Widgets::ContributoriesWidget, 88
 - Models::ContributoriesList, 81
- AddProjectDialog
 - Gui::Dialogs::AddProjectDialog, 22
- addProjectToCustomer
 - Utils::HierarchicalSystem, 127
- addQuote
 - Gui::MainWindow, 138
- AddQuoteDialog
 - Gui::Dialogs::AddQuoteDialog, 23
- addRateProject
 - Databases::RateDatabase, 180
- allProjectsChosen
 - Gui::Widgets::WdgModels::ProjectContributories-TableModel, 163
- append
 - Gui::Widgets::WdgModels::BillingsTableModel, 41
 - Gui::Widgets::WdgModels::ContributoriesTable-Model, 85
 - Gui::Widgets::WdgModels::CustomersTableModel, 110
 - Gui::Widgets::WdgModels::ProjectContributories-TableModel, 163
 - Gui::Widgets::WdgModels::ProjectsTableModel, 172
- beginDateControl
 - Gui::Dialogs::ComputeTurnoverDialog, 75
- Billing
 - Models::Billing, 27
- BillingDatabaseTest, 39
- BillingModelTest, 39
- BillingsTableModel
 - Gui::Widgets::WdgModels::BillingsTableModel, 41
- BrowseImageWidget
 - Gui::Widgets::BrowseImageWidget, 44
- bytesToPixmap
 - Gui::Utils::Image, 129
- canEval
 - CounterContext, 97
 - Mustache::Context, 77
 - Mustache::QtVariantContext, 176
- changeDatabase
 - Databases::Database, 115
- check
 - Gui::Widgets::CheckFields::CheckEmail, 48
 - Gui::Widgets::CheckFields::CheckFieldsLetters, 50
 - Gui::Widgets::CheckFields::CheckFieldsNumbers, 53
 - Gui::Widgets::CheckFields::CheckIpAddress, 54
 - Gui::Widgets::CheckFields::CheckLogin, 55
 - Gui::Widgets::CheckFields::CheckPhone, 57
 - Gui::Widgets::CheckFields::CheckPortNumber, 59
 - Gui::Widgets::CheckFields::CheckPostalCode, 60
 - Gui::Widgets::CheckFields::CheckSiretNumber, 63
 - Gui::Widgets::CheckFields::CheckUntilField, 64
 - Gui::Widgets::CheckFields::CheckValidField, 65
 - Gui::Widgets::CheckFields::CheckWebsite, 66
 - Gui::Widgets::CheckFields::ICheckField, 128
- CheckCity
 - Gui::Widgets::CheckFields::CheckCity, 46
- CheckCountry
 - Gui::Widgets::CheckFields::CheckCountry, 47
- CheckEmail
 - Gui::Widgets::CheckFields::CheckEmail, 48
- CheckFieldsLetters
 - Gui::Widgets::CheckFields::CheckFieldsLetters, 49
- CheckFieldsNumbers
 - Gui::Widgets::CheckFields::CheckFieldsNumbers, 52
- CheckIpAddress
 - Gui::Widgets::CheckFields::CheckIpAddress, 54
- CheckLogin
 - Gui::Widgets::CheckFields::CheckLogin, 55
- CheckName
 - Gui::Widgets::CheckFields::CheckName, 56
- CheckPhone
 - Gui::Widgets::CheckFields::CheckPhone, 57

- CheckPortNumber
 - Gui::Widgets::CheckFields::CheckPortNumber, 59
- CheckPostalCode
 - Gui::Widgets::CheckFields::CheckPostalCode, 60
- CheckQLineEdit
 - Gui::Widgets::CheckFields::CheckQLineEdit, 61
- CheckSiretNumber
 - Gui::Widgets::CheckFields::CheckSiretNumber, 63
- CheckUntilField
 - Gui::Widgets::CheckFields::CheckUntilField, 64
- CheckValidField
 - Gui::Widgets::CheckFields::CheckValidField, 65
- CheckWebsite
 - Gui::Widgets::CheckFields::CheckWebsite, 66
- ChoseDirectoryWidget
 - Gui::Widgets::Path::ChoseDirectoryWidget, 67
- ChoseFileWidget
 - Gui::Widgets::Path::ChoseFileWidget, 68
- ChosePathWidget
 - Gui::Widgets::Path::ChosePathWidget, 70
- columnCount
 - Gui::Widgets::WdgModels::BillingsTableModel, 41
 - Gui::Widgets::WdgModels::ContributoriesTable-Model, 85
 - Gui::Widgets::WdgModels::CustomersTableModel, 110
 - Gui::Widgets::WdgModels::ProjectContributories-TableModel, 163
 - Gui::Widgets::WdgModels::ProjectsTableModel, 172
- ComboBoxDelegate
 - Gui::Widgets::Delegates::ComboBoxDelegate, 72
- ComboBoxModelWidget
 - Gui::Widgets::ComboBoxModelWidget, 74
- Comment
 - Mustache::Tag, 202
- commit
 - Models::Customer, 99
- Context
 - Mustache::Context, 77
- ContributoriesDatabaseTest, 78
- ContributoriesTableModel
 - Gui::Widgets::WdgModels::ContributoriesTable-Model, 84
- ContributoriesWidget
 - Gui::Widgets::ContributoriesWidget, 88
- Contributory
 - Models::Contributory, 90
- ContributoryListTest, 96
- ContributoryModelTest, 96
- count
 - Gui::Widgets::ContributoriesWidget, 88
 - Gui::Widgets::WdgModels::BillingsTableModel, 41
 - Gui::Widgets::WdgModels::ContributoriesTable-Model, 85
 - Gui::Widgets::WdgModels::CustomersTableModel, 110
 - Gui::Widgets::WdgModels::ProjectsTableModel, 172
- CounterContext, 97
 - canEval, 97
 - eval, 97, 98
 - stringValue, 98
- createEditor
 - Gui::Widgets::Delegates::ComboBoxDelegate, 72
 - Gui::Widgets::Delegates::DoubleSpinBoxDelegate, 123
 - Gui::Widgets::Delegates::ProjectComboDelegate, 161
 - Gui::Widgets::Delegates::TextareaDelegate, 206
 - Gui::Widgets::Delegates::UnitComboDelegate, 210
- Customer
 - Models::Customer, 99
- CustomerContextualMenu
 - Gui::Widgets::CustomerContextualMenu, 102
- CustomerDataWidget
 - Gui::Widgets::CustomerDataWidget, 108
- CustomerDatabaseTest, 107
- CustomerModelTest, 109
- CustomersTableModel
 - Gui::Widgets::WdgModels::CustomersTableModel, 110
- DB_FILENAME
 - Parameters, 143
- data
 - Gui::Widgets::WdgModels::BillingsTableModel, 41
 - Gui::Widgets::WdgModels::ContributoriesTable-Model, 85
 - Gui::Widgets::WdgModels::CustomersTableModel, 110
 - Gui::Widgets::WdgModels::ProjectContributories-TableModel, 164
 - Gui::Widgets::WdgModels::ProjectsTableModel, 172
- DatabaseSettingsWidget
 - Gui::Widgets::DatabaseSettingsWidget, 117
- databaseTypeChanged
 - Gui::Dialogs::StartedWindowsDialog, 195
- Databases, 17
- Databases::AccessDatabase, 21
- Databases::BillingDatabase, 31
 - addBilling, 33
 - addBillingProject, 33
 - getAllBillingsOfProject, 33
 - getBilling, 33
 - getBillingsTable, 35
 - getBills, 35
 - getBillsBetweenDates, 35
 - getBillsPaid, 35
 - getMaxBillingNumber, 36
 - getMaxBillingNumberOfCustomer, 36
 - getMaxQuoteNumber, 36
 - getMaxQuoteNumberOfCustomer, 36
 - getNbBills, 36
 - getNbBillsPaid, 37

- getNbDocs, 37
- getNbQuotes, 37
- instance, 37
- isBillingPaid, 37
- removeBilling, 39
- removeBillingProject, 39
- Databases::ContributoryDatabase, 93
 - addContributory, 94
 - getContributoriesByBilling, 94
 - getContributoriesByBillingAndProject, 95
 - getContributory, 95
 - instance, 95
 - removeContributory, 96
- Databases::CustomerDatabase, 102
 - addCustomer, 103
 - getCustomer, 103, 104
 - getCustomerImage, 104
 - getCustomers, 104
 - getCustomersTable, 104
 - getItemCustomer, 104
 - getItemProject, 106
 - getItemRoot, 106
 - getNbCustomers, 106
 - getTree, 106
 - instance, 106
 - removeCustomer, 107
 - setCustomerImage, 107
 - updateCustomer, 107
- Databases::Database, 113
 - changeDatabase, 115
 - executeFile, 115
 - instance, 115
 - lastError, 115
 - setDatabase, 115
 - value, 115
- Databases::ProjectDatabase, 166
 - addProject, 167
 - getAllProjects, 167
 - getCostProjects, 167
 - getNbProjects, 167
 - getProject, 168
 - getProjects, 168
 - getProjectsOfCustomer, 168
 - getProjectsTable, 168
 - instance, 170
 - removeProject, 170
 - updateProject, 170
- Databases::RateDatabase, 179
 - addRateProject, 180
 - getRate, 180
 - instance, 180
 - updateRateProject, 180
- Databases::UserDatabase, 216
 - getUser, 217
 - getUserImage, 217
 - instance, 217
 - setUserImage, 217
- DbException
 - Exceptions::DbException, 119
- deleteIfNotNull
 - Utils::pointers, 154
- DialogAddCustomer
 - Gui::Dialogs::DialogAddCustomer, 120
- DoubleSpinBoxDelegate
 - Gui::Widgets::Delegates::DoubleSpinBoxDelegate, 122
- editUser
 - Gui::MainWindow, 138
- endDateControl
 - Gui::Dialogs::ComputeTurnoverDialog, 76
- error
 - Mustache::Renderer, 183
- errorPartial
 - Mustache::Renderer, 183
- errorPos
 - Mustache::Renderer, 183
- eval
 - CounterContext, 97, 98
 - Mustache::Context, 77
 - Mustache::QtVariantContext, 176
- Exceptions::DbException, 118
 - DbException, 119
 - popupMessage, 119
- Exceptions::FileException, 125
 - FileException, 125
 - popupMessage, 126
- executeFile
 - Databases::Database, 115
- FileChoseWidget, 124
- FileException
 - Exceptions::FileException, 125
- fillLabels
 - Gui::Dialogs::ComputeTurnoverDialog, 76
- fillQuoteBilling
 - Gui::Dialogs::AddQuoteDialog, 24
- filterOnBillsOrQuotes
 - Models::Search, 185
- filterOnCompany
 - Models::Search, 185
- filterOnContributories
 - Models::Search, 185
- filterOnCustomersWithoutProject
 - Models::Search, 186
- filterOnNumberElements
 - Models::Search, 186
- filterOnProjects
 - Models::Search, 186
- filterOnReferentLastname
 - Models::Search, 186
- filterOnVarcharElements
 - Models::Search, 186
- firstLetterToUpper
 - Utils::String, 200
- flags
 - Gui::Widgets::WdgModels::BillingsTableModel, 42

- Gui::Widgets::WdgModels::ContributoriesTable-Model, 85
- Gui::Widgets::WdgModels::CustomersTableModel, 112
- Gui::Widgets::WdgModels::ProjectContributories-TableModel, 164
- Gui::Widgets::WdgModels::ProjectsTableModel, 173
- fn_t
 - Mustache::QtVariantContext, 176
- generate
 - Generator::PdfGenerator, 145
 - Generator::TexGenerator, 205
- Generation, 126
- Generator::PdfGenerator, 145
 - generate, 145
 - PdfGenerator, 145
- Generator::TexGenerator, 203
 - generate, 205
 - TexGenerator, 204
- getAddress
 - Models::People, 148
- getAddressComplement
 - Models::People, 148
- getAllBillingsOfProject
 - Databases::BillingDatabase, 33
- getAllContributories
 - Models::ContributoriesList, 81
- getAllProjects
 - Databases::ProjectDatabase, 167
- getBeginDate
 - Models::Project, 157
- getBilling
 - Databases::BillingDatabase, 33
- getBillings
 - Gui::Widgets::WdgModels::BillingsTableModel, 42
- getBillingsTable
 - Databases::BillingDatabase, 35
- getBills
 - Databases::BillingDatabase, 35
- getBillsBetweenDates
 - Databases::BillingDatabase, 35
- getBillsPaid
 - Databases::BillingDatabase, 35
- getBtnValid
 - Gui::Widgets::CheckFields::CheckQLineEdit, 62
- getCity
 - Models::People, 148
- getCompany
 - Models::People, 148
- getContributories
 - Gui::Widgets::ContributoriesWidget, 88
 - Gui::Widgets::WdgModels::ContributoriesTable-Model, 85
 - Models::Billing, 27
 - Models::ContributoriesList, 81
- getContributoriesByBilling
 - Databases::ContributoryDatabase, 94
- getContributoriesByBillingAndProject
 - Databases::ContributoryDatabase, 95
- getContributory
 - Databases::ContributoryDatabase, 95
- getCopy
 - Gui::Dialogs::AddQuoteDialog, 24
- getCost
 - Models::Project, 157
- getCostProjects
 - Databases::ProjectDatabase, 167
- getCountry
 - Gui::Widgets::CheckFields::CheckPhone, 57
 - Gui::Widgets::CheckFields::CheckPostalCode, 60
 - Models::People, 148
- getCurrentCustomerId
 - Gui::MainWindow, 138
 - Gui::Widgets::searchWidget, 193
- getCurrentCustomerName
 - Gui::MainWindow, 139
- getCurrentProjectId
 - Gui::MainWindow, 139
- getCurrentProjectName
 - Gui::MainWindow, 139
- getCurrentQuoteId
 - Gui::MainWindow, 139
- getCustomer
 - Databases::CustomerDatabase, 103, 104
 - Models::ContributoriesList, 81
 - Models::Project, 157
- getCustomerImage
 - Databases::CustomerDatabase, 104
- getCustomers
 - Databases::CustomerDatabase, 104
 - Gui::Widgets::WdgModels::CustomersTableModel, 112
 - Utils::HierarchicalSystem, 127
- getCustomersTable
 - Databases::CustomerDatabase, 104
- getDailyRate
 - Gui::Widgets::RateWidget, 182
 - Models::Project, 157
 - Models::Rate, 178
- getDataMap
 - Models::Billing, 27
 - Models::ContributoriesList, 81
 - Models::Contributory, 90
 - Models::Customer, 100
 - Models::IModel, 131
 - Models::Project, 157
 - Models::User, 213
- getDatabaseName
 - Gui::Widgets::DatabaseSettingsWidget, 117
- getDate
 - Models::Billing, 27
- getDefaultLocation
 - Gui::Widgets::Path::ChosePathWidget, 70
- getDescription
 - Models::Billing, 27

- Models::Contributory, 90
- Models::Project, 157
- getDomainNameOrIP
 - Gui::Widgets::DatabaseSettingsWidget, 117
- getEmail
 - Models::People, 148
- getEndDate
 - Models::Project, 158
- getExtension
 - Gui::Widgets::BrowseImageWidget, 44
- getExtensionFile
 - Utils::String, 201
- getExtensionImage
 - Models::People, 148
- getFax
 - Models::People, 149
- getField
 - Gui::Widgets::Path::ChosePathWidget, 70
- getFilename
 - Models::Billing, 28
- getFilter
 - Models::Search, 186
- getFirstname
 - Models::People, 149
- getFolder
 - Models::Billing, 28
- getGlobalTurnover
 - Models::Statistics, 196
- getGroupFilter
 - Models::Search, 187
- getHourlyRate
 - Gui::Widgets::RateWidget, 182
 - Models::Contributory, 91
 - Models::Rate, 178
- getId
 - Models::IModel, 131
- getIdBilling
 - Models::ContributoriesList, 81
- getIdCustomer
 - Gui::Dialogs::AddQuoteDialog, 24
 - Gui::Widgets::searchWidget, 193
- getImage
 - Gui::Dialogs::StartedWindowsDialog, 195
 - Gui::Widgets::BrowseImageWidget, 44
 - Models::Customer, 100
 - Models::People, 149
 - Models::User, 213
- getItem
 - Models::Billing, 28
- getItemCustomer
 - Databases::CustomerDatabase, 104
- getItemProject
 - Databases::CustomerDatabase, 106
- getItemRoot
 - Databases::CustomerDatabase, 106
- getLastName
 - Models::People, 149
- getLegalRate
 - Models::Rate, 179
- getLogin
 - Gui::Widgets::DatabaseSettingsWidget, 117
- getLongDescription
 - Models::Contributory, 91
- getMaxBillingNumber
 - Databases::BillingDatabase, 36
- getMaxBillingNumberOfCustomer
 - Databases::BillingDatabase, 36
- getMaxQuoteNumber
 - Databases::BillingDatabase, 36
- getMaxQuoteNumberOfCustomer
 - Databases::BillingDatabase, 36
- getMobilePhone
 - Models::People, 149
- getModel
 - Utils::ItemType, 133
- getName
 - Models::Project, 158
 - Utils::ItemType, 133
- getNameFolder
 - Models::Customer, 100
- getNbBills
 - Databases::BillingDatabase, 36
- getNbBillsPaid
 - Databases::BillingDatabase, 37
- getNbCustomers
 - Databases::CustomerDatabase, 106
- getNbDailyHours
 - Models::Rate, 179
- getNbDaysPerMonths
 - Models::User, 213
- getNbDocs
 - Databases::BillingDatabase, 37
- getNbHoursPerDays
 - Models::User, 213
- getNbProjects
 - Databases::ProjectDatabase, 167
 - Models::ContributoriesList, 81
- getNbQuotes
 - Databases::BillingDatabase, 37
- getNoSiret
 - Models::User, 213
- getNumber
 - Gui::Dialogs::AddQuoteDialog, 24
 - Models::Billing, 28
- getPartial
 - Mustache::PartialFileLoader, 143
 - Mustache::PartialMap, 144
 - Mustache::PartialResolver, 145
- getPassword
 - Gui::Widgets::DatabaseSettingsWidget, 117
- getPath
 - Models::Billing, 28
 - Models::Customer, 100
- getPdflatexPath
 - Models::User, 213
- getPhone

- Models::People, 149
- getPort
 - Gui::Widgets::DatabaseSettingsWidget, 118
- getPostalCode
 - Models::People, 149
- getPrice
 - Models::Billing, 28
 - Models::Calculable, 45
 - Models::ContributoriesList, 82
 - Models::Contributory, 91
- getProject
 - Databases::ProjectDatabase, 168
 - Gui::Widgets::WdgModels::ProjectContributories-TableModel, 164
 - Models::Contributory, 91
- getProjects
 - Databases::ProjectDatabase, 168
 - Gui::Widgets::Delegates::ProjectComboDelegate, 161
 - Gui::Widgets::WdgModels::ProjectContributories-TableModel, 164
 - Gui::Widgets::WdgModels::ProjectsTableModel, 173
 - Models::ContributoriesList, 82
 - Utils::HierarchicalSystem, 127
- getProjectsOfCustomer
 - Databases::ProjectDatabase, 168
- getProjectsTable
 - Databases::ProjectDatabase, 168
- getQuantity
 - Models::Contributory, 91
- getRate
 - Databases::RateDatabase, 180
 - Models::ContributoriesList, 82
- getSearchInBillsQuotes
 - Models::Search, 187
- getSearchInCompanies
 - Models::Search, 187
- getSearchInProjects
 - Models::Search, 187
- getSearchInReferentLastname
 - Models::Search, 187
- getSelectedProjects
 - Gui::Widgets::WdgModels::ProjectContributories-TableModel, 164
- getSumQuantity
 - Gui::Widgets::WdgModels::ContributoriesTable-Model, 86
 - Models::Billing, 29
 - Models::Calculable, 45
 - Models::ContributoriesList, 82
 - Models::Contributory, 91
- getText
 - Models::Search, 187
- getTitle
 - Models::Billing, 29
 - Models::User, 213
- getTree
 - Databases::CustomerDatabase, 106
- getTurnover
 - Models::Customer, 100
- getTurnoverBetweenDates
 - Models::Statistics, 197
- getType
 - Utils::ItemType, 133
- getUnit
 - Models::Contributory, 92
- getUser
 - Databases::UserDatabase, 217
- getUserImage
 - Databases::UserDatabase, 217
- getWebsite
 - Models::People, 150
- getWorkspaceName
 - Models::User, 214
- getWorkspacePath
 - Models::User, 214
- gettype
 - Models::Unit, 208
- gettypeFiles
 - Gui::Widgets::Path::ChoseFileWidget, 69
- Gui, 17
- Gui::Dialogs::AddProjectDialog, 21
 - AddProjectDialog, 22
- Gui::Dialogs::AddQuoteDialog, 22
 - AddQuoteDialog, 23
 - fillQuoteBilling, 24
 - getCopy, 24
 - getCustomerId, 24
 - getNumber, 24
 - setCopy, 24
 - setQuoteIdNumber, 25
- Gui::Dialogs::ComputeTurnoverDialog, 75
 - beginDateControl, 75
 - endDateControl, 76
 - fillLabels, 76
- Gui::Dialogs::DialogAddCustomer, 119
 - DialogAddCustomer, 120
- Gui::Dialogs::MessageBox, 141
 - MessageBox, 142
 - setImage, 142
 - setText, 142
- Gui::Dialogs::StartedWindowsDialog, 194
 - databaseTypeChanged, 195
 - getImage, 195
 - isDatabaseCentralized, 195
 - isDatabaseTypeValid, 196
 - StartedWindowsDialog, 195
- Gui::Dialogs::StatisticsDialog, 197
 - singularPlural, 199
 - StatisticsDialog, 198
 - updateUi, 199
- Gui::Dialogs::UserDataDialog, 218
 - UserDataDialog, 219
- Gui::Docks::SearchDock, 189
 - search, 191

- SearchDock, 190
- textChanged, 191
- Gui::MainWindow, 135
 - addBill, 138
 - addDoc, 138
 - addProject, 138
 - addQuote, 138
 - editUser, 138
 - getCurrentCustomerId, 138
 - getCurrentCustomerName, 139
 - getCurrentProjectId, 139
 - getCurrentProjectName, 139
 - getCurrentQuotId, 139
 - MainWindow, 137
 - resizeEvent, 139
 - rootTree, 139
 - search, 139
 - treeLevel, 141
- Gui::Utils::Image, 128
 - bytesToPixmap, 129
 - imageToBytes, 129
 - pixmapToBytes, 129
 - pixmapToImage, 130
- Gui::Utils::WindowSettings, 219
 - setMaximumSize, 220
 - setPositionToCenter, 220
- Gui::Widgets, 18
- Gui::Widgets::BrowseImageWidget, 43
 - BrowseImageWidget, 44
 - getExtension, 44
 - getImage, 44
 - setImage, 44
 - setImageScaled, 44
- Gui::Widgets::CheckFields::CheckCity, 46
 - CheckCity, 46
- Gui::Widgets::CheckFields::CheckCountry, 47
 - CheckCountry, 47
- Gui::Widgets::CheckFields::CheckEmail, 47
 - check, 48
 - CheckEmail, 48
- Gui::Widgets::CheckFields::CheckFieldsLetters, 49
 - check, 50
 - CheckFieldsLetters, 49
- Gui::Widgets::CheckFields::CheckFieldsNumbers, 51
 - check, 53
 - CheckFieldsNumbers, 52
- Gui::Widgets::CheckFields::CheckIpAddress, 53
 - check, 54
 - CheckIpAddress, 54
- Gui::Widgets::CheckFields::CheckLogin, 54
 - check, 55
 - CheckLogin, 55
- Gui::Widgets::CheckFields::CheckName, 56
 - CheckName, 56
- Gui::Widgets::CheckFields::CheckPhone, 56
 - check, 57
 - CheckPhone, 57
 - getCountry, 57
 - setCountry, 58
- Gui::Widgets::CheckFields::CheckPortNumber, 58
 - check, 59
 - CheckPortNumber, 59
- Gui::Widgets::CheckFields::CheckPostalCode, 59
 - check, 60
 - CheckPostalCode, 60
 - getCountry, 60
 - setCountry, 60
- Gui::Widgets::CheckFields::CheckQLineEdit, 61
 - CheckQLineEdit, 61
 - getBtnValid, 62
 - isValid, 62
 - setBtnValid, 62
- Gui::Widgets::CheckFields::CheckSiretNumber, 62
 - check, 63
 - CheckSiretNumber, 63
- Gui::Widgets::CheckFields::CheckUntilField, 63
 - check, 64
 - CheckUntilField, 64
- Gui::Widgets::CheckFields::CheckValidField, 64
 - check, 65
 - CheckValidField, 65
- Gui::Widgets::CheckFields::CheckWebsite, 66
 - check, 66
 - CheckWebsite, 66
- Gui::Widgets::CheckFields::ICheckField, 128
 - check, 128
- Gui::Widgets::ComboBoxModelWidget, 74
 - ComboBoxModelWidget, 74
- Gui::Widgets::ContributoriesWidget, 87
 - add, 88
 - addProject, 88
 - ContributoriesWidget, 88
 - count, 88
 - getContributories, 88
- Gui::Widgets::CustomerContextualMenu, 101
 - CustomerContextualMenu, 102
- Gui::Widgets::CustomerDataWidget, 108
 - CustomerDataWidget, 108
 - printInformations, 108
- Gui::Widgets::DatabaseSettingsWidget, 116
 - DatabaseSettingsWidget, 117
 - getDatabaseName, 117
 - getDomainNameOrIp, 117
 - getLogin, 117
 - getPassword, 117
 - getPort, 118
 - isValid, 118
- Gui::Widgets::Delegates::ComboBoxDelegate, 71
 - ComboBoxDelegate, 72
 - createEditor, 72
 - paint, 72
 - setEditorData, 72
 - setModelData, 72
 - updateEditorGeometry, 74
- Gui::Widgets::Delegates::DoubleSpinBoxDelegate, 122
 - createEditor, 123

- DoubleSpinBoxDelegate, 122
- setEditorData, 124
- setModelData, 124
- updateEditorGeometry, 124
- Gui::Widgets::Delegates::ProjectComboDelegate, 160
 - createEditor, 161
 - getProjects, 161
 - isLocked, 161
 - paint, 161
 - ProjectComboDelegate, 161
 - setLocked, 162
- Gui::Widgets::Delegates::TextareaDelegate, 205
 - createEditor, 206
 - setEditorData, 206
 - setModelData, 206
 - TextareaDelegate, 206
 - updateEditorGeometry, 206
- Gui::Widgets::Delegates::UnitComboDelegate, 209
 - createEditor, 210
 - paint, 210
 - UnitComboDelegate, 210
- Gui::Widgets::Path::ChoseDirectoryWidget, 67
 - ChoseDirectoryWidget, 67
- Gui::Widgets::Path::ChoseFileWidget, 68
 - ChoseFileWidget, 68
 - gettypeFiles, 69
 - setTypeFiles, 69
- Gui::Widgets::Path::ChosePathWidget, 69
 - ChosePathWidget, 70
 - getDefaultLocation, 70
 - getField, 70
 - setField, 70
- Gui::Widgets::Popup, 155
- Gui::Widgets::ProjectsWidget, 174
 - ProjectsWidget, 175
 - updateBtn, 175
- Gui::Widgets::RateWidget, 181
 - getDailyRate, 182
 - getHourlyRate, 182
 - RateWidget, 182
 - setDailyRate, 182
 - setHourlyRate, 182
 - setWidgetDailyRateValue, 182
 - setWidgetHourlyRateValue, 183
- Gui::Widgets::WdgModels::BillingsTableModel, 40
 - append, 41
 - BillingsTableModel, 41
 - columnCount, 41
 - count, 41
 - data, 41
 - flags, 42
 - getBillings, 42
 - headerData, 42
 - remove, 42
 - rowCount, 42
 - setData, 43
- Gui::Widgets::WdgModels::ContributoriesTableModel, 83
 - append, 85
 - columnCount, 85
 - ContributoriesTableModel, 84
 - count, 85
 - data, 85
 - flags, 85
 - getContributories, 85
 - getSumQuantity, 86
 - headerData, 86
 - remove, 86
 - rowCount, 86
 - setData, 86
- Gui::Widgets::WdgModels::CustomersTableModel, 109
 - append, 110
 - columnCount, 110
 - count, 110
 - CustomersTableModel, 110
 - data, 110
 - flags, 112
 - getCustomers, 112
 - headerData, 112
 - remove, 112
 - rowCount, 112
 - setData, 113
- Gui::Widgets::WdgModels::ProjectContributoriesTableModel, 162
 - allProjectsChosen, 163
 - append, 163
 - columnCount, 163
 - data, 164
 - flags, 164
 - getProject, 164
 - getProjects, 164
 - getSelectedProjects, 164
 - headerData, 165
 - ProjectContributoriesTableModel, 163
 - remove, 165
 - rowCount, 165
 - setData, 165
- Gui::Widgets::WdgModels::ProjectsTableModel, 171
 - append, 172
 - columnCount, 172
 - count, 172
 - data, 172
 - flags, 173
 - getProjects, 173
 - headerData, 173
 - ProjectsTableModel, 172
 - remove, 173
 - rowCount, 173
 - setData, 174
- Gui::Widgets::searchWidget, 191
 - getCurrentCustomerId, 193
 - getCustomerId, 193
 - isCustomerSelected, 193
 - search, 193
 - searchWidget, 192
 - selectCustomer, 193

- setCustomerId, 193
- headerData
 - Gui::Widgets::WdgModels::BillingsTableModel, 42
 - Gui::Widgets::WdgModels::ContributoriesTableModel, 86
 - Gui::Widgets::WdgModels::CustomersTableModel, 112
 - Gui::Widgets::WdgModels::ProjectContributoriesTableModel, 165
 - Gui::Widgets::WdgModels::ProjectsTableModel, 173
- hydrat
 - Models::Billing, 29
 - Models::Contributory, 92
 - Models::Customer, 100
 - Models::IModel, 131
 - Models::Project, 158
 - Models::User, 214
- imageToBytes
 - Gui::Utils::Image, 129
- instance
 - Databases::BillingDatabase, 37
 - Databases::ContributoryDatabase, 95
 - Databases::CustomerDatabase, 106
 - Databases::Database, 115
 - Databases::ProjectDatabase, 170
 - Databases::RateDatabase, 180
 - Databases::UserDatabase, 217
 - Utils::Log, 135
- InvertedSectionStart
 - Mustache::Tag, 202
- isArchived
 - Models::Customer, 101
- isBilling
 - Models::Billing, 29
- isBillingPaid
 - Databases::BillingDatabase, 37
- isCustomerSelected
 - Gui::Widgets::searchWidget, 193
- isDatabaseCentralized
 - Gui::Dialogs::StartedWindowsDialog, 195
- isDatabaseTypeValid
 - Gui::Dialogs::StartedWindowsDialog, 196
- isFalse
 - Mustache::Context, 77
 - Mustache::QtVariantContext, 177
- isInsert
 - Models::ContributoriesList, 83
- isLocked
 - Gui::Widgets::Delegates::ProjectComboDelegate, 161
- isPaid
 - Models::Billing, 29
- isToRemoved
 - Models::IModel, 132
- isValid
 - Gui::Widgets::CheckFields::CheckQLineEdit, 62
- Gui::Widgets::DatabaseSettingsWidget, 118
- ItemType
 - Utils::ItemType, 133
- ItemTypeTest, 134
- lastError
 - Databases::Database, 115
- listCount
 - Mustache::Context, 77
 - Mustache::QtVariantContext, 177
- MainWindow
 - Gui::MainWindow, 137
- makeDirectory
 - Utils::Directories, 120
- MessageBox
 - Gui::Dialogs::MessageBox, 142
- Models, 18
- Models::Billing, 25
 - addContributory, 27
 - Billing, 27
 - getContributories, 27
 - getDataMap, 27
 - getDate, 27
 - getDescription, 27
 - getFilename, 28
 - getFolder, 28
 - getItem, 28
 - getNumber, 28
 - getPath, 28
 - getPrice, 28
 - getSumQuantity, 29
 - getTitle, 29
 - hydrat, 29
 - isBilling, 29
 - isPaid, 29
 - operator<, 30
 - operator==, 30
 - setDate, 30
 - setDescription, 30
 - setIsBilling, 30
 - setIsPaid, 31
 - setNumber, 31
 - setTitle, 31
- Models::Calculable, 45
 - getPrice, 45
 - getSumQuantity, 45
- Models::ContributoriesList, 78
 - addContributory, 80
 - addProject, 81
 - getAllContributories, 81
 - getContributories, 81
 - getCustomer, 81
 - getDataMap, 81
 - getIdBilling, 81
 - getNbProjects, 81
 - getPrice, 82
 - getProjects, 82
 - getRate, 82

- getSumQuantity, [82](#)
- isInsert, [83](#)
- setAllIdContributories, [83](#)
- setIdBilling, [83](#)
- setInsert, [83](#)
- Models::Contributory, [89](#)
 - Contributory, [90](#)
 - getDataMap, [90](#)
 - getDescription, [90](#)
 - getHourlyRate, [91](#)
 - getLongDescription, [91](#)
 - getPrice, [91](#)
 - getProject, [91](#)
 - getQuantity, [91](#)
 - getSumQuantity, [91](#)
 - getUnit, [92](#)
 - hydrat, [92](#)
 - operator==, [92](#)
 - setDescription, [92](#)
 - setHourlyRate, [93](#)
 - setLongDescription, [93](#)
 - setProject, [93](#)
 - setQuantity, [93](#)
 - setUnit, [93](#)
- Models::Customer, [98](#)
 - commit, [99](#)
 - Customer, [99](#)
 - getDataMap, [100](#)
 - getImage, [100](#)
 - getNameFolder, [100](#)
 - getPath, [100](#)
 - getTurnover, [100](#)
 - hydrat, [100](#)
 - isArchived, [101](#)
 - setImage, [101](#)
 - setIsArchived, [101](#)
- Models::IModel, [130](#)
 - getDataMap, [131](#)
 - getId, [131](#)
 - hydrat, [131](#)
 - isToRemoved, [132](#)
 - setId, [132](#)
 - setToRemoved, [132](#)
- Models::People, [146](#)
 - getAddress, [148](#)
 - getAddressComplement, [148](#)
 - getCity, [148](#)
 - getCompany, [148](#)
 - getCountry, [148](#)
 - getEmail, [148](#)
 - getExtensionImage, [148](#)
 - getFax, [149](#)
 - getFirstname, [149](#)
 - getImage, [149](#)
 - getLastName, [149](#)
 - getMobilePhone, [149](#)
 - getPhone, [149](#)
 - getPostalCode, [149](#)
 - getWebsite, [150](#)
 - operator==, [150](#)
 - setAddress, [150](#)
 - setAddressComplement, [150](#)
 - setCity, [151](#)
 - setCompany, [151](#)
 - setCountry, [151](#)
 - setEmail, [151](#)
 - setExtensionImage, [151](#)
 - setFax, [151](#)
 - setFirstname, [152](#)
 - setImage, [152](#)
 - setLastName, [152](#)
 - setMobilePhone, [152](#)
 - setPhone, [152](#)
 - setPostalCode, [152](#)
 - setWebsite, [152](#)
- Models::Project, [155](#)
 - getBeginDate, [157](#)
 - getCost, [157](#)
 - getCustomer, [157](#)
 - getDailyRate, [157](#)
 - getDataMap, [157](#)
 - getDescription, [157](#)
 - getEndDate, [158](#)
 - getName, [158](#)
 - hydrat, [158](#)
 - operator<, [158](#)
 - operator==, [159](#)
 - Project, [157](#)
 - setBeginDate, [159](#)
 - setCustomer, [159](#)
 - setDailyRate, [159](#)
 - setDescription, [159](#)
 - setEndDate, [159](#)
 - setName, [160](#)
- Models::Rate, [177](#)
 - getDailyRate, [178](#)
 - getHourlyRate, [178](#)
 - getLegalRate, [179](#)
 - getNbDailyHours, [179](#)
 - Rate, [178](#)
- Models::Search, [184](#)
 - filterOnBillsOrQuotes, [185](#)
 - filterOnCompany, [185](#)
 - filterOnContributories, [185](#)
 - filterOnCustomersWithoutProject, [186](#)
 - filterOnNumberElements, [186](#)
 - filterOnProjects, [186](#)
 - filterOnReferentLastname, [186](#)
 - filterOnVarcharElements, [186](#)
 - getFilter, [186](#)
 - getGroupFilter, [187](#)
 - getSearchInBillsQuotes, [187](#)
 - getSearchInCompanies, [187](#)
 - getSearchInProjects, [187](#)
 - getSearchInReferentLastname, [187](#)
 - getText, [187](#)

- searchInContributories, 187
- setGroupFilter, 188
- setSearchInBillsQuotes, 188
- setSearchInCompanies, 188
- setSearchInContributories, 188
- setSearchInProjects, 188
- setSearchInReferentLastname, 188
- setText, 189
- Models::Statistics, 196
 - getGlobalTurnover, 196
 - getTurnoverBetweenDates, 197
- Models::Unit, 208
 - gettype, 208
 - operator==, 209
 - setType, 209
 - toString, 209
 - Unit, 208
- Models::User, 211
 - getDataMap, 213
 - getImage, 213
 - getNbDaysPerMonths, 213
 - getNbHoursPerDays, 213
 - getNoSiret, 213
 - getPdflatexPath, 213
 - getTitle, 213
 - getWorkspaceName, 214
 - getWorkspacePath, 214
 - hydrat, 214
 - operator==, 214
 - setImage, 215
 - setNoSiret, 215
 - setPdflatexPath, 215
 - setTitle, 215
 - setWorkspaceName, 215
 - setWorkspacePath, 215
 - updateFolders, 216
 - User, 212
- Mustache::Tag
 - Comment, 202
 - InvertedSectionStart, 202
 - Partial, 202
 - SectionEnd, 202
 - SectionStart, 202
 - SetDelimiter, 202
- Mustache::Context, 76
 - canEval, 77
 - Context, 77
 - eval, 77
 - isFalse, 77
 - listCount, 77
 - partialResolver, 77
 - partialValue, 77
 - pop, 77
 - push, 78
 - stringValue, 78
- Mustache::PartialFileLoader, 143
 - getPartial, 143
- Mustache::PartialMap, 144
 - getPartial, 144
- Mustache::PartialResolver, 144
 - getPartial, 145
- Mustache::QtVariantContext, 175
 - canEval, 176
 - eval, 176
 - fn_t, 176
 - isFalse, 177
 - listCount, 177
 - pop, 177
 - push, 177
 - stringValue, 177
- Mustache::Renderer, 183
 - error, 183
 - errorPartial, 183
 - errorPos, 183
 - render, 183
 - setTagMarkers, 184
- Mustache::Tag, 201
 - Type, 202
- operator<
 - Models::Billing, 30
 - Models::Project, 158
- operator<<
 - Utils::Log, 135
- operator==
 - Models::Billing, 30
 - Models::Contributory, 92
 - Models::People, 150
 - Models::Project, 159
 - Models::Unit, 209
 - Models::User, 214
- paint
 - Gui::Widgets::Delegates::ComboBoxDelegate, 72
 - Gui::Widgets::Delegates::ProjectComboDelegate, 161
 - Gui::Widgets::Delegates::UnitComboDelegate, 210
- Parameters, 142
 - DB_FILENAME, 143
 - VERSION, 143
- Partial
 - Mustache::Tag, 202
- partialResolver
 - Mustache::Context, 77
- partialValue
 - Mustache::Context, 77
- PdfGenerator
 - Generator::PdfGenerator, 145
- pixmapToBytes
 - Gui::Utils::Image, 129
- pixmapToImage
 - Gui::Utils::Image, 130
- PointersTest, 154
- pop
 - Mustache::Context, 77
 - Mustache::QtVariantContext, 177
- popupMessage

- Exceptions::DbException, 119
- Exceptions::FileException, 126
- printInformations
 - Gui::Widgets::CustomerDataWidget, 108
- Project
 - Models::Project, 157
- ProjectComboDelegate
 - Gui::Widgets::Delegates::ProjectComboDelegate, 161
- ProjectContributoriesTableModel
 - Gui::Widgets::WdgModels::ProjectContributoriesTableModel, 163
- ProjectDatabaseTest, 170
- ProjectModelTest, 171
- ProjectsTableModel
 - Gui::Widgets::WdgModels::ProjectsTableModel, 172
- ProjectsWidget
 - Gui::Widgets::ProjectsWidget, 175
- push
 - Mustache::Context, 78
 - Mustache::QtVariantContext, 177
- Rate
 - Models::Rate, 178
- RateModelTest, 181
- RateWidget
 - Gui::Widgets::RateWidget, 182
- remove
 - Gui::Widgets::WdgModels::BillingsTableModel, 42
 - Gui::Widgets::WdgModels::ContributoriesTableModel, 86
 - Gui::Widgets::WdgModels::CustomersTableModel, 112
 - Gui::Widgets::WdgModels::ProjectContributoriesTableModel, 165
 - Gui::Widgets::WdgModels::ProjectsTableModel, 173
- removeBilling
 - Databases::BillingDatabase, 39
- removeBillingProject
 - Databases::BillingDatabase, 39
- removeContributory
 - Databases::ContributoryDatabase, 96
- removeCustomer
 - Databases::CustomerDatabase, 107
- removeProject
 - Databases::ProjectDatabase, 170
- render
 - Mustache::Renderer, 183
- resizeEvent
 - Gui::MainWindow, 139
- rootTree
 - Gui::MainWindow, 139
- round
 - Utils::Double, 121
- rowCount
 - Gui::Widgets::WdgModels::BillingsTableModel, 42
- Gui::Widgets::WdgModels::ContributoriesTableModel, 86
- Gui::Widgets::WdgModels::CustomersTableModel, 112
- Gui::Widgets::WdgModels::ProjectContributoriesTableModel, 165
- Gui::Widgets::WdgModels::ProjectsTableModel, 173
- search
 - Gui::Docks::SearchDock, 191
 - Gui::MainWindow, 139
 - Gui::Widgets::searchWidget, 193
- SearchDock
 - Gui::Docks::SearchDock, 190
- searchInContributories
 - Models::Search, 187
- searchTest, 191
- searchWidget
 - Gui::Widgets::searchWidget, 192
- SectionEnd
 - Mustache::Tag, 202
- SectionStart
 - Mustache::Tag, 202
- selectCustomer
 - Gui::Widgets::searchWidget, 193
- SetDelimiter
 - Mustache::Tag, 202
- setAddress
 - Models::People, 150
- setAddressComplement
 - Models::People, 150
- setAllIdContributories
 - Models::ContributoriesList, 83
- setBeginDate
 - Models::Project, 159
- setBtnValid
 - Gui::Widgets::CheckFields::CheckQLineEdit, 62
- setCity
 - Models::People, 151
- setCompany
 - Models::People, 151
- setCopy
 - Gui::Dialogs::AddQuoteDialog, 24
- setCountry
 - Gui::Widgets::CheckFields::CheckPhone, 58
 - Gui::Widgets::CheckFields::CheckPostalCode, 60
 - Models::People, 151
- setCustomer
 - Models::Project, 159
- setCustomerImage
 - Databases::CustomerDatabase, 107
- setDailyRate
 - Gui::Widgets::RateWidget, 182
 - Models::Project, 159
- setData
 - Gui::Widgets::WdgModels::BillingsTableModel, 43
 - Gui::Widgets::WdgModels::ContributoriesTableModel, 86

- Gui::Widgets::WdgModels::CustomersTableModel, 113
- Gui::Widgets::WdgModels::ProjectContributoriesTableModel, 165
- Gui::Widgets::WdgModels::ProjectsTableModel, 174
- setDatabase
 - Databases::Database, 115
- setDate
 - Models::Billing, 30
- setDescription
 - Models::Billing, 30
 - Models::Contributory, 92
 - Models::Project, 159
- setEditorData
 - Gui::Widgets::Delegates::ComboBoxDelegate, 72
 - Gui::Widgets::Delegates::DoubleSpinBoxDelegate, 124
 - Gui::Widgets::Delegates::TextareaDelegate, 206
- setEmail
 - Models::People, 151
- setEndDate
 - Models::Project, 159
- setExtensionImage
 - Models::People, 151
- setFax
 - Models::People, 151
- setField
 - Gui::Widgets::Path::ChosePathWidget, 70
- setFirstname
 - Models::People, 152
- setGroupFilter
 - Models::Search, 188
- setHourlyRate
 - Gui::Widgets::RateWidget, 182
 - Models::Contributory, 93
- setId
 - Models::IModel, 132
- setIdBilling
 - Models::ContributoriesList, 83
- setIdCustomer
 - Gui::Widgets::searchWidget, 193
- setImage
 - Gui::Dialogs::MessageBox, 142
 - Gui::Widgets::BrowseImageWidget, 44
 - Models::Customer, 101
 - Models::People, 152
 - Models::User, 215
- setImageScaled
 - Gui::Widgets::BrowseImageWidget, 44
- setInsert
 - Models::ContributoriesList, 83
- setIsArchived
 - Models::Customer, 101
- setIsBilling
 - Models::Billing, 30
- setIsPaid
 - Models::Billing, 31
- setLastname
 - Models::People, 152
- setLocked
 - Gui::Widgets::Delegates::ProjectComboDelegate, 162
- setLongDescription
 - Models::Contributory, 93
- setMaximumSize
 - Gui::Utils::WindowSettings, 220
- setMobilePhone
 - Models::People, 152
- setModelData
 - Gui::Widgets::Delegates::ComboBoxDelegate, 72
 - Gui::Widgets::Delegates::DoubleSpinBoxDelegate, 124
 - Gui::Widgets::Delegates::TextareaDelegate, 206
- setName
 - Models::Project, 160
 - Utils::ItemType, 133
- setNoSiret
 - Models::User, 215
- setNumber
 - Models::Billing, 31
- setPdflatexPath
 - Models::User, 215
- setPhone
 - Models::People, 152
- setPositionToCenter
 - Gui::Utils::WindowSettings, 220
- setPostalCode
 - Models::People, 152
- setProject
 - Models::Contributory, 93
- setQuantity
 - Models::Contributory, 93
- setQuoteIdNumber
 - Gui::Dialogs::AddQuoteDialog, 25
- setSearchInBillsQuotes
 - Models::Search, 188
- setSearchInCompanies
 - Models::Search, 188
- setSearchInContributories
 - Models::Search, 188
- setSearchInProjects
 - Models::Search, 188
- setSearchInReferentLastname
 - Models::Search, 188
- setTagMarkers
 - Mustache::Renderer, 184
- setText
 - Gui::Dialogs::MessageBox, 142
 - Models::Search, 189
- setTitle
 - Models::Billing, 31
 - Models::User, 215
- setToRemoved
 - Models::IModel, 132
- setType

- Models::Unit, [209](#)
- Utils::ItemType, [134](#)
- setTypeFiles
 - Gui::Widgets::Path::ChoseFileWidget, [69](#)
- setUnit
 - Models::Contributory, [93](#)
- setUserImage
 - Databases::UserDatabase, [217](#)
- setWebsite
 - Models::People, [152](#)
- setWidgetDailyRateValue
 - Gui::Widgets::RateWidget, [182](#)
- setWidgetHourlyRateValue
 - Gui::Widgets::RateWidget, [183](#)
- setWorkspaceName
 - Models::User, [215](#)
- setWorkspacePath
 - Models::User, [215](#)
- singularPlural
 - Gui::Dialogs::StatisticsDialog, [199](#)
- StartedWindowsDialog
 - Gui::Dialogs::StartedWindowsDialog, [195](#)
- StatisticModelTest, [196](#)
- StatisticsDialog
 - Gui::Dialogs::StatisticsDialog, [198](#)
- StringTest, [201](#)
- stringValue
 - CounterContext, [98](#)
 - Mustache::Context, [78](#)
 - Mustache::QtVariantContext, [177](#)
- TestAdder< T >, [202](#)
- TestMustache, [203](#)
- TestRunner, [203](#)
- testadder, [202](#)
- TexGenerator
 - Generator::TexGenerator, [204](#)
- textChanged
 - Gui::Docks::SearchDock, [191](#)
- TextareaDelegate
 - Gui::Widgets::Delegates::TextareaDelegate, [206](#)
- toString
 - Models::Unit, [209](#)
- treeLevel
 - Gui::MainWindow, [141](#)
- Type
 - Mustache::Tag, [202](#)
- Unit
 - Models::Unit, [208](#)
- UnitComboDelegate
 - Gui::Widgets::Delegates::UnitComboDelegate, [210](#)
- updateBtn
 - Gui::Widgets::ProjectsWidget, [175](#)
- updateCustomer
 - Databases::CustomerDatabase, [107](#)
- updateEditorGeometry
 - Gui::Widgets::Delegates::ComboBoxDelegate, [74](#)
- Gui::Widgets::Delegates::DoubleSpinBoxDelegate, [124](#)
- Gui::Widgets::Delegates::TextareaDelegate, [206](#)
- updateFolders
 - Models::User, [216](#)
- updateProject
 - Databases::ProjectDatabase, [170](#)
- updateRateProject
 - Databases::RateDatabase, [180](#)
- updateUi
 - Gui::Dialogs::StatisticsDialog, [199](#)
- User
 - Models::User, [212](#)
- UserDataDialog
 - Gui::Dialogs::UserDataDialog, [219](#)
- UserDatabaseTest, [218](#)
- UserModelTest, [219](#)
- Utils::Directories, [120](#)
 - makeDirectory, [120](#)
- Utils::Double, [121](#)
 - round, [121](#)
- Utils::HierarchicalSystem, [126](#)
 - addBillingToProject, [127](#)
 - addProjectToCustomer, [127](#)
 - getCustomers, [127](#)
 - getProjects, [127](#)
- Utils::ItemType, [132](#)
 - getModel, [133](#)
 - getName, [133](#)
 - getType, [133](#)
 - ItemType, [133](#)
 - setName, [133](#)
 - setType, [134](#)
- Utils::Log, [134](#)
 - instance, [135](#)
 - operator<<, [135](#)
 - write, [135](#)
- Utils::String, [199](#)
 - firstLetterToUpper, [200](#)
 - getExtensionFile, [201](#)
- Utils::pointers, [154](#)
 - deleteIfNotNull, [154](#)
- VERSION
 - Parameters, [143](#)
- value
 - Databases::Database, [115](#)
- write
 - Utils::Log, [135](#)