

FactDev

0.1

Generated by Doxygen 1.8.6

Sun Mar 15 2015 11:41:46



# Contents

<b>1</b>	<b>FactDev documentation</b>	<b>1</b>
<b>2</b>	<b>README</b>	<b>3</b>
<b>3</b>	<b>QTestRunner</b>	<b>5</b>
<b>4</b>	<b>Namespace Index</b>	<b>7</b>
4.1	Namespace List . . . . .	7
<b>5</b>	<b>Hierarchical Index</b>	<b>9</b>
5.1	Class Hierarchy . . . . .	9
<b>6</b>	<b>Class Index</b>	<b>13</b>
6.1	Class List . . . . .	13
<b>7</b>	<b>Namespace Documentation</b>	<b>17</b>
7.1	Databases Namespace Reference . . . . .	17
7.1.1	Detailed Description . . . . .	17
7.2	Gui Namespace Reference . . . . .	17
7.2.1	Detailed Description . . . . .	18
7.3	Gui::Widgets Namespace Reference . . . . .	18
7.3.1	Detailed Description . . . . .	18
7.4	Models Namespace Reference . . . . .	18
7.4.1	Detailed Description . . . . .	19
<b>8</b>	<b>Class Documentation</b>	<b>21</b>
8.1	Gui::Dialogs::AddProjectDialog Class Reference . . . . .	21
8.1.1	Detailed Description . . . . .	21
8.1.2	Constructor & Destructor Documentation . . . . .	22
8.1.2.1	AddProjectDialog . . . . .	22
8.2	Gui::Dialogs::AddQuoteDialog Class Reference . . . . .	22
8.2.1	Detailed Description . . . . .	23
8.2.2	Constructor & Destructor Documentation . . . . .	23
8.2.2.1	AddQuoteDialog . . . . .	23

8.2.3	Member Function Documentation	23
8.2.3.1	fillQuoteBilling	23
8.2.3.2	getCopy	23
8.2.3.3	getCustomerId	24
8.2.3.4	getNumber	24
8.2.3.5	setCopy	24
8.2.3.6	setQuoteIdNumber	24
8.3	Models::Billing Class Reference	24
8.3.1	Detailed Description	26
8.3.2	Constructor & Destructor Documentation	26
8.3.2.1	Billing	26
8.3.3	Member Function Documentation	26
8.3.3.1	addContributory	26
8.3.3.2	getContributories	26
8.3.3.3	getDataMap	27
8.3.3.4	getDate	27
8.3.3.5	getDescription	27
8.3.3.6	getFilename	27
8.3.3.7	getFolder	27
8.3.3.8	getNumber	27
8.3.3.9	getPath	28
8.3.3.10	getSumQuantity	28
8.3.3.11	getSumRate	28
8.3.3.12	getTitle	28
8.3.3.13	hydrat	28
8.3.3.14	isBilling	28
8.3.3.15	isPaid	28
8.3.3.16	operator!=	29
8.3.3.17	operator<	29
8.3.3.18	operator==	29
8.3.3.19	setDate	29
8.3.3.20	setDescription	29
8.3.3.21	setIsBilling	29
8.3.3.22	setIsPaid	30
8.3.3.23	setNumber	30
8.3.3.24	setTitle	30
8.4	Databases::BillingDatabase Class Reference	30
8.4.1	Detailed Description	31
8.4.2	Member Function Documentation	32
8.4.2.1	addBilling	32

8.4.2.2	<a href="#">addBillingProject</a>	32
8.4.2.3	<a href="#">getAllBillingsOfProject</a>	32
8.4.2.4	<a href="#">getBilling</a>	32
8.4.2.5	<a href="#">getBilling</a>	32
8.4.2.6	<a href="#">getBillings</a>	32
8.4.2.7	<a href="#">getBillingsTable</a>	33
8.4.2.8	<a href="#">getMaxBillingNumber</a>	33
8.4.2.9	<a href="#">getMaxBillingNumberOfCustomer</a>	33
8.4.2.10	<a href="#">getMaxQuoteNumber</a>	33
8.4.2.11	<a href="#">getMaxQuoteNumberOfCustomer</a>	33
8.4.2.12	<a href="#">instance</a>	34
8.4.2.13	<a href="#">isBillingPaid</a>	34
8.4.2.14	<a href="#">removeBilling</a>	34
8.4.2.15	<a href="#">removeBillingProject</a>	34
8.5	<a href="#">BillingDatabaseTest Class Reference</a>	35
8.6	<a href="#">BillingModelTest Class Reference</a>	35
8.7	<a href="#">Gui::Widgets::WdgModels::BillingsTableModel Class Reference</a>	35
8.7.1	<a href="#">Detailed Description</a>	36
8.7.2	<a href="#">Constructor &amp; Destructor Documentation</a>	36
8.7.2.1	<a href="#">BillingsTableModel</a>	36
8.7.3	<a href="#">Member Function Documentation</a>	36
8.7.3.1	<a href="#">append</a>	36
8.7.3.2	<a href="#">columnCount</a>	37
8.7.3.3	<a href="#">count</a>	37
8.7.3.4	<a href="#">data</a>	37
8.7.3.5	<a href="#">flags</a>	37
8.7.3.6	<a href="#">getBillings</a>	37
8.7.3.7	<a href="#">headerData</a>	38
8.7.3.8	<a href="#">remove</a>	39
8.7.3.9	<a href="#">rowCount</a>	39
8.7.3.10	<a href="#">setData</a>	39
8.8	<a href="#">Gui::Widgets::CheckFields::CheckCity Class Reference</a>	39
8.8.1	<a href="#">Detailed Description</a>	40
8.8.2	<a href="#">Constructor &amp; Destructor Documentation</a>	40
8.8.2.1	<a href="#">CheckCity</a>	40
8.9	<a href="#">Gui::Widgets::CheckFields::CheckCountry Class Reference</a>	40
8.9.1	<a href="#">Detailed Description</a>	41
8.9.2	<a href="#">Constructor &amp; Destructor Documentation</a>	41
8.9.2.1	<a href="#">CheckCountry</a>	41
8.10	<a href="#">Gui::Widgets::CheckFields::CheckEmail Class Reference</a>	41

8.10.1 Detailed Description . . . . .	42
8.10.2 Constructor & Destructor Documentation . . . . .	42
8.10.2.1 CheckEmail . . . . .	42
8.10.3 Member Function Documentation . . . . .	42
8.10.3.1 check . . . . .	42
8.11 Gui::Widgets::CheckFields::CheckFieldsLetters Class Reference . . . . .	43
8.11.1 Detailed Description . . . . .	43
8.11.2 Constructor & Destructor Documentation . . . . .	43
8.11.2.1 CheckFieldsLetters . . . . .	43
8.11.3 Member Function Documentation . . . . .	43
8.11.3.1 check . . . . .	43
8.12 Gui::Widgets::CheckFields::CheckFieldsNumbers Class Reference . . . . .	44
8.12.1 Detailed Description . . . . .	44
8.12.2 Constructor & Destructor Documentation . . . . .	44
8.12.2.1 CheckFieldsNumbers . . . . .	44
8.12.3 Member Function Documentation . . . . .	45
8.12.3.1 check . . . . .	45
8.13 Gui::Widgets::CheckFields::CheckIpAddress Class Reference . . . . .	45
8.13.1 Detailed Description . . . . .	45
8.13.2 Constructor & Destructor Documentation . . . . .	46
8.13.2.1 CheckIpAddress . . . . .	46
8.13.3 Member Function Documentation . . . . .	46
8.13.3.1 check . . . . .	46
8.14 Gui::Widgets::CheckFields::CheckLogin Class Reference . . . . .	46
8.14.1 Detailed Description . . . . .	47
8.14.2 Constructor & Destructor Documentation . . . . .	47
8.14.2.1 CheckLogin . . . . .	47
8.14.3 Member Function Documentation . . . . .	47
8.14.3.1 check . . . . .	47
8.15 Gui::Widgets::CheckFields::CheckName Class Reference . . . . .	48
8.15.1 Detailed Description . . . . .	48
8.15.2 Constructor & Destructor Documentation . . . . .	48
8.15.2.1 CheckName . . . . .	48
8.16 Gui::Widgets::CheckFields::CheckPhone Class Reference . . . . .	48
8.16.1 Detailed Description . . . . .	49
8.16.2 Constructor & Destructor Documentation . . . . .	49
8.16.2.1 CheckPhone . . . . .	49
8.16.3 Member Function Documentation . . . . .	49
8.16.3.1 check . . . . .	49
8.16.3.2 getCountry . . . . .	50

8.16.3.3	setCountry	50
8.17	Gui::Widgets::CheckFields::CheckPortNumber Class Reference	50
8.17.1	Detailed Description	50
8.17.2	Constructor & Destructor Documentation	51
8.17.2.1	CheckPortNumber	51
8.17.3	Member Function Documentation	51
8.17.3.1	check	51
8.18	Gui::Widgets::CheckFields::CheckPostalCode Class Reference	51
8.18.1	Detailed Description	52
8.18.2	Constructor & Destructor Documentation	52
8.18.2.1	CheckPostalCode	52
8.18.3	Member Function Documentation	52
8.18.3.1	check	52
8.18.3.2	getCountry	52
8.18.3.3	setCountry	52
8.19	Gui::Widgets::CheckFields::CheckQLineEdit Class Reference	53
8.19.1	Detailed Description	53
8.19.2	Constructor & Destructor Documentation	53
8.19.2.1	CheckQLineEdit	53
8.19.3	Member Function Documentation	54
8.19.3.1	getBtnValid	54
8.19.3.2	isValid	54
8.19.3.3	setBtnValid	54
8.20	Gui::Widgets::CheckFields::CheckSiretNumber Class Reference	54
8.20.1	Detailed Description	55
8.20.2	Constructor & Destructor Documentation	55
8.20.2.1	CheckSiretNumber	55
8.20.3	Member Function Documentation	55
8.20.3.1	check	55
8.21	Gui::Widgets::CheckFields::CheckUntilField Class Reference	55
8.21.1	Detailed Description	56
8.21.2	Constructor & Destructor Documentation	56
8.21.2.1	CheckUntilField	56
8.21.3	Member Function Documentation	56
8.21.3.1	check	56
8.22	Gui::Widgets::CheckFields::CheckValidField Class Reference	56
8.22.1	Detailed Description	57
8.22.2	Constructor & Destructor Documentation	57
8.22.2.1	CheckValidField	57
8.22.3	Member Function Documentation	57

8.22.3.1	check	57
8.23	Gui::Widgets::Delegates::ComboBoxDelegate Class Reference	58
8.23.1	Detailed Description	58
8.23.2	Constructor & Destructor Documentation	58
8.23.2.1	ComboBoxDelegate	58
8.23.3	Member Function Documentation	59
8.23.3.1	createEditor	59
8.23.3.2	paint	59
8.23.3.3	setEditorData	59
8.23.3.4	setModelData	59
8.23.3.5	updateEditorGeometry	60
8.24	Gui::Widgets::ComboBoxModelWidget Class Reference	60
8.24.1	Detailed Description	60
8.24.2	Constructor & Destructor Documentation	60
8.24.2.1	ComboBoxModelWidget	60
8.25	Mustache::Context Class Reference	61
8.25.1	Detailed Description	61
8.25.2	Constructor & Destructor Documentation	61
8.25.2.1	Context	61
8.25.3	Member Function Documentation	61
8.25.3.1	canEval	61
8.25.3.2	eval	62
8.25.3.3	isFalse	62
8.25.3.4	listCount	62
8.25.3.5	partialResolver	62
8.25.3.6	partialValue	62
8.25.3.7	pop	62
8.25.3.8	push	62
8.25.3.9	stringValue	62
8.26	ContributoriesDatabaseTest Class Reference	63
8.27	Models::ContributoriesList Class Reference	63
8.27.1	Detailed Description	64
8.27.2	Member Function Documentation	64
8.27.2.1	addContributory	64
8.27.2.2	addProject	64
8.27.2.3	getAllContributories	65
8.27.2.4	getContributories	65
8.27.2.5	getCustomer	65
8.27.2.6	getDataMap	65
8.27.2.7	getIIdBilling	65



8.27.2.8	<a href="#">getNbProjects</a>	65
8.27.2.9	<a href="#">getProjects</a>	66
8.27.2.10	<a href="#">getRate</a>	66
8.27.2.11	<a href="#">getSumQuantity</a>	66
8.27.2.12	<a href="#">getSumRate</a>	66
8.27.2.13	<a href="#">isInsert</a>	66
8.27.2.14	<a href="#">setAllIdContributories</a>	66
8.27.2.15	<a href="#">setIdBilling</a>	67
8.27.2.16	<a href="#">setInsert</a>	67
8.28	<a href="#">Gui::Widgets::WdgModels::ContributoriesTableModel Class Reference</a>	67
8.28.1	<a href="#">Detailed Description</a>	68
8.28.2	<a href="#">Constructor &amp; Destructor Documentation</a>	68
8.28.2.1	<a href="#">ContributoriesTableModel</a>	68
8.28.3	<a href="#">Member Function Documentation</a>	68
8.28.3.1	<a href="#">append</a>	68
8.28.3.2	<a href="#">columnCount</a>	68
8.28.3.3	<a href="#">count</a>	69
8.28.3.4	<a href="#">data</a>	69
8.28.3.5	<a href="#">flags</a>	69
8.28.3.6	<a href="#">getContributories</a>	69
8.28.3.7	<a href="#">getSumQuantity</a>	69
8.28.3.8	<a href="#">headerData</a>	69
8.28.3.9	<a href="#">remove</a>	70
8.28.3.10	<a href="#">rowCount</a>	70
8.28.3.11	<a href="#">setData</a>	70
8.29	<a href="#">Gui::Widgets::ContributoriesWidget Class Reference</a>	70
8.29.1	<a href="#">Detailed Description</a>	71
8.29.2	<a href="#">Constructor &amp; Destructor Documentation</a>	71
8.29.2.1	<a href="#">ContributoriesWidget</a>	71
8.29.3	<a href="#">Member Function Documentation</a>	72
8.29.3.1	<a href="#">add</a>	72
8.29.3.2	<a href="#">addProject</a>	72
8.29.3.3	<a href="#">count</a>	72
8.29.3.4	<a href="#">getContributories</a>	72
8.30	<a href="#">Models::Contributory Class Reference</a>	72
8.30.1	<a href="#">Detailed Description</a>	73
8.30.2	<a href="#">Constructor &amp; Destructor Documentation</a>	74
8.30.2.1	<a href="#">Contributory</a>	74
8.30.3	<a href="#">Member Function Documentation</a>	75
8.30.3.1	<a href="#">getDataMap</a>	75

8.30.3.2	<a href="#">getDescription</a>	75
8.30.3.3	<a href="#">getNbHours</a>	75
8.30.3.4	<a href="#">getProject</a>	75
8.30.3.5	<a href="#">hydrat</a>	75
8.30.3.6	<a href="#">operator!=</a>	75
8.30.3.7	<a href="#">operator==</a>	76
8.30.3.8	<a href="#">setDescription</a>	76
8.30.3.9	<a href="#">setNbHours</a>	76
8.30.3.10	<a href="#">setProject</a>	76
8.31	<a href="#">Databases::ContributoryDatabase Class Reference</a>	76
8.31.1	<a href="#">Detailed Description</a>	77
8.31.2	<a href="#">Member Function Documentation</a>	77
8.31.2.1	<a href="#">addContributory</a>	77
8.31.2.2	<a href="#">getContributoriesByBilling</a>	78
8.31.2.3	<a href="#">getContributoriesByBillingAndProject</a>	79
8.31.2.4	<a href="#">getContributory</a>	79
8.31.2.5	<a href="#">getContributory</a>	79
8.31.2.6	<a href="#">instance</a>	79
8.31.2.7	<a href="#">removeContributory</a>	80
8.32	<a href="#">ContributoryListTest Class Reference</a>	81
8.33	<a href="#">ContributoryModelTest Class Reference</a>	81
8.34	<a href="#">CounterContext Class Reference</a>	81
8.34.1	<a href="#">Member Function Documentation</a>	82
8.34.1.1	<a href="#">canEval</a>	82
8.34.1.2	<a href="#">canEval</a>	82
8.34.1.3	<a href="#">eval</a>	82
8.34.1.4	<a href="#">eval</a>	82
8.34.1.5	<a href="#">stringValue</a>	83
8.34.1.6	<a href="#">stringValue</a>	83
8.35	<a href="#">Models::Customer Class Reference</a>	83
8.35.1	<a href="#">Detailed Description</a>	84
8.35.2	<a href="#">Constructor &amp; Destructor Documentation</a>	84
8.35.2.1	<a href="#">Customer</a>	84
8.35.3	<a href="#">Member Function Documentation</a>	84
8.35.3.1	<a href="#">getDataMap</a>	84
8.35.3.2	<a href="#">getNameFolder</a>	84
8.35.3.3	<a href="#">getPath</a>	84
8.35.3.4	<a href="#">getTurnover</a>	85
8.35.3.5	<a href="#">hydrat</a>	85
8.35.3.6	<a href="#">operator!=</a>	85

8.35.3.7	operator==	85
8.35.3.8	setTurnover	85
8.35.3.9	turnoverCompute	86
8.36	Gui::Widgets::CustomerContextualMenu Class Reference	86
8.36.1	Detailed Description	86
8.36.2	Constructor & Destructor Documentation	86
8.36.2.1	CustomerContextualMenu	86
8.37	Databases::CustomerDatabase Class Reference	87
8.37.1	Detailed Description	88
8.37.2	Member Function Documentation	88
8.37.2.1	addCustomer	88
8.37.2.2	getCustomer	88
8.37.2.3	getCustomer	88
8.37.2.4	getCustomersTable	89
8.37.2.5	getItemBillQuote	90
8.37.2.6	getItemCustomer	90
8.37.2.7	getItemProject	90
8.37.2.8	getItemRoot	90
8.37.2.9	getNbCustomers	91
8.37.2.10	getTree	91
8.37.2.11	instance	91
8.37.2.12	removeCustomer	91
8.37.2.13	updateCustomer	91
8.38	CustomerDatabaseTest Class Reference	92
8.39	Gui::Widgets::CustomerDataWidget Class Reference	92
8.39.1	Detailed Description	92
8.39.2	Constructor & Destructor Documentation	92
8.39.2.1	CustomerDataWidget	92
8.39.3	Member Function Documentation	93
8.39.3.1	printInformations	93
8.40	CustomerModelTest Class Reference	93
8.41	Gui::Widgets::WdgModels::CustomersTableModel Class Reference	93
8.41.1	Detailed Description	94
8.41.2	Constructor & Destructor Documentation	94
8.41.2.1	CustomersTableModel	94
8.41.3	Member Function Documentation	94
8.41.3.1	append	94
8.41.3.2	columnCount	95
8.41.3.3	count	95
8.41.3.4	data	95

8.41.3.5	flags	95
8.41.3.6	getCustomers	95
8.41.3.7	headerData	95
8.41.3.8	remove	96
8.41.3.9	rowCount	96
8.41.3.10	setData	96
8.42	Databases::Database Class Reference	96
8.42.1	Detailed Description	98
8.42.2	Member Function Documentation	98
8.42.2.1	executeFile	98
8.42.2.2	instance	98
8.42.2.3	lastError	98
8.42.2.4	setDatabase	98
8.42.2.5	value	99
8.43	Gui::Widgets::DatabaseSettingsWidget Class Reference	99
8.43.1	Detailed Description	100
8.43.2	Constructor & Destructor Documentation	100
8.43.2.1	DatabaseSettingsWidget	100
8.43.3	Member Function Documentation	100
8.43.3.1	getDatabaseName	100
8.43.3.2	getDomainNameOrIP	100
8.43.3.3	getLogin	101
8.43.3.4	getPassword	101
8.43.3.5	getPort	101
8.43.3.6	isValid	101
8.44	Exceptions::DbException Class Reference	101
8.44.1	Detailed Description	102
8.44.2	Constructor & Destructor Documentation	102
8.44.2.1	DbException	102
8.44.3	Member Function Documentation	102
8.44.3.1	popupMessage	102
8.45	Gui::Dialogs::DialogAddCustomer Class Reference	102
8.45.1	Detailed Description	103
8.45.2	Constructor & Destructor Documentation	103
8.45.2.1	DialogAddCustomer	103
8.46	Utils::Directories Class Reference	103
8.46.1	Member Function Documentation	104
8.46.1.1	makeDirectory	104
8.47	Gui::Widgets::Delegates::DoubleSpinBoxDelegate Class Reference	104
8.47.1	Detailed Description	105

8.47.2	Constructor & Destructor Documentation	105
8.47.2.1	DoubleSpinBoxDelegate	105
8.47.3	Member Function Documentation	105
8.47.3.1	createEditor	105
8.47.3.2	setEditorData	105
8.47.3.3	setModelData	105
8.47.3.4	updateEditorGeometry	106
8.48	Exceptions::FileException Class Reference	106
8.48.1	Detailed Description	106
8.48.2	Constructor & Destructor Documentation	106
8.48.2.1	FileException	106
8.48.3	Member Function Documentation	107
8.48.3.1	popupMessage	107
8.49	Generation Class Reference	107
8.50	Utils::HierarchicalSystem Class Reference	107
8.50.1	Detailed Description	108
8.50.2	Member Function Documentation	108
8.50.2.1	addBillingToProject	108
8.50.2.2	addProjectToCustomer	108
8.50.2.3	getCustomers	108
8.50.2.4	getProjects	109
8.51	Gui::Widgets::CheckFields::ICheckField Class Reference	109
8.51.1	Detailed Description	109
8.51.2	Member Function Documentation	109
8.51.2.1	check	109
8.52	Models::IModel Class Reference	110
8.52.1	Detailed Description	110
8.52.2	Member Function Documentation	111
8.52.2.1	getDataMap	111
8.52.2.2	getId	111
8.52.2.3	hydrat	111
8.52.2.4	isToRemoved	111
8.52.2.5	setId	111
8.52.2.6	setToRemoved	111
8.53	Utils::ItemType Class Reference	112
8.53.1	Detailed Description	112
8.53.2	Constructor & Destructor Documentation	112
8.53.2.1	ItemType	112
8.53.3	Member Function Documentation	112
8.53.3.1	getModel	112

8.53.3.2	getName	113
8.53.3.3	getType	113
8.53.3.4	setName	113
8.53.3.5	setType	113
8.54	ItemTypeTest Class Reference	113
8.55	Utils::Log Class Reference	114
8.55.1	Detailed Description	114
8.55.2	Member Function Documentation	114
8.55.2.1	instance	114
8.55.2.2	write	114
8.55.3	Friends And Related Function Documentation	115
8.55.3.1	operator<<	115
8.56	Gui::MainWindow Class Reference	115
8.56.1	Detailed Description	117
8.56.2	Constructor & Destructor Documentation	117
8.56.2.1	MainWindow	117
8.56.3	Member Function Documentation	117
8.56.3.1	addBill	117
8.56.3.2	addDoc	117
8.56.3.3	addProject	117
8.56.3.4	addQuote	117
8.56.3.5	editUser	118
8.56.3.6	getCurrentCustomerId	118
8.56.3.7	getCurrentCustomerName	118
8.56.3.8	getCurrentProjectId	118
8.56.3.9	getCurrentProjectName	118
8.56.3.10	getCurrentQuoteId	118
8.56.3.11	rootTree	118
8.56.3.12	search	119
8.56.3.13	treeLevel	120
8.57	Gui::Dialogs::MessageBox Class Reference	120
8.57.1	Detailed Description	121
8.57.2	Constructor & Destructor Documentation	121
8.57.2.1	MessageBox	121
8.57.3	Member Function Documentation	121
8.57.3.1	setImage	121
8.57.3.2	setText	121
8.58	Parameters Class Reference	121
8.58.1	Detailed Description	122
8.58.2	Member Data Documentation	122

8.58.2.1	DB_FILENAME	122
8.58.2.2	VERSION	122
8.59	Mustache::PartialFileLoader Class Reference	122
8.59.1	Detailed Description	122
8.59.2	Member Function Documentation	122
8.59.2.1	getPartial	122
8.60	Mustache::PartialMap Class Reference	123
8.60.1	Detailed Description	123
8.60.2	Member Function Documentation	123
8.60.2.1	getPartial	123
8.61	Mustache::PartialResolver Class Reference	123
8.61.1	Detailed Description	124
8.61.2	Member Function Documentation	124
8.61.2.1	getPartial	124
8.62	Generator::PdfGenerator Class Reference	124
8.62.1	Detailed Description	124
8.62.2	Constructor & Destructor Documentation	124
8.62.2.1	PdfGenerator	124
8.62.3	Member Function Documentation	124
8.62.3.1	generate	124
8.63	Models::People Class Reference	125
8.63.1	Detailed Description	126
8.63.2	Member Function Documentation	126
8.63.2.1	getAddress	126
8.63.2.2	getCity	126
8.63.2.3	getCompany	127
8.63.2.4	getCountry	127
8.63.2.5	getEmail	127
8.63.2.6	getFax	127
8.63.2.7	getFirstname	127
8.63.2.8	getLastname	127
8.63.2.9	getMobilePhone	127
8.63.2.10	getPhone	128
8.63.2.11	getPostalCode	128
8.63.2.12	operator!=	128
8.63.2.13	operator==	128
8.63.2.14	setAddress	128
8.63.2.15	setCity	128
8.63.2.16	setCompany	129
8.63.2.17	setCountry	129

8.63.2.18 setEmail . . . . .	129
8.63.2.19 setFax . . . . .	129
8.63.2.20 setFirstname . . . . .	129
8.63.2.21 setLastname . . . . .	129
8.63.2.22 setMobilePhone . . . . .	130
8.63.2.23 setPhone . . . . .	131
8.63.2.24 setPostalCode . . . . .	131
8.64 Utils::pointers Class Reference . . . . .	131
8.65 Gui::Widgets::Popup Class Reference . . . . .	131
8.65.1 Detailed Description . . . . .	131
8.66 Models::Project Class Reference . . . . .	132
8.66.1 Detailed Description . . . . .	133
8.66.2 Constructor & Destructor Documentation . . . . .	133
8.66.2.1 Project . . . . .	133
8.66.3 Member Function Documentation . . . . .	134
8.66.3.1 costCompute . . . . .	134
8.66.3.2 getBeginDate . . . . .	134
8.66.3.3 getCost . . . . .	134
8.66.3.4 getCustomer . . . . .	134
8.66.3.5 getDailyRate . . . . .	134
8.66.3.6 getDataMap . . . . .	134
8.66.3.7 getDescription . . . . .	135
8.66.3.8 getEndDate . . . . .	135
8.66.3.9 getName . . . . .	135
8.66.3.10 hydrat . . . . .	135
8.66.3.11 operator!= . . . . .	135
8.66.3.12 operator< . . . . .	135
8.66.3.13 operator== . . . . .	136
8.66.3.14 setBeginDate . . . . .	136
8.66.3.15 setCost . . . . .	136
8.66.3.16 setCustomer . . . . .	136
8.66.3.17 setDailyRate . . . . .	136
8.66.3.18 setDescription . . . . .	136
8.66.3.19 setEndDate . . . . .	137
8.66.3.20 setName . . . . .	137
8.67 Gui::Widgets::Delegates::ProjectComboDelegate Class Reference . . . . .	137
8.67.1 Detailed Description . . . . .	138
8.67.2 Constructor & Destructor Documentation . . . . .	138
8.67.2.1 ProjectComboDelegate . . . . .	138
8.67.3 Member Function Documentation . . . . .	138



8.67.3.1	<a href="#">createEditor</a>	138
8.67.3.2	<a href="#">getProjects</a>	138
8.67.3.3	<a href="#">isLocked</a>	139
8.67.3.4	<a href="#">paint</a>	139
8.67.3.5	<a href="#">setLocked</a>	139
8.68	<a href="#">Gui::Widgets::WdgModels::ProjectContributoriesTableModel Class Reference</a>	139
8.68.1	<a href="#">Detailed Description</a>	140
8.68.2	<a href="#">Constructor &amp; Destructor Documentation</a>	140
8.68.2.1	<a href="#">ProjectContributoriesTableModel</a>	140
8.68.3	<a href="#">Member Function Documentation</a>	140
8.68.3.1	<a href="#">allProjectsChosen</a>	140
8.68.3.2	<a href="#">append</a>	141
8.68.3.3	<a href="#">columnCount</a>	142
8.68.3.4	<a href="#">data</a>	142
8.68.3.5	<a href="#">flags</a>	142
8.68.3.6	<a href="#">getProject</a>	142
8.68.3.7	<a href="#">getProjects</a>	143
8.68.3.8	<a href="#">getSelectedProjects</a>	143
8.68.3.9	<a href="#">headerData</a>	143
8.68.3.10	<a href="#">remove</a>	143
8.68.3.11	<a href="#">rowCount</a>	143
8.68.3.12	<a href="#">setData</a>	143
8.69	<a href="#">Databases::ProjectDatabase Class Reference</a>	144
8.69.1	<a href="#">Detailed Description</a>	145
8.69.2	<a href="#">Member Function Documentation</a>	145
8.69.2.1	<a href="#">addProject</a>	145
8.69.2.2	<a href="#">getAllProjects</a>	145
8.69.2.3	<a href="#">getNbProjects</a>	145
8.69.2.4	<a href="#">getNbProjectsForACustomer</a>	145
8.69.2.5	<a href="#">getProject</a>	146
8.69.2.6	<a href="#">getProject</a>	146
8.69.2.7	<a href="#">getProjects</a>	146
8.69.2.8	<a href="#">getProjectsOfCustomer</a>	146
8.69.2.9	<a href="#">getProjectsTable</a>	147
8.69.2.10	<a href="#">instance</a>	148
8.69.2.11	<a href="#">removeProject</a>	148
8.69.2.12	<a href="#">updateProject</a>	148
8.70	<a href="#">ProjectDatabaseTest Class Reference</a>	148
8.71	<a href="#">ProjectModelTest Class Reference</a>	149
8.72	<a href="#">Gui::Widgets::WdgModels::ProjectsTableModel Class Reference</a>	149

8.72.1	Detailed Description	150
8.72.2	Constructor & Destructor Documentation	150
8.72.2.1	ProjectsTableModel	150
8.72.3	Member Function Documentation	150
8.72.3.1	append	150
8.72.3.2	columnCount	150
8.72.3.3	count	150
8.72.3.4	data	150
8.72.3.5	flags	151
8.72.3.6	getProjects	151
8.72.3.7	headerData	151
8.72.3.8	remove	151
8.72.3.9	rowCount	152
8.72.3.10	setData	152
8.73	Gui::Widgets::ProjectsWidget Class Reference	152
8.73.1	Detailed Description	153
8.73.2	Constructor & Destructor Documentation	153
8.73.2.1	ProjectsWidget	153
8.73.3	Member Function Documentation	153
8.73.3.1	updateBtn	153
8.74	Mustache::QtVariantContext Class Reference	153
8.74.1	Detailed Description	154
8.74.2	Member Typedef Documentation	154
8.74.2.1	fn_t	154
8.74.3	Member Function Documentation	154
8.74.3.1	canEval	154
8.74.3.2	eval	154
8.74.3.3	isFalse	155
8.74.3.4	listCount	155
8.74.3.5	pop	155
8.74.3.6	push	155
8.74.3.7	stringValue	155
8.75	Models::Rate Class Reference	155
8.75.1	Detailed Description	156
8.75.2	Constructor & Destructor Documentation	156
8.75.2.1	Rate	156
8.75.2.2	Rate	156
8.75.3	Member Function Documentation	156
8.75.3.1	getDailyRate	156
8.75.3.2	getHourlyRate	157

8.75.3.3	<a href="#">getLegalRate</a>	157
8.75.3.4	<a href="#">getNbDailyHours</a>	157
8.76	<a href="#">Databases::RateDatabase Class Reference</a>	157
8.76.1	<a href="#">Member Function Documentation</a>	158
8.76.1.1	<a href="#">addRateProject</a>	158
8.76.1.2	<a href="#">getRate</a>	158
8.76.1.3	<a href="#">instance</a>	158
8.76.1.4	<a href="#">updateRateProject</a>	158
8.77	<a href="#">RateModelTest Class Reference</a>	159
8.78	<a href="#">Gui::Widgets::RateWidget Class Reference</a>	159
8.78.1	<a href="#">Detailed Description</a>	160
8.78.2	<a href="#">Constructor &amp; Destructor Documentation</a>	160
8.78.2.1	<a href="#">RateWidget</a>	160
8.78.3	<a href="#">Member Function Documentation</a>	160
8.78.3.1	<a href="#">getDailyRate</a>	160
8.78.3.2	<a href="#">getHourlyRate</a>	160
8.78.3.3	<a href="#">setDailyRate</a>	160
8.78.3.4	<a href="#">setHourlyRate</a>	160
8.78.3.5	<a href="#">setWidgetDailyRateValue</a>	160
8.78.3.6	<a href="#">setWidgetHourlyRateValue</a>	161
8.79	<a href="#">Mustache::Renderer Class Reference</a>	161
8.79.1	<a href="#">Detailed Description</a>	161
8.79.2	<a href="#">Member Function Documentation</a>	161
8.79.2.1	<a href="#">error</a>	161
8.79.2.2	<a href="#">errorPartial</a>	161
8.79.2.3	<a href="#">errorPos</a>	161
8.79.2.4	<a href="#">render</a>	162
8.79.2.5	<a href="#">setTagMarkers</a>	162
8.80	<a href="#">Models::Search Class Reference</a>	162
8.80.1	<a href="#">Detailed Description</a>	163
8.80.2	<a href="#">Member Function Documentation</a>	163
8.80.2.1	<a href="#">filterOnBillsOrQuotes</a>	163
8.80.2.2	<a href="#">filterOnCompany</a>	163
8.80.2.3	<a href="#">filterOnContributories</a>	163
8.80.2.4	<a href="#">filterOnCustomersWithoutProject</a>	164
8.80.2.5	<a href="#">filterOnNumberElements</a>	164
8.80.2.6	<a href="#">filterOnProjects</a>	164
8.80.2.7	<a href="#">filterOnReferentLastname</a>	164
8.80.2.8	<a href="#">filterOnVarcharElements</a>	164
8.80.2.9	<a href="#">getFilter</a>	165

8.80.2.10	getGroupFilter	165
8.80.2.11	getSearchInBillsQuotes	165
8.80.2.12	getSearchInCompanies	165
8.80.2.13	getSearchInProjects	165
8.80.2.14	getSearchInReferentLastname	165
8.80.2.15	getText	165
8.80.2.16	searchInContributories	166
8.80.2.17	setGroupFilter	166
8.80.2.18	setSearchInBillsQuotes	166
8.80.2.19	setSearchInCompanies	166
8.80.2.20	setSearchInContributories	166
8.80.2.21	setSearchInProjects	166
8.80.2.22	setSearchInReferentLastname	166
8.80.2.23	setText	167
8.81	Gui::Docks::SearchDock Class Reference	167
8.81.1	Detailed Description	167
8.81.2	Constructor & Destructor Documentation	168
8.81.2.1	SearchDock	168
8.81.3	Member Function Documentation	169
8.81.3.1	search	169
8.81.3.2	textChanged	169
8.82	searchTest Class Reference	169
8.83	Gui::Widgets::searchWidget Class Reference	169
8.83.1	Detailed Description	170
8.83.2	Constructor & Destructor Documentation	170
8.83.2.1	searchWidget	170
8.83.3	Member Function Documentation	171
8.83.3.1	getCurrentCustomerId	171
8.83.3.2	getCustomerId	171
8.83.3.3	isCustomerSelected	171
8.83.3.4	search	171
8.83.3.5	selectCustomer	171
8.83.3.6	setIdCustomer	171
8.84	Gui::Dialogs::StartedWindowsDialog Class Reference	172
8.84.1	Detailed Description	173
8.84.2	Constructor & Destructor Documentation	173
8.84.2.1	StartedWindowsDialog	173
8.84.3	Member Function Documentation	173
8.84.3.1	databaseTypeChanged	173
8.84.3.2	getImage	173

8.84.3.3	isDatabaseCentralized	173
8.84.3.4	isDatabaseTypeValid	174
8.85	Utils::String Class Reference	174
8.85.1	Detailed Description	174
8.85.2	Member Function Documentation	174
8.85.2.1	firstLetterToUpper	174
8.86	StringTest Class Reference	175
8.87	Mustache::Tag Struct Reference	175
8.87.1	Detailed Description	175
8.87.2	Member Enumeration Documentation	175
8.87.2.1	Type	175
8.88	TestAdder< T > Class Template Reference	176
8.89	testadder Class Reference	176
8.90	TestMustache Class Reference	176
8.91	TestRunner Class Reference	176
8.92	Generator::TexGenerator Class Reference	177
8.92.1	Detailed Description	177
8.92.2	Constructor & Destructor Documentation	177
8.92.2.1	TexGenerator	177
8.92.3	Member Function Documentation	177
8.92.3.1	generate	177
8.93	Gui::Widgets::Delegates::UnitComboDelegate Class Reference	177
8.93.1	Detailed Description	178
8.93.2	Constructor & Destructor Documentation	178
8.93.2.1	UnitComboDelegate	178
8.93.3	Member Function Documentation	178
8.93.3.1	createEditor	178
8.93.3.2	paint	179
8.94	Models::User Class Reference	180
8.94.1	Detailed Description	181
8.94.2	Constructor & Destructor Documentation	181
8.94.2.1	User	181
8.94.3	Member Function Documentation	181
8.94.3.1	getDataMap	181
8.94.3.2	getNoSiret	181
8.94.3.3	getTitle	182
8.94.3.4	getWorkspaceName	182
8.94.3.5	getWorkspacePath	182
8.94.3.6	hydrat	182
8.94.3.7	operator!=	182

8.94.3.8	operator==	182
8.94.3.9	setNoSiret	183
8.94.3.10	setTitle	183
8.94.3.11	setWorkspaceName	183
8.94.3.12	setWorkspacePath	183
8.94.3.13	updateFolders	183
8.95	Databases::UserDatabase Class Reference	184
8.95.1	Detailed Description	184
8.95.2	Member Function Documentation	184
8.95.2.1	getUser	184
8.95.2.2	instance	185
8.96	UserDatabaseTest Class Reference	185
8.97	Gui::Dialogs::UserDataDialog Class Reference	185
8.97.1	Detailed Description	186
8.97.2	Constructor & Destructor Documentation	186
8.97.2.1	UserDataDialog	186
8.98	UserModelTest Class Reference	186
<b>Index</b>		<b>188</b>

# Chapter 1

## FactDev documentation

This website contains the documentation of FactDev, a billings and quotes software.

### Team

FACT team is a team for University Project. Members of this team are :

- Florent Berbie ([KraTuX31](#))
- Antoine de Roquemaurel ([aroquemaurel](#))
- Cédric Rohaut ([Oxynos](#))
- Manantsoa Andriamihary Razanajatovo ([manantsoa](#))

For more informations, you can go to <http://fact-team.github.io>.

### What is FactDev ?

FactDev is a software for quotes and billings developped by FACT team for university project in Toulouse III University – Paul Sabatier.

This software is developed with C++ and Qt framework, and there is differents features :

- Customers database
- Differents projects for customers
- Quotes
- Billings

### Documentation

You can access to the documentation generated by Doxygen here :

- [HTML Documentation](#)
- [PDF Documentation](#)

## Installation and using

- [User Manual](#)



## Chapter 2

# README

! [Build Status] (<https://travis-ci.org/robertknight/qt-mustache.svg?branch=master>)

### Qt Mustache

qt-mustache is a simple library for rendering **Mustache templates**.

#### Example Usage

```
“cpp #include "mustache.h"
```

```
QVariantHash contact; contact["name"] = "John Smith"; contact["email"] = "john.smith@gmail.com";
```

```
QString contactTemplate = "<b>{{name}}</b> <a href='mailto:{{email}}'>{{email}}";
```

```
Mustache::Renderer renderer; Mustache::QtVariantContext context(contact);
```

```
QTextStream output(stdout); output << renderer.render(contactTemplate, &context); “
```

Outputs:        <b>John Smith</b> <a href="mailto:john.smith@gmail.com">john.smith@gmail.com</a>

For further examples, see the tests in `test_mustache.cpp`

#### Building

- To build the tests, run `qmake` followed by `make`
- To use qt-mustache in your project, just add the `mustache.h` and `mustache.cpp` files to your project.

#### License

qt-mustache is licensed under the BSD license.

#### Dependencies

qt-mustache depends on the QtCore library. It is compatible with Qt 4 and Qt 5.

#### Usage

## Syntax

qt-mustache uses the standard Mustache syntax. See the [Mustache manual](#) for details.

## Data Sources

qt-mustache expands Mustache tags using values from a `Mustache::Context`. `Mustache::QtVariantContext` is a simple context implementation which wraps a `QVariantHash` or `QVariantMap`. If you want to render a template using a custom data source, you can either create a `QVariantHash` which mirrors the data source or you can re-implement `Mustache::Context`.

## Partials

When a `{{>partial}}` Mustache tag is encountered, qt-mustache will attempt to load the partial using a `Mustache::PartialResolver` provided by the context. `Mustache::PartialMap` is a simple resolver which takes a `QHash<QString,QString>` map of partial names to values and looks up partials in that map. `Mustache::PartialFileLoader` is another simple resolver which fetches partials from `<partial name>.mustache` files in a specified directory.

You can re-implement the `Mustache::PartialResolver` interface if you want to load partials from a custom source (eg. a database).

## Error Handling

If an error occurs when rendering a template, `Mustache::Renderer::errorPosition()` is set to non-negative value and template rendering stops. If the error occurs whilst rendering a partial template, `errorPartial()` contains the name of the partial.

## Lambdas

The [Mustache manual](#) provides a mechanism to customize rendering of template sections by setting the value for a tag to a callable object (eg. a lambda in Ruby or Javascript), which takes the unrendered block of text for a template section and renders it itself. qt-mustache supports this via the `Context::canEval()` and `Context::eval()` methods.

## Chapter 3

# QTestRunner

A repo for Increase QTest productivity

Thanks to <https://marcoarena.wordpress.com/2012/06/23/increase-your-qtest-productivity/>!

The QTestLib framework is a tool for unit testing Qt based applications and libraries. I find it precious and simple to use, though it lacks some important features, supported, for example, by GTest. I'm not talking about mocking – for this you generally need an out-and-out framework (like GMock) – instead, I'm referring to simple things like fast deploying. Suppose you have written a test class like this:

This repo contains only the code in this article.



## Chapter 4

# Namespace Index

### 4.1 Namespace List

Here is a list of all documented namespaces with brief descriptions:

<a href="#">Databases</a>		
	Class for <a href="#">Database</a> , contains queries . . . . .	??
<a href="#">Gui</a>	. . . . .	??
<a href="#">Gui::Widgets</a>		
	Contains <a href="#">Widgets</a> classes . . . . .	??
<a href="#">Models</a>		
	<a href="#">Models</a> classes . . . . .	??



## Chapter 5

# Hierarchical Index

### 5.1 Class Hierarchy

This inheritance list is sorted roughly, but not completely, alphabetically:

Mustache::Context . . . . .	??
Mustache::QtVariantContext . . . . .	??
CounterContext . . . . .	??
CounterContext . . . . .	??
Databases::Database . . . . .	??
Databases::BillingDatabase . . . . .	??
Databases::ContributoryDatabase . . . . .	??
Databases::CustomerDatabase . . . . .	??
Databases::ProjectDatabase . . . . .	??
Databases::RateDatabase . . . . .	??
Databases::UserDatabase . . . . .	??
Utils::Directories . . . . .	??
exception	
Exceptions::DbException . . . . .	??
Exceptions::FileException . . . . .	??
Utils::HierarchicalSystem . . . . .	??
Gui::Widgets::CheckFields::ICheckField . . . . .	??
Gui::Widgets::CheckFields::CheckQLineEdit . . . . .	??
Gui::Widgets::CheckFields::CheckEmail . . . . .	??
Gui::Widgets::CheckFields::CheckPortNumber . . . . .	??
Gui::Widgets::CheckFields::CheckSiretNumber . . . . .	??
Gui::Widgets::CheckFields::CheckUntilField . . . . .	??
Gui::Widgets::CheckFields::CheckFieldsLetters . . . . .	??
Gui::Widgets::CheckFields::CheckCity . . . . .	??
Gui::Widgets::CheckFields::CheckCountry . . . . .	??
Gui::Widgets::CheckFields::CheckName . . . . .	??
Gui::Widgets::CheckFields::CheckFieldsNumbers . . . . .	??
Gui::Widgets::CheckFields::CheckIpAddress . . . . .	??
Gui::Widgets::CheckFields::CheckLogin . . . . .	??
Gui::Widgets::CheckFields::CheckPhone . . . . .	??
Gui::Widgets::CheckFields::CheckPostalCode . . . . .	??
Gui::Widgets::CheckFields::CheckValidField . . . . .	??
Models::IModel . . . . .	??
Models::Billing . . . . .	??
Models::Contributory . . . . .	??
Models::Customer . . . . .	??
Models::Project . . . . .	??

Models::User . . . . .	??
Utils::ItemType . . . . .	??
Utils::Log . . . . .	??
Parameters . . . . .	??
Mustache::PartialResolver . . . . .	??
Mustache::PartialFileLoader . . . . .	??
Mustache::PartialMap . . . . .	??
Generator::PdfGenerator . . . . .	??
Models::People . . . . .	??
Models::Customer . . . . .	??
Models::User . . . . .	??
Utils::pointers . . . . .	??
Gui::Widgets::Popup . . . . .	??
QAbstractTableModel	
Gui::Widgets::WdgModels::BillingsTableModel . . . . .	??
Gui::Widgets::WdgModels::ContributoriesTableModel . . . . .	??
Gui::Widgets::WdgModels::CustomersTableModel . . . . .	??
Gui::Widgets::WdgModels::ProjectContributoriesTableModel . . . . .	??
Gui::Widgets::WdgModels::ProjectsTableModel . . . . .	??
QDialog	
Gui::Dialogs::AddProjectDialog . . . . .	??
Gui::Dialogs::AddQuoteDialog . . . . .	??
Gui::Dialogs::DialogAddCustomer . . . . .	??
Gui::Dialogs::MessageBox . . . . .	??
Gui::Dialogs::StartedWindowsDialog . . . . .	??
Gui::Dialogs::UserDataDialog . . . . .	??
QDockWidget	
Gui::Docks::SearchDock . . . . .	??
QItemDelegate	
Gui::Widgets::Delegates::ComboBoxDelegate . . . . .	??
Gui::Widgets::Delegates::ProjectComboDelegate . . . . .	??
Gui::Widgets::Delegates::UnitComboDelegate . . . . .	??
Gui::Widgets::Delegates::DoubleSpinBoxDelegate . . . . .	??
QLineEdit	
Gui::Widgets::CheckFields::CheckQLineEdit . . . . .	??
QMainWindow	
Gui::MainWindow . . . . .	??
QMap	
Models::ContributoriesList . . . . .	??
QMenu	
Gui::Widgets::CustomerContextualMenu . . . . .	??
QObject	
BillingDatabaseTest . . . . .	??
BillingModelTest . . . . .	??
ContributoriesDatabaseTest . . . . .	??
ContributoryListTest . . . . .	??
ContributoryModelTest . . . . .	??
CustomerDatabaseTest . . . . .	??
CustomerModelTest . . . . .	??
Generation . . . . .	??
ItemTypeTest . . . . .	??
ProjectDatabaseTest . . . . .	??
ProjectModelTest . . . . .	??
RateModelTest . . . . .	??
searchTest . . . . .	??
StringTest . . . . .	??
TestMustache . . . . .	??
TestMustache . . . . .	??



UserDatabaseTest . . . . .	??
UserModelTest . . . . .	??
QWidget	
Gui::Widgets::ComboBoxModelWidget . . . . .	??
Gui::Widgets::ContributoriesWidget . . . . .	??
Gui::Widgets::CustomerDataWidget . . . . .	??
Gui::Widgets::DatabaseSettingsWidget . . . . .	??
Gui::Widgets::ProjectsWidget . . . . .	??
Gui::Widgets::RateWidget . . . . .	??
Gui::Widgets::searchWidget . . . . .	??
Models::Rate . . . . .	??
Mustache::Renderer . . . . .	??
Models::Search . . . . .	??
Utils::String . . . . .	??
Mustache::Tag . . . . .	??
TestAdder< T > . . . . .	??
testadder . . . . .	??
TestRunner . . . . .	??
Generator::TexGenerator . . . . .	??



## Chapter 6

# Class Index

### 6.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

<a href="#">Gui::Dialogs::AddProjectDialog</a>	
Windows to add a new Project . . . . .	??
<a href="#">Gui::Dialogs::AddQuoteDialog</a>	
Window to add or modify a Quote . . . . .	??
<a href="#">Models::Billing</a>	
: <a href="#">Billing</a> or Quote of a <a href="#">Customer</a> . . . . .	??
<a href="#">Databases::BillingDatabase</a>	
The <a href="#">BillingDatabase</a> class Billing (or Quote) table database . . . . .	??
<a href="#">BillingDatabaseTest</a> . . . . .	??
<a href="#">BillingModelTest</a> . . . . .	??
<a href="#">Gui::Widgets::WdgModels::BillingsTableModel</a>	
For a Billing table . . . . .	??
<a href="#">Gui::Widgets::CheckFields::CheckCity</a>	
Line Edit of City with a check icon . . . . .	??
<a href="#">Gui::Widgets::CheckFields::CheckCountry</a>	
<a href="#">CheckCountry::CheckCountry</a> Line Edit of country with a check icon . . . . .	??
<a href="#">Gui::Widgets::CheckFields::CheckEmail</a>	
Line Edit of email with a check icon . . . . .	??
<a href="#">Gui::Widgets::CheckFields::CheckFieldsLetters</a>	
Field with only letters (no numbers) . . . . .	??
<a href="#">Gui::Widgets::CheckFields::CheckFieldsNumbers</a>	
Line Edit of number with a check icon . . . . .	??
<a href="#">Gui::Widgets::CheckFields::CheckIpAddress</a>	
Line Edit of IP address with a check icon . . . . .	??
<a href="#">Gui::Widgets::CheckFields::CheckLogin</a>	
Line Edit of login with a check icon . . . . .	??
<a href="#">Gui::Widgets::CheckFields::CheckName</a>	
Line edit of name with a check icon . . . . .	??
<a href="#">Gui::Widgets::CheckFields::CheckPhone</a>	
Line Edit of Phone number with a check icon . . . . .	??
<a href="#">Gui::Widgets::CheckFields::CheckPortNumber</a>	
The <a href="#">CheckFieldsNumbers</a> class Line Edit of number with a check icon . . . . .	??
<a href="#">Gui::Widgets::CheckFields::CheckPostalCode</a>	
Line Edit of postal code with a check icon . . . . .	??
<a href="#">Gui::Widgets::CheckFields::CheckQLineEdit</a>	
LineEdit custom with a check of text inputed . . . . .	??
<a href="#">Gui::Widgets::CheckFields::CheckSiretNumber</a>	
Line Edit with a check icon . . . . .	??

<a href="#">Gui::Widgets::CheckFields::CheckUntilField</a>	
The <a href="#">CheckUntilField</a> class	??
<a href="#">Gui::Widgets::CheckFields::CheckValidField</a>	
Check field not required	??
<a href="#">Gui::Widgets::Delegates::ComboBoxDelegate</a>	
The <a href="#">ComboBoxDelegate</a> class	??
<a href="#">Gui::Widgets::ComboBoxModelWidget</a>	
Model of ComboBox	??
<a href="#">Mustache::Context</a>	??
<a href="#">ContributoriesDatabaseTest</a>	??
<a href="#">Models::ContributoriesList</a>	
List of contributories	??
<a href="#">Gui::Widgets::WdgModels::ContributoriesTableModel</a>	
For a custom table for contributories widget	??
<a href="#">Gui::Widgets::ContributoriesWidget</a>	
Widget of Contributories	??
<a href="#">Models::Contributory</a>	
The <a href="#">Contributory</a> class	??
<a href="#">Databases::ContributoryDatabase</a>	
The <a href="#">ContributoryDatabase</a> class Contributory (or Quote) table database	??
<a href="#">ContributoryListTest</a>	??
<a href="#">ContributoryModelTest</a>	??
<a href="#">CounterContext</a>	??
<a href="#">Models::Customer</a>	
Customer	??
<a href="#">Gui::Widgets::CustomerContextualMenu</a>	
Display contextual menu on a customer	??
<a href="#">Databases::CustomerDatabase</a>	
The <a href="#">CustomerDatabase</a> class Customer table database	??
<a href="#">CustomerDatabaseTest</a>	??
<a href="#">Gui::Widgets::CustomerDataWidget</a>	
Class for display info of a customer	??
<a href="#">CustomerModelTest</a>	??
<a href="#">Gui::Widgets::WdgModels::CustomersTableModel</a>	
For a customer table	??
<a href="#">Databases::Database</a>	
The <a href="#">Database</a> class Master class for all database access	??
<a href="#">Gui::Widgets::DatabaseSettingsWidget</a>	
Windows of database settings	??
<a href="#">Exceptions::DbException</a>	
For database exception : queries, db file, ...	??
<a href="#">Gui::Dialogs::DialogAddCustomer</a>	
Window to add or modify a Customer	??
<a href="#">Utils::Directories</a>	??
<a href="#">Gui::Widgets::Delegates::DoubleSpinBoxDelegate</a>	
The <a href="#">DoubleSpinBoxDelegate</a> class	??
<a href="#">Exceptions::FileException</a>	
For file/access file exception	??
<a href="#">Generation</a>	??
<a href="#">Utils::HierarchicalSystem</a>	
Create class which contains hierarchical system of FactDev	??
<a href="#">Gui::Widgets::CheckFields::ICheckField</a>	
Interface to check fields validity	??
<a href="#">Models::IModel</a>	
The <a href="#">IModel</a> class	??
<a href="#">Utils::ItemType</a>	
Item type model	??
<a href="#">ItemTypeTest</a>	??

<a href="#">Utils::Log</a>	
For Simple management of log	??
<a href="#">Gui::MainWindow</a>	
Main Window of the software	??
<a href="#">Gui::Dialogs::MessageBox</a>	
Information window with message	??
<a href="#">Parameters</a>	
Class for simple user parameters	??
<a href="#">Mustache::PartialFileLoader</a>	??
<a href="#">Mustache::PartialMap</a>	??
<a href="#">Mustache::PartialResolver</a>	??
<a href="#">Generator::PdfGenerator</a>	
Generator of PDF files	??
<a href="#">Models::People</a>	
People	??
<a href="#">Utils::pointers</a>	??
<a href="#">Gui::Widgets::Popup</a>	
Class for display popup quickly	??
<a href="#">Models::Project</a>	
: <a href="#">Project</a> linked to a <a href="#">Customer</a>	??
<a href="#">Gui::Widgets::Delegates::ProjectComboDelegate</a>	
The <a href="#">ProjectComboDelegate</a> class	??
<a href="#">Gui::Widgets::WdgModels::ProjectContributoriesTableModel</a>	
Table model of contributories linked to projets	??
<a href="#">Databases::ProjectDatabase</a>	
Project table database	??
<a href="#">ProjectDatabaseTest</a>	??
<a href="#">ProjectModelTest</a>	??
<a href="#">Gui::Widgets::WdgModels::ProjectsTableModel</a>	
For a Project table	??
<a href="#">Gui::Widgets::ProjectsWidget</a>	
Actions on Project	??
<a href="#">Mustache::QtVariantContext</a>	??
<a href="#">Models::Rate</a>	
Rate of a prestation	??
<a href="#">Databases::RateDatabase</a>	??
<a href="#">RateModelTest</a>	??
<a href="#">Gui::Widgets::RateWidget</a>	
Class for display Rate	??
<a href="#">Mustache::Renderer</a>	??
<a href="#">Models::Search</a>	
The <a href="#">Search</a> class	??
<a href="#">Gui::Docks::SearchDock</a>	
Dock which contains search bar	??
<a href="#">searchTest</a>	??
<a href="#">Gui::Widgets::searchWidget</a>	
Class for search in database	??
<a href="#">Gui::Dialogs::StartedWindowsDialog</a>	
Construct a Windows for the first begin	??
<a href="#">Utils::String</a>	
The Utils class	??
<a href="#">StringTest</a>	??
<a href="#">Mustache::Tag</a>	??
<a href="#">TestAdder&lt; T &gt;</a>	??
<a href="#">testadder</a>	??
<a href="#">TestMustache</a>	??
<a href="#">TestRunner</a>	??

<a href="#">Generator::TexGenerator</a>	
Generate a LaTeX file . . . . .	??
<a href="#">Gui::Widgets::Delegates::UnitComboDelegate</a>	
The <a href="#">UnitComboDelegate</a> class . . . . .	??
<a href="#">Models::User</a>	
<b>User</b> of it application . . . . .	??
<a href="#">Databases::UserDatabase</a>	
Access to User data in the the table User of the <a href="#">Database</a> . . . . .	??
<a href="#">UserDatabaseTest</a> . . . . .	??
<a href="#">Gui::Dialogs::UserDataDialog</a>	
Window to fill user data . . . . .	??
<a href="#">UserModelTest</a> . . . . .	??

## Chapter 7

# Namespace Documentation

### 7.1 Databases Namespace Reference

Class for [Database](#), contains queries.

#### Classes

- class [BillingDatabase](#)  
*The **BillingDatabase** class Billing (or Quote) table database.*
- class [ContributoryDatabase](#)  
*The **ContributoryDatabase** class Contributory (or Quote) table database.*
- class [CustomerDatabase](#)  
*The **CustomerDatabase** class Customer table database.*
- class [Database](#)  
*The **Database** class Master class for all database access.*
- class [ProjectDatabase](#)  
*The **ProjectDatabase** class Project table database.*
- class [RateDatabase](#)
- class [UserDatabase](#)  
*The **UserDatabase** class Access to User data in the the table User of the **Database***

#### 7.1.1 Detailed Description

Class for [Database](#), contains queries.

### 7.2 Gui Namespace Reference

#### Namespaces

- [Widgets](#)  
*Contains **Widgets** classes.*

#### Classes

- class [MainWindow](#)  
*The **MainWindow** class Main Window of the software.*

### 7.2.1 Detailed Description

Classes for Graphical User Interface

## 7.3 Gui::Widgets Namespace Reference

Contains [Widgets](#) classes.

### Classes

- class [ComboBoxModelWidget](#)  
*The [ComboBoxModelWidget](#) class Model of ComboBox.*
- class [ContributoriesWidget](#)  
*The [ContributoriesWidget](#) class Widget of Contributories.*
- class [CustomerContextualMenu](#)  
*Display contextual menu on a customer.*
- class [CustomerDataWidget](#)  
*Class for display info of a customer.*
- class [DatabaseSettingsWidget](#)  
*The [DatabaseSettingsWidget](#) class Windows of database settings.*
- class [Popup](#)  
*Class for display popup quickly.*
- class [ProjectsWidget](#)  
*The [ProjectsWidget](#) class Actions on Project.*
- class [RateWidget](#)  
*Class for display Rate.*
- class [searchWidget](#)  
*Class for search in database.*

### 7.3.1 Detailed Description

Contains [Widgets](#) classes.

## 7.4 Models Namespace Reference

[Models](#) classes.

### Classes

- class [Billing](#)  
*The [Billing](#) class : [Billing](#) or Quote of a [Customer](#).*
- class [ContributoriesList](#)  
*The [ContributoriesList](#) class List of contributories.*
- class [Contributory](#)  
*The [Contributory](#) class.*
- class [Customer](#)  
*The [Customer](#) class [Customer](#).*
- class [IModel](#)



- The [IModel](#) class.*
- class [People](#)
  - The [People](#) class [People](#).*
- class [Project](#)
  - The [Project](#) class : [Project](#) linked to a [Customer](#).*
- class [Rate](#)
  - The [Rate](#) class [Rate](#) of a prestation.*
- class [Search](#)
  - The [Search](#) class.*
- class [User](#)
  - The [User](#) class [User](#) of it application.*

#### 7.4.1 Detailed Description

[Models](#) classes.



## Chapter 8

# Class Documentation

### 8.1 Gui::Dialogs::AddProjectDialog Class Reference

The [AddProjectDialog](#) class Windows to add a new Project.

```
#include <addprojectdialog.h>
```

Inheritance diagram for Gui::Dialogs::AddProjectDialog:



#### Public Slots

- void [checkFields](#) ()  
*[AddProjectDialog::checkFields](#) Check if fields are valid.*

#### Public Member Functions

- [AddProjectDialog](#) (int idProject=0, int noRowCustomer=0, QWidget \*parent=0)  
*[AddProjectDialogAddProjectDialog](#) Construct a windows according an idCustomer and, optionnaly, an idProject*
- void [accept](#) ()  
*[AddProjectDialog::accept](#) Valid data inputed by user and add these data in Database.*
- void [reject](#) ()  
*[AddProjectDialog::reject](#) Cancel the operation and close the windows.*
- void [fillFields](#) ()  
*[AddProjectDialog::fillFields](#) Fill the differents fields of the current windows according the Project data existing As a project requires to be linked to a Customer, the Customer selection part may be disable.*

#### 8.1.1 Detailed Description

The [AddProjectDialog](#) class Windows to add a new Project.

Author

Florent Berbie

See Also

Project

## 8.1.2 Constructor & Destructor Documentation

8.1.2.1 `Gui::Dialogs::AddProjectDialog::AddProjectDialog ( int idProject = 0, int noRowCustomer = 0, QWidget * parent = 0 )`  
`[explicit]`

AddProjectDialogAddProjectDialog Construct a windows according an *idCustomer* and, optionnaly, an *idProject*

Parameters

<i>noRowCustomer</i>	Row number of the Customer
<i>idProject</i>	Project identify
<i>parent</i>	QWidget of the current windows

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/dialogs/addprojectdialog.h
- /home/travis/build/FACT-Team/FactDev/src/gui/dialogs/addprojectdialog.cpp

## 8.2 Gui::Dialogs::AddQuoteDialog Class Reference

The [AddQuoteDialog](#) class Window to add or modify a Quote.

```
#include <addquotedialog.h>
```

Inheritance diagram for Gui::Dialogs::AddQuoteDialog:



### Public Slots

- void **updateBtn** (void)
- void **changeDocType** ()

### Public Member Functions

- [AddQuoteDialog](#) (bool isBilling, int idCustomer=0, int id=0, bool copy=false, QWidget \*parent=0)  
[AddQuoteDialog::AddQuoteDialog](#) Construct a windows [AddQuoteDialog](#).
- void [fillFields](#) ()  
[AddQuoteDialog::Fill](#) line edits with the data of the quote.
- int [getNumber](#) ()  
[AddQuoteDialog::getNumber](#) return the number of bill or quote.
- void [accept](#) ()  
[AddQuoteDialog::accept](#) Valid data inputed by user and add these data in Database.
- void [reject](#) ()  
[AddQuoteDialog::reject](#) Cancel the operation and close the windows.
- bool [getCopy](#) () const

- [AddQuoteDialog::getCopy](#) return if [AddQuoteDialog](#) is an add by copy of Billing/quote or if it's edition or add of Billing/quote.
- void [setCopy](#) (bool copy)  
[AddQuoteDialog::setCopy](#) Change the `_copy` value to define if it's a copy of a Billing/quote or if it's a new Billing or a Billing edition.
  - int [getIdCustomer](#) () const  
[AddQuoteDialog::getIdCustomer](#) get the id of the customer changing his quote/billing.
  - void [fillQuoteBilling](#) (bool isBilling)  
[AddQuoteDialog::fillQuoteBilling](#) fill fields for a Billing or a quote.
  - void [fillQuoteBillingCopy](#) (bool isBilling)  
[AddQuoteDialog::fillQuoteBilling](#) fill fields if it's a Billing or a quote for a copy.
  - void [setQuoteIdNumber](#) (int id, int idCustomer, bool isBilling)  
[AddQuoteDialog::setQuoteIdNumber](#) set id and number of the `_quote`

### 8.2.1 Detailed Description

The [AddQuoteDialog](#) class Window to add or modify a Quote.

Author

### 8.2.2 Constructor & Destructor Documentation

- 8.2.2.1 [Gui::Dialogs::AddQuoteDialog::AddQuoteDialog](#) ( bool *isBilling*, int *idCustomer* = 0, int *id* = 0, bool *copy* = false, QWidget \* *parent* = 0 ) [explicit]

[AddQuoteDialog::AddQuoteDialog](#) Construct a windows [AddQuoteDialog](#).

Parameters

<i>isBilling</i>	displaying of a quote or a Billing
<i>idCustomer</i>	the id of the Customer
<i>id</i>	the id of the quote or the billing of the Customer's Project
<i>edit</i>	if it's an edition or a copy of a quote/Billing
<i>parent</i>	QWidget of the current windows

### 8.2.3 Member Function Documentation

- 8.2.3.1 void [Gui::Dialogs::AddQuoteDialog::fillQuoteBilling](#) ( bool *isBilling* )

[AddQuoteDialog::fillQuoteBilling](#) fill fields for a Billing or a quote.

Parameters

<i>isBilling</i>	if it's a quote or a Billing
------------------	------------------------------

- 8.2.3.2 bool [Gui::Dialogs::AddQuoteDialog::getCopy](#) ( ) const

[AddQuoteDialog::getCopy](#) return if [AddQuoteDialog](#) is an add by copy of Billing/quote or if it's edition or add of Billing/quote.

Returns

if it's a copy or not

8.2.3.3 `int Gui::Dialogs::AddQuoteDialog::getIdCustomer ( ) const`

[AddQuoteDialog::getIdCustomer](#) get the id of the customer changing his quote/billing.

Returns

the id of the customer

8.2.3.4 `int Gui::Dialogs::AddQuoteDialog::getNumber ( )`

[AddQuoteDialog::getNumber](#) return the number of bill or quote.

Returns

int

8.2.3.5 `void Gui::Dialogs::AddQuoteDialog::setCopy ( bool copy )`

[AddQuoteDialog::setCopy](#) Change the `_copy` value to define if it's a copy of a Billing/quote or if it's a new Billing or a Billing edition.

Parameters

<i>copy</i>	
-------------	--

8.2.3.6 `void Gui::Dialogs::AddQuoteDialog::setQuoteldNumber ( int id, int idCustomer, bool isBilling )`

[AddQuoteDialog::setQuoteldNumber](#) set id and number of the `_quote`

Parameters

<i>id</i>	the id of the Billing
<i>idCustomer</i>	the id of the customer to set the <i>number</i>
<i>isBilling</i>	if it's a quote or a Billing

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/dialogs/addquotedialog.h
- /home/travis/build/FACT-Team/FactDev/src/gui/dialogs/addquotedialog.cpp

## 8.3 Models::Billing Class Reference

The [Billing](#) class : [Billing](#) or Quote of a [Customer](#).

```
#include <billing.h>
```

Inheritance diagram for Models::Billing:



## Public Member Functions

- [Billing](#) ()  
*Billing::Billing.* Construct a [Billing](#).
- [Billing](#) (int id)  
*Billing::Billing.* Construct a [Billing](#) or quote.
- [~Billing](#) ()  
destruct a billing object
- void [commit](#) ()  
*Billing::commit.* Insert a modification in [Billing](#) table on the database.
- void [hydrat](#) (int [getId](#))  
*Billing::hydrat.* Update of the [Billing](#) which is specified by [getId](#)
- void [remove](#) ()  
*Billing::remove.* Remove a [Billing](#).
- QVariantHash [getDataMap](#) ()  
*Billing::getDataMap* Get all data of model with a HashMap key/value.
- void [generateTex](#) ()  
*Billing::generateTex* Generate a .tex file for the billing.
- void [generatePdf](#) ()  
*Billing::generatePdf* Generate a .pdf file for the billing.
- QString [getPath](#) ()  
*Billing::getPath* Return the path of billing filename (without extension)
- QString [getFolder](#) ()  
*Billing::getFolder* Return the directory of billing.
- QString [getFilename](#) ()  
*Billing::getFilename* Return the filename of billing (without extension)
- [ContributoriesList](#) & [getContributories](#) ()  
*Billing::getContributories.* Return a map of [Contributory](#) for each [Project](#) of the [Billing](#)
- void [addContributory](#) ([Contributory](#) &c)  
*Billing::addContributories* Add a new contributory for project p.
- double [getSumRate](#) ()  
*Billing::getSumRate.* return [Billing](#) Rate.
- double [getSumQuantity](#) ()  
*Billing::getSumQuantity.* return [Billing](#) total by time.
- QString [getTitle](#) () const  
*Billing::getTitle.* return title of [Billing](#)
- void [setTitle](#) (const QString &[getTitle](#))  
*Billing::setTitle.* Modify the title of [Billing](#)
- QString [getDescription](#) () const  
*Billing::getDescription.* return description of [Billing](#)
- void [setDescription](#) (const QString &[getDescription](#))  
*Billing::setDescription.* Modify the description of [Billing](#)
- int [getNumber](#) () const  
*Billing::getNumber.* Return number of the [Billing](#).
- void [setNumber](#) (int [getNumber](#))  
*Billing::setNumber.* Modify \_number of [Billing](#).
- bool [isBilling](#) () const  
*Billing::isBilling.* Return if it's a billing or a quote.
- void [setIsBilling](#) (bool [isBilling](#))  
*Billing::setIsBilling.* Modify [isBilling](#) of [Billing](#).
- QDate [getDate](#) () const

- *Billing::getDate.* return date of the **Billing**
- void **setDate** (const QDate &getDate)
- *Billing::setDate.* Modify date of the **Billing**
- bool **isPaid** () const
- *Billing::isPaid* Return TRUE if thee current billing is paid else return FALSE.
- void **setIsPaid** (bool **isPaid**)
- *Billing::setIsPaid* Define the current billing according the argument **isPaid**
- bool **operator==** (const **Billing** &b)
- *Billing::operator ==* define the operator "==" to compare two billings and to see if they are the same.
- bool **operator!=** (const **Billing** &b)
- *Billing::operator !=* defines the operator "!=" to compare two **Billing** and to see if they are different.
- void **setContributories** (const **ContributoriesList** &contributories)
- bool **operator<** (const **Billing** &b) const
- *Billing::operator <* defines the operator "<" to compare two **Billing** and to see if the first is anterior to the second.

## Additional Inherited Members

### 8.3.1 Detailed Description

The **Billing** class : **Billing** or Quote of a **Customer**.

#### Author

Antoine de Roquemaurel  
Florent Berbie

### 8.3.2 Constructor & Destructor Documentation

#### 8.3.2.1 Models::Billing::Billing ( int id )

**Billing::Billing.** Construct a **Billing** or quote.

#### Parameters

<i>int</i>	id
------------	----

### 8.3.3 Member Function Documentation

#### 8.3.3.1 void Models::Billing::addContributory ( Contributory & c )

**Billing::addContributories** Add a new contributory for project p.

#### Parameters

<i>p</i>	The <b>Project</b> who contain <b>Contributory</b>
<i>c</i>	The new <b>Contributory</b>

#### 8.3.3.2 ContributoriesList & Models::Billing::getContributories ( )

**Billing::getContributories.** Return a map of **Contributory** for each **Project** of the **Billing**

#### Returns

QMap<**Project**, QList<Contributory>>



#### 8.3.3.3 QVariantHash Models::Billing::getDataMap ( ) [virtual]

[Billing::getDataMap](#) Get all data of model with a HashMap key/value.

Returns

Model's data

Implements [Models::IModel](#).

#### 8.3.3.4 QDate Models::Billing::getDate ( ) const

[Billing::getDate](#). return date of the [Billing](#)

Returns

date of [Billing](#)

#### 8.3.3.5 QString Models::Billing::getDescription ( ) const

[Billing::getDescription](#). return description of [Billing](#)

Returns

description of [Billing](#)

#### 8.3.3.6 QString Models::Billing::getFilename ( )

[Billing::getFilename](#) Return the filename of billing (without extension)

Returns

Filename of [Billing](#)

#### 8.3.3.7 QString Models::Billing::getFolder ( )

[Billing::getFolder](#) Return the directory of billing.

Returns

[Billing](#) directory

#### 8.3.3.8 int Models::Billing::getNumber ( ) const

[Billing::getNumber](#). Return number of the [Billing](#).

Returns

\_number of [Billing](#)

#### 8.3.3.9 QString Models::Billing::getPath ( )

[Billing::getPath](#) Return the path of billing filename (without extension)

Returns

billing path

#### 8.3.3.10 double Models::Billing::getSumQuantity ( )

[Billing::getSumQuantity](#). return **Billing** total by time.

Returns

time in hours

#### 8.3.3.11 double Models::Billing::getSumRate ( )

[Billing::getSumRate](#). return **Billing Rate**.

Returns

#### 8.3.3.12 QString Models::Billing::getTitle ( ) const

[Billing::getTitle](#). return title of **Billing**

Returns

title of **Billing**

#### 8.3.3.13 void Models::Billing::hydrat ( int *getId* ) [virtual]

[Billing::hydrat](#). Update of the **Billing** which is specified by *getId*

Parameters

<i>getId</i>	
--------------	--

Implements [Models::IModel](#).

#### 8.3.3.14 bool Models::Billing::isBilling ( ) const

[Billing::isBilling](#). Return if it's a billing or a quote.

Returns

if it's billing or a quote

#### 8.3.3.15 bool Models::Billing::isPaid ( ) const

[Billing::isPaid](#) Return TRUE if thee current billing is paid else return FALSE.

Returns

Boolean

8.3.3.16 `bool Models::Billing::operator!= ( const Billing & b )`

`Billing::operator !=` defines the operator "!=" to compare two `Billing` and to see if they are different.

Parameters

<i>b</i>	the <code>Billing</code> to compare with the current <code>Billing</code>
----------	---------------------------------------------------------------------------

Returns

true if the `Billing` are different else false

8.3.3.17 `bool Models::Billing::operator< ( const Billing & b ) const`

`Billing::operator <` defines the operator "<" to compare two `Billing` and to see if the first is anterior to the second.

Parameters

<i>b</i>	the <code>Billing</code> to compare with the current <code>Billing</code>
----------	---------------------------------------------------------------------------

Returns

true if the `Billing` are different else false

8.3.3.18 `bool Models::Billing::operator== ( const Billing & b )`

`Billing::operator ==` define the operator "==" to compare two billings and to see if they are the same.

Parameters

<i>b</i>	the <code>Billing</code> to compare with the current <code>Billing</code>
----------	---------------------------------------------------------------------------

Returns

true if they are the same billings else false

8.3.3.19 `void Models::Billing::setDate ( const QDate & getDate )`

`Billing::setDate`. Modify *date* of the `Billing`

Parameters

<i>getDate</i>	the new date of the <code>Billing</code>
----------------	------------------------------------------

8.3.3.20 `void Models::Billing::setDescription ( const QString & getDescription )`

`Billing::setDescription`. Modify the description of `Billing`

Parameters

<i>getDescription</i>	Modify the description with <i>getDescription</i>
-----------------------	---------------------------------------------------

8.3.3.21 `void Models::Billing::setIsBilling ( bool isBilling )`

`Billing::setIsBilling`. Modify *isBilling* of `Billing`.

## Parameters

<i>isBilling</i>	
------------------	--

8.3.3.22 void Models::Billing::setIsPaid ( bool *isPaid* )

[Billing::setIsPaid](#) Define the current billing according the argument *isPaid*

## Parameters

<i>isPaid</i>	Boolean
---------------	---------

8.3.3.23 void Models::Billing::setNumber ( int *getNumber* )

[Billing::setNumber](#). Modify *\_number* of [Billing](#).

## Parameters

<i>getNumber</i>	the new number of the <a href="#">Billing</a>
------------------	-----------------------------------------------

8.3.3.24 void Models::Billing::setTitle ( const QString & *getTitle* )

[Billing::setTitle](#). Modify the title of [Billing](#)

## Parameters

<i>getTitle</i>	Modify the title with <i>getTitle</i>
-----------------	---------------------------------------

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/models/billing.h
- /home/travis/build/FACT-Team/FactDev/src/models/billing.cpp

## 8.4 Databases::BillingDatabase Class Reference

The [BillingDatabase](#) class Billing (or Quote) table database.

```
#include <billingdatabase.h>
```

Inheritance diagram for Databases::BillingDatabase:



### Public Member Functions

- [Models::Billing](#) \* [getBilling](#) (const int pId)  
*BillingDatabase::getCustomer* get informations about the billing identified by pId
- [WdgModels::BillingsTableModel](#) \* [getBillingsTable](#) (const int idProject) throw (DbException\*)  
*BillingDatabase::getBillingsTable* Return an item model of billings for QTableView.
- int [addBilling](#) (const [Models::Billing](#) &)

- [\*BillingDatabase::addBilling\*](#) Add the billing pBilling to the database.
- void [updateBilling](#) (const [Models::Billing](#) &)
  - [\*BillingDatabase::updateCustomer\*](#) Update informations about the billing pCustomer
- void [removeBilling](#) (const int pld)
  - [\*BillingDatabase::removeCustomer\*](#) Remove the billing with the id pld
- void [addBillingProject](#) (const int idProject, const int idBilling, const int idContributory)
  - [\*BillingDatabase::addBillingProject\*](#) Link a project, a billing and a contributory in the table BillingProject.
- bool [isBillingPaid](#) (const int pld)
  - [\*BillingDatabase::isBillingPaid\*](#) Return TRUE if the id pld correspond to a Billing and not quote (isBilling = 1) and if this billing is paid (isPaid = 1) else return FALSE.
- void [removeBillingProject](#) (const int idProject, const int idBilling, const int idContributory)
  - [\*BillingDatabase::removeBillingProject\*](#) remove a link between a project, a billing and a contributory in the table BillingProject.
- int [getMaxBillingNumber](#) ()
  - [\*getMaxBillingNumber\*](#) Get the last number of a billing
- int [getMaxQuoteNumber](#) ()
  - [\*getMaxQuoteNumber\*](#) Get the last number of a quote
- int [getMaxBillingNumberOfCustomer](#) (const int idCustomer)
  - [\*BillingDatabase::getMaxBillingNumberOfCustomer\*](#) Get the last number of a **Customer's** Billing.
- int [getMaxQuoteNumberOfCustomer](#) (const int idCustomer)
  - [\*BillingDatabase::getMaxQuoteNumberOfCustomer\*](#) Get the last number of a **Customer's** quote.
- QSharedPointer< [Models::Billing](#) > [getBilling](#) (QStringQuery &q)
  - [\*BillingDatabase::getBilling\*](#) Add the element of the q request and return their.
- QMap< [Project](#) \*, [Billing](#) \* > [getAllBillingsOfProject](#) ()
  - [\*BillingDatabase::getAllBillingsOfProject\*](#) Return a map with the project id as key linked to the billing.
- QList< [Billing](#) > [getBillings](#) (const int projectId)
  - [\*BillingDatabase::getBillings\*](#) get bills by project.

## Static Public Member Functions

- static [BillingDatabase](#) \* [instance](#) () throw (DbException\*)
  - [\*BillingDatabase::getInstance\*](#) Return an instance of [BillingDatabase](#)

## Additional Inherited Members

### 8.4.1 Detailed Description

The [BillingDatabase](#) class Billing (or Quote) table database.

Author

See Also

[Database](#)  
Billing/Quote

## 8.4.2 Member Function Documentation

### 8.4.2.1 `int Databases::BillingDatabase::addBilling ( const Models::Billing & pBilling )`

[BillingDatabase::addBilling](#) Add the billing *pBilling* to the database.

Returns

billing id

### 8.4.2.2 `void Databases::BillingDatabase::addBillingProject ( const int idProject, const int idBilling, const int idContributory )`

[BillingDatabase::addBillingProject](#) Link a project, a billing and a contributory in the table BillingProject.

Parameters

<i>idProject</i>	Project id
<i>idBilling</i>	Billing id
<i>idContributory</i>	Contributory id

### 8.4.2.3 `QMap< Project *, Billing * > Databases::BillingDatabase::getAllBillingsOfProject ( )`

[BillingDatabase::getAllBillingsOfProject](#) Return a map with the project id as key linked to the billing.

Returns

Map with projects and Billing

### 8.4.2.4 `Models::Billing * Databases::BillingDatabase::getBilling ( const int pld )`

`BillingDatabase::getCustomer` get informations about the billing identified by *pld*

Parameters

<i>pld</i>	billing id
------------	------------

Returns

the Billing

### 8.4.2.5 `QSharedPointer< Billing > Databases::BillingDatabase::getBilling ( QSqlQuery & q )`

[BillingDatabase::getBilling](#) Add the element of the *q* request and return their.

Parameters

<i>q</i>	SQL request
----------	-------------

Returns

a billing formed according to QSharedPointer

### 8.4.2.6 `QList< Billing > Databases::BillingDatabase::getBillings ( const int projectId )`

[BillingDatabase::getBillings](#) get bills by project.

## Parameters

<i>projectId</i>	
------------------	--

## Returns

List with bills

**8.4.2.7** `WdgModels::BillingsTableModel * Databases::BillingDatabase::getBillingsTable ( const int idProject ) throw DbException *`

[BillingDatabase::getBillingsTable](#) Return an item model of billings for QTableView.

## Parameters

<i>pId</i>	the project id of the billings returned
------------	-----------------------------------------

## Exceptions

<i>DbException</i>	
--------------------	--

## Returns

QStandardItemModel an item model for QTableView

**8.4.2.8** `int Databases::BillingDatabase::getMaxBillingNumber ( )`

`getMaxBillingNumber` Get the last number of a billing

## Returns

The max number

**8.4.2.9** `int Databases::BillingDatabase::getMaxBillingNumberOfCustomer ( const int idCustomer )`

[BillingDatabase::getMaxBillingNumberOfCustomer](#) Get the last number of a **Customer's** Billing.

## Parameters

<i>idCustomer</i>	Customer id
-------------------	-------------

## Returns

the last number of the **Customer's** Billing

**8.4.2.10** `int Databases::BillingDatabase::getMaxQuoteNumber ( )`

`getMaxQuoteNumber` Get the last number of a quote

## Returns

The last number

**8.4.2.11** `int Databases::BillingDatabase::getMaxQuoteNumberOfCustomer ( const int idCustomer )`

[BillingDatabase::getMaxQuoteNumberOfCustomer](#) Get the last number of a **Customer's** quote.

## Parameters

<i>idCustomer</i>	Customer id
-------------------	-------------

## Returns

the last number of the **Customer's** quote

#### 8.4.2.12 **BillingDatabase** \* **Databases::BillingDatabase::instance** ( ) throw **DbException** \*) [static]

**BillingDatabase::getInstance** Return an instance of [BillingDatabase](#)

## See Also

[DbException](#)

## Returns

Instance of [BillingDatabase](#)

#### 8.4.2.13 **bool** **Databases::BillingDatabase::isBillingPaid** ( const int *pld* )

[BillingDatabase::isBillingPaid](#) Return TRUE if the id *pld* correspond to a Billing and not quote (isBilling = 1) and if this billing is paid (isPaid = 1) else return FALSE.

## Parameters

<i>pld</i>	Billing id
------------	------------

## Returns

TRUE if billing is paid

#### 8.4.2.14 **void** **Databases::BillingDatabase::removeBilling** ( const int *pld* )

**BillingDatabase::removeCustomer** Remove the billing with the id *pld*

## Parameters

<i>pld</i>	billing id
------------	------------

#### 8.4.2.15 **void** **Databases::BillingDatabase::removeBillingProject** ( const int *idProject*, const int *idBilling*, const int *idContributory* )

[BillingDatabase::removeBillingProject](#) remove a link between a project, a billing and a contributory in the table **BillingProject**.

## Parameters

<i>idProject</i>	Project id
<i>idBilling</i>	Billing id



<i>idContributory</i>	Contributory id
-----------------------	-----------------

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/database/billingdatabase.h
- /home/travis/build/FACT-Team/FactDev/src/database/billingdatabase.cpp

## 8.5 BillingDatabaseTest Class Reference

Inheritance diagram for BillingDatabaseTest:



The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/tests/database/billingdatabasetest.h
- /home/travis/build/FACT-Team/FactDev/tests/database/billingdatabasetest.cpp

## 8.6 BillingModelTest Class Reference

Inheritance diagram for BillingModelTest:



The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/tests/models/billingmodeltest.h
- /home/travis/build/FACT-Team/FactDev/tests/models/billingmodeltest.cpp

## 8.7 Gui::Widgets::WdgModels::BillingsTableModel Class Reference

The [BillingsTableModel](#) class for a Billing table.

```
#include <billingstablemodel.h>
```

Inheritance diagram for Gui::Widgets::WdgModels::BillingsTableModel:



## Public Member Functions

- [BillingsTableModel](#) ()  
*[BillingsTableModel::BillingsTableModel](#) Construct a [BillingsTableModel](#).*
- int [rowCount](#) (const QModelIndex &) const  
*[BillingsTableModel::rowCount](#) Number of billings row.*
- int [columnCount](#) (const QModelIndex &) const  
*[BillingsTableModel::columnCount](#) Number of column of a Billing.*
- QVariant [data](#) (const QModelIndex &index, int role=Qt::DisplayRole) const  
*[BillingsTableModel::data](#) Obtains data of a specify cell.*
- QVariant [headerData](#) (int section, Qt::Orientation orientation, int role=Qt::DisplayRole) const  
*[BillingsTableModel::headerData](#) Obtains header title of table.*
- bool [setData](#) (const QModelIndex &index, const QVariant &value, int role=Qt::EditRole)  
*[BillingsTableModel::setData](#) Change data of a cell.*
- void [append](#) (const [Billing](#) &billing)  
*[BillingsTableModel::append](#) Add a new line in table.*
- void [remove](#) (const int i)  
*[BillingsTableModel::remove](#) Remove a line.*
- Qt::ItemFlags [flags](#) (const QModelIndex &index) const  
*[BillingsTableModel::flags](#) Differents table flags.*
- int [count](#) ()  
*[BillingsTableModel::count](#) Number of billings in table.*
- QList< [Billing](#) > [getBillings](#) () const  
*[BillingsTableModel::getbillings](#) Return the list of billings.*

### 8.7.1 Detailed Description

The [BillingsTableModel](#) class for a Billing table.

#### Author

Florent Berbie

#### See Also

[Billing](#)

### 8.7.2 Constructor & Destructor Documentation

#### 8.7.2.1 Gui::Widgets::WdgModels::BillingsTableModel::BillingsTableModel ( )

[BillingsTableModel::BillingsTableModel](#) Construct a [BillingsTableModel](#).

#### Parameters

<i>parent</i>	Parent widget
---------------	---------------

### 8.7.3 Member Function Documentation

#### 8.7.3.1 void Gui::Widgets::WdgModels::BillingsTableModel::append ( const [Billing](#) & *billing* )

[BillingsTableModel::append](#) Add a new line in table.

## Parameters

<i>Billing</i>	The new Billing
----------------	-----------------

**8.7.3.2** `int Gui::Widgets::WdgModels::BillingsTableModel::columnCount ( const QModelIndex & ) const`

[BillingsTableModel::columnCount](#) Number of column of a Billing.

## Returns

The number of column

**8.7.3.3** `int Gui::Widgets::WdgModels::BillingsTableModel::count ( )`

[BillingsTableModel::count](#) Number of billings in table.

## Returns

The number of billings

**8.7.3.4** `QVariant Gui::Widgets::WdgModels::BillingsTableModel::data ( const QModelIndex & index, int role = Qt::DisplayRole ) const`

[BillingsTableModel::data](#) Obtains data of a specify cell.

## Parameters

<i>index</i>	The cell who we want data
<i>role</i>	The role of set

## Returns

The data of cell

**8.7.3.5** `Qt::ItemFlags Gui::Widgets::WdgModels::BillingsTableModel::flags ( const QModelIndex & index ) const`

[BillingsTableModel::flags](#) Differents table flags.

## Parameters

<i>index</i>	The cell who we want to know flags
--------------	------------------------------------

## Returns

Flags

**8.7.3.6** `QList< Billing > Gui::Widgets::WdgModels::BillingsTableModel::getBillings ( ) const`

[BillingsTableModel::getbillings](#) Return the list of billings.

## Returns

list of billings

**8.7.3.7** `QVariant Gui::Widgets::WdgModels::BillingsTableModel::headerData ( int section, Qt::Orientation orientation, int role = Qt::DisplayRole ) const`

[BillingsTableModel::headerData](#) Obtains header title of table.

## Parameters

<i>section</i>	The number of column
<i>orientation</i>	The table orientation
<i>role</i>	

## Returns

The Title header of column

**8.7.3.8** void Gui::Widgets::WdgModels::BillingsTableModel::remove ( const int *i* )

[BillingsTableModel::remove](#) Remove a line.

## Parameters

<i>i</i>	The number of line to remove
----------	------------------------------

**8.7.3.9** int Gui::Widgets::WdgModels::BillingsTableModel::rowCount ( const QModelIndex & ) const

[BillingsTableModel::rowCount](#) Number of billings row.

## Returns

The number of billings

**8.7.3.10** bool Gui::Widgets::WdgModels::BillingsTableModel::setData ( const QModelIndex & *index*, const QVariant & *value*, int *role* = Qt::EditRole )

[BillingsTableModel::setData](#) Change data of a cell.

## Parameters

<i>index</i>	The cell to change data
<i>value</i>	The new value
<i>role</i>	The role of cell

## Returns

True if we could edit

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/widgetsmodels/billingstablemodel.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/widgetsmodels/billingstablemodel.cpp

## 8.8 Gui::Widgets::CheckFields::CheckCity Class Reference

The [CheckCity](#) class Line Edit of City with a check icon.

```
#include <checkcity.h>
```

Inheritance diagram for Gui::Widgets::CheckFields::CheckCity:



## Public Member Functions

- [CheckCity](#) (QWidget \*w=0, QPushButton \*btn=0)

[CheckCity::CheckCity](#) Construct a [CheckCity](#).

## Additional Inherited Members

### 8.8.1 Detailed Description

The [CheckCity](#) class Line Edit of City with a check icon.

### 8.8.2 Constructor & Destructor Documentation

#### 8.8.2.1 Gui::Widgets::CheckFields::CheckCity::CheckCity ( QWidget \* w = 0, QPushButton \* btn = 0 )

[CheckCity::CheckCity](#) Construct a [CheckCity](#).

#### Parameters

<i>w</i>	QWidget linked to <a href="#">CheckCity</a>
----------	---------------------------------------------

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkcity.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkcity.cpp

## 8.9 Gui::Widgets::CheckFields::CheckCountry Class Reference

[CheckCountry::CheckCountry](#) Line Edit of country with a check icon.

```
#include <checkcountry.h>
```

Inheritance diagram for Gui::Widgets::CheckFields::CheckCountry:



## Public Member Functions

- [CheckCountry](#) (QWidget \*w=0, QPushButton \*btn=0)  
*CheckCountry::CheckCountry* Construct a [CheckCountry](#).

## Additional Inherited Members

### 8.9.1 Detailed Description

[CheckCountry::CheckCountry](#) Line Edit of country with a check icon.

### 8.9.2 Constructor & Destructor Documentation

8.9.2.1 [Gui::Widgets::CheckFields::CheckCountry::CheckCountry](#) ( [QWidget](#) \* *w* = 0, [QPushButton](#) \* *btn* = 0 )

[CheckCountry::CheckCountry](#) Construct a [CheckCountry](#).

Parameters

<i>w</i>	<a href="#">QWidget</a> linked to <a href="#">CheckCountry</a>
----------	----------------------------------------------------------------

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkcountry.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkcountry.cpp

## 8.10 Gui::Widgets::CheckFields::CheckEmail Class Reference

The [CheckEmail](#) class Line Edit of email with a check icon.

```
#include <checkemail.h>
```

Inheritance diagram for [Gui::Widgets::CheckFields::CheckEmail](#):



## Public Member Functions

- [CheckEmail](#) (QWidget \*w=0, QPushButton \*btn=0)  
[CheckEmail::CheckEmail](#) Construct a CheckMail.
- bool [check](#) (const QString text)  
[CheckEmail::check](#) Check if the field email is valid. To be valid, an email address should be under this form: *me@me. - xx* An email address need:

## Additional Inherited Members

### 8.10.1 Detailed Description

The [CheckEmail](#) class Line Edit of email with a check icon.

### 8.10.2 Constructor & Destructor Documentation

8.10.2.1 [Gui::Widgets::CheckFields::CheckEmail::CheckEmail](#) ( [QWidget](#) \* *w* = 0, [QPushButton](#) \* *btn* = 0 )

[CheckEmail::CheckEmail](#) Construct a CheckMail.

Parameters

<i>w</i>	<a href="#">QWidget</a> linked to <a href="#">CheckEmail</a>
----------	--------------------------------------------------------------

### 8.10.3 Member Function Documentation

8.10.3.1 bool [Gui::Widgets::CheckFields::CheckEmail::check](#) ( const [QString](#) *text* ) [virtual]

[CheckEmail::check](#) Check if the field email is valid. To be valid, an email address should be under this form: *me@me. xx* An email address need:

- 1 character [A-Z] or [a-z] minimum before the character *</i>*
- the character '@'
- 1 character [A-Z] or [a-z] after the character *</i>* minimum and before the character .
- 1 character [A-Z] or [a-z] minimum after the character . Return TRUE if email address is valid, else FALSE

Parameters

<i>text</i>	<i>Text to check</i>
-------------	----------------------

Returns

*boolean Validity of the text*

Implements [Gui::Widgets::CheckFields::ICheckField](#).

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkemail.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkemail.cpp



## 8.11 Gui::Widgets::CheckFields::CheckFieldsLetters Class Reference

The [CheckFieldsLetters](#) class Field with only letters (no numbers)

```
#include <checkfieldsletters.h>
```

Inheritance diagram for Gui::Widgets::CheckFields::CheckFieldsLetters:



### Public Member Functions

- [CheckFieldsLetters](#) (QWidget \*w=0, QPushButton \*btn=0)  
[CheckFieldsLetters::CheckFieldsLetters](#) Construct a [CheckFieldsLetters](#).
- bool [check](#) (QString text)  
[CheckFieldsLetters::check](#) Check if the field contains only letters.

### Additional Inherited Members

#### 8.11.1 Detailed Description

The [CheckFieldsLetters](#) class Field with only letters (no numbers)

#### 8.11.2 Constructor & Destructor Documentation

8.11.2.1 [Gui::Widgets::CheckFields::CheckFieldsLetters::CheckFieldsLetters](#) ( [QWidget](#) \* *w* = 0, [QPushButton](#) \* *btn* = 0 )

[CheckFieldsLetters::CheckFieldsLetters](#) Construct a [CheckFieldsLetters](#).

Parameters

<i>w</i>	QWidget linked to <a href="#">CheckFieldsLetters</a>
----------	------------------------------------------------------

#### 8.11.3 Member Function Documentation

8.11.3.1 bool [Gui::Widgets::CheckFields::CheckFieldsLetters::check](#) ( [QString](#) *text* ) [virtual]

[CheckFieldsLetters::check](#) Check if the field contains only letters.

Parameters

<i>text</i>	Text to check
-------------	---------------

**Returns**

boolean Validity of the text

Implements [Gui::Widgets::CheckFields::ICheckField](#).

The documentation for this class was generated from the following files:


- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkfieldsletters.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkfieldsletters.cpp

## 8.12 Gui::Widgets::CheckFields::CheckFieldsNumbers Class Reference

The [CheckFieldsNumbers](#) class Line Edit of number with a check icon.

```
#include <checkfieldsnumbers.h>
```

Inheritance diagram for Gui::Widgets::CheckFields::CheckFieldsNumbers:

**Public Member Functions**

- [CheckFieldsNumbers](#) (QWidget \*w=0, QPushButton \*btn=0)  
*CheckFieldsNumbers::CheckFieldsNumbers* Construct a [CheckFieldsNumbers](#).
- bool [check](#) (QString text)  
*CheckFieldsNumbers::check* Check if the field contains only numbers.

**Additional Inherited Members**

### 8.12.1 Detailed Description

The [CheckFieldsNumbers](#) class Line Edit of number with a check icon.

**Author**

Florent BERBIE

**See Also**

[CheckQLineEdit](#)  
[CheckUntilField](#)

### 8.12.2 Constructor & Destructor Documentation

8.12.2.1 [Gui::Widgets::CheckFields::CheckFieldsNumbers::CheckFieldsNumbers](#) ( [QWidget](#) \* *w* = 0, [QPushButton](#) \* *btn* = 0 )

[CheckFieldsNumbers::CheckFieldsNumbers](#) Construct a [CheckFieldsNumbers](#).

## Parameters

<i>w</i>	QWidget linked to <a href="#">CheckFieldsNumbers</a>
----------	------------------------------------------------------

## 8.12.3 Member Function Documentation

8.12.3.1 bool Gui::Widgets::CheckFields::CheckFieldsNumbers::check ( QString *text* ) [virtual]

[CheckFieldsNumbers::check](#) Check if the field contains only numbers.

## Parameters

<i>text</i>	Text to check
-------------	---------------

## Returns

boolean Validity of the text

Implements [Gui::Widgets::CheckFields::ICheckField](#).

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkfieldsnumbers.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkfieldsnumbers.cpp

## 8.13 Gui::Widgets::CheckFields::CheckIpAddress Class Reference

The [CheckIpAddress](#) class Line Edit of IP address with a check icon.

```
#include <checkipaddress.h>
```

Inheritance diagram for Gui::Widgets::CheckFields::CheckIpAddress:



## Public Member Functions

- [CheckIpAddress](#) (QWidget \*w=0, QPushButton \*btn=0)  
[CheckIpAddress::CheckIpAddress](#) Construct a [CheckIpAddress](#).
- bool [check](#) (QString *text*)  
[CheckIpAddress::check](#) Check if the field contains an IP address or domain name valid.

## Additional Inherited Members

## 8.13.1 Detailed Description

The [CheckIpAddress](#) class Line Edit of IP address with a check icon.

## Author

Florent BERBIE

## See Also

[CheckQLineEdit](#)  
[CheckUntilField](#)

## 8.13.2 Constructor &amp; Destructor Documentation

8.13.2.1 `Gui::Widgets::CheckFields::CheckIpAddress::CheckIpAddress ( QWidget * w = 0, QPushButton * btn = 0 )`[CheckIpAddress::CheckIpAddress](#) Construct a [CheckIpAddress](#).

## Parameters

<i>w</i>	QWidget linked to <a href="#">CheckIpAddress</a>
----------	--------------------------------------------------

## 8.13.3 Member Function Documentation

8.13.3.1 `bool Gui::Widgets::CheckFields::CheckIpAddress::check ( QString text ) [virtual]`[CheckIpAddress::check](#) Check if the field contains an IP address or domain name valid.

## Parameters

<i>text</i>	Text to check
-------------	---------------

## Returns

boolean Validity of the text

Implements [Gui::Widgets::CheckFields::ICheckField](#).

The documentation for this class was generated from the following files:


- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkipaddress.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkipaddress.cpp

## 8.14 Gui::Widgets::CheckFields::CheckLogin Class Reference

The [CheckLogin](#) class Line Edit of login with a check icon.

#include &lt;checklogin.h&gt;

Inheritance diagram for Gui::Widgets::CheckFields::CheckLogin:



## Public Slots

- void [passwordPreviousInputed](#) (const QString &text)  
[CheckLogin::fieldTextChanged](#) For each new characater inputed or removed, displays an icon to show if the field is valid or not.

## Public Member Functions

- [CheckLogin](#) (QWidget \*w=0, QPushButton \*btn=0)  
[CheckLogin::CheckLogin](#) Construct a [CheckLogin](#).
- bool [check](#) (QString text)  
[CheckLogin::check](#) Check if the field contains only numbers.

### 8.14.1 Detailed Description

The [CheckLogin](#) class Line Edit of login with a check icon.

#### Author

Florent BERBIE

#### See Also

[CheckQLineEdit](#)  
[CheckUntilField](#)

### 8.14.2 Constructor & Destructor Documentation

#### 8.14.2.1 Gui::Widgets::CheckFields::CheckLogin::CheckLogin ( QWidget \* w = 0, QPushButton \* btn = 0 )

[CheckLogin::CheckLogin](#) Construct a [CheckLogin](#).

#### Parameters

<i>w</i>	QWidget linked to <a href="#">CheckIpAddress</a>
----------	--------------------------------------------------

### 8.14.3 Member Function Documentation

#### 8.14.3.1 bool Gui::Widgets::CheckFields::CheckLogin::check ( QString text ) [virtual]

[CheckLogin::check](#) Check if the field contains only numbers.

#### Parameters

<i>text</i>	Text to check
-------------	---------------

#### Returns

boolean Validity of the text

Implements [Gui::Widgets::CheckFields::ICheckField](#).

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checklogin.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checklogin.cpp

## 8.15 Gui::Widgets::CheckFields::CheckName Class Reference

The [CheckName](#) class Line edit of name with a check icon.

```
#include <checkname.h>
```

Inheritance diagram for Gui::Widgets::CheckFields::CheckName:



### Public Member Functions

- [CheckName](#) (QWidget \*w=0, QPushButton \*btn=0)  
*CheckName::CheckName* Construct a [CheckName](#).

### Additional Inherited Members

#### 8.15.1 Detailed Description

The [CheckName](#) class Line edit of name with a check icon.

#### 8.15.2 Constructor & Destructor Documentation

##### 8.15.2.1 Gui::Widgets::CheckFields::CheckName::CheckName ( QWidget \* w = 0, QPushButton \* btn = 0 )

[CheckName::CheckName](#) Construct a [CheckName](#).

Parameters

<i>w</i>	QWidget linked to <a href="#">CheckName</a>
----------	---------------------------------------------

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkname.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkname.cpp

## 8.16 Gui::Widgets::CheckFields::CheckPhone Class Reference

The [CheckPhone](#) class Line Edit of Phone number with a check icon.

```
#include <checkphone.h>
```

Inheritance diagram for Gui::Widgets::CheckFields::CheckPhone:



## Public Member Functions

- [CheckPhone](#) (QWidget \*w=0, QPushButton \*btn=0)  
[CheckPhone::CheckPhone](#) Construct a [CheckPhone](#).
- bool [check](#) (QString text)  
[CheckPhone::check](#) Check if the field is valid. To be valid, a name should be composed of a character.
- QString [getCountry](#) () const  
[CheckPhone::getCountry](#) Return the country linked to current field.
- void [setCountry](#) (const QString &country)  
[CheckPhone::setCountry](#) Modify the country linked to field.

## Additional Inherited Members

### 8.16.1 Detailed Description

The [CheckPhone](#) class Line Edit of Phone number with a check icon.

### 8.16.2 Constructor & Destructor Documentation

8.16.2.1 [Gui::Widgets::CheckFields::CheckPhone::CheckPhone](#) ( [QWidget](#) \* *w* = 0, [QPushButton](#) \* *btn* = 0 )

[CheckPhone::CheckPhone](#) Construct a [CheckPhone](#).

Parameters

<i>w</i>	QWidget linked to <a href="#">CheckPhone</a>
----------	----------------------------------------------

### 8.16.3 Member Function Documentation

8.16.3.1 bool [Gui::Widgets::CheckFields::CheckPhone::check](#) ( [QString](#) *text* ) [virtual]

[CheckPhone::check](#) Check if the field is valid. To be valid, a name should be composed of a character.

Parameters

<i>text</i>	Text to check
-------------	---------------

Returns

boolean Validity of the text

Implements [Gui::Widgets::CheckFields::ICheckField](#).

### 8.16.3.2 QString Gui::Widgets::CheckFields::CheckPhone::getCountry ( ) const

[CheckPhone::getCountry](#) Return the country linked to current field.

Returns

### 8.16.3.3 void Gui::Widgets::CheckFields::CheckPhone::setCountry ( const QString & country )

[CheckPhone::setCountry](#) Modify the *country* linked to field.

Parameters

<i>country</i>	New country
----------------	-------------

The documentation for this class was generated from the following files:


- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkphone.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkphone.cpp

## 8.17 Gui::Widgets::CheckFields::CheckPortNumber Class Reference

The [CheckFieldsNumbers](#) class Line Edit of number with a check icon.

```
#include <checkportnumber.h>
```

Inheritance diagram for Gui::Widgets::CheckFields::CheckPortNumber:



### Public Member Functions

- [CheckPortNumber](#) (QWidget \*w=0, QPushButton \*btn=0)  
*CheckPortNumber.*
- bool [check](#) (QString text)  
*CheckPortNumber::check* Check if the field contains only numbers or an empty text.

### Additional Inherited Members

#### 8.17.1 Detailed Description

The [CheckFieldsNumbers](#) class Line Edit of number with a check icon.

Author

Florent BERBIE



See Also

[CheckQLineEdit](#)  
[CheckUntilField](#)

## 8.17.2 Constructor & Destructor Documentation

8.17.2.1 `Gui::Widgets::CheckFields::CheckPortNumber::CheckPortNumber ( QWidget * w = 0, QPushButton * btn = 0 )`

[CheckPortNumber.](#)

Parameters

<i>w</i>	Widget parent
<i>btn</i>	Button parretrn

## 8.17.3 Member Function Documentation

8.17.3.1 `bool Gui::Widgets::CheckFields::CheckPortNumber::check ( QString text )` `[virtual]`

[CheckPortNumber::check](#) Check if the field contains only numbers or an empty text.

Parameters

<i>text</i>	Text to check
-------------	---------------

Returns

boolean Validity of the text

Implements [Gui::Widgets::CheckFields::ICheckField](#).

The documentation for this class was generated from the following files:


- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkportnumber.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkportnumber.cpp

## 8.18 Gui::Widgets::CheckFields::CheckPostalCode Class Reference

The [CheckPostalCode](#) class Line Edit of postal code with a check icon.

```
#include <checkpostalcode.h>
```

Inheritance diagram for Gui::Widgets::CheckFields::CheckPostalCode:



## Public Member Functions

- [CheckPostalCode](#) (QWidget \*w=0, QPushButton \*btn=0)  
*[CheckPostalCode::CheckPostalCode](#) Construct a [CheckPostalCode](#).*
- bool [check](#) (QString text)  
*[CheckPostalCode::check](#) Check if the field is valid. To be valid, a name should be composed of a character.*
- QString [getCountry](#) () const  
*[CheckPostalCode::getCountry](#) Return the country linked to current field.*
- void [setCountry](#) (const QString &country)  
*[CheckPostalCode::setCountry](#) Modify the country linked to field.*

## Additional Inherited Members

### 8.18.1 Detailed Description

The [CheckPostalCode](#) class Line Edit of postal code with a check icon.

### 8.18.2 Constructor & Destructor Documentation

8.18.2.1 `Gui::Widgets::CheckFields::CheckPostalCode::CheckPostalCode ( QWidget * w = 0, QPushButton * btn = 0 )`

[CheckPostalCode::CheckPostalCode](#) Construct a [CheckPostalCode](#).

Parameters

<i>w</i>	QWidget linked to <a href="#">CheckPostalCode</a>
----------	---------------------------------------------------

### 8.18.3 Member Function Documentation

8.18.3.1 `bool Gui::Widgets::CheckFields::CheckPostalCode::check ( QString text ) [virtual]`

[CheckPostalCode::check](#) Check if the field is valid. To be valid, a name should be composed of a character.

Parameters

<i>text</i>	Text to check
-------------	---------------

Returns

boolean Validity of the text

Implements [Gui::Widgets::CheckFields::ICheckField](#).

8.18.3.2 `QString Gui::Widgets::CheckFields::CheckPostalCode::getCountry ( ) const`

[CheckPostalCode::getCountry](#) Return the country linked to current field.

Returns

country Country of the field

8.18.3.3 `void Gui::Widgets::CheckFields::CheckPostalCode::setCountry ( const QString & country )`

[CheckPostalCode::setCountry](#) Modify the *country* linked to field.

## Parameters

<i>country</i>	New country
----------------	-------------

The documentation for this class was generated from the following files:


- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkpostalcode.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkpostalcode.cpp

## 8.19 Gui::Widgets::CheckFields::CheckQLineEdit Class Reference

The [CheckQLineEdit](#) class QLineEdit custom with a check of text inputed.

```
#include <checkqlineEdit.h>
```

Inheritance diagram for Gui::Widgets::CheckFields::CheckQLineEdit:



### Public Slots

- void [fieldTextChanged](#) (const QString &text)  
[CheckQLineEdit::fieldTextChanged](#) For each new characater inputed or removed, displays an icon to show if the field is valid or not.

### Public Member Functions

- [CheckQLineEdit](#) (QWidget \*parent=0, QPushButton \*btn=0)  
[CheckQLineEdit::CheckQLineEdit](#) Construct a [CheckQLineEdit](#).
- void [displayCheckValidFieldIcon](#) ()  
[CheckQLineEdit::displayCheckValidFieldIcon](#) Display a valid icon into the field.
- void [displayCheckNoValidFieldIcon](#) ()  
[CheckQLineEdit::displayCheckNoValidFieldIcon](#) Display a "no valid" icon into the field.
- QPushButton \* [getBtnValid](#) () const  
[CheckQLineEdit::getBtnValid](#).
- void [setBtnValid](#) (QPushButton \*getBtnValid)  
[CheckQLineEdit::setBtnValid](#).
- bool [isValid](#) ()  
[isValid](#) Return true if the current field if valid

#### 8.19.1 Detailed Description

The [CheckQLineEdit](#) class QLineEdit custom with a check of text inputed.

#### 8.19.2 Constructor & Destructor Documentation

- 8.19.2.1 [Gui::Widgets::CheckFields::CheckQLineEdit::CheckQLineEdit](#) ( QWidget \* *parent* = 0, QPushButton \* *btn* = 0 )  
[explicit]

[CheckQLineEdit::CheckQLineEdit](#) Construct a [CheckQLineEdit](#).

## Parameters

<i>parent</i>	
---------------	--

### 8.19.3 Member Function Documentation

8.19.3.1 `QPushButton * Gui::Widgets::CheckFields::CheckQLineEdit::getBtnValid ( ) const`

[CheckQLineEdit::getBtnValid.](#)

## Returns

a

8.19.3.2 `bool Gui::Widgets::CheckFields::CheckQLineEdit::isValid ( )`

isValid Return true if the current field if valid

## Returns

boolean

8.19.3.3 `void Gui::Widgets::CheckFields::CheckQLineEdit::setBtnValid ( QPushButton * getBtnValid )`

[CheckQLineEdit::setBtnValid.](#)

## Parameters

<i>getBtnValid</i>	
--------------------	--

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkqlineEdit.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkqlineEdit.cpp

## 8.20 Gui::Widgets::CheckFields::CheckSiretNumber Class Reference

The [CheckSiretNumber](#) class Line Edit with a check icon.

```
#include <checksiretnumber.h>
```

Inheritance diagram for Gui::Widgets::CheckFields::CheckSiretNumber:



### Public Member Functions

- [CheckSiretNumber](#) (QWidget \*w=0, QPushButton \*btn=0)

[CheckSiretNumber::CheckSiretNumber](#) Construct a [CheckSiretNumber](#).

- bool [check](#) (QString text)

[CheckSiretNumber::check](#) Check if the field noSiret is valid. To be valid, a SIRET number should be composed of numbers.

## Additional Inherited Members

### 8.20.1 Detailed Description

The [CheckSiretNumber](#) class Line Edit with a check icon.

### 8.20.2 Constructor & Destructor Documentation

8.20.2.1 [Gui::Widgets::CheckFields::CheckSiretNumber::CheckSiretNumber \( QWidget \\* \*w\* = 0, QPushButton \\* \*btn\* = 0 \)](#)

[CheckSiretNumber::CheckSiretNumber](#) Construct a [CheckSiretNumber](#).

Parameters

<i>w</i>	QWidget linked to <a href="#">CheckSiretNumber</a>
----------	----------------------------------------------------

### 8.20.3 Member Function Documentation

8.20.3.1 [bool Gui::Widgets::CheckFields::CheckSiretNumber::check \( QString \*text\* \)](#) [virtual]

[CheckSiretNumber::check](#) Check if the field noSiret is valid. To be valid, a SIRET number should be composed of numbers.

Parameters

<i>text</i>	Text to check
-------------	---------------

Returns

boolean Validity of the text

Implements [Gui::Widgets::CheckFields::ICheckField](#).

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checksiretnumber.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checksiretnumber.cpp

## 8.21 Gui::Widgets::CheckFields::CheckUntilField Class Reference

The [CheckUntilField](#) class.

```
#include <checkuntilfield.h>
```

Inheritance diagram for [Gui::Widgets::CheckFields::CheckUntilField](#):



## Public Member Functions

- [CheckUntilField](#) (QWidget \*w=0, QPushButton \*btn=0)  
[CheckUntilField::CheckUntilField](#) Construct a [CheckUntilField](#).
- bool [check](#) (QString text)  
[CheckUntilField::check](#) Check if the field is valid. To be valid, a name should be composed of a character.

## Additional Inherited Members

### 8.21.1 Detailed Description

The [CheckUntilField](#) class.

### 8.21.2 Constructor & Destructor Documentation

8.21.2.1 [Gui::Widgets::CheckFields::CheckUntilField::CheckUntilField](#) ( [QWidget](#) \* *w* = 0, [QPushButton](#) \* *btn* = 0 )

[CheckUntilField::CheckUntilField](#) Construct a [CheckUntilField](#).

Parameters

<i>w</i>	<a href="#">QWidget</a> linked to <a href="#">CheckUntilField</a>
----------	-------------------------------------------------------------------

### 8.21.3 Member Function Documentation

8.21.3.1 bool [Gui::Widgets::CheckFields::CheckUntilField::check](#) ( [QString](#) *text* ) [\[virtual\]](#)

[CheckUntilField::check](#) Check if the field is valid. To be valid, a name should be composed of a character.

Parameters

<i>text</i>	Text to check
-------------	---------------

Returns

boolean Validity of the text

Implements [Gui::Widgets::CheckFields::ICheckField](#).

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkuntilfield.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkuntilfield.cpp

## 8.22 Gui::Widgets::CheckFields::CheckValidField Class Reference

The [CheckValidField](#) class Check field not required.

```
#include <checkvalidfield.h>
```

Inheritance diagram for [Gui::Widgets::CheckFields::CheckValidField](#):



## Public Member Functions

- [CheckValidField](#) (QWidget \*w=0, QPushButton \*btn=0)  
*[CheckValidField::CheckValidField](#)*.
- bool [check](#) (QString text)  
*[CheckValidField::check](#) Return TRUE : the field is not required.*

## Additional Inherited Members

### 8.22.1 Detailed Description

The [CheckValidField](#) class Check field not required.

### 8.22.2 Constructor & Destructor Documentation

8.22.2.1 [Gui::Widgets::CheckFields::CheckValidField::CheckValidField](#) ( [QWidget](#) \* *w* = 0, [QPushButton](#) \* *btn* = 0 )

[CheckValidField::CheckValidField](#).

Parameters

<i>w</i>	<a href="#">QWidget</a> linked to <a href="#">CheckValidField</a>
----------	-------------------------------------------------------------------

### 8.22.3 Member Function Documentation

8.22.3.1 bool [Gui::Widgets::CheckFields::CheckValidField::check](#) ( [QString](#) *text* ) [virtual]

[CheckValidField::check](#) Return TRUE : the field is not required.

Parameters

<i>text</i>	Text to check
-------------	---------------

Returns

boolean Validity of the text

Implements [Gui::Widgets::CheckFields::ICheckField](#).

The documentation for this class was generated from the following files:


- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkvalidfield.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkvalidfield.cpp

## 8.23 Gui::Widgets::Delegates::ComboBoxDelegate Class Reference

The [ComboBoxDelegate](#) class.

```
#include <comboboxdelegate.h>
```

Inheritance diagram for Gui::Widgets::Delegates::ComboBoxDelegate:



### Public Member Functions

- [ComboBoxDelegate](#) (QObject \*parent=0)  
*ComboBoxDelegate::ComboBoxDelegate* Construct a [ComboBoxDelegate](#).
- virtual QWidget \* [createEditor](#) (QWidget \*parent, const QStyleOptionViewItem &option, const QModelIndex &index) const =0  
*ComboBoxDelegate::createEditor* Return a *ComboBox* specified by index item defined by the parent widget and style option which are used to control how the editor widgets appears.
- void [paint](#) (QPainter \*painter, const QStyleOptionViewItem &option, const QModelIndex &index) const =0  
*ComboBoxDelegate::paint* Renders the delegate using the given painter and style option for the item specified by index
- void [setEditorData](#) (QWidget \*editor, const QModelIndex &index) const  
*ComboBoxDelegate::setEditorData* Sets the data to be displayed and edited by the editor from the data model item specified by the model index
- void [setModelData](#) (QWidget \*editor, QAbstractItemModel \*model, const QModelIndex &index) const  
*ComboBoxDelegate::setModelData* Gets data from the editor widget and stores it in the specified model at the item index
- void [updateEditorGeometry](#) (QWidget \*editor, const QStyleOptionViewItem &option, const QModelIndex &index) const  
*ComboBoxDelegate::updateEditorGeometry* Update the editor for the item specified by index according to the style option given.

### 8.23.1 Detailed Description

The [ComboBoxDelegate](#) class.

Author

Antoine de Roquemaurel

### 8.23.2 Constructor & Destructor Documentation

#### 8.23.2.1 Gui::Widgets::Delegates::ComboBoxDelegate::ComboBoxDelegate ( QObject \* parent = 0 )

[ComboBoxDelegate::ComboBoxDelegate](#) Construct a [ComboBoxDelegate](#).



## Parameters

<i>parent</i>	Object parent
---------------	---------------

## 8.23.3 Member Function Documentation

8.23.3.1 `virtual QWidget* Gui::Widgets::Delegates::ComboBoxDelegate::createEditor ( QWidget * parent, const QStyleOptionViewItem & option, const QModelIndex & index ) const` [pure virtual]

[ComboBoxDelegate::createEditor](#) Return a ComboBox specified by *index* item defined by the *parent* widget and style *option* which are used to control how the editor widgets appears.

## Parameters

<i>parent</i>	Widget parent
<i>option</i>	Option style
<i>index</i>	Index for editing

## Returns

ComboBox

Implemented in [Gui::Widgets::Delegates::UnitComboDelegate](#), and [Gui::Widgets::Delegates::ProjectComboDelegate](#).

8.23.3.2 `void Gui::Widgets::Delegates::ComboBoxDelegate::paint ( QPainter * painter, const QStyleOptionViewItem & option, const QModelIndex & index ) const` [pure virtual]

[ComboBoxDelegate::paint](#) Renders the delegate using the given *painter* and style *option* for the item specified by *index*

## Parameters

<i>parent</i>	Widget parent
<i>option</i>	Option style
<i>index</i>	Index for editing

Implemented in [Gui::Widgets::Delegates::UnitComboDelegate](#), and [Gui::Widgets::Delegates::ProjectComboDelegate](#).

8.23.3.3 `void Gui::Widgets::Delegates::ComboBoxDelegate::setEditorData ( QWidget * editor, const QModelIndex & index ) const`

[ComboBoxDelegate::setEditorData](#) Sets the data to be displayed and edited by the *editor* from the data model item specified by the model *index*

## Parameters

<i>editor</i>	Data edited
<i>index</i>	Index of the model to edit

8.23.3.4 `void Gui::Widgets::Delegates::ComboBoxDelegate::setModelData ( QWidget * editor, QAbstractItemModel * model, const QModelIndex & index ) const`

[ComboBoxDelegate::setModelData](#) Gets data from the *editor* widget and stores it in the specified *model* at the item *index*

## Parameters

<i>editor</i>	Editor Widget
<i>model</i>	Model to store data
<i>index</i>	Item index

8.23.3.5 void Gui::Widgets::Delegates::ComboBoxDelegate::updateEditorGeometry ( QWidget \* *editor*, const QStyleOptionViewItem & *option*, const QModelIndex & *index* ) const

[ComboBoxDelegate::updateEditorGeometry](#) Update the *editor* for the item specified by *index* according to the style *option* given.

## Parameters

<i>editor</i>	Editor widget to update
<i>option</i>	Style option
<i>index</i>	Item index

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/delegates/comboboxdelegate.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/delegates/comboboxdelegate.cpp

## 8.24 Gui::Widgets::ComboBoxModelWidget Class Reference

The [ComboBoxModelWidget](#) class Model of ComboBox.

```
#include <comboboxmodelwidget.h>
```

Inheritance diagram for Gui::Widgets::ComboBoxModelWidget:



### Public Member Functions

- [ComboBoxModelWidget](#) (QWidget \*parent=0)  
[ComboBoxModelWidget::ComboBoxModelWidget](#) Construct a [ComboBoxModelWidget](#).

#### 8.24.1 Detailed Description

The [ComboBoxModelWidget](#) class Model of ComboBox.

#### 8.24.2 Constructor & Destructor Documentation

8.24.2.1 Gui::Widgets::ComboBoxModelWidget::ComboBoxModelWidget ( QWidget \* *parent* = 0 ) [explicit]

[ComboBoxModelWidget::ComboBoxModelWidget](#) Construct a [ComboBoxModelWidget](#).

## Parameters

<i>parent</i>	QWidget parent
---------------	----------------

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/comboboxmodelwidget.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/comboboxmodelwidget.cpp

## 8.25 Mustache::Context Class Reference

```
#include <mustache.h>
```

Inheritance diagram for Mustache::Context:



### Public Member Functions

- [Context](#) ([PartialResolver](#) \*resolver=0)
- virtual QString [stringValue](#) (const QString &key) const =0
- virtual bool [isFalse](#) (const QString &key) const =0
- virtual int [listCount](#) (const QString &key) const =0
- virtual void [push](#) (const QString &key, int index=-1)=0
- virtual void [pop](#) ()=0
- QString [partialValue](#) (const QString &key) const
- [PartialResolver](#) \* [partialResolver](#) () const
- virtual bool [canEval](#) (const QString &key) const
- virtual QString [eval](#) (const QString &key, const QString &\_template, [Renderer](#) \*renderer)

### 8.25.1 Detailed Description

[Context](#) is an interface that [Mustache::Renderer::render\(\)](#) uses to fetch substitutions for template tags.

### 8.25.2 Constructor & Destructor Documentation

8.25.2.1 `Context::Context ( PartialResolver * resolver = 0 )` `[explicit]`

Create a context. `resolver` is used to fetch the expansions for any `{{>partial}}` tags which appear in a template.

### 8.25.3 Member Function Documentation

8.25.3.1 `bool Context::canEval ( const QString & key ) const` `[virtual]`

Returns true if [eval\(\)](#) should be used to render section tags using `key`. If [canEval\(\)](#) returns true for a key, the renderer will pass the literal, unrendered block of text for the section to [eval\(\)](#) and replace the section with the result.

[canEval\(\)](#) and [eval\(\)](#) are equivalents for callable objects (eg. lambdas) in other Mustache implementations.

The default implementation always returns false.

Reimplemented in [CounterContext](#), [CounterContext](#), and [Mustache::QtVariantContext](#).

#### 8.25.3.2 QString Context::eval ( const QString & key, const QString & \_template, Renderer \* renderer ) [virtual]

Callback used to render a template section with the given `key`. `renderer` will substitute the original section tag with the result of [eval\(\)](#).

The default implementation returns an empty string.

Reimplemented in [CounterContext](#), [CounterContext](#), and [Mustache::QtVariantContext](#).

#### 8.25.3.3 virtual bool Mustache::Context::isFalse ( const QString & key ) const [pure virtual]

Returns true if the value for `key` is 'false' or an empty list. 'False' values typically include empty strings, the boolean value false etc.

When processing a section Mustache tag, the section is not rendered if the key is false, or for an inverted section tag, the section is only rendered if the key is false.

Implemented in [Mustache::QtVariantContext](#).

#### 8.25.3.4 virtual int Mustache::Context::listCount ( const QString & key ) const [pure virtual]

Returns the number of items in the list value for `key` or 0 if the value for `key` is not a list.

Implemented in [Mustache::QtVariantContext](#).

#### 8.25.3.5 PartialResolver \* Context::partialResolver ( ) const

Returns the partial resolver passed to the constructor.

#### 8.25.3.6 QString Context::partialValue ( const QString & key ) const

Returns the partial template for a given `key`.

#### 8.25.3.7 virtual void Mustache::Context::pop ( ) [pure virtual]

Exit the current context.

Implemented in [Mustache::QtVariantContext](#).

#### 8.25.3.8 virtual void Mustache::Context::push ( const QString & key, int index = -1 ) [pure virtual]

Set the current context to the value for `key`. If `index` is  $\geq 0$ , set the current context to the `index`'th value in the list value for `key`.

Implemented in [Mustache::QtVariantContext](#).

#### 8.25.3.9 virtual QString Mustache::Context::stringValue ( const QString & key ) const [pure virtual]

Returns a string representation of the value for `key` in the current context. This is used to replace a Mustache value tag.

Implemented in [CounterContext](#), [CounterContext](#), and [Mustache::QtVariantContext](#).

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/libs/qt-mustache/src/mustache.h
- /home/travis/build/FACT-Team/FactDev/src/libs/qt-mustache/src/mustache.cpp

## 8.26 ContributoriesDatabaseTest Class Reference

Inheritance diagram for ContributoriesDatabaseTest:



The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/tests/database/contributoriesdatabasetest.h
- /home/travis/build/FACT-Team/FactDev/tests/database/contributoriesdatabasetest.cpp

## 8.27 Models::ContributoriesList Class Reference

The [ContributoriesList](#) class List of contributories.

```
#include <contributorieslist.h>
```

Inheritance diagram for Models::ContributoriesList:



### Public Member Functions

- [ContributoriesList](#) ()  
*ContributoriesList::ContributoriesList* Construct a [ContributoriesList](#).
- virtual void [commit](#) ()  
*ContributoriesList::commit* Update or insert data into the database.
- void [addContributory](#) ([Models::Contributory](#) &contributory)  
*ContributoriesList::addContributory* Add a new contributory
- void [addProject](#) ([Project](#) \*p, [Models::Rate](#) rate)  
*ContributoriesList::addProject* Add a [Project](#) p and it rate
- [QList< Contributority >](#) & [getContributories](#) ([Project](#) \*p)  
*ContributoriesList::getContributories* Return a list of Contributories for the [Project](#) p
- int [getIdBilling](#) () const  
*ContributoriesList::getIdBilling* Return the [Billing](#) ID.
- void [setIdBilling](#) (int idBilling)

- [ContributoriesList::setIdBilling](#) Change the [Billing](#) id by the new idBilling
- void [setAllIdContributories](#) (int idContributory)
- [ContributoriesList::setAllIdContributories](#) Change all [Contributory](#) id with the same id.
- bool [isInsert](#) () const
- [ContributoriesList::isInsert](#) Return TRUE if an element is inserting else FALSE.
- void [setInsert](#) (bool insert)
- [ContributoriesList::setInsert](#) Change the state of insertion.
- int [getNbProjects](#) ()
- [ContributoriesList::getNbProjects](#) Return the number of projects.
- double [getSumRate](#) ()
- [ContributoriesList::getSumRate](#) Return the sum of the contributories rates.
- double [getSumQuantity](#) ()
- [ContributoriesList::getSumQuantity](#) Return the sum of quantity (number of hours) of the Contributories.
- QSharedPointer< [Customer](#) > [getCustomer](#) ()
- [ContributoriesList::getCustomer](#) Return the Customers linked to theses contributories.
- QList< [Project](#) \* > [getProjects](#) ()
- [ContributoriesList::getProjects](#) List of Projects.
- QList< [Contributory](#) > \* [getAllContributories](#) ()
- [ContributoriesList::getAllContributories](#) List of all contributories (all contributories from all projects)
- [Models::Rate](#) [getRate](#) ([Models::Project](#) \*project)
- [ContributoriesList::getRate](#).
- QVariantList [getDataMap](#) ()
- [ContributoriesList::getDataMap](#) Return a list of [Billing](#) and it value linked which indicates if it is inserting or not.

### 8.27.1 Detailed Description

The [ContributoriesList](#) class List of contributories.

Author

Antoine de Roquemaurel

### 8.27.2 Member Function Documentation

#### 8.27.2.1 void [Models::ContributoriesList::addContributory](#) ( [Models::Contributory](#) & *contributory* )

[ContributoriesList::addContributory](#) Add a new *contributory*

Parameters

<i>contributory</i>	<a href="#">Contributory</a> to add
---------------------	-------------------------------------

#### 8.27.2.2 void [Models::ContributoriesList::addProject](#) ( [Project](#) \* *p*, [Models::Rate](#) *rate* )

[ContributoriesList::addProject](#) Add a [Project](#) *p* and it *rate*

Parameters

<i>p</i>	<a href="#">Project</a> to add
----------	--------------------------------

<i>rate</i>	<a href="#">Rate</a> of the project
-------------	-------------------------------------

### 8.27.2.3 `QList< Contributory > * Models::ContributoriesList::getAllContributories ( )`

[ContributoriesList::getAllContributories](#) List of all contributories (all contributories from all projects)

#### Returns

List of all contributories

### 8.27.2.4 `QList< Contributory > & Models::ContributoriesList::getContributories ( Project * p )`

[ContributoriesList::getContributories](#) Return a list of Contributories for the [Project](#) *p*

#### Parameters

<i>p</i>	<a href="#">Project</a>
----------	-------------------------

#### Returns

List of Contributories for a project

### 8.27.2.5 `QSharedPointer< Customer > Models::ContributoriesList::getCustomer ( )`

[ContributoriesList::getCustomer](#) Return the Customers linked to theses contributories.

#### Returns

[Customer](#)

### 8.27.2.6 `QVariantList Models::ContributoriesList::getDataMap ( )`

[ContributoriesList::getDataMap](#) Return a list of [Billing](#) and it value linked which indicates if it is inserting or not.

#### Returns

List of billing and value linked

### 8.27.2.7 `int Models::ContributoriesList::getIldBilling ( ) const`

[ContributoriesList::getIldBilling](#) Return the [Billing](#) ID.

#### Returns

[Billing](#) id

### 8.27.2.8 `int Models::ContributoriesList::getNbProjects ( )`

[ContributoriesList::getNbProjects](#) Return the number of projects.

#### Returns

Count number of project

8.27.2.9 `QList< Project * > Models::ContributoriesList::getProjects ( void )`

[ContributoriesList::getProjects](#) List of Projects.

Returns

List of Projects

8.27.2.10 `Models::Rate Models::ContributoriesList::getRate ( Models::Project * project )`

[ContributoriesList::getRate](#).

Parameters

<i>project</i>	
----------------	--

Returns

8.27.2.11 `double Models::ContributoriesList::getSumQuantity ( )`

[ContributoriesList::getSumQuantity](#) Return the sum of quantity (number of hours) of the Contributories.

Returns

sum of quantity

8.27.2.12 `double Models::ContributoriesList::getSumRate ( )`

[ContributoriesList::getSumRate](#) Return the sum of the contributories rates.

Returns

Sum of contributories rates

8.27.2.13 `bool Models::ContributoriesList::isInsert ( ) const`

[ContributoriesList::isInsert](#) Return TRUE if an element is inserting else FALSE.

Returns

boolean

8.27.2.14 `void Models::ContributoriesList::setAllIdContributories ( int idContributory )`

[ContributoriesList::setAllIdContributories](#) Change all [Contributory](#) id with the same id.

Parameters



<i>idContributory</i>	the new <a href="#">Contributory</a> id
-----------------------	-----------------------------------------

8.27.2.15 void [Models::ContributoriesList::setIdBilling](#) ( int *idBilling* )

[ContributoriesList::setIdBilling](#) Change the [Billing](#) id by the new *idBilling*

Parameters

<i>idBilling</i>	Billing id
------------------	------------

8.27.2.16 void [Models::ContributoriesList::setInsert](#) ( bool *insert* )

[ContributoriesList::setInsert](#) Change the state of insertion.

Parameters

<i>insert</i>	Boolean
---------------	---------

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/models/contributorieslist.h
- /home/travis/build/FACT-Team/FactDev/src/models/contributorieslist.cpp

## 8.28 Gui::Widgets::WdgModels::ContributoriesTableModel Class Reference

The [ContributoriesTableModel](#) class for a custom table for contributories widget.

```
#include <contributoriestablemodel.h>
```

Inheritance diagram for Gui::Widgets::WdgModels::ContributoriesTableModel:



### Public Member Functions

- [ContributoriesTableModel](#) (QObject \*parent=0)  
*ContributoriesTableModel::ContributoriesTableModel* Construct a [ContributoriesTableModel](#).
- int [rowCount](#) (const QModelIndex &) const  
*ContributoriesTableModel::rowCount* Number of contributories row.
- int [columnCount](#) (const QModelIndex &) const  
*ContributoriesTableModel::columnCount* Number of column of a contributory.
- QVariant [data](#) (const QModelIndex &index, int role) const  
*ContributoriesTableModel::data* Obtains data of a specify cell.
- QVariant [headerData](#) (int section, Qt::Orientation orientation, int role) const  
*ContributoriesTableModel::headerData* Obtains header title of table.
- bool [setData](#) (const QModelIndex &index, const QVariant &value, int role=Qt::EditRole)  
*ContributoriesTableModel::setData* Change data of a cell.
- void [append](#) (const [Contributory](#) &contributory)

- [\*ContributoriesTableModel::append\*](#) Add a new line in table.
- void [\*remove\*](#) (const int i)
- [\*ContributoriesTableModel::remove\*](#) Remove a line.
- Qt::ItemFlags [\*flags\*](#) (const QModelIndex &index) const
- [\*ContributoriesTableModel::flags\*](#) Differents table flags.
- QList< [\*Contributory\*](#) > [\*getContributories\*](#) ()
- [\*ContributoriesTableModel::getContributories\*](#) Get all contributories of table.
- int [\*count\*](#) ()
- [\*ContributoriesTableModel::count\*](#) Number of contributories in table.
- double [\*getSumQuantity\*](#) () const
- [\*ContributoriesTableModel::getSumQuantity\*](#) Return the sum of the hours of all contributories added.
- void [\*clear\*](#) ()
- [\*ContributoriesTableModel::clear\*](#) Remove all contributories.

### 8.28.1 Detailed Description

The [\*ContributoriesTableModel\*](#) class for a custom table for contributories widget.

#### Author

Antoine de Roquemaurel

#### See Also

[\*Contributory\*](#)

### 8.28.2 Constructor & Destructor Documentation

8.28.2.1 [\*Gui::Widgets::WdgModels::ContributoriesTableModel::ContributoriesTableModel \( QObject \\* parent = 0 \)\*](#)

[\*ContributoriesTableModel::ContributoriesTableModel\*](#) Construct a [\*ContributoriesTableModel\*](#).

#### Parameters

<i>parent</i>	Parent widget
---------------	---------------

### 8.28.3 Member Function Documentation

8.28.3.1 void [\*Gui::Widgets::WdgModels::ContributoriesTableModel::append \( const Contributory & contributory \)\*](#)

[\*ContributoriesTableModel::append\*](#) Add a new line in table.

#### Parameters

<i>contributory</i>	The new contributory
---------------------	----------------------

8.28.3.2 int [\*Gui::Widgets::WdgModels::ContributoriesTableModel::columnCount \( const QModelIndex & \)\*](#) const

[\*ContributoriesTableModel::columnCount\*](#) Number of column of a contributory.

#### Returns

The number of column

8.28.3.3 `int Gui::Widgets::WdgModels::ContributoriesTableModel::count ( )`

[ContributoriesTableModel::count](#) Number of contributories in table.

#### Returns

The number of contributories

8.28.3.4 `QVariant Gui::Widgets::WdgModels::ContributoriesTableModel::data ( const QModelIndex & index, int role ) const`

[ContributoriesTableModel::data](#) Obtains data of a specify cell.

#### Parameters

<i>index</i>	The cell who we want data
<i>role</i>	The role of set

#### Returns

The data of cell

8.28.3.5 `Qt::ItemFlags Gui::Widgets::WdgModels::ContributoriesTableModel::flags ( const QModelIndex & index ) const`

[ContributoriesTableModel::flags](#) Differents table flags.

#### Parameters

<i>index</i>	The cell who we want to know flags
--------------	------------------------------------

#### Returns

Flags

8.28.3.6 `QList< Contributory > Gui::Widgets::WdgModels::ContributoriesTableModel::getContributories ( )`

[ContributoriesTableModel::getContributories](#) Get all contributories of table.

#### Returns

The contributory list

8.28.3.7 `double Gui::Widgets::WdgModels::ContributoriesTableModel::getSumQuantity ( ) const`

[ContributoriesTableModel::getSumQuantity](#) Return the sum of the hours of all contriburoies added.

#### Returns

sum quantity

8.28.3.8 `QVariant Gui::Widgets::WdgModels::ContributoriesTableModel::headerData ( int section, Qt::Orientation orientation, int role ) const`

[ContributoriesTableModel::headerData](#) Obtains header title of table.

## Parameters

<i>section</i>	The number of column
<i>orientation</i>	The table orientation
<i>role</i>	

## Returns

The Title header of column

8.28.3.9 `void Gui::Widgets::WdgModels::ContributoriesTableModel::remove ( const int i )`

[ContributoriesTableModel::remove](#) Remove a line.

## Parameters

<i>i</i>	The number of line to remove
----------	------------------------------

8.28.3.10 `int Gui::Widgets::WdgModels::ContributoriesTableModel::rowCount ( const QModelIndex & ) const`

[ContributoriesTableModel::rowCount](#) Number of contributories row.

## Returns

The number of contributories

8.28.3.11 `bool Gui::Widgets::WdgModels::ContributoriesTableModel::setData ( const QModelIndex & index, const QVariant & value, int role = Qt::EditRole )`

[ContributoriesTableModel::setData](#) Change data of a cell.

## Parameters

<i>index</i>	The cell to change data
<i>value</i>	The new value
<i>role</i>	The role of cell

## Returns

True if we could edit

The documentation for this class was generated from the following files:


- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/widgetmodels/contributoriestablemodel.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/widgetmodels/contributoriestablemodel.cpp

## 8.29 Gui::Widgets::ContributoriesWidget Class Reference

The [ContributoriesWidget](#) class Widget of Contributories.

```
#include <contributorieswidget.h>
```

Inheritance diagram for Gui::Widgets::ContributoriesWidget:



## Public Slots

- void [add](#) (void)  
*[ContributoriesWidget::add](#) Add a new empty contributory.*
- void [remove](#) (void)  
*[ContributoriesWidget::remove](#) Remove the current contributory.*
- void [addProject](#) (QPair< [Project](#) \*, [Rate](#) > \*p=0)  
*[ContributoriesWidget::addProject](#) Add a Projet and it rate p*
- void [removeProject](#) (void)  
*[ContributoriesWidget::removeProject](#) Remove the current Project.*
- void [changeProject](#) (void)  
*[ContributoriesWidget::changeProject](#) Change the current Project.*
- void [editing](#) (void)  
*[ContributoriesWidget::editing](#) Remove the current Project in the combobox not used.*
- void [updateUi](#) (void)  
*[ContributoriesWidget::updateUi](#) Update the User Interface.*
- void [updatePrice](#) (void)  
*[ContributoriesWidget::updatePrice](#) Update total price.*

## Signals

- void [contributoryChanged](#) ()  
*[ContributoriesWidget::contributoryChanged](#) Signal that a contributory has changed.*

## Public Member Functions

- [ContributoriesWidget](#) (QSharedPointer< [Customer](#) > c, QWidget \*parent=0)  
*[ContributoriesWidget::ContributoriesWidget](#) Construct a [ContributoriesWidget](#).*
- [ContributoriesList](#) \* [getContributories](#) () const  
*[ContributoriesWidget::getContributories](#) Get contributories List.*
- int [count](#) ()  
*[ContributoriesWidget::count](#) Numbers of contributories.*
- void [add](#) ([ContributoriesList](#) &list)  
*[ContributoriesWidget::add](#) Add contributorieslist list in the model.*

### 8.29.1 Detailed Description

The [ContributoriesWidget](#) class Widget of Contributories.

### 8.29.2 Constructor & Destructor Documentation

- 8.29.2.1 [Gui::Widgets::ContributoriesWidget::ContributoriesWidget](#) ( QSharedPointer< [Customer](#) > c, QWidget \* parent = 0 ) [explicit]

[ContributoriesWidget::ContributoriesWidget](#) Construct a [ContributoriesWidget](#).

## Parameters

<i>c</i>	Customer
<i>parent</i>	Widget parent

### 8.29.3 Member Function Documentation

8.29.3.1 `void Gui::Widgets::ContributoriesWidget::add ( ContributoriesList & list )`

[ContributoriesWidget::add](#) Add contributorieslist *list* in the model.

## Parameters

<i>list</i>	the <b>ContributoriesList</b>
-------------	-------------------------------

8.29.3.2 `void Gui::Widgets::ContributoriesWidget::addProject ( QPair< Project *, Rate > * p = 0 ) [slot]`

[ContributoriesWidget::addProject](#) Add a Projet and it rate *p*

## Parameters

<i>p</i>	Rate linked to Project
----------	------------------------

8.29.3.3 `int Gui::Widgets::ContributoriesWidget::count ( )`

[ContributoriesWidget::count](#) Numbers of contributories.

## Returns

Numbers of contributories

8.29.3.4 `ContributoriesList * Gui::Widgets::ContributoriesWidget::getContributories ( ) const`

[ContributoriesWidget::getContributories](#) Get contributories List.

## Returns

ContributoriesList

The documentation for this class was generated from the following files:


- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/contributorieswidget.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/contributorieswidget.cpp

## 8.30 Models::Contributory Class Reference

The [Contributory](#) class.

```
#include <contributory.h>
```

Inheritance diagram for Models::Contributory:



## Public Member Functions

- [Contributory](#) ()  
*Contributory::Contributory* Construct a [Contributory](#).
- [Contributory](#) (int id)  
*Contributory::Contributory* Construct a [Contributory](#) and get data in database.
- [~Contributory](#) ()  
*Destroy an contributory object.*
- void [commit](#) ()  
*Contributory::commit* Update or insert a contributory to the database.
- void [hydrat](#) (int id)  
*Contributory::hydrat* Get data about the [Contributory](#) which is specified by the identify id
- void [remove](#) ()  
*Contributory::remove* Remove the current [Contributory](#).
- QVariantHash [getDataMap](#) ()  
*getDataMap* Get all data of model with a HashMap key/value
- [Project](#) \* [getProject](#) () const  
*Contributory::getProject* Return the project linked to this [Contributory](#).
- void [setProject](#) ([Project](#) \*id)  
*Contributory::setProject* Modify the identify id of the [Project](#) linked to this [Contributory](#).
- double [getNbHours](#) () const  
*getNbHours* Number of work hour of a contributory
- void [setNbHours](#) (double value)  
*setNbHours* Change nbHours
- QString [getDescription](#) () const  
*getDescription* Description of a contributory
- void [setDescription](#) (const QString &[getDescription](#))  
*setDescription* Change the contributory description
- bool [operator==](#) (const [Contributory](#) &c)  
*operator ==* define the operator "==" to compare two [Contributory](#)
- bool [operator!=](#) (const [Contributory](#) &c)  
*operator !=* define the operator "!=" to compare two [Contributory](#)
- QString [getLongDescription](#) () const
- void [setLongDescription](#) (const QString &getLongDescription)

## Additional Inherited Members

### 8.30.1 Detailed Description

The [Contributory](#) class.

Author

## 8.30.2 Constructor & Destructor Documentation

### 8.30.2.1 Models::Contributory::Contributory ( int *id* )

[Contributory::Contributory](#) Construct a [Contributory](#) and get data in database.



## Parameters

<i>id</i>	<a href="#">Contributory</a> 's id
-----------	------------------------------------

### 8.30.3 Member Function Documentation

#### 8.30.3.1 QVariantHash Models::Contributory::getDataMap ( ) [virtual]

getDataMap Get all data of model with a HashMap key/value

## Returns

Model's data

Implements [Models::IModel](#).

#### 8.30.3.2 QString Models::Contributory::getDescription ( ) const

getDescription Description of a contributory

## Returns

The description

#### 8.30.3.3 double Models::Contributory::getNbHours ( ) const

getNbHours Number of work hour of a contributory

## Returns

Then number of hours

#### 8.30.3.4 Project \* Models::Contributory::getProject ( ) const

[Contributory::getProject](#) Return the project linked to this [Contributory](#).

## Returns

[Project](#) linked to this [Contributory](#)

#### 8.30.3.5 void Models::Contributory::hydrat ( int *id* ) [virtual]

[Contributory::hydrat](#) Get data about the [Contributory](#) which is specified by the identify *id*

## Parameters

<i>id</i>	<a href="#">Contributory</a> identify
-----------	---------------------------------------

Implements [Models::IModel](#).

#### 8.30.3.6 bool Models::Contributory::operator!= ( const Contributory & c )

operator != define the operator "!=" to compare two [Contributory](#)

## Parameters

<i>c</i>	the <a href="#">Contributory</a> to compare with the current <a href="#">Contributory</a>
----------	-------------------------------------------------------------------------------------------

## Returns

true if the [Contributory](#) are different else false

8.30.3.7 `bool Models::Contributory::operator==( const Contributory & c )`

`operator ==` define the operator "==" to compare two [Contributory](#)

## Parameters

<i>c</i>	the <a href="#">Contributory</a> to compare with the current <a href="#">Contributory</a>
----------	-------------------------------------------------------------------------------------------

## Returns

true if the [Contributory](#) are equals else false

8.30.3.8 `void Models::Contributory::setDescription ( const QString & getDescription )`

`setDescription` Change the contributory description

## Parameters

<i>getDescription</i>	The new description
-----------------------	---------------------

8.30.3.9 `void Models::Contributory::setNbHours ( double value )`

`setNbHours` Change nbHours

## Parameters

<i>value</i>	The new value of nbHours
--------------	--------------------------

8.30.3.10 `void Models::Contributory::setProject ( Project * id )`

[Contributory::setProject](#) Modify the identify *id* of the [Project](#) linked to this [Contributory](#).

## Parameters

<i>id</i>	<a href="#">Project</a> Identify
-----------	----------------------------------

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/models/contributory.h
- /home/travis/build/FACT-Team/FactDev/src/models/contributory.cpp

## 8.31 Databases::ContributoryDatabase Class Reference

The [ContributoryDatabase](#) class Contributory (or Quote) table database.

```
#include <contributorydatabase.h>
```

Inheritance diagram for Databases::ContributoryDatabase:



## Public Member Functions

- [Models::Contributory](#) \* [getContributory](#) (const int idContributory)  
*ContributoryDatabase::getCustomer* get informations about the Contributory identified by pld
- [Models::ContributoriesList](#) [getContributoriesByBilling](#) (const int billingId)  
*ContributoryDatabase::getContributoriesByBilling* get informations about the Contributory identified by Billing
- int [addContributory](#) (const [Models::Contributory](#) &)  
*ContributoryDatabase::addContributory* Add the Contributory pContributory to the database.
- void [updateContributory](#) (const [Models::Contributory](#) &)  
*ContributoryDatabase::updateCustomer* Update informations about the Contributory pCustomer
- void [removeContributory](#) (const int pld)  
*ContributoryDatabase::removeCustomer* Remove the Contributory with the id pld
- [Models::Contributory](#) \* [getContributory](#) (QString &q)  
*getContributory* Obtain a contributory without new query
- [Models::ContributoriesList](#) [getContributoriesByBillingAndProject](#) (const int billingId, const int projectId)  
*getContributory* Get contributories list by project and billing

## Static Public Member Functions

- static [ContributoryDatabase](#) \* [instance](#) () throw (DbException\*)  
*ContributoryDatabase::getInstance* Return an instance of [ContributoryDatabase](#)

## Additional Inherited Members

### 8.31.1 Detailed Description

The [ContributoryDatabase](#) class Contributory (or Quote) table database.

Author

See Also

[Database](#)  
[Contributory/Quote](#)

### 8.31.2 Member Function Documentation

8.31.2.1 int [Databases::ContributoryDatabase::addContributory](#) ( const [Models::Contributory](#) & pContributory )

[ContributoryDatabase::addContributory](#) Add the Contributory pContributory to the database.

Returns

Contributory id

8.31.2.2 **Models::ContributoriesList** Databases::ContributoryDatabase::getContributoriesByBilling ( const int *billingId* )

[ContributoryDatabase::getContributoriesByBilling](#) get informations about the Contributory identified by *Billing*

## Parameters

<i>idBilling</i>	Contributory id
------------------	-----------------

## Returns

the Contributory

### 8.31.2.3 Models::ContributoriesList Databases::ContributoryDatabase::getContributoriesByBillingAndProject ( const int *billingId*, const int *projectId* )

getContributory Get contributories list by project and billing

## Parameters

<i>billingId</i>	
<i>projectId</i>	

## Returns

The contributories list by project and billing

### 8.31.2.4 Models::Contributory \* Databases::ContributoryDatabase::getContributory ( const int *idContributory* )

ContributoryDatabase::getCustomer get informations about the Contributory identified by *pId*

## Parameters

<i>idContributory</i>	Contributory id
-----------------------	-----------------

## Returns

the Contributory

### 8.31.2.5 Models::Contributory \* Databases::ContributoryDatabase::getContributory ( QSqlQuery & *q* )

getContributory Obtain a contributory without new query

## Parameters

<i>q</i>	The query to use
----------	------------------

## Returns

The contributory linked to *q*

### 8.31.2.6 ContributoryDatabase \* Databases::ContributoryDatabase::instance ( ) throw DbException \* ) [static]

ContributoryDatabase::getInstance Return an instance of [ContributoryDatabase](#)

## See Also

DbException

## Returns

Instance of [ContributoryDatabase](#)

8.31.2.7 void Databases::ContributoryDatabase::removeContributory ( const int *pld* )

ContributoryDatabase::removeCustomer Remove the Contributory with the id *pld*

## Parameters

<i>pld</i>	Contributory id
------------	-----------------

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/database/contributorydatabase.h
- /home/travis/build/FACT-Team/FactDev/src/database/contributorydatabase.cpp

## 8.32 ContributoryListTest Class Reference

Inheritance diagram for ContributoryListTest:




The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/tests/models/contributorylisttest.h
- /home/travis/build/FACT-Team/FactDev/tests/models/contributorylisttest.cpp

## 8.33 ContributoryModelTest Class Reference

Inheritance diagram for ContributoryModelTest:




The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/tests/models/contributorymodeltest.h
- /home/travis/build/FACT-Team/FactDev/tests/models/contributorymodeltest.cpp

## 8.34 CounterContext Class Reference

Inheritance diagram for CounterContext:



## Public Member Functions

- **CounterContext** (const QVariantHash &map)
- virtual bool [canEval](#) (const QString &key) const
- virtual QString [eval](#) (const QString &key, const QString &\_template, [Mustache::Renderer](#) \*renderer)
- virtual QString [stringValue](#) (const QString &key) const
- **CounterContext** (const QVariantHash &map)
- virtual bool [canEval](#) (const QString &key) const
- virtual QString [eval](#) (const QString &key, const QString &\_template, [Mustache::Renderer](#) \*renderer)
- virtual QString [stringValue](#) (const QString &key) const

## Public Attributes

- int **counter**

## Additional Inherited Members

### 8.34.1 Member Function Documentation

8.34.1.1 virtual bool CounterContext::canEval ( const QString & key ) const [inline], [virtual]

Returns true if [eval\(\)](#) should be used to render section tags using `key`. If [canEval\(\)](#) returns true for a key, the renderer will pass the literal, unrendered block of text for the section to [eval\(\)](#) and replace the section with the result.

[canEval\(\)](#) and [eval\(\)](#) are equivalents for callable objects (eg. lambdas) in other Mustache implementations.

The default implementation always returns false.

Reimplemented from [Mustache::QtVariantContext](#).

8.34.1.2 virtual bool CounterContext::canEval ( const QString & key ) const [inline], [virtual]

Returns true if [eval\(\)](#) should be used to render section tags using `key`. If [canEval\(\)](#) returns true for a key, the renderer will pass the literal, unrendered block of text for the section to [eval\(\)](#) and replace the section with the result.

[canEval\(\)](#) and [eval\(\)](#) are equivalents for callable objects (eg. lambdas) in other Mustache implementations.

The default implementation always returns false.

Reimplemented from [Mustache::QtVariantContext](#).

8.34.1.3 virtual QString CounterContext::eval ( const QString & key, const QString & \_template, [Mustache::Renderer](#) \* *renderer* ) [inline], [virtual]

Callback used to render a template section with the given `key`. `renderer` will substitute the original section tag with the result of [eval\(\)](#).

The default implementation returns an empty string.

Reimplemented from [Mustache::QtVariantContext](#).

8.34.1.4 virtual QString CounterContext::eval ( const QString & key, const QString & \_template, [Mustache::Renderer](#) \* *renderer* ) [inline], [virtual]

Callback used to render a template section with the given `key`. `renderer` will substitute the original section tag with the result of [eval\(\)](#).

The default implementation returns an empty string.

Reimplemented from [Mustache::QtVariantContext](#).



8.34.1.5 virtual QString CounterContext::stringValue ( const QString & key ) const [inline], [virtual]

Returns a string representation of the value for `key` in the current context. This is used to replace a Mustache value tag.

Reimplemented from [Mustache::QtVariantContext](#).

8.34.1.6 virtual QString CounterContext::stringValue ( const QString & key ) const [inline], [virtual]

Returns a string representation of the value for `key` in the current context. This is used to replace a Mustache value tag.

Reimplemented from [Mustache::QtVariantContext](#).

The documentation for this class was generated from the following file:


- /home/travis/build/FACT-Team/FactDev/src/libs/qt-mustache/tests/test\_mustache.cpp

## 8.35 Models::Customer Class Reference

The [Customer](#) class [Customer](#).

```
#include <customer.h>
```

Inheritance diagram for Models::Customer:



### Public Member Functions

- [Customer](#) ()  
*Customer::Customer* Construct a [Customer](#).
- [Customer](#) (int id)  
*Customer::Customer* Construct a [Customer](#) who is specified by id
- void [commit](#) ()  
*Customer::commit* Update customer data on the database.
- void [hydrat](#) (int id)  
*Customer::hydrat* Insert into database informations related to the [Customer](#) who is specified by id
- void [remove](#) ()  
*Customer::remove* Remove the current customer.
- QVariantHash [getDataMap](#) ()  
*getDataMap* Get all data of model with a HashMap key/value
- QString [getPath](#) () const  
*Customer::getPath* Return the path of the workspace for the current [Customer](#).
- QString [getNameFolder](#) () const  
*Customer::getNameFolder* Return the name of the current [Customer](#)'s folder in the workspace.
- double [getTurnover](#) () const  
*Customer::getTurnover* Return the turnover of the customer money that customer pay, revenue sales.
- void [setTurnover](#) (const double &turnover)  
*Customer::setTurnover* Replace the current turnover by turnover

- bool `operator==` (const [Customer](#) &c)  
*[Customer::operator ==](#) Re-define the operator "==" to compare if the current customer is the same to the other [Customer](#) c Return TRUE if both customers are the same, else FALSE.*
- bool `operator!=` (const [Customer](#) &c)  
*[Customer::operator !=](#) Re-define the operator "!=" to compare if the current customer is different to the other [Customer](#) c Return TRUE if both customers are different, else FALSE.*
- double `turnoverCompute` ()  
*[Customer::turnoverCompute](#) calculates the customer turnover.*

## Additional Inherited Members

### 8.35.1 Detailed Description

The [Customer](#) class [Customer](#).

#### Author

Antoine de Roquemaurel  
 Florent Berbie

### 8.35.2 Constructor & Destructor Documentation

#### 8.35.2.1 `Models::Customer::Customer ( int id )`

[Customer::Customer](#) Construct a [Customer](#) who is specified by *id*

#### Parameters

<i>id</i>	<a href="#">Customer</a> identify
-----------	-----------------------------------

### 8.35.3 Member Function Documentation

#### 8.35.3.1 `QVariantHash Models::Customer::getDataMap ( ) [virtual]`

`getDataMap` Get all data of model with a HashMap key/value

#### Returns

Model's data

Implements [Models::IModel](#).

#### 8.35.3.2 `QString Models::Customer::getNameFolder ( ) const`

[Customer::getNameFolder](#) Return the name of the current [Customer](#)'s folder in the workspace.

#### Returns

name of the [Customer](#)'s folder

#### 8.35.3.3 `QString Models::Customer::getPath ( ) const`

[Customer::getPath](#) Return the path of the workspace for the current [Customer](#).

## Returns

workspace path

## 8.35.3.4 double Models::Customer::getTurnover ( ) const

[Customer::getTurnover](#) Return the turnover of the customer money that customer pay, revenue sales.

## Returns

turnover

8.35.3.5 void Models::Customer::hydrat ( int *id* ) [virtual][Customer::hydrat](#) Insert into database informations related to the [Customer](#) who is specified by *id*

## Parameters

<i>id</i>	<a href="#">Customer</a> identify
-----------	-----------------------------------

Implements [Models::IModel](#).8.35.3.6 bool Models::Customer::operator!= ( const **Customer** & *c* )[Customer::operator ==](#) Re-define the operator "!=" to compare if the current customer is differnt to the other [Customer](#) *c* Return TRUE if both customers are different, else FALSE.

## Parameters

<i>c</i>	<a href="#">Customer</a> to compare
----------	-------------------------------------

## Returns

boolean

8.35.3.7 bool Models::Customer::operator== ( const **Customer** & *c* )[Customer::operator ==](#) Re-define the operator "==" to compare if the current customer is the same to the other [Customer](#) *c* Return TRUE if both customers are the same, else FALSE.

## Parameters

<i>c</i>	<a href="#">Customer</a> to compare
----------	-------------------------------------

## Returns

boolean

8.35.3.8 void Models::Customer::setTurnover ( const double & *turnover* )[Customer::setTurnover](#) Replace the current turnover by *turnover*

## Parameters

<i>turnover</i>	new revenue sales of a customer
-----------------	---------------------------------

## 8.35.3.9 double Models::Customer::turnoverCompute ( )

[Customer::turnoverCompute](#) calculates the customer turnover.

## Returns

double turnover

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/models/customer.h
- /home/travis/build/FACT-Team/FactDev/src/models/customer.cpp

## 8.36 Gui::Widgets::CustomerContextualMenu Class Reference

Display contextual menu on a customer.

```
#include <customercontextualmenu.h>
```

Inheritance diagram for Gui::Widgets::CustomerContextualMenu:



## Public Member Functions

- [CustomerContextualMenu](#) (QWidget \*w=0)  
[CustomerContextualMenu::CustomerContextualMenu](#) Construct a new contextual menu.
- [~CustomerContextualMenu](#) ()  
[CustomerContextualMenu::Destruct](#) the contextual menu.

## 8.36.1 Detailed Description

Display contextual menu on a customer.

## Author

Antoine de Roquemaurel

## 8.36.2 Constructor &amp; Destructor Documentation

## 8.36.2.1 Gui::Widgets::CustomerContextualMenu::CustomerContextualMenu ( QWidget \* w = 0 )

[CustomerContextualMenu::CustomerContextualMenu](#) Construct a new contextual menu.

## Parameters

<i>w</i>	Parent
----------	--------

The documentation for this class was generated from the following files:


- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/customercontextualmenu.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/customercontextualmenu.cpp

## 8.37 Databases::CustomerDatabase Class Reference

The **CustomerDatabase** class Customer table database.

```
#include <customerdatabase.h>
```

Inheritance diagram for Databases::CustomerDatabase:



### Public Member Functions

- **WdgModels::CustomersTableModel \* getCustomersTable** (QString filter="") throw (DbException\*)  
*CustomerDatabase::getCustomersTable* Return an item model of customers for QTableView.
- **QStandardItemModel \* getTree** (QString filter="") throw (DbException\*)  
*CustomerDatabase::getTree* Return an item model of customers for QTree.
- **QSharedPointer< Models::Customer > getCustomer** (const int pld)  
*CustomerDatabase::getCustomer* get informations about the customer identified by pld
- **int addCustomer** (const Models::Customer &)  
*CustomerDatabase::addCustomer* Add the customer pCustomer to the database.
- **void updateCustomer** (const Models::Customer &)  
*CustomerDatabase::updateCustomer* Update informations about the customer pCustomer
- **void removeCustomer** (const int pld)  
*CustomerDatabase::removeCustomer* Remove the customer with the id pld
- **int getNbCustomers** ()  
*CustomerDatabase::getNbCustomers* Return the number of customers existing.
- **QStandardItem \* getItemRoot** ()  
*CustomerDatabase::getItemRoot* Return the first item for the QStandardItemModel.
- **QStandardItem \* getItemCustomer** (QString q1)  
*CustomerDatabase::getItemCustomer* Return the customer item for the QStandardItemModel.
- **QStandardItem \* getItemProject** (QString q2)  
*CustomerDatabase::getItemProject* Return the project item for the QStandardItemModel.
- **QStandardItem \* getItemBillQuote** (QString q3)  
*CustomerDatabase::getItemCustomer* Return the bill/quote item for the QStandardItemModel.
- **QSharedPointer< Models::Customer > getCustomer** (QString q)  
*CustomerDatabase::getCustomer* Add the element of the q request and return their.
- **void updateCustomer** (QString q, Models::Customer &pCustomer)  
*CustomerDatabase::updateCustomer* Update customer data according to the request q

## Static Public Member Functions

- static [CustomerDatabase](#) \* [instance](#) () throw (DbException\*)  
[CustomerDatabase::instance](#) Return an instance of [CustomerDatabase](#)

## Additional Inherited Members

### 8.37.1 Detailed Description

The [CustomerDatabase](#) class Customer table database.

#### Author

Antoine de Roquemaurel  
 Manantsoa Razanajatovo  
 Florent Berbie

#### See Also

[Database](#)  
[Customer](#)

### 8.37.2 Member Function Documentation

8.37.2.1 int Databases::CustomerDatabase::addCustomer ( const [Models::Customer](#) & *pCustomer* )

[CustomerDatabase::addCustomer](#) Add the customer *pCustomer* to the database.

#### Returns

customer id

8.37.2.2 [QSharedPointer](#)< [Models::Customer](#) > Databases::CustomerDatabase::getCustomer ( const int *pld* )

[CustomerDatabase::getCustomer](#) get informations about the customer identified by *pld*

#### Parameters

<i>pld</i>	customer id
------------	-------------

#### Returns

the Customer

8.37.2.3 [QSharedPointer](#)< [Models::Customer](#) > Databases::CustomerDatabase::getCustomer ( [QSqlQuery](#) & *q* )

[CustomerDatabase::getCustomer](#) Add the element of the *q* request and return their.

#### Parameters

<i>q</i>	SQL request
----------	-------------

#### Returns

a customer formed according to [QSharedPointer](#)

8.37.2.4 `WdgModels::CustomersTableModel *` `Databases::CustomerDatabase::getCustomersTable ( QString filter = " " )` `throw DbException *`

[CustomerDatabase::getCustomersTable](#) Return an item model of customers for QTableView.

## Parameters

<i>filter</i>	Select only customers who are specified by <i>filter</i>
---------------	----------------------------------------------------------

## Exceptions

<i>DbException</i>	
--------------------	--

## Returns

QStandardItemModel an item model for QTableView

#### 8.37.2.5 QStandardItem \* Databases::CustomerDatabase::getItemBillQuote ( QSqlQuery q3 )

[CustomerDatabase::getItemCustomer](#) Return the bill/quote item for the QStandardItemModel.

## Parameters

<i>q3</i>	the first row of the sql query for bills/quotes
-----------	-------------------------------------------------

## Returns

QStandardItem an item for QTree (level/depth 3)

#### 8.37.2.6 QStandardItem \* Databases::CustomerDatabase::getItemCustomer ( QSqlQuery q1 )

[CustomerDatabase::getItemCustomer](#) Return the customer item for the QStandardItemModel.

## Parameters

<i>q1</i>	the row of the sql query for customers
-----------	----------------------------------------

## Returns

QStandardItem an item for QTree (level/depth 1)

#### 8.37.2.7 QStandardItem \* Databases::CustomerDatabase::getItemProject ( QSqlQuery q2 )

[CustomerDatabase::getItemProject](#) Return the project item for the QStandardItemModel.

## Parameters

<i>q2</i>	the row of the sql query for projects
-----------	---------------------------------------

## Returns

QStandardItem an item for QTree (level/depth 2)

#### 8.37.2.8 QStandardItem \* Databases::CustomerDatabase::getItemRoot ( )

[CustomerDatabase::getItemRoot](#) Return the first item for the QStandardItemModel.

## Returns

QStandardItem an item for QTree (level/depth 0)



8.37.2.9 `int Databases::CustomerDatabase::getNbCustomers ( )`

[CustomerDatabase::getNbCustomers](#) Return the number of customers existing.

Returns

number of customers

8.37.2.10 `QStandardItemModel * Databases::CustomerDatabase::getTree ( QString filter = " " ) throw DbException *`

[CustomerDatabase::getTree](#) Return an item model of customers for QTree.

Parameters

<i>filter</i>	Select only customers who are specified by <i>filter</i>
---------------	----------------------------------------------------------

Exceptions

<i>DbException</i>	
--------------------	--

Returns

QStandardItemModel an item model for QTreeView

8.37.2.11 `CustomerDatabase * Databases::CustomerDatabase::instance ( ) throw DbException *` [static]

[CustomerDatabase::instance](#) Return an instance of [CustomerDatabase](#)

See Also

DbException

Returns

Instance of [CustomerDatabase](#)

8.37.2.12 `void Databases::CustomerDatabase::removeCustomer ( const int pId )`

[CustomerDatabase::removeCustomer](#) Remove the customer with the id *pId*

Parameters

<i>pId</i>	customer id
------------	-------------

8.37.2.13 `void Databases::CustomerDatabase::updateCustomer ( QSqlQuery & q, Customer & pCustomer )`

[CustomerDatabase::updateCustomer](#) Update customer data according to the request *q*

Parameters


<i>q</i>	SQL request
----------	-------------

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/database/customerdatabase.h
- /home/travis/build/FACT-Team/FactDev/src/database/customerdatabase.cpp

## 8.38 CustomerDatabaseTest Class Reference

Inheritance diagram for CustomerDatabaseTest:



The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/tests/database/customerdatabasetest.h
- /home/travis/build/FACT-Team/FactDev/tests/database/customerdatabasetest.cpp

## 8.39 Gui::Widgets::CustomerDataWidget Class Reference

Class for display info of a customer.

```
#include <customerdatawidget.h>
```

Inheritance diagram for Gui::Widgets::CustomerDataWidget:



### Public Member Functions

- [CustomerDataWidget](#) (QWidget \*parent=0)  
*CustomerDataWidget::CustomerDataWidget* Construct a [CustomerDataWidget](#).
- void [printUserData](#) ()  
*CustomerDataWidget::printUserData* Print Data of current user.
- void [printInformations](#) (int id)  
*CustomerDataWidget::printInformations* Print Data of customer id.

### 8.39.1 Detailed Description

Class for display info of a customer.

Author

### 8.39.2 Constructor & Destructor Documentation

8.39.2.1 [Gui::Widgets::CustomerDataWidget::CustomerDataWidget](#) ( [QWidget](#) \* *parent* = 0 ) [explicit]

[CustomerDataWidget::CustomerDataWidget](#) Construct a [CustomerDataWidget](#).

## Parameters

<i>parent</i>	Widget parent
---------------	---------------

## 8.39.3 Member Function Documentation

8.39.3.1 void Gui::Widgets::CustomerDataWidget::printInformations ( int *id* )

[CustomerDataWidget::printInformations](#) Print Data of customer id.

## Parameters


<i>id</i>	of customer to print
-----------	----------------------

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/customerdatawidget.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/customerdatawidget.cpp

## 8.40 CustomerModelTest Class Reference

Inheritance diagram for CustomerModelTest:



The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/tests/models/customermodeltest.h
- /home/travis/build/FACT-Team/FactDev/tests/models/customermodeltest.cpp

## 8.41 Gui::Widgets::WdgModels::CustomersTableModel Class Reference

The [CustomersTableModel](#) class for a customer table.

```
#include <customerstablemodel.h>
```

Inheritance diagram for Gui::Widgets::WdgModels::CustomersTableModel:



## Public Member Functions

- [CustomersTableModel](#) (QObject \*parent=0)  
[CustomersTableModel::CustomersTableModel](#) Construct a [CustomersTableModel](#).
- int [rowCount](#) (const QModelIndex &) const

- CustomersTableModel::rowCount* Number of customers row.
- int [columnCount](#) (const QModelIndex &) const  
*CustomersTableModel::columnCount* Number of column of a customer.
- QVariant [data](#) (const QModelIndex &index, int role=Qt::DisplayRole) const  
*CustomersTableModel::data* Obtains data of a specify cell.
- QVariant [headerData](#) (int section, Qt::Orientation orientation, int role=Qt::DisplayRole) const  
*CustomersTableModel::headerData* Obtains header title of table.
- bool [setData](#) (const QModelIndex &index, const QVariant &value, int role=Qt::EditRole)  
*CustomersTableModel::setData* Change data of a cell.
- void [append](#) (const Customer &customer)  
*CustomersTableModel::append* Add a new line in table.
- void [remove](#) (const int i)  
*CustomersTableModel::remove* Remove a line.
- Qt::ItemFlags [flags](#) (const QModelIndex &index) const  
*CustomersTableModel::flags* Differents table flags.
- int [count](#) ()  
*CustomersTableModel::count* Number of customers in table.
- QList< Customer > [getCustomers](#) () const  
*CustomersTableModel::getCustomers* Return the list of customers.

### 8.41.1 Detailed Description

The [CustomersTableModel](#) class for a customer table.

#### Author

Florent Berbie

#### See Also

[Customer](#)

### 8.41.2 Constructor & Destructor Documentation

#### 8.41.2.1 Gui::Widgets::WdgModels::CustomersTableModel::CustomersTableModel ( QObject \* *parent* = 0 )

[CustomersTableModel::CustomersTableModel](#) Construct a [CustomersTableModel](#).

#### Parameters

<i>parent</i>	Parent widget
---------------	---------------

### 8.41.3 Member Function Documentation

#### 8.41.3.1 void Gui::Widgets::WdgModels::CustomersTableModel::append ( const Customer & *customer* )

[CustomersTableModel::append](#) Add a new line in table.

#### Parameters

<i>Customer</i>	The new customer
-----------------	------------------

8.41.3.2 `int Gui::Widgets::WdgModels::CustomersTableModel::columnCount ( const QModelIndex & ) const`

[CustomersTableModel::columnCount](#) Number of column of a customer.

Returns

The number of column

8.41.3.3 `int Gui::Widgets::WdgModels::CustomersTableModel::count ( )`

[CustomersTableModel::count](#) Number of customers in table.

Returns

The number of customers

8.41.3.4 `QVariant Gui::Widgets::WdgModels::CustomersTableModel::data ( const QModelIndex & index, int role = Qt::DisplayRole ) const`

[CustomersTableModel::data](#) Obtains data of a specify cell.

Parameters

<i>index</i>	The cell who we want data
<i>role</i>	The role of set

Returns

The data of cell

8.41.3.5 `Qt::ItemFlags Gui::Widgets::WdgModels::CustomersTableModel::flags ( const QModelIndex & index ) const`

[CustomersTableModel::flags](#) Differents table flags.

Parameters

<i>index</i>	The cell who we want to know flags
--------------	------------------------------------

Returns

Flags

8.41.3.6 `QList< Customer > Gui::Widgets::WdgModels::CustomersTableModel::getCustomers ( ) const`

[CustomersTableModel::getCustomers](#) Return the list of customers.

Returns

list of Customers

8.41.3.7 `QVariant Gui::Widgets::WdgModels::CustomersTableModel::headerData ( int section, Qt::Orientation orientation, int role = Qt::DisplayRole ) const`

[CustomersTableModel::headerData](#) Obtains header title of table.

## Parameters

<i>section</i>	The number of column
<i>orientation</i>	The table orientation
<i>role</i>	

## Returns

The Title header of column

8.41.3.8 void Gui::Widgets::WdgModels::CustomersTableModel::remove ( const int *i* )

[CustomersTableModel::remove](#) Remove a line.

## Parameters

<i>i</i>	The number of line to remove
----------	------------------------------

8.41.3.9 int Gui::Widgets::WdgModels::CustomersTableModel::rowCount ( const QModelIndex & ) const

[CustomersTableModel::rowCount](#) Number of customers row.

## Returns

The number of customers

8.41.3.10 bool Gui::Widgets::WdgModels::CustomersTableModel::setData ( const QModelIndex & *index*, const QVariant & *value*, int *role* = Qt::EditRole )

[CustomersTableModel::setData](#) Change data of a cell.

## Parameters

<i>index</i>	The cell to change data
<i>value</i>	The new value
<i>role</i>	The role of cell

## Returns

True if we could edit

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/widgetmodels/customerstablemodel.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/widgetmodels/customerstablemodel.cpp

## 8.42 Databases::Database Class Reference

The [Database](#) class Master class for all database access.

```
#include <database.h>
```

Inheritance diagram for Databases::Database:



## Public Member Functions

- QString [lastError](#) (const QSqlQuery &q) const  
*Database::lastError* Return an error message on the last error occurred during the SQL request q
- void [testCases](#) ()  
*Database::testCases* Realise a test cases.
- void [cleanDatabase](#) ()  
*Database::viderDatabase* Clear database.
- void [executeFile](#) (QString pName)  
*Database::executerFichier* Exeute a specified file named pName
- void [openTransaction](#) ()  
*Database::openTransaction* Open new transaction.
- void [closeTransaction](#) ()  
*Database::closeTransaction* Close current transaction.
- void [close](#) ()  
*Database::close* Close database access.
- void [open](#) ()  
*Database::open* Open database.
- [~Database](#) ()  
*Database::~~Database* Suppression object, and close database access.
- void [setDatabase](#) (QSqlDatabase sql)  
*Database::setDatabase* Set database.
- void [createDatabase](#) ()  
*Database::createDatabase* Create a new database.
- void [updateBillingNumber](#) ()  
*Database::updateBillingNumber* Update the billing number.

## Static Public Member Functions

- static [Database \\* instance](#) () throw (DbException\*)  
*Database::getInstance* Return an instance of [Database](#).

## Protected Member Functions

- [Database](#) () throw (DbException\*)  
*Database::Database* [Database](#) is a singleton.
- QVariant [value](#) (const QSqlQuery &q, const QString &champ) const  
*Database::valeur* Value of database field.

## Protected Attributes

- QSettings \* [\\_settings](#)  
*settings*
- QSqlDatabase [mDatabase](#)  
*contains Database*
- QList< [Database \\* > \\_instances](#)  
*List of instances.*

## Static Protected Attributes

- static [Database](#) \* [\\_instance](#) = 0  
*Instance.*
- static bool [\\_dbInstance](#) = 0  
*an instance of db is open*
- static bool [isOpen](#) = false  
*[Database](#) is open.*

### 8.42.1 Detailed Description

The [Database](#) class Master class for all database access.

Author

Antoine de Roquemaurel

### 8.42.2 Member Function Documentation

#### 8.42.2.1 void Databases::Database::executeFile ( QString *pName* )

Database::executerFichier Exeute a specified file named *pName*

Parameters

<i>pNom</i>	File name
-------------	-----------

#### 8.42.2.2 Database \* Databases::Database::instance ( ) throw DbException \*) [static]

Database::getInstance Return an instance of [Database](#).

Returns

Instance of [Database](#)

#### 8.42.2.3 QString Databases::Database::lastError ( const QSqlQuery & *q* ) const [inline]

[Database::lastError](#) Return an error message on the last error ocured during the SQL request *q*

Parameters

<i>q</i>	SQL request
----------	-------------

Returns

an error message

#### 8.42.2.4 void Databases::Database::setDatabase ( QSqlDatabase *sql* )

[Database::setDatabase](#) Set database.



## Parameters

<i>sql</i>	The new database
------------	------------------

8.42.2.5 QVariant Databases::Database::value ( const QSqlQuery & *q*, const QString & *champ* ) const [protected]

Database::valeur Value of database field.

## Parameters

<i>q</i>	Query
<i>champ</i>	Field

## Returns

The value

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/database/database.h
- /home/travis/build/FACT-Team/FactDev/src/database/database.cpp

## 8.43 Gui::Widgets::DatabaseSettingsWidget Class Reference

The [DatabaseSettingsWidget](#) class Windows of database settings.

```
#include <databasesettingswidget.h>
```

Inheritance diagram for Gui::Widgets::DatabaseSettingsWidget:



## Public Slots

- bool [isValid](#) ()  
*DatabaseSettingsWidget::isValid* Return TRUE if all fields are correctly inputed else FALSE.
- void [checkRepeatPassword](#) (QString text)  
*DatabaseSettingsWidget::checkRepeatLogin* Check if the second login field is the same than the first.
- void [userInterfaceChanged](#) ()  
*DatabaseSettingsWidget::userInterfaceChanged* User interface has changed.

## Signals

- void [textfieldChanged](#) ()  
*DatabaseSettingsWidget::textfieldChanged* Signal which indicates if a fieldtext has changed.

## Public Member Functions

- [DatabaseSettingsWidget](#) (QWidget \*parent=0)  
[DatabaseSettingsWidget::DatabaseSettingsWidget](#) Construct a [DatabaseSettingsWidget](#).
- void [fillFields](#) ()  
[DatabaseSettingsWidget::fillFields](#) Complete fields with a default value for field Database name, Username, IP address and port.
- QString [getDatabaseName](#) ()  
[DatabaseSettingsWidget::getDatabaseName](#) Return the database name.
- QString [getLogin](#) ()  
[DatabaseSettingsWidget::getLogin](#) Return the login of the user.
- QString [getPassword](#) ()  
[DatabaseSettingsWidget::getPassword](#) Return the password of the user.
- QString [getDomainNameOrIP](#) ()  
[DatabaseSettingsWidget::getDomainNameOrIP](#) Return the domain name or IP address on the machine where is the database.
- QString [getPort](#) ()  
[DatabaseSettingsWidget::getPort](#) Return the port of the database.

### 8.43.1 Detailed Description

The [DatabaseSettingsWidget](#) class Windows of database settings.

Author

### 8.43.2 Constructor & Destructor Documentation

8.43.2.1 `Gui::Widgets::DatabaseSettingsWidget::DatabaseSettingsWidget ( QWidget * parent = 0 )` [explicit]

[DatabaseSettingsWidget::DatabaseSettingsWidget](#) Construct a [DatabaseSettingsWidget](#).

Parameters

<i>parent</i>	Parent widget of this windows
---------------	-------------------------------

### 8.43.3 Member Function Documentation

8.43.3.1 `QString Gui::Widgets::DatabaseSettingsWidget::getDatabaseName ( )`

[DatabaseSettingsWidget::getDatabaseName](#) Return the database name.

Returns

Database name

8.43.3.2 `QString Gui::Widgets::DatabaseSettingsWidget::getDomainNameOrIP ( )`

[DatabaseSettingsWidget::getDomainNameOrIP](#) Return the domain name or IP address on the machine where is the database.

Returns

Domain name or IP address

## 8.43.3.3 QString Gui::Widgets::DatabaseSettingsWidget::getLogin ( )

[DatabaseSettingsWidget::getLogin](#) Return the login of the user.

## Returns

Login of the user

## 8.43.3.4 QString Gui::Widgets::DatabaseSettingsWidget::getPassword ( )

[DatabaseSettingsWidget::getPassword](#) Return the password of the user.

## Returns

User password

## 8.43.3.5 QString Gui::Widgets::DatabaseSettingsWidget::getPort ( )

[DatabaseSettingsWidget::getPort](#) Return the port of the database.

## Returns

Database port

## 8.43.3.6 bool Gui::Widgets::DatabaseSettingsWidget::isValid ( ) [slot]

[DatabaseSettingsWidget::isValid](#) Return TRUE if all fields are correctly inputed else FALSE.

## Returns

boolean

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/databasesettingswidget.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/databasesettingswidget.cpp

## 8.44 Exceptions::DbException Class Reference

The [DbException](#) class for database exception : queries, db file, ...

```
#include <dbexception.h>
```

Inheritance diagram for Exceptions::DbException:



## Public Member Functions

- [DbException](#) (const QString fct, const QString fctName, const QString logError, float errorCode)  
*DbException::DbException. Construct a DbException.*
- virtual [~DbException](#) () throw ()  
*~DbException*
- void [popupMessage](#) (QWidget \*parent)  
*DbException::popupMessage. Display a popup message with the message error.*

### 8.44.1 Detailed Description

The [DbException](#) class for database exception : queries, db file, ...

#### Author

Antoine de Roquemaurel

### 8.44.2 Constructor & Destructor Documentation

- 8.44.2.1 [Exceptions::DbException::DbException](#) ( const QString *fct*, const QString *fctName*, const QString *logError*, float *errorCode* )

[DbException::DbException](#). Construct a [DbException](#).

#### Parameters

<i>userError</i>	ClassName of error
<i>fctName</i>	Function name
<i>logError</i>	Message error
<i>errorCode</i>	Code of error

### 8.44.3 Member Function Documentation

- 8.44.3.1 void [Exceptions::DbException::popupMessage](#) ( QWidget \* *parent* )

[DbException::popupMessage](#). Display a popup message with the message error.

#### Parameters

<i>parent</i>	
---------------	--

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/exceptions/dbexception.h
- /home/travis/build/FACT-Team/FactDev/src/exceptions/dbexception.cpp

## 8.45 Gui::Dialogs::DialogAddCustomer Class Reference

The [DialogAddCustomer](#) class Window to add or modify a Customer.

```
#include <dialogaddcustomer.h>
```

Inheritance diagram for Gui::Dialogs::DialogAddCustomer:



## Public Slots

- void [checkFields](#) ()  
*DialogAddCustomer::checkFields* Check if fields are valid.

## Public Member Functions

- [DialogAddCustomer](#) (int id=0, QWidget \*parent=0)  
*DialogAddCustomer::DialogAddCustomer* Construct a window to add/modify a Customer.
- void [fillFields](#) ()  
*DialogAddCustomer::fillFields* If the Customer exists, fill line edits with the data of the current Customer.
- void [accept](#) ()  
*DialogAddCustomer::accept* Valid data inputed by user and add these data in Database.
- void [reject](#) ()  
*DialogAddCustomer::reject* Cancel the operation and close the windows.

### 8.45.1 Detailed Description

The [DialogAddCustomer](#) class Window to add or modify a Customer.

Author

### 8.45.2 Constructor & Destructor Documentation

8.45.2.1 [Gui::Dialogs::DialogAddCustomer::DialogAddCustomer](#) ( int *id* = 0, QWidget \* *parent* = 0 ) [explicit]

[DialogAddCustomer::DialogAddCustomer](#) Construct a window to add/modify a Customer.

Parameters

<i>id</i>	Customer id
<i>parent</i>	QWidget parent

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/dialogs/dialogaddcustomer.h
- /home/travis/build/FACT-Team/FactDev/src/gui/dialogs/dialogaddcustomer.cpp

## 8.46 Utils::Directories Class Reference

### Static Public Member Functions

- static QString [makeDirectory](#) (QDir &directory, const QString path, const QString folder) throw (Exceptions::FileException\*)  
*MainWindow::makeDirectory* If not exists make a new directory folder

### 8.46.1 Member Function Documentation

#### 8.46.1.1 QString Utils::Directories::makeDirectory ( QDir & *directory*, const QString *path*, const QString *folder* ) throw Exceptions::FileException \*) [static]

MainWindow::makeDirectory If not exists make a new directory *folder*

##### Parameters

<i>path</i>	Return the path of the folder just created
<i>folder</i>	Folder name to create

##### Returns

Path of the folder just created

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/utils/directories.h
- /home/travis/build/FACT-Team/FactDev/src/utils/directories.cpp

## 8.47 Gui::Widgets::Delegates::DoubleSpinBoxDelegate Class Reference

The [DoubleSpinBoxDelegate](#) class.

```
#include <doublespinboxdelegate.h>
```

Inheritance diagram for Gui::Widgets::Delegates::DoubleSpinBoxDelegate:



### Public Member Functions

- [DoubleSpinBoxDelegate](#) (QObject \*parent=0)  
[DoubleSpinBoxDelegate::DoubleSpinBoxDelegate](#).
- QWidget \* [createEditor](#) (QWidget \*parent, const QStyleOptionViewItem &option, const QModelIndex &index) const  
[DoubleSpinBoxDelegate::createEditor](#) Return a ComboBox specified by index item defined by the parent widget and style option which are used to control how the editor widgets appears.
- void [setEditorData](#) (QWidget \*editor, const QModelIndex &index) const  
[DoubleSpinBoxDelegate::setEditorData](#) Sets the data to be displayed and edited by the editor from the data model item specified by the model index
- void [setModelData](#) (QWidget \*editor, QAbstractItemModel \*model, const QModelIndex &index) const  
[DoubleSpinBoxDelegate::setEditorData](#) Sets the data to be displayed and edited by the editor from the data model item specified by the model index
- void [updateEditorGeometry](#) (QWidget \*editor, const QStyleOptionViewItem &option, const QModelIndex &index) const  
[DoubleSpinBoxDelegate::updateEditorGeometry](#) Update the editor for the item specified by index according to the style option given.

### 8.47.1 Detailed Description

The [DoubleSpinBoxDelegate](#) class.

Author

Florent Berbie

### 8.47.2 Constructor & Destructor Documentation

8.47.2.1 [Gui::Widgets::Delegates::DoubleSpinBoxDelegate::DoubleSpinBoxDelegate \( QObject \\* \*parent\* = 0 \)](#)

[DoubleSpinBoxDelegate::DoubleSpinBoxDelegate](#).

Parameters

<i>parent</i>	
---------------	--

### 8.47.3 Member Function Documentation

8.47.3.1 [QWidget \\* Gui::Widgets::Delegates::DoubleSpinBoxDelegate::createEditor \( QWidget \\* \*parent\*, const QStyleOptionViewItem & \*option\*, const QModelIndex & \*index\* \) const](#)

[DoubleSpinBoxDelegate::createEditor](#) Return a ComboBox specified by *index* item defined by the *parent* widget and style *option* which are used to control how the editor widgets appears.

Parameters

<i>parent</i>	Widget parent
<i>option</i>	Option style
<i>index</i>	Index for editing

Returns

[DoubleSpinBoxDelegate](#)

8.47.3.2 [void Gui::Widgets::Delegates::DoubleSpinBoxDelegate::setEditorData \( QWidget \\* \*editor\*, const QModelIndex & \*index\* \) const](#)

[DoubleSpinBoxDelegate::setEditorData](#) Sets the data to be displayed and edited by the *editor* from the data model item specified by the model *index*

Parameters

<i>editor</i>	Data edited
<i>index</i>	Index of the model to edit

8.47.3.3 [void Gui::Widgets::Delegates::DoubleSpinBoxDelegate::setModelData \( QWidget \\* \*editor\*, QAbstractItemModel \\* \*model\*, const QModelIndex & \*index\* \) const](#)

[DoubleSpinBoxDelegate::setEditorData](#) Sets the data to be displayed and edited by the *editor* from the data model item specified by the model *index*

## Parameters

<i>editor</i>	Data edited
<i>index</i>	Index of the model to edit

8.47.3.4 void Gui::Widgets::Delegates::DoubleSpinBoxDelegate::updateEditorGeometry ( QWidget \* *editor*, const QStyleOptionViewItem & *option*, const QModelIndex & *index* ) const

[DoubleSpinBoxDelegate::updateEditorGeometry](#) Update the *editor* for the item specified by *index* according to the style *option* given.

## Parameters

<i>editor</i>	Editor widget to update
<i>option</i>	Style option
<i>index</i>	Item index

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/delegates/doublespinboxdelegate.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/delegates/doublespinboxdelegate.cpp

## 8.48 Exceptions::FileException Class Reference

The [FileException](#) class for file/acess file exception.

```
#include <fileexception.h>
```

### Public Member Functions

- [FileException](#) (const QString userError, const QString fctName, const QString logError, float errorCode)  
*FileException::FileException.* Construct a [FileException](#).
- void [popupMessage](#) (QWidget \*parent)  
*FileException::popupMessage.* Display a popup message with the message error.

### 8.48.1 Detailed Description

The [FileException](#) class for file/acess file exception.

#### Author

Florent Berbie

### 8.48.2 Constructor & Destructor Documentation

8.48.2.1 Exceptions::FileException::FileException ( const QString *userError*, const QString *fctName*, const QString *logError*, float *errorCode* )

[FileException::FileException.](#) Construct a [FileException](#).



## Parameters

<i>userError</i>	ClassName of error
<i>fctName</i>	Function name
<i>logError</i>	Message error
<i>errorCode</i>	Code of error

## 8.48.3 Member Function Documentation

8.48.3.1 void Exceptions::FileException::popupMessage ( QWidget \* *parent* )

[FileException::popupMessage](#). Display a popup message with the message error.

## Parameters

<i>parent</i>	
---------------	--

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/exceptions/fileexception.h
- /home/travis/build/FACT-Team/FactDev/src/exceptions/fileexception.cpp

## 8.49 Generation Class Reference

Inheritance diagram for Generation:



The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/tests/generation.h
- /home/travis/build/FACT-Team/FactDev/tests/generation.cpp

## 8.50 Utils::HierarchicalSystem Class Reference

The [HierarchicalSystem](#) class Create class which contains hierarchical system of FactDev.

```
#include <hierarchichalsystem.h>
```

## Public Member Functions

- [HierarchicalSystem](#) ()  
*HierarchicalSystem::HierarchicalSystem* Construct a *HierarchicalSystem*.
- void [getAllProjects](#) ()  
*HierarchicalSystem::getAllProjects* Get all projects and add each project to Customer linked.
- void [getAllBillings](#) ()  
*HierarchicalSystem::getAllBillings* Get all billings and add each billing to Project linked.
- void [updateData](#) ()

- [\*HierarchicalSystem::updateData\*](#) Update data on Customers, Projects, Billings.
- void [\*addProjectToCustomer\*](#) ([Project \\*p](#), [Customer c](#))  
[\*HierarchicalSystem::addProjectToCustomer\*](#) Add the Project *p* to the Customer *c*
- void [\*addBillingToProject\*](#) ([Billing \\*b](#), [Project \\*p](#))  
[\*HierarchicalSystem::addBillingToProject\*](#) Add the Billing *b* to the Project *p*
- QMap< [Project \\*](#), [Customer](#) > [\*getCustomers\*](#) () const  
[\*HierarchicalSystem::getCustomers\*](#) Return all customers and these projects linked.
- QMap< [Billing \\*](#), [Project \\*](#) > [\*getProjects\*](#) () const  
[\*HierarchicalSystem::getProjects\*](#) Return all projects and these billing linked.

### 8.50.1 Detailed Description

The [HierarchicalSystem](#) class Create class which contains hierarchical system of FactDev.

#### Author

Florent Berbie

#### See Also

Customer  
Project  
Billing

### 8.50.2 Member Function Documentation

#### 8.50.2.1 void Utils::HierarchicalSystem::addBillingToProject ( [Billing \\* b](#), [Project \\* p](#) )

[\*HierarchicalSystem::addBillingToProject\*](#) Add the Billing *b* to the Project *p*

##### Parameters

<i>b</i>	Billing
<i>p</i>	Project

#### 8.50.2.2 void Utils::HierarchicalSystem::addProjectToCustomer ( [Project \\* p](#), [Customer c](#) )

[\*HierarchicalSystem::addProjectToCustomer\*](#) Add the Project *p* to the Customer *c*

##### Parameters

<i>p</i>	Project
<i>c</i>	Customer

#### 8.50.2.3 QMap< [Project \\*](#), [Customer](#) > Utils::HierarchicalSystem::getCustomers ( ) const

[\*HierarchicalSystem::getCustomers\*](#) Return all customers and these projects linked.

##### Returns

Projects linked to Customers

8.50.2.4 QMap< Billing \*, Project \* > Utils::HierarchicalSystem::getProjects ( void ) const

[HierarchicalSystem::getProjects](#) Return all projects and these billing linked.

#### Returns

Billing linked to Projects

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/utls/hierarchichalsystem.h
- /home/travis/build/FACT-Team/FactDev/src/utls/hierarchichalsystem.cpp

## 8.51 Gui::Widgets::CheckFields::ICheckField Class Reference

The [ICheckField](#) class Interface to check fields validity.

```
#include <icheckfield.h>
```

Inheritance diagram for Gui::Widgets::CheckFields::ICheckField:



### Public Member Functions

- virtual bool [check](#) (QString text)=0  
*[ICheckField::check](#) Check if the field (line edit) is valid Return TRUE if the field is valid, else FALSE.*

### 8.51.1 Detailed Description

The [ICheckField](#) class Interface to check fields validity.

### 8.51.2 Member Function Documentation

8.51.2.1 virtual bool Gui::Widgets::CheckFields::ICheckField::check ( QString text ) [pure virtual]

[ICheckField::check](#) Check if the field (line edit) is valid Return TRUE if the field is valid, else FALSE.

#### Returns

boolean Validity of the text

Implemented in [Gui::Widgets::CheckFields::CheckEmail](#), [Gui::Widgets::CheckFields::CheckPortNumber](#), [Gui::Widgets::CheckFields::CheckFieldsNumbers](#), [Gui::Widgets::CheckFields::CheckIpAddress](#), [Gui::Widgets::CheckFields::CheckLogin](#), [Gui::Widgets::CheckFields::CheckPhone](#), [Gui::Widgets::CheckFields::CheckPostalCode](#), [Gui::Widgets::CheckFields::CheckSiretNumber](#), [Gui::Widgets::CheckFields::CheckUntilField](#), [Gui::Widgets::CheckFields::CheckFieldsLetters](#), and [Gui::Widgets::CheckFields::CheckValidField](#).

The documentation for this class was generated from the following file:

- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/icheckfield.h

## 8.52 Models::IModel Class Reference

The [IModel](#) class.

```
#include <imodel.h>
```

Inheritance diagram for Models::IModel:



### Public Member Functions

- virtual [~IModel](#) ()  
*~IModel Remove an instance of [IModel](#)*
- virtual void [commit](#) ()=0  
*[IModel::commit](#) Update or insert data into the database.*
- virtual void [hydrat](#) (int id)=0  
*[IModel::hydrat](#) Get data of the element which is specified by the identify id from the database.*
- virtual void [remove](#) ()=0  
*[IModel::remove](#) Remove the current element in the database.*
- virtual QVariantHash [getDataMap](#) ()=0  
*[getDataMap](#) Get all data of model with a HashMap key/value*
- int [getId](#) () const  
*[IModel::getId](#) Return the identify of the element of the database.*
- void [setId](#) (int id)  
*[IModel::setId](#) Replace the current identify by id*
- bool [isToRemoved](#) () const  
*[toRemoved](#) return if object must be removed.*
- void [setToRemoved](#) (bool toRemoved)  
*[setToRemoved](#) Change the flag for removed object*

### Protected Attributes

- int [\\_id](#)  
*Element identify.*
- bool [\\_toRemoved](#)  
*Flag to know if the object must be removed.*

#### 8.52.1 Detailed Description

The [IModel](#) class.

Author

Antoine de Roquemaurel

## 8.52.2 Member Function Documentation

8.52.2.1 `virtual QVariantHash Models::IModel::getDataMap ( ) [pure virtual]`

getDataMap Get all data of model with a HashMap key/value

Returns

Model's data

Implemented in [Models::Billing](#), [Models::Project](#), [Models::User](#), [Models::Contributory](#), and [Models::Customer](#).

8.52.2.2 `int Models::IModel::getId ( ) const [inline]`

[IModel::getId](#) Return the identify of the element of the database.

Returns

identity

8.52.2.3 `virtual void Models::IModel::hydrat ( int id ) [pure virtual]`

[IModel::hydrat](#) Get data of the element which is specified by the identify *id* from the database.

Parameters

<i>id</i>	
-----------	--

Implemented in [Models::Billing](#), [Models::Project](#), [Models::User](#), [Models::Contributory](#), and [Models::Customer](#).

8.52.2.4 `bool Models::IModel::isToRemoved ( ) const [inline]`

toRemoved return if object must be removed.

Returns

boolean

8.52.2.5 `void Models::IModel::setId ( int id ) [inline]`

[IModel::setId](#) Replace the current identify by *id*

Parameters

<i>id</i>	New identify
-----------	--------------

8.52.2.6 `void Models::IModel::setToRemoved ( bool toRemoved ) [inline]`

setToRemoved Change the flag for removed object

Parameters

<i>toRemoved</i>	The new flag
------------------	--------------

The documentation for this class was generated from the following file:

- /home/travis/build/FACT-Team/FactDev/src/models/imodel.h

## 8.53 Utils::ItemType Class Reference

The [ItemType](#) class Item type model.

```
#include <itemtype.h>
```

### Public Member Functions

- [ItemType](#) (int type, QString name)  
*ItemType::ItemType* Construct an Item type.
- QString [getName](#) () const  
*ItemType::getName* Get item name.
- [Models::IModel](#) \* [getModel](#) (int id)  
*ItemType::getModel* Get the databasemodel of the [ItemType](#) according to this identity id
- void [setName](#) (const QString &name)  
*ItemType::setName* Modify the item name.
- int [getType](#) () const  
*ItemType::getType* Get the type of the current item.
- void [setType](#) (int type)  
*ItemType::setType* Modify the type of the current item.

### Static Public Attributes

- static const int [CUSTOMER](#) = 0  
*constant value assigned to Customer*
- static const int [PROJECT](#) = 1  
*constant value assigned to Project*
- static const int [BILLING](#) = 2  
*constant value assigned to Billing*
- static const int [QUOTE](#) = 3  
*constant value assigned to Quote*

#### 8.53.1 Detailed Description

The [ItemType](#) class Item type model.

#### 8.53.2 Constructor & Destructor Documentation

##### 8.53.2.1 Utils::ItemType::ItemType ( int type, QString name )

[ItemType::ItemType](#) Construct an Item type.

## Parameters

<i>type</i>	Type of the item
<i>name</i>	Name of the item

### 8.53.3 Member Function Documentation

#### 8.53.3.1 Models::IModel \* Utils::ItemType::getModel ( int *id* )

[ItemType::getModel](#) Get the databasemodel of the [ItemType](#) according to this identity *id*

## Parameters

<i>id</i>	Item type identity
-----------	--------------------

## Returns

database model

#### 8.53.3.2 QString Utils::ItemType::getName ( ) const

[ItemType::getName](#) Get item name.

## Returns

item name

#### 8.53.3.3 int Utils::ItemType::getType ( ) const

[ItemType::getType](#) Get the type of the current item.

## Returns

type of the current item

#### 8.53.3.4 void Utils::ItemType::setName ( const QString & *name* )

[ItemType::setName](#) Modify the item name.

## Parameters

<i>name</i>	New Item name
-------------	---------------

#### 8.53.3.5 void Utils::ItemType::setType ( int *type* )

[ItemType::setType](#) Modify the type of the current item.

## Parameters

<i>type</i>	New item type
-------------	---------------

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/utils/itemtype.h
- /home/travis/build/FACT-Team/FactDev/src/utils/itemtype.cpp

## 8.54 ItemTypeTest Class Reference

Inheritance diagram for ItemTypeTest:



The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/tests/utils/itemtypetest.h
- /home/travis/build/FACT-Team/FactDev/tests/utils/itemtypetest.cpp

## 8.55 Utils::Log Class Reference

The [Log](#) class for Simple management of log.

```
#include <log.h>
```

### Public Member Functions

- [~Log](#) ()  
*Log::~~Log.*
- void [write](#) (const QString text)  
*Log::write. Write log message in file.*
- [Log](#) ()  
*Log::Log. Log is a singleton.*

### Static Public Member Functions

- static [Log](#) & [instance](#) (TypeLog type=INFO)  
*Log::instance. Return the instance of logger.*

### Friends

- [Log](#) & [operator<<](#) ([Log](#) &logger, const QString &text)  
*operator << for log writing*

### 8.55.1 Detailed Description

The [Log](#) class for Simple management of log.

### 8.55.2 Member Function Documentation

#### 8.55.2.1 [Log](#) & [Utils::Log::instance](#) ( TypeLog *type* = INFO ) [static]

[Log::instance](#). Return the instance of logger.



## Parameters

<i>type</i>	Type of log : WARNING, INFO, ERROR
-------------	------------------------------------

## Returns

Instance of logger.

## 8.55.2.2 void Utils::Log::write ( const QString text )

[Log::write](#). Write log message in file.

## Parameters

<i>text</i>	
-------------	--

## 8.55.3 Friends And Related Function Documentation

## 8.55.3.1 Log&amp; operator&lt;&lt; ( Log &amp; logger, const QString &amp; text ) [friend]

operator << for log writing

## Parameters

<i>logger</i>	Instance of Logger
<i>text</i>	Text to write

## Returns

New logger.

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/utils/log.h
- /home/travis/build/FACT-Team/FactDev/src/utils/log.cpp

## 8.56 Gui::MainWindow Class Reference

The [MainWindow](#) class Main Window of the software.

```
#include <mainwindow.h>
```

Inheritance diagram for Gui::MainWindow:



## Public Slots

- void [addCustomer](#) ()  
[MainWindow::addCustomer](#) open window to add a new customer.
- void [editCustomer](#) ()

- [\*MainWindow::editCustomer\*](#) open window to modify a customer.
- void [\*removeCustomer\*](#) ()
  - [\*MainWindow::removeCustomer\*](#) open a popup to confirm the deletion of a customer, if ok remove the customer.
- void [\*addQuote\*](#) ()
  - [\*MainWindow::addQuote\*](#) open window to add a new quote.
- void [\*addBill\*](#) ()
  - [\*MainWindow::addBill\*](#) open window to add a new bill.
- void [\*billingsIsPaid\*](#) ()
  - [\*MainWindow::billingsIsPaid\*](#) Define the current billing as "paid".
- void [\*editUser\*](#) ()
  - [\*MainWindow::editUser\*](#) modify the user.
- void [\*search\*](#) (QString s)
  - [\*MainWindow::search\*](#) launch a new search.
- void [\*addProject\*](#) ()
  - [\*MainWindow::addProject\*](#) Create a new project for a customer.
- void [\*removeProject\*](#) (void)
  - [\*MainWindow::removeProject\*](#) Remove a project for a customer.
- void [\*editProject\*](#) (void)
  - [\*MainWindow::editProject\*](#) Modify the customer project.
- void [\*aboutQt\*](#) ()
  - [\*MainWindow::aboutQt\*](#) show Qt's details.
- void [\*aboutFact\*](#) ()
  - [\*MainWindow::aboutFact\*](#) show FACT's details (FACT team)
- void [\*aboutFactDev\*](#) ()
  - [\*MainWindow::aboutFactDev\(\)\*](#) show FactDev's details (FactDev Software)
- void [\*aboutIcons\*](#) ()
  - [\*MainWindow::aboutIcons\(\)\*](#) show icons's details.
- void [\*updateButtons\*](#) (void)
  - [\*updateButton\*](#) Update all button to disable or enabled its
- void [\*editDoc\*](#) ()
  - [\*MainWindow::editDoc\*](#) Edit the quote or bill of the project.
- void [\*removeDoc\*](#) ()
  - [\*MainWindow::removeDoc\*](#) Remove the quote or bill of the project.
- void [\*copyDoc\*](#) ()
  - [\*MainWindow::copyDoc\*](#) Copy all elements of a quote or a bill and Display these elements in a new quote or bill.
- void [\*openPdf\*](#) ()
  - [\*MainWindow::openPdf\*](#) Open the PDF file of the current Quote or Billing selected in the TableView.

## Public Member Functions

- [\*MainWindow\*](#) (QWidget \*parent=0)
  - [\*MainWindow\*](#): Construct a window.
- int [\*getCurrentCustomerId\*](#) ()
  - [\*MainWindow::getCurrentCustomerId\*](#) get the selected customer.
- int [\*getCurrentProjectId\*](#) ()
  - [\*MainWindow::getCurrentProjectId\*](#) get the selected project id.
- int [\*getCurrentQuoteId\*](#) ()
  - [\*MainWindow::getCurrentQuoteId\*](#) get the selected quote id.
- QString [\*getCurrentCustomerName\*](#) ()
  - [\*MainWindow::getCurrentCustomerName\*](#) get the selected customer name in the customers' table.

- QString [getCurrentProjectName](#) ()  
*MainWindow::getCurrentProjectName* get the selected project name in the table of projects.
- int [treeLevel](#) ()  
*MainWindow::treeLevel* return the level of the node selected in the tree.
- QModelIndex [rootTree](#) ()  
*MainWindow::rootTree* return the root of the tree "Tous les clients".
- void [addDoc](#) (bool isBilling)  
*MainWindow::addDoc* open window to add a new document.

### 8.56.1 Detailed Description

The [MainWindow](#) class Main Window of the software.

Author

Everybody

### 8.56.2 Constructor & Destructor Documentation

8.56.2.1 [Gui::MainWindow::MainWindow](#) ( [QWidget](#) \* *parent* = 0 ) [explicit]

[MainWindow](#): Construct a window.

Parameters

<i>parent</i>	
---------------	--

### 8.56.3 Member Function Documentation

8.56.3.1 void [Gui::MainWindow::addBill](#) ( ) [slot]

[MainWindow::addBill](#) open window to add a new bill.

See Also

[AddQuoteDialog](#)

8.56.3.2 void [Gui::MainWindow::addDoc](#) ( bool *isBilling* )

[MainWindow::addDoc](#) open window to add a new document.

Parameters

<i>bool</i>	quote or bill
-------------	---------------

See Also

[addBill](#) [addQuote](#)

8.56.3.3 void [Gui::MainWindow::addProject](#) ( ) [slot]

[MainWindow::addProject](#) Create a new project for a customer.

See Also

[AddProjectDialog](#)

8.56.3.4 void Gui::MainWindow::addQuote ( ) [slot]

[MainWindow::addQuote](#) open window to add a new quote.

See Also

AddQuoteDialog

8.56.3.5 void Gui::MainWindow::editUser ( ) [slot]

[MainWindow::editUser](#) modify the user.

See Also

UserDataDialog

8.56.3.6 int Gui::MainWindow::getCurrentCustomerId ( )

[MainWindow::getCurrentCustomerId](#) get the selected customer.

Returns

id of the selected customer

8.56.3.7 QString Gui::MainWindow::getCurrentCustomerName ( )

[MainWindow::getCurrentCustomerName](#) get the selected customer name in the customers' table.

Returns

name of the selected customer

8.56.3.8 int Gui::MainWindow::getCurrentProjectId ( )

[MainWindow::getCurrentProjectId](#) get the selected project id.

Returns

id of the selected project

8.56.3.9 QString Gui::MainWindow::getCurrentProjectName ( )

[MainWindow::getCurrentProjectName](#) get the selected project name in the table of projects.

Returns

name of the selected project

8.56.3.10 int Gui::MainWindow::getCurrentQuoteId ( )

[MainWindow::getCurrentQuoteId](#) get the selected quote id.

Returns

id of the selected quote

## 8.56.3.11 QModelIndex Gui::MainWindow::rootTree ( )

[MainWindow::rootTree](#) return the root of the tree "Tous les clients".

## Returns

QModelIndex

## 8.56.3.12 void Gui::MainWindow::search ( QString s ) [slot]

[MainWindow::search](#) launch a new search.

## Parameters

s	text in field
---	---------------

## 8.56.3.13 int Gui::MainWindow::treeLevel ( )

[MainWindow::treeLevel](#) return the level of the node selected in the tree.

## Returns

integer, depth of the item in tree

The documentation for this class was generated from the following files:


- /home/travis/build/FACT-Team/FactDev/src/gui/mainwindow/mainwindow.h
- /home/travis/build/FACT-Team/FactDev/src/gui/mainwindow/mainwindow.cpp

## 8.57 Gui::Dialogs::MessageBox Class Reference

The [MessageBox](#) class Information window with message.

```
#include <messagebox.h>
```

Inheritance diagram for Gui::Dialogs::MessageBox:



## Public Member Functions

- [MessageBox](#) (QWidget \*parent=0)  
[MessageBox::MessageBox](#) Construt a [MessageBox](#)
- void [aboutFact](#) ()  
[MessageBox::aboutFact](#) Defines FACT team information.
- void [aboutFactDev](#) ()  
[MessageBox::aboutFactDev](#) Defines FactDev software information.
- void [aboutIcons](#) ()  
[MessageBox::aboutIcons](#) Defines icons theme information.
- void [setImage](#) (QString img, int width=128, int height=128)

- [MessageBox::setImage](#) Add the icon *img* to the current window.
- void [setText](#) (QString txt)  
[MessageBox::setText](#) Add the text *txt* to the current window.

## Static Public Member Functions

- static void [showAboutFact](#) ()  
[MessageBox::showAboutFact](#) Shows window about FACT team.
- static void [showAboutFactDev](#) ()  
[MessageBox::showAboutFactDev](#) Shows window about FactDev software.
- static void [showAboutIcons](#) ()  
[MessageBox::showAboutIcons](#) Shows about icons theme of FactDev software.

## 8.57.1 Detailed Description

The [MessageBox](#) class Information window with message.

Author

Florent Berbie

## 8.57.2 Constructor & Destructor Documentation

8.57.2.1 [Gui::Dialogs::MessageBox::MessageBox](#) ( QWidget \* *parent* = 0 ) [explicit]

[MessageBox::MessageBox](#) Construt a [MessageBox](#)

Parameters

<i>parent</i>	
---------------	--

## 8.57.3 Member Function Documentation

8.57.3.1 void [Gui::Dialogs::MessageBox::setImage](#) ( QString *img*, int *width* = 128, int *height* = 128 )

[MessageBox::setImage](#) Add the icon *img* to the current window.

Parameters

<i>img</i>	Icon
<i>width</i>	Icon width (default: 128)
<i>height</i>	Icon height (default: 128)

8.57.3.2 void [Gui::Dialogs::MessageBox::setText](#) ( QString *txt* )

[MessageBox::setText](#) Add the text *txt* to the current window.

Parameters

<i>txt</i>	Text inside the current window
------------	--------------------------------

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/dialogs/messagebox.h
- /home/travis/build/FACT-Team/FactDev/src/gui/dialogs/messagebox.cpp

## 8.58 Parameters Class Reference

The [Parameters](#) class Class for simple user parameters.

```
#include <parameters.h>
```

### Static Public Attributes

- static const QString [DB\\_FILENAME](#) = "database.db"  
*DB\_FILENAME* The database sqlite file name.
- static const double [VERSION](#) = 1.0  
*VERSION* Version number of software.

### 8.58.1 Detailed Description

The [Parameters](#) class Class for simple user parameters.

Author

Antoine de Roquemaurel

### 8.58.2 Member Data Documentation

**8.58.2.1** `const QString Parameters::DB_FILENAME = "database.db" [static]`

*DB\_FILENAME* The database sqlite file name.

Database file name

**8.58.2.2** `const double Parameters::VERSION = 1.0 [static]`

*VERSION* Version number of software.

Application version


The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/parameters.h
- /home/travis/build/FACT-Team/FactDev/src/parameters.cpp

## 8.59 Mustache::PartialFileLoader Class Reference

```
#include <mustache.h>
```

Inheritance diagram for Mustache::PartialFileLoader:



## Public Member Functions

- **PartialFileLoader** (const QString &basePath)
- virtual QString [getPartial](#) (const QString &name)

### 8.59.1 Detailed Description

A partial fetcher when loads templates from '<name>.mustache' files in a given directory.  
Once a partial has been loaded, it is cached for future use.

### 8.59.2 Member Function Documentation

#### 8.59.2.1 QString PartialFileLoader::getPartial ( const QString & name ) [virtual]

Returns the partial template with a given `name`.

Implements [Mustache::PartialResolver](#).


The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/libs/qt-mustache/src/mustache.h
- /home/travis/build/FACT-Team/FactDev/src/libs/qt-mustache/src/mustache.cpp

## 8.60 Mustache::PartialMap Class Reference

```
#include <mustache.h>
```

Inheritance diagram for Mustache::PartialMap:



## Public Member Functions

- **PartialMap** (const QHash< QString, QString > &partials)
- virtual QString [getPartial](#) (const QString &name)

### 8.60.1 Detailed Description

A simple partial fetcher which returns templates from a map of (partial name -> template)

### 8.60.2 Member Function Documentation

#### 8.60.2.1 QString PartialMap::getPartial ( const QString & name ) [virtual]

Returns the partial template with a given `name`.

Implements [Mustache::PartialResolver](#).

The documentation for this class was generated from the following files:




- /home/travis/build/FACT-Team/FactDev/src/libs/qt-mustache/src/mustache.h
- /home/travis/build/FACT-Team/FactDev/src/libs/qt-mustache/src/mustache.cpp

## 8.61 Mustache::PartialResolver Class Reference

```
#include <mustache.h>
```

Inheritance diagram for Mustache::PartialResolver:



### Public Member Functions

- virtual QString [getPartial](#) (const QString &name)=0

#### 8.61.1 Detailed Description

Interface for fetching template partials.

#### 8.61.2 Member Function Documentation

8.61.2.1 virtual QString Mustache::PartialResolver::getPartial ( const QString & *name* ) [pure virtual]

Returns the partial template with a given *name*.

Implemented in [Mustache::PartialFileLoader](#), and [Mustache::PartialMap](#).

The documentation for this class was generated from the following file:

- /home/travis/build/FACT-Team/FactDev/src/libs/qt-mustache/src/mustache.h

## 8.62 Generator::PdfGenerator Class Reference

The [PdfGenerator](#) class Generator of PDF files.

```
#include <pdfgenerator.h>
```

### Public Member Functions

- [PdfGenerator](#) (QString pdflatexPath="pdflatex")  
[PdfGenerator::PdfGenerator](#) Construct a [PdfGenerator](#).
- void [generate](#) (QString inputDir, QString filename)  
[PdfGenerator::generate](#) Generate a PDF of the file named filename into the directory inputDir

#### 8.62.1 Detailed Description

The [PdfGenerator](#) class Generator of PDF files.

## 8.62.2 Constructor & Destructor Documentation

### 8.62.2.1 Generator::PdfGenerator::PdfGenerator ( QString *pdflatexPath* = "pdflatex" )

[PdfGenerator::PdfGenerator](#) Construct a [PdfGenerator](#).

Parameters

<i>pdflatexPath</i>	Path to the command to generate PDF file
---------------------	------------------------------------------

## 8.62.3 Member Function Documentation

### 8.62.3.1 void Generator::PdfGenerator::generate ( QString *inputDir*, QString *filename* )

[PdfGenerator::generate](#) Generate a PDF of the file named *filename* into the directory *inputDir*

Parameters

<i>inputDir</i>	Directory where is store the PDF generated
<i>filename</i>	File name

The documentation for this class was generated from the following files:


- /home/travis/build/FACT-Team/FactDev/src/generator/pdfgenerator.h
- /home/travis/build/FACT-Team/FactDev/src/generator/pdfgenerator.cpp

## 8.63 Models::People Class Reference

The [People](#) class [People](#).

```
#include <people.h>
```

Inheritance diagram for Models::People:



## Public Member Functions

- [People](#) ()  
*People::People* Construct a *People*.
- QString [getFirstname](#) () const  
*People::getFirstname* Return the *People* firstname.
- void [setFirstname](#) (const QString &firstname)  
*People::setFirstnament* Modify the *People* firstname
- QString [getLastname](#) () const  
*People::getLastname* Return the *People* lastname.
- void [setLastname](#) (const QString &lastname)  
*People::setLastname* Modify the *People* lastname
- QString [getCompany](#) () const  
*People::getCompany* Return the *People* company.
- void [setCompany](#) (const QString &company)

- *People::setCompany* Modify the *People* company name.
- QString *getAddress* () const  
*People::getAddress* Return the company address (Number and name of street)
- void *setAddress* (const QString &address)  
*People::setAddress* Modify the *People* company address
- QString *getPostalCode* () const  
*People::getPostalCode* Return the postal code.
- void *setPostalCode* (const QString &postalCode)  
*People::setPostalCode* Modify the postal code postalCode
- QString *getCity* () const  
*People::getCity* Return the city.
- void *setCity* (const QString &city)  
*People::setCity* Modify the city
- QString *getCountry* () const  
*People::getCountry* Return the country of the *People*.
- void *setCountry* (const QString &country)  
*People::setCountry* Replace the country of the *People* by country
- QString *getEmail* () const  
*People::getEmail* Return the *People* professional email
- void *setEmail* (const QString &email)  
*People::setEmail* Modify the *People* professional email
- QString *getPhone* () const  
*People::getPhone* Return the number of the desktop phone.
- void *setPhone* (const QString &phone)  
*People::setPhone* Modify the number of the desktop phone
- QString *getMobilePhone* () const  
*People::getMobilePhone* Return the number of the professional mobile phone.
- void *setMobilePhone* (const QString &mobilePhone)  
*People::setMobilePhone* Modify the number of the professional *People* mobile phone mobilePhone
- QString *getFax* () const  
*People::getFax* Return the fax number.
- void *setFax* (const QString &fax)  
*People::setFax* Replace the current fax number by fax
- bool *operator==* (const *People* &c)  
*People::operator ==* Re-define the operator "==" to compare if the current *People* is the same to the other *People* c  
Return TRUE if both Peoples are the same, else FALSE.
- bool *operator!=* (const *People* &c)  
*People::operator !=* Re-define the operator "!=" to compare if the current *People* is differnt to the other *People* c  
Return TRUE if both Peoples are different, else FALSE.

### 8.63.1 Detailed Description

The *People* class *People*.

### 8.63.2 Member Function Documentation

#### 8.63.2.1 QString Models::People::getAddress ( ) const

*People::getAddress* Return the company address (Number and name of street)

Returns

Address company

#### 8.63.2.2 QString Models::People::getCity ( ) const

[People::getCity](#) Return the city.

Returns

city

#### 8.63.2.3 QString Models::People::getCompany ( ) const

[People::getCompany](#) Return the [People](#) company.

Returns

New company name

#### 8.63.2.4 QString Models::People::getCountry ( ) const

[People::getCountry](#) Return the country of the [People](#).

Returns

country of the [People](#)

#### 8.63.2.5 QString Models::People::getEmail ( ) const

[People::getEmail](#) Return the [People](#) professional *email*

Returns

professional email

#### 8.63.2.6 QString Models::People::getFax ( ) const

[People::getFax](#) Return the fax number.

Returns

fax number

#### 8.63.2.7 QString Models::People::getFirstname ( ) const

[People::getFirstname](#) Return the [People](#) firstname.

Returns

[People](#) firstname

#### 8.63.2.8 QString Models::People::getLastname ( ) const

[People::getLastname](#) Return the [People](#) lastname.

Returns

[People](#) lastname

**8.63.2.9** QString Models::People::getMobilePhone ( ) const

[People::getMobilePhone](#) Return the number of the professional mobile phone.

**Returns**

number of mobile phone

**8.63.2.10** QString Models::People::getPhone ( ) const

[People::getPhone](#) Return the number of the desktop phone.

**Returns**

number of the desktop phone

**8.63.2.11** QString Models::People::getPostalCode ( ) const

[People::getPostalCode](#) Return the postal code.

**Returns**

postal code

**8.63.2.12** bool Models::People::operator!= ( const People & c )

[People::operator !=](#) Re-define the operator "!=" to compare if the current [People](#) is different to the other [People](#) c  
Return TRUE if both Peoples are different, else FALSE.

**Parameters**

c	<a href="#">People</a> to compare
---	-----------------------------------

**Returns**

boolean

**8.63.2.13** bool Models::People::operator== ( const People & c )

[People::operator ==](#) Re-define the operator "==" to compare if the current [People](#) is the same to the other [People](#) c  
Return TRUE if both Peoples are the same, else FALSE.

**Parameters**

c	<a href="#">People</a> to compare
---	-----------------------------------

**Returns**

boolean

**8.63.2.14** void Models::People::setAddress ( const QString & address )

[People::setAddress](#) Modify the [People](#) company *address*

## Parameters

<i>address</i>	Company address (name and number of street)
----------------	---------------------------------------------

8.63.2.15 void Models::People::setCity ( const QString & *city* )

[People::setCity](#) Modify the *city*

## Parameters

<i>city</i>	Company city address
-------------	----------------------

8.63.2.16 void Models::People::setCompany ( const QString & *company* )

[People::setCompany](#) Modify the [People](#) *company* name.

## Parameters

<i>company</i>	New <a href="#">People</a> company name
----------------	-----------------------------------------

8.63.2.17 void Models::People::setCountry ( const QString & *country* )

[People::setCountry](#) Replace the country of the [People](#) by *country*

## Parameters

<i>country</i>	New country of the <a href="#">People</a>
----------------	-------------------------------------------

8.63.2.18 void Models::People::setEmail ( const QString & *email* )

[People::setEmail](#) Modify the [People](#) professional *email*

## Parameters

<i>email</i>	The <a href="#">People</a> professional email
--------------	-----------------------------------------------

8.63.2.19 void Models::People::setFax ( const QString & *fax* )

[People::setFax](#) Replace the current fax number by *fax*

## Parameters

<i>fax</i>	new fax number
------------	----------------

8.63.2.20 void Models::People::setFirstname ( const QString & *firstname* )

[People::setFirstname](#) Modify the [People](#) *firstname*

## Parameters

<i>firstname</i>	New <a href="#">People</a> firstname
------------------	--------------------------------------

8.63.2.21 void Models::People::setLastname ( const QString & *lastname* )

[People::setLastname](#) Modify the [People](#) *lastname*

## Parameters

<i>lastname</i>	New <a href="#">People</a> lastname
-----------------	-------------------------------------

8.63.2.22 void Models::People::setMobilePhone ( const QString & *mobilePhone* )

[People::setMobilePhone](#) Modify the number of the professional [People](#) mobile phone *mobilePhone*

## Parameters

<i>mobilePhone</i>	Number of the professional mobile phone
--------------------	-----------------------------------------

8.63.2.23 void Models::People::setPhone ( const QString & *phone* )

[People::setPhone](#) Modify the number of the desktop *phone*

## Parameters

<i>phone</i>	Number of the desktop phone
--------------	-----------------------------

8.63.2.24 void Models::People::setPostalCode ( const QString & *postalCode* )

[People::setPostalCode](#) Modify the postal code *postalCode*

## Parameters

<i>postalCode</i>	New postal code
-------------------	-----------------

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/models/people.h
- /home/travis/build/FACT-Team/FactDev/src/models/people.cpp

## 8.64 Utils::pointers Class Reference

### Static Public Member Functions

- static void **deleteIfNotNull** (QObject \*p)

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/utils/pointers.h
- /home/travis/build/FACT-Team/FactDev/src/utils/pointers.cpp

## 8.65 Gui::Widgets::Popup Class Reference

Class for display popup quickly.

```
#include <popup.h>
```

### Static Public Member Functions

- static void [toImplement](#) (QString, QWidget \*)  
[Popup::toImplement](#) Method to display a critical message : feature is not implemented now.



### 8.65.1 Detailed Description

Class for display popup quickly.

Author

Antoine de Roquemaurel

The documentation for this class was generated from the following files:


- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/popup.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/popup.cpp

## 8.66 Models::Project Class Reference

The [Project](#) class : [Project](#) linked to a [Customer](#).

```
#include <project.h>
```

Inheritance diagram for Models::Project:



### Public Member Functions

- [Project](#) ()  
*Project::Project Construct a [Project](#).*
- [Project](#) (QString name)  
*Project::project Construct a project with a name.*
- [Project](#) (int id)  
*Project::Project Construct a [Project](#) which is specified by an id*
- virtual [~Project](#) ()  
*~Project Desctruct project object*
- void [commit](#) ()  
*Project::commit Update project data in the database.*
- void [hydrat](#) (int id)  
*Project::hydrat Insert project data which is specified by id in the database.*
- void [remove](#) ()  
*Project::remove Remove the current project.*
- QVariantHash [getDataMap](#) ()  
*getDataMap Get all data of model with a HashMap key/value*
- QString [getName](#) () const  
*Project::getName Return the project name.*
- void [setName](#) (const QString &name)  
*Project::setName Modify the project name*
- QString [getDescription](#) () const  
*Project::getDescription Return a project description.*
- void [setDescription](#) (const QString &description)

- Project::setDescription* Modify the project description
- QDate **getBeginDate** () const  
*Project::getBeginDate* return the date of creation of the **Project**
- void **setBeginDate** (QDate beginDate)  
*Project::setBeginDate* Modify beginDate of a **Project**
- QDate **getEndDate** () const  
*Project::getEndDate* Return the endDate of the **Project**
- void **setEndDate** (QDate endDate)  
*Project::setEndDate* Modify endDate of **Project**
- double **getCost** () const  
*Project::getCost* Return the **Project** cost
- void **setCost** (double cost)  
*Project::setCost* Modify the **Project** cost
- double **getDailyRate** () const  
*Project::getDailyRate* Return the daily rate estimated for this project.
- void **setDailyRate** (double dailyRate)  
*Project::setDailyRate* Modify the daily rate dailyRate of the current project.
- QSharedPointer< **Customer** > **getCustomer** () const  
*Project::getCustomer* Return the reference to the customer linked to this project.
- void **setCustomer** (QSharedPointer< **Customer** > customer)  
*Project::setCustomer* Modify the customer linked to this project.
- bool **operator==** (const **Project** &p)  
*Project::operator ==* Re-define the operator "==" to compare if the current project is the same to the other **Project** p  
Return TRUE if both projects are the same, else FALSE.
- bool **operator<** (const **Project** &p) const  
*Project::operator <* defines the operator "<" to compare two **Project** and to see if the first is anterior to the second.
- bool **operator!=** (const **Project** &p)  
*Project::operator !=* Re-define the operator "!=" to compare if the current project is different to the other **Project** p  
Return TRUE if both projects are different, else FALSE.
- double **costCompute** ()  
*Project::costCompute* compute the **Project** cost

## Additional Inherited Members

### 8.66.1 Detailed Description

The **Project** class : **Project** linked to a **Customer**.

#### Author

Florent Berbie

#### See Also

**IModel**

### 8.66.2 Constructor & Destructor Documentation

#### 8.66.2.1 Models::Project::Project ( int id )

**Project::Project** Construct a **Project** which is specified by an *id*

## Parameters

<i>id</i>	
-----------	--

### 8.66.3 Member Function Documentation

#### 8.66.3.1 double Models::Project::costCompute ( )

[Project::costCompute](#) compute the **Project** cost

**Returns**

the project cost

#### 8.66.3.2 QDate Models::Project::getBeginDate ( ) const

[Project::getBeginDate](#) return the date of creation of the **Project**

**Returns**

the begin date of the **Project**

#### 8.66.3.3 double Models::Project::getCost ( ) const

[Project::getCost](#) Return the **Project** cost

**Returns**

the project cost

#### 8.66.3.4 QSharedPointer< Customer > Models::Project::getCustomer ( ) const

[Project::getCustomer](#) Return the reference to the customer linked to this project.

**Returns**

customer linked to this project

#### 8.66.3.5 double Models::Project::getDailyRate ( ) const

[Project::getDailyRate](#) Return the daily rate estimated for this project.

**Returns**

the daily rate linket to the current project

#### 8.66.3.6 QVariantHash Models::Project::getDataMap ( ) [virtual]

[getDataMap](#) Get all data of model with a HashMap key/value

**Returns**

Model's data

Implements [Models::IModel](#).

#### 8.66.3.7 QString Models::Project::getDescription ( ) const

[Project::getDescription](#) Return a project description.

##### Returns

project description

#### 8.66.3.8 QDate Models::Project::getEndDate ( ) const

[Project::getEndDate](#) Return the *endDate* of the **Project**

##### Returns

the end date of the project

#### 8.66.3.9 QString Models::Project::getName ( ) const

[Project::getName](#) Return the project name.

##### Returns

project name

#### 8.66.3.10 void Models::Project::hydrat ( int *id* ) [virtual]

[Project::hydrat](#) Insert project data which is specified by *id* in the database.

##### Parameters

<i>id</i>	<a href="#">Project</a> identify
-----------	----------------------------------

Implements [Models::IModel](#).

#### 8.66.3.11 bool Models::Project::operator!= ( const **Project** & *p* )

[Project::operator ==](#) Re-define the operator "!=" to compare if the current project is differnt to the other **Project** *p*  
Return TRUE if both projects are different, else FALSE.

##### Parameters

<i>c</i>	<a href="#">Project</a> to compare
----------	------------------------------------

##### Returns

boolean

#### 8.66.3.12 bool Models::Project::operator< ( const **Project** & *p* ) const

[Project::operator <](#) defines the operator "<" to compare two **Project** and to see if the first is anterior to the second.

## Parameters

<i>b</i>	the <a href="#">Project</a> to compare with the current <a href="#">Project</a>
----------	---------------------------------------------------------------------------------

## Returns

true if the [Project](#) are different else false

8.66.3.13 bool Models::Project::operator==( const [Project](#) & *p* )

[Project::operator ==](#) Re-define the operator "==" to compare if the current project is the same to the other [Project](#) *p*  
Return TRUE if both projects are the same, else FALSE.

## Parameters

<i>c</i>	<a href="#">Project</a> to compare
----------	------------------------------------

## Returns

boolean

8.66.3.14 void Models::Project::setBeginDate ( [QDate](#) *beginDate* )

[Project::setBeginDate](#) Modify *beginDate* of a [Project](#)

## Parameters

<i>beginDate</i>	the new date of creation of the project
------------------	-----------------------------------------

8.66.3.15 void Models::Project::setCost ( double *cost* )

[Project::setCost](#) Modify the [Project](#) *cost*

## Parameters

<i>cost</i>	the projectCost
-------------	-----------------

8.66.3.16 void Models::Project::setCustomer ( [QSharedPointer](#)< [Customer](#) > *customer* )

[Project::setCustomer](#) Modify the *customer* linked to this project.

## Parameters

<i>customer</i>	New customer associated to this project
-----------------	-----------------------------------------

8.66.3.17 void Models::Project::setDailyRate ( double *dailyRate* )

[Project::setDailyRate](#) Modify the daily rate *dailyRate* of the current project.

## Parameters

---

<i>dailyRate</i>	New daily rate associated to the current project
------------------	--------------------------------------------------

8.66.3.18 void Models::Project::setDescription ( const QString & *description* )

[Project::setDescription](#) Modify the project *description*

Parameters

<i>description</i>	New project description
--------------------	-------------------------

8.66.3.19 void Models::Project::setEndDate ( QDate *endDate* )

[Project::setEndDate](#) Modify *endDate* of [Project](#)

Parameters

<i>endDate</i>	the new end date of the project
----------------	---------------------------------

8.66.3.20 void Models::Project::setName ( const QString & *name* )

[Project::setName](#) Modify the project *name*

Parameters

<i>name</i>	<a href="#">Project</a> name
-------------	------------------------------

The documentation for this class was generated from the following files:


- /home/travis/build/FACT-Team/FactDev/src/models/project.h
- /home/travis/build/FACT-Team/FactDev/src/models/project.cpp

## 8.67 Gui::Widgets::Delegates::ProjectComboDelegate Class Reference

The [ProjectComboDelegate](#) class.

```
#include <projectcombodelegate.h>
```

Inheritance diagram for Gui::Widgets::Delegates::ProjectComboDelegate:



### Public Member Functions

- [ProjectComboDelegate](#) (QSharedPointer< [Models::Customer](#) > c, QObject \*parent=0)  
[ProjectComboDelegate::ProjectComboDelegate](#).
- QWidget \* [createEditor](#) (QWidget \*parent, const QStyleOptionViewItem &option, const QModelIndex &index) const

[\*ProjectComboDelegate::createEditor\*](#) Return a ComboBox specified by *index* item defined by the parent widget and style option which are used to control how the editor widgets appears.

- void [\*paint\*](#) (QPainter \*painter, const QStyleOptionViewItem &option, const QModelIndex &index) const

[\*ProjectComboDelegate::paint\*](#) Renders the delegate using the given painter and style option for the item specified by *index*

- void [\*removeInCombo\*](#) (QList< int > &l)

[\*ProjectComboDelegate::removeInCombo\*](#) Remove the items contained in the list *l* into the current ComboBox.

- QMap< int, [\*Models::Project\*](#) > [\*getProjects\*](#) () const

[\*ProjectComboDelegate::getProjects\*](#) Return a list of projects linked to a Customer ID.

- bool [\*isLocked\*](#) () const

[\*ProjectComboDelegate::isLocked\*](#) Return TRUE if is locked else FALSE.

- void [\*setLocked\*](#) (bool locked)

[\*ProjectComboDelegate::setLocked\*](#) Change the state of the lock by a new value *locked*

### 8.67.1 Detailed Description

The [\*ProjectComboDelegate\*](#) class.

### 8.67.2 Constructor & Destructor Documentation

- 8.67.2.1 [\*Gui::Widgets::Delegates::ProjectComboDelegate::ProjectComboDelegate\*](#) ( QSharedPointer< [\*Models::Customer\*](#) > *c*, QObject \* *parent* = 0 )

[\*ProjectComboDelegate::ProjectComboDelegate\*](#).

Parameters

<i>c</i>	
<i>parent</i>	

### 8.67.3 Member Function Documentation

- 8.67.3.1 [\*QWidget \\* Gui::Widgets::Delegates::ProjectComboDelegate::createEditor\*](#) ( QWidget \* *parent*, const QStyleOptionViewItem & *option*, const QModelIndex & *index* ) const [virtual]

[\*ProjectComboDelegate::createEditor\*](#) Return a ComboBox specified by *index* item defined by the *parent* widget and style *option* which are used to control how the editor widgets appears.

Parameters

<i>parent</i>	Widget parent
<i>option</i>	Option style
<i>index</i>	Index for editing

Returns

ComboBox

Implements [\*Gui::Widgets::Delegates::ComboBoxDelegate\*](#).

- 8.67.3.2 [\*QMap< int, Models::Project > Gui::Widgets::Delegates::ProjectComboDelegate::getProjects\*](#) ( ) const

[\*ProjectComboDelegate::getProjects\*](#) Return a list of projects linked to a Customer ID.

## Returns

Projets of a Customer

8.67.3.3 `bool Gui::Widgets::Delegates::ProjectComboDelegate::isLocked ( ) const`

[ProjectComboDelegate::isLocked](#) Return TRUE if is locked else FALSE.

## Returns

boolean

8.67.3.4 `void Gui::Widgets::Delegates::ProjectComboDelegate::paint ( QPainter * painter, const QStyleOptionViewItem & option, const QModelIndex & index ) const` [virtual]

[ProjectComboDelegate::paint](#) Renders the delegate using the given *painter* and style *option* for the item specified by *index*

## Parameters

<i>parent</i>	Widget parent
<i>option</i>	Option style
<i>index</i>	Index for editing

Implements [Gui::Widgets::Delegates::ComboBoxDelegate](#).

8.67.3.5 `void Gui::Widgets::Delegates::ProjectComboDelegate::setLocked ( bool locked )`

[ProjectComboDelegate::setLocked](#) Change the state of the lock by a new value *locked*

## Parameters

<i>locked</i>	
---------------	--

The documentation for this class was generated from the following files:


- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/delegates/projectcombodelegate.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/delegates/projectcombodelegate.cpp

## 8.68 Gui::Widgets::WdgModels::ProjectContributoriesTableModel Class Reference

The [ProjectContributoriesTableModel](#) class Table model of contributories linked to projets.

```
#include <projectcontributoriестablemodel.h>
```

Inheritance diagram for Gui::Widgets::WdgModels::ProjectContributoriesTableModel:



### Public Member Functions

- [ProjectContributoriesTableModel](#) (QObject \*parent=0)



- [ProjectContributoriesTableModel::ProjectContributoriesTableModel](#) Construct a [ProjectContributoriesTableModel](#).*

  - int [rowCount](#) (const QModelIndex &) const
  - [ProjectContributoriesTableModel::rowCount](#) Number of contributories row.*
  - int [columnCount](#) (const QModelIndex &) const
  - [ProjectContributoriesTableModel::columnCount](#) Number of column of a contributory.*
  - QVariant [data](#) (const QModelIndex &index, int role) const
  - [ProjectContributoriesTableModel::data](#) Obtains data of a specify cell.*
  - QVariant [headerData](#) (int section, Qt::Orientation orientation, int role) const
  - [ProjectContributoriesTableModel::headerData](#) Obtains header title of table.*
  - bool [setData](#) (const QModelIndex &index, const QVariant &value, int role=Qt::EditRole)
  - [ProjectContributoriesTableModel::setData](#) Change data of a cell.*
  - Qt::ItemFlags [flags](#) (const QModelIndex &index) const
  - [ProjectContributoriesTableModel::flags](#) Differents table flags.*
  - void [append](#) (QPair< [Models::Project](#) \*, [Models::Rate](#) > p)
  - [ProjectContributoriesTableModel::append](#) Add a new rate p to a Project.*
  - void [append](#) ()
  - [ProjectContributoriesTableModel::append](#) Add the current element to the list.*
  - bool [allProjectsChosen](#) ()
  - [ProjectContributoriesTableModel::allProjectsChosen](#) Return TRUE if all projects have been selected else FALSE.*
  - QList< int > & [getSelectedProjects](#) ()
  - [ProjectContributoriesTableModel::getSelectedProjects](#) Return the list of the Project id which are selected.*
  - void [remove](#) (int index)
  - [ProjectContributoriesTableModel::remove](#) Remove the element to the index*
  - QPair< [Models::Project](#) \*, [Models::Rate](#) > [getProject](#) (const int row)
  - [ProjectContributoriesTableModel::getProject](#) Return the project and it rate linked which correspond to the row*
  - QList< QPair< [Models::Project](#) \*, [Models::Rate](#) > > [getProjects](#) (void)
  - [ProjectContributoriesTableModel::getProjects](#) Return a list of the set of projects and their rates linked.*

### 8.68.1 Detailed Description

The [ProjectContributoriesTableModel](#) class Table model of contributories linked to projects.

Author

Antoine de Roquemaurel

### 8.68.2 Constructor & Destructor Documentation

- 8.68.2.1 [Gui::Widgets::WdgModels::ProjectContributoriesTableModel::ProjectContributoriesTableModel \( QObject \\* parent = 0 \)](#)

[ProjectContributoriesTableModel::ProjectContributoriesTableModel](#) Construct a [ProjectContributoriesTableModel](#).

Parameters

<i>parent</i>	Parent widget
---------------	---------------

### 8.68.3 Member Function Documentation

8.68.3.1 `bool Gui::Widgets::WdgModels::ProjectContributoriesTableModel::allProjectsChosen ( )`

[ProjectContributoriesTableModel::allProjectsChosen](#) Return TRUE if all projects have been selected else FALSE.

Returns

boolean All projects selected

8.68.3.2 `void Gui::Widgets::WdgModels::ProjectContributoriesTableModel::append ( QPair< Models::Project *, Models::Rate > p )`

[ProjectContributoriesTableModel::append](#) Add a new rate  $p$  to a Project.

Parameters

$p$	
-----	--

8.68.3.3 `int Gui::Widgets::WdgModels::ProjectContributoriesTableModel::columnCount ( const QModelIndex & ) const`

[ProjectContributoriesTableModel::columnCount](#) Number of column of a contributory.

Returns

The number of column

8.68.3.4 `QVariant Gui::Widgets::WdgModels::ProjectContributoriesTableModel::data ( const QModelIndex & index, int role ) const`

[ProjectContributoriesTableModel::data](#) Obtains data of a specify cell.

Parameters

<i>index</i>	The cell who we want data
<i>role</i>	The role of set

Returns

The data of cell

8.68.3.5 `Qt::ItemFlags Gui::Widgets::WdgModels::ProjectContributoriesTableModel::flags ( const QModelIndex & index ) const`

[ProjectContributoriesTableModel::flags](#) Differents table flags.

Parameters

<i>index</i>	The cell who we want to know flags
--------------	------------------------------------

Returns

Flags

8.68.3.6 `QPair< Models::Project *, Models::Rate > Gui::Widgets::WdgModels::ProjectContributoriesTableModel::getProject ( const int row )`

[ProjectContributoriesTableModel::getProject](#) Return the project and it rate linked which correspond to the *row*

## Parameters

<i>row</i>	Row of the project to get
------------	---------------------------

## Returns

a Project and it rate

**8.68.3.7** `QList< QPair< Models::Project *, Models::Rate > > Gui::Widgets::WdgModels::ProjectContributoriesTableModel::getProjects ( void )`

[ProjectContributoriesTableModel::getProjects](#) Return a list of the set of projects and their rates linked.

## Returns

List of Projects and Rates linked

**8.68.3.8** `QList< int > & Gui::Widgets::WdgModels::ProjectContributoriesTableModel::getSelectedProjects ( )`

[ProjectContributoriesTableModel::getSelectedProjects](#) Return the list of the Project id which are selected.

## Returns

List of ID Project

**8.68.3.9** `QVariant Gui::Widgets::WdgModels::ProjectContributoriesTableModel::headerData ( int section, Qt::Orientation orientation, int role ) const`

[ProjectContributoriesTableModel::headerData](#) Obtains header title of table.

## Parameters

<i>section</i>	The number of column
<i>orientation</i>	The table orientation
<i>role</i>	

## Returns

The Title header of column

**8.68.3.10** `void Gui::Widgets::WdgModels::ProjectContributoriesTableModel::remove ( int index )`

[ProjectContributoriesTableModel::remove](#) Remove the element to the *index*

## Parameters

<i>index</i>	Index of the element to remove
--------------	--------------------------------

**8.68.3.11** `int Gui::Widgets::WdgModels::ProjectContributoriesTableModel::rowCount ( const QModelIndex & ) const`

[ProjectContributoriesTableModel::rowCount](#) Number of contributories row.

## Returns

The number of contributories

8.68.3.12 `bool Gui::Widgets::WdgModels::ProjectContributoriesTableModel::setData ( const QModelIndex & index, const QVariant & value, int role = Qt::EditRole )`

[ProjectContributoriesTableModel::setData](#) Change data of a cell.

## Parameters

<i>index</i>	The cell to change data
<i>value</i>	The new value
<i>role</i>	The role of cell

## Returns

True if we could edit

The documentation for this class was generated from the following files:


- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/widgetmodels/projectcontributoriestablemodel.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/widgetmodels/projectcontributoriestablemodel.cpp

## 8.69 Databases::ProjectDatabase Class Reference

The [ProjectDatabase](#) class Project table database.

```
#include <projectdatabase.h>
```

Inheritance diagram for Databases::ProjectDatabase:



### Public Member Functions

- [Models::Project](#) \* [getProject](#) (const int pld)  
*ProjectDatabase::getProject* Get informations about the project identified by 'pld'.
- [Models::Project](#) \* [getProject](#) (QStringQuery &q)  
*ProjectDatabase::getProject*.
- int [addProject](#) (const [Models::Project](#) &)  
*ProjectDatabase::addProject* Add the project 'pProject' to the database.
- void [updateProject](#) (const [Models::Project](#) &)  
*ProjectDatabase::updateProject* Update informations about the project.
- void [removeProject](#) (const int pld)  
*removeProject* Remove the project with the id 'pld'
- int [getNbProjects](#) ()  
*ProjectDatabase::getNbProjects* Return the number of projects existing.
- int [getNbProjectsForACustomer](#) (const int pld)  
*ProjectDatabase::getNbProjectsForACustomer* Return the number of projects existing for an identify customer pld
- QMap< int, [Models::Project](#) > [getProjectsOfCustomer](#) (QSharedPointer< [Models::Customer](#) > c)  
*getProjectsOfCustomer* Return all projects of a customer
- QList< [Models::Project](#) > [getProjects](#) (const int customerId)  
*getProjects* Return all projects of a customer
- [WdgModels::ProjectsTableModel](#) \* [getProjectsTable](#) (const int pld) throw (DbException\*)  
*getProjectsTable* Return all projects of a customer in QStandardItemModel
- QSharedPointer< [Project](#) > [updateProject](#) (QStringQuery &q)  
*getProject* Obtain a project without new query
- QList< [Project](#) \* > [getAllProjects](#) ()  
*Project::getAllProjects* Return the list of projects.

## Static Public Member Functions

- static [ProjectDatabase](#) \* [instance](#) () throw (DbException\*)  
*ProjectDatabase::getInstance* Return an instance of [ProjectDatabase](#).

## Additional Inherited Members

### 8.69.1 Detailed Description

The [ProjectDatabase](#) class Project table database.

#### Author

Florent Berbie

#### See Also

[Database](#)  
[Project](#)

### 8.69.2 Member Function Documentation

8.69.2.1 int Databases::ProjectDatabase::addProject ( const Models::Project & *pProject* )

[ProjectDatabase](#)::addProject Add the project 'pProject' to the database.

#### Returns

project id

8.69.2.2 QList< [Project](#) \* > Databases::ProjectDatabase::getAllProjects ( )

[Project](#)::getAllProjects Return the list of projects.

#### Returns

Projects list

8.69.2.3 int Databases::ProjectDatabase::getNbProjects ( )

[ProjectDatabase](#)::getNbProjects Return the number of projects existing.

#### Returns

number of projects

8.69.2.4 int Databases::ProjectDatabase::getNbProjectsForACustomer ( const int *pld* )

[ProjectDatabase](#)::getNbProjectsForACustomer Return the number of projects existing for an identify customer *pld*

## Parameters

<i>pld</i>	Project id
------------	------------

## Returns

number of projects

**8.69.2.5 Models::Project \* Databases::ProjectDatabase::getProject ( const int *pld* )**

[ProjectDatabase::getProject](#) Get informations about the project identified by 'pld'.

## Parameters

<i>pld</i>	project
------------	---------

## Returns

the project

**8.69.2.6 Models::Project \* Databases::ProjectDatabase::getProject ( QSqlQuery & *q* )**

[ProjectDatabase::getProject](#).

## Parameters

<i>q</i>	
----------	--

## Returns

**8.69.2.7 QList< Project > Databases::ProjectDatabase::getProjects ( const int *customerId* )**

getProjects Return all projects of a customer

## Parameters

<i>customerId</i>	The customer id
-------------------	-----------------

## Returns

List with all projects of customer

**8.69.2.8 QMap< int, Models::Project > Databases::ProjectDatabase::getProjectsOfCustomer ( QSharedPointer< Models::Customer > *c* )**

getProjectsOfCustomer Return all projects of a customer

## Parameters

<i>c</i>	The customer
----------	--------------

## Returns

All projects of c with id in key

8.69.2.9 **WdgModels::ProjectsTableModel** \* **Databases::ProjectDatabase::getProjectsTable** ( const int *pld* ) throw **DbException** \*)

getProjectsTable Return all projects of a customer in QStandardItemModel



## Parameters

<i>filter</i>	Select only projects who are specified by <i>filter</i>
---------------	---------------------------------------------------------

## Returns

QStandardItemModel an item model for QTableView

8.69.2.10 **ProjectDatabase \* Databases::ProjectDatabase::instance ( ) throw DbException \*** [static]

ProjectDatabase::getInstance Return an instance of [ProjectDatabase](#).

## Returns

Instance of [ProjectDatabase](#)

8.69.2.11 **void Databases::ProjectDatabase::removeProject ( const int *pld* )**

removeProject Remove the project with the id 'pld'

## Parameters

<i>pld</i>	project id
------------	------------

8.69.2.12 **QSharedPointer< Models::Project > Databases::ProjectDatabase::updateProject ( QSqlQuery & *q* )**

getProject Obtain a project without new query

## Parameters

<i>q</i>	The query to use
----------	------------------

## Returns


The project linked to q

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/database/projectdatabase.h
- /home/travis/build/FACT-Team/FactDev/src/database/projectdatabase.cpp

## 8.70 ProjectDatabaseTest Class Reference

Inheritance diagram for ProjectDatabaseTest:




The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/tests/database/projectdatabasetest.h
- /home/travis/build/FACT-Team/FactDev/tests/database/projectdatabasetest.cpp

## 8.71 ProjectModelTest Class Reference

Inheritance diagram for ProjectModelTest:



The documentation for this class was generated from the following files:


- /home/travis/build/FACT-Team/FactDev/tests/models/projectmodeltest.h
- /home/travis/build/FACT-Team/FactDev/tests/models/projectmodeltest.cpp

## 8.72 Gui::Widgets::WdgModels::ProjectsTableModel Class Reference

The [ProjectsTableModel](#) class for a Project table.

```
#include <projectstablemodel.h>
```

Inheritance diagram for Gui::Widgets::WdgModels::ProjectsTableModel:



### Public Member Functions

- [ProjectsTableModel](#) ()  
*ProjectsTableModel::ProjectsTableModel* Construct a [ProjectsTableModel](#).
- int [rowCount](#) (const QModelIndex &) const  
*ProjectsTableModel::rowCount* Number of projects row.
- int [columnCount](#) (const QModelIndex &) const  
*ProjectsTableModel::columnCount* Number of column of a Project.
- QVariant [data](#) (const QModelIndex &index, int role=Qt::DisplayRole) const  
*ProjectsTableModel::data* Obtains data of a specify cell.
- QVariant [headerData](#) (int section, Qt::Orientation orientation, int role=Qt::DisplayRole) const  
*ProjectsTableModel::headerData* Obtains header title of table.
- bool [setData](#) (const QModelIndex &index, const QVariant &value, int role=Qt::EditRole)  
*ProjectsTableModel::setData* Change data of a cell.
- void [append](#) (const [Project](#) &project)  
*ProjectsTableModel::append* Add a new line in table.
- void [remove](#) (const int i)  
*ProjectsTableModel::remove* Remove a line.
- Qt::ItemFlags [flags](#) (const QModelIndex &index) const  
*ProjectsTableModel::flags* Differents table flags.
- int [count](#) ()  
*ProjectsTableModel::count* Number of projects in table.
- QList< [Project](#) > [getProjects](#) () const  
*ProjectsTableModel::getProjects* Return the list of projects.

### 8.72.1 Detailed Description

The [ProjectsTableModel](#) class for a Project table.

#### Author

Florent Berbie

#### See Also

[Project](#)

### 8.72.2 Constructor & Destructor Documentation

#### 8.72.2.1 Gui::Widgets::WdgModels::ProjectsTableModel::ProjectsTableModel ( )

[ProjectsTableModel::ProjectsTableModel](#) Construct a [ProjectsTableModel](#).

##### Parameters

<i>parent</i>	Parent widget
---------------	---------------

### 8.72.3 Member Function Documentation

#### 8.72.3.1 void Gui::Widgets::WdgModels::ProjectsTableModel::append ( const Project & *project* )

[ProjectsTableModel::append](#) Add a new line in table.

##### Parameters

<i>Project</i>	The new Project
----------------	-----------------

#### 8.72.3.2 int Gui::Widgets::WdgModels::ProjectsTableModel::columnCount ( const QModelIndex & ) const

[ProjectsTableModel::columnCount](#) Number of column of a Project.

##### Returns

The number of column

#### 8.72.3.3 int Gui::Widgets::WdgModels::ProjectsTableModel::count ( )

[ProjectsTableModel::count](#) Number of projects in table.

##### Returns

The number of projects

#### 8.72.3.4 QVariant Gui::Widgets::WdgModels::ProjectsTableModel::data ( const QModelIndex & *index*, int *role* = Qt::DisplayRole ) const

[ProjectsTableModel::data](#) Obtains data of a specify cell.

## Parameters

<i>index</i>	The cell who we want data
<i>role</i>	The role of set

## Returns

The data of cell

8.72.3.5 `Qt::ItemFlags Gui::Widgets::WdgModels::ProjectsTableModel::flags ( const QModelIndex & index ) const`

[ProjectsTableModel::flags](#) Differents table flags.

## Parameters

<i>index</i>	The cell who we want to know flags
--------------	------------------------------------

## Returns

Flags

8.72.3.6 `QList< Project > Gui::Widgets::WdgModels::ProjectsTableModel::getProjects ( void ) const`

[ProjectsTableModel::getProjects](#) Return the list of projects.

## Returns

list of projects

8.72.3.7 `QVariant Gui::Widgets::WdgModels::ProjectsTableModel::headerData ( int section, Qt::Orientation orientation, int role = Qt::DisplayRole ) const`

[ProjectsTableModel::headerData](#) Obtains header title of table.

## Parameters

<i>section</i>	The number of column
<i>orientation</i>	The table orientation
<i>role</i>	

## Returns

The Title header of column

8.72.3.8 `void Gui::Widgets::WdgModels::ProjectsTableModel::remove ( const int i )`

[ProjectsTableModel::remove](#) Remove a line.

## Parameters

<i>i</i>	The number of line to remove
----------	------------------------------

8.72.3.9 `int Gui::Widgets::WdgModels::ProjectsTableModel::rowCount ( const QModelIndex & ) const`

[ProjectsTableModel::rowCount](#) Number of projects row.

#### Returns

The number of projects

8.72.3.10 `bool Gui::Widgets::WdgModels::ProjectsTableModel::setData ( const QModelIndex & index, const QVariant & value, int role = Qt::EditRole )`

[ProjectsTableModel::setData](#) Change data of a cell.

#### Parameters

<i>index</i>	The cell to change data
<i>value</i>	The new value
<i>role</i>	The role of cell

#### Returns

True if we could edit

The documentation for this class was generated from the following files:


- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/widgetsmodels/projectstablemodel.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/widgetsmodels/projectstablemodel.cpp

## 8.73 Gui::Widgets::ProjectsWidget Class Reference

The [ProjectsWidget](#) class Actions on Project.

```
#include <projectswidget.h>
```

Inheritance diagram for Gui::Widgets::ProjectsWidget:



#### Public Slots

- void [newProject](#) ()  
*ProjectsWidget::addProject* Event which sends a signal to add a new project.
- void [editSelectedProject](#) ()  
*ProjectsWidget::editSelectedProject* Event which sends a signal to edit the project selected.
- void [removeSelectedProject](#) ()  
*ProjectsWidget::removeSelectedProject* Event which sends a signal to remove the project selected.
- void [updateBtn](#) (bool b)  
*ProjectsWidget::updateBtn* Update the toolbar in tblProjects.

## Signals

- void [addProject](#) ()  
*[ProjectsWidget::addProject](#) Add a new project to the current Customer.*
- void [editProject](#) ()  
*[ProjectsWidget::editProject](#) Edit the current Customer selected.*
- void [removeProject](#) ()  
*[ProjectsWidget::removeProject](#) Remove the current Customer selected.*

## Public Member Functions

- [ProjectsWidget](#) (QWidget \*parent=0)  
*[ProjectsWidget::ProjectsWidget](#) Construct a [ProjectsWidget](#).*

### 8.73.1 Detailed Description

The [ProjectsWidget](#) class Actions on Project.

#### Author

Florent Berbie

### 8.73.2 Constructor & Destructor Documentation

8.73.2.1 [Gui::Widgets::ProjectsWidget::ProjectsWidget](#) ( [QWidget](#) \* *parent* = 0 ) [explicit]

[ProjectsWidget::ProjectsWidget](#) Construct a [ProjectsWidget](#).

#### Parameters

<i>parent</i>	
---------------	--

### 8.73.3 Member Function Documentation

8.73.3.1 void [Gui::Widgets::ProjectsWidget::updateBtn](#) ( bool *b* ) [slot]

[ProjectsWidget::updateBtn](#) Update the toolbar in tblProjects.

#### Parameters

<i>boolean</i>	if a row is selected
----------------	----------------------


The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/projectswidget.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/projectswidget.cpp

## 8.74 Mustache::QtVariantContext Class Reference

```
#include <mustache.h>
```

Inheritance diagram for [Mustache::QtVariantContext](#):



## Public Types

- typedef QString(\* [fn\\_t](#))(const QString &, [Mustache::Renderer](#) \*, [Mustache::Context](#) \*)

## Public Member Functions

- **QtVariantContext** (const QVariant &root, [PartialResolver](#) \*resolver=0)
- virtual QString [stringValue](#) (const QString &key) const
- virtual bool [isFalse](#) (const QString &key) const
- virtual int [listCount](#) (const QString &key) const
- virtual void [push](#) (const QString &key, int index=-1)
- virtual void [pop](#) ()
- virtual bool [canEval](#) (const QString &key) const
- virtual QString [eval](#) (const QString &key, const QString &\_template, [Mustache::Renderer](#) \*renderer)

### 8.74.1 Detailed Description

A context implementation which wraps a QVariantHash or QVariantMap.

### 8.74.2 Member Typedef Documentation

8.74.2.1 typedef QString(\* [Mustache::QtVariantContext::fn\\_t](#))(const QString &, [Mustache::Renderer](#) \*, [Mustache::Context](#) \*)

Construct a [QtVariantContext](#) which wraps a dictionary in a QVariantHash or a QVariantMap.

### 8.74.3 Member Function Documentation

8.74.3.1 bool [QtVariantContext::canEval](#) ( const QString & *key* ) const [virtual]

Returns true if [eval\(\)](#) should be used to render section tags using *key*. If [canEval\(\)](#) returns true for a key, the renderer will pass the literal, unrendered block of text for the section to [eval\(\)](#) and replace the section with the result. [canEval\(\)](#) and [eval\(\)](#) are equivalents for callable objects (eg. lambdas) in other Mustache implementations.

The default implementation always returns false.

Reimplemented from [Mustache::Context](#).

Reimplemented in [CounterContext](#), and [CounterContext](#).

8.74.3.2 QString [QtVariantContext::eval](#) ( const QString & *key*, const QString & *\_template*, [Mustache::Renderer](#) \* *renderer* ) [virtual]

Callback used to render a template section with the given *key*. *renderer* will substitute the original section tag with the result of [eval\(\)](#).

The default implementation returns an empty string.

Reimplemented from [Mustache::Context](#).

Reimplemented in [CounterContext](#), and [CounterContext](#).

#### 8.74.3.3 `bool QtVariantContext::isFalse ( const QString & key ) const` [virtual]

Returns true if the value for `key` is 'false' or an empty list. 'False' values typically include empty strings, the boolean value false etc.

When processing a section Mustache tag, the section is not rendered if the key is false, or for an inverted section tag, the section is only rendered if the key is false.

Implements [Mustache::Context](#).

#### 8.74.3.4 `int QtVariantContext::listCount ( const QString & key ) const` [virtual]

Returns the number of items in the list value for `key` or 0 if the value for `key` is not a list.

Implements [Mustache::Context](#).

#### 8.74.3.5 `void QtVariantContext::pop ( )` [virtual]

Exit the current context.

Implements [Mustache::Context](#).

#### 8.74.3.6 `void QtVariantContext::push ( const QString & key, int index = -1 )` [virtual]

Set the current context to the value for `key`. If `index` is  $\geq 0$ , set the current context to the `index`'th value in the list value for `key`.

Implements [Mustache::Context](#).

#### 8.74.3.7 `QString QtVariantContext::stringValue ( const QString & key ) const` [virtual]

Returns a string representation of the value for `key` in the current context. This is used to replace a Mustache value tag.

Implements [Mustache::Context](#).

Reimplemented in [CounterContext](#), and [CounterContext](#).

The documentation for this class was generated from the following files:

- `/home/travis/build/FACT-Team/FactDev/src/libs/qt-mustache/src/mustache.h`
- `/home/travis/build/FACT-Team/FactDev/src/libs/qt-mustache/src/mustache.cpp`

## 8.75 Models::Rate Class Reference

The [Rate](#) class [Rate](#) of a prestation.

```
#include <rate.h>
```

### Public Member Functions

- [Rate](#) ()



- [Rate::Rate](#) Construct a [Rate](#).
- [Rate](#) (double hourly)  
[Rate::Rate](#) Construct a [Rate](#) with an hourly rate.
- [Rate](#) (int idBilling, int idProject)  
[Rate::Rate](#) Construct a [Rate](#) for the [Billing](#) with idBilling as identify and from the project identified by idProject
- void [setDailyRate](#) (const double &)  
[Rate::setDailyRate](#) Modify the daily rate with the new value.
- void [setHourlyRate](#) (const double &)  
[Rate::setHourlyRate](#) Modify the hourly rate with the new value.
- double [getDailyRate](#) () const  
[Rate::getDailyRate](#) Return the daily rate.
- double [getHourlyRate](#) () const  
[Rate::getHourlyRate](#) Return the hourly rate.
- int [getNbDailyHours](#) () const  
[Rate::getNbDailyHours](#) Return the number of daily hours.
- double [getLegalRate](#) () const  
[Rate::getLegalRate](#) Return the legal rate.

### 8.75.1 Detailed Description

The [Rate](#) class [Rate](#) of a prestation.

Author

Antoine de Roquemaurel

### 8.75.2 Constructor & Destructor Documentation

#### 8.75.2.1 Models::Rate::Rate ( double hourly )

[Rate::Rate](#) Construct a [Rate](#) with an hourly rate.

Parameters

<i>hourly</i>	Hourly rate
---------------	-------------

#### 8.75.2.2 Models::Rate::Rate ( int idBilling, int idProject )

[Rate::Rate](#) Construct a [Rate](#) for the [Billing](#) with idBilling as identify and from the project identified by idProject

Parameters

<i>idBilling</i>	<a href="#">Billing</a> identify
<i>idProject</i>	<a href="#">Project</a> identify

### 8.75.3 Member Function Documentation

#### 8.75.3.1 double Models::Rate::getDailyRate ( ) const

[Rate::getDailyRate](#) Return the daily rate.

Returns

8.75.3.2 `double Models::Rate::getHourlyRate ( ) const`

[Rate::getHourlyRate](#) Return the hourly rate.

Returns

8.75.3.3 `double Models::Rate::getLegalRate ( ) const`

[Rate::getLegalRate](#) Return the legal rate.

Returns

8.75.3.4 `int Models::Rate::getNbDailyHours ( ) const`

[Rate::getNbDailyHours](#) Return the number of daily hours.


Returns

The documentation for this class was generated from the following files:

- `/home/travis/build/FACT-Team/FactDev/src/models/rate.h`
- `/home/travis/build/FACT-Team/FactDev/src/models/rate.cpp`

## 8.76 Databases::RateDatabase Class Reference

Inheritance diagram for `Databases::RateDatabase`:



### Public Member Functions

- void [addRateProject](#) (int idProject, int idBilling, double hourlyRate)  
*[RateDatabase::addRateProject](#) Add a new rate hourlyRate to the Project identified by idProject of the Billing with idBilling as identify.*
- double [getRate](#) (const int idBilling, const int idProject) const  
*[RateDatabase::getRate](#) Return the rate of the Project identified by idProject of the Billing with idBilling as identify.*
- void [updateRateProject](#) (int idProject, int idBilling, double hourlyRate)  
*[RateDatabase::updateRateProject](#) Update the current rate by the new hourlyRate of the Project identified by idProject of the Billing with idBilling as identify.*

## Static Public Member Functions

- static [RateDatabase](#) \* [instance](#) () throw (DbException\*)  
*RateDatabase::getInstance* Return an instance of [RateDatabase](#).

## Additional Inherited Members

### 8.76.1 Member Function Documentation

8.76.1.1 void Databases::RateDatabase::addRateProject ( int *idProject*, int *idBilling*, double *hourlyRate* )

[RateDatabase::addRateProject](#) Add a new rate *hourlyRate* to the Project identified by *idProject* of the Billing with *idBilling* as identify.

#### Parameters

<i>idProject</i>	Project identify
<i>idBilling</i>	Billing identify
<i>hourlyRate</i>	New hourly rate

8.76.1.2 double Databases::RateDatabase::getRate ( const int *idBilling*, const int *idProject* ) const

[RateDatabase::getRate](#) Return the rate of the Project identified by *idProject* of the Billing with *idBilling* as identify.

#### Parameters

<i>idBilling</i>	Billing identify
<i>idProject</i>	Project identify

#### Returns

Rate of the Project of a Billing

8.76.1.3 [RateDatabase](#) \* Databases::RateDatabase::instance ( ) throw DbException \* ) [static]

[RateDatabase::getInstance](#) Return an instance of [RateDatabase](#).

#### Returns

Instance of [RateDatabase](#)

8.76.1.4 void Databases::RateDatabase::updateRateProject ( int *idProject*, int *idBilling*, double *hourlyRate* )

[RateDatabase::updateRateProject](#) Update the current rate by the new *hourlyRate* of the Project identified by *idProject* of the Billing with *idBilling* as identify.

#### Parameters

<i>idProject</i>	Project identify
<i>idBilling</i>	Billing identify
<i>hourlyRate</i>	New hourly rate

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/database/ratedatabase.h
- /home/travis/build/FACT-Team/FactDev/src/database/ratedatabase.cpp

## 8.77 RateModelTest Class Reference

Inheritance diagram for RateModelTest:



The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/tests/models/ratemodeltest.h
- /home/travis/build/FACT-Team/FactDev/tests/models/ratemodeltest.cpp

## 8.78 Gui::Widgets::RateWidget Class Reference

Class for display Rate.

```
#include <ratewidget.h>
```

Inheritance diagram for Gui::Widgets::RateWidget:



### Public Slots

- void [setDailyRate](#) ()  
*setDailyRate Set a new value for the daily rate*
- void [setHourlyRate](#) ()  
*setHourlyRate Set a new value for the hourly rate*

### Public Member Functions

- [RateWidget](#) (QWidget \*parent=0)  
*RateWidget::RateWidget Construct a rate widget.*
- void [initRate](#) ()  
*RateWidget::initRate Initialize the rate.*
- void [setWidgetDailyRateValue](#) (double value)  
*RateWidget::setWidgetDailyRateValue Modify the value of the daily rate spin box component.*
- double [getDailyRate](#) ()  
*RateWidget::getDailyRate Get the daily rate.*
- double [getHourlyRate](#) ()  
*RateWidget::getHourlyRate Get the hourly rate.*
- void [setWidgetHourlyRateValue](#) (double value)  
*RateWidget::setWidgetHourlyRateValue Modify the value of the hourly rate spin box component.*
- void [updateConversionRate](#) ()  
*updateConversionRate Update daily rate or hourly rate*

### 8.78.1 Detailed Description

Class for display Rate.

Author

Florent Berbie

### 8.78.2 Constructor & Destructor Documentation

8.78.2.1 `Gui::Widgets::RateWidget::RateWidget ( QWidget * parent = 0 )` `[explicit]`

[RateWidget::RateWidget](#) Construct a rate widget.

Parameters

<i>parent</i>	The QWidget parent
---------------	--------------------

### 8.78.3 Member Function Documentation

8.78.3.1 `double Gui::Widgets::RateWidget::getDailyRate ( )`

[RateWidget::getDailyRate](#) Get the daily rate.

Returns

The daily rate

8.78.3.2 `double Gui::Widgets::RateWidget::getHourlyRate ( )`

[RateWidget::getHourlyRate](#) Get the hourly rate.

Returns

The hourly rate

8.78.3.3 `void Gui::Widgets::RateWidget::setDailyRate ( )` `[slot]`

[setDailyRate](#) Set a new value for the daily rate

Parameters

<i>dailyRate</i>	The new daily rate
------------------	--------------------

8.78.3.4 `void Gui::Widgets::RateWidget::setHourlyRate ( )` `[slot]`

[setHourlyRate](#) Set a new value for the hourly rate

Parameters

<i>hourlyRate</i>	The new hourly rate
-------------------	---------------------

8.78.3.5 `void Gui::Widgets::RateWidget::setWidgetDailyRateValue ( double value )`

[RateWidget::setWidgetDailyRateValue](#) Modify the *value* of the daily rate spin box component.

## Parameters

<i>value</i>	New Value
--------------	-----------

8.78.3.6 void Gui::Widgets::RateWidget::setWidgetHourlyRateValue ( double *value* )

[RateWidget::setWidgetHourlyRateValue](#) Modify the *value* of the hourly rate spin box component.

## Parameters

<i>value</i>	New value
--------------	-----------

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/ratewidget.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/ratewidget.cpp

## 8.79 Mustache::Renderer Class Reference

```
#include <mustache.h>
```

### Public Member Functions

- QString [render](#) (const QString &\_template, [Context](#) \*context)
- QString [error](#) () const
- int [errorPos](#) () const
- QString [errorPartial](#) () const
- void [setTagMarkers](#) (const QString &startMarker, const QString &endMarker)

### 8.79.1 Detailed Description

Renders Mustache templates, replacing mustache tags with values from a provided context.

### 8.79.2 Member Function Documentation

#### 8.79.2.1 QString Renderer::error ( ) const

Returns a message describing the last error encountered by the previous [render\(\)](#) call.

#### 8.79.2.2 QString Renderer::errorPartial ( ) const

Returns the name of the partial where the error occurred, or an empty string if the error occurred in the main template.

#### 8.79.2.3 int Renderer::errorPos ( ) const

Returns the position in the template where the last error occurred when rendering the template or -1 if no error occurred.

If the error occurred in a partial template, the returned position is the offset in the partial template.

8.79.2.4 QString Renderer::render ( const QString & *\_template*, Context \* *context* )

Render a Mustache template, using `context` to fetch the values used to replace Mustache tags.

8.79.2.5 void Renderer::setTagMarkers ( const QString & *startMarker*, const QString & *endMarker* )

Sets the default tag start and end markers. This can be overridden within a template.

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/libs/qt-mustache/src/mustache.h
- /home/travis/build/FACT-Team/FactDev/src/libs/qt-mustache/src/mustache.cpp

## 8.80 Models::Search Class Reference

The [Search](#) class.

```
#include <search.h>
```

### Public Member Functions

- [Search](#) ()  
*Search::Search* Construct a search.
- [~Search](#) ()  
*Search::Search* Destruct a search.
- QString [getFilter](#) ()  
*Search::getFilter* Return the search filter.
- void [filterOnVarcharElements](#) (QString &filter, const QStringList list, QString element)  
*Search::filterOnVarcharElements* *Search*, for each word of the list from the filter, if it corresponds to the element in the database.
- void [filterOnNumberElements](#) (QString &filter, const QStringList list, QString element)  
*Search::filterOnNumberElements* *Search*, for each number of the list from the filter, if it corresponds to the element in the database.
- void [filterOnCompany](#) (QString &filter, const QStringList list)  
*Search::filterOnCompany* *Search* all companies contained in the list of the filter
- void [filterOnReferentLastname](#) (QString &filter, const QStringList list)  
*Search::filterOnReferentLastname* *Search* all referents last name contained in the list of the filter
- void [filterOnProjects](#) (QString &filter, const QStringList list)  
*Search::filterOnProjects* *Search* all projects contained in the list of the filter
- void [filterOnContributories](#) (QString &filter, const QStringList list)  
*Search::filterOnContributories* *Search* all contributories contained in the list of the filter
- void [filterOnBillsOrQuotes](#) (QString &filter, const QStringList list)  
*Search::filterOnBillsOrQuotes* *Search* all bills or quotes which are contained in the list of the filter
- void [filterOnCustomersWithoutProject](#) (QString &filter, const QStringList list)  
*Search::filterOnCustomersWithoutProject* *Search* all customers which are contained in the list of the filter
- bool [getSearchInCompanies](#) () const  
*Search::getSearchInCompanies* Return if we search a company.
- void [setSearchInCompanies](#) (bool searchInCompanies)  
*Search::setSearchInCompanies* Modify the filter of companies search.
- bool [getSearchInReferentLastname](#) () const  
*Search::getSearchInReferentLastname* Return if we search a Last name referent.
- void [setSearchInReferentLastname](#) (bool searchInReferentLastname)

- [Search::setSearchInReferentLastname](#) *Modify the filter of referents last name search.*
- bool [getSearchInProjects](#) () const  
[Search::getSearchInProjects](#) *Return TRUE if it exists one or more projets in database.*
- void [setSearchInProjects](#) (bool searchInProjects)  
[Search::setSearchInProjects](#) *Modify the filter of projects search.*
- bool [searchInContributories](#) () const  
[Search::getSearchInContributories](#) *Return TRUE if it exists one or more projets in database.*
- void [setSearchInContributories](#) (bool [searchInContributories](#))  
[Search::setSearchInContributories](#) *Modify the filter of contributories search.*
- bool [getSearchInBillsQuotes](#) () const  
[Search::searchInBillsQuotes](#) *Return TRUE if it exists one or more bills or quotes in database.*
- void [setSearchInBillsQuotes](#) (bool searchInBillsQuotes)  
[Search::setSearchInBillsQuotes](#) *Modify the filter of bills and quotes search.*
- bool [getGroupFilter](#) () const  
[Search::getGroupFilter](#) *Return if the filter is activated.*
- void [setGroupFilter](#) (bool [getGroupFilter](#))  
[Search::setGroupFilter](#) *Modify if we active search filter.*
- QString [getText](#) () const  
[Search::getText](#) *Return sql portion of filter.*
- void [setText](#) (const QString &[getText](#))  
[Search::setText](#) *Modify sql portion.*

### 8.80.1 Detailed Description

The [Search](#) class.

Author

Antoine de Roquemaurel  
 Florent Berbie

### 8.80.2 Member Function Documentation

#### 8.80.2.1 void Models::Search::filterOnBillsOrQuotes ( QString & *filter*, const QStringList *list* )

[Search::filterOnBillsOrQuotes](#) [Search](#) all bills or quotes which are contained in the *list* of the *filter*

Parameters

<i>filter</i>	Text inputed in searchbar
<i>list</i>	List of bills or quotes

#### 8.80.2.2 void Models::Search::filterOnCompany ( QString & *filter*, const QStringList *list* )

[Search::filterOnCompany](#) [Search](#) all companies contained in the *list* of the *filter*

Parameters

<i>filter</i>	Text inputed in searchbar
<i>list</i>	List of companies

#### 8.80.2.3 void Models::Search::filterOnContributories ( QString & *filter*, const QStringList *list* )

[Search::filterOnContributories](#) [Search](#) all contributories contained in the *list* of the *filter*



## Parameters

<i>filter</i>	Text inputted in searchbar
<i>list</i>	List of contributories

8.80.2.4 void Models::Search::filterOnCustomersWithoutProject ( QString & *filter*, const QStringList *list* )

[Search::filterOnCustomersWithoutProject Search](#) all customers which are contained in the *list* of the *filter*

## Parameters

<i>filter</i>	Text inputted in searchbar
<i>list</i>	List of bills or quotes

8.80.2.5 void Models::Search::filterOnNumberElements ( QString & *filter*, const QStringList *list*, QString *element* )

[Search::filterOnNumberElements Search](#), for each number of the *list* from the *filter*, if it corresponds to the *element* in the database.

## Parameters

<i>filter</i>	Text inputted in the searchbar
<i>list</i>	List of numbers from the <i>filter</i>
<i>element</i>	Attribute name into the database

8.80.2.6 void Models::Search::filterOnProjects ( QString & *filter*, const QStringList *list* )

[Search::filterOnProjects Search](#) all projects contained in the *list* of the *filter*

## Parameters

<i>filter</i>	Text inputted in searchbar
<i>list</i>	List of projects

8.80.2.7 void Models::Search::filterOnReferentLastname ( QString & *filter*, const QStringList *list* )

[Search::filterOnReferentLastname Search](#) all referents last name contained in the *list* of the *filter*

## Parameters

<i>filter</i>	Text inputted in searchbar
<i>list</i>	List of referent last name

8.80.2.8 void Models::Search::filterOnVarcharElements ( QString & *filter*, const QStringList *list*, QString *element* )

[Search::filterOnVarcharElements Search](#), for each word of the *list* from the *filter*, if it corresponds to the *element* in the database.

## Parameters

<i>filter</i>	Text inputted in the searchbar
<i>list</i>	List of words from the <i>filter</i>

<i>element</i>	Attribute name into the database
----------------	----------------------------------

#### 8.80.2.9 QString Models::Search::getFilter ( )

[Search::getFilter](#) Return the search filter.

##### Returns

filter selected (sql portion)

#### 8.80.2.10 bool Models::Search::getGroupFilter ( ) const

[Search::getGroupFilter](#) Return if the filter is activated.

##### Returns

boolean if search filter is activated

#### 8.80.2.11 bool Models::Search::getSearchInBillsQuotes ( ) const

[Search::searchInBillsQuotes](#) Return TRUE if it exists one or more bills or quotes in database.

##### Returns

boolean if bills or quotes are existing

#### 8.80.2.12 bool Models::Search::getSearchInCompanies ( ) const

[Search::getSearchInCompanies](#) Return if we search a company.

##### Returns

boolean if we search a company

#### 8.80.2.13 bool Models::Search::getSearchInProjects ( ) const

[Search::getSearchInProjects](#) Return TRUE if it exists one or more projects in database.

##### Returns

boolean if project are existing

#### 8.80.2.14 bool Models::Search::getSearchInReferentLastname ( ) const

[Search::getSearchInReferentLastname](#) Return if we search a Last name referent.

##### Returns

boolean if search concerns the last name of referent

**8.80.2.15** QString Models::Search::getText ( ) const

[Search::getText](#) Return sql portion of filter.

**Returns**

QString the sql portion

**8.80.2.16** bool Models::Search::searchInContributories ( ) const

[Search::getSearchInContributories](#) Return TRUE if it exists one or more projets in database.

**Returns**

boolean if contributories are existing

**8.80.2.17** void Models::Search::setGroupFilter ( bool *getGroupFilter* )

[Search::setGroupFilter](#) Modify if we active search filter.

**Parameters**

<i>getGroupFilter</i>	Get if filter is activated
-----------------------	----------------------------

**8.80.2.18** void Models::Search::setSearchInBillsQuotes ( bool *searchInBillsQuotes* )

[Search::setSearchInBillsQuotes](#) Modify the filter of bills and quotes search.

**Parameters**

<i>searchInBills- Quotes</i>	<a href="#">Search</a> in bills or quotes which are concerned
----------------------------------	---------------------------------------------------------------

**8.80.2.19** void Models::Search::setSearchInCompanies ( bool *searchInCompanies* )

[Search::setSearchInCompanies](#) Modify the filter of companies search.

**Parameters**

<i>getSearchIn- Companies</i>	<a href="#">Search</a> in companies is concerned
-----------------------------------	--------------------------------------------------

**8.80.2.20** void Models::Search::setSearchInContributories ( bool *searchInContributories* )

[Search::setSearchInContributories](#) Modify the filter of contributories search.

**Parameters**

<i>searchIn- Contributories</i>	<a href="#">Search</a> in contributories which are concerned
-------------------------------------	--------------------------------------------------------------

**8.80.2.21** void Models::Search::setSearchInProjects ( bool *searchInProjects* )

[Search::setSearchInProjects](#) Modify the filter of projects search.

## Parameters

<i>searchInProjects</i>	<a href="#">Search</a> in projects which are concerned
-------------------------	--------------------------------------------------------

8.80.2.22 void Models::Search::setSearchInReferentLastname ( bool *searchInReferentLastname* )

[Search::setSearchInReferentLastname](#) Modify the filter of referents last name search.

## Parameters

<i>searchIn-Referent-Lastname</i>	<a href="#">Search</a> in referents last name which are concerned
-----------------------------------	-------------------------------------------------------------------

8.80.2.23 void Models::Search::setText ( const QString & *getText* )

[Search::setText](#) Modify sql portion.

## Parameters

<i>getText</i>	Get sql portion
----------------	-----------------

The documentation for this class was generated from the following files:


- /home/travis/build/FACT-Team/FactDev/src/models/search.h
- /home/travis/build/FACT-Team/FactDev/src/models/search.cpp

## 8.81 Gui::Docks::SearchDock Class Reference

The [SearchDock](#) class Dock which contains search bar.

```
#include <searchdock.h>
```

Inheritance diagram for Gui::Docks::SearchDock:



### Public Slots

- void [search](#) (QString text)  
[SearchDock::search](#) Search elements in database which correspond to the text

### Signals

- void [textChanged](#) (QString text)  
[SearchDock::textChanged](#) Current text changed by text

## Public Member Functions

- [SearchDock](#) (QWidget \*parent=0, Qt::WindowFlags flags=0)  
[SearchDock::SearchDock](#) Construct a [SearchDock](#).

### 8.81.1 Detailed Description

The [SearchDock](#) class Dock which contains search bar.

### 8.81.2 Constructor & Destructor Documentation

8.81.2.1 `Gui::Docks::SearchDock::SearchDock ( QWidget * parent = 0, Qt::WindowFlags flags = 0 )` `[explicit]`

[SearchDock::SearchDock](#) Construct a [SearchDock](#).

Parameters

<i>parent</i>	Widget Parent
<i>flags</i>	Window flag

### 8.81.3 Member Function Documentation

8.81.3.1 `void Gui::Docks::SearchDock::search ( QString text )` `[slot]`

[SearchDock::search](#) Search elements in database which correspond to the *text*

Parameters

<i>text</i>	Element to search
-------------	-------------------

8.81.3.2 `void Gui::Docks::SearchDock::textChanged ( QString text )` `[signal]`

[SearchDock::textChanged](#) Current text changed by *text*

Parameters


<i>text</i>	New text
-------------	----------

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/docks/searchdock.h
- /home/travis/build/FACT-Team/FactDev/src/gui/docks/searchdock.cpp

## 8.82 searchTest Class Reference

Inheritance diagram for searchTest:



The documentation for this class was generated from the following files:


- /home/travis/build/FACT-Team/FactDev/tests/models/searchtest.h
- /home/travis/build/FACT-Team/FactDev/tests/models/searchtest.cpp

## 8.83 Gui::Widgets::searchWidget Class Reference

Class for search in database.

```
#include <searchwidget.h>
```

Inheritance diagram for Gui::Widgets::searchWidget:



### Public Slots

- void [search](#) (QString toSearch)  
*searchWidget::launch a search*
- void [getCustomerData](#) ()  
*searchWidget::getCustomerData Return data on the customer selected in the QTableView and display this data (First-name, Lastname, Company)*

### Signals

- void [selectCustomer](#) ()  
*searchWidget::selectCustomer Signal that the Customer selected has changed*

### Public Member Functions

- [searchWidget](#) (QWidget \*parent=0)  
*searchWidget::searchWidget Construct a search widget*
- int [getCurrentCustomerId](#) ()  
*searchWidget::getCurrentCustomerId Return the id of the customer selected in the table*
- bool [isCustomerSelected](#) () const  
*searchWidget::isCustomerSelected Return TRUE if a customer is selected, else FALSE*
- void [selectCustomer](#) (int id)  
*searchWidget::selectCustomer Select the Customer with it id*
- int [getIdCustomer](#) () const  
*searchWidget::getIdCustomer Return the Customer id of the Customer line selected*
- void [setIdCustomer](#) (int idCustomer)  
*searchWidget::setIdCustomer Change the customer id by the new idCustomer*

#### 8.83.1 Detailed Description

Class for search in database.

Author

Antoine de Roquemaurel

## 8.83.2 Constructor & Destructor Documentation

8.83.2.1 `Gui::Widgets::searchWidget::searchWidget ( QWidget * parent = 0 )` `[explicit]`

[searchWidget::searchWidget](#) Construct a search widget

Parameters

<i>parent</i>	The QWidget parent
---------------	--------------------

## 8.83.3 Member Function Documentation

8.83.3.1 `int Gui::Widgets::searchWidget::getCurrentCustomerId ( )`

[searchWidget::getCurrentCustomerId](#) Return the id of the customer selected in the table

Returns

id of the current customer

8.83.3.2 `int Gui::Widgets::searchWidget::getIdCustomer ( ) const`

[searchWidget::getIdCustomer](#) Return the Customer id of the Customer line selected

Returns

The Customer ID

8.83.3.3 `bool Gui::Widgets::searchWidget::isCustomerSelected ( ) const`

[searchWidget::isCustomerSelected](#) Return TRUE if a customer is selected, else FALSE

Returns

boolean

8.83.3.4 `void Gui::Widgets::searchWidget::search ( QString toSearch )` `[slot]`

[searchWidget::launch](#) a search

Parameters

<i>toSearch</i>	The value to search
-----------------	---------------------

8.83.3.5 `void Gui::Widgets::searchWidget::selectCustomer ( int id )`

[searchWidget::selectCustomer](#) Select the Customer with it *id*

Parameters

<i>id</i>	Customer ID
-----------	-------------

8.83.3.6 `void Gui::Widgets::searchWidget::setIdCustomer ( int idCustomer )`

[searchWidget::setIdCustomer](#) Change the customer id by the new *idCustomer*

## Parameters

<i>idCustomer</i>	Customer id
-------------------	-------------

The documentation for this class was generated from the following files:


- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/searchwidget.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/searchwidget.cpp

## 8.84 Gui::Dialogs::StartedWindowsDialog Class Reference

The [StartedWindowsDialog](#) class Construct a Windows for the first begin.

```
#include <startedwindowsdialog.h>
```

Inheritance diagram for Gui::Dialogs::StartedWindowsDialog:



### Public Slots

- void [checkFields](#) ()  
*StartedWindowsDialog::checkFields* Check all fields of dialog components.
- void [backToPage2](#) ()  
*StartedWindowsDialog::backToPage2* Return to the second page.
- void [nextToPage2](#) ()  
*StartedWindowsDialog::nextToPage2* Go to the second page.
- void [nextToPage3](#) ()  
*StartedWindowsDialog::nextToPage3* Go to the third page.
- void [databaseTypeChanged](#) (const int index)  
*StartedWindowsDialog::databaseTypeChanged* Listener on the Database type combobox.
- void [updateNextButton](#) ()  
*StartedWindowsDialog::updateNextButton* Check if the next button is enabled.
- void [accept](#) ()  
*StartedWindowsDialog::accept* Valid data inputed by user and add these data in Database.

### Public Member Functions

- [StartedWindowsDialog](#) (QWidget \*parent=0)  
*StartedWindowsDialog::StartedWindowsDialog* Construct a [StartedWindowsDialog](#).
- void [fillFields](#) ()  
*StartedWindowsDialog::fillFields* Fill line edits with the data of the user.
- QPixmap [getImage](#) (QString path, int width=256, int height=256)  
*StartedWindowsDialog::getImage* Return a scaled image from the icon specified by it path. The image returned has a resolution of width\*height (default 256\*256)
- bool [isDatabaseTypeValid](#) ()  
*StartedWindowsDialog::isDatabaseTypeValid* Return TRUE if settings of database type is valid else return FALSE.
- bool [isDatabaseCentralized](#) ()  
*StartedWindowsDialog::isDatabaseCentralized* Return TRUE if the current type of database is centralized else FALSE.



### 8.84.1 Detailed Description

The [StartedWindowsDialog](#) class Construct a Windows for the first begin.

#### Author

Florent Berbie

#### See Also

[DatabaseSettingsWidget](#)

### 8.84.2 Constructor & Destructor Documentation

**8.84.2.1** [Gui::Dialogs::StartedWindowsDialog::StartedWindowsDialog](#) ( [QWidget](#) \* *parent* = 0 ) [explicit]

[StartedWindowsDialog::StartedWindowsDialog](#) Construct a [StartedWindowsDialog](#).

#### Parameters

<i>parent</i>	QWidget parent
---------------	----------------

### 8.84.3 Member Function Documentation

**8.84.3.1** void [Gui::Dialogs::StartedWindowsDialog::databaseTypeChanged](#) ( const int *index* ) [slot]

[StartedWindowsDialog::databaseTypeChanged](#) Listener on the Database type combobox.

#### Parameters

<i>index</i>	Current index selected
--------------	------------------------

**8.84.3.2** [QPixmap](#) [Gui::Dialogs::StartedWindowsDialog::getImage](#) ( [QString](#) *path*, int *width* = 256, int *height* = 256 )

[StartedWindowsDialog::getImage](#) Return a scaled image from the icon specified by it *path*. The image returned has a resolution of *width\*height* (default 256\*256)

#### Parameters

<i>path</i>	Icon path
<i>width</i>	Icon width
<i>height</i>	Icon height

#### Returns

Scaled image

**8.84.3.3** bool [Gui::Dialogs::StartedWindowsDialog::isDatabaseCentralized](#) ( )

[StartedWindowsDialog::isDatabaseCentralized](#) Return TRUE if the current type of database is centralized else FALSE.

#### Returns

boolean

#### 8.84.3.4 bool Gui::Dialogs::StartedWindowsDialog::isDatabaseTypeValid ( )

[StartedWindowsDialog::isDatabaseTypeValid](#) Return TRUE if settings of database type is valid else return FALSE.

##### Returns

boolean on the database type validity

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/dialogs/startedwindowsdialog.h
- /home/travis/build/FACT-Team/FactDev/src/gui/dialogs/startedwindowsdialog.cpp

## 8.85 Utils::String Class Reference

The Utils class.

```
#include <string.h>
```

### Static Public Member Functions

- static QString [firstLetterToUpper](#) (QString s)  
*firstLetterToUpper Put the first letter of a string in capslock*

#### 8.85.1 Detailed Description

The Utils class.

##### Author

Antoine de Roquemaurel

#### 8.85.2 Member Function Documentation

##### 8.85.2.1 QString Utils::String::firstLetterToUpper ( QString s ) [static]

[firstLetterToUpper](#) Put the first letter of a string in capslock

##### Parameters

s	The string to display
---	-----------------------

##### Returns


The new string with caps

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/Utils/string.h
- /home/travis/build/FACT-Team/FactDev/src/Utils/string.cpp

## 8.86 StringTest Class Reference

Inheritance diagram for StringTest:



The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/tests/utls/stringtest.h
- /home/travis/build/FACT-Team/FactDev/tests/utls/stringtest.cpp

## 8.87 Mustache::Tag Struct Reference

```
#include <mustache.h>
```

### Public Types

- enum `Type` {  
**Null**, **Value**, **SectionStart**, **InvertedSectionStart**,  
**SectionEnd**, **Partial**, **Comment**, **SetDelimiter** }
- enum **EscapeMode** { **Escape**, **Unescape**, **Raw** }

### Public Attributes

- `Type` **type**
- `QString` **key**
- `int` **start**
- `int` **end**
- `EscapeMode` **escapeMode**

### 8.87.1 Detailed Description

Holds properties of a tag in a mustache template.

### 8.87.2 Member Enumeration Documentation

#### 8.87.2.1 enum `Mustache::Tag::Type`

Enumerator

- SectionStart** A `{{key}}` or `{{{key}}}` tag.
- InvertedSectionStart** A `{{#section}}` tag.
- SectionEnd** An `{{^inverted-section}}` tag.
- Partial** A `{{/section}}` tag.
- Comment** A `{{^partial}}` tag.
- SetDelimiter** A `{{! comment }}` tag. A `{{=<% %>=}}` tag

The documentation for this struct was generated from the following file:

- /home/travis/build/FACT-Team/FactDev/src/libs/qt-mustache/src/mustache.h

## 8.88 TestAdder< T > Class Template Reference

### Public Member Functions

- **TestAdder** (const QString &name)

The documentation for this class was generated from the following file:

- /home/travis/build/FACT-Team/FactDev/tests/QStringRunner/testadder.cpp


## 8.89 testadder Class Reference

The documentation for this class was generated from the following file:

- /home/travis/build/FACT-Team/FactDev/tests/QStringRunner/testadder.h

## 8.90 TestMustache Class Reference

Inheritance diagram for TestMustache:



The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/libs/qt-mustache/tests/test\_mustache.h
- /home/travis/build/FACT-Team/FactDev/src/libs/qt-mustache/tests/test\_mustache.cpp

## 8.91 TestRunner Class Reference

### Public Member Functions

- template<typename T >  
char **RegisterTest** (QString name)
- int **RunAll** (int argc, char \*argv[])

### Static Public Member Functions

- static [TestRunner](#) & **Instance** ()

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/tests/QStringRunner/testrunner.h
- /home/travis/build/FACT-Team/FactDev/tests/QStringRunner/testrunner.cpp

## 8.92 Generator::TexGenerator Class Reference

The [TexGenerator](#) class Generate a LaTeX file.

```
#include <texgenerator.h>
```

### Public Member Functions

- [TexGenerator](#) (QString tpl)  
*TexGenerator::TexGenerator Construct a [TexGenerator](#).*
- void [generate](#) (QVariantHash data, QString path)  
*TexGenerator::generate Generate a LaTeX file into a file specified by the path and which contains data*

### 8.92.1 Detailed Description

The [TexGenerator](#) class Generate a LaTeX file.

### 8.92.2 Constructor & Destructor Documentation

#### 8.92.2.1 Generator::TexGenerator::TexGenerator ( QString *tpl* )

[TexGenerator::TexGenerator](#) Construct a [TexGenerator](#).

Parameters

<i>tpl</i>	Template LaTeX to apply
------------	-------------------------

### 8.92.3 Member Function Documentation

#### 8.92.3.1 void Generator::TexGenerator::generate ( QVariantHash *data*, QString *path* )

[TexGenerator::generate](#) Generate a LaTeX file into a file specified by the *path* and which contains *data*

Parameters

<i>data</i>	Data to integrate in the file
<i>path</i>	Path of the out file

The documentation for this class was generated from the following files:


- /home/travis/build/FACT-Team/FactDev/src/generator/texgenerator.h
- /home/travis/build/FACT-Team/FactDev/src/generator/texgenerator.cpp

## 8.93 Gui::Widgets::Delegates::UnitComboDelegate Class Reference

The [UnitComboDelegate](#) class.

```
#include <unitcombodelegate.h>
```

Inheritance diagram for Gui::Widgets::Delegates::UnitComboDelegate:



## Public Member Functions

- [UnitComboDelegate](#) (QObject \*parent=0)  
[UnitComboDelegate::UnitComboDelegate](#).
- QWidget \* [createEditor](#) (QWidget \*parent, const QStyleOptionViewItem &option, const QModelIndex &index) const  
[UnitComboDelegate::createEditor](#) Return a ComboBox specified by index item defined by the parent widget and style option which are used to control how the editor widgets appears.
- void [paint](#) (QPainter \*painter, const QStyleOptionViewItem &option, const QModelIndex &index) const  
[UnitComboDelegate::paint](#) Renders the delegate using the given painter and style option for the item specified by index

### 8.93.1 Detailed Description

The [UnitComboDelegate](#) class.

### 8.93.2 Constructor & Destructor Documentation

8.93.2.1 [Gui::Widgets::Delegates::UnitComboDelegate::UnitComboDelegate](#) ( QObject \* *parent* = 0 )

[UnitComboDelegate::UnitComboDelegate](#).

Parameters

<i>parent</i>	
---------------	--

### 8.93.3 Member Function Documentation

8.93.3.1 QWidget \* [Gui::Widgets::Delegates::UnitComboDelegate::createEditor](#) ( QWidget \* *parent*, const QStyleOptionViewItem & *option*, const QModelIndex & *index* ) const [virtual]

[UnitComboDelegate::createEditor](#) Return a ComboBox specified by *index* item defined by the *parent* widget and style *option* which are used to control how the editor widgets appears.

Parameters

<i>parent</i>	Widget parent
<i>option</i>	Option style
<i>index</i>	Index for editing

Returns

ComboBox

Implements [Gui::Widgets::Delegates::ComboBoxDelegate](#).

8.93.3.2 void Gui::Widgets::Delegates::UnitComboDelegate::paint ( QPainter \* *painter*, const QStyleOptionViewItem & *option*, const QModelIndex & *index* ) const [virtual]

[UnitComboDelegate::paint](#) Renders the delegate using the given *painter* and style *option* for the item specified by *index*

## Parameters

<i>parent</i>	Widget parent
<i>option</i>	Option style
<i>index</i>	Index for editing

Implements [Gui::Widgets::Delegates::ComboBoxDelegate](#).

The documentation for this class was generated from the following files:


- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/delegates/unitcombodelegate.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/delegates/unitcombodelegate.cpp

## 8.94 Models::User Class Reference

The [User](#) class [User](#) of it application.

```
#include <user.h>
```

Inheritance diagram for Models::User:



### Public Member Functions

- [User](#) ()  
*User::User. Construct an [User](#).*
- [User](#) (int id)  
*User::User. Construct a [User](#) with the identify id*
- void [commit](#) ()  
*User::commit Update user data in [User](#) table on the database.*
- void [hydrat](#) (int id=1)  
*User::hydrat Get data of the user who is specified by id from the database.*
- void [remove](#) ()  
*remove Remove the current [User](#)*
- QVariantHash [getDataMap](#) ()  
*getDataMap Get all data of model with a HashMap key/value*
- void [updateFolders](#) (void)  
*MainWindow::updateFolders Make directories which contain quotes and billings. Directories are the same than theirs of the Tree organisation (without Projects).*
- QString [getTitle](#) () const  
*User::getTitle Return a short description of [User](#) (company) activity.*
- void [setTitle](#) (const QString &title)  
*User::setTitle Modify the user/company activities description*
- QString [getNoSiret](#) () const  
*User::getNoSiret Return the SIRET number (company registration number)*
- void [setNoSiret](#) (const QString &noSiret)  
*User::setNoSiret Modify the SIRET number (company registration number) noSiret*
- QString [getWorkspaceName](#) () const  
*User::getWorkspaceName Return the name of the workspace user.*



- void [setWorkspaceName](#) (const QString &workspaceName)  
*[User::setWorkspaceName](#) Change the current workspace name by the new workspaceName*
- QString [getWorkspacePath](#) () const  
*[User::getWorkspacePath](#) Return the path of the workspace user.*
- void [setWorkspacePath](#) (const QString &workspacePath)  
*[User::setWorkspacePath](#) Change the current workspace path by the new workspacePath*
- bool [operator==](#) (const [User](#) &u)  
*[User::operator ==](#) Re-define the operator "==" to compare if the current [User](#) is the same to the other [User](#) c Return TRUE if both Users are the same, else FALSE.*
- bool [operator!=](#) (const [User](#) &u)  
*[User::operator !=](#) Re-define the operator "!=" to compare if the current [User](#) is differnt to the other [User](#) c Return TRUE if both Users are different, else FALSE.*

## Additional Inherited Members

### 8.94.1 Detailed Description

The [User](#) class [User](#) of it application.

#### Author

Florent Berbie

### 8.94.2 Constructor & Destructor Documentation

#### 8.94.2.1 Models::User::User ( int *id* )

[User::User](#). Construct a [User](#) with the identify *id*

#### Parameters

<i>id</i>	<a href="#">User</a> <i>id</i>
-----------	--------------------------------

### 8.94.3 Member Function Documentation

#### 8.94.3.1 QVariantHash Models::User::getDataMap ( ) [virtual]

[getDataMap](#) Get all data of model with a HashMap key/value

#### Returns

Model's data

Implements [Models::IModel](#).

#### 8.94.3.2 QString Models::User::getNoSiret ( ) const

[User::getNoSiret](#) Return the SIRET number (company registration number)

#### Returns

SIRET number

#### 8.94.3.3 QString Models::User::getTitle ( ) const

[User::getTitle](#) Return a short description of [User](#) (company) activity.

##### Returns

a short description of user (company) activity

#### 8.94.3.4 QString Models::User::getWorkspaceName ( ) const

[User::getWorkspaceName](#) Return the name of the workspace user.

##### Returns

workspace name

#### 8.94.3.5 QString Models::User::getWorkspacePath ( ) const

[User::getWorkspacePath](#) Return the path of the workspace user.

##### Returns

workspace path

#### 8.94.3.6 void Models::User::hydrat ( int *id* = 1 ) [virtual]

[User::hydrat](#) Get data of the user who is specified by *id* from the database.

##### Parameters

<i>id</i>	<a href="#">User</a> identify
-----------	-------------------------------

Implements [Models::IModel](#).

#### 8.94.3.7 bool Models::User::operator!= ( const User & *u* )

[User::operator !=](#) Re-define the operator "!=" to compare if the current [User](#) is differnt to the other [User](#) c Return TRUE if both Users are different, else FALSE.

##### Parameters

<i>u</i>	<a href="#">User</a> to compare
----------	---------------------------------

##### Returns

boolean

#### 8.94.3.8 bool Models::User::operator== ( const User & *u* )

[User::operator ==](#) Re-define the operator "==" to compare if the current [User](#) is the same to the other [User](#) c Return TRUE if both Users are the same, else FALSE.

## Parameters

<i>u</i>	<a href="#">User</a> to compare
----------	---------------------------------

## Returns

boolean

8.94.3.9 void Models::User::setNoSiret ( const QString & *noSiret* )[User::setNoSiret](#) Modify the SIRET number (company registration number) *noSiret*

## Parameters

<i>noSiret</i>	SIRET number
----------------	--------------

8.94.3.10 void Models::User::setTitle ( const QString & *title* )[User::setTitle](#) Modify the user/company activities *description*

## Parameters

<i>title</i>	Short description on activity(ies) of <a href="#">User</a> company
--------------	--------------------------------------------------------------------

8.94.3.11 void Models::User::setWorkspaceName ( const QString & *workspaceName* )[User::setWorkspaceName](#) Change the current workspace name by the new *workspaceName*

## Parameters

<i>workspaceName</i>	
----------------------	--

8.94.3.12 void Models::User::setWorkspacePath ( const QString & *workspacePath* )[User::setWorkspacePath](#) Change the current workspace path by the new *workspacePath*

## Parameters

<i>workspacePath</i>	
----------------------	--

## 8.94.3.13 void Models::User::updateFolders ( void )

[MainWindow::updateFolders](#) Make directories which contain quotes and billings. Directories are the same than theirs of the Tree organisation (without Projects).

Organisation of folders are formed like this:

- COMPANY CustomerLastname CustomerFirstname/
  - Quotes/
    - \* quote1 ...
  - Billings/
    - \* billing1 ...

The documentation for this class was generated from the following files:


- /home/travis/build/FACT-Team/FactDev/src/models/user.h
- /home/travis/build/FACT-Team/FactDev/src/models/user.cpp

## 8.95 Databases::UserDatabase Class Reference

The [UserDatabase](#) class Access to User data in the the table User of the [Database](#)

```
#include <userdatabase.h>
```

Inheritance diagram for Databases::UserDatabase:



### Public Member Functions

- [Models::User](#) \* [getUser](#) (const int pld=1)  
[UserDatabase::getUser](#) Get informations about the user (identified by 'pld')
- void [updateUser](#) (const [Models::User](#) &)  
[UserDatabase::updateUser](#) Update informations about the user.

### Static Public Member Functions

- static [UserDatabase](#) \* [instance](#) () throw (DbException\*)  
[UserDatabase::getInstance](#) Return an instance of [UserDatabase](#).

### Additional Inherited Members

#### 8.95.1 Detailed Description

The [UserDatabase](#) class Access to User data in the the table User of the [Database](#)

#### Author

Florent Berbie

#### See Also

[Database](#)  
[User](#)

#### 8.95.2 Member Function Documentation

##### 8.95.2.1 [Models::User](#) \* [Databases::UserDatabase::getUser](#) ( const int *pld* = 1 )

[UserDatabase::getUser](#) Get informations about the user (identified by 'pld')

## Parameters

<i>pId</i>	user id (1 default)
------------	---------------------

## Returns

the user

**8.95.2.2** `UserDatabase * Databases::UserDatabase::instance ( ) throw DbException *` `[static]`

`UserDatabase::getInstance` Return an instance of [UserDatabase](#).

## Returns


Instance of [UserDatabase](#)

The documentation for this class was generated from the following files:

- `/home/travis/build/FACT-Team/FactDev/src/database/userdatabase.h`
- `/home/travis/build/FACT-Team/FactDev/src/database/userdatabase.cpp`

## 8.96 UserDatabaseTest Class Reference

Inheritance diagram for `UserDatabaseTest`:



The documentation for this class was generated from the following files:


- `/home/travis/build/FACT-Team/FactDev/tests/database/userdatabasetest.h`
- `/home/travis/build/FACT-Team/FactDev/tests/database/userdatabasetest.cpp`

## 8.97 Gui::Dialogs::UserDataDialog Class Reference

The [UserDataDialog](#) class Window to fill user data.

```
#include <userdatadialog.h>
```

Inheritance diagram for `Gui::Dialogs::UserDataDialog`:



## Public Slots

- void [checkFields](#) ()  
*[UserDataDialog::checkFields](#) Check all fields of dialog components.*
- void [browseWorkspacePath](#) ()  
*[UserDataDialog::browseWorkspacePath](#) Open a new window to define the workspace path of the user.*

## Public Member Functions

- [UserDataDialog](#) (QWidget \*parent=0)  
*[UserDataDialog::UserDataDialog](#) Construct a window with user data.*
- void [fillFields](#) ()  
*[UserDataDialog::fillFields](#) Fill line edits with the data of the user.*
- void [accept](#) ()  
*[UserDataDialog::accept](#) Valid data inputed by user and add these data in Database.*
- void [reject](#) ()  
*[UserDataDialog::reject](#) Cancel the operation and close the windows.*

### 8.97.1 Detailed Description

The [UserDataDialog](#) class Window to fill user data.

#### Author

Florent Berbie

#### See Also

Project

### 8.97.2 Constructor & Destructor Documentation

#### 8.97.2.1 [Gui::Dialogs::UserDataDialog::UserDataDialog](#) ( [QWidget](#) \* *parent* = 0 ) [explicit]

[UserDataDialog::UserDataDialog](#) Construct a window with user data.

#### Parameters

<i>parent</i>	
---------------	--

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/dialogs/userdatadialog.h
- /home/travis/build/FACT-Team/FactDev/src/gui/dialogs/userdatadialog.cpp

## 8.98 UserModelTest Class Reference

Inheritance diagram for UserModelTest:



The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/tests/models/usermodeltest.h
- /home/travis/build/FACT-Team/FactDev/tests/models/usermodeltest.cpp

# Index

- add
  - Gui::Widgets::ContributoriesWidget, [72](#)
- addBill
  - Gui::MainWindow, [117](#)
- addBilling
  - Databases::BillingDatabase, [32](#)
- addBillingProject
  - Databases::BillingDatabase, [32](#)
- addBillingToProject
  - Utils::HierarchicalSystem, [108](#)
- addContributory
  - Databases::ContributoryDatabase, [77](#)
  - Models::Billing, [26](#)
  - Models::ContributoriesList, [64](#)
- addCustomer
  - Databases::CustomerDatabase, [88](#)
- addDoc
  - Gui::MainWindow, [117](#)
- addProject
  - Databases::ProjectDatabase, [145](#)
  - Gui::MainWindow, [117](#)
  - Gui::Widgets::ContributoriesWidget, [72](#)
  - Models::ContributoriesList, [64](#)
- AddProjectDialog
  - Gui::Dialogs::AddProjectDialog, [22](#)
- addProjectToCustomer
  - Utils::HierarchicalSystem, [108](#)
- addQuote
  - Gui::MainWindow, [117](#)
- AddQuoteDialog
  - Gui::Dialogs::AddQuoteDialog, [23](#)
- addRateProject
  - Databases::RateDatabase, [158](#)
- allProjectsChosen
  - Gui::Widgets::WdgModels::ProjectContributories-TableModel, [140](#)
- append
  - Gui::Widgets::WdgModels::BillingsTableModel, [36](#)
  - Gui::Widgets::WdgModels::ContributoriesTable-Model, [68](#)
  - Gui::Widgets::WdgModels::CustomersTableModel, [94](#)
  - Gui::Widgets::WdgModels::ProjectContributories-TableModel, [140](#)
  - Gui::Widgets::WdgModels::ProjectsTableModel, [150](#)
- Billing
  - Models::Billing, [26](#)
- BillingDatabaseTest, [35](#)
- BillingModelTest, [35](#)
- BillingsTableModel
  - Gui::Widgets::WdgModels::BillingsTableModel, [36](#)
- canEval
  - CounterContext, [82](#)
  - Mustache::Context, [61](#)
  - Mustache::QtVariantContext, [154](#)
- check
  - Gui::Widgets::CheckFields::CheckEmail, [42](#)
  - Gui::Widgets::CheckFields::CheckFieldsLetters, [43](#)
  - Gui::Widgets::CheckFields::CheckFieldsNumbers, [45](#)
  - Gui::Widgets::CheckFields::CheckIpAddress, [46](#)
  - Gui::Widgets::CheckFields::CheckLogin, [47](#)
  - Gui::Widgets::CheckFields::CheckPhone, [49](#)
  - Gui::Widgets::CheckFields::CheckPortNumber, [51](#)
  - Gui::Widgets::CheckFields::CheckPostalCode, [52](#)
  - Gui::Widgets::CheckFields::CheckSiretNumber, [55](#)
  - Gui::Widgets::CheckFields::CheckUntilField, [56](#)
  - Gui::Widgets::CheckFields::CheckValidField, [57](#)
  - Gui::Widgets::CheckFields::ICheckField, [109](#)
- CheckCity
  - Gui::Widgets::CheckFields::CheckCity, [40](#)
- CheckCountry
  - Gui::Widgets::CheckFields::CheckCountry, [41](#)
- CheckEmail
  - Gui::Widgets::CheckFields::CheckEmail, [42](#)
- CheckFieldsLetters
  - Gui::Widgets::CheckFields::CheckFieldsLetters, [43](#)
- CheckFieldsNumbers
  - Gui::Widgets::CheckFields::CheckFieldsNumbers, [44](#)
- CheckIpAddress
  - Gui::Widgets::CheckFields::CheckIpAddress, [46](#)
- CheckLogin
  - Gui::Widgets::CheckFields::CheckLogin, [47](#)
- CheckName
  - Gui::Widgets::CheckFields::CheckName, [48](#)
- CheckPhone
  - Gui::Widgets::CheckFields::CheckPhone, [49](#)
- CheckPortNumber
  - Gui::Widgets::CheckFields::CheckPortNumber, [51](#)
- CheckPostalCode
  - Gui::Widgets::CheckFields::CheckPostalCode, [52](#)
- CheckQLineEdit
  - Gui::Widgets::CheckFields::CheckQLineEdit, [53](#)
- CheckSiretNumber
  - Gui::Widgets::CheckFields::CheckSiretNumber, [55](#)
- CheckUntilField



- Gui::Widgets::CheckFields::CheckUntilField, 56
- CheckValidField
  - Gui::Widgets::CheckFields::CheckValidField, 57
- columnCount
  - Gui::Widgets::WdgModels::BillingsTableModel, 37
  - Gui::Widgets::WdgModels::ContributoriesTable-Model, 68
  - Gui::Widgets::WdgModels::CustomersTableModel, 94
  - Gui::Widgets::WdgModels::ProjectContributories-TableModel, 142
  - Gui::Widgets::WdgModels::ProjectsTableModel, 150
- ComboBoxDelegate
  - Gui::Widgets::Delegates::ComboBoxDelegate, 58
- ComboBoxModelWidget
  - Gui::Widgets::ComboBoxModelWidget, 60
- Comment
  - Mustache::Tag, 175
- Context
  - Mustache::Context, 61
- ContributoriesDatabaseTest, 63
- ContributoriesTableModel
  - Gui::Widgets::WdgModels::ContributoriesTable-Model, 68
- ContributoriesWidget
  - Gui::Widgets::ContributoriesWidget, 71
- Contributory
  - Models::Contributory, 74
- ContributoryListTest, 81
- ContributoryModelTest, 81
- costCompute
  - Models::Project, 134
- count
  - Gui::Widgets::ContributoriesWidget, 72
  - Gui::Widgets::WdgModels::BillingsTableModel, 37
  - Gui::Widgets::WdgModels::ContributoriesTable-Model, 68
  - Gui::Widgets::WdgModels::CustomersTableModel, 95
  - Gui::Widgets::WdgModels::ProjectsTableModel, 150
- CounterContext, 81
  - canEval, 82
  - eval, 82
  - stringValue, 82, 83
- createEditor
  - Gui::Widgets::Delegates::ComboBoxDelegate, 59
  - Gui::Widgets::Delegates::DoubleSpinBoxDelegate, 105
  - Gui::Widgets::Delegates::ProjectComboDelegate, 138
  - Gui::Widgets::Delegates::UnitComboDelegate, 178
- Customer
  - Models::Customer, 84
- CustomerContextualMenu
  - Gui::Widgets::CustomerContextualMenu, 86
- CustomerDataWidget
  - Gui::Widgets::CustomerDataWidget, 92
- CustomerDatabaseTest, 92
- CustomerModelTest, 93
- CustomersTableModel
  - Gui::Widgets::WdgModels::CustomersTableModel, 94
- DB\_FILENAME
  - Parameters, 122
- data
  - Gui::Widgets::WdgModels::BillingsTableModel, 37
  - Gui::Widgets::WdgModels::ContributoriesTable-Model, 69
  - Gui::Widgets::WdgModels::CustomersTableModel, 95
  - Gui::Widgets::WdgModels::ProjectContributories-TableModel, 142
  - Gui::Widgets::WdgModels::ProjectsTableModel, 150
- DatabaseSettingsWidget
  - Gui::Widgets::DatabaseSettingsWidget, 100
- databaseTypeChanged
  - Gui::Dialogs::StartedWindowsDialog, 173
- Databases, 17
- Databases::BillingDatabase, 30
  - addBilling, 32
  - addBillingProject, 32
  - getAllBillingsOfProject, 32
  - getBilling, 32
  - getBillings, 32
  - getBillingsTable, 33
  - getMaxBillingNumber, 33
  - getMaxBillingNumberOfCustomer, 33
  - getMaxQuoteNumber, 33
  - getMaxQuoteNumberOfCustomer, 33
  - instance, 34
  - isBillingPaid, 34
  - removeBilling, 34
  - removeBillingProject, 34
- Databases::ContributoryDatabase, 76
  - addContributory, 77
  - getContributoriesByBilling, 77
  - getContributoriesByBillingAndProject, 79
  - getContributory, 79
  - instance, 79
  - removeContributory, 79
- Databases::CustomerDatabase, 87
  - addCustomer, 88
  - getCustomer, 88
  - getCustomersTable, 88
  - getItemBillQuote, 90
  - getItemCustomer, 90
  - getItemProject, 90
  - getItemRoot, 90
  - getNbCustomers, 90
  - getTree, 91
  - instance, 91
  - removeCustomer, 91
  - updateCustomer, 91

- Databases::Database, 96
  - executeFile, 98
  - instance, 98
  - lastError, 98
  - setDatabase, 98
  - value, 99
- Databases::ProjectDatabase, 144
  - addProject, 145
  - getAllProjects, 145
  - getNbProjects, 145
  - getNbProjectsForACustomer, 145
  - getProject, 146
  - getProjects, 146
  - getProjectsOfCustomer, 146
  - getProjectsTable, 146
  - instance, 148
  - removeProject, 148
  - updateProject, 148
- Databases::RateDatabase, 157
  - addRateProject, 158
  - getRate, 158
  - instance, 158
  - updateRateProject, 158
- Databases::UserDatabase, 184
  - getUser, 184
  - instance, 185
- DbException
  - Exceptions::DbException, 102
- DialogAddCustomer
  - Gui::Dialogs::DialogAddCustomer, 103
- DoubleSpinBoxDelegate
  - Gui::Widgets::Delegates::DoubleSpinBoxDelegate, 105
- editUser
  - Gui::MainWindow, 117
- error
  - Mustache::Renderer, 161
- errorPartial
  - Mustache::Renderer, 161
- errorPos
  - Mustache::Renderer, 161
- eval
  - CounterContext, 82
  - Mustache::Context, 62
  - Mustache::QtVariantContext, 154
- Exceptions::DbException, 101
  - DbException, 102
  - popupMessage, 102
- Exceptions::FileException, 106
  - FileException, 106
  - popupMessage, 107
- executeFile
  - Databases::Database, 98
- FileException
  - Exceptions::FileException, 106
- fillQuoteBilling
  - Gui::Dialogs::AddQuoteDialog, 23
- filterOnBillsOrQuotes
  - Models::Search, 163
- filterOnCompany
  - Models::Search, 163
- filterOnContributories
  - Models::Search, 163
- filterOnCustomersWithoutProject
  - Models::Search, 164
- filterOnNumberElements
  - Models::Search, 164
- filterOnProjects
  - Models::Search, 164
- filterOnReferentLastname
  - Models::Search, 164
- filterOnVarcharElements
  - Models::Search, 164
- firstLetterToUpper
  - Utils::String, 174
- flags
  - Gui::Widgets::WdgModels::BillingsTableModel, 37
  - Gui::Widgets::WdgModels::ContributoriesTable-Model, 69
  - Gui::Widgets::WdgModels::CustomersTableModel, 95
  - Gui::Widgets::WdgModels::ProjectContributories-TableModel, 142
  - Gui::Widgets::WdgModels::ProjectsTableModel, 151
- fn\_t
  - Mustache::QtVariantContext, 154
- generate
  - Generator::PdfGenerator, 124
  - Generator::TexGenerator, 177
- Generation, 107
- Generator::PdfGenerator, 124
  - generate, 124
  - PdfGenerator, 124
- Generator::TexGenerator, 177
  - generate, 177
  - TexGenerator, 177
- getAddress
  - Models::People, 126
- getAllBillingsOfProject
  - Databases::BillingDatabase, 32
- getAllContributories
  - Models::ContributoriesList, 65
- getAllProjects
  - Databases::ProjectDatabase, 145
- getBeginDate
  - Models::Project, 134
- getBilling
  - Databases::BillingDatabase, 32
- getBillings
  - Databases::BillingDatabase, 32
  - Gui::Widgets::WdgModels::BillingsTableModel, 37
- getBillingsTable
  - Databases::BillingDatabase, 33
- getBtnValid

- Gui::Widgets::CheckFields::CheckQLineEdit, 54
- getCity
  - Models::People, 126
- getCompany
  - Models::People, 126
- getContributories
  - Gui::Widgets::ContributoriesWidget, 72
  - Gui::Widgets::WdgModels::ContributoriesTableModel, 69
  - Models::Billing, 26
  - Models::ContributoriesList, 65
- getContributoriesByBilling
  - Databases::ContributoryDatabase, 77
- getContributoriesByBillingAndProject
  - Databases::ContributoryDatabase, 79
- getContributory
  - Databases::ContributoryDatabase, 79
- getCopy
  - Gui::Dialogs::AddQuoteDialog, 23
- getCost
  - Models::Project, 134
- getCountry
  - Gui::Widgets::CheckFields::CheckPhone, 49
  - Gui::Widgets::CheckFields::CheckPostalCode, 52
  - Models::People, 127
- getCurrentCustomerId
  - Gui::MainWindow, 118
  - Gui::Widgets::searchWidget, 171
- getCurrentCustomerName
  - Gui::MainWindow, 118
- getCurrentProjectId
  - Gui::MainWindow, 118
- getCurrentProjectName
  - Gui::MainWindow, 118
- getCurrentQuoteId
  - Gui::MainWindow, 118
- getCustomer
  - Databases::CustomerDatabase, 88
  - Models::ContributoriesList, 65
  - Models::Project, 134
- getCustomers
  - Gui::Widgets::WdgModels::CustomersTableModel, 95
  - Utils::HierarchicalSystem, 108
- getCustomersTable
  - Databases::CustomerDatabase, 88
- getDailyRate
  - Gui::Widgets::RateWidget, 160
  - Models::Project, 134
  - Models::Rate, 156
- getDataMap
  - Models::Billing, 26
  - Models::ContributoriesList, 65
  - Models::Contributory, 75
  - Models::Customer, 84
  - Models::IModel, 111
  - Models::Project, 134
  - Models::User, 181
- getDatabaseName
  - Gui::Widgets::DatabaseSettingsWidget, 100
- getDate
  - Models::Billing, 27
- getDescription
  - Models::Billing, 27
  - Models::Contributory, 75
  - Models::Project, 134
- getDomainNameOrIP
  - Gui::Widgets::DatabaseSettingsWidget, 100
- getEmail
  - Models::People, 127
- getEndDate
  - Models::Project, 135
- getFax
  - Models::People, 127
- getFilename
  - Models::Billing, 27
- getFilter
  - Models::Search, 164
- getFirstname
  - Models::People, 127
- getFolder
  - Models::Billing, 27
- getGroupFilter
  - Models::Search, 165
- getHourlyRate
  - Gui::Widgets::RateWidget, 160
  - Models::Rate, 156
- getId
  - Models::IModel, 111
- getIdBilling
  - Models::ContributoriesList, 65
- getIdCustomer
  - Gui::Dialogs::AddQuoteDialog, 23
  - Gui::Widgets::searchWidget, 171
- getImage
  - Gui::Dialogs::StartedWindowsDialog, 173
- getItemBillQuote
  - Databases::CustomerDatabase, 90
- getItemCustomer
  - Databases::CustomerDatabase, 90
- getItemProject
  - Databases::CustomerDatabase, 90
- getItemRoot
  - Databases::CustomerDatabase, 90
- getLastName
  - Models::People, 127
- getLegalRate
  - Models::Rate, 157
- getLogin
  - Gui::Widgets::DatabaseSettingsWidget, 100
- getMaxBillingNumber
  - Databases::BillingDatabase, 33
- getMaxBillingNumberOfCustomer
  - Databases::BillingDatabase, 33
- getMaxQuoteNumber
  - Databases::BillingDatabase, 33

- getMaxQuoteNumberOfCustomer
  - Databases::BillingDatabase, 33
- getMobilePhone
  - Models::People, 127
- getModel
  - Utils::ItemType, 112
- getName
  - Models::Project, 135
  - Utils::ItemType, 113
- getNameFolder
  - Models::Customer, 84
- getNbCustomers
  - Databases::CustomerDatabase, 90
- getNbDailyHours
  - Models::Rate, 157
- getNbHours
  - Models::Contributory, 75
- getNbProjects
  - Databases::ProjectDatabase, 145
  - Models::ContributoriesList, 65
- getNbProjectsForACustomer
  - Databases::ProjectDatabase, 145
- getNoSiret
  - Models::User, 181
- getNumber
  - Gui::Dialogs::AddQuoteDialog, 24
  - Models::Billing, 27
- getPartial
  - Mustache::PartialFileLoader, 122
  - Mustache::PartialMap, 123
  - Mustache::PartialResolver, 124
- getPassword
  - Gui::Widgets::DatabaseSettingsWidget, 101
- getPath
  - Models::Billing, 27
  - Models::Customer, 84
- getPhone
  - Models::People, 127
- getPort
  - Gui::Widgets::DatabaseSettingsWidget, 101
- getPostalCode
  - Models::People, 128
- getProject
  - Databases::ProjectDatabase, 146
  - Gui::Widgets::WdgModels::ProjectContributories-TableModel, 142
  - Models::Contributory, 75
- getProjects
  - Databases::ProjectDatabase, 146
  - Gui::Widgets::Delegates::ProjectComboDelegate, 138
  - Gui::Widgets::WdgModels::ProjectContributories-TableModel, 142
  - Gui::Widgets::WdgModels::ProjectsTableModel, 151
  - Models::ContributoriesList, 65
  - Utils::HierarchicalSystem, 108
- getProjectsOfCustomer
  - Databases::ProjectDatabase, 146
- getProjectsTable
  - Databases::ProjectDatabase, 146
- getRate
  - Databases::RateDatabase, 158
  - Models::ContributoriesList, 66
- getSearchInBillsQuotes
  - Models::Search, 165
- getSearchInCompanies
  - Models::Search, 165
- getSearchInProjects
  - Models::Search, 165
- getSearchInReferentLastname
  - Models::Search, 165
- getSelectedProjects
  - Gui::Widgets::WdgModels::ProjectContributories-TableModel, 143
- getSumQuantity
  - Gui::Widgets::WdgModels::ContributoriesTable-Model, 69
  - Models::Billing, 28
  - Models::ContributoriesList, 66
- getSumRate
  - Models::Billing, 28
  - Models::ContributoriesList, 66
- getText
  - Models::Search, 165
- getTitle
  - Models::Billing, 28
  - Models::User, 181
- getTree
  - Databases::CustomerDatabase, 91
- getTurnover
  - Models::Customer, 85
- getType
  - Utils::ItemType, 113
- getUser
  - Databases::UserDatabase, 184
- getWorkspaceName
  - Models::User, 182
- getWorkspacePath
  - Models::User, 182
- Gui, 17
- Gui::Dialogs::AddProjectDialog, 21
  - AddProjectDialog, 22
- Gui::Dialogs::AddQuoteDialog, 22
  - AddQuoteDialog, 23
  - fillQuoteBilling, 23
  - getCopy, 23
  - getCustomerId, 23
  - getNumber, 24
  - setCopy, 24
  - setQuoteIdNumber, 24
- Gui::Dialogs::DialogAddCustomer, 102
  - DialogAddCustomer, 103
- Gui::Dialogs::MessageBox, 120
  - MessageBox, 121
  - setImage, 121

- setText, 121
- Gui::Dialogs::StartedWindowsDialog, 172
  - databaseTypeChanged, 173
  - getImage, 173
  - isDatabaseCentralized, 173
  - isDatabaseTypeValid, 173
  - StartedWindowsDialog, 173
- Gui::Dialogs::UserDataDialog, 185
  - UserDataDialog, 186
- Gui::Docks::SearchDock, 167
  - search, 169
  - SearchDock, 168
  - textChanged, 169
- Gui::MainWindow, 115
  - addBill, 117
  - addDoc, 117
  - addProject, 117
  - addQuote, 117
  - editUser, 117
  - getCurrentCustomerId, 118
  - getCurrentCustomerName, 118
  - getCurrentProjectId, 118
  - getCurrentProjectName, 118
  - getCurrentQuoteId, 118
  - MainWindow, 117
  - rootTree, 118
  - search, 118
  - treeLevel, 120
- Gui::Widgets, 18
- Gui::Widgets::CheckFields::CheckCity, 39
  - CheckCity, 40
- Gui::Widgets::CheckFields::CheckCountry, 40
  - CheckCountry, 41
- Gui::Widgets::CheckFields::CheckEmail, 41
  - check, 42
  - CheckEmail, 42
- Gui::Widgets::CheckFields::CheckFieldsLetters, 43
  - check, 43
  - CheckFieldsLetters, 43
- Gui::Widgets::CheckFields::CheckFieldsNumbers, 44
  - check, 45
  - CheckFieldsNumbers, 44
- Gui::Widgets::CheckFields::CheckIpAddress, 45
  - check, 46
  - CheckIpAddress, 46
- Gui::Widgets::CheckFields::CheckLogin, 46
  - check, 47
  - CheckLogin, 47
- Gui::Widgets::CheckFields::CheckName, 48
  - CheckName, 48
- Gui::Widgets::CheckFields::CheckPhone, 48
  - check, 49
  - CheckPhone, 49
  - getCountry, 49
  - setCountry, 50
- Gui::Widgets::CheckFields::CheckPortNumber, 50
  - check, 51
  - CheckPortNumber, 51
- Gui::Widgets::CheckFields::CheckPostalCode, 51
  - check, 52
  - CheckPostalCode, 52
  - getCountry, 52
  - setCountry, 52
- Gui::Widgets::CheckFields::CheckQLineEdit, 53
  - CheckQLineEdit, 53
  - getBtnValid, 54
  - isValid, 54
  - setBtnValid, 54
- Gui::Widgets::CheckFields::CheckSiretNumber, 54
  - check, 55
  - CheckSiretNumber, 55
- Gui::Widgets::CheckFields::CheckUntilField, 55
  - check, 56
  - CheckUntilField, 56
- Gui::Widgets::CheckFields::CheckValidField, 56
  - check, 57
  - CheckValidField, 57
- Gui::Widgets::CheckFields::ICheckField, 109
  - check, 109
- Gui::Widgets::ComboBoxModelWidget, 60
  - ComboBoxModelWidget, 60
- Gui::Widgets::ContributoriesWidget, 70
  - add, 72
  - addProject, 72
  - ContributoriesWidget, 71
  - count, 72
  - getContributories, 72
- Gui::Widgets::CustomerContextualMenu, 86
  - CustomerContextualMenu, 86
- Gui::Widgets::CustomerDataWidget, 92
  - CustomerDataWidget, 92
  - printInformations, 93
- Gui::Widgets::DatabaseSettingsWidget, 99
  - DatabaseSettingsWidget, 100
  - getDatabaseName, 100
  - getDomainNameOrIP, 100
  - getLogin, 100
  - getPassword, 101
  - getPort, 101
  - isValid, 101
- Gui::Widgets::Delegates::ComboBoxDelegate, 58
  - ComboBoxDelegate, 58
  - createEditor, 59
  - paint, 59
  - setEditorData, 59
  - setModelData, 59
  - updateEditorGeometry, 60
- Gui::Widgets::Delegates::DoubleSpinBoxDelegate, 104
  - createEditor, 105
  - DoubleSpinBoxDelegate, 105
  - setEditorData, 105
  - setModelData, 105
  - updateEditorGeometry, 106
- Gui::Widgets::Delegates::ProjectComboDelegate, 137
  - createEditor, 138
  - getProjects, 138

- isLocked, 138
- paint, 139
- ProjectComboDelegate, 138
- setLocked, 139
- Gui::Widgets::Delegates::UnitComboDelegate, 177
  - createEditor, 178
  - paint, 178
  - UnitComboDelegate, 178
- Gui::Widgets::Popup, 131
- Gui::Widgets::ProjectsWidget, 152
  - ProjectsWidget, 153
  - updateBtn, 153
- Gui::Widgets::RateWidget, 159
  - getDailyRate, 160
  - getHourlyRate, 160
  - RateWidget, 160
  - setDailyRate, 160
  - setHourlyRate, 160
  - setWidgetDailyRateValue, 160
  - setWidgetHourlyRateValue, 161
- Gui::Widgets::WdgModels::BillingsTableModel, 35
  - append, 36
  - BillingsTableModel, 36
  - columnCount, 37
  - count, 37
  - data, 37
  - flags, 37
  - getBillings, 37
  - headerData, 37
  - remove, 39
  - rowCount, 39
  - setData, 39
- Gui::Widgets::WdgModels::ContributoriesTableModel, 67
  - append, 68
  - columnCount, 68
  - ContributoriesTableModel, 68
  - count, 68
  - data, 69
  - flags, 69
  - getContributories, 69
  - getSumQuantity, 69
  - headerData, 69
  - remove, 70
  - rowCount, 70
  - setData, 70
- Gui::Widgets::WdgModels::CustomersTableModel, 93
  - append, 94
  - columnCount, 94
  - count, 95
  - CustomersTableModel, 94
  - data, 95
  - flags, 95
  - getCustomers, 95
  - headerData, 95
  - remove, 96
  - rowCount, 96
  - setData, 96
- Gui::Widgets::WdgModels::ProjectContributoriesTableModel, 139
  - allProjectsChosen, 140
  - append, 140
  - columnCount, 142
  - data, 142
  - flags, 142
  - getProject, 142
  - getProjects, 142
  - getSelectedProjects, 143
  - headerData, 143
  - ProjectContributoriesTableModel, 140
  - remove, 143
  - rowCount, 143
  - setData, 143
- Gui::Widgets::WdgModels::ProjectsTableModel, 149
  - append, 150
  - columnCount, 150
  - count, 150
  - data, 150
  - flags, 151
  - getProjects, 151
  - headerData, 151
  - ProjectsTableModel, 150
  - remove, 151
  - rowCount, 151
  - setData, 152
- Gui::Widgets::searchWidget, 169
  - getCurrentCustomerId, 171
  - getCustomerId, 171
  - isCustomerSelected, 171
  - search, 171
  - searchWidget, 170
  - selectCustomer, 171
  - setCustomerId, 171
- headerData
  - Gui::Widgets::WdgModels::BillingsTableModel, 37
  - Gui::Widgets::WdgModels::ContributoriesTableModel, 69
  - Gui::Widgets::WdgModels::CustomersTableModel, 95
  - Gui::Widgets::WdgModels::ProjectContributoriesTableModel, 143
  - Gui::Widgets::WdgModels::ProjectsTableModel, 151
- hydrat
  - Models::Billing, 28
  - Models::Contributory, 75
  - Models::Customer, 85
  - Models::IModel, 111
  - Models::Project, 135
  - Models::User, 182
- instance
  - Databases::BillingDatabase, 34
  - Databases::ContributoryDatabase, 79
  - Databases::CustomerDatabase, 91
  - Databases::Database, 98



- Databases::ProjectDatabase, 148
- Databases::RateDatabase, 158
- Databases::UserDatabase, 185
- Utils::Log, 114
- InvertedSectionStart
  - Mustache::Tag, 175
- isBilling
  - Models::Billing, 28
- isBillingPaid
  - Databases::BillingDatabase, 34
- isCustomerSelected
  - Gui::Widgets::searchWidget, 171
- isDatabaseCentralized
  - Gui::Dialogs::StartedWindowsDialog, 173
- isDatabaseTypeValid
  - Gui::Dialogs::StartedWindowsDialog, 173
- isFalse
  - Mustache::Context, 62
  - Mustache::QtVariantContext, 155
- isInsert
  - Models::ContributoriesList, 66
- isLocked
  - Gui::Widgets::Delegates::ProjectComboDelegate, 138
- isPaid
  - Models::Billing, 28
- isToRemoved
  - Models::IModel, 111
- isValid
  - Gui::Widgets::CheckFields::CheckQLineEdit, 54
  - Gui::Widgets::DatabaseSettingsWidget, 101
- ItemType
  - Utils::ItemType, 112
- ItemTypeTest, 113
- lastError
  - Databases::Database, 98
- listCount
  - Mustache::Context, 62
  - Mustache::QtVariantContext, 155
- MainWindow
  - Gui::MainWindow, 117
- makeDirectory
  - Utils::Directories, 104
- MessageBox
  - Gui::Dialogs::MessageBox, 121
- Models, 18
- Models::Billing, 24
  - addContributory, 26
  - Billing, 26
  - getContributories, 26
  - getDataMap, 26
  - getDate, 27
  - getDescription, 27
  - getFilename, 27
  - getFolder, 27
  - getNumber, 27
  - getPath, 27
  - getSumQuantity, 28
  - getSumRate, 28
  - getTitle, 28
  - hydrat, 28
  - isBilling, 28
  - isPaid, 28
  - operator<, 29
  - operator==, 29
  - setDate, 29
  - setDescription, 29
  - setIsBilling, 29
  - setIsPaid, 30
  - setNumber, 30
  - setTitle, 30
- Models::ContributoriesList, 63
  - addContributory, 64
  - addProject, 64
  - getAllContributories, 65
  - getContributories, 65
  - getCustomer, 65
  - getDataMap, 65
  - getIdBilling, 65
  - getNbProjects, 65
  - getProjects, 65
  - getRate, 66
  - getSumQuantity, 66
  - getSumRate, 66
  - isInsert, 66
  - setAllIdContributories, 66
  - setIdBilling, 67
  - setInsert, 67
- Models::Contributory, 72
  - Contributory, 74
  - getDataMap, 75
  - getDescription, 75
  - getNbHours, 75
  - getProject, 75
  - hydrat, 75
  - operator==, 76
  - setDescription, 76
  - setNbHours, 76
  - setProject, 76
- Models::Customer, 83
  - Customer, 84
  - getDataMap, 84
  - getNameFolder, 84
  - getPath, 84
  - getTurnover, 85
  - hydrat, 85
  - operator==, 85
  - setTurnover, 85
  - turnoverCompute, 86
- Models::IModel, 110
  - getDataMap, 111
  - getId, 111
  - hydrat, 111
  - isToRemoved, 111
  - setId, 111

- setToRemoved, 111
- Models::People, 125
  - getAddress, 126
  - getCity, 126
  - getCompany, 126
  - getCountry, 127
  - getEmail, 127
  - getFax, 127
  - getFirstname, 127
  - getLastName, 127
  - getMobilePhone, 127
  - getPhone, 127
  - getPostalCode, 128
  - operator==, 128
  - setAddress, 128
  - setCity, 128
  - setCompany, 129
  - setCountry, 129
  - setEmail, 129
  - setFax, 129
  - setFirstname, 129
  - setLastName, 129
  - setMobilePhone, 129
  - setPhone, 131
  - setPostalCode, 131
- Models::Project, 132
  - costCompute, 134
  - getBeginDate, 134
  - getCost, 134
  - getCustomer, 134
  - getDailyRate, 134
  - getDataMap, 134
  - getDescription, 134
  - getEndDate, 135
  - getName, 135
  - hydrat, 135
  - operator<, 135
  - operator==, 136
  - Project, 133
  - setBeginDate, 136
  - setCost, 136
  - setCustomer, 136
  - setDailyRate, 136
  - setDescription, 136
  - setEndDate, 137
  - setName, 137
- Models::Rate, 155
  - getDailyRate, 156
  - getHourlyRate, 156
  - getLegalRate, 157
  - getNbDailyHours, 157
  - Rate, 156
- Models::Search, 162
  - filterOnBillsOrQuotes, 163
  - filterOnCompany, 163
  - filterOnContributories, 163
  - filterOnCustomersWithoutProject, 164
  - filterOnNumberElements, 164
  - filterOnProjects, 164
  - filterOnReferentLastname, 164
  - filterOnVarcharElements, 164
  - getFilter, 164
  - getGroupFilter, 165
  - getSearchInBillsQuotes, 165
  - getSearchInCompanies, 165
  - getSearchInProjects, 165
  - getSearchInReferentLastname, 165
  - getText, 165
  - searchInContributories, 165
  - setGroupFilter, 166
  - setSearchInBillsQuotes, 166
  - setSearchInCompanies, 166
  - setSearchInContributories, 166
  - setSearchInProjects, 166
  - setSearchInReferentLastname, 166
  - setText, 167
- Models::User, 180
  - getDataMap, 181
  - getNoSiret, 181
  - getTitle, 181
  - getWorkspaceName, 182
  - getWorkspacePath, 182
  - hydrat, 182
  - operator==, 182
  - setNoSiret, 183
  - setTitle, 183
  - setWorkspaceName, 183
  - setWorkspacePath, 183
  - updateFolders, 183
  - User, 181
- Mustache::Tag
  - Comment, 175
  - InvertedSectionStart, 175
  - Partial, 175
  - SectionEnd, 175
  - SectionStart, 175
  - SetDelimiter, 175
- Mustache::Context, 61
  - canEval, 61
  - Context, 61
  - eval, 62
  - isFalse, 62
  - listCount, 62
  - partialResolver, 62
  - partialValue, 62
  - pop, 62
  - push, 62
  - stringValue, 62
- Mustache::PartialFileLoader, 122
  - getPartial, 122
- Mustache::PartialMap, 123
  - getPartial, 123
- Mustache::PartialResolver, 123
  - getPartial, 124
- Mustache::QtVariantContext, 153
  - canEval, 154



- eval, [154](#)
- fn\_t, [154](#)
- isFalse, [155](#)
- listCount, [155](#)
- pop, [155](#)
- push, [155](#)
- stringValue, [155](#)
- Mustache::Renderer, [161](#)
  - error, [161](#)
  - errorPartial, [161](#)
  - errorPos, [161](#)
  - render, [161](#)
  - setTagMarkers, [162](#)
- Mustache::Tag, [175](#)
  - Type, [175](#)
- operator<
  - Models::Billing, [29](#)
  - Models::Project, [135](#)
- operator<<
  - Utils::Log, [115](#)
- operator==
  - Models::Billing, [29](#)
  - Models::Contributory, [76](#)
  - Models::Customer, [85](#)
  - Models::People, [128](#)
  - Models::Project, [136](#)
  - Models::User, [182](#)
- paint
  - Gui::Widgets::Delegates::ComboBoxDelegate, [59](#)
  - Gui::Widgets::Delegates::ProjectComboDelegate, [139](#)
  - Gui::Widgets::Delegates::UnitComboDelegate, [178](#)
- Parameters, [121](#)
  - DB\_FILENAME, [122](#)
  - VERSION, [122](#)
- Partial
  - Mustache::Tag, [175](#)
- partialResolver
  - Mustache::Context, [62](#)
- partialValue
  - Mustache::Context, [62](#)
- PdfGenerator
  - Generator::PdfGenerator, [124](#)
- pop
  - Mustache::Context, [62](#)
  - Mustache::QtVariantContext, [155](#)
- popupMessage
  - Exceptions::DbException, [102](#)
  - Exceptions::FileException, [107](#)
- printInformations
  - Gui::Widgets::CustomerDataWidget, [93](#)
- Project
  - Models::Project, [133](#)
- ProjectComboDelegate
  - Gui::Widgets::Delegates::ProjectComboDelegate, [138](#)
- ProjectContributoriesTableModel
  - Gui::Widgets::WdgModels::ProjectContributoriesTableModel, [140](#)
- ProjectDatabaseTest, [148](#)
- ProjectModelTest, [149](#)
- ProjectsTableModel
  - Gui::Widgets::WdgModels::ProjectsTableModel, [150](#)
- ProjectsWidget
  - Gui::Widgets::ProjectsWidget, [153](#)
- push
  - Mustache::Context, [62](#)
  - Mustache::QtVariantContext, [155](#)
- Rate
  - Models::Rate, [156](#)
- RateModelTest, [159](#)
- RateWidget
  - Gui::Widgets::RateWidget, [160](#)
- remove
  - Gui::Widgets::WdgModels::BillingsTableModel, [39](#)
  - Gui::Widgets::WdgModels::ContributoriesTableModel, [70](#)
  - Gui::Widgets::WdgModels::CustomersTableModel, [96](#)
  - Gui::Widgets::WdgModels::ProjectContributoriesTableModel, [143](#)
  - Gui::Widgets::WdgModels::ProjectsTableModel, [151](#)
- removeBilling
  - Databases::BillingDatabase, [34](#)
- removeBillingProject
  - Databases::BillingDatabase, [34](#)
- removeContributory
  - Databases::ContributoryDatabase, [79](#)
- removeCustomer
  - Databases::CustomerDatabase, [91](#)
- removeProject
  - Databases::ProjectDatabase, [148](#)
- render
  - Mustache::Renderer, [161](#)
- rootTree
  - Gui::MainWindow, [118](#)
- rowCount
  - Gui::Widgets::WdgModels::BillingsTableModel, [39](#)
  - Gui::Widgets::WdgModels::ContributoriesTableModel, [70](#)
  - Gui::Widgets::WdgModels::CustomersTableModel, [96](#)
  - Gui::Widgets::WdgModels::ProjectContributoriesTableModel, [143](#)
  - Gui::Widgets::WdgModels::ProjectsTableModel, [151](#)
- search
  - Gui::Docks::SearchDock, [169](#)
  - Gui::MainWindow, [118](#)
  - Gui::Widgets::searchWidget, [171](#)
- SearchDock
  - Gui::Docks::SearchDock, [168](#)

- searchInContributories
  - Models::Search, 165
- searchTest, 169
- searchWidget
  - Gui::Widgets::searchWidget, 170
- SectionEnd
  - Mustache::Tag, 175
- SectionStart
  - Mustache::Tag, 175
- selectCustomer
  - Gui::Widgets::searchWidget, 171
- SetDelimiter
  - Mustache::Tag, 175
- setAddress
  - Models::People, 128
- setAllIdContributories
  - Models::ContributoriesList, 66
- setBeginDate
  - Models::Project, 136
- setBtnValid
  - Gui::Widgets::CheckFields::CheckQLineEdit, 54
- setCity
  - Models::People, 128
- setCompany
  - Models::People, 129
- setCopy
  - Gui::Dialogs::AddQuoteDialog, 24
- setCost
  - Models::Project, 136
- setCountry
  - Gui::Widgets::CheckFields::CheckPhone, 50
  - Gui::Widgets::CheckFields::CheckPostalCode, 52
  - Models::People, 129
- setCustomer
  - Models::Project, 136
- setDailyRate
  - Gui::Widgets::RateWidget, 160
  - Models::Project, 136
- setData
  - Gui::Widgets::WdgModels::BillingsTableModel, 39
  - Gui::Widgets::WdgModels::ContributoriesTable-Model, 70
  - Gui::Widgets::WdgModels::CustomersTableModel, 96
  - Gui::Widgets::WdgModels::ProjectContributories-TableModel, 143
  - Gui::Widgets::WdgModels::ProjectsTableModel, 152
- setDatabase
  - Databases::Database, 98
- setDate
  - Models::Billing, 29
- setDescription
  - Models::Billing, 29
  - Models::Contributory, 76
  - Models::Project, 136
- setEditorData
  - Gui::Widgets::Delegates::ComboBoxDelegate, 59
- Gui::Widgets::Delegates::DoubleSpinBoxDelegate, 105
- setEmail
  - Models::People, 129
- setEndDate
  - Models::Project, 137
- setFax
  - Models::People, 129
- setFirstname
  - Models::People, 129
- setGroupFilter
  - Models::Search, 166
- setHourlyRate
  - Gui::Widgets::RateWidget, 160
- setId
  - Models::IModel, 111
- setIdBilling
  - Models::ContributoriesList, 67
- setIdCustomer
  - Gui::Widgets::searchWidget, 171
- setImage
  - Gui::Dialogs::MessageBox, 121
- setInsert
  - Models::ContributoriesList, 67
- setIsBilling
  - Models::Billing, 29
- setIsPaid
  - Models::Billing, 30
- setLastname
  - Models::People, 129
- setLocked
  - Gui::Widgets::Delegates::ProjectComboDelegate, 139
- setMobilePhone
  - Models::People, 129
- setModelData
  - Gui::Widgets::Delegates::ComboBoxDelegate, 59
  - Gui::Widgets::Delegates::DoubleSpinBoxDelegate, 105
- setName
  - Models::Project, 137
  - Utils::ItemType, 113
- setNbHours
  - Models::Contributory, 76
- setNoSiret
  - Models::User, 183
- setNumber
  - Models::Billing, 30
- setPhone
  - Models::People, 131
- setPostalCode
  - Models::People, 131
- setProject
  - Models::Contributory, 76
- setQuoteIdNumber
  - Gui::Dialogs::AddQuoteDialog, 24
- setSearchInBillsQuotes
  - Models::Search, 166

- setSearchInCompanies
  - Models::Search, 166
- setSearchInContributories
  - Models::Search, 166
- setSearchInProjects
  - Models::Search, 166
- setSearchInReferentLastname
  - Models::Search, 166
- setTagMarkers
  - Mustache::Renderer, 162
- setText
  - Gui::Dialogs::MessageBox, 121
  - Models::Search, 167
- setTitle
  - Models::Billing, 30
  - Models::User, 183
- setToRemoved
  - Models::IModel, 111
- setTurnover
  - Models::Customer, 85
- setType
  - Utils::ItemType, 113
- setWidgetDailyRateValue
  - Gui::Widgets::RateWidget, 160
- setWidgetHourlyRateValue
  - Gui::Widgets::RateWidget, 161
- setWorkspaceName
  - Models::User, 183
- setWorkspacePath
  - Models::User, 183
- StartedWindowsDialog
  - Gui::Dialogs::StartedWindowsDialog, 173
- StringTest, 175
- stringValue
  - CounterContext, 82, 83
  - Mustache::Context, 62
  - Mustache::QtVariantContext, 155
- TestAdder< T >, 176
- TestMustache, 176
- TestRunner, 176
- testadder, 176
- TexGenerator
  - Generator::TexGenerator, 177
- textChanged
  - Gui::Docks::SearchDock, 169
- treeLevel
  - Gui::MainWindow, 120
- turnoverCompute
  - Models::Customer, 86
- Type
  - Mustache::Tag, 175
- UnitComboDelegate
  - Gui::Widgets::Delegates::UnitComboDelegate, 178
- updateBtn
  - Gui::Widgets::ProjectsWidget, 153
- updateCustomer
  - Databases::CustomerDatabase, 91
- updateEditorGeometry
  - Gui::Widgets::Delegates::ComboBoxDelegate, 60
  - Gui::Widgets::Delegates::DoubleSpinBoxDelegate, 106
- updateFolders
  - Models::User, 183
- updateProject
  - Databases::ProjectDatabase, 148
- updateRateProject
  - Databases::RateDatabase, 158
- User
  - Models::User, 181
- UserDataDialog
  - Gui::Dialogs::UserDataDialog, 186
- UserDatabaseTest, 185
- UserModelTest, 186
- Utils::Directories, 103
  - makeDirectory, 104
- Utils::HierarchicalSystem, 107
  - addBillingToProject, 108
  - addProjectToCustomer, 108
  - getCustomers, 108
  - getProjects, 108
- Utils::ItemType, 112
  - getModel, 112
  - getName, 113
  - getType, 113
  - ItemType, 112
  - setName, 113
  - setType, 113
- Utils::Log, 114
  - instance, 114
  - operator<<, 115
  - write, 114
- Utils::String, 174
  - firstLetterToUpper, 174
- Utils::pointers, 131
- VERSION
  - Parameters, 122
- value
  - Databases::Database, 99
- write
  - Utils::Log, 114