

FactDev

0.1

Generated by Doxygen 1.8.6

Sat Mar 28 2015 15:38:11

Contents

1	FactDev documentation	1
2	README	3
3	QTestRunner	5
4	Namespace Index	7
4.1	Namespace List	7
5	Hierarchical Index	9
5.1	Class Hierarchy	9
6	Class Index	13
6.1	Class List	13
7	Namespace Documentation	17
7.1	Databases Namespace Reference	17
7.1.1	Detailed Description	17
7.2	Gui Namespace Reference	17
7.2.1	Detailed Description	18
7.3	Gui::Widgets Namespace Reference	18
7.3.1	Detailed Description	18
7.4	Models Namespace Reference	18
7.4.1	Detailed Description	19
8	Class Documentation	21
8.1	Databases::AccessDatabase Class Reference	21
8.2	Gui::Dialogs::AddProjectDialog Class Reference	21
8.2.1	Detailed Description	22
8.2.2	Constructor & Destructor Documentation	22
8.2.2.1	AddProjectDialog	22
8.3	Gui::Dialogs::AddQuoteDialog Class Reference	22
8.3.1	Detailed Description	23
8.3.2	Constructor & Destructor Documentation	23

8.3.2.1	AddQuoteDialog	23
8.3.3	Member Function Documentation	24
8.3.3.1	fillQuoteBilling	24
8.3.3.2	getCopy	24
8.3.3.3	getIdCustomer	24
8.3.3.4	getNumber	24
8.3.3.5	setCopy	24
8.3.3.6	setQuoteIdNumber	25
8.4	Models::Billing Class Reference	25
8.4.1	Detailed Description	27
8.4.2	Constructor & Destructor Documentation	27
8.4.2.1	Billing	27
8.4.3	Member Function Documentation	27
8.4.3.1	addContributory	27
8.4.3.2	getContributories	27
8.4.3.3	getDataMap	27
8.4.3.4	getDate	27
8.4.3.5	getDescription	28
8.4.3.6	getFilename	28
8.4.3.7	getFolder	28
8.4.3.8	getItem	28
8.4.3.9	getNumber	28
8.4.3.10	getPath	28
8.4.3.11	getSumQuantity	28
8.4.3.12	getSumRate	29
8.4.3.13	getTitle	29
8.4.3.14	hydrat	29
8.4.3.15	isBilling	29
8.4.3.16	isPaid	29
8.4.3.17	operator!=	29
8.4.3.18	operator<	29
8.4.3.19	operator==	30
8.4.3.20	setDate	30
8.4.3.21	setDescription	30
8.4.3.22	setIsBilling	30
8.4.3.23	setIsPaid	30
8.4.3.24	setNumber	30
8.4.3.25	setTitle	31
8.5	Databases::BillingDatabase Class Reference	31
8.5.1	Detailed Description	32

8.5.2	Member Function Documentation	32
8.5.2.1	addBilling	32
8.5.2.2	addBillingProject	33
8.5.2.3	getAllBillingsOfProject	34
8.5.2.4	getBilling	34
8.5.2.5	getBilling	34
8.5.2.6	getBillingsTable	34
8.5.2.7	getBills	34
8.5.2.8	getBillsBetweenDates	35
8.5.2.9	getBillsPaid	35
8.5.2.10	getMaxBillingNumber	35
8.5.2.11	getMaxBillingNumberOfCustomer	35
8.5.2.12	getMaxQuoteNumber	36
8.5.2.13	getMaxQuoteNumberOfCustomer	36
8.5.2.14	getNbBills	36
8.5.2.15	getNbBillsPaid	36
8.5.2.16	getNbDocs	36
8.5.2.17	getNbQuotes	37
8.5.2.18	instance	38
8.5.2.19	isBillingPaid	38
8.5.2.20	removeBilling	38
8.5.2.21	removeBillingProject	38
8.6	BillingDatabaseTest Class Reference	39
8.7	BillingModelTest Class Reference	39
8.8	Gui::Widgets::WdgModels::BillingsTableModel Class Reference	39
8.8.1	Detailed Description	40
8.8.2	Constructor & Destructor Documentation	40
8.8.2.1	BillingsTableModel	40
8.8.3	Member Function Documentation	40
8.8.3.1	append	40
8.8.3.2	columnCount	41
8.8.3.3	count	41
8.8.3.4	data	41
8.8.3.5	flags	41
8.8.3.6	getBillings	41
8.8.3.7	headerData	41
8.8.3.8	remove	42
8.8.3.9	rowCount	42
8.8.3.10	setData	42
8.9	Gui::Widgets::CheckFields::CheckCity Class Reference	42

8.9.1	Detailed Description	43
8.9.2	Constructor & Destructor Documentation	43
8.9.2.1	CheckCity	43
8.10	Gui::Widgets::CheckFields::CheckCountry Class Reference	43
8.10.1	Detailed Description	44
8.10.2	Constructor & Destructor Documentation	44
8.10.2.1	CheckCountry	44
8.11	Gui::Widgets::CheckFields::CheckEmail Class Reference	44
8.11.1	Detailed Description	45
8.11.2	Constructor & Destructor Documentation	45
8.11.2.1	CheckEmail	45
8.11.3	Member Function Documentation	45
8.11.3.1	check	45
8.12	Gui::Widgets::CheckFields::CheckFieldsLetters Class Reference	46
8.12.1	Detailed Description	46
8.12.2	Constructor & Destructor Documentation	46
8.12.2.1	CheckFieldsLetters	46
8.12.3	Member Function Documentation	46
8.12.3.1	check	46
8.13	Gui::Widgets::CheckFields::CheckFieldsNumbers Class Reference	47
8.13.1	Detailed Description	47
8.13.2	Constructor & Destructor Documentation	47
8.13.2.1	CheckFieldsNumbers	47
8.13.3	Member Function Documentation	48
8.13.3.1	check	48
8.14	Gui::Widgets::CheckFields::CheckIpAddress Class Reference	48
8.14.1	Detailed Description	48
8.14.2	Constructor & Destructor Documentation	49
8.14.2.1	CheckIpAddress	49
8.14.3	Member Function Documentation	49
8.14.3.1	check	49
8.15	Gui::Widgets::CheckFields::CheckLogin Class Reference	49
8.15.1	Detailed Description	50
8.15.2	Constructor & Destructor Documentation	50
8.15.2.1	CheckLogin	50
8.15.3	Member Function Documentation	50
8.15.3.1	check	50
8.16	Gui::Widgets::CheckFields::CheckName Class Reference	51
8.16.1	Detailed Description	51
8.16.2	Constructor & Destructor Documentation	51

8.16.2.1	CheckName	51
8.17	Gui::Widgets::CheckFields::CheckPhone Class Reference	51
8.17.1	Detailed Description	52
8.17.2	Constructor & Destructor Documentation	52
8.17.2.1	CheckPhone	52
8.17.3	Member Function Documentation	52
8.17.3.1	check	52
8.17.3.2	getCountry	53
8.17.3.3	setCountry	53
8.18	Gui::Widgets::CheckFields::CheckPortNumber Class Reference	53
8.18.1	Detailed Description	53
8.18.2	Constructor & Destructor Documentation	54
8.18.2.1	CheckPortNumber	54
8.18.3	Member Function Documentation	54
8.18.3.1	check	54
8.19	Gui::Widgets::CheckFields::CheckPostalCode Class Reference	54
8.19.1	Detailed Description	55
8.19.2	Constructor & Destructor Documentation	55
8.19.2.1	CheckPostalCode	55
8.19.3	Member Function Documentation	55
8.19.3.1	check	55
8.19.3.2	getCountry	55
8.19.3.3	setCountry	55
8.20	Gui::Widgets::CheckFields::CheckQLineEdit Class Reference	56
8.20.1	Detailed Description	56
8.20.2	Constructor & Destructor Documentation	56
8.20.2.1	CheckQLineEdit	56
8.20.3	Member Function Documentation	57
8.20.3.1	getBtnValid	57
8.20.3.2	isValid	57
8.20.3.3	setBtnValid	57
8.21	Gui::Widgets::CheckFields::CheckSiretNumber Class Reference	57
8.21.1	Detailed Description	58
8.21.2	Constructor & Destructor Documentation	58
8.21.2.1	CheckSiretNumber	58
8.21.3	Member Function Documentation	58
8.21.3.1	check	58
8.22	Gui::Widgets::CheckFields::CheckUntilField Class Reference	58
8.22.1	Detailed Description	59
8.22.2	Constructor & Destructor Documentation	59

8.22.2.1	CheckUntilField	59
8.22.3	Member Function Documentation	59
8.22.3.1	check	59
8.23	Gui::Widgets::CheckFields::CheckValidField Class Reference	59
8.23.1	Detailed Description	60
8.23.2	Constructor & Destructor Documentation	60
8.23.2.1	CheckValidField	60
8.23.3	Member Function Documentation	60
8.23.3.1	check	60
8.24	Gui::Widgets::Delegates::ComboBoxDelegate Class Reference	61
8.24.1	Detailed Description	61
8.24.2	Constructor & Destructor Documentation	61
8.24.2.1	ComboBoxDelegate	61
8.24.3	Member Function Documentation	62
8.24.3.1	createEditor	62
8.24.3.2	paint	62
8.24.3.3	setEditorData	62
8.24.3.4	setModelData	62
8.24.3.5	updateEditorGeometry	63
8.25	Gui::Widgets::ComboBoxModelWidget Class Reference	63
8.25.1	Detailed Description	63
8.25.2	Constructor & Destructor Documentation	63
8.25.2.1	ComboBoxModelWidget	63
8.26	Gui::Dialogs::ComputeTurnoverDialog Class Reference	64
8.26.1	Detailed Description	64
8.26.2	Member Function Documentation	64
8.26.2.1	beginDateControl	64
8.26.2.2	endDateControl	65
8.26.2.3	fillLabels	65
8.27	Mustache::Context Class Reference	65
8.27.1	Detailed Description	66
8.27.2	Constructor & Destructor Documentation	66
8.27.2.1	Context	66
8.27.3	Member Function Documentation	66
8.27.3.1	canEval	66
8.27.3.2	eval	66
8.27.3.3	isFalse	66
8.27.3.4	listCount	66
8.27.3.5	partialResolver	66
8.27.3.6	partialValue	66

8.27.3.7	pop	67
8.27.3.8	push	67
8.27.3.9	stringValue	67
8.28	ContributoriesDatabaseTest Class Reference	67
8.29	Models::ContributoriesList Class Reference	67
8.29.1	Detailed Description	68
8.29.2	Member Function Documentation	68
8.29.2.1	addContributory	68
8.29.2.2	addProject	69
8.29.2.3	getAllContributories	69
8.29.2.4	getContributories	69
8.29.2.5	getCustomer	69
8.29.2.6	getDataMap	69
8.29.2.7	getIldBilling	69
8.29.2.8	getNbProjects	70
8.29.2.9	getProjects	70
8.29.2.10	getRate	70
8.29.2.11	getSumQuantity	70
8.29.2.12	getSumRate	70
8.29.2.13	isInsert	70
8.29.2.14	setAllIldContributories	70
8.29.2.15	setIldBilling	71
8.29.2.16	setInsert	71
8.30	Gui::Widgets::WdgModels::ContributoriesTableModel Class Reference	71
8.30.1	Detailed Description	72
8.30.2	Constructor & Destructor Documentation	72
8.30.2.1	ContributoriesTableModel	72
8.30.3	Member Function Documentation	72
8.30.3.1	append	72
8.30.3.2	columnCount	72
8.30.3.3	count	73
8.30.3.4	data	73
8.30.3.5	flags	73
8.30.3.6	getContributories	73
8.30.3.7	getSumQuantity	73
8.30.3.8	headerData	73
8.30.3.9	remove	74
8.30.3.10	rowCount	74
8.30.3.11	setData	74
8.31	Gui::Widgets::ContributoriesWidget Class Reference	74

8.31.1 Detailed Description	75
8.31.2 Constructor & Destructor Documentation	75
8.31.2.1 ContributoriesWidget	75
8.31.3 Member Function Documentation	76
8.31.3.1 add	76
8.31.3.2 addProject	76
8.31.3.3 count	76
8.31.3.4 getContributories	76
8.32 Models::Contributory Class Reference	76
8.32.1 Detailed Description	77
8.32.2 Constructor & Destructor Documentation	78
8.32.2.1 Contributory	78
8.32.3 Member Function Documentation	79
8.32.3.1 getDataMap	79
8.32.3.2 getDescription	79
8.32.3.3 getNbHours	79
8.32.3.4 getProject	79
8.32.3.5 hydrat	79
8.32.3.6 operator!=	79
8.32.3.7 operator==	80
8.32.3.8 setDescription	80
8.32.3.9 setNbHours	80
8.32.3.10 setProject	80
8.33 Databases::ContributoryDatabase Class Reference	80
8.33.1 Detailed Description	81
8.33.2 Member Function Documentation	81
8.33.2.1 addContributory	81
8.33.2.2 getContributoriesByBilling	82
8.33.2.3 getContributoriesByBillingAndProject	83
8.33.2.4 getContributory	83
8.33.2.5 getContributory	83
8.33.2.6 instance	83
8.33.2.7 removeContributory	84
8.34 ContributoryListTest Class Reference	85
8.35 ContributoryModelTest Class Reference	85
8.36 CounterContext Class Reference	85
8.36.1 Member Function Documentation	86
8.36.1.1 canEval	86
8.36.1.2 canEval	86
8.36.1.3 eval	86

8.36.1.4	eval	86
8.36.1.5	stringValue	87
8.36.1.6	stringValue	87
8.37	Models::Customer Class Reference	87
8.37.1	Detailed Description	88
8.37.2	Constructor & Destructor Documentation	88
8.37.2.1	Customer	88
8.37.3	Member Function Documentation	88
8.37.3.1	getDataMap	88
8.37.3.2	getNameFolder	88
8.37.3.3	getPath	88
8.37.3.4	getTurnover	88
8.37.3.5	hydrat	89
8.38	Gui::Widgets::CustomerContextualMenu Class Reference	90
8.38.1	Detailed Description	90
8.38.2	Constructor & Destructor Documentation	90
8.38.2.1	CustomerContextualMenu	90
8.39	Databases::CustomerDatabase Class Reference	91
8.39.1	Detailed Description	92
8.39.2	Member Function Documentation	92
8.39.2.1	addCustomer	92
8.39.2.2	getCustomer	92
8.39.2.3	getCustomer	92
8.39.2.4	getCustomers	92
8.39.2.5	getCustomersTable	93
8.39.2.6	getItemCustomer	94
8.39.2.7	getItemProject	94
8.39.2.8	getItemRoot	94
8.39.2.9	getNbCustomers	94
8.39.2.10	getTree	94
8.39.2.11	instance	95
8.39.2.12	removeCustomer	95
8.39.2.13	updateCustomer	95
8.40	CustomerDatabaseTest Class Reference	95
8.41	Gui::Widgets::CustomerDataWidget Class Reference	96
8.41.1	Detailed Description	96
8.41.2	Constructor & Destructor Documentation	96
8.41.2.1	CustomerDataWidget	96
8.41.3	Member Function Documentation	96
8.41.3.1	printInformations	96

8.42	CustomerModelTest Class Reference	97
8.43	Gui::Widgets::WdgModels::CustomersTableModel Class Reference	97
8.43.1	Detailed Description	98
8.43.2	Constructor & Destructor Documentation	98
8.43.2.1	CustomersTableModel	98
8.43.3	Member Function Documentation	98
8.43.3.1	append	98
8.43.3.2	columnCount	98
8.43.3.3	count	99
8.43.3.4	data	99
8.43.3.5	flags	99
8.43.3.6	getCustomers	99
8.43.3.7	headerData	99
8.43.3.8	remove	100
8.43.3.9	rowCount	100
8.43.3.10	setData	100
8.44	Databases::Database Class Reference	100
8.44.1	Detailed Description	102
8.44.2	Member Function Documentation	102
8.44.2.1	changeDatabase	102
8.44.2.2	executeFile	102
8.44.2.3	instance	102
8.44.2.4	lastError	102
8.44.2.5	setDatabase	103
8.44.2.6	value	103
8.45	Gui::Widgets::DatabaseSettingsWidget Class Reference	103
8.45.1	Detailed Description	104
8.45.2	Constructor & Destructor Documentation	104
8.45.2.1	DatabaseSettingsWidget	104
8.45.3	Member Function Documentation	104
8.45.3.1	getDatabaseName	104
8.45.3.2	getDomainNameOrIP	105
8.45.3.3	getLogin	105
8.45.3.4	getPassword	105
8.45.3.5	getPort	105
8.45.3.6	isValid	105
8.46	Exceptions::DbException Class Reference	105
8.46.1	Detailed Description	106
8.46.2	Constructor & Destructor Documentation	106
8.46.2.1	DbException	106

8.46.3	Member Function Documentation	106
8.46.3.1	popupMessage	106
8.47	Gui::Dialogs::DialogAddCustomer Class Reference	107
8.47.1	Detailed Description	107
8.47.2	Constructor & Destructor Documentation	107
8.47.2.1	DialogAddCustomer	107
8.48	Utils::Directories Class Reference	108
8.48.1	Member Function Documentation	108
8.48.1.1	makeDirectory	108
8.49	Gui::Widgets::Delegates::DoubleSpinBoxDelegate Class Reference	108
8.49.1	Detailed Description	109
8.49.2	Constructor & Destructor Documentation	109
8.49.2.1	DoubleSpinBoxDelegate	109
8.49.3	Member Function Documentation	109
8.49.3.1	createEditor	109
8.49.3.2	setEditorData	109
8.49.3.3	setModelData	110
8.49.3.4	updateEditorGeometry	110
8.50	Exceptions::FileException Class Reference	110
8.50.1	Detailed Description	110
8.50.2	Constructor & Destructor Documentation	111
8.50.2.1	FileException	111
8.50.3	Member Function Documentation	112
8.50.3.1	popupMessage	112
8.51	Generation Class Reference	112
8.52	Utils::HierarchicalSystem Class Reference	112
8.52.1	Detailed Description	113
8.52.2	Member Function Documentation	113
8.52.2.1	addBillingToProject	113
8.52.2.2	addProjectToCustomer	113
8.52.2.3	getCustomers	113
8.52.2.4	getProjects	114
8.53	Gui::Widgets::CheckFields::!CheckField Class Reference	114
8.53.1	Detailed Description	114
8.53.2	Member Function Documentation	114
8.53.2.1	check	114
8.54	Models::!Model Class Reference	115
8.54.1	Detailed Description	115
8.54.2	Member Function Documentation	116
8.54.2.1	getDataMap	116

8.54.2.2	getId	116
8.54.2.3	hydrat	116
8.54.2.4	isToRemoved	116
8.54.2.5	setId	116
8.54.2.6	setToRemoved	116
8.55	Utils::ItemType Class Reference	117
8.55.1	Detailed Description	117
8.55.2	Constructor & Destructor Documentation	117
8.55.2.1	ItemType	117
8.55.3	Member Function Documentation	118
8.55.3.1	getModel	118
8.55.3.2	getName	118
8.55.3.3	getType	118
8.55.3.4	setName	118
8.55.3.5	setType	118
8.56	ItemTypeTest Class Reference	119
8.57	Utils::Log Class Reference	119
8.57.1	Detailed Description	119
8.57.2	Member Function Documentation	119
8.57.2.1	instance	119
8.57.2.2	write	120
8.57.3	Friends And Related Function Documentation	120
8.57.3.1	operator<<	120
8.58	Gui::MainWindow Class Reference	120
8.58.1	Detailed Description	122
8.58.2	Constructor & Destructor Documentation	122
8.58.2.1	MainWindow	122
8.58.3	Member Function Documentation	122
8.58.3.1	addBill	122
8.58.3.2	addDoc	123
8.58.3.3	addProject	123
8.58.3.4	addQuote	123
8.58.3.5	editUser	123
8.58.3.6	getCurrentCustomerId	123
8.58.3.7	getCurrentCustomerName	123
8.58.3.8	getCurrentProjectId	124
8.58.3.9	getCurrentProjectName	124
8.58.3.10	getCurrentQuoteId	124
8.58.3.11	resizeEvent	124
8.58.3.12	rootTree	124

8.58.3.13 search	124
8.58.3.14 treeLevel	124
8.59 Gui::Dialogs::MessageBox Class Reference	125
8.59.1 Detailed Description	125
8.59.2 Constructor & Destructor Documentation	126
8.59.2.1 MessageBox	126
8.59.3 Member Function Documentation	126
8.59.3.1 setImage	126
8.59.3.2 setText	126
8.60 Parameters Class Reference	126
8.60.1 Detailed Description	126
8.60.2 Member Data Documentation	127
8.60.2.1 DB_FILENAME	127
8.60.2.2 VERSION	127
8.61 Mustache::PartialFileLoader Class Reference	127
8.61.1 Detailed Description	127
8.61.2 Member Function Documentation	127
8.61.2.1 getPartial	127
8.62 Mustache::PartialMap Class Reference	128
8.62.1 Detailed Description	128
8.62.2 Member Function Documentation	128
8.62.2.1 getPartial	128
8.63 Mustache::PartialResolver Class Reference	128
8.63.1 Detailed Description	128
8.63.2 Member Function Documentation	129
8.63.2.1 getPartial	129
8.64 Generator::PdfGenerator Class Reference	129
8.64.1 Detailed Description	129
8.64.2 Constructor & Destructor Documentation	129
8.64.2.1 PdfGenerator	129
8.64.3 Member Function Documentation	129
8.64.3.1 generate	129
8.65 Models::People Class Reference	130
8.65.1 Detailed Description	131
8.65.2 Member Function Documentation	131
8.65.2.1 getAddress	131
8.65.2.2 getCity	131
8.65.2.3 getCompany	131
8.65.2.4 getCountry	131
8.65.2.5 getEmail	132

8.65.2.6	getFax	132
8.65.2.7	getFirstname	132
8.65.2.8	getLastname	132
8.65.2.9	getMobilePhone	132
8.65.2.10	getPhone	132
8.65.2.11	getPostalCode	132
8.65.2.12	operator!=	133
8.65.2.13	operator==	134
8.65.2.14	setAddress	134
8.65.2.15	setCity	134
8.65.2.16	setCompany	134
8.65.2.17	setCountry	134
8.65.2.18	setEmail	135
8.65.2.19	setFax	135
8.65.2.20	setFirstname	135
8.65.2.21	setLastname	135
8.65.2.22	setMobilePhone	135
8.65.2.23	setPhone	135
8.65.2.24	setPostalCode	135
8.66	Utils::pointers Class Reference	136
8.67	PointersTest Class Reference	136
8.68	Gui::Widgets::Popup Class Reference	136
8.68.1	Detailed Description	136
8.69	Models::Project Class Reference	137
8.69.1	Detailed Description	138
8.69.2	Constructor & Destructor Documentation	138
8.69.2.1	Project	138
8.69.3	Member Function Documentation	139
8.69.3.1	computeProjectCost	139
8.69.3.2	getBeginDate	139
8.69.3.3	getCost	139
8.69.3.4	getCustomer	139
8.69.3.5	getDailyRate	139
8.69.3.6	getDataMap	139
8.69.3.7	getDescription	140
8.69.3.8	getEndDate	140
8.69.3.9	getName	140
8.69.3.10	hydrat	140
8.69.3.11	operator!=	140
8.69.3.12	operator<	140

8.69.3.13 operator==	141
8.69.3.14 setBeginDate	141
8.69.3.15 setCost	141
8.69.3.16 setCustomer	141
8.69.3.17 setDailyRate	141
8.69.3.18 setDescription	142
8.69.3.19 setEndDate	142
8.69.3.20 setName	142
8.70 Gui::Widgets::Delegates::ProjectComboDelegate Class Reference	142
8.70.1 Detailed Description	143
8.70.2 Constructor & Destructor Documentation	143
8.70.2.1 ProjectComboDelegate	143
8.70.3 Member Function Documentation	143
8.70.3.1 createEditor	143
8.70.3.2 getProjects	143
8.70.3.3 isLocked	144
8.70.3.4 paint	144
8.70.3.5 setLocked	144
8.71 Gui::Widgets::WdgModels::ProjectContributoriesTableModel Class Reference	144
8.71.1 Detailed Description	145
8.71.2 Constructor & Destructor Documentation	145
8.71.2.1 ProjectContributoriesTableModel	145
8.71.3 Member Function Documentation	146
8.71.3.1 allProjectsChosen	146
8.71.3.2 append	146
8.71.3.3 columnCount	146
8.71.3.4 data	146
8.71.3.5 flags	146
8.71.3.6 getProject	146
8.71.3.7 getProjects	147
8.71.3.8 getSelectedProjects	147
8.71.3.9 headerData	147
8.71.3.10 remove	147
8.71.3.11 rowCount	147
8.71.3.12 setData	148
8.72 Databases::ProjectDatabase Class Reference	149
8.72.1 Detailed Description	150
8.72.2 Member Function Documentation	150
8.72.2.1 addProject	150
8.72.2.2 getAllProjects	150

8.72.2.3	getCostProjects	150
8.72.2.4	getNbProjects	151
8.72.2.5	getNbProjects	151
8.72.2.6	getProject	151
8.72.2.7	getProject	151
8.72.2.8	getProjects	151
8.72.2.9	getProjectsOfCustomer	152
8.72.2.10	getProjectsTable	152
8.72.2.11	instance	152
8.72.2.12	removeProject	152
8.72.2.13	updateProject	152
8.73	ProjectDatabaseTest Class Reference	153
8.74	ProjectModelTest Class Reference	153
8.75	Gui::Widgets::WdgModels::ProjectsTableModel Class Reference	153
8.75.1	Detailed Description	154
8.75.2	Constructor & Destructor Documentation	154
8.75.2.1	ProjectsTableModel	154
8.75.3	Member Function Documentation	155
8.75.3.1	append	155
8.75.3.2	columnCount	155
8.75.3.3	count	155
8.75.3.4	data	155
8.75.3.5	flags	155
8.75.3.6	getProjects	156
8.75.3.7	headerData	156
8.75.3.8	remove	156
8.75.3.9	rowCount	156
8.75.3.10	setData	156
8.76	Gui::Widgets::ProjectsWidget Class Reference	157
8.76.1	Detailed Description	157
8.76.2	Constructor & Destructor Documentation	157
8.76.2.1	ProjectsWidget	157
8.76.3	Member Function Documentation	158
8.76.3.1	updateBtn	158
8.77	Mustache::QtVariantContext Class Reference	158
8.77.1	Detailed Description	158
8.77.2	Member Typedef Documentation	159
8.77.2.1	fn_t	159
8.77.3	Member Function Documentation	159
8.77.3.1	canEval	159

8.77.3.2	eval	159
8.77.3.3	isFalse	159
8.77.3.4	listCount	159
8.77.3.5	pop	159
8.77.3.6	push	160
8.77.3.7	stringValue	160
8.78	Models::Rate Class Reference	160
8.78.1	Detailed Description	160
8.78.2	Constructor & Destructor Documentation	161
8.78.2.1	Rate	161
8.78.2.2	Rate	161
8.78.3	Member Function Documentation	161
8.78.3.1	getDailyRate	161
8.78.3.2	getHourlyRate	161
8.78.3.3	getLegalRate	161
8.78.3.4	getNbDailyHours	161
8.79	Databases::RateDatabase Class Reference	162
8.79.1	Member Function Documentation	162
8.79.1.1	addRateProject	162
8.79.1.2	getRate	162
8.79.1.3	instance	163
8.79.1.4	updateRateProject	163
8.80	RateModelTest Class Reference	163
8.81	Gui::Widgets::RateWidget Class Reference	163
8.81.1	Detailed Description	164
8.81.2	Constructor & Destructor Documentation	164
8.81.2.1	RateWidget	164
8.81.3	Member Function Documentation	164
8.81.3.1	getDailyRate	164
8.81.3.2	getHourlyRate	165
8.81.3.3	setDailyRate	165
8.81.3.4	setHourlyRate	165
8.81.3.5	setWidgetDailyRateValue	165
8.81.3.6	setWidgetHourlyRateValue	165
8.82	Mustache::Renderer Class Reference	165
8.82.1	Detailed Description	166
8.82.2	Member Function Documentation	166
8.82.2.1	error	166
8.82.2.2	errorPartial	166
8.82.2.3	errorPos	166

8.82.2.4	render	166
8.82.2.5	setTagMarkers	166
8.83	Models::Search Class Reference	166
8.83.1	Detailed Description	168
8.83.2	Member Function Documentation	168
8.83.2.1	filterOnBillsOrQuotes	168
8.83.2.2	filterOnCompany	168
8.83.2.3	filterOnContributories	168
8.83.2.4	filterOnCustomersWithoutProject	168
8.83.2.5	filterOnNumberElements	168
8.83.2.6	filterOnProjects	169
8.83.2.7	filterOnReferentLastname	169
8.83.2.8	filterOnVarcharElements	169
8.83.2.9	getFilter	169
8.83.2.10	getGroupFilter	169
8.83.2.11	getSearchInBillsQuotes	169
8.83.2.12	getSearchInCompanies	170
8.83.2.13	getSearchInProjects	170
8.83.2.14	getSearchInReferentLastname	170
8.83.2.15	getText	170
8.83.2.16	searchInContributories	170
8.83.2.17	setGroupFilter	170
8.83.2.18	setSearchInBillsQuotes	171
8.83.2.19	setSearchInCompanies	171
8.83.2.20	setSearchInContributories	171
8.83.2.21	setSearchInProjects	171
8.83.2.22	setSearchInReferentLastname	171
8.83.2.23	setText	171
8.84	Gui::Docks::SearchDock Class Reference	172
8.84.1	Detailed Description	172
8.84.2	Constructor & Destructor Documentation	172
8.84.2.1	SearchDock	172
8.84.3	Member Function Documentation	173
8.84.3.1	search	173
8.84.3.2	textChanged	173
8.85	searchTest Class Reference	173
8.86	Gui::Widgets::searchWidget Class Reference	173
8.86.1	Detailed Description	174
8.86.2	Constructor & Destructor Documentation	174
8.86.2.1	searchWidget	174

8.86.3	Member Function Documentation	175
8.86.3.1	getCurrentCustomerId	175
8.86.3.2	getIdCustomer	175
8.86.3.3	isCustomerSelected	175
8.86.3.4	search	175
8.86.3.5	selectCustomer	175
8.86.3.6	setIdCustomer	175
8.87	Gui::Dialogs::StartedWindowsDialog Class Reference	176
8.87.1	Detailed Description	177
8.87.2	Constructor & Destructor Documentation	177
8.87.2.1	StartedWindowsDialog	177
8.87.3	Member Function Documentation	177
8.87.3.1	databaseTypeChanged	177
8.87.3.2	getImage	177
8.87.3.3	isDatabaseCentralized	177
8.87.3.4	isDatabaseTypeValid	178
8.88	StatisticModelTest Class Reference	178
8.89	Models::Statistics Class Reference	178
8.89.1	Member Function Documentation	178
8.89.1.1	getGlobalTurnover	178
8.89.1.2	getTurnoverBetweenDates	178
8.90	Gui::Dialogs::StatisticsDialog Class Reference	179
8.90.1	Detailed Description	179
8.90.2	Constructor & Destructor Documentation	179
8.90.2.1	StatisticsDialog	179
8.90.3	Member Function Documentation	180
8.90.3.1	singularPlural	180
8.91	Utils::String Class Reference	181
8.91.1	Detailed Description	181
8.91.2	Member Function Documentation	181
8.91.2.1	firstLetterToUpper	181
8.92	StringTest Class Reference	181
8.93	Mustache::Tag Struct Reference	182
8.93.1	Detailed Description	182
8.93.2	Member Enumeration Documentation	182
8.93.2.1	Type	182
8.94	testadder Class Reference	182
8.95	TestAdder< T > Class Template Reference	183
8.96	TestMustache Class Reference	183
8.97	TestRunner Class Reference	183

8.98	Generator::TexGenerator Class Reference	183
8.98.1	Detailed Description	184
8.98.2	Constructor & Destructor Documentation	184
8.98.2.1	TexGenerator	184
8.98.3	Member Function Documentation	184
8.98.3.1	generate	184
8.99	Gui::Widgets::Delegates::TextareaDelegate Class Reference	184
8.99.1	Detailed Description	185
8.99.2	Constructor & Destructor Documentation	185
8.99.2.1	TextareaDelegate	185
8.99.3	Member Function Documentation	185
8.99.3.1	createEditor	185
8.99.3.2	setEditorData	185
8.99.3.3	setModelData	186
8.99.3.4	updateEditorGeometry	186
8.100	Gui::Widgets::Delegates::UnitComboDelegate Class Reference	186
8.100.1	Detailed Description	187
8.100.2	Constructor & Destructor Documentation	187
8.100.2.1	UnitComboDelegate	187
8.100.3	Member Function Documentation	187
8.100.3.1	createEditor	187
8.100.3.2	paint	187
8.101	Models::User Class Reference	188
8.101.1	Detailed Description	189
8.101.2	Constructor & Destructor Documentation	189
8.101.2.1	User	189
8.101.3	Member Function Documentation	189
8.101.3.1	getDataMap	189
8.101.3.2	getNoSiret	189
8.101.3.3	getTitle	189
8.101.3.4	getWorkspaceName	189
8.101.3.5	getWorkspacePath	190
8.101.3.6	hydrat	190
8.101.3.7	operator!=	190
8.101.3.8	operator==	190
8.101.3.9	setNoSiret	190
8.101.3.10	setTitle	190
8.101.3.11	setWorkspaceName	191
8.101.3.12	setWorkspacePath	191
8.101.3.13	updateFolders	191

8.102Databases::UserDatabase Class Reference	191
8.102.1 Detailed Description	192
8.102.2 Member Function Documentation	192
8.102.2.1 getUser	192
8.102.2.2 instance	192
8.103UserDatabaseTest Class Reference	193
8.104Gui::Dialogs::UserDataDialog Class Reference	193
8.104.1 Detailed Description	193
8.104.2 Constructor & Destructor Documentation	194
8.104.2.1 UserDataDialog	194
8.105UserModelTest Class Reference	194
Index	195

Chapter 1

FactDev documentation

This website contains the documentation of FactDev, a billings and quotes software.

Team

FACT team is a team for University Project. Members of this team are :

- Florent Berbie ([KraTuX31](#))
- Antoine de Roquemaurel ([aroquemaurel](#))
- Cédric Rohaut ([Oxynos](#))
- Manantsoa Andriamihary Razanajatovo ([manantsoa](#))

For more informations, you can go to <http://fact-team.github.io>.

What is FactDev ?

FactDev is a software for quotes and billings developped by FACT team for university project in Toulouse III University – Paul Sabatier.

This software is developed with C++ and Qt framework, and there is differents features :

- Customers database
- Differents projects for customers
- Quotes
- Billings

Documentation

You can access to the documentation generated by Doxygen here :

- [HTML Documentation](#)
- [PDF Documentation](#)

Installation and using

- [User Manual](#)

Chapter 2

README

! [Build Status] (<https://travis-ci.org/robertknight/qt-mustache.svg?branch=master>)

Qt Mustache

qt-mustache is a simple library for rendering `Mustache templates`.

Example Usage

```
“cpp #include "mustache.h"
```

```
QVariantHash contact; contact["name"] = "John Smith"; contact["email"] = "john.smith@gmail.com";
```

```
QString contactTemplate = "<b>{{name}}</b> <a href='mailto:{{email}}'>{{email}}";
```

```
Mustache::Renderer renderer; Mustache::QtVariantContext context(contact);
```

```
QTextStream output(stdout); output << renderer.render(contactTemplate, &context); “
```

Outputs: `John Smith john.smith@gmail.com`

For further examples, see the tests in `test_mustache.cpp`

Building

- To build the tests, run `qmake` followed by `make`
- To use qt-mustache in your project, just add the `mustache.h` and `mustache.cpp` files to your project.

License

qt-mustache is licensed under the BSD license.

Dependencies

qt-mustache depends on the QtCore library. It is compatible with Qt 4 and Qt 5.

Usage

Syntax

qt-mustache uses the standard Mustache syntax. See the [Mustache manual](#) for details.

Data Sources

qt-mustache expands Mustache tags using values from a `Mustache::Context`. `Mustache::QtVariantContext` is a simple context implementation which wraps a `QVariantHash` or `QVariantMap`. If you want to render a template using a custom data source, you can either create a `QVariantHash` which mirrors the data source or you can re-implement `Mustache::Context`.

Partials

When a `{{>partial}}` Mustache tag is encountered, qt-mustache will attempt to load the partial using a `Mustache::PartialResolver` provided by the context. `Mustache::PartialMap` is a simple resolver which takes a `QHash<QString,QString>` map of partial names to values and looks up partials in that map. `Mustache::PartialFileLoader` is another simple resolver which fetches partials from `<partial name>.mustache` files in a specified directory.

You can re-implement the `Mustache::PartialResolver` interface if you want to load partials from a custom source (eg. a database).

Error Handling

If an error occurs when rendering a template, `Mustache::Renderer::errorPosition()` is set to non-negative value and template rendering stops. If the error occurs whilst rendering a partial template, `errorPartial()` contains the name of the partial.

Lambdas

The [Mustache manual](#) provides a mechanism to customize rendering of template sections by setting the value for a tag to a callable object (eg. a lambda in Ruby or Javascript), which takes the unrendered block of text for a template section and renders it itself. qt-mustache supports this via the `Context::canEval()` and `Context::eval()` methods.

Chapter 3

QTestRunner

A repo for Increase QTest productivity

Thanks to <https://marcoarena.wordpress.com/2012/06/23/increase-your-qtest-productivity/>!

The QTestLib framework is a tool for unit testing Qt based applications and libraries. I find it precious and simple to use, though it lacks some important features, supported, for example, by GTest. I'm not talking about mocking – for this you generally need an out-and-out framework (like GMock) – instead, I'm referring to simple things like fast deploying. Suppose you have written a test class like this:

This repo contains only the code in this article.

Chapter 4

Namespace Index

4.1 Namespace List

Here is a list of all documented namespaces with brief descriptions:

Databases		
	Class for Database , contains queries	??
Gui	??
Gui::Widgets		
	Contains Widgets classes	??
Models		
	Models classes	??

Chapter 5

Hierarchical Index

5.1 Class Hierarchy

This inheritance list is sorted roughly, but not completely, alphabetically:

Databases::AccessDatabase	??
Mustache::Context	??
Mustache::QtVariantContext	??
CounterContext	??
CounterContext	??
Databases::Database	??
Databases::BillingDatabase	??
Databases::ContributoryDatabase	??
Databases::CustomerDatabase	??
Databases::ProjectDatabase	??
Databases::RateDatabase	??
Databases::UserDatabase	??
Utils::Directories	??
exception	
Exceptions::DbException	??
Exceptions::FileException	??
Utils::HierarchicalSystem	??
Gui::Widgets::CheckFields::ICheckField	??
Gui::Widgets::CheckFields::CheckQLineEdit	??
Gui::Widgets::CheckFields::CheckEmail	??
Gui::Widgets::CheckFields::CheckPortNumber	??
Gui::Widgets::CheckFields::CheckSiretNumber	??
Gui::Widgets::CheckFields::CheckUntilField	??
Gui::Widgets::CheckFields::CheckFieldsLetters	??
Gui::Widgets::CheckFields::CheckCity	??
Gui::Widgets::CheckFields::CheckCountry	??
Gui::Widgets::CheckFields::CheckName	??
Gui::Widgets::CheckFields::CheckFieldsNumbers	??
Gui::Widgets::CheckFields::CheckIpAddress	??
Gui::Widgets::CheckFields::CheckLogin	??
Gui::Widgets::CheckFields::CheckPhone	??
Gui::Widgets::CheckFields::CheckPostalCode	??
Gui::Widgets::CheckFields::CheckValidField	??
Models::IModel	??
Models::Billing	??
Models::Contributory	??
Models::Customer	??

Models::Project	??
Models::User	??
Utils::ItemType	??
Utils::Log	??
Parameters	??
Mustache::PartialResolver	??
Mustache::PartialFileLoader	??
Mustache::PartialMap	??
Generator::PdfGenerator	??
Models::People	??
Models::Customer	??
Models::User	??
Utils::pointers	??
Gui::Widgets::Popup	??
QAbstractTableModel	
Gui::Widgets::WdgModels::BillingsTableModel	??
Gui::Widgets::WdgModels::ContributoriesTableModel	??
Gui::Widgets::WdgModels::CustomersTableModel	??
Gui::Widgets::WdgModels::ProjectContributoriesTableModel	??
Gui::Widgets::WdgModels::ProjectsTableModel	??
QDialog	
Gui::Dialogs::AddProjectDialog	??
Gui::Dialogs::AddQuoteDialog	??
Gui::Dialogs::ComputeTurnoverDialog	??
Gui::Dialogs::DialogAddCustomer	??
Gui::Dialogs::MessageBox	??
Gui::Dialogs::StartedWindowsDialog	??
Gui::Dialogs::StatisticsDialog	??
Gui::Dialogs::UserDataDialog	??
QDockWidget	
Gui::Docks::SearchDock	??
QItemDelegate	
Gui::Widgets::Delegates::ComboBoxDelegate	??
Gui::Widgets::Delegates::ProjectComboDelegate	??
Gui::Widgets::Delegates::UnitComboDelegate	??
Gui::Widgets::Delegates::DoubleSpinBoxDelegate	??
Gui::Widgets::Delegates::TextareaDelegate	??
QLineEdit	
Gui::Widgets::CheckFields::CheckQLineEdit	??
QMainWindow	
Gui::MainWindow	??
QMap	
Models::ContributoriesList	??
QMenu	
Gui::Widgets::CustomerContextualMenu	??
QObject	
BillingDatabaseTest	??
BillingModelTest	??
ContributoriesDatabaseTest	??
ContributoryListTest	??
ContributoryModelTest	??
CustomerDatabaseTest	??
CustomerModelTest	??
Generation	??
ItemTypeTest	??
PointersTest	??
ProjectDatabaseTest	??
ProjectModelTest	??

RateModelTest	??
searchTest	??
StatisticModelTest	??
StringTest	??
TestMustache	??
TestMustache	??
UserDatabaseTest	??
UserModelTest	??
QWidget	
Gui::Widgets::ComboBoxModelWidget	??
Gui::Widgets::ContributoriesWidget	??
Gui::Widgets::CustomerDataWidget	??
Gui::Widgets::DatabaseSettingsWidget	??
Gui::Widgets::ProjectsWidget	??
Gui::Widgets::RateWidget	??
Gui::Widgets::searchWidget	??
Models::Rate	??
Mustache::Renderer	??
Models::Search	??
Models::Statistics	??
Utils::String	??
Mustache::Tag	??
testadder	??
TestAdder< T >	??
TestRunner	??
Generator::TexGenerator	??

Chapter 6

Class Index

6.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

Databases::AccessDatabase	??
Gui::Dialogs::AddProjectDialog	
Windows to add a new Project	??
Gui::Dialogs::AddQuoteDialog	
Window to add or modify a Quote	??
Models::Billing	
: Billing or Quote of a Customer	??
Databases::BillingDatabase	
The BillingDatabase class Billing (or Quote) table database	??
BillingDatabaseTest	??
BillingModelTest	??
Gui::Widgets::WdgModels::BillingsTableModel	
For a Billing table	??
Gui::Widgets::CheckFields::CheckCity	
Line Edit of City with a check icon	??
Gui::Widgets::CheckFields::CheckCountry	
CheckCountry::CheckCountry Line Edit of country with a check icon	??
Gui::Widgets::CheckFields::CheckEmail	
Line Edit of email with a check icon	??
Gui::Widgets::CheckFields::CheckFieldsLetters	
Field with only letters (no numbers)	??
Gui::Widgets::CheckFields::CheckFieldsNumbers	
Line Edit of number with a check icon	??
Gui::Widgets::CheckFields::CheckIpAddress	
Line Edit of IP address with a check icon	??
Gui::Widgets::CheckFields::CheckLogin	
Line Edit of login with a check icon	??
Gui::Widgets::CheckFields::CheckName	
Line edit of name with a check icon	??
Gui::Widgets::CheckFields::CheckPhone	
Line Edit of Phone number with a check icon	??
Gui::Widgets::CheckFields::CheckPortNumber	
The CheckFieldsNumbers class Line Edit of number with a check icon	??
Gui::Widgets::CheckFields::CheckPostalCode	
Line Edit of postal code with a check icon	??
Gui::Widgets::CheckFields::CheckQLineEdit	
LineEdit custom with a check of text inputed	??

Gui::Widgets::CheckFields::CheckSiretNumber	
Line Edit with a check icon	??
Gui::Widgets::CheckFields::CheckUntilField	
The CheckUntilField class	??
Gui::Widgets::CheckFields::CheckValidField	
Check field not required	??
Gui::Widgets::Delegates::ComboBoxDelegate	
The ComboBoxDelegate class	??
Gui::Widgets::ComboBoxModelWidget	
Model of ComboBox	??
Gui::Dialogs::ComputeTurnoverDialog	
Window to compute a turnover with a period	??
Mustache::Context	??
ContributoriesDatabaseTest	??
Models::ContributoriesList	
List of contributories	??
Gui::Widgets::WdgModels::ContributoriesTableModel	
For a custom table for contributories widget	??
Gui::Widgets::ContributoriesWidget	
Widget of Contributories	??
Models::Contributory	
The Contributory class	??
Databases::ContributoryDatabase	
The ContributoryDatabase class Contributory (or Quote) table database	??
ContributoryListTest	??
ContributoryModelTest	??
CounterContext	??
Models::Customer	
Customer	??
Gui::Widgets::CustomerContextualMenu	
Display contextual menu on a customer	??
Databases::CustomerDatabase	
The CustomerDatabase class Customer table database	??
CustomerDatabaseTest	??
Gui::Widgets::CustomerDataWidget	
Class for display info of a customer	??
CustomerModelTest	??
Gui::Widgets::WdgModels::CustomersTableModel	
For a customer table	??
Databases::Database	
The Database class Master class for all database access	??
Gui::Widgets::DatabaseSettingsWidget	
Windows of database settings	??
Exceptions::DbException	
For database exception : queries, db file,	??
Gui::Dialogs::DialogAddCustomer	
Window to add or modify a Customer	??
Utils::Directories	??
Gui::Widgets::Delegates::DoubleSpinBoxDelegate	
The DoubleSpinBoxDelegate class	??
Exceptions::FileException	
For file/access file exception	??
Generation	??
Utils::HierarchicalSystem	
Create class which contains hierarchical system of FactDev	??
Gui::Widgets::CheckFields::ICheckField	
Interface to check fields validity	??

Models::IModel	
The IModel class	??
Utils::ItemType	
Item type model	??
ItemTypeTest	??
Utils::Log	
For Simple management of log	??
Gui::MainWindow	
Main Window of the software	??
Gui::Dialogs::MessageBox	
Information window with message	??
Parameters	
Class for simple user parameters	??
Mustache::PartialFileLoader	??
Mustache::PartialMap	??
Mustache::PartialResolver	??
Generator::PdfGenerator	
Generator of PDF files	??
Models::People	
People	??
Utils::pointers	??
PointersTest	??
Gui::Widgets::Popup	
Class for display popup quickly	??
Models::Project	
: Project linked to a Customer	??
Gui::Widgets::Delegates::ProjectComboDelegate	
The ProjectComboDelegate class	??
Gui::Widgets::WdgModels::ProjectContributoriesTableModel	
Table model of contributories linked to projets	??
Databases::ProjectDatabase	
Project table database	??
ProjectDatabaseTest	??
ProjectModelTest	??
Gui::Widgets::WdgModels::ProjectsTableModel	
For a Project table	??
Gui::Widgets::ProjectsWidget	
Actions on Project	??
Mustache::QtVariantContext	??
Models::Rate	
Rate of a prestation	??
Databases::RateDatabase	??
RateModelTest	??
Gui::Widgets::RateWidget	
Class for display Rate	??
Mustache::Renderer	??
Models::Search	
The Search class	??
Gui::Docks::SearchDock	
Dock which contains search bar	??
searchTest	??
Gui::Widgets::searchWidget	
Class for search in database	??
Gui::Dialogs::StartedWindowsDialog	
Construct a Windows for the first begin	??
StatisticModelTest	??
Models::Statistics	??

Gui::Dialogs::StatisticsDialog	
Window to have global informations or about a customer	??
Utils::String	
The Utils class	??
StringTest	??
Mustache::Tag	??
testadder	??
TestAdder< T >	??
TestMustache	??
TestRunner	??
Generator::TexGenerator	
Generate a LaTeX file	??
Gui::Widgets::Delegates::TextareaDelegate	
The TextareaDelegate class	??
Gui::Widgets::Delegates::UnitComboDelegate	
The UnitComboDelegate class	??
Models::User	
User of it application	??
Databases::UserDatabase	
Access to User data in the the table User of the Database	??
UserDatabaseTest	??
Gui::Dialogs::UserDataDialog	
Window to fill user data	??
UserModelTest	??

Chapter 7

Namespace Documentation

7.1 Databases Namespace Reference

Class for [Database](#), contains queries.

Classes

- class [AccessDatabase](#)
- class [BillingDatabase](#)
The [BillingDatabase](#) class Billing (or Quote) table database.
- class [ContributoryDatabase](#)
The [ContributoryDatabase](#) class Contributory (or Quote) table database.
- class [CustomerDatabase](#)
The [CustomerDatabase](#) class Customer table database.
- class [Database](#)
The [Database](#) class Master class for all database access.
- class [ProjectDatabase](#)
The [ProjectDatabase](#) class Project table database.
- class [RateDatabase](#)
- class [UserDatabase](#)
The [UserDatabase](#) class Access to User data in the the table User of the [Database](#)

Enumerations

- enum **DbType** { [SQLITE](#), [MYSQL](#) }

7.1.1 Detailed Description

Class for [Database](#), contains queries.

7.2 Gui Namespace Reference

Namespaces

- [Widgets](#)
Contains [Widgets](#) classes.

Classes

- class [MainWindow](#)
The [MainWindow](#) class Main Window of the software.

7.2.1 Detailed Description

Classes for Graphical User Interface

7.3 Gui::Widgets Namespace Reference

Contains [Widgets](#) classes.

Classes

- class [ComboBoxModelWidget](#)
The [ComboBoxModelWidget](#) class Model of ComboBox.
- class [ContributoriesWidget](#)
The [ContributoriesWidget](#) class Widget of Contributories.
- class [CustomerContextualMenu](#)
Display contextual menu on a customer.
- class [CustomerDataWidget](#)
Class for display info of a customer.
- class [DatabaseSettingsWidget](#)
The [DatabaseSettingsWidget](#) class Windows of database settings.
- class [Popup](#)
Class for display popup quickly.
- class [ProjectsWidget](#)
The [ProjectsWidget](#) class Actions on Project.
- class [RateWidget](#)
Class for display Rate.
- class [searchWidget](#)
Class for search in database.

7.3.1 Detailed Description

Contains [Widgets](#) classes.

7.4 Models Namespace Reference

[Models](#) classes.

Classes

- class [Billing](#)
The [Billing](#) class : [Billing](#) or Quote of a [Customer](#).
- class [ContributoriesList](#)
The [ContributoriesList](#) class List of contributories.

- class [Contributory](#)
The [Contributory](#) class.
- class [Customer](#)
The [Customer](#) class [Customer](#).
- class [IModel](#)
The [IModel](#) class.
- class [People](#)
The [People](#) class [People](#).
- class [Project](#)
The [Project](#) class : [Project](#) linked to a [Customer](#).
- class [Rate](#)
The [Rate](#) class [Rate](#) of a prestation.
- class [Search](#)
The [Search](#) class.
- class [Statistics](#)
- class [User](#)
The [User](#) class [User](#) of it application.

7.4.1 Detailed Description

[Models](#) classes.

Chapter 8

Class Documentation

8.1 Databases::AccessDatabase Class Reference

Static Public Member Functions

- static void **init** ()
- static void **commit** ()

Static Public Attributes

- static QString **_address**
- static int **_port**
- static QString **_userDb**
- static QString **_password**
- static QString **_dbName**
- static Databases::DbType **_dbType**
- static bool **_exists**

The documentation for this class was generated from the following files:


- /home/travis/build/FACT-Team/FactDev/src/database/accessdatabase.h
- /home/travis/build/FACT-Team/FactDev/src/database/accessdatabase.cpp

8.2 Gui::Dialogs::AddProjectDialog Class Reference

The [AddProjectDialog](#) class Windows to add a new Project.

```
#include <addprojectdialog.h>
```

Inheritance diagram for Gui::Dialogs::AddProjectDialog:



Public Slots

- void [checkFields](#) ()
AddProjectDialog::checkFields Check if fields are valid.

Public Member Functions

- [AddProjectDialog](#) (int idProject=0, int noRowCustomer=0, QWidget *parent=0)
AddProjectDialogAddProjectDialog Construct a windows according an idCustomer and, optionnaly, an idProject
- void [accept](#) ()
AddProjectDialog::accept Valid data inputed by user and add these data in Database.
- void [reject](#) ()
AddProjectDialog::reject Cancel the operation and close the windows.
- void [fillFields](#) ()
AddProjectDialog::fillFields Fill the differents fields of the current windows according the Project data existing As a project requires to be linked to a Customer, the Customer selection part may be disable.

8.2.1 Detailed Description

The [AddProjectDialog](#) class Windows to add a new Project.

Author

Florent Berbie

See Also

[Project](#)

8.2.2 Constructor & Destructor Documentation

8.2.2.1 [Gui::Dialogs::AddProjectDialog::AddProjectDialog](#) (int *idProject* = 0, int *noRowCustomer* = 0, QWidget * *parent* = 0) [explicit]

[AddProjectDialogAddProjectDialog](#) Construct a windows according an *idCustomer* and, optionnaly, an *idProject*

Parameters

<i>noRowCustomer</i>	Row number of the Customer
<i>idProject</i>	Project identify
<i>parent</i>	QWidget of the current windows

The documentation for this class was generated from the following files:


- /home/travis/build/FACT-Team/FactDev/src/gui/dialogs/addprojectdialog.h
- /home/travis/build/FACT-Team/FactDev/src/gui/dialogs/addprojectdialog.cpp

8.3 [Gui::Dialogs::AddQuoteDialog](#) Class Reference

The [AddQuoteDialog](#) class Window to add or modify a Quote.

```
#include <addquotedialog.h>
```

Inheritance diagram for [Gui::Dialogs::AddQuoteDialog](#):



Public Slots

- void **updateBtn** (void)
- void **changeDocType** ()

Public Member Functions

- [AddQuoteDialog](#) (bool isBilling, int idCustomer=0, int id=0, bool copy=false, QWidget *parent=0)
[AddQuoteDialog::AddQuoteDialog](#) Construct a windows [AddQuoteDialog](#).
- void [fillFields](#) ()
[AddQuoteDialog::fillFields](#) Fill line edits with the data of the quote.
- int [getNumber](#) ()
[AddQuoteDialog::getNumber](#) return the number of bill or quote.
- void [accept](#) ()
[AddQuoteDialog::accept](#) Valid data inputed by user and add these data in Database.
- void [reject](#) ()
[AddQuoteDialog::reject](#) Cancel the operation and close the windows.
- bool [getCopy](#) () const
[AddQuoteDialog::getCopy](#) return if [AddQuoteDialog](#) is an add by copy of Billing/quote or if it's edition or add of Billing/quote.
- void [setCopy](#) (bool copy)
[AddQuoteDialog::setCopy](#) Change the `_copy` value to define if it's a copy of a Billing/quote or if it's a new Billing or a Billing edition.
- int [getIdCustomer](#) () const
[AddQuoteDialog::getIdCustomer](#) get the id of the customer changing his quote/billing.
- void [fillQuoteBilling](#) (bool isBilling)
[AddQuoteDialog::fillQuoteBilling](#) fill fields for a Billing or a quote.
- void [fillQuoteBillingCopy](#) (bool isBilling)
[AddQuoteDialog::fillQuoteBilling](#) fill fields if it's a Billing or a quote for a copy.
- void [setQuoteIdNumber](#) (int id, int idCustomer, bool isBilling)
[AddQuoteDialog::setQuoteIdNumber](#) set id and number of the `_quote`

8.3.1 Detailed Description

The [AddQuoteDialog](#) class Window to add or modify a Quote.

Author

8.3.2 Constructor & Destructor Documentation

- 8.3.2.1 [Gui::Dialogs::AddQuoteDialog::AddQuoteDialog](#) (bool *isBilling*, int *idCustomer* = 0, int *id* = 0, bool *copy* = false, QWidget * *parent* = 0) [explicit]

[AddQuoteDialog::AddQuoteDialog](#) Construct a windows [AddQuoteDialog](#).

Parameters

<i>isBilling</i>	displaying of a quote or a Billing
<i>idCustomer</i>	the id of the Customer
<i>id</i>	the id of the quote or the billing of the Customer's Project
<i>edit</i>	if it's an edition or a copy of a quote/Billing
<i>parent</i>	QWidget of the current windows

8.3.3 Member Function Documentation

8.3.3.1 void Gui::Dialogs::AddQuoteDialog::fillQuoteBilling (bool *isBilling*)

[AddQuoteDialog::fillQuoteBilling](#) fill fields for a Billing or a quote.

Parameters

<i>isBilling</i>	if it's a quote or a Billing
------------------	------------------------------

8.3.3.2 bool Gui::Dialogs::AddQuoteDialog::getCopy () const

[AddQuoteDialog::getCopy](#) return if [AddQuoteDialog](#) is an add by copy of Billing/quote or if it's edition or add of Billing/quote.

Returns

if it's a copy or not

8.3.3.3 int Gui::Dialogs::AddQuoteDialog::getIdCustomer () const

[AddQuoteDialog::getIdCustomer](#) get the id of the customer changing his quote/billing.

Returns

the id of the customer

8.3.3.4 int Gui::Dialogs::AddQuoteDialog::getNumber ()

[AddQuoteDialog::getNumber](#) return the number of bill or quote.

Returns

int

8.3.3.5 void Gui::Dialogs::AddQuoteDialog::setCopy (bool *copy*)

[AddQuoteDialog::setCopy](#) Change the `_copy` value to define if it's a copy of a Billing/quote or if it's a new Billing or a Billing edition.

Parameters

<i>copy</i>	
-------------	--

8.3.3.6 void Gui::Dialogs::AddQuoteDialog::setQuoteIdNumber (int *id*, int *idCustomer*, bool *isBilling*)

AddQuoteDialog::setQuoteIdNumber set id and number of the *_quote*

Parameters

<i>id</i>	the id of the Billing
<i>idCustomer</i>	the id of the customer to set the <i>number</i>
<i>isBilling</i>	if it's a quote or a Billing

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/dialogs/addquotedialog.h
- /home/travis/build/FACT-Team/FactDev/src/gui/dialogs/addquotedialog.cpp

8.4 Models::Billing Class Reference

The **Billing** class : **Billing** or Quote of a **Customer**.

```
#include <billing.h>
```

Inheritance diagram for Models::Billing:



Public Member Functions

- **Billing** ()
Billing::Billing. Construct a *Billing*.
- **Billing** (int *id*)
Billing::Billing. Construct a *Billing* or quote.
- **~Billing** ()
destruct a billing object
- void **commit** ()
Billing::commit. Insert a modification in *Billing* table on the database.
- void **hydrat** (int *getId*)
Billing::hydrat. Update of the *Billing* which is specified by *getId*
- void **remove** ()
Billing::remove. Remove a *Billing*.
- QVariantHash **getDataMap** ()
Billing::getDataMap Get all data of model with a HashMap key/value.
- void **generateTex** ()
Billing::generateTex Generate a *.tex* file for the billing.
- void **generatePdf** ()
Billing::generatePdf Generate a *.pdf* file for the billing.
- QString **getPath** ()

- Billing::getPath* Return the path of billing filename (without extension)
- QString **getFolder** ()
 - Billing::getFolder* Return the directory of billing.
- QString **getFilename** ()
 - Billing::getFilename* Return the filename of billing (without extension)
- **ContributoriesList** & **getContributories** ()
 - Billing::getContributories.* Return a map of **Contributory** for each **Project** of the **Billing**
- void **addContributory** (**Contributory** &c)
 - Billing::addContributories* Add a new contributory for project p.
- double **getSumRate** ()
 - Billing::getSumRate.* return **Billing Rate**.
- double **getSumQuantity** ()
 - Billing::getSumQuantity.* return **Billing** total by time.
- QString **getTitle** () const
 - Billing::getTitle.* return title of **Billing**
- void **setTitle** (const QString &**getTitle**)
 - Billing::setTitle.* Modify the title of **Billing**
- QString **getDescription** () const
 - Billing::getDescription.* return description of **Billing**
- void **setDescription** (const QString &**getDescription**)
 - Billing::setDescription.* Modify the description of **Billing**
- int **getNumber** () const
 - Billing::getNumber.* Return number of the **Billing**.
- void **setNumber** (int **getNumber**)
 - Billing::setNumber.* Modify _number of **Billing**.
- bool **isBilling** () const
 - Billing::isBilling.* Return if it's a billing or a quote.
- void **setIsBilling** (bool **isBilling**)
 - Billing::setIsBilling.* Modify isBilling of **Billing**.
- QDate **getDate** () const
 - Billing::getDate.* return date of the **Billing**
- void **setDate** (const QDate &**getDate**)
 - Billing::setDate.* Modify date of the **Billing**
- bool **isPaid** () const
 - Billing::isPaid* Return TRUE if thee current billing is paid else return FALSE.
- void **setIsPaid** (bool **isPaid**)
 - Billing::setIsPaid* Define the current billing according the argument isPaid
- bool **operator==** (const **Billing** &b)
 - Billing::operator ==* define the operator "==" to compare two billings and to see if they are the same.
- bool **operator!=** (const **Billing** &b)
 - Billing::operator !=* defines the operator "!=" to compare two **Billing** and to see if they are different.
- void **setContributories** (const **ContributoriesList** &contributories)
- bool **operator<** (const **Billing** &b) const
 - Billing::operator <* defines the operator "<" to compare two **Billing** and to see if the first is anterior to the second.
- QStandardItem * **getItem** ()
 - Billing::getItem* Return the bill/quote item.

Additional Inherited Members

8.4.1 Detailed Description

The [Billing](#) class : [Billing](#) or Quote of a [Customer](#).

Author

Antoine de Roquemaurel
Florent Berbie

8.4.2 Constructor & Destructor Documentation

8.4.2.1 Models::Billing::Billing (int *id*)

[Billing::Billing](#). Construct a [Billing](#) or quote.

Parameters

<i>int</i>	id
------------	----

8.4.3 Member Function Documentation

8.4.3.1 void Models::Billing::addContributory (Contributory & *c*)

[Billing::addContributories](#) Add a new contributory for project p.

Parameters

<i>p</i>	The Project who contain Contributory
<i>c</i>	The new Contributory

8.4.3.2 ContributoriesList & Models::Billing::getContributories ()

[Billing::getContributories](#). Return a map of [Contributory](#) for each [Project](#) of the [Billing](#)

Returns

QMap<[Project](#), QList<Contributory>>

8.4.3.3 QVariantHash Models::Billing::getDataMap () [virtual]

[Billing::getDataMap](#) Get all data of model with a HashMap key/value.

Returns

Model's data

Implements [Models::IModel](#).

8.4.3.4 QDate Models::Billing::getDate () const

[Billing::getDate](#). return date of the [Billing](#)

Returns

date of [Billing](#)

8.4.3.5 QString Models::Billing::getDescription () const

[Billing::getDescription](#). return description of [Billing](#)

Returns

description of [Billing](#)

8.4.3.6 QString Models::Billing::getFilename ()

[Billing::getFilename](#) Return the filename of billing (without extension)

Returns

Filename of Bulling

8.4.3.7 QString Models::Billing::getFolder ()

[Billing::getFolder](#) Return the directory of billing.

Returns

[Billing](#) directory

8.4.3.8 QStandardItem * Models::Billing::getItem ()

[Billing::getItem](#) Return the bill/quote item.

Returns

QStandardItem an item for QTree (level/depth 3)

8.4.3.9 int Models::Billing::getNumber () const

[Billing::getNumber](#). Return number of the [Billing](#).

Returns

_number of [Billing](#)

8.4.3.10 QString Models::Billing::getPath ()

[Billing::getPath](#) Return the path of billing filename (without extension)

Returns

billing path

8.4.3.11 double Models::Billing::getSumQuantity ()

[Billing::getSumQuantity](#). return [Billing](#) total by time.

Returns

time in hours

8.4.3.12 double Models::Billing::getSumRate ()

[Billing::getSumRate](#). return **Billing Rate**.

Returns

8.4.3.13 QString Models::Billing::getTitle () const

[Billing::getTitle](#). return title of **Billing**

Returns

title of **Billing**

8.4.3.14 void Models::Billing::hydrat (int *getId*) [virtual]

[Billing::hydrat](#). Update of the **Billing** which is specified by *getId*

Parameters

<i>getId</i>	
--------------	--

Implements [Models::IModel](#).

8.4.3.15 bool Models::Billing::isBilling () const

[Billing::isBilling](#). Return if it's a billing or a quote.

Returns

if it's billing or a quote

8.4.3.16 bool Models::Billing::isPaid () const

[Billing::isPaid](#) Return TRUE if thee current billing is paid else return FALSE.

Returns

Boolean

8.4.3.17 bool Models::Billing::operator!= (const **Billing** & *b*)

[Billing::operator !=](#) defines the operator "!=" to compare two **Billing** and to see if they are different.

Parameters

<i>b</i>	the Billing to compare with the current Billing
----------	---

Returns

true if the **Billing** are different else false

8.4.3.18 bool Models::Billing::operator< (const **Billing** & *b*) const

[Billing::operator <](#) defines the operator "<" to compare two **Billing** and to see if the first is anterior to the second.

Parameters

<i>b</i>	the Billing to compare with the current Billing
----------	---

Returns

true if the [Billing](#) are different else false

8.4.3.19 `bool Models::Billing::operator== (const Billing & b)`

[Billing::operator ==](#) define the operator "==" to compare two billings and to see if they are the same.

Parameters

<i>b</i>	the Billing to compare with the current Billing
----------	---

Returns

true if they are the same billings else false

8.4.3.20 `void Models::Billing::setDate (const QDate & getDate)`

[Billing::setDate](#). Modify *date* of the [Billing](#)

Parameters

<i>getDate</i>	the new date of the Billing
----------------	---

8.4.3.21 `void Models::Billing::setDescription (const QString & getDescription)`

[Billing::setDescription](#). Modify the description of [Billing](#)

Parameters

<i>getDescription</i>	Modify the description with <i>getDescription</i>
-----------------------	---

8.4.3.22 `void Models::Billing::setIsBilling (bool isBilling)`

[Billing::setIsBilling](#). Modify *isBilling* of [Billing](#).

Parameters

<i>isBilling</i>	
------------------	--

8.4.3.23 `void Models::Billing::setIsPaid (bool isPaid)`

[Billing::setIsPaid](#) Define the current billing according the argument *isPaid*

Parameters

<i>isPaid</i>	Boolean
---------------	---------

8.4.3.24 `void Models::Billing::setNumber (int getNumber)`

[Billing::setNumber](#). Modify *_number* of [Billing](#).

Parameters

<code>getNumber</code>	the new number of the Billing
------------------------	---

8.4.3.25 void Models::Billing::setTitle (const QString & getTitle)

[Billing::setTitle](#). Modify the title of [Billing](#)

Parameters

<code>getTitle</code>	Modify the title with <code>getTitle</code>
-----------------------	---

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/models/billing.h
- /home/travis/build/FACT-Team/FactDev/src/models/billing.cpp

8.5 Databases::BillingDatabase Class Reference

The [BillingDatabase](#) class Billing (or Quote) table database.

```
#include <billingdatabase.h>
```

Inheritance diagram for Databases::BillingDatabase:



Public Member Functions

- [Models::Billing](#) * [getBilling](#) (const int pld)
BillingDatabase::getBilling get informations about the billing identified by pld
- [WdgModels::BillingsTableModel](#) * [getBillingsTable](#) (const int idProject) throw (DbException*)
BillingDatabase::getBillingsTable Return an item model of billings for QTableView.
- int [addBilling](#) (const [Models::Billing](#) &)
BillingDatabase::addBilling Add the billing pBilling to the database.
- void [updateBilling](#) (const [Models::Billing](#) &)
BillingDatabase::updateCustomer Update informations about the billing pCustomer
- void [removeBilling](#) (const int pld)
BillingDatabase::removeCustomer Remove the billing with the id pld
- void [addBillingProject](#) (const int idProject, const int idBilling, const int idContributory)
BillingDatabase::addBillingProject Link a project, a billing and a contributory in the table BillingProject.
- bool [isBillingPaid](#) (const int pld)
BillingDatabase::isBillingPaid Return TRUE if the id pld correspond to a Billing and not quote (isBilling = 1) and if this billing is paid (isPaid = 1) else return FALSE.
- void [removeBillingProject](#) (const int idProject, const int idBilling, const int idContributory)
BillingDatabase::removeBillingProject remove a link between a project, a billing and a contributory in the table BillingProject.
- int [getMaxBillingNumber](#) ()
getMaxBillingNumber Get the last number of a billing

- int [getMaxQuoteNumber](#) ()
getMaxQuoteNumber Get the last number of a quote
- int [getMaxBillingNumberOfCustomer](#) (const int idCustomer)
BillingDatabase::getMaxBillingNumberOfCustomer Get the last number of a **Customer's** Billing.
- int [getMaxQuoteNumberOfCustomer](#) (const int idCustomer)
BillingDatabase::getMaxQuoteNumberOfCustomer Get the last number of a **Customer's** quote.
- QSharedPointer< [Models::Billing](#) > [getBilling](#) (QString query &q)
BillingDatabase::getBilling Add the element of the q request and return their.
- QMap< [Project](#) *, [Billing](#) * > [getAllBillingsOfProject](#) ()
BillingDatabase::getAllBillingsOfProject Return a map with the project id as key linked to the billing.
- QList< [Billing](#) > [getBillsBetweenDates](#) (QDate begin, QDate end)
Get the bills between begin and end dates.
- QList< [Billing](#) > [getBills](#) (const int projectId=0)
Get the bills.
- QList< [Billing](#) > [getBillsPaid](#) (const int projectId=0)
Get the bills paid.
- int [getNbBills](#) (const int customerId=0)
Get the number of bills.
- int [getNbBillsPaid](#) (const int customerId=0)
Get the number of bills paid.
- int [getNbQuotes](#) (const int customerId=0)
Get the number of quotes.
- int [getNbDocs](#) (const int customerId=0)
Get the number of documents.

Static Public Member Functions

- static [BillingDatabase](#) * [instance](#) () throw (DbException*)
BillingDatabase::getInstance Return an instance of [BillingDatabase](#)

Additional Inherited Members

8.5.1 Detailed Description

The [BillingDatabase](#) class Billing (or Quote) table database.

Author

See Also

[Database](#)
[Billing/Quote](#)

8.5.2 Member Function Documentation

8.5.2.1 int Databases::BillingDatabase::addBilling (const Models::Billing & pBilling)

[BillingDatabase::addBilling](#) Add the billing *pBilling* to the database.

Returns

billing id

8.5.2.2 void Databases::BillingDatabase::addBillingProject (const int *idProject*, const int *idBilling*, const int *idContributory*)

[BillingDatabase::addBillingProject](#) Link a project, a billing and a contributory in the table BillingProject.

Parameters

<i>idProject</i>	Project id
<i>idBilling</i>	Billing id
<i>idContributory</i>	Contributory id

8.5.2.3 QMap< Project *, Billing * > Databases::BillingDatabase::getAllBillingsOfProject ()

[BillingDatabase::getAllBillingsOfProject](#) Return a map with the project id as key linked to the billing.

Returns

Map with projects and Billing

8.5.2.4 Models::Billing * Databases::BillingDatabase::getBilling (const int *pld*)

[BillingDatabase::getBilling](#) get informations about the billing identified by *pld*

Parameters

<i>pld</i>	billing id
------------	------------

Returns

the Billing

8.5.2.5 QSharedPointer< Billing > Databases::BillingDatabase::getBilling (QSqlQuery & *q*)

[BillingDatabase::getBilling](#) Add the element of the *q* request and return their.

Parameters

<i>q</i>	SQL request
----------	-------------

Returns

a billing formed according to QSharedPointer

8.5.2.6 WdgModels::BillingsTableModel * Databases::BillingDatabase::getBillingsTable (const int *idProject*) throw DbException *)

[BillingDatabase::getBillingsTable](#) Return an item model of billings for QTableView.

Parameters

<i>pld</i>	the project id of the billings returned
------------	---

Exceptions

<i>DbException</i>	
--------------------	--

Returns

QStandardItemModel an item model for QTableView

8.5.2.7 QList< Billing > Databases::BillingDatabase::getBills (const int *projectId* = 0)

Get the bills.

Parameters

<i>projectId</i>	Get the specified project bills
------------------	---------------------------------

Returns

The list of bills

8.5.2.8 `QList< Billing > Databases::BillingDatabase::getBillsBetweenDates (QDate begin, QDate end)`

Get the bills between *begin* and *end* dates.

Parameters

<i>begin</i>	
<i>end</i>	

Returns

the list of **Bills**

8.5.2.9 `QList< Billing > Databases::BillingDatabase::getBillsPaid (const int projectId = 0)`

Get the bills paid.

Parameters

<i>projectId</i>	Get the specified project bills paid
------------------	--------------------------------------

Returns

The list of bills paid

8.5.2.10 `int Databases::BillingDatabase::getMaxBillingNumber ()`

`getMaxBillingNumber` Get the last number of a billing

Returns

The max number

8.5.2.11 `int Databases::BillingDatabase::getMaxBillingNumberOfCustomer (const int idCustomer)`

[BillingDatabase::getMaxBillingNumberOfCustomer](#) Get the last number of a **Customer's** Billing.

Parameters

<i>idCustomer</i>	Customer id
-------------------	-------------

Returns

the last number of the **Customer's** Billing

8.5.2.12 `int Databases::BillingDatabase::getMaxQuoteNumber ()`

`getMaxQuoteNumber` Get the last number of a quote

Returns

The last number

8.5.2.13 `int Databases::BillingDatabase::getMaxQuoteNumberOfCustomer (const int idCustomer)`

[BillingDatabase::getMaxQuoteNumberOfCustomer](#) Get the last number of a **Customer's** quote.

Parameters

<i>idCustomer</i>	Customer id
-------------------	-------------

Returns

the last number of the **Customer's** quote

8.5.2.14 `int Databases::BillingDatabase::getNbBills (const int customerId = 0)`

Get the number of bills.

Parameters

<i>customerId</i>	If customerId isn't specified or if it's not valid, get all bills else get the specified customer bills
-------------------	---

Returns

Number of bills in the database for all or for a customer

8.5.2.15 `int Databases::BillingDatabase::getNbBillsPaid (const int customerId = 0)`

Get the number of bills paid.

Parameters

<i>customerId</i>	If customerId isn't specified if it's not valid, get all bills paid else get the specified customer bills paid
-------------------	--

Returns

Number of bills paid in the database for all or for a customer

8.5.2.16 `int Databases::BillingDatabase::getNbDocs (const int customerId = 0)`

Get the number of documents.

Parameters

<i>customerId</i>	If customerId isn't specified or if it's not valid, get all documents else get the specified customer documents
-------------------	---

Returns

Number of quotes in the database for all or for a customer

8.5.2.17 `int Databases::BillingDatabase::getNbQuotes (const int customerId = 0)`

Get the number of quotes.

Parameters

<i>customerId</i>	If customerId isn't specified or if it's not valid, get all quotes else get the specified customer quotes
-------------------	---

Returns

Number of quotes in the database for all or for a customer

8.5.2.18 **BillingDatabase * Databases::BillingDatabase::instance () throw DbException *** [static]

BillingDatabase::getInstance Return an instance of [BillingDatabase](#)

See Also

DbException

Returns

Instance of [BillingDatabase](#)

8.5.2.19 **bool Databases::BillingDatabase::isBillingPaid (const int *pId*)**

[BillingDatabase::isBillingPaid](#) Return TRUE if the id *pId* correspond to a Billing and not quote (isBilling = 1) and if this billing is paid (isPaid = 1) else return FALSE.

Parameters

<i>pId</i>	Billing id
------------	------------

Returns

TRUE if billing is paid

8.5.2.20 **void Databases::BillingDatabase::removeBilling (const int *pId*)**

BillingDatabase::removeCustomer Remove the billing with the id *pId*

Parameters

<i>pId</i>	billing id
------------	------------

8.5.2.21 **void Databases::BillingDatabase::removeBillingProject (const int *idProject*, const int *idBilling*, const int *idContributory*)**

[BillingDatabase::removeBillingProject](#) remove a link between a project, a billing and a contributory in the table BillingProject.

Parameters

<i>idProject</i>	Project id
------------------	------------


<i>idBilling</i>	Billing id
<i>idContributory</i>	Contributory id

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/database/billingdatabase.h
- /home/travis/build/FACT-Team/FactDev/src/database/billingdatabase.cpp

8.6 BillingDatabaseTest Class Reference

Inheritance diagram for BillingDatabaseTest:




The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/tests/database/billingdatabasetest.h
- /home/travis/build/FACT-Team/FactDev/tests/database/billingdatabasetest.cpp

8.7 BillingModelTest Class Reference

Inheritance diagram for BillingModelTest:



The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/tests/models/billingmodeltest.h
- /home/travis/build/FACT-Team/FactDev/tests/models/billingmodeltest.cpp

8.8 Gui::Widgets::WdgModels::BillingsTableModel Class Reference

The [BillingsTableModel](#) class for a Billing table.

```
#include <billingstablemodel.h>
```

Inheritance diagram for Gui::Widgets::WdgModels::BillingsTableModel:



Public Member Functions

- [BillingsTableModel \(\)](#)
BillingsTableModel::BillingsTableModel Construct a [BillingsTableModel](#).
- int [rowCount](#) (const QModelIndex &) const
BillingsTableModel::rowCount Number of billings row.
- int [columnCount](#) (const QModelIndex &) const
BillingsTableModel::columnCount Number of column of a Billing.
- QVariant [data](#) (const QModelIndex &index, int role=Qt::DisplayRole) const
BillingsTableModel::data Obtains data of a specify cell.
- QVariant [headerData](#) (int section, Qt::Orientation orientation, int role=Qt::DisplayRole) const
BillingsTableModel::headerData Obtains header title of table.
- bool [setData](#) (const QModelIndex &index, const QVariant &value, int role=Qt::EditRole)
BillingsTableModel::setData Change data of a cell.
- void [append](#) (const [Billing](#) &billing)
BillingsTableModel::append Add a new line in table.
- void [remove](#) (const int i)
BillingsTableModel::remove Remove a line.
- Qt::ItemFlags [flags](#) (const QModelIndex &index) const
BillingsTableModel::flags Differents table flags.
- int [count](#) ()
BillingsTableModel::count Number of billings in table.
- QList< [Billing](#) > [getBillings](#) () const
BillingsTableModel::getbillings Return the list of billings.

8.8.1 Detailed Description

The [BillingsTableModel](#) class for a Billing table.

Author

Florent Berbie

See Also

[Billing](#)

8.8.2 Constructor & Destructor Documentation

8.8.2.1 Gui::Widgets::WdgModels::BillingsTableModel::BillingsTableModel ()

[BillingsTableModel::BillingsTableModel](#) Construct a [BillingsTableModel](#).

Parameters

<i>parent</i>	Parent widget
---------------	---------------

8.8.3 Member Function Documentation

8.8.3.1 void Gui::Widgets::WdgModels::BillingsTableModel::append (const [Billing](#) & *billing*)

[BillingsTableModel::append](#) Add a new line in table.

Parameters

<i>Billing</i>	The new Billing
----------------	-----------------

8.8.3.2 `int Gui::Widgets::WdgModels::BillingsTableModel::columnCount (const QModelIndex &) const`

[BillingsTableModel::columnCount](#) Number of column of a Billing.

Returns

The number of column

8.8.3.3 `int Gui::Widgets::WdgModels::BillingsTableModel::count ()`

[BillingsTableModel::count](#) Number of billings in table.

Returns

The number of billings

8.8.3.4 `QVariant Gui::Widgets::WdgModels::BillingsTableModel::data (const QModelIndex & index, int role = Qt::DisplayRole) const`

[BillingsTableModel::data](#) Obtains data of a specify cell.

Parameters

<i>index</i>	The cell who we want data
<i>role</i>	The role of set

Returns

The data of cell

8.8.3.5 `Qt::ItemFlags Gui::Widgets::WdgModels::BillingsTableModel::flags (const QModelIndex & index) const`

[BillingsTableModel::flags](#) Differents table flags.

Parameters

<i>index</i>	The cell who we want to know flags
--------------	------------------------------------

Returns

Flags

8.8.3.6 `QList< Billing > Gui::Widgets::WdgModels::BillingsTableModel::getBillings () const`

[BillingsTableModel::getbillings](#) Return the list of billings.

Returns

list of billings

8.8.3.7 `QVariant Gui::Widgets::WdgModels::BillingsTableModel::headerData (int section, Qt::Orientation orientation, int role = Qt::DisplayRole) const`

[BillingsTableModel::headerData](#) Obtains header title of table.

Parameters

<i>section</i>	The number of column
<i>orientation</i>	The table orientation
<i>role</i>	

Returns

The Title header of column

8.8.3.8 void Gui::Widgets::WdgModels::BillingsTableModel::remove (const int *i*)

[BillingsTableModel::remove](#) Remove a line.

Parameters

<i>i</i>	The number of line to remove
----------	------------------------------

8.8.3.9 int Gui::Widgets::WdgModels::BillingsTableModel::rowCount (const QModelIndex &) const

[BillingsTableModel::rowCount](#) Number of billings row.

Returns

The number of billings

8.8.3.10 bool Gui::Widgets::WdgModels::BillingsTableModel::setData (const QModelIndex & *index*, const QVariant & *value*, int *role* = Qt::EditRole)

[BillingsTableModel::setData](#) Change data of a cell.

Parameters

<i>index</i>	The cell to change data
<i>value</i>	The new value
<i>role</i>	The role of cell

Returns

True if we could edit

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/widgetmodels/billingstablemodel.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/widgetmodels/billingstablemodel.cpp

8.9 Gui::Widgets::CheckFields::CheckCity Class Reference

The [CheckCity](#) class Line Edit of City with a check icon.

```
#include <checkcity.h>
```

Inheritance diagram for Gui::Widgets::CheckFields::CheckCity:



Public Member Functions

- [CheckCity](#) (QWidget *w=0, QPushButton *btn=0)

[CheckCity::CheckCity](#) Construct a [CheckCity](#).

Additional Inherited Members

8.9.1 Detailed Description

The [CheckCity](#) class Line Edit of City with a check icon.

8.9.2 Constructor & Destructor Documentation

8.9.2.1 Gui::Widgets::CheckFields::CheckCity::CheckCity (QWidget * w = 0, QPushButton * btn = 0)

[CheckCity::CheckCity](#) Construct a [CheckCity](#).

Parameters

<i>w</i>	QWidget linked to CheckCity
----------	---

The documentation for this class was generated from the following files:


- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkcity.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkcity.cpp

8.10 Gui::Widgets::CheckFields::CheckCountry Class Reference

[CheckCountry::CheckCountry](#) Line Edit of country with a check icon.

```
#include <checkcountry.h>
```

Inheritance diagram for Gui::Widgets::CheckFields::CheckCountry:



Public Member Functions

- [CheckCountry](#) (QWidget *w=0, QPushButton *btn=0)
CheckCountry::CheckCountry Construct a [CheckCountry](#).

Additional Inherited Members

8.10.1 Detailed Description

[CheckCountry::CheckCountry](#) Line Edit of country with a check icon.

8.10.2 Constructor & Destructor Documentation

8.10.2.1 [Gui::Widgets::CheckFields::CheckCountry::CheckCountry](#) ([QWidget](#) * *w* = 0, [QPushButton](#) * *btn* = 0)

[CheckCountry::CheckCountry](#) Construct a [CheckCountry](#).

Parameters

<i>w</i>	QWidget linked to CheckCountry
----------	--

The documentation for this class was generated from the following files:


- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkcountry.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkcountry.cpp

8.11 Gui::Widgets::CheckFields::CheckEmail Class Reference

The [CheckEmail](#) class Line Edit of email with a check icon.

```
#include <checkemail.h>
```

Inheritance diagram for [Gui::Widgets::CheckFields::CheckEmail](#):



Public Member Functions

- [CheckEmail](#) (QWidget *w=0, QPushButton *btn=0)
[CheckEmail::CheckEmail](#) Construct a CheckMail.
- bool [check](#) (const QString text)
[CheckEmail::check](#) Check if the field email is valid. To be valid, an email address should be under this form: *me@me. - xx* An email address need:

Additional Inherited Members

8.11.1 Detailed Description

The [CheckEmail](#) class Line Edit of email with a check icon.

8.11.2 Constructor & Destructor Documentation

8.11.2.1 [Gui::Widgets::CheckFields::CheckEmail::CheckEmail](#) ([QWidget](#) * *w* = 0, [QPushButton](#) * *btn* = 0)

[CheckEmail::CheckEmail](#) Construct a CheckMail.

Parameters

<i>w</i>	QWidget linked to CheckEmail
----------	--

8.11.3 Member Function Documentation

8.11.3.1 bool [Gui::Widgets::CheckFields::CheckEmail::check](#) (const [QString](#) *text*) [virtual]

[CheckEmail::check](#) Check if the field email is valid. To be valid, an email address should be under this form: *me@me. xx* An email address need:

- 1 character [A-Z] or [a-z] minimum before the character *</i>*
- the character '@'
- 1 character [A-Z] or [a-z] after the character *</i>* minimum and before the character .
- 1 character [A-Z] or [a-z] minimum after the character . Return TRUE if email address is valid, else FALSE

Parameters

<i>text</i>	Text to check
-------------	---------------

Returns

boolean Validity of the text

Implements [Gui::Widgets::CheckFields::ICheckField](#).

The documentation for this class was generated from the following files:


- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkemail.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkemail.cpp

8.12 Gui::Widgets::CheckFields::CheckFieldsLetters Class Reference

The [CheckFieldsLetters](#) class Field with only letters (no numbers)

```
#include <checkfieldsletters.h>
```

Inheritance diagram for Gui::Widgets::CheckFields::CheckFieldsLetters:



Public Member Functions

- [CheckFieldsLetters](#) (QWidget *w=0, QPushButton *btn=0)
[CheckFieldsLetters::CheckFieldsLetters](#) Construct a [CheckFieldsLetters](#).
- bool [check](#) (QString text)
[CheckFieldsLetters::check](#) Check if the field contains only letters.

Additional Inherited Members

8.12.1 Detailed Description

The [CheckFieldsLetters](#) class Field with only letters (no numbers)

8.12.2 Constructor & Destructor Documentation

8.12.2.1 Gui::Widgets::CheckFields::CheckFieldsLetters::CheckFieldsLetters (QWidget * w = 0, QPushButton * btn = 0)

[CheckFieldsLetters::CheckFieldsLetters](#) Construct a [CheckFieldsLetters](#).

Parameters

w	QWidget linked to CheckFieldsLetters
---	--

8.12.3 Member Function Documentation

8.12.3.1 bool Gui::Widgets::CheckFields::CheckFieldsLetters::check (QString text) [virtual]

[CheckFieldsLetters::check](#) Check if the field contains only letters.

Parameters

text	Text to check
------	---------------

Returns

boolean Validity of the text

Implements [Gui::Widgets::CheckFields::ICheckField](#).

The documentation for this class was generated from the following files:


- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkfieldsletters.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkfieldsletters.cpp

8.13 Gui::Widgets::CheckFields::CheckFieldsNumbers Class Reference

The [CheckFieldsNumbers](#) class Line Edit of number with a check icon.

```
#include <checkfieldsnumbers.h>
```

Inheritance diagram for Gui::Widgets::CheckFields::CheckFieldsNumbers:

**Public Member Functions**

- [CheckFieldsNumbers](#) (QWidget *w=0, QPushButton *btn=0)
CheckFieldsNumbers::CheckFieldsNumbers Construct a [CheckFieldsNumbers](#).
- bool [check](#) (QString text)
CheckFieldsNumbers::check Check if the field contains only numbers.

Additional Inherited Members

8.13.1 Detailed Description

The [CheckFieldsNumbers](#) class Line Edit of number with a check icon.

Author

Florent BERBIE

See Also

[CheckQLineEdit](#)
[CheckUntilField](#)

8.13.2 Constructor & Destructor Documentation

8.13.2.1 [Gui::Widgets::CheckFields::CheckFieldsNumbers::CheckFieldsNumbers](#) ([QWidget](#) * *w* = 0, [QPushButton](#) * *btn* = 0)

[CheckFieldsNumbers::CheckFieldsNumbers](#) Construct a [CheckFieldsNumbers](#).

Parameters

<i>w</i>	QWidget linked to CheckFieldsNumbers
----------	--

8.13.3 Member Function Documentation

8.13.3.1 bool Gui::Widgets::CheckFields::CheckFieldsNumbers::check (QString *text*) [virtual]

[CheckFieldsNumbers::check](#) Check if the field contains only numbers.

Parameters

<i>text</i>	Text to check
-------------	---------------

Returns

boolean Validity of the text

Implements [Gui::Widgets::CheckFields::ICheckField](#).

The documentation for this class was generated from the following files:


- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkfieldsnumbers.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkfieldsnumbers.cpp

8.14 Gui::Widgets::CheckFields::CheckIpAddress Class Reference

The [CheckIpAddress](#) class Line Edit of IP address with a check icon.

```
#include <checkipaddress.h>
```

Inheritance diagram for Gui::Widgets::CheckFields::CheckIpAddress:



Public Member Functions

- [CheckIpAddress](#) (QWidget *w=0, QPushButton *btn=0)
[CheckIpAddress::CheckIpAddress](#) Construct a [CheckIpAddress](#).
- bool [check](#) (QString *text*)
[CheckIpAddress::check](#) Check if the field contains an IP address or domain name valid.

Additional Inherited Members

8.14.1 Detailed Description

The [CheckIpAddress](#) class Line Edit of IP address with a check icon.

Author

Florent BERBIE

See Also

[CheckQLineEdit](#)
[CheckUntilField](#)

8.14.2 Constructor & Destructor Documentation

8.14.2.1 `Gui::Widgets::CheckFields::CheckIpAddress::CheckIpAddress (QWidget * w = 0, QPushButton * btn = 0)`[CheckIpAddress::CheckIpAddress](#) Construct a [CheckIpAddress](#).

Parameters

<i>w</i>	QWidget linked to CheckIpAddress
----------	--

8.14.3 Member Function Documentation

8.14.3.1 `bool Gui::Widgets::CheckFields::CheckIpAddress::check (QString text) [virtual]`[CheckIpAddress::check](#) Check if the field contains an IP address or domain name valid.

Parameters

<i>text</i>	Text to check
-------------	---------------

Returns

boolean Validity of the text

Implements [Gui::Widgets::CheckFields::ICheckField](#).

The documentation for this class was generated from the following files:


- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkipaddress.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkipaddress.cpp

8.15 Gui::Widgets::CheckFields::CheckLogin Class Reference

The [CheckLogin](#) class Line Edit of login with a check icon.

#include <checklogin.h>

Inheritance diagram for Gui::Widgets::CheckFields::CheckLogin:



Public Slots

- void [passwordPreviousInputed](#) (const QString &text)
[CheckLogin::fieldTextChanged](#) For each new characater inputed or removed, displays an icon to show if the field is valid or not.

Public Member Functions

- [CheckLogin](#) (QWidget *w=0, QPushButton *btn=0)
[CheckLogin::CheckLogin](#) Construct a [CheckLogin](#).
- bool [check](#) (QString text)
[CheckLogin::check](#) Check if the field contains only numbers.

8.15.1 Detailed Description

The [CheckLogin](#) class Line Edit of login with a check icon.

Author

Florent BERBIE

See Also

[CheckQLineEdit](#)
[CheckUntilField](#)

8.15.2 Constructor & Destructor Documentation

8.15.2.1 [Gui::Widgets::CheckFields::CheckLogin::CheckLogin](#) ([QWidget](#) * *w* = 0, [QPushButton](#) * *btn* = 0)

[CheckLogin::CheckLogin](#) Construct a [CheckLogin](#).

Parameters

<i>w</i>	QWidget linked to CheckIpAddress
----------	--

8.15.3 Member Function Documentation

8.15.3.1 bool [Gui::Widgets::CheckFields::CheckLogin::check](#) ([QString](#) *text*) [virtual]

[CheckLogin::check](#) Check if the field contains only numbers.

Parameters

<i>text</i>	Text to check
-------------	---------------

Returns

boolean Validity of the text

Implements [Gui::Widgets::CheckFields::ICheckField](#).

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checklogin.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checklogin.cpp

8.16 Gui::Widgets::CheckFields::CheckName Class Reference

The [CheckName](#) class Line edit of name with a check icon.

```
#include <checkname.h>
```

Inheritance diagram for Gui::Widgets::CheckFields::CheckName:



Public Member Functions

- [CheckName](#) (QWidget *w=0, QPushButton *btn=0)
CheckName::CheckName Construct a [CheckName](#).

Additional Inherited Members

8.16.1 Detailed Description

The [CheckName](#) class Line edit of name with a check icon.

8.16.2 Constructor & Destructor Documentation

8.16.2.1 Gui::Widgets::CheckFields::CheckName::CheckName (QWidget * w = 0, QPushButton * btn = 0)

[CheckName::CheckName](#) Construct a [CheckName](#).

Parameters

<i>w</i>	QWidget linked to CheckName
----------	---

The documentation for this class was generated from the following files:


- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkname.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkname.cpp

8.17 Gui::Widgets::CheckFields::CheckPhone Class Reference

The [CheckPhone](#) class Line Edit of Phone number with a check icon.

```
#include <checkphone.h>
```

Inheritance diagram for Gui::Widgets::CheckFields::CheckPhone:



Public Member Functions

- [CheckPhone](#) (QWidget *w=0, QPushButton *btn=0)
CheckPhone::CheckPhone Construct a [CheckPhone](#).
- bool [check](#) (QString text)
CheckPhone::check Check if the field is valid. To be valid, a name should be composed of a character.
- QString [getCountry](#) () const
CheckPhone::getCountry Return the country linked to current field.
- void [setCountry](#) (const QString &country)
CheckPhone::setCountry Modify the country linked to field.

Additional Inherited Members

8.17.1 Detailed Description

The [CheckPhone](#) class Line Edit of Phone number with a check icon.

8.17.2 Constructor & Destructor Documentation

8.17.2.1 [Gui::Widgets::CheckFields::CheckPhone::CheckPhone](#) ([QWidget](#) * *w* = 0, [QPushButton](#) * *btn* = 0)

[CheckPhone::CheckPhone](#) Construct a [CheckPhone](#).

Parameters

<i>w</i>	QWidget linked to CheckPhone
----------	--

8.17.3 Member Function Documentation

8.17.3.1 bool [Gui::Widgets::CheckFields::CheckPhone::check](#) ([QString](#) *text*) [virtual]

[CheckPhone::check](#) Check if the field is valid. To be valid, a name should be composed of a character.

Parameters

<i>text</i>	Text to check
-------------	---------------

Returns

boolean Validity of the text

Implements [Gui::Widgets::CheckFields::ICheckField](#).

8.17.3.2 QString Gui::Widgets::CheckFields::CheckPhone::getCountry () const

[CheckPhone::getCountry](#) Return the country linked to current field.

Returns

8.17.3.3 void Gui::Widgets::CheckFields::CheckPhone::setCountry (const QString & country)

[CheckPhone::setCountry](#) Modify the *country* linked to field.

Parameters

<i>country</i>	New country
----------------	-------------

The documentation for this class was generated from the following files:


- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkphone.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkphone.cpp

8.18 Gui::Widgets::CheckFields::CheckPortNumber Class Reference

The [CheckFieldsNumbers](#) class Line Edit of number with a check icon.

```
#include <checkportnumber.h>
```

Inheritance diagram for Gui::Widgets::CheckFields::CheckPortNumber:



Public Member Functions

- [CheckPortNumber](#) (QWidget *w=0, QPushButton *btn=0)
[CheckPortNumber](#).
- bool [check](#) (QString text)
[CheckPortNumber::check](#) Check if the field contains only numbers or an empty text.

Additional Inherited Members

8.18.1 Detailed Description

The [CheckFieldsNumbers](#) class Line Edit of number with a check icon.

Author

Florent BERBIE

See Also

[CheckQLineEdit](#)
[CheckUntilField](#)

8.18.2 Constructor & Destructor Documentation

8.18.2.1 `Gui::Widgets::CheckFields::CheckPortNumber::CheckPortNumber (QWidget * w = 0, QPushButton * btn = 0)`

[CheckPortNumber.](#)

Parameters

<i>w</i>	Widget parent
<i>btn</i>	Button parretrn

8.18.3 Member Function Documentation

8.18.3.1 `bool Gui::Widgets::CheckFields::CheckPortNumber::check (QString text)` `[virtual]`

[CheckPortNumber::check](#) Check if the field contains only numbers or an empty text.

Parameters

<i>text</i>	Text to check
-------------	---------------

Returns

boolean Validity of the text

Implements [Gui::Widgets::CheckFields::ICheckField](#).

The documentation for this class was generated from the following files:


- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkportnumber.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkportnumber.cpp

8.19 Gui::Widgets::CheckFields::CheckPostalCode Class Reference

The [CheckPostalCode](#) class Line Edit of postal code with a check icon.

```
#include <checkpostalcode.h>
```

Inheritance diagram for Gui::Widgets::CheckFields::CheckPostalCode:



Public Member Functions

- [CheckPostalCode](#) (QWidget *w=0, QPushButton *btn=0)
[CheckPostalCode::CheckPostalCode](#) Construct a [CheckPostalCode](#).
- bool [check](#) (QString text)
[CheckPostalCode::check](#) Check if the field is valid. To be valid, a name should be composed of a character.
- QString [getCountry](#) () const
[CheckPostalCode::getCountry](#) Return the country linked to current field.
- void [setCountry](#) (const QString &country)
[CheckPostalCode::setCountry](#) Modify the country linked to field.

Additional Inherited Members

8.19.1 Detailed Description

The [CheckPostalCode](#) class Line Edit of postal code with a check icon.

8.19.2 Constructor & Destructor Documentation

8.19.2.1 `Gui::Widgets::CheckFields::CheckPostalCode::CheckPostalCode (QWidget * w = 0, QPushButton * btn = 0)`

[CheckPostalCode::CheckPostalCode](#) Construct a [CheckPostalCode](#).

Parameters

<i>w</i>	QWidget linked to CheckPostalCode
----------	---

8.19.3 Member Function Documentation

8.19.3.1 `bool Gui::Widgets::CheckFields::CheckPostalCode::check (QString text) [virtual]`

[CheckPostalCode::check](#) Check if the field is valid. To be valid, a name should be composed of a character.

Parameters

<i>text</i>	Text to check
-------------	---------------

Returns

boolean Validity of the text

Implements [Gui::Widgets::CheckFields::ICheckField](#).

8.19.3.2 `QString Gui::Widgets::CheckFields::CheckPostalCode::getCountry () const`

[CheckPostalCode::getCountry](#) Return the country linked to current field.

Returns

country Country of the field

8.19.3.3 `void Gui::Widgets::CheckFields::CheckPostalCode::setCountry (const QString & country)`

[CheckPostalCode::setCountry](#) Modify the *country* linked to field.

Parameters

<i>country</i>	New country
----------------	-------------

The documentation for this class was generated from the following files:


- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkpostalcode.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkpostalcode.cpp

8.20 Gui::Widgets::CheckFields::CheckQLineEdit Class Reference

The [CheckQLineEdit](#) class QLineEdit custom with a check of text inputed.

```
#include <checkqlineEdit.h>
```

Inheritance diagram for Gui::Widgets::CheckFields::CheckQLineEdit:



Public Slots

- void [fieldTextChanged](#) (const QString &text)
[CheckQLineEdit::fieldTextChanged](#) For each new characater inputed or removed, displays an icon to show if the field is valid or not.

Public Member Functions

- [CheckQLineEdit](#) (QWidget *parent=0, QPushButton *btn=0)
[CheckQLineEdit::CheckQLineEdit](#) Construct a [CheckQLineEdit](#).
- void [displayCheckValidFieldIcon](#) ()
[CheckQLineEdit::displayCheckValidFieldIcon](#) Display a valid icon into the field.
- void [displayCheckNoValidFieldIcon](#) ()
[CheckQLineEdit::displayCheckNoValidFieldIcon](#) Display a "no valid" icon into the field.
- QPushButton * [getBtnValid](#) () const
[CheckQLineEdit::getBtnValid](#).
- void [setBtnValid](#) (QPushButton *getBtnValid)
[CheckQLineEdit::setBtnValid](#).
- bool [isValid](#) ()
[isValid](#) Return true if the current field if valid

8.20.1 Detailed Description

The [CheckQLineEdit](#) class QLineEdit custom with a check of text inputed.

8.20.2 Constructor & Destructor Documentation

- 8.20.2.1 [Gui::Widgets::CheckFields::CheckQLineEdit::CheckQLineEdit](#) (QWidget * *parent* = 0, QPushButton * *btn* = 0)
[explicit]

[CheckQLineEdit::CheckQLineEdit](#) Construct a [CheckQLineEdit](#).

Parameters

<i>parent</i>	
---------------	--

8.20.3 Member Function Documentation

8.20.3.1 `QPushButton * Gui::Widgets::CheckFields::CheckQLineEdit::getBtnValid () const`

[CheckQLineEdit::getBtnValid.](#)

Returns

a

8.20.3.2 `bool Gui::Widgets::CheckFields::CheckQLineEdit::isValid ()`

isValid Return true if the current field if valid

Returns

boolean

8.20.3.3 `void Gui::Widgets::CheckFields::CheckQLineEdit::setBtnValid (QPushButton * getBtnValid)`

[CheckQLineEdit::setBtnValid.](#)

Parameters

<i>getBtnValid</i>	
--------------------	--

The documentation for this class was generated from the following files:


- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkqlineEdit.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkqlineEdit.cpp

8.21 Gui::Widgets::CheckFields::CheckSiretNumber Class Reference

The [CheckSiretNumber](#) class Line Edit with a check icon.

```
#include <checksiretnumber.h>
```

Inheritance diagram for Gui::Widgets::CheckFields::CheckSiretNumber:



Public Member Functions

- [CheckSiretNumber](#) (QWidget *w=0, QPushButton *btn=0)

[CheckSiretNumber::CheckSiretNumber](#) Construct a [CheckSiretNumber](#).

- bool [check](#) (QString text)

[CheckSiretNumber::check](#) Check if the field noSiret is valid. To be valid, a SIRET number should be composed of numbers.

Additional Inherited Members

8.21.1 Detailed Description

The [CheckSiretNumber](#) class Line Edit with a check icon.

8.21.2 Constructor & Destructor Documentation

8.21.2.1 [Gui::Widgets::CheckFields::CheckSiretNumber::CheckSiretNumber](#) ([QWidget](#) * *w* = 0, [QPushButton](#) * *btn* = 0)

[CheckSiretNumber::CheckSiretNumber](#) Construct a [CheckSiretNumber](#).

Parameters

<i>w</i>	QWidget linked to CheckSiretNumber
----------	--

8.21.3 Member Function Documentation

8.21.3.1 bool [Gui::Widgets::CheckFields::CheckSiretNumber::check](#) ([QString](#) *text*) [virtual]

[CheckSiretNumber::check](#) Check if the field noSiret is valid. To be valid, a SIRET number should be composed of numbers.

Parameters

<i>text</i>	Text to check
-------------	---------------

Returns

boolean Validity of the text

Implements [Gui::Widgets::CheckFields::ICheckField](#).

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checksiretnumber.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checksiretnumber.cpp

8.22 Gui::Widgets::CheckFields::CheckUntilField Class Reference

The [CheckUntilField](#) class.

```
#include <checkuntilfield.h>
```

Inheritance diagram for [Gui::Widgets::CheckFields::CheckUntilField](#):



Public Member Functions

- [CheckUntilField](#) (QWidget *w=0, QPushButton *btn=0)
[CheckUntilField::CheckUntilField](#) Construct a [CheckUntilField](#).
- bool [check](#) (QString text)
[CheckUntilField::check](#) Check if the field is valid. To be valid, a name should be composed of a character.

Additional Inherited Members

8.22.1 Detailed Description

The [CheckUntilField](#) class.

8.22.2 Constructor & Destructor Documentation

8.22.2.1 [Gui::Widgets::CheckFields::CheckUntilField::CheckUntilField](#) ([QWidget](#) * *w* = 0, [QPushButton](#) * *btn* = 0)

[CheckUntilField::CheckUntilField](#) Construct a [CheckUntilField](#).

Parameters

<i>w</i>	QWidget linked to CheckUntilField
----------	---

8.22.3 Member Function Documentation

8.22.3.1 bool [Gui::Widgets::CheckFields::CheckUntilField::check](#) ([QString](#) *text*) [virtual]

[CheckUntilField::check](#) Check if the field is valid. To be valid, a name should be composed of a character.

Parameters

<i>text</i>	Text to check
-------------	---------------

Returns

boolean Validity of the text

Implements [Gui::Widgets::CheckFields::ICheckField](#).

The documentation for this class was generated from the following files:


- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkuntilfield.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkuntilfield.cpp

8.23 Gui::Widgets::CheckFields::CheckValidField Class Reference

The [CheckValidField](#) class Check field not required.

```
#include <checkvalidfield.h>
```

Inheritance diagram for [Gui::Widgets::CheckFields::CheckValidField](#):



Public Member Functions

- [CheckValidField](#) (QWidget *w=0, QPushButton *btn=0)
[CheckValidField::CheckValidField](#).
- bool [check](#) (QString text)
[CheckValidField::check](#) Return TRUE : the field is not required.

Additional Inherited Members

8.23.1 Detailed Description

The [CheckValidField](#) class Check field not required.

8.23.2 Constructor & Destructor Documentation

8.23.2.1 [Gui::Widgets::CheckFields::CheckValidField::CheckValidField](#) (QWidget * *w* = 0, QPushButton * *btn* = 0)

[CheckValidField::CheckValidField](#).

Parameters

<i>w</i>	QWidget linked to CheckValidField
----------	---

8.23.3 Member Function Documentation

8.23.3.1 bool [Gui::Widgets::CheckFields::CheckValidField::check](#) (QString *text*) [virtual]

[CheckValidField::check](#) Return TRUE : the field is not required.

Parameters

<i>text</i>	Text to check
-------------	---------------

Returns

boolean Validity of the text

Implements [Gui::Widgets::CheckFields::ICheckField](#).

The documentation for this class was generated from the following files:


- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkvalidfield.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkvalidfield.cpp

8.24 Gui::Widgets::Delegates::ComboBoxDelegate Class Reference

The [ComboBoxDelegate](#) class.

```
#include <comboboxdelegate.h>
```

Inheritance diagram for Gui::Widgets::Delegates::ComboBoxDelegate:



Public Member Functions

- [ComboBoxDelegate](#) (QObject *parent=0)
ComboBoxDelegate::ComboBoxDelegate Construct a [ComboBoxDelegate](#).
- virtual QWidget * [createEditor](#) (QWidget *parent, const QStyleOptionViewItem &option, const QModelIndex &index) const =0
ComboBoxDelegate::createEditor Return a *ComboBox* specified by index item defined by the parent widget and style option which are used to control how the editor widgets appears.
- void [paint](#) (QPainter *painter, const QStyleOptionViewItem &option, const QModelIndex &index) const =0
ComboBoxDelegate::paint Renders the delegate using the given painter and style option for the item specified by index
- void [setEditorData](#) (QWidget *editor, const QModelIndex &index) const
ComboBoxDelegate::setEditorData Sets the data to be displayed and edited by the editor from the data model item specified by the model index
- void [setModelData](#) (QWidget *editor, QAbstractItemModel *model, const QModelIndex &index) const
ComboBoxDelegate::setModelData Gets data from the editor widget and stores it in the specified model at the item index
- void [updateEditorGeometry](#) (QWidget *editor, const QStyleOptionViewItem &option, const QModelIndex &index) const
ComboBoxDelegate::updateEditorGeometry Update the editor for the item specified by index according to the style option given.

8.24.1 Detailed Description

The [ComboBoxDelegate](#) class.

Author

Antoine de Roquemaurel

8.24.2 Constructor & Destructor Documentation

8.24.2.1 Gui::Widgets::Delegates::ComboBoxDelegate::ComboBoxDelegate (QObject * parent = 0)

[ComboBoxDelegate::ComboBoxDelegate](#) Construct a [ComboBoxDelegate](#).

Parameters

<i>parent</i>	Object parent
---------------	---------------

8.24.3 Member Function Documentation

8.24.3.1 `virtual QWidget* Gui::Widgets::Delegates::ComboBoxDelegate::createEditor (QWidget * parent, const QStyleOptionViewItem & option, const QModelIndex & index) const` [pure virtual]

[ComboBoxDelegate::createEditor](#) Return a ComboBox specified by *index* item defined by the *parent* widget and style *option* which are used to control how the editor widgets appears.

Parameters

<i>parent</i>	Widget parent
<i>option</i>	Option style
<i>index</i>	Index for editing

Returns

ComboBox

Implemented in [Gui::Widgets::Delegates::UnitComboDelegate](#), and [Gui::Widgets::Delegates::ProjectComboDelegate](#).

8.24.3.2 `void Gui::Widgets::Delegates::ComboBoxDelegate::paint (QPainter * painter, const QStyleOptionViewItem & option, const QModelIndex & index) const` [pure virtual]

[ComboBoxDelegate::paint](#) Renders the delegate using the given *painter* and style *option* for the item specified by *index*

Parameters

<i>parent</i>	Widget parent
<i>option</i>	Option style
<i>index</i>	Index for editing

Implemented in [Gui::Widgets::Delegates::UnitComboDelegate](#), and [Gui::Widgets::Delegates::ProjectComboDelegate](#).

8.24.3.3 `void Gui::Widgets::Delegates::ComboBoxDelegate::setEditorData (QWidget * editor, const QModelIndex & index) const`

[ComboBoxDelegate::setEditorData](#) Sets the data to be displayed and edited by the *editor* from the data model item specified by the model *index*

Parameters

<i>editor</i>	Data edited
<i>index</i>	Index of the model to edit

8.24.3.4 `void Gui::Widgets::Delegates::ComboBoxDelegate::setModelData (QWidget * editor, QAbstractItemModel * model, const QModelIndex & index) const`

[ComboBoxDelegate::setModelData](#) Gets data from the *editor* widget and stores it in the specified *model* at the item *index*

Parameters

<i>editor</i>	Editor Widget
<i>model</i>	Model to store data
<i>index</i>	Item index

8.24.3.5 void Gui::Widgets::Delegates::ComboBoxDelegate::updateEditorGeometry (QWidget * *editor*, const QStyleOptionViewItem & *option*, const QModelIndex & *index*) const

[ComboBoxDelegate::updateEditorGeometry](#) Update the *editor* for the item specified by *index* according to the style *option* given.

Parameters

<i>editor</i>	Editor widget to update
<i>option</i>	Style option
<i>index</i>	Item index

The documentation for this class was generated from the following files:


- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/delegates/comboboxdelegate.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/delegates/comboboxdelegate.cpp

8.25 Gui::Widgets::ComboBoxModelWidget Class Reference

The [ComboBoxModelWidget](#) class Model of ComboBox.

```
#include <comboboxmodelwidget.h>
```

Inheritance diagram for Gui::Widgets::ComboBoxModelWidget:



Public Member Functions

- [ComboBoxModelWidget](#) (QWidget *parent=0)
[ComboBoxModelWidget::ComboBoxModelWidget](#) Construct a [ComboBoxModelWidget](#).

8.25.1 Detailed Description

The [ComboBoxModelWidget](#) class Model of ComboBox.

8.25.2 Constructor & Destructor Documentation

8.25.2.1 Gui::Widgets::ComboBoxModelWidget::ComboBoxModelWidget (QWidget * *parent* = 0) [explicit]

[ComboBoxModelWidget::ComboBoxModelWidget](#) Construct a [ComboBoxModelWidget](#).

Parameters

<i>parent</i>	QWidget parent
---------------	----------------

The documentation for this class was generated from the following files:


- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/comboboxmodelwidget.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/comboboxmodelwidget.cpp

8.26 Gui::Dialogs::ComputeTurnoverDialog Class Reference

The [ComputeTurnoverDialog](#) class window to compute a turnover with a period.

```
#include <computeturnoverdialog.h>
```

Inheritance diagram for Gui::Dialogs::ComputeTurnoverDialog:



Public Slots

- void [computeTurnover](#) ()
ComputeTurnoverDialog::computeTurnover compute the turnover between chosen dates in the window.
- void [endDateControl](#) (const QDate end)
ComputeTurnoverDialog::endDateControl controls if the end date field is valid.
- void [beginDateControl](#) (const QDate begin)
ComputeTurnoverDialog::beginDateControl controls if the begin date field is valid.

Public Member Functions

- **ComputeTurnoverDialog** (QWidget *parent=0)
- void [fillLabels](#) (const int nbBillings, const int turnover)
ComputeTurnoverDialog::fillLabels Fills the labels with nbBillings and turnover

8.26.1 Detailed Description

The [ComputeTurnoverDialog](#) class window to compute a turnover with a period.

Author

Manantsoa Razanajatovo

8.26.2 Member Function Documentation

8.26.2.1 void [Gui::Dialogs::ComputeTurnoverDialog::beginDateControl](#) (const QDate *begin*) [slot]

[ComputeTurnoverDialog::beginDateControl](#) controls if the *begin* date field is valid.

Parameters

<i>begin</i>	
--------------	--

8.26.2.2 void Gui::Dialogs::ComputeTurnoverDialog::endDateControl (const QDate *end*) [slot]

[ComputeTurnoverDialog::endDateControl](#) controls if the *end* date field is valid.

Parameters

<i>end</i>	
------------	--

8.26.2.3 void Gui::Dialogs::ComputeTurnoverDialog::fillLabels (const int *nbBillings*, const int *turnover*)

[ComputeTurnoverDialog::fillLabels](#) Fills the labels with *nbBillings* and *turnover*

Parameters

<i>nbBillings</i>	the number of Billings
<i>turnover</i>	the turnover computed


The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/dialogs/computeturnoverdialog.h
- /home/travis/build/FACT-Team/FactDev/src/gui/dialogs/computeturnoverdialog.cpp

8.27 Mustache::Context Class Reference

```
#include <mustache.h>
```

Inheritance diagram for Mustache::Context:



Public Member Functions

- [Context](#) ([PartialResolver](#) *resolver=0)
- virtual QString [stringValue](#) (const QString &key) const =0
- virtual bool [isFalse](#) (const QString &key) const =0
- virtual int [listCount](#) (const QString &key) const =0
- virtual void [push](#) (const QString &key, int index=-1)=0
- virtual void [pop](#) ()=0
- QString [partialValue](#) (const QString &key) const
- [PartialResolver](#) * [partialResolver](#) () const
- virtual bool [canEval](#) (const QString &key) const
- virtual QString [eval](#) (const QString &key, const QString &_template, [Renderer](#) *renderer)

8.27.1 Detailed Description

[Context](#) is an interface that [Mustache::Renderer::render\(\)](#) uses to fetch substitutions for template tags.

8.27.2 Constructor & Destructor Documentation

8.27.2.1 `Context::Context (PartialResolver * resolver = 0)` `[explicit]`

Create a context. `resolver` is used to fetch the expansions for any `{{>partial}}` tags which appear in a template.

8.27.3 Member Function Documentation

8.27.3.1 `bool Context::canEval (const QString & key) const` `[virtual]`

Returns true if `eval()` should be used to render section tags using `key`. If `canEval()` returns true for a key, the renderer will pass the literal, unrendered block of text for the section to `eval()` and replace the section with the result.

`canEval()` and `eval()` are equivalents for callable objects (eg. lambdas) in other Mustache implementations.

The default implementation always returns false.

Reimplemented in [CounterContext](#), [CounterContext](#), and [Mustache::QtVariantContext](#).

8.27.3.2 `QString Context::eval (const QString & key, const QString & _template, Renderer * renderer)` `[virtual]`

Callback used to render a template section with the given `key`. `renderer` will substitute the original section tag with the result of `eval()`.

The default implementation returns an empty string.

Reimplemented in [CounterContext](#), [CounterContext](#), and [Mustache::QtVariantContext](#).

8.27.3.3 `virtual bool Mustache::Context::isFalse (const QString & key) const` `[pure virtual]`

Returns true if the value for `key` is 'false' or an empty list. 'False' values typically include empty strings, the boolean value false etc.

When processing a section Mustache tag, the section is not rendered if the key is false, or for an inverted section tag, the section is only rendered if the key is false.

Implemented in [Mustache::QtVariantContext](#).

8.27.3.4 `virtual int Mustache::Context::listCount (const QString & key) const` `[pure virtual]`

Returns the number of items in the list value for `key` or 0 if the value for `key` is not a list.

Implemented in [Mustache::QtVariantContext](#).

8.27.3.5 `PartialResolver * Context::partialResolver () const`

Returns the partial resolver passed to the constructor.

8.27.3.6 `QString Context::partialValue (const QString & key) const`

Returns the partial template for a given `key`.

8.27.3.7 virtual void Mustache::Context::pop () [pure virtual]

Exit the current context.

Implemented in [Mustache::QtVariantContext](#).

8.27.3.8 virtual void Mustache::Context::push (const QString & key, int index = -1) [pure virtual]

Set the current context to the value for `key`. If `index` is ≥ 0 , set the current context to the `index`'th value in the list value for `key`.

Implemented in [Mustache::QtVariantContext](#).

8.27.3.9 virtual QString Mustache::Context::stringValue (const QString & key) const [pure virtual]

Returns a string representation of the value for `key` in the current context. This is used to replace a Mustache value tag.


Implemented in [CounterContext](#), [CounterContext](#), and [Mustache::QtVariantContext](#).

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/libs/qt-mustache/src/mustache.h
- /home/travis/build/FACT-Team/FactDev/src/libs/qt-mustache/src/mustache.cpp

8.28 ContributoriesDatabaseTest Class Reference

Inheritance diagram for ContributoriesDatabaseTest:



The documentation for this class was generated from the following files:


- /home/travis/build/FACT-Team/FactDev/tests/database/contributoriesdatabasetest.h
- /home/travis/build/FACT-Team/FactDev/tests/database/contributoriesdatabasetest.cpp

8.29 Models::ContributoriesList Class Reference

The [ContributoriesList](#) class List of contributories.

```
#include <contributorieslist.h>
```

Inheritance diagram for Models::ContributoriesList:



Public Member Functions

- [ContributorList \(\)](#)
ContributorList::ContributorList Construct a [ContributorList](#).
- virtual void [commit \(\)](#)
ContributorList::commit Update or insert data into the database.
- void [addContributory \(Models::Contributory &contributory\)](#)
ContributorList::addContributory Add a new contributory
- void [addProject \(Project *p, Models::Rate rate\)](#)
ContributorList::addProject Add a [Project](#) p and it rate
- QList< [Contributory](#) > & [getContributories \(Project *p\)](#)
ContributorList::getContributories Return a list of ContributorList for the [Project](#) p
- int [getIdBilling \(\)](#) const
ContributorList::getIdBilling Return the [Billing](#) ID.
- void [setIdBilling \(int idBilling\)](#)
ContributorList::setIdBilling Change the [Billing](#) id by the new idBilling
- void [setAllIdContributories \(int idContributory\)](#)
ContributorList::setAllIdContributories Change all [Contributory](#) id with the same id.
- bool [isInsert \(\)](#) const
ContributorList::isInsert Return TRUE if an element is inserting else FALSE.
- void [setInsert \(bool insert\)](#)
ContributorList::setInsert Change the state of insertion.
- int [getNbProjects \(\)](#)
ContributorList::getNbProjects Return the number of projects.
- double [getSumRate \(\)](#)
ContributorList::getSumRate Return the sum of the contributories rates.
- double [getSumQuantity \(\)](#)
ContributorList::getSumQuantity Return the sum of quantity (number of hours) of the ContributorList.
- QSharedPointer< [Customer](#) > [getCustomer \(\)](#)
ContributorList::getCustomer Return the Customers linked to theses contributories.
- QList< [Project](#) * > [getProjects \(\)](#)
ContributorList::getProjects List of Projects.
- QList< [Contributory](#) > * [getAllContributories \(\)](#)
ContributorList::getAllContributories List of all contributories (all contributories from all projects)
- [Models::Rate](#) [getRate \(Models::Project *project\)](#)
ContributorList::getRate.
- QVariantList [getDataMap \(\)](#)
ContributorList::getDataMap Return a list of [Billing](#) and it value linked which indicates if it is inserting or not.

8.29.1 Detailed Description

The [ContributorList](#) class List of contributories.

Author

Antoine de Roquemaurel

8.29.2 Member Function Documentation

8.29.2.1 void [Models::ContributorList::addContributory \(Models::Contributory & contributory \)](#)

[ContributorList::addContributory](#) Add a new contributory

Parameters

<i>contributory</i>	Contributory to add
---------------------	-------------------------------------

8.29.2.2 void Models::ContributoriesList::addProject ([Project](#) * *p*, Models::Rate *rate*)

[ContributoriesList::addProject](#) Add a [Project](#) *p* and it *rate*

Parameters

<i>p</i>	Project to add
<i>rate</i>	Rate of the project

8.29.2.3 QList< [Contributory](#) > * Models::ContributoriesList::getAllContributories ()

[ContributoriesList::getAllContributories](#) List of all contributories (all contributories from all projects)

Returns

List of all contributories

8.29.2.4 QList< [Contributory](#) > & Models::ContributoriesList::getContributories ([Project](#) * *p*)

[ContributoriesList::getContributories](#) Return a list of Contributories for the [Project](#) *p*

Parameters

<i>p</i>	Project
----------	-------------------------

Returns

List of Contributories for a project

8.29.2.5 QSharedPointer< [Customer](#) > Models::ContributoriesList::getCustomer ()

[ContributoriesList::getCustomer](#) Return the Customers linked to theses contributories.

Returns

[Customer](#)

8.29.2.6 QVariantList Models::ContributoriesList::getDataMap ()

[ContributoriesList::getDataMap](#) Return a list of [Billing](#) and it value linked which indicates if it is inserting or not.

Returns

List of billing and value linked

8.29.2.7 int Models::ContributoriesList::getIdBilling () const

[ContributoriesList::getIdBilling](#) Return the [Billing](#) ID.

Returns

[Billing](#) id

8.29.2.8 `int Models::ContributoriesList::getNbProjects ()`

[ContributoriesList::getNbProjects](#) Return the number of projects.

Returns

Count number of project

8.29.2.9 `QList< Project * > Models::ContributoriesList::getProjects (void)`

[ContributoriesList::getProjects](#) List of Projects.

Returns

List of Projects

8.29.2.10 `Models::Rate Models::ContributoriesList::getRate (Models::Project * project)`

[ContributoriesList::getRate](#).

Parameters

<i>project</i>	
----------------	--

Returns

8.29.2.11 `double Models::ContributoriesList::getSumQuantity ()`

[ContributoriesList::getSumQuantity](#) Return the sum of quantity (number of hours) of the Contributories.

Returns

sum of quantity

8.29.2.12 `double Models::ContributoriesList::getSumRate ()`

[ContributoriesList::getSumRate](#) Return the sum of the contributories rates.

Returns

Sum of contributories rates

8.29.2.13 `bool Models::ContributoriesList::isInsert () const`

[ContributoriesList::isInsert](#) Return TRUE if an element is inserting else FALSE.

Returns

boolean

8.29.2.14 `void Models::ContributoriesList::setAllIdContributories (int idContributory)`

[ContributoriesList::setAllIdContributories](#) Change all [Contributory](#) id with the same id.

Parameters

<i>idContributory</i>	the new Contributory id
-----------------------	---

8.29.2.15 void Models::ContributoriesList::setIdBilling (int *idBilling*)

[ContributoriesList::setIdBilling](#) Change the [Billing](#) id by the new *idBilling*

Parameters

<i>idBilling</i>	Billing id
------------------	------------

8.29.2.16 void Models::ContributoriesList::setInsert (bool *insert*)

[ContributoriesList::setInsert](#) Change the state of insertion.

Parameters

<i>insert</i>	Boolean
---------------	---------

The documentation for this class was generated from the following files:


- /home/travis/build/FACT-Team/FactDev/src/models/contributorieslist.h
- /home/travis/build/FACT-Team/FactDev/src/models/contributorieslist.cpp

8.30 Gui::Widgets::WdgModels::ContributoriesTableModel Class Reference

The [ContributoriesTableModel](#) class for a custom table for contributories widget.

```
#include <contributoriestablemodel.h>
```

Inheritance diagram for Gui::Widgets::WdgModels::ContributoriesTableModel:



Public Member Functions

- [ContributoriesTableModel](#) (QObject *parent=0)
[ContributoriesTableModel::ContributoriesTableModel](#) Construct a [ContributoriesTableModel](#).
- int [rowCount](#) (const QModelIndex &) const
[ContributoriesTableModel::rowCount](#) Number of contributories row.
- int [columnCount](#) (const QModelIndex &) const
[ContributoriesTableModel::columnCount](#) Number of column of a contributory.
- QVariant [data](#) (const QModelIndex &index, int role) const
[ContributoriesTableModel::data](#) Obtains data of a specify cell.
- QVariant [headerData](#) (int section, Qt::Orientation orientation, int role) const
[ContributoriesTableModel::headerData](#) Obtains header title of table.
- bool [setData](#) (const QModelIndex &index, const QVariant &value, int role=Qt::EditRole)
[ContributoriesTableModel::setData](#) Change data of a cell.
- void [append](#) (const [Contributory](#) &contributory)

- [*ContributoriesTableModel::append*](#) Add a new line in table.
- void [*remove*](#) (const int i)
- [*ContributoriesTableModel::remove*](#) Remove a line.
- Qt::ItemFlags [*flags*](#) (const QModelIndex &index) const
- [*ContributoriesTableModel::flags*](#) Differents table flags.
- QList< [*Contributory*](#) > [*getContributories*](#) ()
- [*ContributoriesTableModel::getContributories*](#) Get all contributories of table.
- int [*count*](#) ()
- [*ContributoriesTableModel::count*](#) Number of contributories in table.
- double [*getSumQuantity*](#) () const
- [*ContributoriesTableModel::getSumQuantity*](#) Return the sum of the hours of all contriburoies added.
- void [*clear*](#) ()
- [*ContributoriesTableModel::clear*](#) Remove all contributories.

8.30.1 Detailed Description

The [*ContributoriesTableModel*](#) class for a custom table for contributories widget.

Author

Antoine de Roquemaurel

See Also

[*Contributory*](#)

8.30.2 Constructor & Destructor Documentation

8.30.2.1 [*Gui::Widgets::WdgModels::ContributoriesTableModel::ContributoriesTableModel \(QObject * parent = 0 \)*](#)

[*ContributoriesTableModel::ContributoriesTableModel*](#) Construct a [*ContributoriesTableModel*](#).

Parameters

<i>parent</i>	Parent widget
---------------	---------------

8.30.3 Member Function Documentation

8.30.3.1 void [*Gui::Widgets::WdgModels::ContributoriesTableModel::append \(const Contributory & contributory \)*](#)

[*ContributoriesTableModel::append*](#) Add a new line in table.

Parameters

<i>contributory</i>	The new contributory
---------------------	----------------------

8.30.3.2 int [*Gui::Widgets::WdgModels::ContributoriesTableModel::columnCount \(const QModelIndex & \)*](#) const

[*ContributoriesTableModel::columnCount*](#) Number of column of a contributory.

Returns

The number of column

8.30.3.3 `int Gui::Widgets::WdgModels::ContributoriesTableModel::count ()`

[ContributoriesTableModel::count](#) Number of contributories in table.

Returns

The number of contributories

8.30.3.4 `QVariant Gui::Widgets::WdgModels::ContributoriesTableModel::data (const QModelIndex & index, int role) const`

[ContributoriesTableModel::data](#) Obtains data of a specify cell.

Parameters

<i>index</i>	The cell who we want data
<i>role</i>	The role of set

Returns

The data of cell

8.30.3.5 `Qt::ItemFlags Gui::Widgets::WdgModels::ContributoriesTableModel::flags (const QModelIndex & index) const`

[ContributoriesTableModel::flags](#) Differents table flags.

Parameters

<i>index</i>	The cell who we want to know flags
--------------	------------------------------------

Returns

Flags

8.30.3.6 `QList< Contributory > Gui::Widgets::WdgModels::ContributoriesTableModel::getContributories ()`

[ContributoriesTableModel::getContributories](#) Get all contributories of table.

Returns

The contributory list

8.30.3.7 `double Gui::Widgets::WdgModels::ContributoriesTableModel::getSumQuantity () const`

[ContributoriesTableModel::getSumQuantity](#) Return the sum of the hours of all contriburoies added.

Returns

sum quantity

8.30.3.8 `QVariant Gui::Widgets::WdgModels::ContributoriesTableModel::headerData (int section, Qt::Orientation orientation, int role) const`

[ContributoriesTableModel::headerData](#) Obtains header title of table.

Parameters

<i>section</i>	The number of column
<i>orientation</i>	The table orientation
<i>role</i>	

Returns

The Title header of column

8.30.3.9 void Gui::Widgets::WdgModels::ContributoriesTableModel::remove (const int *i*)

[ContributoriesTableModel::remove](#) Remove a line.

Parameters

<i>i</i>	The number of line to remove
----------	------------------------------

8.30.3.10 int Gui::Widgets::WdgModels::ContributoriesTableModel::rowCount (const QModelIndex &) const

[ContributoriesTableModel::rowCount](#) Number of contributories row.

Returns

The number of contributories

8.30.3.11 bool Gui::Widgets::WdgModels::ContributoriesTableModel::setData (const QModelIndex & *index*, const QVariant & *value*, int *role* = Qt::EditRole)

[ContributoriesTableModel::setData](#) Change data of a cell.

Parameters

<i>index</i>	The cell to change data
<i>value</i>	The new value
<i>role</i>	The role of cell

Returns

True if we could edit

The documentation for this class was generated from the following files:


- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/widgetmodels/contributoriestablemodel.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/widgetmodels/contributoriestablemodel.cpp

8.31 Gui::Widgets::ContributoriesWidget Class Reference

The [ContributoriesWidget](#) class Widget of Contributories.

```
#include <contributorieswidget.h>
```

Inheritance diagram for Gui::Widgets::ContributoriesWidget:



Public Slots

- void [add](#) (void)
[ContributoriesWidget::add](#) Add a new empty contributory.
- void [remove](#) (void)
[ContributoriesWidget::remove](#) Remove the current contributory.
- void [addProject](#) (QPair< [Project](#) *, [Rate](#) > *p=0)
[ContributoriesWidget::addProject](#) Add a Projet and it rate p
- void [removeProject](#) (void)
[ContributoriesWidget::removeProject](#) Remove the current Project.
- void [changeProject](#) (void)
[ContributoriesWidget::changeProject](#) Change the current Project.
- void [editing](#) (void)
[ContributoriesWidget::editing](#) Remove the current Project in the combobox not used.
- void [updateUi](#) (void)
[ContributoriesWidget::updateUi](#) Update the User Interface.
- void [updatePrice](#) (void)
[ContributoriesWidget::updatePrice](#) Update total price.

Signals

- void [contributoryChanged](#) ()
[ContributoriesWidget::contributoryChanged](#) Signal that a contributory has changed.

Public Member Functions

- [ContributoriesWidget](#) (QSharedPointer< [Customer](#) > c, QWidget *parent=0)
[ContributoriesWidget::ContributoriesWidget](#) Construct a [ContributoriesWidget](#).
- [ContributoriesList](#) * [getContributories](#) () const
[ContributoriesWidget::getContributories](#) Get contributories List.
- int [count](#) ()
[ContributoriesWidget::count](#) Numbers of contributories.
- void [add](#) ([ContributoriesList](#) &list)
[ContributoriesWidget::add](#) Add contributorieslist list in the model.

8.31.1 Detailed Description

The [ContributoriesWidget](#) class Widget of Contributories.

8.31.2 Constructor & Destructor Documentation

- 8.31.2.1 [Gui::Widgets::ContributoriesWidget::ContributoriesWidget](#) (QSharedPointer< [Customer](#) > c, QWidget * parent = 0) [explicit]

[ContributoriesWidget::ContributoriesWidget](#) Construct a [ContributoriesWidget](#).

Parameters

<i>c</i>	Customer
<i>parent</i>	Widget parent

8.31.3 Member Function Documentation

8.31.3.1 void Gui::Widgets::ContributoriesWidget::add (ContributoriesList & *list*)

[ContributoriesWidget::add](#) Add contributorieslist *list* in the model.

Parameters

<i>list</i>	the ContributoriesList
-------------	-------------------------------

8.31.3.2 void Gui::Widgets::ContributoriesWidget::addProject (QPair< Project *, Rate > * *p* = 0) [slot]

[ContributoriesWidget::addProject](#) Add a Projet and it rate *p*

Parameters

<i>p</i>	Rate linked to Project
----------	------------------------

8.31.3.3 int Gui::Widgets::ContributoriesWidget::count ()

[ContributoriesWidget::count](#) Numbers of contributories.

Returns

Numbers of contributories

8.31.3.4 ContributoriesList * Gui::Widgets::ContributoriesWidget::getContributories () const

[ContributoriesWidget::getContributories](#) Get contributories List.

Returns

ContributoriesList

The documentation for this class was generated from the following files:


- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/contributorieswidget.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/contributorieswidget.cpp

8.32 Models::Contributory Class Reference

The [Contributory](#) class.

```
#include <contributory.h>
```

Inheritance diagram for Models::Contributory:



Public Member Functions

- [Contributory](#) ()
Contributory::Contributory Construct a [Contributory](#).
- [Contributory](#) (int id)
Contributory::Contributory Construct a [Contributory](#) and get data in database.
- [~Contributory](#) ()
Destroy an contributory object.
- void [commit](#) ()
Contributory::commit Update or insert a contributory to the database.
- void [hydrat](#) (int id)
Contributory::hydrat Get data about the [Contributory](#) which is specified by the identify id
- void [remove](#) ()
Contributory::remove Remove the current [Contributory](#).
- QVariantHash [getDataMap](#) ()
getDataMap Get all data of model with a HashMap key/value
- [Project](#) * [getProject](#) () const
Contributory::getProject Return the project linked to this [Contributory](#).
- void [setProject](#) ([Project](#) *id)
Contributory::setProject Modify the identify id of the [Project](#) linked to this [Contributory](#).
- double [getNbHours](#) () const
getNbHours Number of work hour of a contributory
- void [setNbHours](#) (double value)
setNbHours Change nbHours
- QString [getDescription](#) () const
getDescription Description of a contributory
- void [setDescription](#) (const QString &[getDescription](#))
setDescription Change the contributory description
- bool [operator==](#) (const [Contributory](#) &c)
operator == define the operator "==" to compare two [Contributory](#)
- bool [operator!=](#) (const [Contributory](#) &c)
operator != define the operator "!=" to compare two [Contributory](#)
- QString [getLongDescription](#) () const
- void [setLongDescription](#) (const QString &getLongDescription)

Additional Inherited Members

8.32.1 Detailed Description

The [Contributory](#) class.

Author

8.32.2 Constructor & Destructor Documentation

8.32.2.1 Models::Contributory::Contributory (int *id*)

[Contributory::Contributory](#) Construct a [Contributory](#) and get data in database.

Parameters

<i>id</i>	Contributory 's id
-----------	------------------------------------

8.32.3 Member Function Documentation

8.32.3.1 QVariantHash Models::Contributory::getDataMap () [virtual]

getDataMap Get all data of model with a HashMap key/value

Returns

Model's data

Implements [Models::IModel](#).

8.32.3.2 QString Models::Contributory::getDescription () const

getDescription Description of a contributory

Returns

The description

8.32.3.3 double Models::Contributory::getNbHours () const

getNbHours Number of work hour of a contributory

Returns

Then number of hours

8.32.3.4 Project * Models::Contributory::getProject () const

[Contributory::getProject](#) Return the project linked to this [Contributory](#).

Returns

[Project](#) linked to this [Contributory](#)

8.32.3.5 void Models::Contributory::hydrat (int *id*) [virtual]

[Contributory::hydrat](#) Get data about the [Contributory](#) which is specified by the identify *id*

Parameters

<i>id</i>	Contributory identify
-----------	---------------------------------------

Implements [Models::IModel](#).

8.32.3.6 bool Models::Contributory::operator!=(const Contributory & c)

operator != define the operator "!=" to compare two [Contributory](#)

Parameters

<i>c</i>	the Contributory to compare with the current Contributory
----------	---

Returns

true if the [Contributory](#) are different else false

8.32.3.7 bool Models::Contributory::operator==(const Contributory & c)

operator == define the operator "==" to compare two [Contributory](#)

Parameters

<i>c</i>	the Contributory to compare with the current Contributory
----------	---

Returns

true if the [Contributory](#) are equals else false

8.32.3.8 void Models::Contributory::setDescription (const QString & getDescription)

setDescription Change the contributory description

Parameters

<i>getDescription</i>	The new description
-----------------------	---------------------

8.32.3.9 void Models::Contributory::setNbHours (double value)

setNbHours Change nbHours

Parameters

<i>value</i>	The new value of nbHours
--------------	--------------------------

8.32.3.10 void Models::Contributory::setProject (Project * id)

[Contributory::setProject](#) Modify the identify *id* of the [Project](#) linked to this [Contributory](#).

Parameters

<i>id</i>	Project Identify
-----------	----------------------------------

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/models/contributory.h
- /home/travis/build/FACT-Team/FactDev/src/models/contributory.cpp

8.33 Databases::ContributoryDatabase Class Reference

The [ContributoryDatabase](#) class Contributory (or Quote) table database.

```
#include <contributorydatabase.h>
```

Inheritance diagram for Databases::ContributoryDatabase:



Public Member Functions

- [Models::Contributory](#) * [getContributory](#) (const int idContributory)
ContributoryDatabase::getCustomer get informations about the Contributory identified by pld
- [Models::ContributoriesList](#) [getContributoriesByBilling](#) (const int billingId)
ContributoryDatabase::getContributoriesByBilling get informations about the Contributory identified by Billing
- int [addContributory](#) (const [Models::Contributory](#) &)
ContributoryDatabase::addContributory Add the Contributory pContributory to the database.
- void [updateContributory](#) (const [Models::Contributory](#) &)
ContributoryDatabase::updateCustomer Update informations about the Contributory pCustomer
- void [removeContributory](#) (const int pld)
ContributoryDatabase::removeCustomer Remove the Contributory with the id pld
- [Models::Contributory](#) * [getContributory](#) (QString &q)
getContributory Obtain a contributory without new query
- [Models::ContributoriesList](#) [getContributoriesByBillingAndProject](#) (const int billingId, const int projectId)
getContributory Get contributories list by project and billing

Static Public Member Functions

- static [ContributoryDatabase](#) * [instance](#) () throw (DbException*)
ContributoryDatabase::getInstance Return an instance of [ContributoryDatabase](#)

Additional Inherited Members

8.33.1 Detailed Description

The [ContributoryDatabase](#) class Contributory (or Quote) table database.

Author

See Also

[Database](#)
Contributory/Quote

8.33.2 Member Function Documentation

8.33.2.1 int Databases::ContributoryDatabase::addContributory (const [Models::Contributory](#) & pContributory)

[ContributoryDatabase::addContributory](#) Add the Contributory pContributory to the database.

Returns

Contributory id

8.33.2.2 Models::ContributoriesList Databases::ContributoryDatabase::getContributoriesByBilling (const int *billingId*)

[ContributoryDatabase::getContributoriesByBilling](#) get informations about the Contributory identified by *Billing*

Parameters

<i>idBilling</i>	Contributory id
------------------	-----------------

Returns

the Contributory

8.33.2.3 **Models::ContributoriesList** Databases::ContributoryDatabase::getContributoriesByBillingAndProject (const int *billingId*, const int *projectId*)

getContributory Get contributories list by project and billing

Parameters

<i>billingId</i>	
<i>projectId</i>	

Returns

The contributories list by project and billing

8.33.2.4 **Models::Contributory** * Databases::ContributoryDatabase::getContributory (const int *idContributory*)

ContributoryDatabase::getCustomer get informations about the Contributory identified by *pId*

Parameters

<i>idContributory</i>	Contributory id
-----------------------	-----------------

Returns

the Contributory

8.33.2.5 **Models::Contributory** * Databases::ContributoryDatabase::getContributory (QSqlQuery & *q*)

getContributory Obtain a contributory without new query

Parameters

<i>q</i>	The query to use
----------	------------------

Returns

The contributory linked to q

8.33.2.6 **ContributoryDatabase** * Databases::ContributoryDatabase::instance () throw DbException *) [static]

ContributoryDatabase::getInstance Return an instance of [ContributoryDatabase](#)

See Also

DbException

Returns

Instance of [ContributoryDatabase](#)

8.33.2.7 void Databases::ContributoryDatabase::removeContributory (const int *pld*)

ContributoryDatabase::removeCustomer Remove the Contributory with the id *pld*

Parameters

<i>pld</i>	Contributory id
------------	-----------------

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/database/contributorydatabase.h
- /home/travis/build/FACT-Team/FactDev/src/database/contributorydatabase.cpp

8.34 ContributoryListTest Class Reference

Inheritance diagram for ContributoryListTest:




The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/tests/models/contributorylisttest.h
- /home/travis/build/FACT-Team/FactDev/tests/models/contributorylisttest.cpp

8.35 ContributoryModelTest Class Reference

Inheritance diagram for ContributoryModelTest:



The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/tests/models/contributorymodeltest.h
- /home/travis/build/FACT-Team/FactDev/tests/models/contributorymodeltest.cpp

8.36 CounterContext Class Reference

Inheritance diagram for CounterContext:



Public Member Functions

- **CounterContext** (const QVariantHash &map)
- virtual bool [canEval](#) (const QString &key) const
- virtual QString [eval](#) (const QString &key, const QString &_template, [Mustache::Renderer](#) *renderer)
- virtual QString [stringValue](#) (const QString &key) const
- **CounterContext** (const QVariantHash &map)
- virtual bool [canEval](#) (const QString &key) const
- virtual QString [eval](#) (const QString &key, const QString &_template, [Mustache::Renderer](#) *renderer)
- virtual QString [stringValue](#) (const QString &key) const

Public Attributes

- int **counter**

Additional Inherited Members

8.36.1 Member Function Documentation

8.36.1.1 virtual bool CounterContext::canEval (const QString &key) const [inline], [virtual]

Returns true if [eval\(\)](#) should be used to render section tags using `key`. If [canEval\(\)](#) returns true for a key, the renderer will pass the literal, unrendered block of text for the section to [eval\(\)](#) and replace the section with the result.

[canEval\(\)](#) and [eval\(\)](#) are equivalents for callable objects (eg. lambdas) in other Mustache implementations.

The default implementation always returns false.

Reimplemented from [Mustache::QtVariantContext](#).

8.36.1.2 virtual bool CounterContext::canEval (const QString &key) const [inline], [virtual]

Returns true if [eval\(\)](#) should be used to render section tags using `key`. If [canEval\(\)](#) returns true for a key, the renderer will pass the literal, unrendered block of text for the section to [eval\(\)](#) and replace the section with the result.

[canEval\(\)](#) and [eval\(\)](#) are equivalents for callable objects (eg. lambdas) in other Mustache implementations.

The default implementation always returns false.

Reimplemented from [Mustache::QtVariantContext](#).

8.36.1.3 virtual QString CounterContext::eval (const QString &key, const QString &_template, [Mustache::Renderer](#) *renderer) [inline], [virtual]

Callback used to render a template section with the given `key`. `renderer` will substitute the original section tag with the result of [eval\(\)](#).

The default implementation returns an empty string.

Reimplemented from [Mustache::QtVariantContext](#).

8.36.1.4 virtual QString CounterContext::eval (const QString &key, const QString &_template, [Mustache::Renderer](#) *renderer) [inline], [virtual]

Callback used to render a template section with the given `key`. `renderer` will substitute the original section tag with the result of [eval\(\)](#).

The default implementation returns an empty string.

Reimplemented from [Mustache::QtVariantContext](#).

8.36.1.5 `virtual QString CounterContext::stringValue (const QString & key) const` `[inline], [virtual]`

Returns a string representation of the value for `key` in the current context. This is used to replace a Mustache value tag.

Reimplemented from [Mustache::QtVariantContext](#).

8.36.1.6 `virtual QString CounterContext::stringValue (const QString & key) const` `[inline], [virtual]`

Returns a string representation of the value for `key` in the current context. This is used to replace a Mustache value tag.

Reimplemented from [Mustache::QtVariantContext](#).

The documentation for this class was generated from the following file:


- `/home/travis/build/FACT-Team/FactDev/src/libs/qt-mustache/tests/test_mustache.cpp`

8.37 Models::Customer Class Reference

The [Customer](#) class [Customer](#).

```
#include <customer.h>
```

Inheritance diagram for Models::Customer:



Public Member Functions

- [Customer](#) ()
Customer::Customer Construct a [Customer](#).
- [Customer](#) (int id)
Customer::Customer Construct a [Customer](#) who is specified by id
- void [commit](#) ()
Customer::commit Update customer data on the database.
- void [hydrat](#) (int id)
Customer::hydrat Insert into database informations related to the [Customer](#) who is specified by id
- void [remove](#) ()
Customer::remove Remove the current customer.
- QVariantHash [getDataMap](#) ()
getDataMap Get all data of model with a HashMap key/value
- QString [getPath](#) () const
Customer::getPath Return the path of the workspace for the current [Customer](#).
- QString [getNameFolder](#) () const
Customer::getNameFolder Return the name of the current [Customer](#)'s folder in the workspace.
- double [getTurnover](#) () const
Customer::getTurnover Return the turnover of the customer money that customer pay, revenue sales.

Additional Inherited Members

8.37.1 Detailed Description

The [Customer](#) class [Customer](#).

Author

Antoine de Roquemaurel
Florent Berbie

8.37.2 Constructor & Destructor Documentation

8.37.2.1 Models::Customer::Customer (int *id*)

[Customer::Customer](#) Construct a [Customer](#) who is specied by *id*

Parameters

<i>id</i>	Customer identify
-----------	-----------------------------------

8.37.3 Member Function Documentation

8.37.3.1 QVariantHash Models::Customer::getDataMap () [virtual]

[getDataMap](#) Get all data of model with a HashMap key/value

Returns

Model's data

Implements [Models::IModel](#).

8.37.3.2 QString Models::Customer::getNameFolder () const

[Customer::getNameFolder](#) Return the name of the current [Customer](#)'s folder in the workspace.

Returns

name of the [Customer](#)'s folder

8.37.3.3 QString Models::Customer::getPath () const

[Customer::getPath](#) Return the path of the workspace for the current [Customer](#).

Returns

workspace path

8.37.3.4 double Models::Customer::getTurnover () const

[Customer::getTurnover](#) Return the turnover of the customer money that customer pay, revenue sales.

Returns

turnover

8.37.3.5 void Models::Customer::hydrat (int *id*) [virtual]

[Customer::hydrat](#) Insert into database informations related to the [Customer](#) who is specified by *id*

Parameters

<i>id</i>	Customer identify
-----------	-----------------------------------

Implements [Models::IModel](#).

The documentation for this class was generated from the following files:


- /home/travis/build/FACT-Team/FactDev/src/models/customer.h
- /home/travis/build/FACT-Team/FactDev/src/models/customer.cpp

8.38 Gui::Widgets::CustomerContextualMenu Class Reference

Display contextual menu on a customer.

```
#include <customercontextualmenu.h>
```

Inheritance diagram for Gui::Widgets::CustomerContextualMenu:



Public Member Functions

- [CustomerContextualMenu](#) (QWidget *w=0)
CustomerContextualMenu::CustomerContextualMenu Construct a new contextual menu.
- [~CustomerContextualMenu](#) ()
CustomerContextualMenu::Destruct the contextual menu.

8.38.1 Detailed Description

Display contextual menu on a customer.

Author

Antoine de Roquemaurel

8.38.2 Constructor & Destructor Documentation

8.38.2.1 Gui::Widgets::CustomerContextualMenu::CustomerContextualMenu (QWidget * w = 0)

[CustomerContextualMenu::CustomerContextualMenu](#) Construct a new contextual menu.

Parameters

<i>w</i>	Parent
----------	--------

The documentation for this class was generated from the following files:


- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/customercontextualmenu.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/customercontextualmenu.cpp

8.39 Databases::CustomerDatabase Class Reference

The **CustomerDatabase** class Customer table database.

```
#include <customerdatabase.h>
```

Inheritance diagram for Databases::CustomerDatabase:



Public Member Functions

- **WdgModels::CustomersTableModel * getCustomersTable** (QString filter="") throw (DbException*)
CustomerDatabase::getCustomersTable Return an item model of customers for QTableView.
- **QStandardItemModel * getTree** (QString filter="") throw (DbException*)
CustomerDatabase::getTree Return an item model of customers for QTree.
- **QSharedPointer< Models::Customer > getCustomer** (const int pld)
CustomerDatabase::getCustomer get informations about the customer identified by pld
- **int addCustomer** (const **Models::Customer** &)
CustomerDatabase::addCustomer Add the customer pCustomer to the database.
- **void updateCustomer** (**Customer** &)
CustomerDatabase::updateCustomer Update informations about the customer pCustomer
- **void removeCustomer** (const int pld)
CustomerDatabase::removeCustomer Remove the customer with the id pld
- **int getNbCustomers** ()
CustomerDatabase::getNbCustomers Return the number of customers existing.
- **QStandardItem * getItemRoot** ()
CustomerDatabase::getItemRoot Return the first item for the QStandardItemModel.
- **QStandardItem * getItemCustomer** (QString query q1)
CustomerDatabase::getItemCustomer Return the customer item for the QStandardItemModel.
- **QStandardItem * getItemProject** (QString query q2)
CustomerDatabase::getItemProject Return the project item for the QStandardItemModel.
- **QSharedPointer< Models::Customer > getCustomer** (QString query &q)
CustomerDatabase::getCustomer Add the element of the q request and return their.
- **void updateCustomer** (QString query &q, **Customer** &pCustomer)
CustomerDatabase::updateCustomer Update customer data according to the request q
- **QList< Customer > getCustomers** ()
CustomerDatabase::getCustomers Return all the customers.

Static Public Member Functions

- **static CustomerDatabase * instance** () throw (DbException*)
CustomerDatabase::instance Return an instance of **CustomerDatabase**

Additional Inherited Members

8.39.1 Detailed Description

The [CustomerDatabase](#) class Customer table database.

Author

Antoine de Roquemaurel
Manantsoa Razanajatovo
Florent Berbie

See Also

[Database](#)
[Customer](#)

8.39.2 Member Function Documentation

8.39.2.1 `int Databases::CustomerDatabase::addCustomer (const Models::Customer & pCustomer)`

[CustomerDatabase::addCustomer](#) Add the customer *pCustomer* to the database.

Returns

customer id

8.39.2.2 `QSharedPointer< Models::Customer > Databases::CustomerDatabase::getCustomer (const int pld)`

[CustomerDatabase::getCustomer](#) get informations about the customer identified by *pld*

Parameters

<i>pld</i>	customer id
------------	-------------

Returns

the Customer

8.39.2.3 `QSharedPointer< Models::Customer > Databases::CustomerDatabase::getCustomer (QSqlQuery & q)`

[CustomerDatabase::getCustomer](#) Add the element of the *q* request and return their.

Parameters

<i>q</i>	SQL request
----------	-------------

Returns

a customer formed according to QSharedPointer

8.39.2.4 `QList< Customer > Databases::CustomerDatabase::getCustomers ()`

[CustomerDatabase::getCustomers](#) Return all the customers.

Returns

QList of customers

8.39.2.5 **WdgModels::CustomersTableModel** * **Databases::CustomerDatabase::getCustomersTable** (**QString** *filter* = " "
) throw **DbException** *)

[CustomerDatabase::getCustomersTable](#) Return an item model of customers for QTableView.

Parameters

<i>filter</i>	Select only customers who are specified by <i>filter</i>
---------------	--

Exceptions

<i>DbException</i>	
--------------------	--

Returns

QStandardItemModel an item model for QTableView

8.39.2.6 QStandardItem * Databases::CustomerDatabase::getItemCustomer (QSqlQuery *q1*)

[CustomerDatabase::getItemCustomer](#) Return the customer item for the QStandardItemModel.

Parameters

<i>q1</i>	the row of the sql query for customers
-----------	--

Returns

QStandardItem an item for QTree (level/depth 1)

8.39.2.7 QStandardItem * Databases::CustomerDatabase::getItemProject (QSqlQuery *q2*)

[CustomerDatabase::getItemProject](#) Return the project item for the QStandardItemModel.

Parameters

<i>q2</i>	the row of the sql query for projects
-----------	---------------------------------------

Returns

QStandardItem an item for QTree (level/depth 2)

8.39.2.8 QStandardItem * Databases::CustomerDatabase::getItemRoot ()

[CustomerDatabase::getItemRoot](#) Return the first item for the QStandardItemModel.

Returns

QStandardItem an item for QTree (level/depth 0)

8.39.2.9 int Databases::CustomerDatabase::getNbCustomers ()

[CustomerDatabase::getNbCustomers](#) Return the number of customers existing.

Returns

number of customers

8.39.2.10 QStandardItemModel * Databases::CustomerDatabase::getTree (QString *filter* = " ") throw DbException *)

[CustomerDatabase::getTree](#) Return an item model of customers for QTree.

Parameters

<i>filter</i>	Select only customers who are specified by <i>filter</i>
---------------	--

Exceptions

<i>DbException</i>	
--------------------	--

Returns

QStandardItemModel an item model for QTreeView

8.39.2.11 **CustomerDatabase * Databases::CustomerDatabase::instance () throw DbException *** [static]

[CustomerDatabase::instance](#) Return an instance of [CustomerDatabase](#)

See Also

[DbException](#)

Returns

Instance of [CustomerDatabase](#)

8.39.2.12 **void Databases::CustomerDatabase::removeCustomer (const int *pld*)**

[CustomerDatabase::removeCustomer](#) Remove the customer with the id *pld*

Parameters

<i>pld</i>	customer id
------------	-------------

8.39.2.13 **void Databases::CustomerDatabase::updateCustomer (QSqlQuery & *q*, Customer & *pCustomer*)**

[CustomerDatabase::updateCustomer](#) Update customer data according to the request *q*

Parameters


<i>q</i>	SQL request
----------	-------------

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/database/customerdatabase.h
- /home/travis/build/FACT-Team/FactDev/src/database/customerdatabase.cpp

8.40 CustomerDatabaseTest Class Reference

Inheritance diagram for CustomerDatabaseTest:



The documentation for this class was generated from the following files:


- /home/travis/build/FACT-Team/FactDev/tests/database/customerdatabasetest.h
- /home/travis/build/FACT-Team/FactDev/tests/database/customerdatabasetest.cpp

8.41 Gui::Widgets::CustomerDataWidget Class Reference

Class for display info of a customer.

```
#include <customerdatawidget.h>
```

Inheritance diagram for Gui::Widgets::CustomerDataWidget:



Public Member Functions

- [CustomerDataWidget](#) (QWidget *parent=0)
[CustomerDataWidget::CustomerDataWidget](#) Construct a [CustomerDataWidget](#).
- void [printUserData](#) ()
[CustomerDataWidget::printUserData](#) Print Data of current user.
- void [printInformations](#) (int id)
[CustomerDataWidget::printInformations](#) Print Data of customer id.

8.41.1 Detailed Description

Class for display info of a customer.

Author

8.41.2 Constructor & Destructor Documentation

8.41.2.1 [Gui::Widgets::CustomerDataWidget::CustomerDataWidget \(QWidget * parent = 0 \)](#) [explicit]

[CustomerDataWidget::CustomerDataWidget](#) Construct a [CustomerDataWidget](#).

Parameters

<i>parent</i>	Widget parent
---------------	---------------

8.41.3 Member Function Documentation

8.41.3.1 void [Gui::Widgets::CustomerDataWidget::printInformations \(int id \)](#)

[CustomerDataWidget::printInformations](#) Print Data of customer id.

Parameters


<i>id</i>	of customer to print
-----------	----------------------

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/customerdatawidget.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/customerdatawidget.cpp

8.42 CustomerModelTest Class Reference

Inheritance diagram for CustomerModelTest:



Public Member Functions

- void **setup** ()

The documentation for this class was generated from the following files:


- /home/travis/build/FACT-Team/FactDev/tests/models/customermodeltest.h
- /home/travis/build/FACT-Team/FactDev/tests/models/customermodeltest.cpp

8.43 Gui::Widgets::WdgModels::CustomersTableModel Class Reference

The [CustomersTableModel](#) class for a customer table.

```
#include <customerstablemodel.h>
```

Inheritance diagram for Gui::Widgets::WdgModels::CustomersTableModel:



Public Member Functions

- [CustomersTableModel](#) (QObject *parent=0)
[CustomersTableModel::CustomersTableModel](#) Construct a [CustomersTableModel](#).
- int [rowCount](#) (const QModelIndex &) const
[CustomersTableModel::rowCount](#) Number of customers row.
- int [columnCount](#) (const QModelIndex &) const
[CustomersTableModel::columnCount](#) Number of column of a customer.
- QVariant [data](#) (const QModelIndex &index, int role=Qt::DisplayRole) const
[CustomersTableModel::data](#) Obtains data of a specify cell.

- QVariant [headerData](#) (int section, Qt::Orientation orientation, int role=Qt::DisplayRole) const
CustomersTableModel::headerData Obtains header title of table.
- bool [setData](#) (const QModelIndex &index, const QVariant &value, int role=Qt::EditRole)
CustomersTableModel::setData Change data of a cell.
- void [append](#) (const [Customer](#) &customer)
CustomersTableModel::append Add a new line in table.
- void [remove](#) (const int i)
CustomersTableModel::remove Remove a line.
- Qt::ItemFlags [flags](#) (const QModelIndex &index) const
CustomersTableModel::flags Differents table flags.
- int [count](#) ()
CustomersTableModel::count Number of customers in table.
- QList< [Customer](#) > [getCustomers](#) () const
CustomersTableModel::getCustomers Return the list of customers.

8.43.1 Detailed Description

The [CustomersTableModel](#) class for a customer table.

Author

Florent Berbie

See Also

[Customer](#)

8.43.2 Constructor & Destructor Documentation

8.43.2.1 Gui::Widgets::WdgModels::CustomersTableModel::CustomersTableModel (QObject * *parent* = 0)

[CustomersTableModel::CustomersTableModel](#) Construct a [CustomersTableModel](#).

Parameters

<i>parent</i>	Parent widget
---------------	---------------

8.43.3 Member Function Documentation

8.43.3.1 void Gui::Widgets::WdgModels::CustomersTableModel::append (const [Customer](#) & *customer*)

[CustomersTableModel::append](#) Add a new line in table.

Parameters

<i>Customer</i>	The new customer
-----------------	------------------

8.43.3.2 int Gui::Widgets::WdgModels::CustomersTableModel::columnCount (const QModelIndex &) const

[CustomersTableModel::columnCount](#) Number of column of a customer.

Returns

The number of column

8.43.3.3 `int Gui::Widgets::WdgModels::CustomersTableModel::count ()`

[CustomersTableModel::count](#) Number of customers in table.

Returns

The number of customers

8.43.3.4 `QVariant Gui::Widgets::WdgModels::CustomersTableModel::data (const QModelIndex & index, int role = Qt::DisplayRole) const`

[CustomersTableModel::data](#) Obtains data of a specify cell.

Parameters

<i>index</i>	The cell who we want data
<i>role</i>	The role of set

Returns

The data of cell

8.43.3.5 `Qt::ItemFlags Gui::Widgets::WdgModels::CustomersTableModel::flags (const QModelIndex & index) const`

[CustomersTableModel::flags](#) Differents table flags.

Parameters

<i>index</i>	The cell who we want to know flags
--------------	------------------------------------

Returns

Flags

8.43.3.6 `QList< Customer > Gui::Widgets::WdgModels::CustomersTableModel::getCustomers () const`

[CustomersTableModel::getCustomers](#) Return the list of customers.

Returns

list of Customers

8.43.3.7 `QVariant Gui::Widgets::WdgModels::CustomersTableModel::headerData (int section, Qt::Orientation orientation, int role = Qt::DisplayRole) const`

[CustomersTableModel::headerData](#) Obtains header title of table.

Parameters

<i>section</i>	The number of column
<i>orientation</i>	The table orientation

<i>role</i>	
-------------	--

Returns

The Title header of column

8.43.3.8 void Gui::Widgets::WdgModels::CustomersTableModel::remove (const int *i*)

[CustomersTableModel::remove](#) Remove a line.

Parameters

<i>i</i>	The number of line to remove
----------	------------------------------

8.43.3.9 int Gui::Widgets::WdgModels::CustomersTableModel::rowCount (const QModelIndex &) const

[CustomersTableModel::rowCount](#) Number of customers row.

Returns

The number of customers

8.43.3.10 bool Gui::Widgets::WdgModels::CustomersTableModel::setData (const QModelIndex & *index*, const QVariant & *value*, int *role* = Qt::EditRole)

[CustomersTableModel::setData](#) Change data of a cell.

Parameters

<i>index</i>	The cell to change data
<i>value</i>	The new value
<i>role</i>	The role of cell

Returns

True if we could edit

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/widgetsmodels/customerstablemodel.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/widgetsmodels/customerstablemodel.cpp

8.44 Databases::Database Class Reference

The [Database](#) class Master class for all database access.

```
#include <database.h>
```

Inheritance diagram for Databases::Database:



Public Member Functions

- QString [lastError](#) (const QSqlQuery &q) const
Database::lastError Return an error message on the last error occurred during the SQL request q
- void [testCases](#) ()
Database::testCases Realise a test cases.
- void [executeFile](#) (QString pName)
Database::executerFichier Exeute a specified file named pName
- void [openTransaction](#) ()
Database::openTransaction Open new transaction.
- void [closeTransaction](#) ()
Database::closeTransaction Close current transaction.
- void [close](#) ()
Database::close Close database access.
- void [open](#) ()
Database::open Open database.
- [~Database](#) ()
Database::~Database Suppression object, and close database access.
- void [setDatabase](#) (QSqlDatabase sql)
Database::setDatabase Set database.
- void [updateBillingNumber](#) ()
Database::updateBillingNumber Update the billing number.
- void [cleanDatabase](#) ()
Database::clearDatabase Drop alls tables of [Database](#) WARNING: We can't restore data after.
- void [changeDatabase](#) (Databases::DbType dbType)
changeDatabase Change the current database : mysql to sqlite or sqlite to mysql

Static Public Member Functions

- static [Database](#) * [instance](#) (bool tests=false) throw (DbException*)
Database::getInstance Return an instance of [Database](#).

Protected Member Functions

- [Database](#) (bool tests=false) throw (DbException*)
Database::Database [Database](#) is a singleton.
- QVariant [value](#) (const QSqlQuery &q, const QString &champ) const
Database::valeur Value of database field.

Protected Attributes

- QSettings * [_settings](#)
settings
- QSqlDatabase [mDatabase](#)
contains Database
- QList< [Database](#) * > [_instances](#)
List of instances.

Static Protected Attributes

- static [Database](#) * `_instance` = 0
Instance.
- static bool `_dbInstance` = 0
an instance of db is open
- static bool `isOpen` = false
[Database](#) is open.
- static bool `_isMysql` = false

8.44.1 Detailed Description

The [Database](#) class Master class for all database access.

Author

Antoine de Roquemaurel

8.44.2 Member Function Documentation

8.44.2.1 void `Databases::Database::changeDatabase (Databases::DbType dbType)`

`changeDatabase` Change the current database : mysql to sqlite or sqlite to mysql

Parameters

<i>dbType</i>	: The new database type, Sqlite or Mysql
---------------	--

8.44.2.2 void `Databases::Database::executeFile (QString pName)`

`Database::executerFichier` Exeute a specified file named *pName*

Parameters

<i>pNom</i>	File name
-------------	-----------

8.44.2.3 `Database * Databases::Database::instance (bool tests = false) throw DbException *` [static]

`Database::getInstance` Return an instance of [Database](#).

Returns

Instance of [Database](#)

8.44.2.4 `QString Databases::Database::lastError (const QSqlQuery & q) const` [inline]

`Database::lastError` Return an error message on the last error occurred during the SQL request *q*

Parameters

<i>q</i>	SQL request
----------	-------------

Returns

an error message

8.44.2.5 void Databases::Database::setDatabase (QSqlDatabase *sql*)

[Database::setDatabase](#) Set database.

Parameters

<i>sql</i>	The new database
------------	------------------

8.44.2.6 QVariant Databases::Database::value (const QSqlQuery & *q*, const QString & *champ*) const [protected]

Database::valeur Value of database field.

Parameters

<i>q</i>	Query
<i>champ</i>	Field

Returns

The value

The documentation for this class was generated from the following files:


- /home/travis/build/FACT-Team/FactDev/src/database/database.h
- /home/travis/build/FACT-Team/FactDev/src/database/database.cpp

8.45 Gui::Widgets::DatabaseSettingsWidget Class Reference

The [DatabaseSettingsWidget](#) class Windows of database settings.

```
#include <databasesettingswidget.h>
```

Inheritance diagram for Gui::Widgets::DatabaseSettingsWidget:

**Public Slots**

- bool [isValid](#) ()
DatabaseSettingsWidget::isValid Return TRUE if all fields are correctly inputed else FALSE.
- void [checkRepeatPassword](#) (QString text)
DatabaseSettingsWidget::checkRepeatLogin Check if the second login field is the same than the first.
- void [userInterfaceChanged](#) ()
DatabaseSettingsWidget::userInterfaceChanged User interface has changed.

Signals

- void [textfieldChanged](#) ()
DatabaseSettingsWidget::textfieldChanged Signal which indicates if a fieldtext has changed.

Public Member Functions

- [DatabaseSettingsWidget](#) (QWidget *parent=0)
DatabaseSettingsWidget::DatabaseSettingsWidget Construct a [DatabaseSettingsWidget](#).
- void [fillFields](#) ()
DatabaseSettingsWidget::fillFields Complete fields with a default value for field Database name, Username, IP address and port.
- QString [getDatabaseName](#) ()
DatabaseSettingsWidget::getDatabaseName Return the database name.
- QString [getLogin](#) ()
DatabaseSettingsWidget::getLogin Return the login of the user.
- QString [getPassword](#) ()
DatabaseSettingsWidget::getPassword Return the password of the user.
- QString [getDomainNameOrIP](#) ()
DatabaseSettingsWidget::getDomainNameOrIP Return the domain name or IP address on the machine where is the database.
- QString [getPort](#) ()
DatabaseSettingsWidget::getPort Return the port of the database.

8.45.1 Detailed Description

The [DatabaseSettingsWidget](#) class Windows of database settings.

Author

8.45.2 Constructor & Destructor Documentation

8.45.2.1 [Gui::Widgets::DatabaseSettingsWidget::DatabaseSettingsWidget](#) ([QWidget](#) * *parent* = 0) [explicit]

[DatabaseSettingsWidget::DatabaseSettingsWidget](#) Construct a [DatabaseSettingsWidget](#).

Parameters

<i>parent</i>	Parent widget of this windows
---------------	-------------------------------

8.45.3 Member Function Documentation

8.45.3.1 [QString](#) [Gui::Widgets::DatabaseSettingsWidget::getDatabaseName](#) ()

[DatabaseSettingsWidget::getDatabaseName](#) Return the database name.

Returns

Database name

8.45.3.2 QString Gui::Widgets::DatabaseSettingsWidget::getDomainNameOrIP ()

[DatabaseSettingsWidget::getDomainNameOrIP](#) Return the domain name or IP address on the machine where is the database.

Returns

Domain name or IP address

8.45.3.3 QString Gui::Widgets::DatabaseSettingsWidget::getLogin ()

[DatabaseSettingsWidget::getLogin](#) Return the login of the user.

Returns

Login of the user

8.45.3.4 QString Gui::Widgets::DatabaseSettingsWidget::getPassword ()

[DatabaseSettingsWidget::getPassword](#) Return the password of the user.

Returns

User password

8.45.3.5 QString Gui::Widgets::DatabaseSettingsWidget::getPort ()

[DatabaseSettingsWidget::getPort](#) Return the port of the database.

Returns

Database port

8.45.3.6 bool Gui::Widgets::DatabaseSettingsWidget::isValid () [slot]

[DatabaseSettingsWidget::isValid](#) Return TRUE if all fields are correctly inputed else FALSE.

Returns

boolean

The documentation for this class was generated from the following files:


- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/databasesettingswidget.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/databasesettingswidget.cpp

8.46 Exceptions::DbException Class Reference

The [DbException](#) class for database exception : queries, db file, ...

```
#include <dbexception.h>
```

Inheritance diagram for Exceptions::DbException:



Public Member Functions

- [DbException](#) (const QString fct, const QString fctName, const QString logError, float errorCode)
[DbException::DbException](#). Construct a [DbException](#).
- virtual [~DbException](#) () throw ()
[~DbException](#)
- void [popupMessage](#) (QWidget *parent)
[DbException::popupMessage](#). Display a popup message with the message error.

8.46.1 Detailed Description

The [DbException](#) class for database exception : queries, db file, ...

Author

Antoine de Roquemaurel

8.46.2 Constructor & Destructor Documentation

8.46.2.1 [Exceptions::DbException::DbException](#) (const QString *fct*, const QString *fctName*, const QString *logError*, float *errorCode*)

[DbException::DbException](#). Construct a [DbException](#).

Parameters

<i>userError</i>	ClassName of error
<i>fctName</i>	Function name
<i>logError</i>	Message error
<i>errorCode</i>	Code of error

8.46.3 Member Function Documentation

8.46.3.1 void [Exceptions::DbException::popupMessage](#) (QWidget * *parent*)

[DbException::popupMessage](#). Display a popup message with the message error.

Parameters

<i>parent</i>	
---------------	--

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/exceptions/dbexception.h
- /home/travis/build/FACT-Team/FactDev/src/exceptions/dbexception.cpp

8.47 Gui::Dialogs::DialogAddCustomer Class Reference

The [DialogAddCustomer](#) class Window to add or modify a Customer.

```
#include <dialogaddcustomer.h>
```

Inheritance diagram for Gui::Dialogs::DialogAddCustomer:



Public Slots

- void [checkFields](#) ()
[DialogAddCustomer::checkFields](#) Check if fields are valid.

Public Member Functions

- [DialogAddCustomer](#) (int id=0, QWidget *parent=0)
[DialogAddCustomer::DialogAddCustomer](#) Construct a window to add/modify a Customer.
- void [fillFields](#) ()
[DialogAddCustomer::fillFields](#) If the Customer exists, fill line edits with the data of the current Customer.
- void [accept](#) ()
[DialogAddCustomer::accept](#) Valid data inputed by user and add these data in Database.
- void [reject](#) ()
[DialogAddCustomer::reject](#) Cancel the operation and close the windows.

8.47.1 Detailed Description

The [DialogAddCustomer](#) class Window to add or modify a Customer.

Author

8.47.2 Constructor & Destructor Documentation

8.47.2.1 [Gui::Dialogs::DialogAddCustomer::DialogAddCustomer](#) (int *id* = 0, QWidget * *parent* = 0) [explicit]

[DialogAddCustomer::DialogAddCustomer](#) Construct a window to add/modify a Customer.

Parameters

<i>id</i>	Customer id
<i>parent</i>	QWidget parent

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/dialogs/dialogaddcustomer.h
- /home/travis/build/FACT-Team/FactDev/src/gui/dialogs/dialogaddcustomer.cpp

8.48 Utils::Directories Class Reference

Static Public Member Functions

- static QString [makeDirectory](#) (QDir &directory, const QString path, const QString folder) throw (Exceptions::FileException*)

MainWindow::makeDirectory If not exists make a new directory folder

8.48.1 Member Function Documentation

8.48.1.1 QString Utils::Directories::makeDirectory (QDir &directory, const QString path, const QString folder) throw Exceptions::FileException *) [static]

MainWindow::makeDirectory If not exists make a new directory *folder*

Parameters

<i>path</i>	Return the path of the folder just created
<i>folder</i>	Folder name to create

Returns

Path of the folder just created

The documentation for this class was generated from the following files:


- /home/travis/build/FACT-Team/FactDev/src/Utils/directories.h
- /home/travis/build/FACT-Team/FactDev/src/Utils/directories.cpp

8.49 Gui::Widgets::Delegates::DoubleSpinBoxDelegate Class Reference

The [DoubleSpinBoxDelegate](#) class.

```
#include <doublespinboxdelegate.h>
```

Inheritance diagram for Gui::Widgets::Delegates::DoubleSpinBoxDelegate:



Public Member Functions

- [DoubleSpinBoxDelegate](#) (QObject *parent=0)
DoubleSpinBoxDelegate::DoubleSpinBoxDelegate.
- QWidget * [createEditor](#) (QWidget *parent, const QStyleOptionViewItem &option, const QModelIndex &index) const
DoubleSpinBoxDelegate::createEditor Return a ComboBox specified by index item defined by the parent widget and style option which are used to control how the editor widgets appears.
- void [setEditorData](#) (QWidget *editor, const QModelIndex &index) const
DoubleSpinBoxDelegate::setEditorData Sets the data to be displayed and edited by the editor from the data model item specified by the model index

- void [setModelData](#) (QWidget *editor, QAbstractItemModel *model, const QModelIndex &index) const
[DoubleSpinBoxDelegate::setEditorData](#) Sets the data to be displayed and edited by the editor from the data model item specified by the model index
- void [updateEditorGeometry](#) (QWidget *editor, const QStyleOptionViewItem &option, const QModelIndex &index) const
[DoubleSpinBoxDelegate::updateEditorGeometry](#) Update the editor for the item specified by index according to the style option given.

8.49.1 Detailed Description

The [DoubleSpinBoxDelegate](#) class.

Author

Florent Berbie

8.49.2 Constructor & Destructor Documentation

8.49.2.1 `Gui::Widgets::Delegates::DoubleSpinBoxDelegate::DoubleSpinBoxDelegate (QObject * parent = 0)`

[DoubleSpinBoxDelegate::DoubleSpinBoxDelegate](#).

Parameters

<i>parent</i>	
---------------	--

8.49.3 Member Function Documentation

8.49.3.1 `QWidget * Gui::Widgets::Delegates::DoubleSpinBoxDelegate::createEditor (QWidget * parent, const QStyleOptionViewItem & option, const QModelIndex & index) const`

[DoubleSpinBoxDelegate::createEditor](#) Return a ComboBox specified by *index* item defined by the *parent* widget and style *option* which are used to control how the editor widgets appears.

Parameters

<i>parent</i>	Widget parent
<i>option</i>	Option style
<i>index</i>	Index for editing

Returns

[DoubleSpinBoxDelegate](#)

8.49.3.2 `void Gui::Widgets::Delegates::DoubleSpinBoxDelegate::setEditorData (QWidget * editor, const QModelIndex & index) const`

[DoubleSpinBoxDelegate::setEditorData](#) Sets the data to be displayed and edited by the *editor* from the data model item specified by the model *index*

Parameters

<i>editor</i>	Data edited
<i>index</i>	Index of the model to edit

8.49.3.3 void Gui::Widgets::Delegates::DoubleSpinBoxDelegate::setModelData (QWidget * *editor*, QAbstractItemModel * *model*, const QModelIndex & *index*) const

[DoubleSpinBoxDelegate::setEditorData](#) Sets the data to be displayed and edited by the *editor* from the data model item specified by the model *index*

Parameters

<i>editor</i>	Data edited
<i>index</i>	Index of the model to edit

8.49.3.4 void Gui::Widgets::Delegates::DoubleSpinBoxDelegate::updateEditorGeometry (QWidget * *editor*, const QStyleOptionViewItem & *option*, const QModelIndex & *index*) const

[DoubleSpinBoxDelegate::updateEditorGeometry](#) Update the *editor* for the item specified by *index* according to the style *option* given.

Parameters

<i>editor</i>	Editor widget to update
<i>option</i>	Style option
<i>index</i>	Item index

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/delegates/doublespinboxdelegate.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/delegates/doublespinboxdelegate.cpp

8.50 Exceptions::FileException Class Reference

The [FileException](#) class for file/acess file exception.

```
#include <fileexception.h>
```

Public Member Functions

- [FileException](#) (const QString userError, const QString fctName, const QString logError, float errorCode)
FileException::FileException. Construct a [FileException](#).
- void [popupMessage](#) (QWidget *parent)
FileException::popupMessage. Display a popup message with the message error.

8.50.1 Detailed Description

The [FileException](#) class for file/acess file exception.

Author

Florent Berbie

8.50.2 Constructor & Destructor Documentation

8.50.2.1 Exceptions::FileException::FileException (const QString *userError*, const QString *fctName*, const QString *logError*, float *errorCode*)

[FileException::FileException](#). Construct a [FileException](#).

Parameters

<i>userError</i>	ClassName of error
<i>fctName</i>	Function name
<i>logError</i>	Message error
<i>errorCode</i>	Code of error

8.50.3 Member Function Documentation

8.50.3.1 void Exceptions::FileException::popupMessage (QWidget * *parent*)

[FileException::popupMessage](#). Display a popup message with the message error.

Parameters

<i>parent</i>	
---------------	--

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/exceptions/fileexception.h
- /home/travis/build/FACT-Team/FactDev/src/exceptions/fileexception.cpp

8.51 Generation Class Reference

Inheritance diagram for Generation:



The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/tests/generation.h
- /home/travis/build/FACT-Team/FactDev/tests/generation.cpp

8.52 Utils::HierarchicalSystem Class Reference

The [HierarchicalSystem](#) class Create class which contains hierarchical system of FactDev.

```
#include <hierarchichalsystem.h>
```

Public Member Functions

- [HierarchicalSystem](#) ()
HierarchicalSystem::HierarchicalSystem Construct a *HierarchicalSystem*.
- void [getAllProjects](#) ()
HierarchicalSystem::getAllProjects Get all projects and add each project to Customer linked.
- void [getAllBillings](#) ()
HierarchicalSystem::getAllBillings Get all billings and add each billing to Project linked.
- void [updateData](#) ()

- [*HierarchicalSystem::updateData*](#) Update data on Customers, Projects, Billings.
- void [*addProjectToCustomer*](#) ([Project *p](#), [Customer c](#))
[*HierarchicalSystem::addProjectToCustomer*](#) Add the Project *p* to the Customer *c*
- void [*addBillingToProject*](#) ([Billing *b](#), [Project *p](#))
[*HierarchicalSystem::addBillingToProject*](#) Add the Billing *b* to the Project *p*
- QMap< [Project *](#), [Customer](#) > [*getCustomers*](#) () const
[*HierarchicalSystem::getCustomers*](#) Return all customers and these projects linked.
- QMap< [Billing *](#), [Project *](#) > [*getProjects*](#) () const
[*HierarchicalSystem::getProjects*](#) Return all projects and these billing linked.

8.52.1 Detailed Description

The [HierarchicalSystem](#) class Create class which contains hierarchical system of FactDev.

Author

Florent Berbie

See Also

Customer
Project
Billing

8.52.2 Member Function Documentation

8.52.2.1 void Utils::HierarchicalSystem::addBillingToProject ([Billing * b](#), [Project * p](#))

[*HierarchicalSystem::addBillingToProject*](#) Add the Billing *b* to the Project *p*

Parameters

<i>b</i>	Billing
<i>p</i>	Project

8.52.2.2 void Utils::HierarchicalSystem::addProjectToCustomer ([Project * p](#), [Customer c](#))

[*HierarchicalSystem::addProjectToCustomer*](#) Add the Project *p* to the Customer *c*

Parameters

<i>p</i>	Project
<i>c</i>	Customer

8.52.2.3 QMap< [Project *](#), [Customer](#) > Utils::HierarchicalSystem::getCustomers () const

[*HierarchicalSystem::getCustomers*](#) Return all customers and these projects linked.

Returns

Projects linked to Customers

8.52.2.4 QMap< Billing *, Project * > Utils::HierarchicalSystem::getProjects (void) const

[HierarchicalSystem::getProjects](#) Return all projects and these billing linked.

Returns

Billing linked to Projects

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/utls/hierarchichalsystem.h
- /home/travis/build/FACT-Team/FactDev/src/utls/hierarchichalsystem.cpp

8.53 Gui::Widgets::CheckFields::ICheckField Class Reference

The [ICheckField](#) class Interface to check fields validity.

```
#include <icheckfield.h>
```

Inheritance diagram for Gui::Widgets::CheckFields::ICheckField:



Public Member Functions

- virtual bool [check](#) (QString text)=0
[ICheckField::check](#) Check if the field (line edit) is valid Return TRUE if the field is valid, else FALSE.

8.53.1 Detailed Description

The [ICheckField](#) class Interface to check fields validity.

8.53.2 Member Function Documentation

8.53.2.1 virtual bool Gui::Widgets::CheckFields::ICheckField::check (QString text) [pure virtual]

[ICheckField::check](#) Check if the field (line edit) is valid Return TRUE if the field is valid, else FALSE.

Returns

boolean Validity of the text

Implemented in [Gui::Widgets::CheckFields::CheckEmail](#), [Gui::Widgets::CheckFields::CheckPortNumber](#), [Gui::Widgets::CheckFields::CheckFieldsNumbers](#), [Gui::Widgets::CheckFields::CheckIpAddress](#), [Gui::Widgets::CheckFields::CheckLogin](#), [Gui::Widgets::CheckFields::CheckPhone](#), [Gui::Widgets::CheckFields::CheckPostalCode](#), [Gui::Widgets::CheckFields::CheckSiretNumber](#), [Gui::Widgets::CheckFields::CheckUntilField](#), [Gui::Widgets::CheckFields::CheckFieldsLetters](#), and [Gui::Widgets::CheckFields::CheckValidField](#).

The documentation for this class was generated from the following file:

- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/icheckfield.h

8.54 Models::IModel Class Reference

The [IModel](#) class.

```
#include <imodel.h>
```

Inheritance diagram for Models::IModel:



Public Member Functions

- virtual [~IModel](#) ()
~IModel Remove an instance of [IModel](#)
- virtual void [commit](#) ()=0
[IModel::commit](#) Update or insert data into the database.
- virtual void [hydrat](#) (int id)=0
[IModel::hydrat](#) Get data of the element which is specified by the identify id from the database.
- virtual void [remove](#) ()=0
[IModel::remove](#) Remove the current element in the database.
- virtual QVariantHash [getDataMap](#) ()=0
[getDataMap](#) Get all data of model with a HashMap key/value
- int [getId](#) () const
[IModel::getId](#) Return the identify of the element of the database.
- void [setId](#) (int id)
[IModel::setId](#) Replace the current identify by id
- bool [isToRemoved](#) () const
[toRemoved](#) return if object must be removed.
- void [setToRemoved](#) (bool toRemoved)
[setToRemoved](#) Change the flag for removed object

Protected Attributes

- int [_id](#)
Element identify.
- bool [_toRemoved](#)
Flag to know if the object must be removed.

8.54.1 Detailed Description

The [IModel](#) class.

Author

Antoine de Roquemaurel

8.54.2 Member Function Documentation

8.54.2.1 `virtual QVariantHash Models::IModel::getDataMap () [pure virtual]`

getDataMap Get all data of model with a HashMap key/value

Returns

Model's data

Implemented in [Models::Billing](#), [Models::Project](#), [Models::User](#), [Models::Contributory](#), and [Models::Customer](#).

8.54.2.2 `int Models::IModel::getId () const [inline]`

[IModel::getId](#) Return the identify of the element of the database.

Returns

identity

8.54.2.3 `virtual void Models::IModel::hydrat (int id) [pure virtual]`

[IModel::hydrat](#) Get data of the element which is specified by the identify *id* from the database.

Parameters

<i>id</i>	
-----------	--

Implemented in [Models::Billing](#), [Models::Project](#), [Models::User](#), [Models::Contributory](#), and [Models::Customer](#).

8.54.2.4 `bool Models::IModel::isToRemoved () const [inline]`

toRemoved return if object must be removed.

Returns

boolean

8.54.2.5 `void Models::IModel::setId (int id) [inline]`

[IModel::setId](#) Replace the current identify by *id*

Parameters

<i>id</i>	New identify
-----------	--------------

8.54.2.6 `void Models::IModel::setToRemoved (bool toRemoved) [inline]`

setToRemoved Change the flag for removed object

Parameters

<i>toRemoved</i>	The new flag
------------------	--------------

The documentation for this class was generated from the following file:

- /home/travis/build/FACT-Team/FactDev/src/models/imodel.h

8.55 Utils::ItemType Class Reference

The [ItemType](#) class Item type model.

```
#include <itemtype.h>
```

Public Member Functions

- [ItemType](#) (int type, QString name)
ItemType::ItemType Construct an Item type.
- QString [getName](#) () const
ItemType::getName Get item name.
- [Models::IModel](#) * [getModel](#) (int id)
ItemType::getModel Get the databasemodel of the [ItemType](#) according to this identity id
- void [setName](#) (const QString &name)
ItemType::setName Modify the item name.
- int [getType](#) () const
ItemType::getType Get the type of the current item.
- void [setType](#) (int type)
ItemType::setType Modify the type of the current item.

Static Public Attributes

- static const int [CUSTOMER](#) = 0
constant value assigned to Customer
- static const int [PROJECT](#) = 1
constant value assigned to Project
- static const int [BILLING](#) = 2
constant value assigned to Billing
- static const int [QUOTE](#) = 3
constant value assigned to Quote

8.55.1 Detailed Description

The [ItemType](#) class Item type model.

8.55.2 Constructor & Destructor Documentation

8.55.2.1 Utils::ItemType::ItemType (int type, QString name)

[ItemType::ItemType](#) Construct an Item type.

Parameters

<i>type</i>	Type of the item
<i>name</i>	Name of the item

8.55.3 Member Function Documentation

8.55.3.1 Models::IModel * Utils::ItemType::getModel (int *id*)

[ItemType::getModel](#) Get the databasemodel of the [ItemType](#) according to this identity *id*

Parameters

<i>id</i>	Item type identity
-----------	--------------------

Returns

database model

8.55.3.2 QString Utils::ItemType::getName () const

[ItemType::getName](#) Get item name.

Returns

item name

8.55.3.3 int Utils::ItemType::getType () const

[ItemType::getType](#) Get the type of the current item.

Returns

type of the current item

8.55.3.4 void Utils::ItemType::setName (const QString & *name*)

[ItemType::setName](#) Modify the item name.

Parameters

<i>name</i>	New Item name
-------------	---------------

8.55.3.5 void Utils::ItemType::setType (int *type*)

[ItemType::setType](#) Modify the type of the current item.

Parameters

<i>type</i>	New item type
-------------	---------------

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/utils/itemtype.h
- /home/travis/build/FACT-Team/FactDev/src/utils/itemtype.cpp

8.56 ItemTypeTest Class Reference

Inheritance diagram for ItemTypeTest:



The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/tests/utils/itemtypetest.h
- /home/travis/build/FACT-Team/FactDev/tests/utils/itemtypetest.cpp

8.57 Utils::Log Class Reference

The [Log](#) class for Simple management of log.

```
#include <log.h>
```

Public Member Functions

- [~Log](#) ()
Log::~~Log.
- void [write](#) (const QString text)
Log::write. Write log message in file.
- [Log](#) ()
Log::Log. Log is a singleton.

Static Public Member Functions

- static [Log](#) & [instance](#) (TypeLog type=INFO)
Log::instance. Return the instance of logger.

Friends

- [Log](#) & [operator<<](#) ([Log](#) &logger, const QString &text)
operator << for log writing

8.57.1 Detailed Description

The [Log](#) class for Simple management of log.

8.57.2 Member Function Documentation

8.57.2.1 [Log](#) & [Utils::Log::instance](#) (TypeLog *type* = INFO) [static]

[Log::instance](#). Return the instance of logger.

Parameters

<i>type</i>	Type of log : WARNING, INFO, ERROR
-------------	------------------------------------

Returns

Instance of logger.

8.57.2.2 void Utils::Log::write (const QString text)

[Log::write](#). Write log message in file.

Parameters

<i>text</i>	
-------------	--

8.57.3 Friends And Related Function Documentation

8.57.3.1 Log& operator<< (Log & logger, const QString & text) [friend]

operator << for log writing

Parameters

<i>logger</i>	Instance of Logger
<i>text</i>	Text to write

Returns

New logger.

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/utils/log.h
- /home/travis/build/FACT-Team/FactDev/src/utils/log.cpp

8.58 Gui::MainWindow Class Reference

The [MainWindow](#) class Main Window of the software.

```
#include <mainwindow.h>
```

Inheritance diagram for Gui::MainWindow:



Public Slots

- void [addCustomer](#) ()
[MainWindow::addCustomer](#) open window to add a new customer.
- void [editCustomer](#) ()

- MainWindow::editCustomer* open window to modify a customer.

 - void `removeCustomer` ()

MainWindow::removeCustomer open a popup to confirm the deletion of a customer, if ok remove the customer.
- void `addQuote` ()

MainWindow::addQuote open window to add a new quote.
- void `addBill` ()

MainWindow::addBill open window to add a new bill.
- void `billingsIsPaid` ()

MainWindow::billingsIsPaid Define the current billing as "paid".
- void `editUser` ()

MainWindow::editUser modify the user.
- void `search` (QString s)

MainWindow::search launch a new search.
- void `addProject` ()

MainWindow::addProject Create a new project for a customer.
- void `removeProject` ()

MainWindow::removeProject Remove a project for a customer.
- void `editProject` ()

MainWindow::editProject Modify the customer project.
- void `aboutQt` ()

MainWindow::aboutQt show Qt's details.
- void `aboutFact` ()

MainWindow::aboutFact show FACT's details (FACT team)
- void `aboutFactDev` ()

MainWindow::aboutFactDev() show FactDev's details (FactDev Software)
- void `aboutIcons` ()

MainWindow::aboutIcons() show icons's details.
- void `updateButtons` ()

updateButton Update all button to disable or enabled its
- void `editDoc` ()

MainWindow::editDoc Edit the quote or bill of the project.
- void `removeDoc` ()

MainWindow::removeDoc Remove the quote or bill of the project.
- void `copyDoc` ()

MainWindow::copyDoc Copy all elements of a quote or a bill and Display these elements in a new quote or bill.
- void `openPdf` ()

MainWindow::openPdf Open the PDF file of the current Quote or Billing selected in the TableView.
- void `computeTurnover` ()

MainWindow::computeTurnover open window to allow computation of a period turnover.
- void `globalStatistics` ()

MainWindow::globalStatistics.
- void `customerStatistics` ()

MainWindow::customerStatistics.

Public Member Functions

- [MainWindow](#) (QWidget *parent=0)
MainWindow: Construct a window.
- int [getCurrentCustomerId](#) ()
MainWindow::getCurrentCustomerId get the selected customer.
- int [getCurrentProjectId](#) ()
MainWindow::getCurrentProjectId get the selected project id.
- int [getCurrentQuoteId](#) ()
MainWindow::getCurrentQuoteId get the selected quote id.
- QString [getCurrentCustomerName](#) ()
MainWindow::getCurrentCustomerName get the selected customer name in the customers' table.
- QString [getCurrentProjectName](#) ()
MainWindow::getCurrentProjectName get the selected project name in the table of projects.
- int [treeLevel](#) ()
MainWindow::treeLevel return the level of the node selected in the tree.
- QModelIndex [rootTree](#) ()
MainWindow::rootTree return the root of the tree "Tous les clients".
- void [addDoc](#) (bool isBilling)
MainWindow::addDoc open window to add a new document.
- void [resizeEvent](#) (QResizeEvent *event)
MainWindow::resizeEvent Resize central TableView when you resize the [MainWindow](#)
- void [responsiveCustomerTable](#) ()
MainWindow::responsiveCustomerTable Resize the Customer TableView according it resolution.
- void [responsiveProjectTable](#) ()
MainWindow::responsiveProjectTable Resize the Project TableView according it resolution.
- void [responsiveBillingTable](#) ()
MainWindow::responsiveBillingTable Resize the Billing TableView according it resolution.

8.58.1 Detailed Description

The [MainWindow](#) class Main Window of the software.

Author

Everybody

8.58.2 Constructor & Destructor Documentation

8.58.2.1 [Gui::MainWindow::MainWindow](#) ([QWidget](#) * *parent* = 0) [[explicit](#)]

[MainWindow](#): Construct a window.

Parameters

<i>parent</i>	
---------------	--

8.58.3 Member Function Documentation

8.58.3.1 void [Gui::MainWindow::addBill](#) () [[slot](#)]

[MainWindow::addBill](#) open window to add a new bill.

See Also

AddQuoteDialog

8.58.3.2 void Gui::MainWindow::addDoc (bool *isBilling*)

[MainWindow::addDoc](#) open window to add a new document.

Parameters

<i>bool</i>	quote or bill
-------------	---------------

See Also

[addBill](#) [addQuote](#)

8.58.3.3 void Gui::MainWindow::addProject () [slot]

[MainWindow::addProject](#) Create a new project for a customer.

See Also

AddProjectDialog

8.58.3.4 void Gui::MainWindow::addQuote () [slot]

[MainWindow::addQuote](#) open window to add a new quote.

See Also

AddQuoteDialog

8.58.3.5 void Gui::MainWindow::editUser () [slot]

[MainWindow::editUser](#) modify the user.

See Also

UserDataDialog

8.58.3.6 int Gui::MainWindow::getCurrentCustomerId ()

[MainWindow::getCurrentCustomerId](#) get the selected customer.

Returns

id of the selected customer

8.58.3.7 QString Gui::MainWindow::getCurrentCustomerName ()

[MainWindow::getCurrentCustomerName](#) get the selected customer name in the customers' table.

Returns

name of the selected customer

8.58.3.8 `int Gui::MainWindow::getCurrentProjectId ()`

[MainWindow::getCurrentProjectId](#) get the selected project id.

Returns

id of the selected project

8.58.3.9 `QString Gui::MainWindow::getCurrentProjectName ()`

[MainWindow::getCurrentProjectName](#) get the selected project name in the table of projects.

Returns

name of the selected project

8.58.3.10 `int Gui::MainWindow::getCurrentQuoteId ()`

[MainWindow::getCurrentQuoteId](#) get the selected quote id.

Returns

id of the selected quote

8.58.3.11 `void Gui::MainWindow::resizeEvent (QResizeEvent * event)`

[MainWindow::resizeEvent](#) Resize central TableView when you resize the [MainWindow](#)

Parameters

<i>event</i>	Resize event
--------------	--------------

8.58.3.12 `QModelIndex Gui::MainWindow::rootTree ()`

[MainWindow::rootTree](#) return the root of the tree "Tous les clients".

Returns

QModelIndex

8.58.3.13 `void Gui::MainWindow::search (QString s) [slot]`

[MainWindow::search](#) launch a new search.

Parameters

<i>s</i>	text in field
----------	---------------

8.58.3.14 `int Gui::MainWindow::treeLevel ()`

[MainWindow::treeLevel](#) return the level of the node selected in the tree.

Returns

integer, depth of the item in tree

The documentation for this class was generated from the following files:


- /home/travis/build/FACT-Team/FactDev/src/gui/mainwindow/mainwindow.h
- /home/travis/build/FACT-Team/FactDev/src/gui/mainwindow/mainwindow.cpp

8.59 Gui::Dialogs::MessageBox Class Reference

The [MessageBox](#) class Information window with message.

```
#include <messagebox.h>
```

Inheritance diagram for Gui::Dialogs::MessageBox:

**Public Member Functions**

- [MessageBox](#) (QWidget *parent=0)
[MessageBox::MessageBox](#) Construt a [MessageBox](#)
- void [aboutFact](#) ()
[MessageBox::aboutFact](#) Defines FACT team information.
- void [aboutFactDev](#) ()
[MessageBox::aboutFactDev](#) Defines FactDev software information.
- void [aboutIcons](#) ()
[MessageBox::aboutIcons](#) Defines icons theme information.
- void [setImage](#) (QString img, int width=128, int height=128)
[MessageBox::setImage](#) Add the icon img to the current window.
- void [setText](#) (QString txt)
[MessageBox::setText](#) Add the text txt to the current window.

Static Public Member Functions

- static void [showAboutFact](#) ()
[MessageBox::showAboutFact](#) Shows window about FACT team.
- static void [showAboutFactDev](#) ()
[MessageBox::showAboutFactDev](#) Shows window about FactDev software.
- static void [showAboutIcons](#) ()
[MessageBox::showAboutIcons](#) Shows about icons theme of FactDev software.

8.59.1 Detailed Description

The [MessageBox](#) class Information window with message.

Author

Florent Berbie

8.59.2 Constructor & Destructor Documentation

8.59.2.1 `Gui::Dialogs::MessageBox::MessageBox (QWidget * parent = 0) [explicit]`

[MessageBox::MessageBox](#) Construt a [MessageBox](#)

Parameters

<i>parent</i>	
---------------	--

8.59.3 Member Function Documentation

8.59.3.1 `void Gui::Dialogs::MessageBox::setImage (QString img, int width = 128, int height = 128)`

[MessageBox::setImage](#) Add the icon *img* to the current window.

Parameters

<i>img</i>	Icon
<i>width</i>	Icon width (default: 128)
<i>height</i>	Icon height (default: 128)

8.59.3.2 `void Gui::Dialogs::MessageBox::setText (QString txt)`

[MessageBox::setText](#) Add the text *txt* to the current window.

Parameters

<i>txt</i>	Text inside the current window
------------	--------------------------------

The documentation for this class was generated from the following files:

- `/home/travis/build/FACT-Team/FactDev/src/gui/dialogs/messagebox.h`
- `/home/travis/build/FACT-Team/FactDev/src/gui/dialogs/messagebox.cpp`

8.60 Parameters Class Reference

The [Parameters](#) class Class for simple user parameters.

```
#include <parameters.h>
```

Static Public Attributes

- static const QString [DB_FILENAME](#) = "database.db"
DB_FILENAME The database sqlite file name.
- static const double [VERSION](#) = 1.0
VERSION Version number of software.

8.60.1 Detailed Description

The [Parameters](#) class Class for simple user parameters.

Author

Antoine de Roquemaurel

8.60.2 Member Data Documentation

8.60.2.1 `const QString Parameters::DB_FILENAME = "database.db" [static]`

DB_FILENAME The database sqlite file name.

Database file name

8.60.2.2 `const double Parameters::VERSION = 1.0 [static]`

VERSION Version number of software.

Application version


The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/parameters.h
- /home/travis/build/FACT-Team/FactDev/src/parameters.cpp

8.61 Mustache::PartialFileLoader Class Reference

```
#include <mustache.h>
```

Inheritance diagram for Mustache::PartialFileLoader:



Public Member Functions

- **PartialFileLoader** (const QString &basePath)
- virtual QString [getPartial](#) (const QString &name)

8.61.1 Detailed Description

A partial fetcher when loads templates from '<name>.mustache' files in a given directory.

Once a partial has been loaded, it is cached for future use.

8.61.2 Member Function Documentation

8.61.2.1 `QString PartialFileLoader::getPartial (const QString & name) [virtual]`

Returns the partial template with a given `name`.

Implements [Mustache::PartialResolver](#).


The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/libs/qt-mustache/src/mustache.h
- /home/travis/build/FACT-Team/FactDev/src/libs/qt-mustache/src/mustache.cpp

8.62 Mustache::PartialMap Class Reference

```
#include <mustache.h>
```

Inheritance diagram for Mustache::PartialMap:



Public Member Functions

- **PartialMap** (const QHash< QString, QString > &partials)
- virtual QString [getPartial](#) (const QString &name)

8.62.1 Detailed Description

A simple partial fetcher which returns templates from a map of (partial name -> template)

8.62.2 Member Function Documentation

8.62.2.1 QString PartialMap::getPartial (const QString & name) [virtual]

Returns the partial template with a given name.

Implements [Mustache::PartialResolver](#).


The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/libs/qt-mustache/src/mustache.h
- /home/travis/build/FACT-Team/FactDev/src/libs/qt-mustache/src/mustache.cpp

8.63 Mustache::PartialResolver Class Reference

```
#include <mustache.h>
```

Inheritance diagram for Mustache::PartialResolver:



Public Member Functions

- virtual QString [getPartial](#) (const QString &name)=0

8.63.1 Detailed Description

Interface for fetching template partials.

8.63.2 Member Function Documentation

8.63.2.1 virtual QString Mustache::PartialResolver::getPartial (const QString & *name*) [pure virtual]

Returns the partial template with a given *name*.

Implemented in [Mustache::PartialFileLoader](#), and [Mustache::PartialMap](#).

The documentation for this class was generated from the following file:

- /home/travis/build/FACT-Team/FactDev/src/libs/qt-mustache/src/mustache.h

8.64 Generator::PdfGenerator Class Reference

The [PdfGenerator](#) class Generator of PDF files.

```
#include <pdfgenerator.h>
```

Public Member Functions

- [PdfGenerator](#) (QString pdflatexPath="pdflatex")
PdfGenerator::PdfGenerator Construct a *PdfGenerator*.
- void [generate](#) (QString inputDir, QString filename)
PdfGenerator::generate Generate a PDF of the file named *filename* into the directory *inputDir*

8.64.1 Detailed Description

The [PdfGenerator](#) class Generator of PDF files.

8.64.2 Constructor & Destructor Documentation

8.64.2.1 Generator::PdfGenerator::PdfGenerator (QString pdflatexPath = "pdflatex")

[PdfGenerator::PdfGenerator](#) Construct a [PdfGenerator](#).

Parameters

<i>pdflatexPath</i>	Path to the command to generate PDF file
---------------------	--

8.64.3 Member Function Documentation

8.64.3.1 void Generator::PdfGenerator::generate (QString inputDir, QString filename)

[PdfGenerator::generate](#) Generate a PDF of the file named *filename* into the directory *inputDir*

Parameters

<i>inputDir</i>	Directory where is store the PDF generated
<i>filename</i>	File name

The documentation for this class was generated from the following files:


- /home/travis/build/FACT-Team/FactDev/src/generator/pdfgenerator.h
- /home/travis/build/FACT-Team/FactDev/src/generator/pdfgenerator.cpp

8.65 Models::People Class Reference

The `People` class `People`.

```
#include <people.h>
```

Inheritance diagram for Models::People:



Public Member Functions

- `People ()`
People::People Construct a *People*.
- `QString getFirstname () const`
People::getFirstname Return the *People* firstname.
- `void setFirstname (const QString &firstname)`
People::setFirstname Modify the *People* firstname
- `QString getLastname () const`
People::getLastname Return the *People* lastname.
- `void setLastname (const QString &lastname)`
People::setLastname Modify the *People* lastname
- `QString getCompany () const`
People::getCompany Return the *People* company.
- `void setCompany (const QString &company)`
People::setCompany Modify the *People* company name.
- `QString getAddress () const`
People::getAddress Return the company address (Number and name of street)
- `void setAddress (const QString &address)`
People::setAddress Modify the *People* company address
- `QString getPostalCode () const`
People::getPostalCode Return the postal code.
- `void setPostalCode (const QString &postalCode)`
People::setPostalCode Modify the postal code postalCode
- `QString getCity () const`
People::getCity Return the city.
- `void setCity (const QString &city)`
People::setCity Modify the city
- `QString getCountry () const`
People::getCountry Return the country of the *People*.
- `void setCountry (const QString &country)`
People::setCountry Replace the country of the *People* by country
- `QString getEmail () const`
People::getEmail Return the *People* professional email
- `void setEmail (const QString &email)`
People::setEmail Modify the *People* professional email
- `QString getPhone () const`
People::getPhone Return the number of the desktop phone.

- void [setPhone](#) (const QString &phone)
People::setPhone Modify the number of the desktop phone
- QString [getMobilePhone](#) () const
People::getMobilePhone Return the number of the professional mobile phone.
- void [setMobilePhone](#) (const QString &mobilePhone)
People::setMobilePhone Modify the number of the professional [People](#) mobile phone mobilePhone
- QString [getFax](#) () const
People::getFax Return the fax number.
- void [setFax](#) (const QString &fax)
People::setFax Replace the current fax number by fax
- bool [operator==](#) (const [People](#) &c)
People::operator == Re-define the operator "==" to compare if the current [People](#) is the same to the other [People](#) c
Return TRUE if both Peoples are the same, else FALSE.
- bool [operator!=](#) (const [People](#) &c)
People::operator != Re-define the operator "!=" to compare if the current [People](#) is differnt to the other [People](#) c
Return TRUE if both Peoples are different, else FALSE.

8.65.1 Detailed Description

The [People](#) class [People](#).

8.65.2 Member Function Documentation

8.65.2.1 QString Models::People::getAddress () const

[People::getAddress](#) Return the company address (Number and name of street)

Returns

Address company

8.65.2.2 QString Models::People::getCity () const

[People::getCity](#) Return the city.

Returns

city

8.65.2.3 QString Models::People::getCompany () const

[People::getCompany](#) Return the [People](#) company.

Returns

New company name

8.65.2.4 QString Models::People::getCountry () const

[People::getCountry](#) Return the country of the [People](#).

Returns

country of the [People](#)

8.65.2.5 QString Models::People::getEmail () const

[People::getEmail](#) Return the [People](#) professional *email*

Returns

professional email

8.65.2.6 QString Models::People::getFax () const

[People::getFax](#) Return the fax number.

Returns

fax number

8.65.2.7 QString Models::People::getFirstname () const

[People::getFirstname](#) Return the [People](#) firstname.

Returns

[People](#) firstname

8.65.2.8 QString Models::People::getLastname () const

[People::getLastname](#) Return the [People](#) lastname.

Returns

[People](#) lastname

8.65.2.9 QString Models::People::getMobilePhone () const

[People::getMobilePhone](#) Return the number of the professional mobile phone.

Returns

number of mobile phone

8.65.2.10 QString Models::People::getPhone () const

[People::getPhone](#) Return the number of the desktop phone.

Returns

number of the desktop phone

8.65.2.11 QString Models::People::getPostalCode () const

[People::getPostalCode](#) Return the postal code.

Returns

postal code

8.65.2.12 `bool Models::People::operator!=(const People & c)`

`People::operator ==` Re-define the operator "!=" to compare if the current `People` is different to the other `People` `c`
Return TRUE if both Peoples are different, else FALSE.

Parameters

<i>c</i>	People to compare
----------	-------------------

Returns

boolean

8.65.2.13 bool Models::People::operator== (const People & *c*)

People::operator == Re-define the operator "==" to compare if the current **People** is the same to the other **People** *c*
Return TRUE if both Peoples are the same, else FALSE.

Parameters

<i>c</i>	People to compare
----------	-------------------

Returns

boolean

8.65.2.14 void Models::People::setAddress (const QString & *address*)

People::setAddress Modify the **People** company *address*

Parameters

<i>address</i>	Company address (name and number of street)
----------------	---

8.65.2.15 void Models::People::setCity (const QString & *city*)

People::setCity Modify the *city*

Parameters

<i>city</i>	Company city address
-------------	----------------------

8.65.2.16 void Models::People::setCompany (const QString & *company*)

People::setCompany Modify the **People** *company* name.

Parameters

<i>company</i>	New People company name
----------------	--------------------------------

8.65.2.17 void Models::People::setCountry (const QString & *country*)

People::setCountry Replace the country of the **People** by *country*

Parameters

<i>country</i>	New country of the People
----------------	---

8.65.2.18 void Models::People::setEmail (const QString & *email*)

[People::setEmail](#) Modify the [People](#) professional *email*

Parameters

<i>email</i>	The People professional email
--------------	---

8.65.2.19 void Models::People::setFax (const QString & *fax*)

[People::setFax](#) Replace the current fax number by *fax*

Parameters

<i>fax</i>	new fax number
------------	----------------

8.65.2.20 void Models::People::setFirstname (const QString & *firstname*)

[People::setFirstname](#) Modify the [People](#) *firstname*

Parameters

<i>firstname</i>	New People firstname
------------------	--------------------------------------

8.65.2.21 void Models::People::setLastname (const QString & *lastname*)

[People::setLastname](#) Modify the [People](#) *lastname*

Parameters

<i>lastname</i>	New People lastname
-----------------	-------------------------------------

8.65.2.22 void Models::People::setMobilePhone (const QString & *mobilePhone*)

[People::setMobilePhone](#) Modify the number of the professional [People](#) mobile phone *mobilePhone*

Parameters

<i>mobilePhone</i>	Number of the professional mobile phone
--------------------	---

8.65.2.23 void Models::People::setPhone (const QString & *phone*)

[People::setPhone](#) Modify the number of the desktop *phone*

Parameters

<i>phone</i>	Number of the desktop phone
--------------	-----------------------------

8.65.2.24 void Models::People::setPostalCode (const QString & *postalCode*)

[People::setPostalCode](#) Modify the postal code *postalCode*

Parameters

<i>postalCode</i>	New postal code
-------------------	-----------------

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/models/people.h
- /home/travis/build/FACT-Team/FactDev/src/models/people.cpp

8.66 Utils::pointers Class Reference

Static Public Member Functions


- static void **deleteIfNotNull** (QObject *p)

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/Utils/pointers.h
- /home/travis/build/FACT-Team/FactDev/src/Utils/pointers.cpp

8.67 PointersTest Class Reference

Inheritance diagram for PointersTest:



The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/tests/Utils/pointertest.h
- /home/travis/build/FACT-Team/FactDev/tests/Utils/pointertest.cpp

8.68 Gui::Widgets::Popup Class Reference

Class for display popup quickly.

```
#include <popup.h>
```

Static Public Member Functions

- static void **toImplement** (QString, QWidget *)
Popup::toImplement Method to display a critical message : feature is not implemented now.

8.68.1 Detailed Description

Class for display popup quickly.

Author

Antoine de Roquemaurel

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/popup.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/popup.cpp

8.69 Models::Project Class Reference

The [Project](#) class : [Project](#) linked to a [Customer](#).

```
#include <project.h>
```

Inheritance diagram for Models::Project:



Public Member Functions

- [Project](#) ()
Project::Project Construct a [Project](#).
- [Project](#) (QString name)
Project::project Construct a project with a name.
- [Project](#) (int id)
Project::Project Construct a [Project](#) which is specified by an id
- virtual [~Project](#) ()
~Project Desctruct project object
- void [commit](#) ()
Project::commit Update project data in the database.
- void [hydrat](#) (int id)
Project::hydrat Insert project data which is specified by id in the database.
- void [remove](#) ()
Project::remove Remove the current project.
- QVariantHash [getDataMap](#) ()
getDataMap Get all data of model with a HashMap key/value
- QString [getName](#) () const
Project::getName Return the project name.
- void [setName](#) (const QString &name)
Project::setName Modify the project name
- QString [getDescription](#) () const
Project::getDescription Return a project description.
- void [setDescription](#) (const QString &description)
Project::setDescription Modify the project description
- QDate [getBeginDate](#) () const
Project::getBeginDate return the date of creation of the [Project](#)
- void [setBeginDate](#) (QDate beginDate)

- Project::setBeginDate* Modify beginDate of a **Project**
- QDate **getEndDate** () const
 - Project::getEndDate* Return the endDate of the **Project**
- void **setEndDate** (QDate endDate)
 - Project::setEndDate* Modify endDate of **Project**
- double **getCost** () const
 - Project::getCost* Return the **Project** cost
- void **setCost** (double cost)
 - Project::setCost* Modify the **Project** cost
- double **getDailyRate** () const
 - Project::getDailyRate* Return the daily rate estimated for this project.
- void **setDailyRate** (double dailyRate)
 - Project::setDailyRate* Modify the daily rate dailyRate of the current project.
- QSharedPointer< **Customer** > **getCustomer** () const
 - Project::getCustomer* Return the reference to the customer linked to this project.
- void **setCustomer** (QSharedPointer< **Customer** > customer)
 - Project::setCustomer* Modify the customer linked to this project.
- bool **operator==** (const **Project** &p)
 - Project::operator ==* Re-define the operator "==" to compare if the current project is the same to the other **Project** p
Return TRUE if both projects are the same, else FALSE.
- bool **operator<** (const **Project** &p) const
 - Project::operator <* defines the operator "<" to compare two **Project** and to see if the first is anterior to the second.
- bool **operator!=** (const **Project** &p)
 - Project::operator !=* Re-define the operator "!=" to compare if the current project is different to the other **Project** p
Return TRUE if both projects are different, else FALSE.
- double **computeProjectCost** ()
 - Project::computeProjectCost* compute the **Project** cost

Additional Inherited Members

8.69.1 Detailed Description

The **Project** class : **Project** linked to a **Customer**.

Author

Florent Berbie

See Also

[IModel](#)

8.69.2 Constructor & Destructor Documentation

8.69.2.1 Models::Project::Project (int id)

Project::Project Construct a **Project** which is specified by an *id*

Parameters

<i>id</i>	
-----------	--

8.69.3 Member Function Documentation

8.69.3.1 double Models::Project::computeProjectCost ()

[Project::computeProjectCost](#) compute the **Project** cost

Returns

the project cost

8.69.3.2 QDate Models::Project::getBeginDate () const

[Project::getBeginDate](#) return the date of creation of the **Project**

Returns

the begin date of the **Project**

8.69.3.3 double Models::Project::getCost () const

[Project::getCost](#) Return the **Project** cost

Returns

the project cost

8.69.3.4 QSharedPointer< Customer > Models::Project::getCustomer () const

[Project::getCustomer](#) Return the reference to the customer linked to this project.

Returns

customer linked to this project

8.69.3.5 double Models::Project::getDailyRate () const

[Project::getDailyRate](#) Return the daily rate estimated for this project.

Returns

the daily rate linket to the current project

8.69.3.6 QVariantHash Models::Project::getDataMap () [virtual]

[getDataMap](#) Get all data of model with a HashMap key/value

Returns

Model's data

Implements [Models::IModel](#).

8.69.3.7 QString Models::Project::getDescription () const

[Project::getDescription](#) Return a project description.

Returns

project description

8.69.3.8 QDate Models::Project::getEndDate () const

[Project::getEndDate](#) Return the *endDate* of the **Project**

Returns

the end date of the project

8.69.3.9 QString Models::Project::getName () const

[Project::getName](#) Return the project name.

Returns

project name

8.69.3.10 void Models::Project::hydrat (int *id*) [virtual]

[Project::hydrat](#) Insert project data which is specified by *id* in the database.

Parameters

<i>id</i>	Project identify
-----------	----------------------------------

Implements [Models::IModel](#).

8.69.3.11 bool Models::Project::operator!= (const Project & *p*)

[Project::operator ==](#) Re-define the operator "!=" to compare if the current project is differnt to the other **Project** *p*
Return TRUE if both projects are different, else FALSE.

Parameters

<i>c</i>	Project to compare
----------	------------------------------------

Returns

boolean

8.69.3.12 bool Models::Project::operator< (const Project & *p*) const

[Project::operator <](#) defines the operator "<" to compare two **Project** and to see if the first is anterior to the second.

Parameters

<i>b</i>	the Project to compare with the current Project
----------	---

Returns

true if the **Project** are different else false

8.69.3.13 bool Models::Project::operator== (const **Project** & *p*)

Project::operator == Re-define the operator "==" to compare if the current project is the same to the other **Project** *p*
Return TRUE if both projects are the same, else FALSE.

Parameters

<i>c</i>	Project to compare
----------	---------------------------

Returns

boolean

8.69.3.14 void Models::Project::setBeginDate (**QDate** *beginDate*)

Project::setBeginDate Modify *beginDate* of a **Project**

Parameters

<i>beginDate</i>	the new date of creation of the project
------------------	---

8.69.3.15 void Models::Project::setCost (double *cost*)

Project::setCost Modify the **Project** *cost*

Parameters

<i>cost</i>	the projectCost
-------------	-----------------

8.69.3.16 void Models::Project::setCustomer (**QSharedPointer< Customer >** *customer*)

Project::setCustomer Modify the *customer* linked to this project.

Parameters

<i>customer</i>	New customer associated to this project
-----------------	---

8.69.3.17 void Models::Project::setDailyRate (double *dailyRate*)

Project::setDailyRate Modify the daily rate *dailyRate* of the current project.

Parameters

<i>dailyRate</i>	New daily rate associated to the current project
------------------	--

8.69.3.18 void Models::Project::setDescription (const QString & *description*)

[Project::setDescription](#) Modify the project *description*

Parameters

<i>description</i>	New project description
--------------------	-------------------------

8.69.3.19 void Models::Project::setEndDate (QDate *endDate*)

[Project::setEndDate](#) Modify *endDate* of [Project](#)

Parameters

<i>endDate</i>	the new end date of the project
----------------	---------------------------------

8.69.3.20 void Models::Project::setName (const QString & *name*)

[Project::setName](#) Modify the project *name*

Parameters

<i>name</i>	Project name
-------------	------------------------------

The documentation for this class was generated from the following files:


- /home/travis/build/FACT-Team/FactDev/src/models/project.h
- /home/travis/build/FACT-Team/FactDev/src/models/project.cpp

8.70 Gui::Widgets::Delegates::ProjectComboDelegate Class Reference

The [ProjectComboDelegate](#) class.

```
#include <projectcombodelegate.h>
```

Inheritance diagram for Gui::Widgets::Delegates::ProjectComboDelegate:



Public Member Functions

- [ProjectComboDelegate](#) (QSharedPointer< [Models::Customer](#) > c, QObject *parent=0)
[ProjectComboDelegate::ProjectComboDelegate](#).
- QWidget * [createEditor](#) (QWidget *parent, const QStyleOptionViewItem &option, const QModelIndex &index) const

[ProjectComboDelegate::createEditor](#) Return a ComboBox specified by *index* item defined by the parent widget and style option which are used to control how the editor widgets appears.

- void [paint](#) (QPainter *painter, const QStyleOptionViewItem &option, const QModelIndex &index) const

[ProjectComboDelegate::paint](#) Renders the delegate using the given painter and style option for the item specified by *index*

- void [removeInCombo](#) (QList< int > &l)

[ProjectComboDelegate::removeInCombo](#) Remove the items contained in the list *l* into the current ComboBox.

- QMap< int, [Models::Project](#) > [getProjects](#) () const

[ProjectComboDelegate::getProjects](#) Return a list of projects linked to a Customer ID.

- bool [isLocked](#) () const

[ProjectComboDelegate::isLocked](#) Return TRUE if is locked else FALSE.

- void [setLocked](#) (bool locked)

[ProjectComboDelegate::setLocked](#) Change the state of the lock by a new value *locked*

8.70.1 Detailed Description

The [ProjectComboDelegate](#) class.

8.70.2 Constructor & Destructor Documentation

- 8.70.2.1 [Gui::Widgets::Delegates::ProjectComboDelegate::ProjectComboDelegate](#) (QSharedPointer< [Models::Customer](#) > *c*, QObject * *parent* = 0)

[ProjectComboDelegate::ProjectComboDelegate](#).

Parameters

<i>c</i>	
<i>parent</i>	

8.70.3 Member Function Documentation

- 8.70.3.1 [QWidget * Gui::Widgets::Delegates::ProjectComboDelegate::createEditor](#) (QWidget * *parent*, const QStyleOptionViewItem & *option*, const QModelIndex & *index*) const [virtual]

[ProjectComboDelegate::createEditor](#) Return a ComboBox specified by *index* item defined by the *parent* widget and style *option* which are used to control how the editor widgets appears.

Parameters

<i>parent</i>	Widget parent
<i>option</i>	Option style
<i>index</i>	Index for editing

Returns

ComboBox

Implements [Gui::Widgets::Delegates::ComboBoxDelegate](#).

- 8.70.3.2 [QMap< int, Models::Project > Gui::Widgets::Delegates::ProjectComboDelegate::getProjects](#) () const

[ProjectComboDelegate::getProjects](#) Return a list of projects linked to a Customer ID.

Returns

Projets of a Customer

8.70.3.3 `bool Gui::Widgets::Delegates::ProjectComboDelegate::isLocked () const`

[ProjectComboDelegate::isLocked](#) Return TRUE if is locked else FALSE.

Returns

boolean

8.70.3.4 `void Gui::Widgets::Delegates::ProjectComboDelegate::paint (QPainter * painter, const QStyleOptionViewItem & option, const QModelIndex & index) const` [virtual]

[ProjectComboDelegate::paint](#) Renders the delegate using the given *painter* and style *option* for the item specified by *index*

Parameters

<i>parent</i>	Widget parent
<i>option</i>	Option style
<i>index</i>	Index for editing

Implements [Gui::Widgets::Delegates::ComboBoxDelegate](#).

8.70.3.5 `void Gui::Widgets::Delegates::ProjectComboDelegate::setLocked (bool locked)`

[ProjectComboDelegate::setLocked](#) Change the state of the lock by a new value *locked*

Parameters

<i>locked</i>	
---------------	--

The documentation for this class was generated from the following files:


- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/delegates/projectcombodelegate.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/delegates/projectcombodelegate.cpp

8.71 Gui::Widgets::WdgModels::ProjectContributoriesTableModel Class Reference

The [ProjectContributoriesTableModel](#) class Table model of contributories linked to projets.

```
#include <projectcontributoriестablemodel.h>
```

Inheritance diagram for Gui::Widgets::WdgModels::ProjectContributoriesTableModel:



Public Member Functions

- [ProjectContributoriesTableModel](#) (QObject *parent=0)

- [ProjectContributoriesTableModel::ProjectContributoriesTableModel](#) Construct a [ProjectContributoriesTableModel](#).
- int [rowCount](#) (const QModelIndex &) const

[ProjectContributoriesTableModel::rowCount](#) Number of contributories row.
- int [columnCount](#) (const QModelIndex &) const

[ProjectContributoriesTableModel::columnCount](#) Number of column of a contributory.
- QVariant [data](#) (const QModelIndex &index, int role) const

[ProjectContributoriesTableModel::data](#) Obtains data of a specify cell.
- QVariant [headerData](#) (int section, Qt::Orientation orientation, int role) const

[ProjectContributoriesTableModel::headerData](#) Obtains header title of table.
- bool [setData](#) (const QModelIndex &index, const QVariant &value, int role=Qt::EditRole)

[ProjectContributoriesTableModel::setData](#) Change data of a cell.
- Qt::ItemFlags [flags](#) (const QModelIndex &index) const

[ProjectContributoriesTableModel::flags](#) Differents table flags.
- void [append](#) (QPair< [Models::Project](#) *, [Models::Rate](#) > p)

[ProjectContributoriesTableModel::append](#) Add a new rate p to a Project.
- void [append](#) ()

[ProjectContributoriesTableModel::append](#) Add the current element to the list.
- bool [allProjectsChosen](#) ()

[ProjectContributoriesTableModel::allProjectsChosen](#) Return TRUE if all projects have been selected else FALSE.
- QList< int > & [getSelectedProjects](#) ()

[ProjectContributoriesTableModel::getSelectedProjects](#) Return the list of the Project id which are selected.
- void [remove](#) (int index)

[ProjectContributoriesTableModel::remove](#) Remove the element to the index
- QPair< [Models::Project](#) *, [Models::Rate](#) > [getProject](#) (const int row)

[ProjectContributoriesTableModel::getProject](#) Return the project and it rate linked which correspond to the row
- QList< QPair< [Models::Project](#) *, [Models::Rate](#) > > [getProjects](#) (void)

[ProjectContributoriesTableModel::getProjects](#) Return a list of the set of projects and their rates linked.

8.71.1 Detailed Description

The [ProjectContributoriesTableModel](#) class Table model of contributories linked to projects.

Author

Antoine de Roquemaurel

8.71.2 Constructor & Destructor Documentation

- 8.71.2.1 [Gui::Widgets::WdgModels::ProjectContributoriesTableModel::ProjectContributoriesTableModel \(QObject * parent = 0 \)](#)

[ProjectContributoriesTableModel::ProjectContributoriesTableModel](#) Construct a [ProjectContributoriesTableModel](#).

Parameters

<i>parent</i>	Parent widget
---------------	---------------

8.71.3 Member Function Documentation

8.71.3.1 `bool Gui::Widgets::WdgModels::ProjectContributoriesTableModel::allProjectsChosen ()`

[ProjectContributoriesTableModel::allProjectsChosen](#) Return TRUE if all projects have been selected else FALSE.

Returns

boolean All projects selected

8.71.3.2 `void Gui::Widgets::WdgModels::ProjectContributoriesTableModel::append (QPair< Models::Project *, Models::Rate > p)`

[ProjectContributoriesTableModel::append](#) Add a new rate p to a Project.

Parameters

p	
-----	--

8.71.3.3 `int Gui::Widgets::WdgModels::ProjectContributoriesTableModel::columnCount (const QModelIndex &) const`

[ProjectContributoriesTableModel::columnCount](#) Number of column of a contributory.

Returns

The number of column

8.71.3.4 `QVariant Gui::Widgets::WdgModels::ProjectContributoriesTableModel::data (const QModelIndex & index, int role) const`

[ProjectContributoriesTableModel::data](#) Obtains data of a specify cell.

Parameters

<i>index</i>	The cell who we want data
<i>role</i>	The role of set

Returns

The data of cell

8.71.3.5 `Qt::ItemFlags Gui::Widgets::WdgModels::ProjectContributoriesTableModel::flags (const QModelIndex & index) const`

[ProjectContributoriesTableModel::flags](#) Differents table flags.

Parameters

<i>index</i>	The cell who we want to know flags
--------------	------------------------------------

Returns

Flags

8.71.3.6 `QPair< Models::Project *, Models::Rate > Gui::Widgets::WdgModels::ProjectContributoriesTableModel::getProject (const int row)`

[ProjectContributoriesTableModel::getProject](#) Return the project and it rate linked which correspond to the *row*

Parameters

<i>row</i>	Row of the project to get
------------	---------------------------

Returns

a Project and it rate

8.71.3.7 `QList< QPair< Models::Project *, Models::Rate > > Gui::Widgets::WdgModels::ProjectContributoriesTableModel::getProjects (void)`

[ProjectContributoriesTableModel::getProjects](#) Return a list of the set of projects and their rates linked.

Returns

List of Projects and Rates linked

8.71.3.8 `QList< int > & Gui::Widgets::WdgModels::ProjectContributoriesTableModel::getSelectedProjects ()`

[ProjectContributoriesTableModel::getSelectedProjects](#) Return the list of the Project id which are selected.

Returns

List of ID Project

8.71.3.9 `QVariant Gui::Widgets::WdgModels::ProjectContributoriesTableModel::headerData (int section, Qt::Orientation orientation, int role) const`

[ProjectContributoriesTableModel::headerData](#) Obtains header title of table.

Parameters

<i>section</i>	The number of column
<i>orientation</i>	The table orientation
<i>role</i>	

Returns

The Title header of column

8.71.3.10 `void Gui::Widgets::WdgModels::ProjectContributoriesTableModel::remove (int index)`

[ProjectContributoriesTableModel::remove](#) Remove the element to the *index*

Parameters

<i>index</i>	Index of the element to remove
--------------	--------------------------------

8.71.3.11 `int Gui::Widgets::WdgModels::ProjectContributoriesTableModel::rowCount (const QModelIndex &) const`

[ProjectContributoriesTableModel::rowCount](#) Number of contributories row.

Returns

The number of contributories

8.71.3.12 `bool Gui::Widgets::WdgModels::ProjectContributoriesTableModel::setData (const QModelIndex & index, const QVariant & value, int role = Qt::EditRole)`

[ProjectContributoriesTableModel::setData](#) Change data of a cell.

Parameters

<i>index</i>	The cell to change data
<i>value</i>	The new value
<i>role</i>	The role of cell

Returns

True if we could edit

The documentation for this class was generated from the following files:


- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/widgetmodels/projectcontributoriestablemodel.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/widgetmodels/projectcontributoriestablemodel.cpp

8.72 Databases::ProjectDatabase Class Reference

The [ProjectDatabase](#) class Project table database.

```
#include <projectdatabase.h>
```

Inheritance diagram for Databases::ProjectDatabase:



Public Member Functions

- [Models::Project](#) * [getProject](#) (const int pld)
ProjectDatabase::getProject Get informations about the project identified by 'pld'.
- [Models::Project](#) * [getProject](#) (QSqlQuery &q)
ProjectDatabase::getProject.
- int [addProject](#) (const [Models::Project](#) &)
ProjectDatabase::addProject Add the project 'pProject' to the database.
- void [updateProject](#) (const [Models::Project](#) &)
ProjectDatabase::updateProject Update informations about the project.
- void [removeProject](#) (const int pld)
removeProject Remove the project with the id 'pld'
- int [getNbProjects](#) ()
ProjectDatabase::getNbProjects Return the number of projects existing.
- int [getNbProjects](#) (const int customerId)
Get the number of projects.
- QMap< int, [Models::Project](#) > [getProjectsOfCustomer](#) (QSharedPointer< [Models::Customer](#) > c)
getProjectsOfCustomer Return all projects of a customer
- QList< [Models::Project](#) > [getProjects](#) (const int customerId)
getProjects Return all projects of a customer
- [WdgModels::ProjectsTableModel](#) * [getProjectsTable](#) (const int pld) throw (DbException*)
getProjectsTable Return all projects of a customer in QStandardItemModel
- QSharedPointer< [Project](#) > [updateProject](#) (QSqlQuery &q)
getProject Obtain a project without new query

- `QList< Project * > getAllProjects ()`
Project::getAllProjects Return the list of projects.
- `double getCostProjects (QList< Project * > projects)`
ProjectDatabase::getCostProjects compute the cost of the project list given in parameter.

Static Public Member Functions

- `static ProjectDatabase * instance () throw (DbException*)`
ProjectDatabase::getInstance Return an instance of [ProjectDatabase](#).

Additional Inherited Members

8.72.1 Detailed Description

The [ProjectDatabase](#) class Project table database.

Author

Florent Berbie

See Also

[Database](#)
[Project](#)

8.72.2 Member Function Documentation

8.72.2.1 `int Databases::ProjectDatabase::addProject (const Models::Project & pProject)`

[ProjectDatabase::addProject](#) Add the project 'pProject' to the database.

Returns

project id

8.72.2.2 `QList< Project * > Databases::ProjectDatabase::getAllProjects ()`

[Project::getAllProjects](#) Return the list of projects.

Returns

Projects list

8.72.2.3 `double Databases::ProjectDatabase::getCostProjects (QList< Project * > projects)`

[ProjectDatabase::getCostProjects](#) compute the cost of the project list given in parameter.

Parameters

<i>projects</i>	the list of projects
-----------------	----------------------

Returns

the cost of the list given

8.72.2.4 int Databases::ProjectDatabase::getNbProjects ()

[ProjectDatabase::getNbProjects](#) Return the number of projects existing.

Returns

number of projects

8.72.2.5 int Databases::ProjectDatabase::getNbProjects (const int *customerId*)

Get the number of projects.

Parameters

<i>customerId</i>	If customerId isn't specified if it's not valid, get all projects else get the specified customer projects
-------------------	--

Returns

Number of projects in the database for all or for a customer

8.72.2.6 Models::Project * Databases::ProjectDatabase::getProject (const int *pld*)

[ProjectDatabase::getProject](#) Get informations about the project identified by 'pld'.

Parameters

<i>pld</i>	project
------------	---------

Returns

the project

8.72.2.7 Models::Project * Databases::ProjectDatabase::getProject (QSqlQuery & *q*)

[ProjectDatabase::getProject](#).

Parameters

<i>q</i>	
----------	--

Returns**8.72.2.8 QList< Project > Databases::ProjectDatabase::getProjects (const int *customerId*)**

[getProjects](#) Return all projects of a customer

Parameters

<i>customerId</i>	The customer id
-------------------	-----------------

Returns

List with all projects of customer

8.72.2.9 `QMap< int, Models::Project > Databases::ProjectDatabase::getProjectsOfCustomer (QSharedPointer< Models::Customer > c)`

getProjectsOfCustomer Return all projects of a customer

Parameters

<i>c</i>	The customer
----------	--------------

Returns

All projects of c with id in key

8.72.2.10 `WdgModels::ProjectsTableModel * Databases::ProjectDatabase::getProjectsTable (const int pld) throw DbException *`

getProjectsTable Return all projects of a customer in QStandardItemModel

Parameters

<i>filter</i>	Select only projects who are specified by <i>filter</i>
---------------	---

Returns

QStandardItemModel an item model for QTableView

8.72.2.11 `ProjectDatabase * Databases::ProjectDatabase::instance () throw DbException *` [static]

ProjectDatabase::getInstance Return an instance of [ProjectDatabase](#).

Returns

Instance of [ProjectDatabase](#)

8.72.2.12 `void Databases::ProjectDatabase::removeProject (const int pld)`

removeProject Remove the project with the id 'pld'

Parameters

<i>pld</i>	project id
------------	------------

8.72.2.13 `QSharedPointer< Models::Project > Databases::ProjectDatabase::updateProject (QSqlQuery & q)`

getProject Obtain a project without new query

Parameters

<i>q</i>	The query to use
----------	------------------

Returns


The project linked to *q*

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/database/projectdatabase.h
- /home/travis/build/FACT-Team/FactDev/src/database/projectdatabase.cpp

8.73 ProjectDatabaseTest Class Reference

Inheritance diagram for ProjectDatabaseTest:




The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/tests/database/projectdatabasetest.h
- /home/travis/build/FACT-Team/FactDev/tests/database/projectdatabasetest.cpp

8.74 ProjectModelTest Class Reference

Inheritance diagram for ProjectModelTest:



The documentation for this class was generated from the following files:


- /home/travis/build/FACT-Team/FactDev/tests/models/projectmodeltest.h
- /home/travis/build/FACT-Team/FactDev/tests/models/projectmodeltest.cpp

8.75 Gui::Widgets::WdgModels::ProjectsTableModel Class Reference

The [ProjectsTableModel](#) class for a Project table.

```
#include <projectstablemodel.h>
```

Inheritance diagram for Gui::Widgets::WdgModels::ProjectsTableModel:



Public Member Functions

- [ProjectsTableModel](#) ()
[ProjectsTableModel::ProjectsTableModel](#) Construct a [ProjectsTableModel](#).
- int [rowCount](#) (const QModelIndex &) const
[ProjectsTableModel::rowCount](#) Number of projects row.
- int [columnCount](#) (const QModelIndex &) const
[ProjectsTableModel::columnCount](#) Number of column of a Project.
- QVariant [data](#) (const QModelIndex &index, int role=Qt::DisplayRole) const
[ProjectsTableModel::data](#) Obtains data of a specify cell.
- QVariant [headerData](#) (int section, Qt::Orientation orientation, int role=Qt::DisplayRole) const
[ProjectsTableModel::headerData](#) Obtains header title of table.
- bool [setData](#) (const QModelIndex &index, const QVariant &value, int role=Qt::EditRole)
[ProjectsTableModel::setData](#) Change data of a cell.
- void [append](#) (const [Project](#) &project)
[ProjectsTableModel::append](#) Add a new line in table.
- void [remove](#) (const int i)
[ProjectsTableModel::remove](#) Remove a line.
- Qt::ItemFlags [flags](#) (const QModelIndex &index) const
[ProjectsTableModel::flags](#) Differents table flags.
- int [count](#) ()
[ProjectsTableModel::count](#) Number of projects in table.
- QList< [Project](#) > [getProjects](#) () const
[ProjectsTableModel::getProjects](#) Return the list of projects.

8.75.1 Detailed Description

The [ProjectsTableModel](#) class for a Project table.

Author

Florent Berbie

See Also

[Project](#)

8.75.2 Constructor & Destructor Documentation

8.75.2.1 Gui::Widgets::WdgModels::ProjectsTableModel::ProjectsTableModel ()

[ProjectsTableModel::ProjectsTableModel](#) Construct a [ProjectsTableModel](#).

Parameters

<i>parent</i>	Parent widget
---------------	---------------

8.75.3 Member Function Documentation

8.75.3.1 void Gui::Widgets::WdgModels::ProjectsTableModel::append (const Project & *project*)

[ProjectsTableModel::append](#) Add a new line in table.

Parameters

<i>Project</i>	The new Project
----------------	-----------------

8.75.3.2 int Gui::Widgets::WdgModels::ProjectsTableModel::columnCount (const QModelIndex &) const

[ProjectsTableModel::columnCount](#) Number of column of a Project.

Returns

The number of column

8.75.3.3 int Gui::Widgets::WdgModels::ProjectsTableModel::count ()

[ProjectsTableModel::count](#) Number of projects in table.

Returns

The number of projects

8.75.3.4 QVariant Gui::Widgets::WdgModels::ProjectsTableModel::data (const QModelIndex & *index*, int *role* = Qt::DisplayRole) const

[ProjectsTableModel::data](#) Obtains data of a specify cell.

Parameters

<i>index</i>	The cell who we want data
<i>role</i>	The role of set

Returns

The data of cell

8.75.3.5 Qt::ItemFlags Gui::Widgets::WdgModels::ProjectsTableModel::flags (const QModelIndex & *index*) const

[ProjectsTableModel::flags](#) Differents table flags.

Parameters

<i>index</i>	The cell who we want to know flags
--------------	------------------------------------

Returns

Flags

8.75.3.6 `QList< Project > Gui::Widgets::WdgModels::ProjectsTableModel::getProjects (void) const`

[ProjectsTableModel::getProjects](#) Return the list of projects.

Returns

list of projects

8.75.3.7 `QVariant Gui::Widgets::WdgModels::ProjectsTableModel::headerData (int section, Qt::Orientation orientation, int role = Qt::DisplayRole) const`

[ProjectsTableModel::headerData](#) Obtains header title of table.

Parameters

<i>section</i>	The number of column
<i>orientation</i>	The table orientation
<i>role</i>	

Returns

The Title header of column

8.75.3.8 `void Gui::Widgets::WdgModels::ProjectsTableModel::remove (const int i)`

[ProjectsTableModel::remove](#) Remove a line.

Parameters

<i>i</i>	The number of line to remove
----------	------------------------------

8.75.3.9 `int Gui::Widgets::WdgModels::ProjectsTableModel::rowCount (const QModelIndex &) const`

[ProjectsTableModel::rowCount](#) Number of projects row.

Returns

The number of projects

8.75.3.10 `bool Gui::Widgets::WdgModels::ProjectsTableModel::setData (const QModelIndex & index, const QVariant & value, int role = Qt::EditRole)`

[ProjectsTableModel::setData](#) Change data of a cell.

Parameters

<i>index</i>	The cell to change data
<i>value</i>	The new value
<i>role</i>	The role of cell

Returns

True if we could edit

The documentation for this class was generated from the following files:


- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/widgetsmodels/projectstablemodel.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/widgetsmodels/projectstablemodel.cpp

8.76 Gui::Widgets::ProjectsWidget Class Reference

The [ProjectsWidget](#) class Actions on Project.

```
#include <projectswidget.h>
```

Inheritance diagram for Gui::Widgets::ProjectsWidget:



Public Slots

- void [newProject](#) ()
ProjectsWidget::addProject Event which sends a signal to add a new project.
- void [editSelectedProject](#) ()
ProjectsWidget::editSelectedProject Event which sends a signal to edit the project selected.
- void [removeSelectedProject](#) ()
ProjectsWidget::removeSelectedProject Event which sends a signal to remove the project selected.
- void [updateBtn](#) (bool b)
ProjectsWidget::updateBtn Update the toolbar in tblProjects.

Signals

- void [addProject](#) ()
ProjectsWidget::addProject Add a new project to the current Customer.
- void [editProject](#) ()
ProjectsWidget::editProject Edit the current Customer selected.
- void [removeProject](#) ()
ProjectsWidget::removeProject Remove the current Customer selected.

Public Member Functions

- [ProjectsWidget](#) (QWidget *parent=0)
ProjectsWidget::ProjectsWidget Construct a [ProjectsWidget](#).

8.76.1 Detailed Description

The [ProjectsWidget](#) class Actions on Project.

Author

Florent Berbie

8.76.2 Constructor & Destructor Documentation

8.76.2.1 [Gui::Widgets::ProjectsWidget::ProjectsWidget \(QWidget * *parent* = 0 \)](#) [explicit]

[ProjectsWidget::ProjectsWidget](#) Construct a [ProjectsWidget](#).

Parameters

<i>parent</i>	
---------------	--

8.76.3 Member Function Documentation

8.76.3.1 void Gui::Widgets::ProjectsWidget::updateBtn (bool *b*) [slot]

[ProjectsWidget::updateBtn](#) Update the toolbar in tblProjects.

Parameters

<i>boolean</i>	if a row is selected
----------------	----------------------


The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/projectswidget.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/projectswidget.cpp

8.77 Mustache::QtVariantContext Class Reference

```
#include <mustache.h>
```

Inheritance diagram for Mustache::QtVariantContext:



Public Types

- typedef QString(* [fn_t](#))(const QString &, [Mustache::Renderer](#) *, [Mustache::Context](#) *)

Public Member Functions

- [QtVariantContext](#) (const QVariant &root, [PartialResolver](#) *resolver=0)
- virtual QString [stringValue](#) (const QString &key) const
- virtual bool [isFalse](#) (const QString &key) const
- virtual int [listCount](#) (const QString &key) const
- virtual void [push](#) (const QString &key, int index=-1)
- virtual void [pop](#) ()
- virtual bool [canEval](#) (const QString &key) const
- virtual QString [eval](#) (const QString &key, const QString &_template, [Mustache::Renderer](#) *renderer)

8.77.1 Detailed Description

A context implementation which wraps a QVariantHash or QVariantMap.

8.77.2 Member Typedef Documentation

8.77.2.1 `typedef QString(* Mustache::QtVariantContext::fn_t)(const QString &, Mustache::Renderer *, Mustache::Context *)`

Construct a [QtVariantContext](#) which wraps a dictionary in a [QVariantHash](#) or a [QVariantMap](#).

8.77.3 Member Function Documentation

8.77.3.1 `bool QtVariantContext::canEval (const QString & key) const [virtual]`

Returns true if [eval\(\)](#) should be used to render section tags using `key`. If [canEval\(\)](#) returns true for a key, the renderer will pass the literal, unrendered block of text for the section to [eval\(\)](#) and replace the section with the result.

[canEval\(\)](#) and [eval\(\)](#) are equivalents for callable objects (eg. lambdas) in other Mustache implementations.

The default implementation always returns false.

Reimplemented from [Mustache::Context](#).

Reimplemented in [CounterContext](#), and [CounterContext](#).

8.77.3.2 `QString QtVariantContext::eval (const QString & key, const QString & _template, Mustache::Renderer * renderer) [virtual]`

Callback used to render a template section with the given `key`. `renderer` will substitute the original section tag with the result of [eval\(\)](#).

The default implementation returns an empty string.

Reimplemented from [Mustache::Context](#).

Reimplemented in [CounterContext](#), and [CounterContext](#).

8.77.3.3 `bool QtVariantContext::isFalse (const QString & key) const [virtual]`

Returns true if the value for `key` is 'false' or an empty list. 'False' values typically include empty strings, the boolean value false etc.

When processing a section Mustache tag, the section is not rendered if the key is false, or for an inverted section tag, the section is only rendered if the key is false.

Implements [Mustache::Context](#).

8.77.3.4 `int QtVariantContext::listCount (const QString & key) const [virtual]`

Returns the number of items in the list value for `key` or 0 if the value for `key` is not a list.

Implements [Mustache::Context](#).

8.77.3.5 `void QtVariantContext::pop () [virtual]`

Exit the current context.

Implements [Mustache::Context](#).

8.77.3.6 void QtVariantContext::push (const QString & key, int index = -1) [virtual]

Set the current context to the value for `key`. If `index` is ≥ 0 , set the current context to the `index`'th value in the list value for `key`.

Implements [Mustache::Context](#).

8.77.3.7 QString QtVariantContext::stringValue (const QString & key) const [virtual]

Returns a string representation of the value for `key` in the current context. This is used to replace a Mustache value tag.

Implements [Mustache::Context](#).

Reimplemented in [CounterContext](#), and [CounterContext](#).

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/libs/qt-mustache/src/mustache.h
- /home/travis/build/FACT-Team/FactDev/src/libs/qt-mustache/src/mustache.cpp

8.78 Models::Rate Class Reference

The [Rate](#) class [Rate](#) of a prestation.

```
#include <rate.h>
```

Public Member Functions

- [Rate](#) ()
Rate::Rate Construct a Rate.
- [Rate](#) (double hourly)
Rate::Rate Construct a Rate with an hourly rate.
- [Rate](#) (int idBilling, int idProject)
Rate::Rate Construct a Rate for the Billing with idBilling as identify and from the project identified by idProject
- void [setDailyRate](#) (const double &)
Rate::setDailyRate Modify the daily rate with the new value.
- void [setHourlyRate](#) (const double &)
Rate::setHourlyRate Modify the hourly rate with the new value.
- double [getDailyRate](#) () const
Rate::getDailyRate Return the daily rate.
- double [getHourlyRate](#) () const
Rate::getHourlyRate Return the hourly rate.
- int [getNbDailyHours](#) () const
Rate::getNbDailyHours Return the number of daily hours.
- double [getLegalRate](#) () const
Rate::getLegalRate Return the legal rate.

8.78.1 Detailed Description

The [Rate](#) class [Rate](#) of a prestation.

Author

Antoine de Roquemaurel

8.78.2 Constructor & Destructor Documentation

8.78.2.1 Models::Rate::Rate (double *hourly*)

[Rate::Rate](#) Construct a [Rate](#) with an hourly rate.

Parameters

<i>hourly</i>	Hourly rate
---------------	-------------

8.78.2.2 Models::Rate::Rate (int *idBilling*, int *idProject*)

[Rate::Rate](#) Construct a [Rate](#) for the [Billing](#) with *idBilling* as identify and from the project identified by *idProject*

Parameters

<i>idBilling</i>	Billing identify
<i>idProject</i>	Project identify

8.78.3 Member Function Documentation

8.78.3.1 double Models::Rate::getDailyRate () const

[Rate::getDailyRate](#) Return the daily rate.

Returns

8.78.3.2 double Models::Rate::getHourlyRate () const

[Rate::getHourlyRate](#) Return the hourly rate.

Returns

8.78.3.3 double Models::Rate::getLegalRate () const

[Rate::getLegalRate](#) Return the legal rate.

Returns

8.78.3.4 int Models::Rate::getNbDailyHours () const

[Rate::getNbDailyHours](#) Return the number of daily hours.


Returns

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/models/rate.h
- /home/travis/build/FACT-Team/FactDev/src/models/rate.cpp

8.79 Databases::RateDatabase Class Reference

Inheritance diagram for Databases::RateDatabase:



Public Member Functions

- void [addRateProject](#) (int idProject, int idBilling, double hourlyRate)
RateDatabase::addRateProject Add a new rate *hourlyRate* to the Project identified by *idProject* of the Billing with *idBilling* as identify.
- double [getRate](#) (const int idBilling, const int idProject) const
RateDatabase::getRate Return the rate of the Project identified by *idProject* of the Billing with *idBilling* as identify.
- void [updateRateProject](#) (int idProject, int idBilling, double hourlyRate)
RateDatabase::updateRateProject Update the current rate by the new *hourlyRate* of the Project identified by *idProject* of the Billing with *idBilling* as identify.

Static Public Member Functions

- static [RateDatabase](#) * [instance](#) () throw (DbException*)
RateDatabase::getInstance Return an instance of [RateDatabase](#).

Additional Inherited Members

8.79.1 Member Function Documentation

8.79.1.1 void Databases::RateDatabase::addRateProject (int *idProject*, int *idBilling*, double *hourlyRate*)

[RateDatabase::addRateProject](#) Add a new rate *hourlyRate* to the Project identified by *idProject* of the Billing with *idBilling* as identify.

Parameters

<i>idProject</i>	Project identify
<i>idBilling</i>	Billing identify
<i>hourlyRate</i>	New hourly rate

8.79.1.2 double Databases::RateDatabase::getRate (const int *idBilling*, const int *idProject*) const

[RateDatabase::getRate](#) Return the rate of the Project identified by *idProject* of the Billing with *idBilling* as identify.

Parameters

<i>idBilling</i>	Billing identify
<i>idProject</i>	Project identify

Returns

Rate of the Project of a Billing

8.79.1.3 RateDatabase * Databases::RateDatabase::instance () throw DbException *) [static]

RateDatabase::getInstance Return an instance of [RateDatabase](#).

Returns

Instance of [RateDatabase](#)

8.79.1.4 void Databases::RateDatabase::updateRateProject (int idProject, int idBilling, double hourlyRate)

[RateDatabase::updateRateProject](#) Update the current rate by the new *hourlyRate* of the Project identified by *id-Project* of the Billing with *idBilling* as identify.

Parameters


<i>idProject</i>	Project identify
<i>idBilling</i>	Billing identify
<i>hourlyRate</i>	New hourly rate

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/database/ratedatabase.h
- /home/travis/build/FACT-Team/FactDev/src/database/ratedatabase.cpp

8.80 RateModelTest Class Reference

Inheritance diagram for RateModelTest:



The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/tests/models/ratemodeltest.h
- /home/travis/build/FACT-Team/FactDev/tests/models/ratemodeltest.cpp

8.81 Gui::Widgets::RateWidget Class Reference

Class for display Rate.

```
#include <ratewidget.h>
```

Inheritance diagram for Gui::Widgets::RateWidget:



Public Slots

- void [setDailyRate](#) ()
setDailyRate Set a new value for the daily rate
- void [setHourlyRate](#) ()
setHourlyRate Set a new value for the hourly rate

Public Member Functions

- [RateWidget](#) (QWidget *parent=0)
RateWidget::RateWidget Construct a rate widget.
- void [initRate](#) ()
RateWidget::initRate Initialize the rate.
- void [setWidgetDailyRateValue](#) (double value)
RateWidget::setWidgetDailyRateValue Modify the value of the daily rate spin box component.
- double [getDailyRate](#) ()
RateWidget::getDailyRate Get the daily rate.
- double [getHourlyRate](#) ()
RateWidget::getHourlyRate Get the hourly rate.
- void [setWidgetHourlyRateValue](#) (double value)
RateWidget::setWidgetHourlyRateValue Modify the value of the hourly rate spin box component.
- void [updateConversionRate](#) ()
updateConversionRate Update daily rate or hourly rate

8.81.1 Detailed Description

Class for display Rate.

Author

Florent Berbie

8.81.2 Constructor & Destructor Documentation

8.81.2.1 [Gui::Widgets::RateWidget::RateWidget \(QWidget * parent = 0 \)](#) `[explicit]`

[RateWidget::RateWidget](#) Construct a rate widget.

Parameters

<i>parent</i>	The QWidget parent
---------------	--------------------

8.81.3 Member Function Documentation

8.81.3.1 [double Gui::Widgets::RateWidget::getDailyRate \(\)](#)

[RateWidget::getDailyRate](#) Get the daily rate.

Returns

The daily rate

8.81.3.2 `double Gui::Widgets::RateWidget::getHourlyRate ()`

[RateWidget::getHourlyRate](#) Get the hourly rate.

Returns

The hourly rate

8.81.3.3 `void Gui::Widgets::RateWidget::setDailyRate () [slot]`

`setDailyRate` Set a new value for the daily rate

Parameters

<i>dailyRate</i>	The new daily rate
------------------	--------------------

8.81.3.4 `void Gui::Widgets::RateWidget::setHourlyRate () [slot]`

`setHourlyRate` Set a new value for the hourly rate

Parameters

<i>hourlyRate</i>	The new hourly rate
-------------------	---------------------

8.81.3.5 `void Gui::Widgets::RateWidget::setWidgetDailyRateValue (double value)`

[RateWidget::setWidgetDailyRateValue](#) Modify the *value* of the daily rate spin box component.

Parameters

<i>value</i>	New Value
--------------	-----------

8.81.3.6 `void Gui::Widgets::RateWidget::setWidgetHourlyRateValue (double value)`

[RateWidget::setWidgetHourlyRateValue](#) Modify the *value* of the hourly rate spin box component.

Parameters

<i>value</i>	New value
--------------	-----------

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/ratewidget.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/ratewidget.cpp

8.82 Mustache::Renderer Class Reference

```
#include <mustache.h>
```

Public Member Functions

- QString [render](#) (const QString &_template, [Context](#) *context)
- QString [error](#) () const
- int [errorPos](#) () const

- QString [errorPartial](#) () const
- void [setTagMarkers](#) (const QString &startMarker, const QString &endMarker)

8.82.1 Detailed Description

Renders Mustache templates, replacing mustache tags with values from a provided context.

8.82.2 Member Function Documentation

8.82.2.1 QString Renderer::error () const

Returns a message describing the last error encountered by the previous [render\(\)](#) call.

8.82.2.2 QString Renderer::errorPartial () const

Returns the name of the partial where the error occurred, or an empty string if the error occurred in the main template.

8.82.2.3 int Renderer::errorPos () const

Returns the position in the template where the last error occurred when rendering the template or -1 if no error occurred.

If the error occurred in a partial template, the returned position is the offset in the partial template.

8.82.2.4 QString Renderer::render (const QString &_template, Context * context)

Render a Mustache template, using `context` to fetch the values used to replace Mustache tags.

8.82.2.5 void Renderer::setTagMarkers (const QString &startMarker, const QString &endMarker)

Sets the default tag start and end markers. This can be overridden within a template.

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/libs/qt-mustache/src/mustache.h
- /home/travis/build/FACT-Team/FactDev/src/libs/qt-mustache/src/mustache.cpp

8.83 Models::Search Class Reference

The [Search](#) class.

```
#include <search.h>
```

Public Member Functions

- [Search](#) ()
[Search::Search](#) Construct a search.
- [~Search](#) ()
[Search::Search](#) Destruct a search.
- QString [getFilter](#) ()

- Search::getFilter* Return the search filter.
- void **filterOnVarcharElements** (QString &filter, const QStringList list, QString element)
 - Search::filterOnVarcharElements* Search, for each word of the list from the filter, if it corresponds to the element in the database.
 - void **filterOnNumberElements** (QString &filter, const QStringList list, QString element)
 - Search::filterOnNumberElements* Search, for each number of the list from the filter, if it corresponds to the element in the database.
 - void **filterOnCompany** (QString &filter, const QStringList list)
 - Search::filterOnCompany* Search all companies contained in the list of the filter
 - void **filterOnReferentLastname** (QString &filter, const QStringList list)
 - Search::filterOnReferentLastname* Search all referents last name contained in the list of the filter
 - void **filterOnProjects** (QString &filter, const QStringList list)
 - Search::filterOnProjects* Search all projects contained in the list of the filter
 - void **filterOnContributories** (QString &filter, const QStringList list)
 - Search::filterOnContributories* Search all contributories contained in the list of the filter
 - void **filterOnBillsOrQuotes** (QString &filter, const QStringList list)
 - Search::filterOnBillsOrQuotes* Search all bills or quotes which are contained in the list of the filter
 - void **filterOnCustomersWithoutProject** (QString &filter, const QStringList list)
 - Search::filterOnCustomersWithoutProject* Search all customers which are contained in the list of the filter
 - bool **getSearchInCompanies** () const
 - Search::getSearchInCompanies* Return if we search a company.
 - void **setSearchInCompanies** (bool searchInCompanies)
 - Search::setSearchInCompanies* Modify the filter of companies search.
 - bool **getSearchInReferentLastname** () const
 - Search::getSearchInReferentLastname* Return if we search a Last name referent.
 - void **setSearchInReferentLastname** (bool searchInReferentLastname)
 - Search::setSearchInReferentLastname* Modify the filter of referents last name search.
 - bool **getSearchInProjects** () const
 - Search::getSearchInProjects* Return TRUE if it exists one or more projets in database.
 - void **setSearchInProjects** (bool searchInProjects)
 - Search::setSearchInProjects* Modify the filter of projects search.
 - bool **searchInContributories** () const
 - Search::getSearchInContributories* Return TRUE if it exists one or more projets in database.
 - void **setSearchInContributories** (bool searchInContributories)
 - Search::setSearchInContributories* Modify the filter of contributories search.
 - bool **getSearchInBillsQuotes** () const
 - Search::searchInBillsQuotes* Return TRUE if it exists one or more bills or quotes in database.
 - void **setSearchInBillsQuotes** (bool searchInBillsQuotes)
 - Search::setSearchInBillsQuotes* Modify the filter of bills and quotes search.
 - bool **getGroupFilter** () const
 - Search::getGroupFilter* Return if the filter is activated.
 - void **setGroupFilter** (bool getGroupFilter)
 - Search::setGroupFilter* Modify if we active search filter.
 - QString **getText** () const
 - Search::getText* Return sql portion of filter.
 - void **setText** (const QString &getText)
 - Search::setText* Modify sql portion.

8.83.1 Detailed Description

The [Search](#) class.

Author

Antoine de Roquemaurel
Florent Berbie

8.83.2 Member Function Documentation

8.83.2.1 void Models::Search::filterOnBillsOrQuotes (QString & *filter*, const QStringList *list*)

[Search::filterOnBillsOrQuotes](#) [Search](#) all bills or quotes which are contained in the *list* of the *filter*

Parameters

<i>filter</i>	Text inputed in searchbar
<i>list</i>	List of bills or quotes

8.83.2.2 void Models::Search::filterOnCompany (QString & *filter*, const QStringList *list*)

[Search::filterOnCompany](#) [Search](#) all companies contained in the *list* of the *filter*

Parameters

<i>filter</i>	Text inputed in searchbar
<i>list</i>	List of companies

8.83.2.3 void Models::Search::filterOnContributories (QString & *filter*, const QStringList *list*)

[Search::filterOnContributories](#) [Search](#) all contributories contained in the *list* of the *filter*

Parameters

<i>filter</i>	Text inputed in searchbar
<i>list</i>	List of contributories

8.83.2.4 void Models::Search::filterOnCustomersWithoutProject (QString & *filter*, const QStringList *list*)

[Search::filterOnCustomersWithoutProject](#) [Search](#) all customers which are contained in the *list* of the *filter*

Parameters

<i>filter</i>	Text inputed in searchbar
<i>list</i>	List of bills or quotes

8.83.2.5 void Models::Search::filterOnNumberElements (QString & *filter*, const QStringList *list*, QString *element*)

[Search::filterOnNumberElements](#) [Search](#), for each number of the *list* from the *filter*, if it corresponds to the *element* in the database.

Parameters

<i>filter</i>	Text inputed in the searchbar
<i>list</i>	List of numbers from the <i>filter</i>
<i>element</i>	Attribute name into the database

8.83.2.6 void Models::Search::filterOnProjects (QString & *filter*, const QStringList *list*)

[Search::filterOnProjects](#) Search all projects contained in the *list* of the *filter*

Parameters

<i>filter</i>	Text inputed in searchbar
<i>list</i>	List of projects

8.83.2.7 void Models::Search::filterOnReferentLastname (QString & *filter*, const QStringList *list*)

[Search::filterOnReferentLastname](#) Search all referents last name contained in the *list* of the *filter*

Parameters

<i>filter</i>	Text inputed in searchbar
<i>list</i>	List of referent last name

8.83.2.8 void Models::Search::filterOnVarcharElements (QString & *filter*, const QStringList *list*, QString *element*)

[Search::filterOnVarcharElements](#) Search, for each word of the *list* from the *filter*, if it corresponds to the *element* in the database.

Parameters

<i>filter</i>	Text inputed in the searchbar
<i>list</i>	List of words from the <i>filter</i>
<i>element</i>	Attribute name into the database

8.83.2.9 QString Models::Search::getFilter ()

[Search::getFilter](#) Return the search filter.

Returns

filter selected (sql portion)

8.83.2.10 bool Models::Search::getGroupFilter () const

[Search::getGroupFilter](#) Return if the filter is activated.

Returns

boolean if search filter is activated

8.83.2.11 bool Models::Search::getSearchInBillsQuotes () const

[Search::searchInBillsQuotes](#) Return TRUE if it exists one or more bills or quotes in database.

Returns

boolean if bills or quotes are existing

8.83.2.12 `bool Models::Search::getSearchInCompanies () const`

[Search::getSearchInCompanies](#) Return if we search a company.

Returns

boolean if we search a company

8.83.2.13 `bool Models::Search::getSearchInProjects () const`

[Search::getSearchInProjects](#) Return TRUE if it exists one or more projets in database.

Returns

boolean if project are existing

8.83.2.14 `bool Models::Search::getSearchInReferentLastname () const`

[Search::getSearchInReferentLastname](#) Return if we search a Last name referent.

Returns

boolean if search concerns the last name of referent

8.83.2.15 `QString Models::Search::getText () const`

[Search::getText](#) Return sql portion of filter.

Returns

QString the sql portion

8.83.2.16 `bool Models::Search::searchInContributories () const`

[Search::getSearchInContributories](#) Return TRUE if it exists one or more projets in database.

Returns

boolean if contributories are existing

8.83.2.17 `void Models::Search::setGroupFilter (bool getGroupFilter)`

[Search::setGroupFilter](#) Modify if we active search filter.

Parameters

<i>getGroupFilter</i>	Get if filter is actived
-----------------------	--------------------------

8.83.2.18 void Models::Search::setSearchInBillsQuotes (bool *searchInBillsQuotes*)

[Search::setSearchInBillsQuotes](#) Modify the filter of bills and quotes search.

Parameters

<i>searchInBills-Quotes</i>	Search in bills or quotes which are concerned
-----------------------------	---

8.83.2.19 void Models::Search::setSearchInCompanies (bool *searchInCompanies*)

[Search::setSearchInCompanies](#) Modify the filter of companies search.

Parameters

<i>getSearchIn-Companies</i>	Search in companies is concerned
------------------------------	--

8.83.2.20 void Models::Search::setSearchInContributories (bool *searchInContributories*)

[Search::setSearchInContributories](#) Modify the filter of contributories search.

Parameters

<i>searchIn-Contributories</i>	Search in contributories which are concerned
--------------------------------	--

8.83.2.21 void Models::Search::setSearchInProjects (bool *searchInProjects*)

[Search::setSearchInProjects](#) Modify the filter of projects search.

Parameters

<i>searchInProjects</i>	Search in projects which are concerned
-------------------------	--

8.83.2.22 void Models::Search::setSearchInReferentLastname (bool *searchInReferentLastname*)

[Search::setSearchInReferentLastname](#) Modify the filter of referents last name search.

Parameters

<i>searchIn-Referent-Lastname</i>	Search in referents last name which are concerned
-----------------------------------	---

8.83.2.23 void Models::Search::setText (const QString & *getText*)

[Search::setText](#) Modify sql portion.

Parameters

<code>getText</code>	Get sql portion
----------------------	-----------------

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/models/search.h
- /home/travis/build/FACT-Team/FactDev/src/models/search.cpp

8.84 Gui::Docks::SearchDock Class Reference

The [SearchDock](#) class Dock which contains search bar.

```
#include <searchdock.h>
```

Inheritance diagram for Gui::Docks::SearchDock:



Public Slots

- void [search](#) (QString text)
[SearchDock::search](#) Search elements in database which correspond to the text

Signals

- void [textChanged](#) (QString text)
[SearchDock::textChanged](#) Current text changed by text

Public Member Functions

- [SearchDock](#) (QWidget *parent=0, Qt::WindowFlags flags=0)
[SearchDock::SearchDock](#) Construct a [SearchDock](#).

8.84.1 Detailed Description

The [SearchDock](#) class Dock which contains search bar.

8.84.2 Constructor & Destructor Documentation

8.84.2.1 [Gui::Docks::SearchDock::SearchDock](#) ([QWidget](#) * *parent* = 0, [Qt::WindowFlags](#) *flags* = 0) [explicit]

[SearchDock::SearchDock](#) Construct a [SearchDock](#).

Parameters

<i>parent</i>	Widget Parent
<i>flags</i>	Window flag

8.84.3 Member Function Documentation

8.84.3.1 void Gui::Docks::SearchDock::search (QString *text*) [slot]

[SearchDock::search](#) Search elements in database which correspond to the *text*

Parameters

<i>text</i>	Element to search
-------------	-------------------

8.84.3.2 void Gui::Docks::SearchDock::textChanged (QString *text*) [signal]

[SearchDock::textChanged](#) Current text changed by *text*

Parameters


<i>text</i>	New text
-------------	----------

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/docks/searchdock.h
- /home/travis/build/FACT-Team/FactDev/src/gui/docks/searchdock.cpp

8.85 searchTest Class Reference

Inheritance diagram for searchTest:



The documentation for this class was generated from the following files:


- /home/travis/build/FACT-Team/FactDev/tests/models/searchtest.h
- /home/travis/build/FACT-Team/FactDev/tests/models/searchtest.cpp

8.86 Gui::Widgets::searchWidget Class Reference

Class for search in database.

```
#include <searchwidget.h>
```

Inheritance diagram for Gui::Widgets::searchWidget:



Public Slots

- void [search](#) (QString toSearch)
searchWidget::launch a search
- void [getCustomerData](#) ()
searchWidget::getCustomerData Return data on the customer selected in the QTableView and display this data (First-name, Lastname, Company)

Signals

- void [selectCustomer](#) ()
searchWidget::selectCustomer Signal that the Customer selected has changed

Public Member Functions

- [searchWidget](#) (QWidget *parent=0)
searchWidget::searchWidget Construct a search widget
- int [getCurrentCustomerId](#) ()
searchWidget::getCurrentCustomerId Return the id of the customer selected in the table
- bool [isCustomerSelected](#) () const
searchWidget::isCustomerSelected Return TRUE if a customer is selected, else FALSE
- void [selectCustomer](#) (int id)
searchWidget::selectCustomer Select the Customer with it id
- int [getIdCustomer](#) () const
searchWidget::getIdCustomer Return the Customer id of the Customer line selected
- void [setIdCustomer](#) (int idCustomer)
searchWidget::setIdCustomer Change the customer id by the new idCustomer

8.86.1 Detailed Description

Class for search in database.

Author

Antoine de Roquemaurel

8.86.2 Constructor & Destructor Documentation

8.86.2.1 [Gui::Widgets::searchWidget::searchWidget \(QWidget * parent = 0 \)](#) [explicit]

[searchWidget::searchWidget](#) Construct a search widget

Parameters

<i>parent</i>	The QWidget parent
---------------	--------------------

8.86.3 Member Function Documentation

8.86.3.1 `int Gui::Widgets::searchWidget::getCurrentCustomerId ()`

[searchWidget::getCurrentCustomerId](#) Return the id of the customer selected in the table

Returns

id of the current customer

8.86.3.2 `int Gui::Widgets::searchWidget::getIdCustomer () const`

[searchWidget::getIdCustomer](#) Return the Customer id of the Customer line selected

Returns

The Customer ID

8.86.3.3 `bool Gui::Widgets::searchWidget::isCustomerSelected () const`

[searchWidget::isCustomerSelected](#) Return TRUE if a customer is selected, else FALSE

Returns

boolean

8.86.3.4 `void Gui::Widgets::searchWidget::search (QString toSearch) [slot]`

`searchWidget::launch` a search

Parameters

<i>toSearch</i>	The value to search
-----------------	---------------------

8.86.3.5 `void Gui::Widgets::searchWidget::selectCustomer (int id)`

[searchWidget::selectCustomer](#) Select the Customer with it *id*

Parameters

<i>id</i>	Customer ID
-----------	-------------

8.86.3.6 `void Gui::Widgets::searchWidget::setIdCustomer (int idCustomer)`

[searchWidget::setIdCustomer](#) Change the customer id by the new *idCustomer*

Parameters

<i>idCustomer</i>	Customer id
-------------------	-------------

The documentation for this class was generated from the following files:


- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/searchwidget.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/searchwidget.cpp

8.87 Gui::Dialogs::StartedWindowsDialog Class Reference

The [StartedWindowsDialog](#) class Construct a Windows for the first begin.

```
#include <startedwindowsdialog.h>
```

Inheritance diagram for Gui::Dialogs::StartedWindowsDialog:



Public Slots

- void [checkFields](#) ()
StartedWindowsDialog::checkFields Check all fields of dialog components.
- void [backToPage2](#) ()
StartedWindowsDialog::backToPage2 Return to the second page.
- void [nextToPage2](#) ()
StartedWindowsDialog::nextToPage2 Go to the second page.
- void [nextToPage3](#) ()
StartedWindowsDialog::nextToPage3 Go to the third page.
- void [databaseTypeChanged](#) (const int index)
StartedWindowsDialog::databaseTypeChanged Listener on the Database type combobox.
- void [updateNextButton](#) ()
StartedWindowsDialog::updateNextButton Check if the next button is enabled.
- void [accept](#) ()
StartedWindowsDialog::accept Valid data inputed by user and add these data in Database.

Public Member Functions

- [StartedWindowsDialog](#) (QWidget *parent=0)
StartedWindowsDialog::StartedWindowsDialog Construct a [StartedWindowsDialog](#).
- void [fillFields](#) ()
StartedWindowsDialog::fillFields Fill line edits with the data of the user.
- QPixmap [getImage](#) (QString path, int width=256, int height=256)
StartedWindowsDialog::getImage Return a scaled image from the icon specified by it path. The image returned has a resolution of width*height (default 256*256)
- bool [isDatabaseTypeValid](#) ()
StartedWindowsDialog::isDatabaseTypeValid Return TRUE if settings of database type is valid else return FALSE.
- bool [isDatabaseCentralized](#) ()
StartedWindowsDialog::isDatabaseCentralized Return TRUE if the current type of database is centralized else FALSE.

8.87.1 Detailed Description

The [StartedWindowsDialog](#) class Construct a Windows for the first begin.

Author

Florent Berbie

See Also

[DatabaseSettingsWidget](#)

8.87.2 Constructor & Destructor Documentation

8.87.2.1 [Gui::Dialogs::StartedWindowsDialog::StartedWindowsDialog \(QWidget * *parent* = 0 \)](#) `[explicit]`

[StartedWindowsDialog::StartedWindowsDialog](#) Construct a [StartedWindowsDialog](#).

Parameters

<i>parent</i>	QWidget parent
---------------	----------------

8.87.3 Member Function Documentation

8.87.3.1 `void Gui::Dialogs::StartedWindowsDialog::databaseTypeChanged (const int index)` `[slot]`

[StartedWindowsDialog::databaseTypeChanged](#) Listener on the Database type combobox.

Parameters

<i>index</i>	Current index selected
--------------	------------------------

8.87.3.2 `QPixmap Gui::Dialogs::StartedWindowsDialog::getImage (QString path, int width = 256, int height = 256)`

[StartedWindowsDialog::getImage](#) Return a scaled image from the icon specified by it *path*. The image returned has a resolution of *width*height* (default 256*256)

Parameters

<i>path</i>	Icon path
<i>width</i>	Icon width
<i>height</i>	Icon height

Returns

Scaled image

8.87.3.3 `bool Gui::Dialogs::StartedWindowsDialog::isDatabaseCentralized ()`

[StartedWindowsDialog::isDatabaseCentralized](#) Return TRUE if the current type of database is centralized else FALSE.

Returns

boolean

8.87.3.4 **bool Gui::Dialogs::StartedWindowsDialog::isDatabaseTypeValid ()**

[StartedWindowsDialog::isDatabaseTypeValid](#) Return TRUE if settings of database type is valid else return FALSE.

Returns


boolean on the database type validity

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/dialogs/startedwindowsdialog.h
- /home/travis/build/FACT-Team/FactDev/src/gui/dialogs/startedwindowsdialog.cpp

8.88 StatisticModelTest Class Reference

Inheritance diagram for StatisticModelTest:



The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/tests/models/statisticmodeltest.h
- /home/travis/build/FACT-Team/FactDev/tests/models/statisticmodeltest.cpp

8.89 Models::Statistics Class Reference**Static Public Member Functions**

- static QPair< int, double > [getTurnoverBetweenDates](#) (QDate begin, QDate end)
getTurnoverBetweenDates Compute the turnover betweenend 2 dates
- static double [getGlobalTurnover](#) ()
Get the global turnover.

8.89.1 Member Function Documentation**8.89.1.1 double Statistics::getGlobalTurnover () [static]**

Get the global turnover.

Returns

The global turnover

8.89.1.2 QPair< int, double > Statistics::getTurnoverBetweenDates (QDate *begin*, QDate *end*) [static]

[getTurnoverBetweenDates](#) Compute the turnover betweenend 2 dates

Parameters

<i>begin</i>	The beginning date
<i>end</i>	The ending date

Returns

A Qpair who contains the number of billing and their costs

The documentation for this class was generated from the following files:


- /home/travis/build/FACT-Team/FactDev/src/models/statistics.h
- /home/travis/build/FACT-Team/FactDev/src/models/statistics.cpp

8.90 Gui::Dialogs::StatisticsDialog Class Reference

The [StatisticsDialog](#) class window to have global informations or about a customer.

```
#include <statisticsdialog.h>
```

Inheritance diagram for Gui::Dialogs::StatisticsDialog:



Public Member Functions

- [StatisticsDialog](#) (bool global=true, int idCustomer=0, QWidget *parent=0)
Construct a windows [StatisticsDialog](#).
- QString [singularPlural](#) (int nb)
Get the correct terminaison.

8.90.1 Detailed Description

The [StatisticsDialog](#) class window to have global informations or about a customer.

8.90.2 Constructor & Destructor Documentation

8.90.2.1 [Gui::Dialogs::StatisticsDialog::StatisticsDialog](#) (bool *global* = true, int *idCustomer* = 0, QWidget * *parent* = 0)
[explicit]

Construct a windows [StatisticsDialog](#).

Parameters

<i>global</i>	if it's the global stats or customer stats
<i>idCustomer</i>	the id of the Customer

8.90.3 Member Function Documentation

8.90.3.1 QString Gui::Dialogs::StatisticsDialog::singularPlural (int *nb*)

Get the correct terminaison.

Parameters

<i>nb</i>	
-----------	--

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/dialogs/statisticsdialog.h
- /home/travis/build/FACT-Team/FactDev/src/gui/dialogs/statisticsdialog.cpp

8.91 Utils::String Class Reference

The Utils class.

```
#include <string.h>
```

Static Public Member Functions

- static QString [firstLetterToUpper](#) (QString s)
firstLetterToUpper Put the first letter of a string in capslock

8.91.1 Detailed Description

The Utils class.

Author

Antoine de Roquemaurel

8.91.2 Member Function Documentation

8.91.2.1 QString Utils::String::firstLetterToUpper (QString s) [static]

firstLetterToUpper Put the first letter of a string in capslock

Parameters

<i>s</i>	The string to display
----------	-----------------------

Returns


The new string with caps

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/Utils/string.h
- /home/travis/build/FACT-Team/FactDev/src/Utils/string.cpp

8.92 StringTest Class Reference

Inheritance diagram for StringTest:



The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/tests/utis/stringtest.h
- /home/travis/build/FACT-Team/FactDev/tests/utis/stringtest.cpp

8.93 Mustache::Tag Struct Reference

```
#include <mustache.h>
```

Public Types

- enum [Type](#) {
 Null, **Value**, [SectionStart](#), [InvertedSectionStart](#),
 [SectionEnd](#), [Partial](#), [Comment](#), [SetDelimiter](#) }
- enum **EscapeMode** { **Escape**, **Unescape**, **Raw** }

Public Attributes

- [Type](#) **type**
- QString **key**
- int **start**
- int **end**
- EscapeMode **escapeMode**

8.93.1 Detailed Description

Holds properties of a tag in a mustache template.

8.93.2 Member Enumeration Documentation

8.93.2.1 enum Mustache::Tag::Type

Enumerator

- SectionStart** A {{key}} or {{{key}}} tag.
- InvertedSectionStart** A {{#section}} tag.
- SectionEnd** An {{^inverted-section}} tag.
- Partial** A {{/section}} tag.
- Comment** A {{^partial}} tag.
- SetDelimiter** A {{! comment }} tag. A {{=<% %>=}} tag

The documentation for this struct was generated from the following file:

- /home/travis/build/FACT-Team/FactDev/src/libs/qt-mustache/src/mustache.h

8.94 testadder Class Reference

The documentation for this class was generated from the following file:

- /home/travis/build/FACT-Team/FactDev/tests/CTestRunner/testadder.h

8.95 TestAdder< T > Class Template Reference

Public Member Functions


- **TestAdder** (const QString &name)

The documentation for this class was generated from the following file:

- /home/travis/build/FACT-Team/FactDev/tests/CTestRunner/testadder.cpp

8.96 TestMustache Class Reference

Inheritance diagram for TestMustache:



The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/libs/qt-mustache/tests/test_mustache.h
- /home/travis/build/FACT-Team/FactDev/src/libs/qt-mustache/tests/test_mustache.cpp

8.97 TestRunner Class Reference

Public Member Functions

- template<typename T >
char **RegisterTest** (QString name)
- int **RunAll** ()

Static Public Member Functions

- static [TestRunner](#) & **Instance** ()

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/tests/CTestRunner/testrunner.h
- /home/travis/build/FACT-Team/FactDev/tests/CTestRunner/testrunner.cpp

8.98 Generator::TexGenerator Class Reference

The [TexGenerator](#) class Generate a LaTeX file.

```
#include <texgenerator.h>
```


Public Member Functions

- [TexGenerator](#) (QString tpl)
[TexGenerator::TexGenerator](#) Construct a [TexGenerator](#).
- void [generate](#) (QVariantHash data, QString path)
[TexGenerator::generate](#) Generate a LaTeX file into a file specified by the path and which contains data

8.98.1 Detailed Description

The [TexGenerator](#) class Generate a LaTeX file.

8.98.2 Constructor & Destructor Documentation

8.98.2.1 Generator::TexGenerator::TexGenerator (QString *tpl*)

[TexGenerator::TexGenerator](#) Construct a [TexGenerator](#).

Parameters

<i>tpl</i>	Template LaTeX to apply
------------	-------------------------

8.98.3 Member Function Documentation

8.98.3.1 void Generator::TexGenerator::generate (QVariantHash *data*, QString *path*)

[TexGenerator::generate](#) Generate a LaTeX file into a file specified by the *path* and which contains *data*

Parameters

<i>data</i>	Data to integrate in the file
<i>path</i>	Path of the out file

The documentation for this class was generated from the following files:


- /home/travis/build/FACT-Team/FactDev/src/generator/texgenerator.h
- /home/travis/build/FACT-Team/FactDev/src/generator/texgenerator.cpp

8.99 Gui::Widgets::Delegates::TextareaDelegate Class Reference

The [TextareaDelegate](#) class.

```
#include <textareadelegate.h>
```

Inheritance diagram for Gui::Widgets::Delegates::TextareaDelegate:



Public Member Functions

- [TextareaDelegate](#) (QWidget *parent=0)

[TextareaDelegate::TextareaDelegate.](#)

- void [setModelData](#) (QWidget *editor, QAbstractItemModel *model, const QModelIndex &index) const

[TextareaDelegate::setModelData](#) Sets the data model from content in editor.

- void [updateEditorGeometry](#) (QWidget *editor, const QStyleOptionViewItem &option, const QModelIndex &) const

[TextareaDelegate::updateEditorGeometry](#) Update the editor for the item specified by index according to the style option given.

- QWidget * [createEditor](#) (QWidget *parent, const QStyleOptionViewItem &, const QModelIndex &) const

[TextareaDelegate::createEditor](#) Return a QTextEdit specified by index item defined by the parent widget and style option which are used to control how the editor widgets appears.

- void [setEditorData](#) (QWidget *editor, const QModelIndex &index) const

[TextareaDelegate::setEditorData](#) Sets the data to be displayed and edited by the editor from the data model item specified by the model index

8.99.1 Detailed Description

The [TextareaDelegate](#) class.

Author

Antoine de Roquemaurel

8.99.2 Constructor & Destructor Documentation

8.99.2.1 Gui::Widgets::Delegates::TextareaDelegate::TextareaDelegate (QWidget * *parent* = 0)

[TextareaDelegate::TextareaDelegate.](#)

Parameters

<i>parent</i>	
---------------	--

8.99.3 Member Function Documentation

8.99.3.1 QWidget * Gui::Widgets::Delegates::TextareaDelegate::createEditor (QWidget * *parent*, const QStyleOptionViewItem &, const QModelIndex &) const

[TextareaDelegate::createEditor](#) Return a QTextEdit specified by *index* item defined by the *parent* widget and style *option* which are used to control how the editor widgets appears.

Parameters

<i>parent</i>	Widget parent
<i>option</i>	Option style
<i>index</i>	Index for editing

Returns

[TextareaDelegate](#)

8.99.3.2 void Gui::Widgets::Delegates::TextareaDelegate::setEditorData (QWidget * *editor*, const QModelIndex & *index*) const

[TextareaDelegate::setEditorData](#) Sets the data to be displayed and edited by the *editor* from the data model item specified by the model *index*

Parameters

<i>editor</i>	Data edited
<i>index</i>	Index of the model to edit

8.99.3.3 void Gui::Widgets::Delegates::TextareaDelegate::setModelData (QWidget * *editor*, QAbstractItemModel * *model*, const QModelIndex & *index*) const

[TextareaDelegate::setModelData](#) Sets the data model from content in editor.

Parameters

<i>editor</i>	Data edited
<i>index</i>	Index of the model to edit

8.99.3.4 void Gui::Widgets::Delegates::TextareaDelegate::updateEditorGeometry (QWidget * *editor*, const QStyleOptionViewItem & *option*, const QModelIndex &) const

[TextareaDelegate::updateEditorGeometry](#) Update the *editor* for the item specified by *index* according to the style *option* given.

Parameters

<i>editor</i>	Editor widget to update
<i>option</i>	Style option
<i>index</i>	Item index

The documentation for this class was generated from the following files:


- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/delegates/textareadelegate.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/delegates/textareadelegate.cpp

8.100 Gui::Widgets::Delegates::UnitComboDelegate Class Reference

The [UnitComboDelegate](#) class.

```
#include <unitcombodelegate.h>
```

Inheritance diagram for Gui::Widgets::Delegates::UnitComboDelegate:



Public Member Functions

- [UnitComboDelegate](#) (QObject *parent=0)
[UnitComboDelegate::UnitComboDelegate](#).
- QWidget * [createEditor](#) (QWidget *parent, const QStyleOptionViewItem &option, const QModelIndex &index) const

[*UnitComboDelegate::createEditor*](#) Return a *ComboBox* specified by *index* item defined by the parent widget and style option which are used to control how the editor widgets appears.

- void [*paint*](#) (QPainter *painter, const QStyleOptionViewItem &option, const QModelIndex &index) const

[*UnitComboDelegate::paint*](#) Renders the delegate using the given painter and style option for the item specified by *index*

8.100.1 Detailed Description

The [*UnitComboDelegate*](#) class.

8.100.2 Constructor & Destructor Documentation

8.100.2.1 Gui::Widgets::Delegates::UnitComboDelegate::UnitComboDelegate (QObject * parent = 0)

[*UnitComboDelegate::UnitComboDelegate*](#).

Parameters

<i>parent</i>	
---------------	--

8.100.3 Member Function Documentation

8.100.3.1 QWidget * Gui::Widgets::Delegates::UnitComboDelegate::createEditor (QWidget * parent, const QStyleOptionViewItem & option, const QModelIndex & index) const [virtual]

[*UnitComboDelegate::createEditor*](#) Return a *ComboBox* specified by *index* item defined by the *parent* widget and style *option* which are used to control how the editor widgets appears.

Parameters

<i>parent</i>	Widget parent
<i>option</i>	Option style
<i>index</i>	Index for editing

Returns

ComboBox

Implements [*Gui::Widgets::Delegates::ComboBoxDelegate*](#).

8.100.3.2 void Gui::Widgets::Delegates::UnitComboDelegate::paint (QPainter * painter, const QStyleOptionViewItem & option, const QModelIndex & index) const [virtual]

[*UnitComboDelegate::paint*](#) Renders the delegate using the given *painter* and style *option* for the item specified by *index*

Parameters

<i>parent</i>	Widget parent
<i>option</i>	Option style
<i>index</i>	Index for editing

Implements [*Gui::Widgets::Delegates::ComboBoxDelegate*](#).

The documentation for this class was generated from the following files:


- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/delegates/unitcombodelegate.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/delegates/unitcombodelegate.cpp

8.101 Models::User Class Reference

The `User` class `User` of it application.

```
#include <user.h>
```

Inheritance diagram for Models::User:



Public Member Functions

- `User ()`
User::User. Construct an User.
- `User (int id)`
User::User. Construct a User with the identify id
- `void commit ()`
User::commit Update user data in User table on the database.
- `void hydrat (int id=1)`
User::hydrat Get data of the user who is specified by id from the database.
- `void remove ()`
remove Remove the current User
- `QVariantHash getDataMap ()`
getDataMap Get all data of model with a HashMap key/value
- `void updateFolders (void)`
MainWindow::updateFolders Make directories which contain quotes and billings. Directories are the same than theirs of the Tree organisation (without Projects).
- `QString getTitle () const`
User::getTitle Return a short description of User (company) activity.
- `void setTitle (const QString &title)`
User::setTitle Modify the user/company activities description
- `QString getNoSiret () const`
User::getNoSiret Return the SIRET number (company registration number)
- `void setNoSiret (const QString &noSiret)`
User::setNoSiret Modify the SIRET number (company registration number) noSiret
- `QString getWorkspaceName () const`
User::getWorkspaceName Return the name of the workspace user.
- `void setWorkspaceName (const QString &workspaceName)`
User::setWorkspaceName Change the current workspace name by the new workspaceName
- `QString getWorkspacePath () const`
User::getWorkspacePath Return the path of the workspace user.
- `void setWorkspacePath (const QString &workspacePath)`
User::setWorkspacePath Change the current workspace path by the new workspacePath
- `bool operator== (const User &u)`
User::operator == Re-define the operator "==" to compare if the current User is the same to the other User c Return TRUE if both Users are the same, else FALSE.
- `bool operator!= (const User &u)`
User::operator != Re-define the operator "!=" to compare if the current User is differnt to the other User c Return TRUE if both Users are different, else FALSE.

Additional Inherited Members

8.101.1 Detailed Description

The [User](#) class [User](#) of it application.

Author

Florent Berbie

8.101.2 Constructor & Destructor Documentation

8.101.2.1 Models::User::User (int *id*)

[User::User](#). Construct a [User](#) with the identify *id*

Parameters

<i>id</i>	User <i>id</i>
-----------	--------------------------------

8.101.3 Member Function Documentation

8.101.3.1 QVariantHash Models::User::getDataMap () [virtual]

getDataMap Get all data of model with a HashMap key/value

Returns

Model's data

Implements [Models::IModel](#).

8.101.3.2 QString Models::User::getNoSiret () const

[User::getNoSiret](#) Return the SIRET number (company registration number)

Returns

SIRET number

8.101.3.3 QString Models::User::getTitle () const

[User::getTitle](#) Return a short description of [User](#) (company) activity.

Returns

a short description of user (company) activity

8.101.3.4 QString Models::User::getWorkspaceName () const

[User::getWorkspaceName](#) Return the name of the workspace user.

Returns

workspace name

8.101.3.5 QString Models::User::getWorkspacePath () const

[User::getWorkspacePath](#) Return the path of the workspace user.

Returns

workspace path

8.101.3.6 void Models::User::hydrat (int *id* = 1) [virtual]

[User::hydrat](#) Get data of the user who is specified by *id* from the database.

Parameters

<i>id</i>	User identify
-----------	-------------------------------

Implements [Models::IModel](#).

8.101.3.7 bool Models::User::operator!= (const User & *u*)

[User::operator !=](#) Re-define the operator "!=" to compare if the current [User](#) is differnt to the other [User](#) c Return TRUE if both Users are different, else FALSE.

Parameters

<i>u</i>	User to compare
----------	---------------------------------

Returns

boolean

8.101.3.8 bool Models::User::operator== (const User & *u*)

[User::operator ==](#) Re-define the operator "==" to compare if the current [User](#) is the same to the other [User](#) c Return TRUE if both Users are the same, else FALSE.

Parameters

<i>u</i>	User to compare
----------	---------------------------------

Returns

boolean

8.101.3.9 void Models::User::setNoSiret (const QString & *noSiret*)

[User::setNoSiret](#) Modify the SIRET number (company registration number) *noSiret*

Parameters

<i>noSiret</i>	SIRET number
----------------	--------------

8.101.3.10 void Models::User::setTitle (const QString & *title*)

[User::setTitle](#) Modify the user/company activities *description*

Parameters

<i>title</i>	Short description on activity(ies) of User company
--------------	--

8.101.3.11 void Models::User::setWorkspaceName (const QString & *workspaceName*)

[User::setWorkspaceName](#) Change the current workspace name by the new *workspaceName*

Parameters

<i>workspaceName</i>	
----------------------	--

8.101.3.12 void Models::User::setWorkspacePath (const QString & *workspacePath*)

[User::setWorkspacePath](#) Change the current workspace path by the new *workspacePath*

Parameters

<i>workspacePath</i>	
----------------------	--

8.101.3.13 void Models::User::updateFolders (void)

MainWindow::updateFolders Make directories which contain quotes and billings. Directories are the same than theirs of the Tree organisation (without Projects).

Organisation of folders are formed like this:

- COMPANY CustomerLastname CustomerFirstname/
 - Quotes/
 - * quote1 ...
 - Billings/
 - * billing1 ...

The documentation for this class was generated from the following files:


- /home/travis/build/FACT-Team/FactDev/src/models/user.h
- /home/travis/build/FACT-Team/FactDev/src/models/user.cpp

8.102 Databases::UserDatabase Class Reference

The [UserDatabase](#) class Access to User data in the the table User of the [Database](#)

```
#include <userdatabase.h>
```

Inheritance diagram for Databases::UserDatabase:



Public Member Functions

- [Models::User](#) * [getUser](#) (const int pld=1)
[UserDatabase::getUser](#) Get informations about the user (identified by 'pld')
- void [updateUser](#) (const [Models::User](#) &)
[UserDatabase::updateUser](#) Update informations about the user.

Static Public Member Functions

- static [UserDatabase](#) * [instance](#) () throw (DbException*)
[UserDatabase::getInstance](#) Return an instance of [UserDatabase](#).

Additional Inherited Members

8.102.1 Detailed Description

The [UserDatabase](#) class Access to User data in the the table User of the [Database](#)

Author

Florent Berbie

See Also

[Database](#)
[User](#)

8.102.2 Member Function Documentation

8.102.2.1 [Models::User](#) * [Databases::UserDatabase::getUser](#) (const int *pld* = 1)

[UserDatabase::getUser](#) Get informations about the user (identified by 'pld')

Parameters

<i>pld</i>	user id (1 default)
------------	---------------------

Returns

the user

8.102.2.2 [UserDatabase](#) * [Databases::UserDatabase::instance](#) () throw [DbException](#) *) [static]

[UserDatabase::getInstance](#) Return an instance of [UserDatabase](#).

Returns


Instance of [UserDatabase](#)

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/database/userdatabase.h
- /home/travis/build/FACT-Team/FactDev/src/database/userdatabase.cpp

8.103 UserDatabaseTest Class Reference

Inheritance diagram for UserDatabaseTest:



The documentation for this class was generated from the following files:


- /home/travis/build/FACT-Team/FactDev/tests/database/userdatabasetest.h
- /home/travis/build/FACT-Team/FactDev/tests/database/userdatabasetest.cpp

8.104 Gui::Dialogs::UserDataDialog Class Reference

The [UserDataDialog](#) class Window to fill user data.

```
#include <userdatadialog.h>
```

Inheritance diagram for Gui::Dialogs::UserDataDialog:



Public Slots

- void [checkFields](#) ()
[UserDataDialog::checkFields](#) Check all fields of dialog components.
- void [browseWorkspacePath](#) ()
[UserDataDialog::browseWorkspacePath](#) Open a new window to define the workspace path of the user.

Public Member Functions

- [UserDataDialog](#) (QWidget *parent=0)
[UserDataDialog::UserDataDialog](#) Construct a window with user data.
- void [fillFields](#) ()
[UserDataDialog::fillFields](#) Fill line edits with the data of the user.
- void [accept](#) ()
[UserDataDialog::accept](#) Valid data inputed by user and add these data in Database.
- void [reject](#) ()
[UserDataDialog::reject](#) Cancel the operation and close the windows.

8.104.1 Detailed Description

The [UserDataDialog](#) class Window to fill user data.

Author

Florent Berbie

See Also

Project

8.104.2 Constructor & Destructor Documentation**8.104.2.1** Gui::Dialogs::UserDataDialog::UserDataDialog (QWidget * *parent* = 0) [explicit]

[UserDataDialog::UserDataDialog](#) Construct a window with user data.

Parameters


<i>parent</i>	
---------------	--

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/dialogs/userdatadialog.h
- /home/travis/build/FACT-Team/FactDev/src/gui/dialogs/userdatadialog.cpp

8.105 UserModelTest Class Reference

Inheritance diagram for UserModelTest:



The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/tests/models/usermodeltest.h
- /home/travis/build/FACT-Team/FactDev/tests/models/usermodeltest.cpp

Index

- add
 - Gui::Widgets::ContributoriesWidget, [76](#)
- addBill
 - Gui::MainWindow, [122](#)
- addBilling
 - Databases::BillingDatabase, [32](#)
- addBillingProject
 - Databases::BillingDatabase, [32](#)
- addBillingToProject
 - Utils::HierarchicalSystem, [113](#)
- addContributory
 - Databases::ContributoryDatabase, [81](#)
 - Models::Billing, [27](#)
 - Models::ContributoriesList, [68](#)
- addCustomer
 - Databases::CustomerDatabase, [92](#)
- addDoc
 - Gui::MainWindow, [123](#)
- addProject
 - Databases::ProjectDatabase, [150](#)
 - Gui::MainWindow, [123](#)
 - Gui::Widgets::ContributoriesWidget, [76](#)
 - Models::ContributoriesList, [69](#)
- AddProjectDialog
 - Gui::Dialogs::AddProjectDialog, [22](#)
- addProjectToCustomer
 - Utils::HierarchicalSystem, [113](#)
- addQuote
 - Gui::MainWindow, [123](#)
- AddQuoteDialog
 - Gui::Dialogs::AddQuoteDialog, [23](#)
- addRateProject
 - Databases::RateDatabase, [162](#)
- allProjectsChosen
 - Gui::Widgets::WdgModels::ProjectContributories-TableModel, [146](#)
- append
 - Gui::Widgets::WdgModels::BillingsTableModel, [40](#)
 - Gui::Widgets::WdgModels::ContributoriesTable-Model, [72](#)
 - Gui::Widgets::WdgModels::CustomersTableModel, [98](#)
 - Gui::Widgets::WdgModels::ProjectContributories-TableModel, [146](#)
 - Gui::Widgets::WdgModels::ProjectsTableModel, [155](#)
- beginDateControl
 - Gui::Dialogs::ComputeTurnoverDialog, [64](#)
- Billing
 - Models::Billing, [27](#)
- BillingDatabaseTest, [39](#)
- BillingModelTest, [39](#)
- BillingsTableModel
 - Gui::Widgets::WdgModels::BillingsTableModel, [40](#)
- canEval
 - CounterContext, [86](#)
 - Mustache::Context, [66](#)
 - Mustache::QtVariantContext, [159](#)
- changeDatabase
 - Databases::Database, [102](#)
- check
 - Gui::Widgets::CheckFields::CheckEmail, [45](#)
 - Gui::Widgets::CheckFields::CheckFieldsLetters, [46](#)
 - Gui::Widgets::CheckFields::CheckFieldsNumbers, [48](#)
 - Gui::Widgets::CheckFields::CheckIpAddress, [49](#)
 - Gui::Widgets::CheckFields::CheckLogin, [50](#)
 - Gui::Widgets::CheckFields::CheckPhone, [52](#)
 - Gui::Widgets::CheckFields::CheckPortNumber, [54](#)
 - Gui::Widgets::CheckFields::CheckPostalCode, [55](#)
 - Gui::Widgets::CheckFields::CheckSiretNumber, [58](#)
 - Gui::Widgets::CheckFields::CheckUntilField, [59](#)
 - Gui::Widgets::CheckFields::CheckValidField, [60](#)
 - Gui::Widgets::CheckFields::ICheckField, [114](#)
- CheckCity
 - Gui::Widgets::CheckFields::CheckCity, [43](#)
- CheckCountry
 - Gui::Widgets::CheckFields::CheckCountry, [44](#)
- CheckEmail
 - Gui::Widgets::CheckFields::CheckEmail, [45](#)
- CheckFieldsLetters
 - Gui::Widgets::CheckFields::CheckFieldsLetters, [46](#)
- CheckFieldsNumbers
 - Gui::Widgets::CheckFields::CheckFieldsNumbers, [47](#)
- CheckIpAddress
 - Gui::Widgets::CheckFields::CheckIpAddress, [49](#)
- CheckLogin
 - Gui::Widgets::CheckFields::CheckLogin, [50](#)
- CheckName
 - Gui::Widgets::CheckFields::CheckName, [51](#)
- CheckPhone
 - Gui::Widgets::CheckFields::CheckPhone, [52](#)
- CheckPortNumber
 - Gui::Widgets::CheckFields::CheckPortNumber, [54](#)
- CheckPostalCode
 - Gui::Widgets::CheckFields::CheckPostalCode, [55](#)
- CheckQLineEdit

- Gui::Widgets::CheckFields::CheckQLineEdit, 56
- CheckSiretNumber
 - Gui::Widgets::CheckFields::CheckSiretNumber, 58
- CheckUntilField
 - Gui::Widgets::CheckFields::CheckUntilField, 59
- CheckValidField
 - Gui::Widgets::CheckFields::CheckValidField, 60
- columnCount
 - Gui::Widgets::WdgModels::BillingsTableModel, 40
 - Gui::Widgets::WdgModels::ContributoriesTable-Model, 72
 - Gui::Widgets::WdgModels::CustomersTableModel, 98
 - Gui::Widgets::WdgModels::ProjectContributories-TableModel, 146
 - Gui::Widgets::WdgModels::ProjectsTableModel, 155
- ComboBoxDelegate
 - Gui::Widgets::Delegates::ComboBoxDelegate, 61
- ComboBoxModelWidget
 - Gui::Widgets::ComboBoxModelWidget, 63
- Comment
 - Mustache::Tag, 182
- computeProjectCost
 - Models::Project, 139
- Context
 - Mustache::Context, 66
- ContributoriesDatabaseTest, 67
- ContributoriesTableModel
 - Gui::Widgets::WdgModels::ContributoriesTable-Model, 72
- ContributoriesWidget
 - Gui::Widgets::ContributoriesWidget, 75
- Contributory
 - Models::Contributory, 78
- ContributoryListTest, 85
- ContributoryModelTest, 85
- count
 - Gui::Widgets::ContributoriesWidget, 76
 - Gui::Widgets::WdgModels::BillingsTableModel, 41
 - Gui::Widgets::WdgModels::ContributoriesTable-Model, 72
 - Gui::Widgets::WdgModels::CustomersTableModel, 98
 - Gui::Widgets::WdgModels::ProjectsTableModel, 155
- CounterContext, 85
 - canEval, 86
 - eval, 86
 - stringValue, 86, 87
- createEditor
 - Gui::Widgets::Delegates::ComboBoxDelegate, 62
 - Gui::Widgets::Delegates::DoubleSpinBoxDelegate, 109
 - Gui::Widgets::Delegates::ProjectComboDelegate, 143
 - Gui::Widgets::Delegates::TextareaDelegate, 185
 - Gui::Widgets::Delegates::UnitComboDelegate, 187
- Customer
 - Models::Customer, 88
- CustomerContextMenu
 - Gui::Widgets::CustomerContextMenu, 90
- CustomerDataWidget
 - Gui::Widgets::CustomerDataWidget, 96
- CustomerDatabaseTest, 95
- CustomerModelTest, 97
- CustomersTableModel
 - Gui::Widgets::WdgModels::CustomersTableModel, 98
- DB_FILENAME
 - Parameters, 127
- data
 - Gui::Widgets::WdgModels::BillingsTableModel, 41
 - Gui::Widgets::WdgModels::ContributoriesTable-Model, 73
 - Gui::Widgets::WdgModels::CustomersTableModel, 99
 - Gui::Widgets::WdgModels::ProjectContributories-TableModel, 146
 - Gui::Widgets::WdgModels::ProjectsTableModel, 155
- DatabaseSettingsWidget
 - Gui::Widgets::DatabaseSettingsWidget, 104
- databaseTypeChanged
 - Gui::Dialogs::StartedWindowsDialog, 177
- Databases, 17
- Databases::AccessDatabase, 21
- Databases::BillingDatabase, 31
 - addBilling, 32
 - addBillingProject, 32
 - getAllBillingsOfProject, 34
 - getBilling, 34
 - getBillingsTable, 34
 - getBills, 34
 - getBillsBetweenDates, 35
 - getBillsPaid, 35
 - getMaxBillingNumber, 35
 - getMaxBillingNumberOfCustomer, 35
 - getMaxQuoteNumber, 35
 - getMaxQuoteNumberOfCustomer, 36
 - getNbBills, 36
 - getNbBillsPaid, 36
 - getNbDocs, 36
 - getNbQuotes, 36
 - instance, 38
 - isBillingPaid, 38
 - removeBilling, 38
 - removeBillingProject, 38
- Databases::ContributoryDatabase, 80
 - addContributory, 81
 - getContributoriesByBilling, 81
 - getContributoriesByBillingAndProject, 83
 - getContributory, 83
 - instance, 83
 - removeContributory, 83
- Databases::CustomerDatabase, 91

- addCustomer, 92
- getCustomer, 92
- getCustomers, 92
- getCustomersTable, 92
- getItemCustomer, 94
- getItemProject, 94
- getItemRoot, 94
- getNbCustomers, 94
- getTree, 94
- instance, 95
- removeCustomer, 95
- updateCustomer, 95
- Databases::Database, 100
 - changeDatabase, 102
 - executeFile, 102
 - instance, 102
 - lastError, 102
 - setDatabase, 103
 - value, 103
- Databases::ProjectDatabase, 149
 - addProject, 150
 - getAllProjects, 150
 - getCostProjects, 150
 - getNbProjects, 151
 - getProject, 151
 - getProjects, 151
 - getProjectsOfCustomer, 152
 - getProjectsTable, 152
 - instance, 152
 - removeProject, 152
 - updateProject, 152
- Databases::RateDatabase, 162
 - addRateProject, 162
 - getRate, 162
 - instance, 162
 - updateRateProject, 163
- Databases::UserDatabase, 191
 - getUser, 192
 - instance, 192
- DbException
 - Exceptions::DbException, 106
- DialogAddCustomer
 - Gui::Dialogs::DialogAddCustomer, 107
- DoubleSpinBoxDelegate
 - Gui::Widgets::Delegates::DoubleSpinBoxDelegate, 109
- editUser
 - Gui::MainWindow, 123
- endDateControl
 - Gui::Dialogs::ComputeTurnoverDialog, 65
- error
 - Mustache::Renderer, 166
- errorPartial
 - Mustache::Renderer, 166
- errorPos
 - Mustache::Renderer, 166
- eval
 - CounterContext, 86
- Mustache::Context, 66
- Mustache::QtVariantContext, 159
- Exceptions::DbException, 105
 - DbException, 106
 - popupMessage, 106
- Exceptions::FileException, 110
 - FileException, 111
 - popupMessage, 112
- executeFile
 - Databases::Database, 102
- FileException
 - Exceptions::FileException, 111
- fillLabels
 - Gui::Dialogs::ComputeTurnoverDialog, 65
- fillQuoteBilling
 - Gui::Dialogs::AddQuoteDialog, 24
- filterOnBillsOrQuotes
 - Models::Search, 168
- filterOnCompany
 - Models::Search, 168
- filterOnContributories
 - Models::Search, 168
- filterOnCustomersWithoutProject
 - Models::Search, 168
- filterOnNumberElements
 - Models::Search, 168
- filterOnProjects
 - Models::Search, 169
- filterOnReferentLastname
 - Models::Search, 169
- filterOnVarcharElements
 - Models::Search, 169
- firstLetterToUpper
 - Utils::String, 181
- flags
 - Gui::Widgets::WdgModels::BillingsTableModel, 41
 - Gui::Widgets::WdgModels::ContributoriesTable-Model, 73
 - Gui::Widgets::WdgModels::CustomersTableModel, 99
 - Gui::Widgets::WdgModels::ProjectContributories-TableModel, 146
 - Gui::Widgets::WdgModels::ProjectsTableModel, 155
- fn_t
 - Mustache::QtVariantContext, 159
- generate
 - Generator::PdfGenerator, 129
 - Generator::TexGenerator, 184
- Generation, 112
- Generator::PdfGenerator, 129
 - generate, 129
 - PdfGenerator, 129
- Generator::TexGenerator, 183
 - generate, 184
 - TexGenerator, 184
- getAddress

- Models::People, 131
- getAllBillingsOfProject
 - Databases::BillingDatabase, 34
- getAllContributories
 - Models::ContributoriesList, 69
- getAllProjects
 - Databases::ProjectDatabase, 150
- getBeginDate
 - Models::Project, 139
- getBilling
 - Databases::BillingDatabase, 34
- getBillings
 - Gui::Widgets::WdgModels::BillingsTableModel, 41
- getBillingsTable
 - Databases::BillingDatabase, 34
- getBills
 - Databases::BillingDatabase, 34
- getBillsBetweenDates
 - Databases::BillingDatabase, 35
- getBillsPaid
 - Databases::BillingDatabase, 35
- getBtnValid
 - Gui::Widgets::CheckFields::CheckQLineEdit, 57
- getCity
 - Models::People, 131
- getCompany
 - Models::People, 131
- getContributories
 - Gui::Widgets::ContributoriesWidget, 76
 - Gui::Widgets::WdgModels::ContributoriesTable-Model, 73
 - Models::Billing, 27
 - Models::ContributoriesList, 69
- getContributoriesByBilling
 - Databases::ContributoryDatabase, 81
- getContributoriesByBillingAndProject
 - Databases::ContributoryDatabase, 83
- getContributory
 - Databases::ContributoryDatabase, 83
- getCopy
 - Gui::Dialogs::AddQuoteDialog, 24
- getCost
 - Models::Project, 139
- getCostProjects
 - Databases::ProjectDatabase, 150
- getCountry
 - Gui::Widgets::CheckFields::CheckPhone, 52
 - Gui::Widgets::CheckFields::CheckPostalCode, 55
 - Models::People, 131
- getCurrentCustomerId
 - Gui::MainWindow, 123
 - Gui::Widgets::searchWidget, 175
- getCurrentCustomerName
 - Gui::MainWindow, 123
- getCurrentProjectId
 - Gui::MainWindow, 123
- getCurrentProjectName
 - Gui::MainWindow, 124
- getCurrentQuoteld
 - Gui::MainWindow, 124
- getCustomer
 - Databases::CustomerDatabase, 92
 - Models::ContributoriesList, 69
 - Models::Project, 139
- getCustomers
 - Databases::CustomerDatabase, 92
 - Gui::Widgets::WdgModels::CustomersTableModel, 99
 - Utils::HierarchicalSystem, 113
- getCustomersTable
 - Databases::CustomerDatabase, 92
- getDailyRate
 - Gui::Widgets::RateWidget, 164
 - Models::Project, 139
 - Models::Rate, 161
- getDataMap
 - Models::Billing, 27
 - Models::ContributoriesList, 69
 - Models::Contributory, 79
 - Models::Customer, 88
 - Models::IModel, 116
 - Models::Project, 139
 - Models::User, 189
- getDatabaseName
 - Gui::Widgets::DatabaseSettingsWidget, 104
- getDate
 - Models::Billing, 27
- getDescription
 - Models::Billing, 27
 - Models::Contributory, 79
 - Models::Project, 139
- getDomainNameOrIP
 - Gui::Widgets::DatabaseSettingsWidget, 104
- getEmail
 - Models::People, 131
- getEndDate
 - Models::Project, 140
- getFax
 - Models::People, 132
- getFilename
 - Models::Billing, 28
- getFilter
 - Models::Search, 169
- getFirstname
 - Models::People, 132
- getFolder
 - Models::Billing, 28
- getGlobalTurnover
 - Models::Statistics, 178
- getGroupFilter
 - Models::Search, 169
- getHourlyRate
 - Gui::Widgets::RateWidget, 164
 - Models::Rate, 161
- getId
 - Models::IModel, 116

- getIdBilling
 - Models::ContributoriesList, 69
- getIdCustomer
 - Gui::Dialogs::AddQuoteDialog, 24
 - Gui::Widgets::searchWidget, 175
- getImage
 - Gui::Dialogs::StartedWindowsDialog, 177
- getItem
 - Models::Billing, 28
- getItemCustomer
 - Databases::CustomerDatabase, 94
- getItemProject
 - Databases::CustomerDatabase, 94
- getItemRoot
 - Databases::CustomerDatabase, 94
- getLastName
 - Models::People, 132
- getLegalRate
 - Models::Rate, 161
- getLogin
 - Gui::Widgets::DatabaseSettingsWidget, 105
- getMaxBillingNumber
 - Databases::BillingDatabase, 35
- getMaxBillingNumberOfCustomer
 - Databases::BillingDatabase, 35
- getMaxQuoteNumber
 - Databases::BillingDatabase, 35
- getMaxQuoteNumberOfCustomer
 - Databases::BillingDatabase, 36
- getMobilePhone
 - Models::People, 132
- getModel
 - Utils::ItemType, 118
- getName
 - Models::Project, 140
 - Utils::ItemType, 118
- getNameFolder
 - Models::Customer, 88
- getNbBills
 - Databases::BillingDatabase, 36
- getNbBillsPaid
 - Databases::BillingDatabase, 36
- getNbCustomers
 - Databases::CustomerDatabase, 94
- getNbDailyHours
 - Models::Rate, 161
- getNbDocs
 - Databases::BillingDatabase, 36
- getNbHours
 - Models::Contributory, 79
- getNbProjects
 - Databases::ProjectDatabase, 151
 - Models::ContributoriesList, 69
- getNbQuotes
 - Databases::BillingDatabase, 36
- getNoSiret
 - Models::User, 189
- getNumber
 - Gui::Dialogs::AddQuoteDialog, 24
 - Models::Billing, 28
- getPartial
 - Mustache::PartialFileLoader, 127
 - Mustache::PartialMap, 128
 - Mustache::PartialResolver, 129
- getPassword
 - Gui::Widgets::DatabaseSettingsWidget, 105
- getPath
 - Models::Billing, 28
 - Models::Customer, 88
- getPhone
 - Models::People, 132
- getPort
 - Gui::Widgets::DatabaseSettingsWidget, 105
- getPostalCode
 - Models::People, 132
- getProject
 - Databases::ProjectDatabase, 151
 - Gui::Widgets::WdgModels::ProjectContributories-TableModel, 146
 - Models::Contributory, 79
- getProjects
 - Databases::ProjectDatabase, 151
 - Gui::Widgets::Delegates::ProjectComboDelegate, 143
 - Gui::Widgets::WdgModels::ProjectContributories-TableModel, 147
 - Gui::Widgets::WdgModels::ProjectsTableModel, 155
 - Models::ContributoriesList, 70
 - Utils::HierarchicalSystem, 113
- getProjectsOfCustomer
 - Databases::ProjectDatabase, 152
- getProjectsTable
 - Databases::ProjectDatabase, 152
- getRate
 - Databases::RateDatabase, 162
 - Models::ContributoriesList, 70
- getSearchInBillsQuotes
 - Models::Search, 169
- getSearchInCompanies
 - Models::Search, 170
- getSearchInProjects
 - Models::Search, 170
- getSearchInReferentLastname
 - Models::Search, 170
- getSelectedProjects
 - Gui::Widgets::WdgModels::ProjectContributories-TableModel, 147
- getSumQuantity
 - Gui::Widgets::WdgModels::ContributoriesTable-Model, 73
 - Models::Billing, 28
 - Models::ContributoriesList, 70
- getSumRate
 - Models::Billing, 28
 - Models::ContributoriesList, 70

- getText
 - Models::Search, 170
- getTitle
 - Models::Billing, 29
 - Models::User, 189
- getTree
 - Databases::CustomerDatabase, 94
- getTurnover
 - Models::Customer, 88
- getTurnoverBetweenDates
 - Models::Statistics, 178
- getType
 - Utils::ItemType, 118
- getUser
 - Databases::UserDatabase, 192
- getWorkspaceName
 - Models::User, 189
- getWorkspacePath
 - Models::User, 189
- Gui, 17
- Gui::Dialogs::AddProjectDialog, 21
 - AddProjectDialog, 22
- Gui::Dialogs::AddQuoteDialog, 22
 - AddQuoteDialog, 23
 - fillQuoteBilling, 24
 - getCopy, 24
 - getCustomerId, 24
 - getNumber, 24
 - setCopy, 24
 - setQuoteIdNumber, 25
- Gui::Dialogs::ComputeTurnoverDialog, 64
 - beginDateControl, 64
 - endDateControl, 65
 - fillLabels, 65
- Gui::Dialogs::DialogAddCustomer, 107
 - DialogAddCustomer, 107
- Gui::Dialogs::MessageBox, 125
 - MessageBox, 126
 - setImage, 126
 - setText, 126
- Gui::Dialogs::StartedWindowsDialog, 176
 - databaseTypeChanged, 177
 - getImage, 177
 - isDatabaseCentralized, 177
 - isDatabaseTypeValid, 177
 - StartedWindowsDialog, 177
- Gui::Dialogs::StatisticsDialog, 179
 - singularPlural, 180
 - StatisticsDialog, 179
- Gui::Dialogs::UserDataDialog, 193
 - UserDataDialog, 194
- Gui::Docks::SearchDock, 172
 - search, 173
 - SearchDock, 172
 - textChanged, 173
- Gui::MainWindow, 120
 - addBill, 122
 - addDoc, 123
 - addProject, 123
 - addQuote, 123
 - editUser, 123
 - getCurrentCustomerId, 123
 - getCurrentCustomerName, 123
 - getCurrentProjectId, 123
 - getCurrentProjectName, 124
 - getCurrentQuoteId, 124
 - MainWindow, 122
 - resizeEvent, 124
 - rootTree, 124
 - search, 124
 - treeLevel, 124
- Gui::Widgets, 18
- Gui::Widgets::CheckFields::CheckCity, 42
 - CheckCity, 43
- Gui::Widgets::CheckFields::CheckCountry, 43
 - CheckCountry, 44
- Gui::Widgets::CheckFields::CheckEmail, 44
 - check, 45
 - CheckEmail, 45
- Gui::Widgets::CheckFields::CheckFieldsLetters, 46
 - check, 46
 - CheckFieldsLetters, 46
- Gui::Widgets::CheckFields::CheckFieldsNumbers, 47
 - check, 48
 - CheckFieldsNumbers, 47
- Gui::Widgets::CheckFields::CheckIpAddress, 48
 - check, 49
 - CheckIpAddress, 49
- Gui::Widgets::CheckFields::CheckLogin, 49
 - check, 50
 - CheckLogin, 50
- Gui::Widgets::CheckFields::CheckName, 51
 - CheckName, 51
- Gui::Widgets::CheckFields::CheckPhone, 51
 - check, 52
 - CheckPhone, 52
 - getCountry, 52
 - setCountry, 53
- Gui::Widgets::CheckFields::CheckPortNumber, 53
 - check, 54
 - CheckPortNumber, 54
- Gui::Widgets::CheckFields::CheckPostalCode, 54
 - check, 55
 - CheckPostalCode, 55
 - getCountry, 55
 - setCountry, 55
- Gui::Widgets::CheckFields::CheckQLineEdit, 56
 - CheckQLineEdit, 56
 - getBtnValid, 57
 - isValid, 57
 - setBtnValid, 57
- Gui::Widgets::CheckFields::CheckSiretNumber, 57
 - check, 58
 - CheckSiretNumber, 58
- Gui::Widgets::CheckFields::CheckUntilField, 58
 - check, 59

- CheckUntilField, 59
- Gui::Widgets::CheckFields::CheckValidField, 59
 - check, 60
 - CheckValidField, 60
- Gui::Widgets::CheckFields::ICheckField, 114
 - check, 114
- Gui::Widgets::ComboBoxModelWidget, 63
 - ComboBoxModelWidget, 63
- Gui::Widgets::ContributoriesWidget, 74
 - add, 76
 - addProject, 76
 - ContributoriesWidget, 75
 - count, 76
 - getContributories, 76
- Gui::Widgets::CustomerContextualMenu, 90
 - CustomerContextualMenu, 90
- Gui::Widgets::CustomerDataWidget, 96
 - CustomerDataWidget, 96
 - printInformations, 96
- Gui::Widgets::DatabaseSettingsWidget, 103
 - DatabaseSettingsWidget, 104
 - getDatabaseName, 104
 - getDomainNameOrIP, 104
 - getLogin, 105
 - getPassword, 105
 - getPort, 105
 - isValid, 105
- Gui::Widgets::Delegates::ComboBoxDelegate, 61
 - ComboBoxDelegate, 61
 - createEditor, 62
 - paint, 62
 - setEditorData, 62
 - setModelData, 62
 - updateEditorGeometry, 63
- Gui::Widgets::Delegates::DoubleSpinBoxDelegate, 108
 - createEditor, 109
 - DoubleSpinBoxDelegate, 109
 - setEditorData, 109
 - setModelData, 110
 - updateEditorGeometry, 110
- Gui::Widgets::Delegates::ProjectComboDelegate, 142
 - createEditor, 143
 - getProjects, 143
 - isLocked, 144
 - paint, 144
 - ProjectComboDelegate, 143
 - setLocked, 144
- Gui::Widgets::Delegates::TextareaDelegate, 184
 - createEditor, 185
 - setEditorData, 185
 - setModelData, 186
 - TextareaDelegate, 185
 - updateEditorGeometry, 186
- Gui::Widgets::Delegates::UnitComboDelegate, 186
 - createEditor, 187
 - paint, 187
 - UnitComboDelegate, 187
- Gui::Widgets::Popup, 136
- Gui::Widgets::ProjectsWidget, 157
 - ProjectsWidget, 157
 - updateBtn, 158
- Gui::Widgets::RateWidget, 163
 - getDailyRate, 164
 - getHourlyRate, 164
 - RateWidget, 164
 - setDailyRate, 165
 - setHourlyRate, 165
 - setWidgetDailyRateValue, 165
 - setWidgetHourlyRateValue, 165
- Gui::Widgets::WdgModels::BillingsTableModel, 39
 - append, 40
 - BillingsTableModel, 40
 - columnCount, 40
 - count, 41
 - data, 41
 - flags, 41
 - getBillings, 41
 - headerData, 41
 - remove, 42
 - rowCount, 42
 - setData, 42
- Gui::Widgets::WdgModels::ContributoriesTableModel, 71
 - append, 72
 - columnCount, 72
 - ContributoriesTableModel, 72
 - count, 72
 - data, 73
 - flags, 73
 - getContributories, 73
 - getSumQuantity, 73
 - headerData, 73
 - remove, 74
 - rowCount, 74
 - setData, 74
- Gui::Widgets::WdgModels::CustomersTableModel, 97
 - append, 98
 - columnCount, 98
 - count, 98
 - CustomersTableModel, 98
 - data, 99
 - flags, 99
 - getCustomers, 99
 - headerData, 99
 - remove, 100
 - rowCount, 100
 - setData, 100
- Gui::Widgets::WdgModels::ProjectContributoriesTable-Model, 144
 - allProjectsChosen, 146
 - append, 146
 - columnCount, 146
 - data, 146
 - flags, 146
 - getProject, 146
 - getProjects, 147

- getSelectedProjects, 147
 - headerData, 147
 - ProjectContributoriesTableModel, 145
 - remove, 147
 - rowCount, 147
 - setData, 147
- Gui::Widgets::WdgModels::ProjectsTableModel, 153
 - append, 155
 - columnCount, 155
 - count, 155
 - data, 155
 - flags, 155
 - getProjects, 155
 - headerData, 156
 - ProjectsTableModel, 154
 - remove, 156
 - rowCount, 156
 - setData, 156
- Gui::Widgets::searchWidget, 173
 - getCurrentCustomerId, 175
 - getCustomerId, 175
 - isCustomerSelected, 175
 - search, 175
 - searchWidget, 174
 - selectCustomer, 175
 - setCustomerId, 175
- headerData
 - Gui::Widgets::WdgModels::BillingsTableModel, 41
 - Gui::Widgets::WdgModels::ContributoriesTable-Model, 73
 - Gui::Widgets::WdgModels::CustomersTableModel, 99
 - Gui::Widgets::WdgModels::ProjectContributories-TableModel, 147
 - Gui::Widgets::WdgModels::ProjectsTableModel, 156
- hydrat
 - Models::Billing, 29
 - Models::Contributory, 79
 - Models::Customer, 88
 - Models::IModel, 116
 - Models::Project, 140
 - Models::User, 190
- instance
 - Databases::BillingDatabase, 38
 - Databases::ContributoryDatabase, 83
 - Databases::CustomerDatabase, 95
 - Databases::Database, 102
 - Databases::ProjectDatabase, 152
 - Databases::RateDatabase, 162
 - Databases::UserDatabase, 192
 - Utils::Log, 119
- InvertedSectionStart
 - Mustache::Tag, 182
- isBilling
 - Models::Billing, 29
- isBillingPaid
 - Databases::BillingDatabase, 38
- isCustomerSelected
 - Gui::Widgets::searchWidget, 175
- isDatabaseCentralized
 - Gui::Dialogs::StartedWindowsDialog, 177
- isDatabaseTypeValid
 - Gui::Dialogs::StartedWindowsDialog, 177
- isFalse
 - Mustache::Context, 66
 - Mustache::QtVariantContext, 159
- isInsert
 - Models::ContributoriesList, 70
- isLocked
 - Gui::Widgets::Delegates::ProjectComboDelegate, 144
- isPaid
 - Models::Billing, 29
- isToRemoved
 - Models::IModel, 116
- isValid
 - Gui::Widgets::CheckFields::CheckQLineEdit, 57
 - Gui::Widgets::DatabaseSettingsWidget, 105
- ItemType
 - Utils::ItemType, 117
- ItemTypeTest, 119
- lastError
 - Databases::Database, 102
- listCount
 - Mustache::Context, 66
 - Mustache::QtVariantContext, 159
- MainWindow
 - Gui::MainWindow, 122
- makeDirectory
 - Utils::Directories, 108
- MessageBox
 - Gui::Dialogs::MessageBox, 126
- Models, 18
- Models::Billing, 25
 - addContributory, 27
 - Billing, 27
 - getContributories, 27
 - getDataMap, 27
 - getDate, 27
 - getDescription, 27
 - getFilename, 28
 - getFolder, 28
 - getItem, 28
 - getNumber, 28
 - getPath, 28
 - getSumQuantity, 28
 - getSumRate, 28
 - getTitle, 29
 - hydrat, 29
 - isBilling, 29
 - isPaid, 29
 - operator<, 29
 - operator==, 30

- setDate, [30](#)
 - setDescription, [30](#)
 - setIsBilling, [30](#)
 - setIsPaid, [30](#)
 - setNumber, [30](#)
 - setTitle, [31](#)
- Models::ContributoriesList, [67](#)
 - addContributory, [68](#)
 - addProject, [69](#)
 - getAllContributories, [69](#)
 - getContributories, [69](#)
 - getCustomer, [69](#)
 - getDataMap, [69](#)
 - getIdBilling, [69](#)
 - getNbProjects, [69](#)
 - getProjects, [70](#)
 - getRate, [70](#)
 - getSumQuantity, [70](#)
 - getSumRate, [70](#)
 - isInsert, [70](#)
 - setAllIdContributories, [70](#)
 - setIdBilling, [71](#)
 - setInsert, [71](#)
- Models::Contributory, [76](#)
 - Contributory, [78](#)
 - getDataMap, [79](#)
 - getDescription, [79](#)
 - getNbHours, [79](#)
 - getProject, [79](#)
 - hydrat, [79](#)
 - operator==, [80](#)
 - setDescription, [80](#)
 - setNbHours, [80](#)
 - setProject, [80](#)
- Models::Customer, [87](#)
 - Customer, [88](#)
 - getDataMap, [88](#)
 - getNameFolder, [88](#)
 - getPath, [88](#)
 - getTurnover, [88](#)
 - hydrat, [88](#)
- Models::IModel, [115](#)
 - getDataMap, [116](#)
 - getId, [116](#)
 - hydrat, [116](#)
 - isToRemoved, [116](#)
 - setId, [116](#)
 - setToRemoved, [116](#)
- Models::People, [130](#)
 - getAddress, [131](#)
 - getCity, [131](#)
 - getCompany, [131](#)
 - getCountry, [131](#)
 - getEmail, [131](#)
 - getFax, [132](#)
 - getFirstname, [132](#)
 - getLastName, [132](#)
 - getMobilePhone, [132](#)
 - getPhone, [132](#)
 - getPostalCode, [132](#)
 - operator==, [134](#)
 - setAddress, [134](#)
 - setCity, [134](#)
 - setCompany, [134](#)
 - setCountry, [134](#)
 - setEmail, [135](#)
 - setFax, [135](#)
 - setFirstname, [135](#)
 - setLastName, [135](#)
 - setMobilePhone, [135](#)
 - setPhone, [135](#)
 - setPostalCode, [135](#)
- Models::Project, [137](#)
 - computeProjectCost, [139](#)
 - getBeginDate, [139](#)
 - getCost, [139](#)
 - getCustomer, [139](#)
 - getDailyRate, [139](#)
 - getDataMap, [139](#)
 - getDescription, [139](#)
 - getEndDate, [140](#)
 - getName, [140](#)
 - hydrat, [140](#)
 - operator<, [140](#)
 - operator==, [141](#)
 - Project, [138](#)
 - setBeginDate, [141](#)
 - setCost, [141](#)
 - setCustomer, [141](#)
 - setDailyRate, [141](#)
 - setDescription, [142](#)
 - setEndDate, [142](#)
 - setName, [142](#)
- Models::Rate, [160](#)
 - getDailyRate, [161](#)
 - getHourlyRate, [161](#)
 - getLegalRate, [161](#)
 - getNbDailyHours, [161](#)
 - Rate, [161](#)
- Models::Search, [166](#)
 - filterOnBillsOrQuotes, [168](#)
 - filterOnCompany, [168](#)
 - filterOnContributories, [168](#)
 - filterOnCustomersWithoutProject, [168](#)
 - filterOnNumberElements, [168](#)
 - filterOnProjects, [169](#)
 - filterOnReferentLastName, [169](#)
 - filterOnVarcharElements, [169](#)
 - getFilter, [169](#)
 - getGroupFilter, [169](#)
 - getSearchInBillsQuotes, [169](#)
 - getSearchInCompanies, [170](#)
 - getSearchInProjects, [170](#)
 - getSearchInReferentLastName, [170](#)
 - getText, [170](#)
 - searchInContributories, [170](#)

- setGroupFilter, 170
 - setSearchInBillsQuotes, 171
 - setSearchInCompanies, 171
 - setSearchInContributories, 171
 - setSearchInProjects, 171
 - setSearchInReferentLastname, 171
 - setText, 171
- Models::Statistics, 178
 - getGlobalTurnover, 178
 - getTurnoverBetweenDates, 178
- Models::User, 188
 - getDataMap, 189
 - getNoSiret, 189
 - getTitle, 189
 - getWorkspaceName, 189
 - getWorkspacePath, 189
 - hydrat, 190
 - operator==, 190
 - setNoSiret, 190
 - setTitle, 190
 - setWorkspaceName, 191
 - setWorkspacePath, 191
 - updateFolders, 191
 - User, 189
- Mustache::Tag
 - Comment, 182
 - InvertedSectionStart, 182
 - Partial, 182
 - SectionEnd, 182
 - SectionStart, 182
 - SetDelimiter, 182
- Mustache::Context, 65
 - canEval, 66
 - Context, 66
 - eval, 66
 - isFalse, 66
 - listCount, 66
 - partialResolver, 66
 - partialValue, 66
 - pop, 66
 - push, 67
 - stringValue, 67
- Mustache::PartialFileLoader, 127
 - getPartial, 127
- Mustache::PartialMap, 128
 - getPartial, 128
- Mustache::PartialResolver, 128
 - getPartial, 129
- Mustache::QtVariantContext, 158
 - canEval, 159
 - eval, 159
 - fn_t, 159
 - isFalse, 159
 - listCount, 159
 - pop, 159
 - push, 159
 - stringValue, 160
- Mustache::Renderer, 165
 - error, 166
 - errorPartial, 166
 - errorPos, 166
 - render, 166
 - setTagMarkers, 166
- Mustache::Tag, 182
 - Type, 182
- operator<
 - Models::Billing, 29
 - Models::Project, 140
- operator<<
 - Utils::Log, 120
- operator==
 - Models::Billing, 30
 - Models::Contributory, 80
 - Models::People, 134
 - Models::Project, 141
 - Models::User, 190
- paint
 - Gui::Widgets::Delegates::ComboBoxDelegate, 62
 - Gui::Widgets::Delegates::ProjectComboDelegate, 144
 - Gui::Widgets::Delegates::UnitComboDelegate, 187
- Parameters, 126
 - DB_FILENAME, 127
 - VERSION, 127
- Partial
 - Mustache::Tag, 182
- partialResolver
 - Mustache::Context, 66
- partialValue
 - Mustache::Context, 66
- PdfGenerator
 - Generator::PdfGenerator, 129
- PointersTest, 136
- pop
 - Mustache::Context, 66
 - Mustache::QtVariantContext, 159
- popupMessage
 - Exceptions::DbException, 106
 - Exceptions::FileException, 112
- printInformations
 - Gui::Widgets::CustomerDataWidget, 96
- Project
 - Models::Project, 138
- ProjectComboDelegate
 - Gui::Widgets::Delegates::ProjectComboDelegate, 143
- ProjectContributoriesTableModel
 - Gui::Widgets::WdgModels::ProjectContributories-TableModel, 145
- ProjectDatabaseTest, 153
- ProjectModelTest, 153
- ProjectsTableModel
 - Gui::Widgets::WdgModels::ProjectsTableModel, 154
- ProjectsWidget

- Gui::Widgets::ProjectsWidget, 157
- push
 - Mustache::Context, 67
 - Mustache::QtVariantContext, 159
- Rate
 - Models::Rate, 161
- RateModelTest, 163
- RateWidget
 - Gui::Widgets::RateWidget, 164
- remove
 - Gui::Widgets::WdgModels::BillingsTableModel, 42
 - Gui::Widgets::WdgModels::ContributoriesTable-Model, 74
 - Gui::Widgets::WdgModels::CustomersTableModel, 100
 - Gui::Widgets::WdgModels::ProjectContributories-TableModel, 147
 - Gui::Widgets::WdgModels::ProjectsTableModel, 156
- removeBilling
 - Databases::BillingDatabase, 38
- removeBillingProject
 - Databases::BillingDatabase, 38
- removeContributory
 - Databases::ContributoryDatabase, 83
- removeCustomer
 - Databases::CustomerDatabase, 95
- removeProject
 - Databases::ProjectDatabase, 152
- render
 - Mustache::Renderer, 166
- resizeEvent
 - Gui::MainWindow, 124
- rootTree
 - Gui::MainWindow, 124
- rowCount
 - Gui::Widgets::WdgModels::BillingsTableModel, 42
 - Gui::Widgets::WdgModels::ContributoriesTable-Model, 74
 - Gui::Widgets::WdgModels::CustomersTableModel, 100
 - Gui::Widgets::WdgModels::ProjectContributories-TableModel, 147
 - Gui::Widgets::WdgModels::ProjectsTableModel, 156
- search
 - Gui::Docks::SearchDock, 173
 - Gui::MainWindow, 124
 - Gui::Widgets::searchWidget, 175
- SearchDock
 - Gui::Docks::SearchDock, 172
- searchInContributories
 - Models::Search, 170
- searchTest, 173
- searchWidget
 - Gui::Widgets::searchWidget, 174
- SectionEnd
 - Mustache::Tag, 182
- SectionStart
 - Mustache::Tag, 182
- selectCustomer
 - Gui::Widgets::searchWidget, 175
- SetDelimiter
 - Mustache::Tag, 182
- setAddress
 - Models::People, 134
- setAllIdContributories
 - Models::ContributoriesList, 70
- setBeginDate
 - Models::Project, 141
- setBtnValid
 - Gui::Widgets::CheckFields::CheckQLineEdit, 57
- setCity
 - Models::People, 134
- setCompany
 - Models::People, 134
- setCopy
 - Gui::Dialogs::AddQuoteDialog, 24
- setCost
 - Models::Project, 141
- setCountry
 - Gui::Widgets::CheckFields::CheckPhone, 53
 - Gui::Widgets::CheckFields::CheckPostalCode, 55
 - Models::People, 134
- setCustomer
 - Models::Project, 141
- setDailyRate
 - Gui::Widgets::RateWidget, 165
 - Models::Project, 141
- setData
 - Gui::Widgets::WdgModels::BillingsTableModel, 42
 - Gui::Widgets::WdgModels::ContributoriesTable-Model, 74
 - Gui::Widgets::WdgModels::CustomersTableModel, 100
 - Gui::Widgets::WdgModels::ProjectContributories-TableModel, 147
 - Gui::Widgets::WdgModels::ProjectsTableModel, 156
- setDatabase
 - Databases::Database, 103
- setDate
 - Models::Billing, 30
- setDescription
 - Models::Billing, 30
 - Models::Contributory, 80
 - Models::Project, 142
- setEditorData
 - Gui::Widgets::Delegates::ComboBoxDelegate, 62
 - Gui::Widgets::Delegates::DoubleSpinBoxDelegate, 109
 - Gui::Widgets::Delegates::TextareaDelegate, 185
- setEmail
 - Models::People, 135
- setEndDate

- Models::Project, 142
- setFax
 - Models::People, 135
- setFirstname
 - Models::People, 135
- setGroupFilter
 - Models::Search, 170
- setHourlyRate
 - Gui::Widgets::RateWidget, 165
- setId
 - Models::IModel, 116
- setIdBilling
 - Models::ContributoriesList, 71
- setIdCustomer
 - Gui::Widgets::searchWidget, 175
- setImage
 - Gui::Dialogs::MessageBox, 126
- setInsert
 - Models::ContributoriesList, 71
- setIsBilling
 - Models::Billing, 30
- setIsPaid
 - Models::Billing, 30
- setLastname
 - Models::People, 135
- setLocked
 - Gui::Widgets::Delegates::ProjectComboDelegate, 144
- setMobilePhone
 - Models::People, 135
- setModelData
 - Gui::Widgets::Delegates::ComboBoxDelegate, 62
 - Gui::Widgets::Delegates::DoubleSpinBoxDelegate, 110
 - Gui::Widgets::Delegates::TextareaDelegate, 186
- setName
 - Models::Project, 142
 - Utils::ItemType, 118
- setNbHours
 - Models::Contributory, 80
- setNoSiret
 - Models::User, 190
- setNumber
 - Models::Billing, 30
- setPhone
 - Models::People, 135
- setPostalCode
 - Models::People, 135
- setProject
 - Models::Contributory, 80
- setQuotIdNumber
 - Gui::Dialogs::AddQuoteDialog, 25
- setSearchInBillsQuotes
 - Models::Search, 171
- setSearchInCompanies
 - Models::Search, 171
- setSearchInContributories
 - Models::Search, 171
- setSearchInProjects
 - Models::Search, 171
- setSearchInReferentLastname
 - Models::Search, 171
- setTagMarkers
 - Mustache::Renderer, 166
- setText
 - Gui::Dialogs::MessageBox, 126
 - Models::Search, 171
- setTitle
 - Models::Billing, 31
 - Models::User, 190
- setToRemoved
 - Models::IModel, 116
- setType
 - Utils::ItemType, 118
- setWidgetDailyRateValue
 - Gui::Widgets::RateWidget, 165
- setWidgetHourlyRateValue
 - Gui::Widgets::RateWidget, 165
- setWorkspaceName
 - Models::User, 191
- setWorkspacePath
 - Models::User, 191
- singularPlural
 - Gui::Dialogs::StatisticsDialog, 180
- StartedWindowsDialog
 - Gui::Dialogs::StartedWindowsDialog, 177
- StatisticModelTest, 178
- StatisticsDialog
 - Gui::Dialogs::StatisticsDialog, 179
- StringTest, 181
- stringValue
 - CounterContext, 86, 87
 - Mustache::Context, 67
 - Mustache::QtVariantContext, 160
- TestAdder< T >, 183
- TestMustache, 183
- TestRunner, 183
- testadder, 182
- TexGenerator
 - Generator::TexGenerator, 184
- textChanged
 - Gui::Docks::SearchDock, 173
- TextareaDelegate
 - Gui::Widgets::Delegates::TextareaDelegate, 185
- treeLevel
 - Gui::MainWindow, 124
- Type
 - Mustache::Tag, 182
- UnitComboDelegate
 - Gui::Widgets::Delegates::UnitComboDelegate, 187
- updateBtn
 - Gui::Widgets::ProjectsWidget, 158
- updateCustomer
 - Databases::CustomerDatabase, 95
- updateEditorGeometry

- Gui::Widgets::Delegates::ComboBoxDelegate, [63](#)
- Gui::Widgets::Delegates::DoubleSpinBoxDelegate, [110](#)
- Gui::Widgets::Delegates::TextareaDelegate, [186](#)
- updateFolders
 - Models::User, [191](#)
- updateProject
 - Databases::ProjectDatabase, [152](#)
- updateRateProject
 - Databases::RateDatabase, [163](#)
- User
 - Models::User, [189](#)
- UserDataDialog
 - Gui::Dialogs::UserDataDialog, [194](#)
- UserDatabaseTest, [193](#)
- UserModelTest, [194](#)
- Utils::Directories, [108](#)
 - makeDirectory, [108](#)
- Utils::HierarchicalSystem, [112](#)
 - addBillingToProject, [113](#)
 - addProjectToCustomer, [113](#)
 - getCustomers, [113](#)
 - getProjects, [113](#)
- Utils::ItemType, [117](#)
 - getModel, [118](#)
 - getName, [118](#)
 - getType, [118](#)
 - ItemType, [117](#)
 - setName, [118](#)
 - setType, [118](#)
- Utils::Log, [119](#)
 - instance, [119](#)
 - operator<<, [120](#)
 - write, [120](#)
- Utils::String, [181](#)
 - firstLetterToUpper, [181](#)
- Utils::pointers, [136](#)
- VERSION
 - Parameters, [127](#)
- value
 - Databases::Database, [103](#)
- write
 - Utils::Log, [120](#)