

FactDev

0.1

Generated by Doxygen 1.8.6

Fri Mar 6 2015 15:33:09

Contents

1	FactDev documentation	1
2	README	3
3	QTestRunner	5
4	Namespace Index	7
4.1	Namespace List	7
5	Hierarchical Index	9
5.1	Class Hierarchy	9
6	Class Index	13
6.1	Class List	13
7	Namespace Documentation	17
7.1	Databases Namespace Reference	17
7.1.1	Detailed Description	17
7.2	Gui Namespace Reference	17
7.2.1	Detailed Description	18
7.3	Gui::Widgets Namespace Reference	18
7.3.1	Detailed Description	18
7.4	Models Namespace Reference	18
7.4.1	Detailed Description	19
8	Class Documentation	21
8.1	Gui::Dialogs::AddProjectDialog Class Reference	21
8.1.1	Detailed Description	21
8.1.2	Constructor & Destructor Documentation	22
8.1.2.1	AddProjectDialog	22
8.2	Gui::Dialogs::AddQuoteDialog Class Reference	22
8.2.1	Detailed Description	23
8.2.2	Constructor & Destructor Documentation	23
8.2.2.1	AddQuoteDialog	23

8.2.3	Member Function Documentation	23
8.2.3.1	getNumber	23
8.3	Models::Billing Class Reference	23
8.3.1	Detailed Description	25
8.3.2	Constructor & Destructor Documentation	25
8.3.2.1	Billing	25
8.3.3	Member Function Documentation	25
8.3.3.1	addContributory	25
8.3.3.2	getContributories	25
8.3.3.3	getDataMap	25
8.3.3.4	getDate	25
8.3.3.5	getDescription	26
8.3.3.6	getNumber	26
8.3.3.7	getTitle	26
8.3.3.8	hydrat	26
8.3.3.9	isBilling	26
8.3.3.10	isPaid	26
8.3.3.11	operator!=	26
8.3.3.12	operator<	27
8.3.3.13	operator==	27
8.3.3.14	setDate	27
8.3.3.15	setDescription	27
8.3.3.16	setIsBilling	27
8.3.3.17	setIsPaid	28
8.3.3.18	setNumber	28
8.3.3.19	setTitle	28
8.4	Databases::BillingDatabase Class Reference	28
8.4.1	Detailed Description	29
8.4.2	Member Function Documentation	29
8.4.2.1	addBilling	29
8.4.2.2	addBillingProject	29
8.4.2.3	getAllBillingsOfProject	30
8.4.2.4	getBilling	30
8.4.2.5	getBilling	30
8.4.2.6	getBillingsTable	30
8.4.2.7	getMaxBillingNumber	31
8.4.2.8	getMaxQuoteNumber	31
8.4.2.9	instance	31
8.4.2.10	isBillingPaid	31
8.4.2.11	removeBilling	31

8.4.2.12	removeBillingProject	31
8.5	BillingDatabaseTest Class Reference	32
8.6	BillingModelTest Class Reference	32
8.7	Gui::Widgets::WdgModels::BillingsTableModel Class Reference	32
8.7.1	Detailed Description	33
8.7.2	Constructor & Destructor Documentation	33
8.7.2.1	BillingsTableModel	33
8.7.3	Member Function Documentation	34
8.7.3.1	append	34
8.7.3.2	columnCount	34
8.7.3.3	count	34
8.7.3.4	data	34
8.7.3.5	flags	34
8.7.3.6	getBillings	35
8.7.3.7	headerData	35
8.7.3.8	remove	35
8.7.3.9	rowCount	35
8.7.3.10	setData	35
8.8	Gui::Widgets::CheckFields::CheckCity Class Reference	36
8.8.1	Detailed Description	36
8.8.2	Constructor & Destructor Documentation	36
8.8.2.1	CheckCity	36
8.9	Gui::Widgets::CheckFields::CheckCountry Class Reference	36
8.9.1	Detailed Description	37
8.9.2	Constructor & Destructor Documentation	37
8.9.2.1	CheckCountry	37
8.10	Gui::Widgets::CheckFields::CheckEmail Class Reference	37
8.10.1	Detailed Description	38
8.10.2	Constructor & Destructor Documentation	38
8.10.2.1	CheckEmail	38
8.10.3	Member Function Documentation	38
8.10.3.1	check	38
8.11	Gui::Widgets::CheckFields::CheckFieldsLetters Class Reference	39
8.11.1	Detailed Description	39
8.11.2	Constructor & Destructor Documentation	39
8.11.2.1	CheckFieldsLetters	39
8.11.3	Member Function Documentation	39
8.11.3.1	check	39
8.12	Gui::Widgets::CheckFields::CheckName Class Reference	40
8.12.1	Detailed Description	40

8.12.2	Constructor & Destructor Documentation	40
8.12.2.1	CheckName	40
8.13	Gui::Widgets::CheckFields::CheckPhone Class Reference	41
8.13.1	Detailed Description	41
8.13.2	Constructor & Destructor Documentation	41
8.13.2.1	CheckPhone	41
8.13.3	Member Function Documentation	41
8.13.3.1	check	41
8.13.3.2	getCountry	42
8.13.3.3	setCountry	42
8.14	Gui::Widgets::CheckFields::CheckPostalCode Class Reference	42
8.14.1	Detailed Description	43
8.14.2	Constructor & Destructor Documentation	43
8.14.2.1	CheckPostalCode	43
8.14.3	Member Function Documentation	43
8.14.3.1	check	43
8.14.3.2	getCountry	43
8.14.3.3	setCountry	43
8.15	Gui::Widgets::CheckFields::CheckQLineEdit Class Reference	44
8.15.1	Detailed Description	44
8.15.2	Constructor & Destructor Documentation	45
8.15.2.1	CheckQLineEdit	45
8.15.3	Member Function Documentation	46
8.15.3.1	getBtnValid	46
8.15.3.2	isValid	46
8.15.3.3	setBtnValid	46
8.16	Gui::Widgets::CheckFields::CheckSiretNumber Class Reference	46
8.16.1	Detailed Description	47
8.16.2	Constructor & Destructor Documentation	47
8.16.2.1	CheckSiretNumber	47
8.16.3	Member Function Documentation	47
8.16.3.1	check	47
8.17	Gui::Widgets::CheckFields::CheckUntilField Class Reference	47
8.17.1	Detailed Description	48
8.17.2	Constructor & Destructor Documentation	48
8.17.2.1	CheckUntilField	48
8.17.3	Member Function Documentation	48
8.17.3.1	check	48
8.18	Gui::Widgets::CheckFields::CheckValidField Class Reference	48
8.18.1	Detailed Description	49

8.18.2	Constructor & Destructor Documentation	49
8.18.2.1	CheckValidField	49
8.18.3	Member Function Documentation	49
8.18.3.1	check	49
8.19	Gui::Widgets::Delegates::ComboBoxDelegate Class Reference	50
8.20	Gui::Widgets::ComboBoxModelWidget Class Reference	50
8.20.1	Detailed Description	50
8.21	Mustache::Context Class Reference	51
8.21.1	Detailed Description	51
8.21.2	Constructor & Destructor Documentation	51
8.21.2.1	Context	51
8.21.3	Member Function Documentation	51
8.21.3.1	canEval	51
8.21.3.2	eval	52
8.21.3.3	isFalse	52
8.21.3.4	listCount	52
8.21.3.5	partialResolver	52
8.21.3.6	partialValue	52
8.21.3.7	pop	52
8.21.3.8	push	52
8.21.3.9	stringValue	52
8.22	ContributoriesDatabaseTest Class Reference	53
8.23	Models::ContributoriesList Class Reference	53
8.24	Gui::Widgets::WdgModels::ContributoriesTableModel Class Reference	54
8.24.1	Detailed Description	54
8.24.2	Constructor & Destructor Documentation	55
8.24.2.1	ContributoriesTableModel	55
8.24.3	Member Function Documentation	56
8.24.3.1	append	56
8.24.3.2	columnCount	56
8.24.3.3	count	56
8.24.3.4	data	56
8.24.3.5	flags	56
8.24.3.6	getContributories	57
8.24.3.7	headerData	57
8.24.3.8	remove	57
8.24.3.9	rowCount	57
8.24.3.10	setData	57
8.25	Gui::Widgets::ContributoriesWidget Class Reference	58
8.25.1	Member Function Documentation	58

8.25.1.1	add	58
8.25.1.2	getContributories	58
8.26	Models::Contributory Class Reference	59
8.26.1	Detailed Description	60
8.26.2	Constructor & Destructor Documentation	60
8.26.2.1	Contributory	60
8.26.3	Member Function Documentation	60
8.26.3.1	getDataMap	60
8.26.3.2	getDescription	60
8.26.3.3	getNbHours	60
8.26.3.4	getProject	60
8.26.3.5	hydrat	61
8.26.3.6	operator!=	62
8.26.3.7	operator==	62
8.26.3.8	setDescription	62
8.26.3.9	setNbHours	62
8.26.3.10	setProject	62
8.27	Databases::ContributoryDatabase Class Reference	63
8.27.1	Detailed Description	63
8.27.2	Member Function Documentation	64
8.27.2.1	addContributory	64
8.27.2.2	getContributory	64
8.27.2.3	getContributory	64
8.27.2.4	instance	64
8.27.2.5	removeContributory	64
8.28	ContributoryListTest Class Reference	65
8.29	ContributoryModelTest Class Reference	65
8.30	CounterContext Class Reference	65
8.30.1	Member Function Documentation	66
8.30.1.1	canEval	66
8.30.1.2	canEval	66
8.30.1.3	eval	66
8.30.1.4	eval	66
8.30.1.5	stringValue	66
8.30.1.6	stringValue	67
8.31	Models::Customer Class Reference	67
8.31.1	Detailed Description	68
8.31.2	Constructor & Destructor Documentation	69
8.31.2.1	Customer	69
8.31.3	Member Function Documentation	69

8.31.3.1	getAddress	69
8.31.3.2	getCity	69
8.31.3.3	getCompany	69
8.31.3.4	getCountry	69
8.31.3.5	getDataMap	69
8.31.3.6	getEmail	70
8.31.3.7	getFax	70
8.31.3.8	getFirstnameReferent	70
8.31.3.9	getLastnameReferent	70
8.31.3.10	getMobilePhone	70
8.31.3.11	getNameFolder	70
8.31.3.12	getPath	70
8.31.3.13	getPhone	71
8.31.3.14	getPostalCode	71
8.31.3.15	hydrat	71
8.31.3.16	operator!=	71
8.31.3.17	operator==	71
8.31.3.18	setAddress	71
8.31.3.19	setCity	72
8.31.3.20	setCompany	72
8.31.3.21	setCountry	72
8.31.3.22	setEmail	72
8.31.3.23	setFax	72
8.31.3.24	setFirstnameReferent	72
8.31.3.25	setLastnameReferent	73
8.31.3.26	setMobilePhone	74
8.31.3.27	setPhone	74
8.31.3.28	setPostalCode	74
8.32	Gui::Widgets::CustomerContextualMenu Class Reference	74
8.32.1	Detailed Description	75
8.32.2	Constructor & Destructor Documentation	75
8.32.2.1	CustomerContextualMenu	75
8.33	Databases::CustomerDatabase Class Reference	75
8.33.1	Detailed Description	76
8.33.2	Member Function Documentation	76
8.33.2.1	addCustomer	76
8.33.2.2	getCustomer	76
8.33.2.3	getCustomer	77
8.33.2.4	getCustomersTable	77
8.33.2.5	getItemBillQuote	77

8.33.2.6	getItemCustomer	77
8.33.2.7	getItemProject	78
8.33.2.8	getItemRoot	78
8.33.2.9	getNbCustomers	78
8.33.2.10	getTree	78
8.33.2.11	instance	79
8.33.2.12	removeCustomer	79
8.33.2.13	updateCustomer	79
8.34	CustomerDatabaseTest Class Reference	79
8.35	Gui::Widgets::CustomerDataWidget Class Reference	79
8.35.1	Detailed Description	80
8.35.2	Member Function Documentation	80
8.35.2.1	printInformations	80
8.36	CustomerModelTest Class Reference	80
8.37	Gui::Widgets::WdgModels::CustomersTableModel Class Reference	81
8.37.1	Detailed Description	81
8.37.2	Constructor & Destructor Documentation	82
8.37.2.1	CustomersTableModel	82
8.37.3	Member Function Documentation	83
8.37.3.1	append	83
8.37.3.2	columnCount	83
8.37.3.3	count	83
8.37.3.4	data	83
8.37.3.5	flags	83
8.37.3.6	getCustomers	84
8.37.3.7	headerData	84
8.37.3.8	remove	84
8.37.3.9	rowCount	84
8.37.3.10	setData	84
8.38	Databases::Database Class Reference	85
8.38.1	Detailed Description	86
8.38.2	Member Function Documentation	86
8.38.2.1	executeFile	86
8.38.2.2	instance	86
8.38.2.3	lastError	86
8.38.2.4	setDatabase	87
8.38.2.5	value	87
8.39	Exceptions::DbException Class Reference	87
8.39.1	Detailed Description	87
8.39.2	Constructor & Destructor Documentation	88

8.39.2.1	DbException	88
8.39.3	Member Function Documentation	88
8.39.3.1	popupMessage	88
8.40	Gui::Dialogs::DialogAddCustomer Class Reference	88
8.40.1	Detailed Description	89
8.40.2	Constructor & Destructor Documentation	89
8.40.2.1	DialogAddCustomer	89
8.41	Utils::Directories Class Reference	89
8.41.1	Member Function Documentation	89
8.41.1.1	makeDirectory	89
8.42	Gui::Widgets::Delegates::DoubleSpinBoxDelegate Class Reference	90
8.43	Exceptions::FileException Class Reference	90
8.43.1	Detailed Description	90
8.43.2	Constructor & Destructor Documentation	90
8.43.2.1	FileException	90
8.43.3	Member Function Documentation	91
8.43.3.1	popupMessage	91
8.44	Generation Class Reference	91
8.45	Generator Class Reference	91
8.46	Utils::HierarchicalSystem Class Reference	91
8.46.1	Detailed Description	92
8.46.2	Member Function Documentation	92
8.46.2.1	addBillingToProject	92
8.46.2.2	addProjectToCustomer	92
8.46.2.3	getCustomers	93
8.46.2.4	getProjects	93
8.47	Gui::Widgets::CheckFields::ICheckField Class Reference	93
8.47.1	Detailed Description	93
8.47.2	Member Function Documentation	93
8.47.2.1	check	93
8.48	Models::IModel Class Reference	94
8.48.1	Detailed Description	95
8.48.2	Member Function Documentation	95
8.48.2.1	getDataMap	95
8.48.2.2	getId	95
8.48.2.3	hydrat	95
8.48.2.4	isToRemoved	95
8.48.2.5	setId	95
8.48.2.6	setToRemoved	95
8.49	Utils::ItemType Class Reference	96

8.49.1 Detailed Description	96
8.49.2 Constructor & Destructor Documentation	96
8.49.2.1 ItemType	96
8.49.3 Member Function Documentation	97
8.49.3.1 getModel	97
8.49.3.2 getName	97
8.49.3.3 getType	97
8.49.3.4 setName	97
8.49.3.5 setType	97
8.50 ItemTypeTest Class Reference	98
8.51 Utils::Log Class Reference	98
8.51.1 Detailed Description	98
8.51.2 Member Function Documentation	98
8.51.2.1 instance	98
8.51.2.2 write	99
8.51.3 Friends And Related Function Documentation	99
8.51.3.1 operator<<	99
8.52 Gui::MainWindow Class Reference	99
8.52.1 Detailed Description	101
8.52.2 Constructor & Destructor Documentation	101
8.52.2.1 MainWindow	101
8.52.3 Member Function Documentation	101
8.52.3.1 addBill	101
8.52.3.2 addDoc	101
8.52.3.3 addProject	101
8.52.3.4 addQuote	102
8.52.3.5 editUser	102
8.52.3.6 getCurrentCustomerId	102
8.52.3.7 getCurrentCustomerName	102
8.52.3.8 getCurrentProjectId	102
8.52.3.9 getCurrentProjectName	102
8.52.3.10 getCurrentQuoteId	102
8.52.3.11 rootTree	103
8.52.3.12 search	103
8.52.3.13 treeLevel	103
8.53 Gui::Dialogs::MessageBox Class Reference	103
8.53.1 Detailed Description	104
8.53.2 Constructor & Destructor Documentation	104
8.53.2.1 MessageBox	104
8.53.3 Member Function Documentation	104

8.53.3.1	setImage	104
8.53.3.2	setText	104
8.54	Parameters Class Reference	105
8.54.1	Detailed Description	105
8.54.2	Member Data Documentation	105
8.54.2.1	DB_FILENAME	105
8.54.2.2	VERSION	105
8.55	Mustache::PartialFileLoader Class Reference	105
8.55.1	Detailed Description	106
8.55.2	Member Function Documentation	106
8.55.2.1	getPartial	106
8.56	Mustache::PartialMap Class Reference	106
8.56.1	Detailed Description	106
8.56.2	Member Function Documentation	106
8.56.2.1	getPartial	106
8.57	Mustache::PartialResolver Class Reference	107
8.57.1	Detailed Description	107
8.57.2	Member Function Documentation	107
8.57.2.1	getPartial	107
8.58	Utils::pointers Class Reference	107
8.59	Gui::Widgets::Popup Class Reference	107
8.59.1	Detailed Description	108
8.60	Models::Project Class Reference	108
8.60.1	Detailed Description	109
8.60.2	Constructor & Destructor Documentation	109
8.60.2.1	Project	109
8.60.3	Member Function Documentation	110
8.60.3.1	getBeginDate	110
8.60.3.2	getCustomer	110
8.60.3.3	getDailyRate	110
8.60.3.4	getDataMap	110
8.60.3.5	getDescription	110
8.60.3.6	getEndDate	110
8.60.3.7	getName	111
8.60.3.8	hydrat	111
8.60.3.9	operator!=	111
8.60.3.10	operator<	111
8.60.3.11	operator==	111
8.60.3.12	setBeginDate	111
8.60.3.13	setCustomer	112

8.60.3.14	setDailyRate	112
8.60.3.15	setDescription	112
8.60.3.16	setEndDate	112
8.60.3.17	setName	112
8.61	Gui::Widgets::Delegates::ProjectComboDelegate Class Reference	112
8.62	Gui::Widgets::WdgModels::ProjectContributoriesTableModel Class Reference	113
8.62.1	Constructor & Destructor Documentation	114
8.62.1.1	ProjectContributoriesTableModel	114
8.62.2	Member Function Documentation	114
8.62.2.1	columnCount	114
8.62.2.2	data	114
8.62.2.3	flags	114
8.62.2.4	headerData	115
8.62.2.5	rowCount	116
8.62.2.6	setData	116
8.63	Databases::ProjectDatabase Class Reference	116
8.63.1	Detailed Description	117
8.63.2	Member Function Documentation	117
8.63.2.1	addProject	117
8.63.2.2	getAllProjects	118
8.63.2.3	getNbProjects	118
8.63.2.4	getNbProjectsForACustomer	118
8.63.2.5	getProject	118
8.63.2.6	getProject	118
8.63.2.7	getProjectsOfCustomer	118
8.63.2.8	getProjectsTable	119
8.63.2.9	instance	119
8.63.2.10	removeProject	119
8.63.2.11	updateProject	119
8.64	ProjectDatabaseTest Class Reference	120
8.65	ProjectModelTest Class Reference	120
8.66	Gui::Widgets::WdgModels::ProjectsTableModel Class Reference	120
8.66.1	Detailed Description	121
8.66.2	Constructor & Destructor Documentation	121
8.66.2.1	ProjectsTableModel	121
8.66.3	Member Function Documentation	121
8.66.3.1	append	121
8.66.3.2	columnCount	122
8.66.3.3	count	122
8.66.3.4	data	122

8.66.3.5	flags	122
8.66.3.6	getProjects	122
8.66.3.7	headerData	122
8.66.3.8	remove	123
8.66.3.9	rowCount	123
8.66.3.10	setData	123
8.67	Gui::Widgets::ProjectsWidget Class Reference	123
8.67.1	Detailed Description	124
8.67.2	Constructor & Destructor Documentation	124
8.67.2.1	ProjectsWidget	124
8.67.3	Member Function Documentation	125
8.67.3.1	updateBtn	125
8.68	Mustache::QtVariantContext Class Reference	126
8.68.1	Detailed Description	126
8.68.2	Member Typedef Documentation	126
8.68.2.1	fn_t	126
8.68.3	Member Function Documentation	127
8.68.3.1	canEval	127
8.68.3.2	eval	127
8.68.3.3	isFalse	127
8.68.3.4	listCount	127
8.68.3.5	pop	127
8.68.3.6	push	127
8.68.3.7	stringValue	127
8.69	Models::Rate Class Reference	128
8.70	Databases::RateDatabase Class Reference	128
8.70.1	Member Function Documentation	129
8.70.1.1	instance	129
8.71	RateModelTest Class Reference	129
8.72	Gui::Widgets::RateWidget Class Reference	129
8.72.1	Detailed Description	130
8.72.2	Constructor & Destructor Documentation	130
8.72.2.1	RateWidget	130
8.72.3	Member Function Documentation	130
8.72.3.1	getDailyRate	130
8.72.3.2	getHourlyRate	130
8.72.3.3	setDailyRate	131
8.72.3.4	setHourlyRate	132
8.72.3.5	setWidgetDailyRateValue	132
8.72.3.6	setWidgetHourlyRateValue	132

8.73	Mustache::Renderer Class Reference	132
8.73.1	Detailed Description	132
8.73.2	Member Function Documentation	133
8.73.2.1	error	133
8.73.2.2	errorPartial	133
8.73.2.3	errorPos	133
8.73.2.4	render	133
8.73.2.5	setTagMarkers	133
8.74	Models::Search Class Reference	133
8.74.1	Detailed Description	134
8.74.2	Member Function Documentation	134
8.74.2.1	filterOnBillsOrQuotes	134
8.74.2.2	filterOnCompany	135
8.74.2.3	filterOnContributories	135
8.74.2.4	filterOnCustomersWithoutProject	135
8.74.2.5	filterOnNumberElements	135
8.74.2.6	filterOnProjects	135
8.74.2.7	filterOnReferentLastname	135
8.74.2.8	filterOnVarcharElements	136
8.74.2.9	getFilter	136
8.74.2.10	getGroupFilter	136
8.74.2.11	getSearchInBillsQuotes	136
8.74.2.12	getSearchInCompanies	136
8.74.2.13	getSearchInProjects	136
8.74.2.14	getSearchInReferentLastname	137
8.74.2.15	getText	137
8.74.2.16	searchInContributories	137
8.74.2.17	setGroupFilter	137
8.74.2.18	setSearchInBillsQuotes	137
8.74.2.19	setSearchInCompanies	137
8.74.2.20	setSearchInContributories	137
8.74.2.21	setSearchInProjects	138
8.74.2.22	setSearchInReferentLastname	138
8.74.2.23	setText	138
8.75	Gui::Docks::SearchDock Class Reference	138
8.76	searchTest Class Reference	139
8.77	Gui::Widgets::searchWidget Class Reference	139
8.77.1	Detailed Description	140
8.77.2	Constructor & Destructor Documentation	140
8.77.2.1	searchWidget	140

8.77.3	Member Function Documentation	140
8.77.3.1	getCurrentCustomerId	140
8.77.3.2	isCustomerSelected	140
8.77.3.3	search	140
8.78	Gui::Dialogs::StartedWindowsDialog Class Reference	141
8.79	Utils::String Class Reference	141
8.79.1	Detailed Description	142
8.79.2	Member Function Documentation	142
8.79.2.1	firstLetterToUpper	142
8.80	StringTest Class Reference	142
8.81	Mustache::Tag Struct Reference	142
8.81.1	Detailed Description	143
8.81.2	Member Enumeration Documentation	143
8.81.2.1	Type	143
8.82	TestAdder< T > Class Template Reference	143
8.83	testadder Class Reference	143
8.84	TestMustache Class Reference	144
8.85	TestRunner Class Reference	144
8.86	Gui::Widgets::Delegates::UnitComboDelegate Class Reference	144
8.87	Models::User Class Reference	145
8.87.1	Detailed Description	146
8.87.2	Constructor & Destructor Documentation	147
8.87.2.1	User	147
8.87.3	Member Function Documentation	147
8.87.3.1	getAddress	147
8.87.3.2	getCity	147
8.87.3.3	getCompany	147
8.87.3.4	getDataMap	147
8.87.3.5	getEmail	147
8.87.3.6	getFirstname	148
8.87.3.7	getLastname	148
8.87.3.8	getMobilePhone	148
8.87.3.9	getNoSiret	148
8.87.3.10	getPhone	148
8.87.3.11	getPostalCode	148
8.87.3.12	getTitle	148
8.87.3.13	getWorkspaceName	149
8.87.3.14	getWorkspacePath	149
8.87.3.15	hydrat	149
8.87.3.16	operator!=	149

8.87.3.17 operator==	149
8.87.3.18 setAddress	149
8.87.3.19 setCity	150
8.87.3.20 setCompany	150
8.87.3.21 setEmail	150
8.87.3.22 setFirstname	150
8.87.3.23 setLastname	150
8.87.3.24 setMobilePhone	150
8.87.3.25 setNoSiret	151
8.87.3.26 setPhone	152
8.87.3.27 setPostalCode	152
8.87.3.28 setTitle	152
8.87.3.29 setWorkspaceName	152
8.87.3.30 setWorkspacePath	152
8.87.3.31 updateFolders	152
8.88 Databases::UserDatabase Class Reference	153
8.88.1 Detailed Description	153
8.88.2 Member Function Documentation	153
8.88.2.1 getUser	153
8.88.2.2 instance	154
8.89 UserDatabaseTest Class Reference	154
8.90 Gui::Dialogs::UserDataDialog Class Reference	154
8.90.1 Detailed Description	155
8.90.2 Constructor & Destructor Documentation	155
8.90.2.1 UserDataDialog	155
8.91 UserModelTest Class Reference	155
Index	157

Chapter 1

FactDev documentation

This website contains the documentation of FactDev, a billings and quotes software.

Team

FACT team is a team for University Project. Members of this team are :

- Florent Berbie ([KraTuX31](#))
- Antoine de Roquemaurel ([aroquemaurel](#))
- Cédric Rohaut ([Oxynos](#))
- Manantsoa Andriamihary Razanajatovo ([manantsoa](#))

For more informations, you can go to <http://fact-team.github.io>.

What is FactDev ?

FactDev is a software for quotes and billings developped by FACT team for university project in Toulouse III University – Paul Sabatier.

This software is developed with C++ and Qt framework, and there is differents features :

- Customers database
- Differents projects for customers
- Quotes
- Billings

Documentation

You can access to the documentation generated by Doxygen here :

- [HTML Documentation](#)
- [PDF Documentation](#)

Installation and using

- [User Manual](#)

Chapter 2

README

! [Build Status] (<https://travis-ci.org/robertknight/qt-mustache.svg?branch=master>)

Qt Mustache

qt-mustache is a simple library for rendering **Mustache templates**.

Example Usage

```
““cpp #include "mustache.h"
```

```
QVariantHash contact; contact["name"] = "John Smith"; contact["email"] = "john.smith@gmail.com";
```

```
QString contactTemplate = "<b>{{name}}</b> <a href='mailto:{{email}}'>{{email}}";
```

```
Mustache::Renderer renderer; Mustache::QtVariantContext context(contact);
```

```
QTextStream output(stdout); output << renderer.render(contactTemplate, &context); ““
```

Outputs: John Smith john.smith@gmail.com

For further examples, see the tests in `test_mustache.cpp`

Building

- To build the tests, run `qmake` followed by `make`
- To use qt-mustache in your project, just add the `mustache.h` and `mustache.cpp` files to your project.

License

qt-mustache is licensed under the BSD license.

Dependencies

qt-mustache depends on the QtCore library. It is compatible with Qt 4 and Qt 5.

Usage

Syntax

qt-mustache uses the standard Mustache syntax. See the [Mustache manual](#) for details.

Data Sources

qt-mustache expands Mustache tags using values from a `Mustache::Context`. `Mustache::QtVariantContext` is a simple context implementation which wraps a `QVariantHash` or `QVariantMap`. If you want to render a template using a custom data source, you can either create a `QVariantHash` which mirrors the data source or you can re-implement `Mustache::Context`.

Partials

When a `{{>partial}}` Mustache tag is encountered, qt-mustache will attempt to load the partial using a `Mustache::PartialResolver` provided by the context. `Mustache::PartialMap` is a simple resolver which takes a `QHash<QString,QString>` map of partial names to values and looks up partials in that map. `Mustache::PartialFileLoader` is another simple resolver which fetches partials from `<partial name>.mustache` files in a specified directory.

You can re-implement the `Mustache::PartialResolver` interface if you want to load partials from a custom source (eg. a database).

Error Handling

If an error occurs when rendering a template, `Mustache::Renderer::errorPosition()` is set to non-negative value and template rendering stops. If the error occurs whilst rendering a partial template, `errorPartial()` contains the name of the partial.

Lambdas

The [Mustache manual](#) provides a mechanism to customize rendering of template sections by setting the value for a tag to a callable object (eg. a lambda in Ruby or Javascript), which takes the unrendered block of text for a template section and renders it itself. qt-mustache supports this via the `Context::canEval()` and `Context::eval()` methods.

Chapter 3

QTestRunner

A repo for Increase QTest productivity

Thanks to <https://marcoarena.wordpress.com/2012/06/23/increase-your-qtest-productivity/>!

The QTestLib framework is a tool for unit testing Qt based applications and libraries. I find it precious and simple to use, though it lacks some important features, supported, for example, by GTest. I'm not talking about mocking – for this you generally need an out-and-out framework (like GMock) – instead, I'm referring to simple things like fast deploying. Suppose you have written a test class like this:

This repo contains only the code in this article.

Chapter 4

Namespace Index

4.1 Namespace List

Here is a list of all documented namespaces with brief descriptions:

Databases		
	Class for Database , contains queries	??
Gui	??
Gui::Widgets		
	Contains Widgets classes	??
Models		
	Models classes	??

Chapter 5

Hierarchical Index

5.1 Class Hierarchy

This inheritance list is sorted roughly, but not completely, alphabetically:

Mustache::Context	??
Mustache::QtVariantContext	??
CounterContext	??
CounterContext	??
ContributoryListTest	??
Databases::Database	??
Databases::BillingDatabase	??
Databases::ContributoryDatabase	??
Databases::CustomerDatabase	??
Databases::ProjectDatabase	??
Databases::RateDatabase	??
Databases::UserDatabase	??
Utils::Directories	??
exception	
Exceptions::DbException	??
Exceptions::FileException	??
Generator	??
Utils::HierarchicalSystem	??
Gui::Widgets::CheckFields::ICheckField	??
Gui::Widgets::CheckFields::CheckQLineEdit	??
Gui::Widgets::CheckFields::CheckEmail	??
Gui::Widgets::CheckFields::CheckSiretNumber	??
Gui::Widgets::CheckFields::CheckUntilField	??
Gui::Widgets::CheckFields::CheckFieldsLetters	??
Gui::Widgets::CheckFields::CheckCity	??
Gui::Widgets::CheckFields::CheckCountry	??
Gui::Widgets::CheckFields::CheckName	??
Gui::Widgets::CheckFields::CheckPhone	??
Gui::Widgets::CheckFields::CheckPostalCode	??
Gui::Widgets::CheckFields::CheckValidField	??
Models::IModel	??
Models::Billing	??
Models::Contributory	??
Models::Customer	??
Models::Project	??
Models::User	??

Utils::ItemType	??
Utils::Log	??
Parameters	??
Mustache::PartialResolver	??
Mustache::PartialFileLoader	??
Mustache::PartialMap	??
Utils::pointers	??
Gui::Widgets::Popup	??
QAbstractTableModel	
Gui::Widgets::WdgModels::BillingsTableModel	??
Gui::Widgets::WdgModels::ContributoriesTableModel	??
Gui::Widgets::WdgModels::CustomersTableModel	??
Gui::Widgets::WdgModels::ProjectContributoriesTableModel	??
Gui::Widgets::WdgModels::ProjectsTableModel	??
QDialog	
Gui::Dialogs::AddProjectDialog	??
Gui::Dialogs::AddQuoteDialog	??
Gui::Dialogs::DialogAddCustomer	??
Gui::Dialogs::MessageBox	??
Gui::Dialogs::StartedWindowsDialog	??
Gui::Dialogs::UserDataDialog	??
QDockWidget	
Gui::Docks::SearchDock	??
QItemDelegate	
Gui::Widgets::Delegates::ComboBoxDelegate	??
Gui::Widgets::Delegates::ProjectComboDelegate	??
Gui::Widgets::Delegates::UnitComboDelegate	??
Gui::Widgets::Delegates::DoubleSpinBoxDelegate	??
QLineEdit	
Gui::Widgets::CheckFields::CheckQLineEdit	??
QMainWindow	
Gui::MainWindow	??
QMap	
Models::ContributoriesList	??
QMenu	
Gui::Widgets::CustomerContextualMenu	??
QObject	
BillingDatabaseTest	??
BillingModelTest	??
ContributoriesDatabaseTest	??
ContributoryModelTest	??
CustomerDatabaseTest	??
CustomerModelTest	??
Generation	??
ItemTypeTest	??
ProjectDatabaseTest	??
ProjectModelTest	??
RateModelTest	??
searchTest	??
StringTest	??
TestMustache	??
TestMustache	??
UserDatabaseTest	??
UserModelTest	??
QWidget	
Gui::Widgets::ComboBoxModelWidget	??
Gui::Widgets::ContributoriesWidget	??
Gui::Widgets::CustomerDataWidget	??

Gui::Widgets::ProjectsWidget	??
Gui::Widgets::RateWidget	??
Gui::Widgets::searchWidget	??
Models::Rate	??
Mustache::Renderer	??
Models::Search	??
Utils::String	??
Mustache::Tag	??
TestAdder< T >	??
testadder	??
TestRunner	??

Chapter 6

Class Index

6.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

Gui::Dialogs::AddProjectDialog	
Windows to add a new Project	??
Gui::Dialogs::AddQuoteDialog	
Window to add or modify a Quote	??
Models::Billing	
: Billing or Quote of a Customer	??
Databases::BillingDatabase	
The BillingDatabase class Billing (or Quote) table database	??
BillingDatabaseTest	??
BillingModelTest	??
Gui::Widgets::WdgModels::BillingsTableModel	
For a Billing table	??
Gui::Widgets::CheckFields::CheckCity	
Line Edit of City with a check icon	??
Gui::Widgets::CheckFields::CheckCountry	
CheckCountry::CheckCountry Line Edit of country with a check icon	??
Gui::Widgets::CheckFields::CheckEmail	
Line Edit of email with a check icon	??
Gui::Widgets::CheckFields::CheckFieldsLetters	
Field with only letters (no numbers)	??
Gui::Widgets::CheckFields::CheckName	
Line edit of name with a check icon	??
Gui::Widgets::CheckFields::CheckPhone	
Line Edit of Phone number with a check icon	??
Gui::Widgets::CheckFields::CheckPostalCode	
Line Edit of postal code with a check icon	??
Gui::Widgets::CheckFields::CheckQLineEdit	
LineEdit custom with a check of text inputed	??
Gui::Widgets::CheckFields::CheckSiretNumber	
Line Edit with a check icon	??
Gui::Widgets::CheckFields::CheckUntilField	
The CheckUntilField class	??
Gui::Widgets::CheckFields::CheckValidField	
Check field not required	??
Gui::Widgets::Delegates::ComboBoxDelegate	
Gui::Widgets::ComboBoxModelWidget	
The ComboBoxModelWidget class	??
Mustache::Context	??

ContributoriesDatabaseTest	??
Models::ContributoriesList	??
Gui::Widgets::WdgModels::ContributoriesTableModel	
For a custom table for contributories widget	??
Gui::Widgets::ContributoriesWidget	??
Models::Contributory	
The Contributory class	??
Databases::ContributoryDatabase	
The ContributoryDatabase class Contributory (or Quote) table database	??
ContributoryListTest	??
ContributoryModelTest	??
CounterContext	??
Models::Customer	
Customer	??
Gui::Widgets::CustomerContextualMenu	
Display contextual menu on a customer	??
Databases::CustomerDatabase	
The CustomerDatabase class Customer table database	??
CustomerDatabaseTest	??
Gui::Widgets::CustomerDataWidget	
Class for display info of a customer	??
CustomerModelTest	??
Gui::Widgets::WdgModels::CustomersTableModel	
For a customer table	??
Databases::Database	
The Database class Master class for all database access	??
Exceptions::DbException	
For database exception : queries, db file, ...	??
Gui::Dialogs::DialogAddCustomer	
Window to add or modify a Customer	??
Utils::Directories	??
Gui::Widgets::Delegates::DoubleSpinBoxDelegate	??
Exceptions::FileException	
For file/access file exception	??
Generation	??
Generator	??
Utils::HierarchicalSystem	
Create class which contains hierarchical system of FactDev	??
Gui::Widgets::CheckFields::ICheckField	
Interface to check fields validity	??
Models::IModel	
The IModel class	??
Utils::ItemType	
Item type model	??
ItemTypeTest	??
Utils::Log	
For Simple management of log	??
Gui::MainWindow	
Main Window of the software	??
Gui::Dialogs::MessageBox	
Information window with message	??
Parameters	
Class for simple user parameters	??
Mustache::PartialFileLoader	??
Mustache::PartialMap	??
Mustache::PartialResolver	??
Utils::pointers	??

Gui::Widgets::Popup	
Class for display popup quickly	??
Models::Project	
: Project linked to a Customer	??
Gui::Widgets::Delegates::ProjectComboDelegate	??
Gui::Widgets::WdgModels::ProjectContributoriesTableModel	??
Databases::ProjectDatabase	
Project table database	??
ProjectDatabaseTest	??
ProjectModelTest	??
Gui::Widgets::WdgModels::ProjectsTableModel	
For a Project table	??
Gui::Widgets::ProjectsWidget	
Actions on Project	??
Mustache::QtVariantContext	??
Models::Rate	??
Databases::RateDatabase	??
RateModelTest	??
Gui::Widgets::RateWidget	
Class for display Rate	??
Mustache::Renderer	??
Models::Search	
The Search class	??
Gui::Docks::SearchDock	??
searchTest	??
Gui::Widgets::searchWidget	
Class for search in database	??
Gui::Dialogs::StartedWindowsDialog	??
Utils::String	
The Utils class	??
StringTest	??
Mustache::Tag	??
TestAdder< T >	??
testadder	??
TestMustache	??
TestRunner	??
Gui::Widgets::Delegates::UnitComboDelegate	??
Models::User	
User of it application	??
Databases::UserDatabase	
Access to User data in the the table User of the Database	??
UserDatabaseTest	??
Gui::Dialogs::UserDataDialog	
Window to fill user data	??
UserModelTest	??

Chapter 7

Namespace Documentation

7.1 Databases Namespace Reference

Class for [Database](#), contains queries.

Classes

- class [BillingDatabase](#)
*The **BillingDatabase** class Billing (or Quote) table database.*
- class [ContributoryDatabase](#)
*The **ContributoryDatabase** class Contributory (or Quote) table database.*
- class [CustomerDatabase](#)
*The **CustomerDatabase** class Customer table database.*
- class [Database](#)
*The **Database** class Master class for all database access.*
- class [ProjectDatabase](#)
*The **ProjectDatabase** class Project table database.*
- class [RateDatabase](#)
- class [UserDatabase](#)
*The **UserDatabase** class Access to User data in the the table User of the **Database***

7.1.1 Detailed Description

Class for [Database](#), contains queries.

7.2 Gui Namespace Reference

Namespaces

- [Widgets](#)
*Contains **Widgets** classes.*

Classes

- class [MainWindow](#)
*The **MainWindow** class Main Window of the software.*

7.2.1 Detailed Description

Classes for Graphical User Interface

7.3 Gui::Widgets Namespace Reference

Contains [Widgets](#) classes.

Classes

- class [ComboBoxModelWidget](#)
The [ComboBoxModelWidget](#) class.
- class [ContributoriesWidget](#)
- class [CustomerContextualMenu](#)
Display contextual menu on a customer.
- class [CustomerDataWidget](#)
Class for display info of a customer.
- class [Popup](#)
Class for display popup quickly.
- class [ProjectsWidget](#)
The [ProjectsWidget](#) class Actions on Project.
- class [RateWidget](#)
Class for display Rate.
- class [searchWidget](#)
Class for search in database.

7.3.1 Detailed Description

Contains [Widgets](#) classes.

7.4 Models Namespace Reference

[Models](#) classes.

Classes

- class [Billing](#)
The [Billing](#) class : [Billing](#) or Quote of a [Customer](#).
- class [ContributoriesList](#)
- class [Contributory](#)
The [Contributory](#) class.
- class [Customer](#)
The [Customer](#) class [Customer](#).
- class [IModel](#)
The [IModel](#) class.
- class [Project](#)
The [Project](#) class : [Project](#) linked to a [Customer](#).
- class [Rate](#)

- class [Search](#)
The [Search](#) class.
- class [User](#)
The [User](#) class [User](#) of it application.

7.4.1 Detailed Description

[Models](#) classes.

Chapter 8

Class Documentation

8.1 Gui::Dialogs::AddProjectDialog Class Reference

The [AddProjectDialog](#) class Windows to add a new Project.

```
#include <addprojectdialog.h>
```

Inheritance diagram for Gui::Dialogs::AddProjectDialog:



Public Slots

- void [checkFields](#) ()
[AddProjectDialog::checkFields](#) Check if fields are valid.

Public Member Functions

- [AddProjectDialog](#) (int idProject=0, int noRowCustomer=0, QWidget *parent=0)
[AddProjectDialogAddProjectDialog](#) Construct a windows according an idCustomer and, optionnaly, an idProject
- void [accept](#) ()
[AddProjectDialog::accept](#) Valid data inputed by user and add these data in Database.
- void [reject](#) ()
[AddProjectDialog::reject](#) Cancel the operation and close the windows.
- void [fillFields](#) ()
[AddProjectDialog::fillFields](#) Fill the differents fields of the current windows according the Project data existing As a project requires to be linked to a Customer, the Customer selection part may be disable.

8.1.1 Detailed Description

The [AddProjectDialog](#) class Windows to add a new Project.

Author

Florent Berbie

See Also

Project

8.1.2 Constructor & Destructor Documentation

8.1.2.1 Gui::Dialogs::AddProjectDialog::AddProjectDialog (int *idProject* = 0, int *noRowCustomer* = 0, QWidget * *parent* = 0) [explicit]

AddProjectDialogAddProjectDialog Construct a windows according an *idCustomer* and, optionnaly, an *idProject*

Parameters

<i>noRowCustomer</i>	Row number of the Customer
<i>idProject</i>	Project identify
<i>parent</i>	QWidget of the current windows

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/dialogs/addprojectdialog.h
- /home/travis/build/FACT-Team/FactDev/src/gui/dialogs/addprojectdialog.cpp

8.2 Gui::Dialogs::AddQuoteDialog Class Reference

The [AddQuoteDialog](#) class Window to add or modify a Quote.

```
#include <addquotedialog.h>
```

Inheritance diagram for Gui::Dialogs::AddQuoteDialog:



Public Slots

- void **updateBtn** (void)

Public Member Functions

- [AddQuoteDialog](#) (bool isBilling, int idCustomer=0, int id=0, QWidget *parent=0)
AddQuoteDialog::AddQuoteDialog Construct a windows [AddQuoteDialog](#).
- void [fillFields](#) ()
AddQuoteDialog::fillFields Fill line edits with the data of the quote.
- int [getNumber](#) ()
AddQuoteDialog::getNumber return the number of bill or quote.
- void [accept](#) ()
AddQuoteDialog::accept Valid data inputed by user and add these data in Database.
- void [reject](#) ()
AddQuoteDialog::reject Cancel the operation and close the windows.

8.2.1 Detailed Description

The [AddQuoteDialog](#) class Window to add or modify a Quote.

Author

Cédric Rohaut

8.2.2 Constructor & Destructor Documentation

8.2.2.1 `Gui::Dialogs::AddQuoteDialog::AddQuoteDialog (bool isBilling, int idCustomer = 0, int id = 0, QWidget * parent = 0)`
`[explicit]`

[AddQuoteDialog::AddQuoteDialog](#) Construct a windows [AddQuoteDialog](#).

Parameters

<i>parent</i>	QWidget of the current windows
---------------	--------------------------------

8.2.3 Member Function Documentation

8.2.3.1 `int Gui::Dialogs::AddQuoteDialog::getNumber ()`

[AddQuoteDialog::getNumber](#) return the number of bill or quote.

Returns

int

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/dialogs/addquotedialog.h
- /home/travis/build/FACT-Team/FactDev/src/gui/dialogs/addquotedialog.cpp

8.3 Models::Billing Class Reference

The [Billing](#) class : [Billing](#) or Quote of a [Customer](#).

```
#include <billing.h>
```

Inheritance diagram for Models::Billing:



Public Member Functions

- [Billing](#) ()
[Billing::Billing](#). Construct a [Billing](#).
- [Billing](#) (int id)
[Billing::Billing](#). Construct a [Billing](#) or quote.
- [~Billing](#) ()

- destruct a billing object*
- void **commit** ()
 - Billing::commit.* Insert a modification in **Billing** table on the database.
- void **hydrat** (int **getId**)
 - Billing::hydrat.* Update of the **Billing** which is specified by **getId**
- void **remove** ()
 - Billing::remove.* Remove a **Billing**.
- QVariantHash **getDataMap** ()
 - getDataMap* Get all data of model with a HashMap key/value
- void **generateTex** ()
 - generateTex* Generate a .tex file for the billing
- **ContributoriesList** & **getContributories** ()
 - Billing::getContributories.* Return a map of **Contributory** for each **Project** of the **Billing**
- void **addContributory** (**Contributory** &c)
 - addContributories* Add a new contributory for project p
- double **getSumRate** ()
- double **getSumQuantity** ()
- QString **getTitle** () const
 - Billing::getTitle.* return title of **Billing**
- void **setTitle** (const QString &**getTitle**)
 - Billing::setTitle.* Modify the title of **Billing**
- QString **getDescription** () const
 - Billing::getDescription.* return description of **Billing**
- void **setDescription** (const QString &**getDescription**)
 - Billing::setDescription.* Modify the description of **Billing**
- int **getNumber** () const
 - Billing::getNumber.* Return number of the **Billing**.
- void **setNumber** (int **getNumber**)
 - Billing::setNumber.* Modify **_number** of **Billing**.
- bool **isBilling** () const
 - Billing::isBilling.* Return if it's a billing or a quote.
- void **setIsBilling** (bool **isBilling**)
 - Billing::setIsBilling.* Modify **isBilling** of **Billing**.
- QDate **getDate** () const
 - Billing::getDate.* return date of the **Billing**
- void **setDate** (const QDate &**getDate**)
 - Billing::setDate.* Modify date of the **Billing**
- bool **isPaid** () const
 - Billing::isPaid* Return TRUE if thee current billing is paid else return FALSE.
- void **setIsPaid** (bool **isPaid**)
 - Billing::setIsPaid* Define the current billing according the argument **isPaid**
- bool **operator==** (const **Billing** &b)
 - Billing::operator ==* define the operator "==" to compare two billings and to see if they are the same.
- bool **operator!=** (const **Billing** &b)
 - Billing::operator !=* defines the operator "!=" to compare two **Billing** and to see if they are different.
- void **setContributories** (const **ContributoriesList** &contributories)
- bool **operator<** (const **Billing** &b) const
 - Billing::operator <* defines the operator "<" to compare two **Billing** and to see if the first is anterior to the second.

Additional Inherited Members

8.3.1 Detailed Description

The [Billing](#) class : [Billing](#) or Quote of a [Customer](#).

Author

Cédric Rohaut for the quote part

8.3.2 Constructor & Destructor Documentation

8.3.2.1 Models::Billing::Billing (int *id*)

[Billing::Billing](#). Construct a [Billing](#) or quote.

Parameters

<i>int</i>	id
------------	----

8.3.3 Member Function Documentation

8.3.3.1 void Models::Billing::addContributory (Contributory & *c*)

addContributories Add a new contributory for project p

Parameters

<i>p</i>	The Project who contain Contributory
<i>c</i>	The new Contributory

8.3.3.2 ContributoriesList & Models::Billing::getContributories ()

[Billing::getContributories](#). Return a map of [Contributory](#) for each [Project](#) of the [Billing](#)

Returns

QMap<[Project](#), QList<Contributory>>

8.3.3.3 QVariantHash Models::Billing::getDataMap () [virtual]

getDataMap Get all data of model with a HashMap key/value

Returns

Model's data

Implements [Models::IModel](#).

8.3.3.4 QDate Models::Billing::getDate () const

[Billing::getDate](#). return date of the [Billing](#)

Returns

date of [Billing](#)

8.3.3.5 QString Models::Billing::getDescription () const

[Billing::getDescription](#). return description of [Billing](#)

Returns

description of [Billing](#)

8.3.3.6 int Models::Billing::getNumber () const

[Billing::getNumber](#). Return number of the [Billing](#).

Returns

_number of [Billing](#)

8.3.3.7 QString Models::Billing::getTitle () const

[Billing::getTitle](#). return title of [Billing](#)

Returns

title of [Billing](#)

8.3.3.8 void Models::Billing::hydrat (int *getId*) [virtual]

[Billing::hydrat](#). Update of the [Billing](#) which is specified by *getId*

Parameters

<i>getId</i>	
--------------	--

Implements [Models::IModel](#).

8.3.3.9 bool Models::Billing::isBilling () const

[Billing::isBilling](#). Return if it's a billing or a quote.

Returns

if it's billing or a quote

8.3.3.10 bool Models::Billing::isPaid () const

[Billing::isPaid](#) Return TRUE if thee current billing is paid else return FALSE.

Returns

Boolean

8.3.3.11 bool Models::Billing::operator!= (const [Billing](#) & *b*)

[Billing::operator !=](#) defines the operator "!=" to compare two [Billing](#) and to see if they are different.

Parameters

<i>b</i>	the Billing to compare with the current Billing
----------	---

Returns

true if the **Billing** are different else false

8.3.3.12 bool Models::Billing::operator< (const **Billing** & *b*) const

Billing::operator < defines the operator "<" to compare two **Billing** and to see if the first is anterior to the second.

Parameters

<i>b</i>	the Billing to compare with the current Billing
----------	---

Returns

true if the **Billing** are different else false

8.3.3.13 bool Models::Billing::operator== (const **Billing** & *b*)

Billing::operator == define the operator "==" to compare two billings and to see if they are the same.

Parameters

<i>b</i>	the Billing to compare with the current Billing
----------	---

Returns

true if they are the same billings else false

8.3.3.14 void Models::Billing::setDate (const **QDate** & *getDate*)

Billing::setDate. Modify *date* of the **Billing**

Parameters

<i>getDate</i>	the new date of the Billing
----------------	------------------------------------

8.3.3.15 void Models::Billing::setDescription (const **QString** & *getDescription*)

Billing::setDescription. Modify the description of **Billing**

Parameters

<i>getDescription</i>	Modify the description with <i>getDescription</i>
-----------------------	---

8.3.3.16 void Models::Billing::setIsBilling (bool *isBilling*)

Billing::setIsBilling. Modify *isBilling* of **Billing**.

Parameters

<i>isBilling</i>	
------------------	--

8.3.3.17 void Models::Billing::setIsPaid (bool *isPaid*)

[Billing::setIsPaid](#) Define the current billing according the argument *isPaid*

Parameters

<i>isPaid</i>	Boolean
---------------	---------

8.3.3.18 void Models::Billing::setNumber (int *getNumber*)

[Billing::setNumber](#). Modify *_number* of [Billing](#).

Parameters

<i>getNumber</i>	the new number of the Billing
------------------	---

8.3.3.19 void Models::Billing::setTitle (const QString & *getTitle*)

[Billing::setTitle](#). Modify the title of [Billing](#)

Parameters

<i>getTitle</i>	Modify the title with <i>getTitle</i>
-----------------	---------------------------------------

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/models/billing.h
- /home/travis/build/FACT-Team/FactDev/src/models/billing.cpp

8.4 Databases::BillingDatabase Class Reference

The [BillingDatabase](#) class Billing (or Quote) table database.

```
#include <billingdatabase.h>
```

Inheritance diagram for Databases::BillingDatabase:



Public Member Functions

- [Models::Billing](#) * [getBilling](#) (const int pId)
BillingDatabase::getCustomer get informations about the billing identified by pId
- [WdgModels::BillingsTableModel](#) * [getBillingsTable](#) (const int idProject) throw (DbException*)
BillingDatabase::getBillingsTable Return an item model of billings for QTableView.
- int [addBilling](#) (const [Models::Billing](#) &)

- [BillingDatabase::addBilling](#) Add the billing *pBilling* to the database.
- void [updateBilling](#) (const [Models::Billing](#) &)
BillingDatabase::updateCustomer Update informations about the billing *pCustomer*
- void [removeBilling](#) (const int *pId*)
BillingDatabase::removeCustomer Remove the billing with the id *pId*
- void [addBillingProject](#) (const int *idProject*, const int *idBilling*, const int *idContributory*)
BillingDatabase::addBillingProject Link a project, a billing and a contributory in the table *BillingProject*.
- bool [isBillingPaid](#) (const int *pId*)
BillingDatabase::isBillingPaid Return *TRUE* if the id *pId* correspond to a Billing and not quote (*isBilling* = 1) and if this billing is paid (*isPaid* = 1) else return *FALSE*.
- void [removeBillingProject](#) (const int *idProject*, const int *idBilling*, const int *idContributory*)
BillingDatabase::removeBillingProject remove a link between a project, a billing and a contributory in the table *BillingProject*.
- int [getMaxBillingNumber](#) ()
getMaxBillingNumber Get the last number of a billing
- int [getMaxQuoteNumber](#) ()
getMaxQuoteNumber Get the last number of a quote
- QSharedPointer< [Models::Billing](#) > [getBilling](#) (QStringQuery &q)
BillingDatabase::getBilling Add the element of the q request and return their.
- QMap< [Project](#) *, [Billing](#) * > [getAllBillingsOfProject](#) ()
BillingDatabase::getAllBillingsOfProject Return a map with the project id as key linked to the billing.

Static Public Member Functions

- static [BillingDatabase](#) * [instance](#) () throw (DbException*)
BillingDatabase::getInstance Return an instance of [BillingDatabase](#)

Additional Inherited Members

8.4.1 Detailed Description

The [BillingDatabase](#) class Billing (or Quote) table database.

Author

Cédric Rohaut

See Also

[Database](#)
[Billing/Quote](#)

8.4.2 Member Function Documentation

8.4.2.1 int Databases::BillingDatabase::addBilling (const [Models::Billing](#) & *pBilling*)

[BillingDatabase::addBilling](#) Add the billing *pBilling* to the database.

Returns

billing id

8.4.2.2 void Databases::BillingDatabase::addBillingProject (const int *idProject*, const int *idBilling*, const int *idContributory*)

[BillingDatabase::addBillingProject](#) Link a project, a billing and a contributory in the table *BillingProject*.

Parameters

<i>idProject</i>	Project id
<i>idBilling</i>	Billing id
<i>idContributory</i>	Contributory id

8.4.2.3 QMap< Project *, Billing * > Databases::BillingDatabase::getAllBillingsOfProject ()

[BillingDatabase::getAllBillingsOfProject](#) Return a map with the project id as key linked to the billing.

Returns

Map with projects and Billing

8.4.2.4 Models::Billing * Databases::BillingDatabase::getBilling (const int *pld*)

[BillingDatabase::getCustomer](#) get informations about the billing identified by *pld*

Parameters

<i>pld</i>	billing id
------------	------------

Returns

the Billing

8.4.2.5 QSharedPointer< Billing > Databases::BillingDatabase::getBilling (QSqlQuery & *q*)

[BillingDatabase::getBilling](#) Add the element of the *q* request and return their.

Parameters

<i>q</i>	SQL request
----------	-------------

Returns

a billing formed according to QSharedPointer

8.4.2.6 WdgModels::BillingsTableModel * Databases::BillingDatabase::getBillingsTable (const int *idProject*) throw DbException *)

[BillingDatabase::getBillingsTable](#) Return an item model of billings for QTableView.

Parameters

<i>pld</i>	the project id of the billings returned
------------	---

Exceptions

<i>DbException</i>	
--------------------	--

Returns

QStandardItemModel an item model for QTableView

8.4.2.7 int Databases::BillingDatabase::getMaxBillingNumber ()

getMaxBillingNumber Get the last number of a billing

Returns

The max number

8.4.2.8 int Databases::BillingDatabase::getMaxQuoteNumber ()

getMaxQuoteNumber Get the last number of a quote

Returns

The last number

8.4.2.9 BillingDatabase * Databases::BillingDatabase::instance () throw DbException * [static]

BillingDatabase::getInstance Return an instance of [BillingDatabase](#)

See Also

DbException

Returns

Instance of [BillingDatabase](#)

8.4.2.10 bool Databases::BillingDatabase::isBillingPaid (const int *pld*)

[BillingDatabase::isBillingPaid](#) Return TRUE if the id *pld* correspond to a Billing and not quote (isBilling = 1) and if this billing is paid (isPaid = 1) else return FALSE.

Parameters

<i>pld</i>	Billing id
------------	------------

Returns

TRUE if billing is paid

8.4.2.11 void Databases::BillingDatabase::removeBilling (const int *pld*)

BillingDatabase::removeCustomer Remove the billing with the id *pld*

Parameters

<i>pld</i>	billing id
------------	------------

8.4.2.12 void Databases::BillingDatabase::removeBillingProject (const int *idProject*, const int *idBilling*, const int *idContributory*)

[BillingDatabase::removeBillingProject](#) remove a link between a project, a billing and a contributory in the table BillingProject.

Parameters


<i>idProject</i>	Project id
<i>idBilling</i>	Billing id
<i>idContributory</i>	Contributory id

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/database/billingdatabase.h
- /home/travis/build/FACT-Team/FactDev/src/database/billingdatabase.cpp

8.5 BillingDatabaseTest Class Reference

Inheritance diagram for BillingDatabaseTest:




The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/tests/database/billingdatabasetest.h
- /home/travis/build/FACT-Team/FactDev/tests/database/billingdatabasetest.cpp

8.6 BillingModelTest Class Reference

Inheritance diagram for BillingModelTest:



The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/tests/models/billingmodeltest.h
- /home/travis/build/FACT-Team/FactDev/tests/models/billingmodeltest.cpp

8.7 Gui::Widgets::WdgModels::BillingsTableModel Class Reference

The [BillingsTableModel](#) class for a Billing table.

```
#include <billingstablemodel.h>
```

Inheritance diagram for Gui::Widgets::WdgModels::BillingsTableModel:



Public Member Functions

- [BillingsTableModel \(\)](#)
BillingsTableModel::BillingsTableModel Construct a *BillingsTableModel*.
- int [rowCount](#) (const QModelIndex &) const
BillingsTableModel::rowCount Number of billings row.
- int [columnCount](#) (const QModelIndex &) const
BillingsTableModel::columnCount Number of column of a Billing.
- QVariant [data](#) (const QModelIndex &index, int role=Qt::DisplayRole) const
BillingsTableModel::data Obtains data of a specify cell.
- QVariant [headerData](#) (int section, Qt::Orientation orientation, int role=Qt::DisplayRole) const
BillingsTableModel::headerData Obtains header title of table.
- bool [setData](#) (const QModelIndex &index, const QVariant &value, int role=Qt::EditRole)
BillingsTableModel::setData Change data of a cell.
- void [append](#) (const [Billing](#) &billing)
BillingsTableModel::append Add a new line in table.
- void [remove](#) (const int i)
BillingsTableModel::remove Remove a line.
- Qt::ItemFlags [flags](#) (const QModelIndex &index) const
BillingsTableModel::flags Differents table flags.
- int [count](#) ()
BillingsTableModel::count Number of billings in table.
- QList< [Billing](#) > [getBillings](#) () const
BillingsTableModel::getbillings Return the list of billings.

8.7.1 Detailed Description

The [BillingsTableModel](#) class for a Billing table.

Author

Florent Berbie

See Also

[Billing](#)

8.7.2 Constructor & Destructor Documentation

8.7.2.1 Gui::Widgets::WdgModels::BillingsTableModel::BillingsTableModel ()

[BillingsTableModel::BillingsTableModel](#) Construct a [BillingsTableModel](#).

Parameters

<i>parent</i>	Parent widget
---------------	---------------

8.7.3 Member Function Documentation

8.7.3.1 void Gui::Widgets::WdgModels::BillingsTableModel::append (const Billing & *billing*)

[BillingsTableModel::append](#) Add a new line in table.

Parameters

<i>Billing</i>	The new Billing
----------------	-----------------

8.7.3.2 int Gui::Widgets::WdgModels::BillingsTableModel::columnCount (const QModelIndex &) const

[BillingsTableModel::columnCount](#) Number of column of a Billing.

Returns

The number of column

8.7.3.3 int Gui::Widgets::WdgModels::BillingsTableModel::count ()

[BillingsTableModel::count](#) Number of billings in table.

Returns

The number of billings

8.7.3.4 QVariant Gui::Widgets::WdgModels::BillingsTableModel::data (const QModelIndex & *index*, int *role* = Qt::DisplayRole) const

[BillingsTableModel::data](#) Obtains data of a specify cell.

Parameters

<i>index</i>	The cell who we want data
<i>role</i>	The role of set

Returns

The data of cell

8.7.3.5 Qt::ItemFlags Gui::Widgets::WdgModels::BillingsTableModel::flags (const QModelIndex & *index*) const

[BillingsTableModel::flags](#) Differents table flags.

Parameters

<i>index</i>	The cell who we want to know flags
--------------	------------------------------------

Returns

Flags

8.7.3.6 `QList< Billing > Gui::Widgets::WdgModels::BillingsTableModel::getBillings () const`

BillingsTableModel::getbillings Return the list of billings.

Returns

list of billings

8.7.3.7 `QVariant Gui::Widgets::WdgModels::BillingsTableModel::headerData (int section, Qt::Orientation orientation, int role = Qt::DisplayRole) const`

[BillingsTableModel::headerData](#) Obtains header title of table.

Parameters

<i>section</i>	The number of column
<i>orientation</i>	The table orientation
<i>role</i>	

Returns

The Title header of column

8.7.3.8 `void Gui::Widgets::WdgModels::BillingsTableModel::remove (const int i)`

[BillingsTableModel::remove](#) Remove a line.

Parameters

<i>i</i>	The number of line to remove
----------	------------------------------

8.7.3.9 `int Gui::Widgets::WdgModels::BillingsTableModel::rowCount (const QModelIndex &) const`

[BillingsTableModel::rowCount](#) Number of billings row.

Returns

The number of billings

8.7.3.10 `bool Gui::Widgets::WdgModels::BillingsTableModel::setData (const QModelIndex & index, const QVariant & value, int role = Qt::EditRole)`

[BillingsTableModel::setData](#) Change data of a cell.

Parameters

<i>index</i>	The cell to change data
<i>value</i>	The new value
<i>role</i>	The role of cell

Returns

True if we could edit

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/widgetmodels/billingstablemodel.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/widgetmodels/billingstablemodel.cpp

8.8 Gui::Widgets::CheckFields::CheckCity Class Reference

The [CheckCity](#) class Line Edit of City with a check icon.

```
#include <checkcity.h>
```

Inheritance diagram for Gui::Widgets::CheckFields::CheckCity:



Public Member Functions

- [CheckCity](#) (QWidget *w=0, QPushButton *btn=0)
[CheckCity::CheckCity](#) Construct a [CheckCity](#).

Additional Inherited Members

8.8.1 Detailed Description

The [CheckCity](#) class Line Edit of City with a check icon.

8.8.2 Constructor & Destructor Documentation

8.8.2.1 Gui::Widgets::CheckFields::CheckCity::CheckCity (QWidget * w = 0, QPushButton * btn = 0)

[CheckCity::CheckCity](#) Construct a [CheckCity](#).

Parameters

<i>w</i>	QWidget linked to CheckCity
----------	---

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkcity.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkcity.cpp

8.9 Gui::Widgets::CheckFields::CheckCountry Class Reference

[CheckCountry::CheckCountry](#) Line Edit of country with a check icon.

```
#include <checkcountry.h>
```

Inheritance diagram for Gui::Widgets::CheckFields::CheckCountry:



Public Member Functions

- [CheckCountry](#) (QWidget *w=0, QPushButton *btn=0)
CheckEmail::CheckCountry Construct a [CheckCountry](#).

Additional Inherited Members

8.9.1 Detailed Description

[CheckCountry::CheckCountry](#) Line Edit of country with a check icon.

8.9.2 Constructor & Destructor Documentation

8.9.2.1 Gui::Widgets::CheckFields::CheckCountry::CheckCountry (QWidget * w = 0, QPushButton * btn = 0)

CheckEmail::CheckCountry Construct a [CheckCountry](#).

Parameters

<i>w</i>	QWidget linked to CheckCountry
----------	--

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkcountry.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkcountry.cpp

8.10 Gui::Widgets::CheckFields::CheckEmail Class Reference

The [CheckEmail](#) class Line Edit of email with a check icon.

```
#include <checkemail.h>
```

Inheritance diagram for Gui::Widgets::CheckFields::CheckEmail:



Public Member Functions

- [CheckEmail](#) (QWidget *w=0, QPushButton *btn=0)
[CheckEmail::CheckEmail](#) Construct a CheckMail.
- bool [check](#) (const QString text)
[CheckEmail::check](#) Check if the field email is valid. To be valid, an email address should be under this form: *me@me. - xx* An email address need:

Additional Inherited Members

8.10.1 Detailed Description

The [CheckEmail](#) class Line Edit of email with a check icon.

8.10.2 Constructor & Destructor Documentation

8.10.2.1 [Gui::Widgets::CheckFields::CheckEmail::CheckEmail](#) ([QWidget](#) * *w* = 0, [QPushButton](#) * *btn* = 0)

[CheckEmail::CheckEmail](#) Construct a CheckMail.

Parameters

<i>w</i>	QWidget linked to CheckEmail
----------	--

8.10.3 Member Function Documentation

8.10.3.1 bool [Gui::Widgets::CheckFields::CheckEmail::check](#) (const [QString](#) *text*) `[virtual]`

[CheckEmail::check](#) Check if the field email is valid. To be valid, an email address should be under this form: *me@me. xx* An email address need:

- 1 character [A-Z] or [a-z] minimum before the character `</i>`
- the character '@'
- 1 character [A-Z] or [a-z] after the character`</i>` minimum and before the character .
- 1 character [A-Z] or [a-z] minimum afer the character . Return TRUE if email address is valid, else FALSE

Parameters

<i>text</i>	
-------------	--

Returns

boolean

Implements [Gui::Widgets::CheckFields::ICheckField](#).

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkemail.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkemail.cpp

8.11 Gui::Widgets::CheckFields::CheckFieldsLetters Class Reference

The [CheckFieldsLetters](#) class Field with only letters (no numbers)

```
#include <checkfieldsletters.h>
```

Inheritance diagram for Gui::Widgets::CheckFields::CheckFieldsLetters:



Public Member Functions

- [CheckFieldsLetters](#) (QWidget *w=0, QPushButton *btn=0)
[CheckFieldsLetters::CheckFieldsLetters](#) Construct a [CheckFieldsLetters](#).
- bool [check](#) (QString text)
[CheckName::check](#) Check if the field contains only letters.

Additional Inherited Members

8.11.1 Detailed Description

The [CheckFieldsLetters](#) class Field with only letters (no numbers)

8.11.2 Constructor & Destructor Documentation

8.11.2.1 Gui::Widgets::CheckFields::CheckFieldsLetters::CheckFieldsLetters (QWidget * w = 0, QPushButton * btn = 0)

[CheckFieldsLetters::CheckFieldsLetters](#) Construct a [CheckFieldsLetters](#).

Parameters

<i>w</i>	QWidget linked to CheckFieldsLetters
----------	--

8.11.3 Member Function Documentation

8.11.3.1 bool Gui::Widgets::CheckFields::CheckFieldsLetters::check (QString *text*) [virtual]

[CheckName::check](#) Check if the field contains only letters.

Parameters

<i>text</i>	
-------------	--

Returns

boolean

Implements [Gui::Widgets::CheckFields::ICheckField](#).

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkfieldsletters.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkfieldsletters.cpp

8.12 Gui::Widgets::CheckFields::CheckName Class Reference

The [CheckName](#) class Line edit of name with a check icon.

```
#include <checkname.h>
```

Inheritance diagram for Gui::Widgets::CheckFields::CheckName:

**Public Member Functions**

- [CheckName](#) (QWidget *w=0, QPushButton *btn=0)
[CheckName::CheckName](#) Construct a [CheckName](#).

Additional Inherited Members

8.12.1 Detailed Description

The [CheckName](#) class Line edit of name with a check icon.

8.12.2 Constructor & Destructor Documentation

8.12.2.1 [Gui::Widgets::CheckFields::CheckName::CheckName](#) (QWidget * w = 0, QPushButton * btn = 0)

[CheckName::CheckName](#) Construct a [CheckName](#).

Parameters

w	QWidget linked to CheckName
---	---

The documentation for this class was generated from the following files:


- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkname.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkname.cpp

8.13 Gui::Widgets::CheckFields::CheckPhone Class Reference

The [CheckPhone](#) class Line Edit of Phone number with a check icon.

```
#include <checkphone.h>
```

Inheritance diagram for Gui::Widgets::CheckFields::CheckPhone:



Public Member Functions

- [CheckPhone](#) (QWidget *w=0, QPushButton *btn=0)
CheckPhone::CheckPhone Construct a [CheckPhone](#).
- bool [check](#) (QString text)
CheckPhone::check Check if the field is valid. To be valid, a name should be composed of a character.
- QString [getCountry](#) () const
CheckPhone::getCountry Return the country linked to current field.
- void [setCountry](#) (const QString &country)
CheckPhone::setCountry Modify the country linked to field.

Additional Inherited Members

8.13.1 Detailed Description

The [CheckPhone](#) class Line Edit of Phone number with a check icon.

8.13.2 Constructor & Destructor Documentation

8.13.2.1 Gui::Widgets::CheckFields::CheckPhone::CheckPhone (QWidget * w = 0, QPushButton * btn = 0)

[CheckPhone::CheckPhone](#) Construct a [CheckPhone](#).

Parameters

<i>w</i>	QWidget linked to CheckPhone
----------	--

8.13.3 Member Function Documentation

8.13.3.1 `bool Gui::Widgets::CheckFields::CheckPhone::check (QString text) [virtual]`

[CheckPhone::check](#) Check if the field is valid. To be valid, a name should be composed of a character.

Parameters

<i>text</i>	
-------------	--

Returns

boolean

Implements [Gui::Widgets::CheckFields::!CheckField](#).

8.13.3.2 `QString Gui::Widgets::CheckFields::CheckPhone::getCountry () const`

[CheckPhone::getCountry](#) Return the country linked to current field.

Returns

8.13.3.3 `void Gui::Widgets::CheckFields::CheckPhone::setCountry (const QString & country)`

[CheckPhone::setCountry](#) Modify the *country* linked to field.

Parameters

<i>country</i>	New country
----------------	-------------

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkphone.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkphone.cpp

8.14 Gui::Widgets::CheckFields::CheckPostalCode Class Reference

The [CheckPostalCode](#) class Line Edit of postal code with a check icon.

```
#include <checkpostalcode.h>
```

Inheritance diagram for Gui::Widgets::CheckFields::CheckPostalCode:



Public Member Functions

- [CheckPostalCode](#) (QWidget *w=0, QPushButton *btn=0)
[CheckPostalCode::CheckPostalCode](#) Construct a [CheckPostalCode](#).
- bool [check](#) (QString text)
[CheckPostalCode::check](#) Check if the field is valid. To be valid, a name should be composed of a character.
- QString [getCountry](#) () const
[CheckPostalCode::getCountry](#) Return the country linked to current field.
- void [setCountry](#) (const QString &country)
[CheckPostalCode::setCountry](#) Modify the country linked to field.

Additional Inherited Members

8.14.1 Detailed Description

The [CheckPostalCode](#) class Line Edit of postal code with a check icon.

8.14.2 Constructor & Destructor Documentation

8.14.2.1 [Gui::Widgets::CheckFields::CheckPostalCode::CheckPostalCode](#) ([QWidget](#) * *w* = 0, [QPushButton](#) * *btn* = 0)

[CheckPostalCode::CheckPostalCode](#) Construct a [CheckPostalCode](#).

Parameters

<i>w</i>	QWidget linked to CheckPostalCode
----------	---

8.14.3 Member Function Documentation

8.14.3.1 bool [Gui::Widgets::CheckFields::CheckPostalCode::check](#) ([QString](#) *text*) [virtual]

[CheckPostalCode::check](#) Check if the field is valid. To be valid, a name should be composed of a character.

Parameters

<i>text</i>	
-------------	--

Returns

boolean

Implements [Gui::Widgets::CheckFields::ICheckField](#).

8.14.3.2 QString Gui::Widgets::CheckFields::CheckPostalCode::getCountry () const

[CheckPostalCode::getCountry](#) Return the country linked to current field.

Returns

country

8.14.3.3 void Gui::Widgets::CheckFields::CheckPostalCode::setCountry (const QString & country)

[CheckPostalCode::setCountry](#) Modify the *country* linked to field.

Parameters

<i>country</i>	New country
----------------	-------------

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkpostalcode.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkpostalcode.cpp

8.15 Gui::Widgets::CheckFields::CheckQLineEdit Class Reference

The [CheckQLineEdit](#) class QLineEdit custom with a check of text inputed.

```
#include <checkqlineedit.h>
```

Inheritance diagram for Gui::Widgets::CheckFields::CheckQLineEdit:



Public Slots

- void [fieldTextChanged](#) (const QString &text)
[CheckQLineEdit::fieldTextChanged](#) For each new characater inputed or removed, displays an icon to show if the field is valid or not.

Public Member Functions

- [CheckQLineEdit](#) (QWidget *parent=0, QPushButton *btn=0)
[CheckQLineEdit::CheckQLineEdit](#) Construct a [CheckQLineEdit](#).
- void [displayCheckValidFieldIcon](#) ()
[CheckQLineEdit::displayCheckValidFieldIcon](#) Display a valid icon into the field.
- void [displayCheckNoValidFieldIcon](#) ()
[CheckQLineEdit::displayCheckNoValidFieldIcon](#) Display a "no valid" icon into the field.
- QPushButton * [getBtnValid](#) () const
[CheckQLineEdit::getBtnValid](#).
- void [setBtnValid](#) (QPushButton *getBtnValid)

[CheckQLineEdit::setBtnValid.](#)

- bool [isValid](#) ()

isValid Return true if the current field if valid

8.15.1 Detailed Description

The [CheckQLineEdit](#) class QLineEdit custom with a check of text inputed.

8.15.2 Constructor & Destructor Documentation

8.15.2.1 [Gui::Widgets::CheckFields::CheckQLineEdit::CheckQLineEdit](#) (QWidget * *parent* = 0, QPushButton * *btn* = 0)
[explicit]

[CheckQLineEdit::CheckQLineEdit](#) Construct a [CheckQLineEdit](#).

Parameters

<i>parent</i>	
---------------	--

8.15.3 Member Function Documentation

8.15.3.1 QPushButton * [Gui::Widgets::CheckFields::CheckQLineEdit::getBtnValid](#) () const

[CheckQLineEdit::getBtnValid.](#)

Returns

a

8.15.3.2 bool [Gui::Widgets::CheckFields::CheckQLineEdit::isValid](#) ()

isValid Return true if the current field if valid

Returns

boolean

8.15.3.3 void [Gui::Widgets::CheckFields::CheckQLineEdit::setBtnValid](#) (QPushButton * *getBtnValid*)

[CheckQLineEdit::setBtnValid.](#)

Parameters

<i>getBtnValid</i>	
--------------------	--

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkqlineedit.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkqlineedit.cpp

8.16 Gui::Widgets::CheckFields::CheckSiretNumber Class Reference

The [CheckSiretNumber](#) class Line Edit with a check icon.

```
#include <checksiretnumber.h>
```

Inheritance diagram for Gui::Widgets::CheckFields::CheckSiretNumber:



Public Member Functions

- [CheckSiretNumber](#) (QWidget *w=0, QPushButton *btn=0)
CheckSiretNumber::CheckSiretNumber Construct a [CheckSiretNumber](#).
- bool [check](#) (QString text)
CheckSiretNumber::check Check if the field noSiret is valid. To be valid, a SIRET number should be composed of numbers.

Additional Inherited Members

8.16.1 Detailed Description

The [CheckSiretNumber](#) class Line Edit with a check icon.

8.16.2 Constructor & Destructor Documentation

8.16.2.1 [Gui::Widgets::CheckFields::CheckSiretNumber::CheckSiretNumber](#) (QWidget * w = 0, QPushButton * btn = 0)

[CheckSiretNumber::CheckSiretNumber](#) Construct a [CheckSiretNumber](#).

Parameters

<i>w</i>	QWidget linked to CheckSiretNumber
----------	--

8.16.3 Member Function Documentation

8.16.3.1 bool [Gui::Widgets::CheckFields::CheckSiretNumber::check](#) (QString *text*) [virtual]

[CheckSiretNumber::check](#) Check if the field noSiret is valid. To be valid, a SIRET number should be composed of numbers.

Parameters

<i>text</i>	
-------------	--

Returns

boolean

Implements [Gui::Widgets::CheckFields::ICheckField](#).

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checksiretnumber.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checksiretnumber.cpp

8.17 Gui::Widgets::CheckFields::CheckUntilField Class Reference

The [CheckUntilField](#) class.

```
#include <checkuntilfield.h>
```

Inheritance diagram for Gui::Widgets::CheckFields::CheckUntilField:



Public Member Functions

- [CheckUntilField](#) (QWidget *w=0, QPushButton *btn=0)
[CheckUntilField::CheckUntilField](#) Construct a [CheckUntilField](#).
- bool [check](#) (QString text)
[CheckUntilField::check](#) Check if the field is valid. To be valid, a name should be composed of a character.

Additional Inherited Members

8.17.1 Detailed Description

The [CheckUntilField](#) class.

8.17.2 Constructor & Destructor Documentation

8.17.2.1 [Gui::Widgets::CheckFields::CheckUntilField::CheckUntilField \(QWidget * w = 0, QPushButton * btn = 0 \)](#)

[CheckUntilField::CheckUntilField](#) Construct a [CheckUntilField](#).

Parameters

<i>w</i>	QWidget linked to CheckUntilField
----------	---

8.17.3 Member Function Documentation

8.17.3.1 bool [Gui::Widgets::CheckFields::CheckUntilField::check \(QString text \)](#) [virtual]

[CheckUntilField::check](#) Check if the field is valid. To be valid, a name should be composed of a character.

Parameters

<i>text</i>	
-------------	--

Returns

boolean

Implements [Gui::Widgets::CheckFields::ICheckField](#).

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkuntilfield.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkuntilfield.cpp

8.18 Gui::Widgets::CheckFields::CheckValidField Class Reference

The [CheckValidField](#) class Check field not required.

```
#include <checkvalidfield.h>
```

Inheritance diagram for Gui::Widgets::CheckFields::CheckValidField:



Public Member Functions

- [CheckValidField](#) (QWidget *w=0, QPushButton *btn=0)
CheckValidField::CheckValidField.
- bool [check](#) (QString text)
CheckValidField::check Return TRUE : the field is not required.

Additional Inherited Members

8.18.1 Detailed Description

The [CheckValidField](#) class Check field not required.

8.18.2 Constructor & Destructor Documentation

8.18.2.1 [Gui::Widgets::CheckFields::CheckValidField::CheckValidField \(QWidget * w = 0, QPushButton * btn = 0 \)](#)

[CheckValidField::CheckValidField.](#)

Parameters

<i>w</i>	QWidget linked to CheckValidField
----------	---

8.18.3 Member Function Documentation

8.18.3.1 bool Gui::Widgets::CheckFields::CheckValidField::check (QString *text*) [virtual]

[CheckValidField::check](#) Return TRUE : the field is not required.

Parameters

<i>text</i>	
-------------	--

Returns

boolean

Implements [Gui::Widgets::CheckFields::ICheckField](#).

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkvalidfield.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/checkvalidfield.cpp

8.19 Gui::Widgets::Delegates::ComboBoxDelegate Class Reference

Inheritance diagram for Gui::Widgets::Delegates::ComboBoxDelegate:



Public Member Functions

- **ComboBoxDelegate** (QObject *parent=0)
- virtual QWidget * **createEditor** (QWidget *parent, const QStyleOptionViewItem &option, const QModelIndex &index) const =0
- void **paint** (QPainter *painter, const QStyleOptionViewItem &option, const QModelIndex &index) const =0
- void **setEditorData** (QWidget *editor, const QModelIndex &index) const
- void **setModelData** (QWidget *editor, QAbstractItemModel *model, const QModelIndex &index) const
- void **updateEditorGeometry** (QWidget *editor, const QStyleOptionViewItem &option, const QModelIndex &index) const

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/delegates/comboboxdelegate.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/delegates/comboboxdelegate.cpp

8.20 Gui::Widgets::ComboBoxModelWidget Class Reference

The [ComboBoxModelWidget](#) class.

```
#include <comboboxmodelwidget.h>
```

Inheritance diagram for Gui::Widgets::ComboBoxModelWidget:



Public Member Functions

- **ComboBoxModelWidget** (QWidget *parent=0)

8.20.1 Detailed Description

The [ComboBoxModelWidget](#) class.

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/comboboxmodelwidget.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/comboboxmodelwidget.cpp

8.21 Mustache::Context Class Reference

```
#include <mustache.h>
```

Inheritance diagram for Mustache::Context:



Public Member Functions

- [Context](#) ([PartialResolver](#) *resolver=0)
- virtual QString [stringValue](#) (const QString &key) const =0
- virtual bool [isFalse](#) (const QString &key) const =0
- virtual int [listCount](#) (const QString &key) const =0
- virtual void [push](#) (const QString &key, int index=-1)=0
- virtual void [pop](#) ()=0
- QString [partialValue](#) (const QString &key) const
- [PartialResolver](#) * [partialResolver](#) () const
- virtual bool [canEval](#) (const QString &key) const
- virtual QString [eval](#) (const QString &key, const QString &_template, [Renderer](#) *renderer)

8.21.1 Detailed Description

[Context](#) is an interface that [Mustache::Renderer::render\(\)](#) uses to fetch substitutions for template tags.

8.21.2 Constructor & Destructor Documentation

8.21.2.1 `Context::Context (PartialResolver * resolver = 0)` `[explicit]`

Create a context. *resolver* is used to fetch the expansions for any `{{>partial}}` tags which appear in a template.

8.21.3 Member Function Documentation

8.21.3.1 `bool Context::canEval (const QString & key) const` `[virtual]`

Returns true if [eval\(\)](#) should be used to render section tags using *key*. If [canEval\(\)](#) returns true for a key, the renderer will pass the literal, unrendered block of text for the section to [eval\(\)](#) and replace the section with the result.

[canEval\(\)](#) and [eval\(\)](#) are equivalents for callable objects (eg. lambdas) in other Mustache implementations.

The default implementation always returns false.

Reimplemented in [CounterContext](#), [CounterContext](#), and [Mustache::QtVariantContext](#).

8.21.3.2 `QString Context::eval (const QString & key, const QString & _template, Renderer * renderer)` `[virtual]`

Callback used to render a template section with the given *key*. *renderer* will substitute the original section tag with the result of [eval\(\)](#).

The default implementation returns an empty string.

Reimplemented in [CounterContext](#), [CounterContext](#), and [Mustache::QtVariantContext](#).

8.21.3.3 `virtual bool Mustache::Context::isFalse (const QString & key) const` `[pure virtual]`

Returns true if the value for *key* is 'false' or an empty list. 'False' values typically include empty strings, the boolean value false etc.

When processing a section Mustache tag, the section is not rendered if the key is false, or for an inverted section tag, the section is only rendered if the key is false.

Implemented in [Mustache::QtVariantContext](#).

8.21.3.4 `virtual int Mustache::Context::listCount (const QString & key) const` `[pure virtual]`

Returns the number of items in the list value for *key* or 0 if the value for *key* is not a list.

Implemented in [Mustache::QtVariantContext](#).

8.21.3.5 `PartialResolver * Context::partialResolver () const`

Returns the partial resolver passed to the constructor.

8.21.3.6 `QString Context::partialValue (const QString & key) const`

Returns the partial template for a given *key*.

8.21.3.7 virtual void Mustache::Context::pop () [pure virtual]

Exit the current context.

Implemented in [Mustache::QtVariantContext](#).

8.21.3.8 virtual void Mustache::Context::push (const QString & key, int index = -1) [pure virtual]

Set the current context to the value for `key`. If `index` is ≥ 0 , set the current context to the `index`'th value in the list value for `key`.

Implemented in [Mustache::QtVariantContext](#).

8.21.3.9 virtual QString Mustache::Context::stringValue (const QString & key) const [pure virtual]

Returns a string representation of the value for `key` in the current context. This is used to replace a Mustache value tag.

Implemented in [CounterContext](#), [CounterContext](#), and [Mustache::QtVariantContext](#).

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/libs/qt-mustache/src/mustache.h
- /home/travis/build/FACT-Team/FactDev/src/libs/qt-mustache/src/mustache.cpp

8.22 ContributoriesDatabaseTest Class Reference

Inheritance diagram for ContributoriesDatabaseTest:




The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/tests/database/contributoriesdatabasetest.h
- /home/travis/build/FACT-Team/FactDev/tests/database/contributoriesdatabasetest.cpp

8.23 Models::ContributoriesList Class Reference

Inheritance diagram for Models::ContributoriesList:



Public Member Functions

- virtual void **commit** ()
commit Update or insert data into the database
- void **addContributory** (Models::Contributory &contributory)
- void **addProject** (Project *p, Models::Rate rate)
- QList< Contributory > & **getContributories** (Project *p)
- int **getIldBilling** () const
- void **setIldBilling** (int getIldBilling)
- bool **getInsert** () const
- void **setInsert** (bool getInsert)
- int **getNbProjects** ()
- double **getSumRate** ()
- double **getSumQuantity** ()
- QSharedPointer< Customer > **getCustomer** ()
- QList< Project * > **getProjects** ()
- QList< Contributory > * **getAllContributories** ()
- Models::Rate **getRate** (Models::Project *project)
- QVariantList **getDataMap** ()

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/models/contributorieslist.h
- /home/travis/build/FACT-Team/FactDev/src/models/contributorieslist.cpp

8.24 Gui::Widgets::WdgModels::ContributoriesTableModel Class Reference

The [ContributoriesTableModel](#) class for a custom table for contributories widget.

```
#include <contributoriestablemodel.h>
```

Inheritance diagram for Gui::Widgets::WdgModels::ContributoriesTableModel:



Public Member Functions

- [ContributoriesTableModel](#) (QObject *parent=0)
ContributoriesTableModel Construct a ContributoriesTableModel.
- int **rowCount** (const QModelIndex &) const
rowCount Number of contributories row
- int **columnCount** (const QModelIndex &) const
columnCount Number of column of a contributory
- QVariant **data** (const QModelIndex &index, int role) const
data Obtains data of a specify cell
- QVariant **headerData** (int section, Qt::Orientation orientation, int role) const
headerData Obtains header title of table
- bool **setData** (const QModelIndex &index, const QVariant &value, int role=Qt::EditRole)
setData Change data of a cell

- void **append** (const [Contributory](#) &contributory)
append Add a new line in table
- void **remove** (const int i)
remove Remove a line
- Qt::ItemFlags **flags** (const QModelIndex &index) const
flags Differents table flags
- QList< [Contributory](#) > **getContributories** ()
getContributories Get all contributories of table
- int **count** ()
count Number of contributories in table
- double **getSumQuantity** () const
- void **clear** ()

8.24.1 Detailed Description

The [ContributoriesTableModel](#) class for a custom table for contributories widget.

Author

Antoine de Roquemaurel

See Also

[Contributory](#)

8.24.2 Constructor & Destructor Documentation

8.24.2.1 `Gui::Widgets::WdgModels::ContributoriesTableModel::ContributoriesTableModel (QObject * parent = 0)`

[ContributoriesTableModel](#) Construct a [ContributoriesTableModel](#).

Parameters

<i>parent</i>	Parent widget
---------------	---------------

8.24.3 Member Function Documentation

8.24.3.1 `void Gui::Widgets::WdgModels::ContributoriesTableModel::append (const Contributory & contributory)`

append Add a new line in table

Parameters

<i>contributory</i>	The new contributory
---------------------	----------------------

8.24.3.2 `int Gui::Widgets::WdgModels::ContributoriesTableModel::columnCount (const QModelIndex &) const`

columnCount Number of column of a contributory

Returns

The number of column

8.24.3.3 int Gui::Widgets::WdgModels::ContributoriesTableModel::count ()

count Number of contributories in table

Returns

The number of contributories

8.24.3.4 QVariant Gui::Widgets::WdgModels::ContributoriesTableModel::data (const QModelIndex & *index*, int *role*) const

data Obtains data of a specify cell

Parameters

<i>index</i>	The cell who we want data
<i>role</i>	The role of set

Returns

The data of cell

8.24.3.5 Qt::ItemFlags Gui::Widgets::WdgModels::ContributoriesTableModel::flags (const QModelIndex & *index*) const

flags Differents table flags

Parameters

<i>index</i>	The cell who we want to know flags
--------------	------------------------------------

Returns

Flags

8.24.3.6 QList< Contributory > Gui::Widgets::WdgModels::ContributoriesTableModel::getContributories ()

getContributories Get all contributories of table

Returns

The contributory list

8.24.3.7 QVariant Gui::Widgets::WdgModels::ContributoriesTableModel::headerData (int *section*, Qt::Orientation *orientation*, int *role*) const

headerData Obtains header title of table

Parameters

<i>section</i>	The number of column
<i>orientation</i>	The table orientation
<i>role</i>	

Returns

The Title header of column

8.24.3.8 void Gui::Widgets::WdgModels::ContributoriesTableModel::remove (const int *i*)

remove Remove a line

Parameters

<i>i</i>	The number of line to remove
----------	------------------------------

8.24.3.9 `int Gui::Widgets::WdgModels::ContributoriesTableModel::rowCount (const QModelIndex &) const`

rowCount Number of contributories row

Returns

The number of contributories

8.24.3.10 `bool Gui::Widgets::WdgModels::ContributoriesTableModel::setData (const QModelIndex & index, const QVariant & value, int role = Qt::EditRole)`

setData Change data of a cell

Parameters

<i>index</i>	The cell to change data
<i>value</i>	The new value
<i>role</i>	The role of cell

Returns

True if we could edit

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/widgetmodels/contributoriesstablemodel.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/widgetmodels/contributoriesstablemodel.cpp

8.25 Gui::Widgets::ContributoriesWidget Class Reference

Inheritance diagram for Gui::Widgets::ContributoriesWidget:



Public Slots

- void **add** (void)
add Add a new empty contributory
- void **remove** (void)
remove Remove the current contributory
- void **addProject** (QPair< **Project** *, **Rate** > *p=0)
- void **removeProject** (void)
- void **changeProject** (void)
- void **editing** (void)
- void **updateUi** (void)
- void **updatePrice** (void)

Signals

- void **contributoryChanged** ()

Public Member Functions

- **ContributoriesWidget** (QSharedPointer< [Customer](#) > c, QWidget *parent=0)
- [ContributoriesList](#) * **getContributories** () const
getContributories Get contributories List
- int **count** ()
- void **add** ([ContributoriesList](#) &list)
add Add the Contributory c in the model

8.25.1 Member Function Documentation

8.25.1.1 void Gui::Widgets::ContributoriesWidget::add ([ContributoriesList](#) & *list*)

add Add the Contributory *c* in the model

Parameters

<i>c</i>	the Contributory
----------	-------------------------

8.25.1.2 [ContributoriesList](#) * Gui::Widgets::ContributoriesWidget::getContributories () const

getContributories Get contributories List

Returns

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/contributorieswidget.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/contributorieswidget.cpp

8.26 Models::Contributory Class Reference

The [Contributory](#) class.

```
#include <contributory.h>
```

Inheritance diagram for Models::Contributory:



Public Member Functions

- [Contributory](#) ()
Contributory::Contributory Construct a [Contributory](#).
- [Contributory](#) (int id)
Contributory::Contributory Construct a [Contributory](#) and get data in database.
- [~Contributory](#) ()
Destroy an contributory object.
- void [commit](#) ()
Contributory::commit Update or insert a contributory to the database.
- void [hydrat](#) (int id)
Contributory::hydrat Get data about the [Contributory](#) which is specified by the identify id
- void [remove](#) ()
Contributory::remove Remove the current [Contributory](#).
- QVariantHash [getDataMap](#) ()
getDataMap Get all data of model with a HashMap key/value
- [Project](#) * [getProject](#) () const
Contributory::getProject Return the project linked to this [Contributory](#).
- void [setProject](#) ([Project](#) *id)
Contributory::setProject Modify the identify id of the [Project](#) linked to this [Contributory](#).
- double [getNbHours](#) () const
getNbHours Number of work hour of a contributory
- void [setNbHours](#) (double value)
setNbHours Change nbHours
- QString [getDescription](#) () const
getDescription Description of a contributory
- void [setDescription](#) (const QString &[getDescription](#))
setDescription Change the contributory description
- bool [operator==](#) (const [Contributory](#) &c)
operator == define the operator "==" to compare two [Contributory](#)
- bool [operator!=](#) (const [Contributory](#) &c)
operator != define the operator "!=" to compare two [Contributory](#)

Additional Inherited Members

8.26.1 Detailed Description

The [Contributory](#) class.

Author

8.26.2 Constructor & Destructor Documentation

8.26.2.1 Models::Contributory::Contributory (int id)

[Contributory::Contributory](#) Construct a [Contributory](#) and get data in database.

Parameters

<i>id</i>	Contributory 's id
-----------	------------------------------------

8.26.3 Member Function Documentation

8.26.3.1 QVariantHash Models::Contributory::getDataMap () [virtual]

getDataMap Get all data of model with a HashMap key/value

Returns

Model's data

Implements [Models::IModel](#).

8.26.3.2 QString Models::Contributory::getDescription () const

getDescription Description of a contributory

Returns

The description

8.26.3.3 double Models::Contributory::getNbHours () const

getNbHours Number of work hour of a contributory

Returns

Then number of hours

8.26.3.4 Project * Models::Contributory::getProject () const

[Contributory::getProject](#) Return the project linked to this [Contributory](#).

Returns

[Project](#) linked to this [Contributory](#)

8.26.3.5 void Models::Contributory::hydrat (int *id*) [virtual]

[Contributory::hydrat](#) Get data about the [Contributory](#) which is specified by the identify *id*

Parameters

<i>id</i>	Contributory identify
-----------	---------------------------------------

Implements [Models::IModel](#).

8.26.3.6 bool Models::Contributory::operator!=(const Contributory & c)

operator != define the operator "!=" to compare two [Contributory](#)

Parameters

<i>c</i>	the Contributory to compare with the current Contributory
----------	---

Returns

true if the [Contributory](#) are different else false

8.26.3.7 bool Models::Contributory::operator==(const Contributory & c)

operator == define the operator "==" to compare two [Contributory](#)

Parameters

<i>c</i>	the Contributory to compare with the current Contributory
----------	---

Returns

true if the [Contributory](#) are equals else false

8.26.3.8 void Models::Contributory::setDescription (const QString & getDescription)

setDescription Change the contributory description

Parameters

<i>getDescription</i>	The new description
-----------------------	---------------------

8.26.3.9 void Models::Contributory::setNbHours (double value)

setNbHours Change nbHours

Parameters

<i>value</i>	The new value of nbHours
--------------	--------------------------

8.26.3.10 void Models::Contributory::setProject (Project * id)

[Contributory::setProject](#) Modify the identify *id* of the [Project](#) linked to this [Contributory](#).

Parameters

<i>id</i>	Project Identify
-----------	----------------------------------

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/models/contributory.h
- /home/travis/build/FACT-Team/FactDev/src/models/contributory.cpp

8.27 Databases::ContributoryDatabase Class Reference

The [ContributoryDatabase](#) class Contributory (or Quote) table database.

```
#include <contributorydatabase.h>
```

Inheritance diagram for Databases::ContributoryDatabase:



Public Member Functions

- [Models::Contributory](#) * [getContributory](#) (const int idContributory)
ContributoryDatabase::getCustomer get informations about the Contributory identified by *pld*
- [Models::ContributoriesList](#) [getContributoriesByBilling](#) (const int idBilling)
- int [addContributory](#) (const [Models::Contributory](#) &)
ContributoryDatabase::addContributory Add the Contributory *pContributory* to the database.
- void [updateContributory](#) (const [Models::Contributory](#) &)
ContributoryDatabase::updateCustomer Update informations about the Contributory *pCustomer*
- void [removeContributory](#) (const int pld)
ContributoryDatabase::removeCustomer Remove the Contributory with the id *pld*
- [Models::Contributory](#) * [getContributory](#) (QString &q)
getContributory Obtain a contributory without new query

Static Public Member Functions

- static [ContributoryDatabase](#) * [instance](#) () throw (DbException*)
ContributoryDatabase::getInstance Return an instance of [ContributoryDatabase](#)

Additional Inherited Members

8.27.1 Detailed Description

The [ContributoryDatabase](#) class Contributory (or Quote) table database.

Author

Cédric Rohaut

See Also

[Database](#)
[Contributory/Quote](#)

8.27.2 Member Function Documentation

8.27.2.1 int Databases::ContributoryDatabase::addContributory (const Models::Contributory & pContributory)

[ContributoryDatabase::addContributory](#) Add the Contributory *pContributory* to the database.

Returns

Contributory id

8.27.2.2 Models::Contributory * Databases::ContributoryDatabase::getContributory (const int idContributory)

ContributoryDatabase::getCustomer get informations about the Contributory identified by *pld*

Parameters

<i>idContributory</i>	Contributory id
-----------------------	-----------------

Returns

the Contributory

8.27.2.3 Models::Contributory * Databases::ContributoryDatabase::getContributory (QSqlQuery & *q*)

getContributory Obtain a contributory without new query

Parameters

<i>q</i>	The query to use
----------	------------------

Returns

The contributory linked to *q*

8.27.2.4 ContributoryDatabase * Databases::ContributoryDatabase::instance () throw DbException *) [static]

ContributoryDatabase::getInstance Return an instance of [ContributoryDatabase](#)

See Also

DbException

Returns

Instance of [ContributoryDatabase](#)

8.27.2.5 void Databases::ContributoryDatabase::removeContributory (const int *pld*)

ContributoryDatabase::removeCustomer Remove the Contributory with the id *pld*

Parameters

<i>pld</i>	Contributory id
------------	-----------------

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/database/contributorydatabase.h
- /home/travis/build/FACT-Team/FactDev/src/database/contributorydatabase.cpp

8.28 ContributoryListTest Class Reference

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/tests/models/contributorylisttest.h
- /home/travis/build/FACT-Team/FactDev/tests/models/contributorylisttest.cpp

8.29 ContributoryModelTest Class Reference

Inheritance diagram for ContributoryModelTest:



The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/tests/models/contributorymodeltest.h
- /home/travis/build/FACT-Team/FactDev/tests/models/contributorymodeltest.cpp

8.30 CounterContext Class Reference

Inheritance diagram for CounterContext:



Public Member Functions

- **CounterContext** (const QVariantHash &map)
- virtual bool [canEval](#) (const QString &key) const
- virtual QString [eval](#) (const QString &key, const QString &_template, [Mustache::Renderer](#) *renderer)
- virtual QString [stringValue](#) (const QString &key) const
- **CounterContext** (const QVariantHash &map)
- virtual bool [canEval](#) (const QString &key) const
- virtual QString [eval](#) (const QString &key, const QString &_template, [Mustache::Renderer](#) *renderer)
- virtual QString [stringValue](#) (const QString &key) const

Public Attributes

- int **counter**

Additional Inherited Members

8.30.1 Member Function Documentation

8.30.1.1 virtual bool CounterContext::canEval (const QString & key) const [inline], [virtual]

Returns true if [eval\(\)](#) should be used to render section tags using `key`. If [canEval\(\)](#) returns true for a key, the renderer will pass the literal, unrendered block of text for the section to [eval\(\)](#) and replace the section with the result.

[canEval\(\)](#) and [eval\(\)](#) are equivalents for callable objects (eg. lambdas) in other Mustache implementations.

The default implementation always returns false.

Reimplemented from [Mustache::QtVariantContext](#).

8.30.1.2 `virtual bool CounterContext::canEval (const QString & key) const [inline],[virtual]`

Returns true if [eval\(\)](#) should be used to render section tags using `key`. If [canEval\(\)](#) returns true for a key, the renderer will pass the literal, unrendered block of text for the section to [eval\(\)](#) and replace the section with the result.

[canEval\(\)](#) and [eval\(\)](#) are equivalents for callable objects (eg. lambdas) in other Mustache implementations.

The default implementation always returns false.

Reimplemented from [Mustache::QtVariantContext](#).

8.30.1.3 `virtual QString CounterContext::eval (const QString & key, const QString & _template, Mustache::Renderer * renderer) [inline],[virtual]`

Callback used to render a template section with the given `key`. `renderer` will substitute the original section tag with the result of [eval\(\)](#).

The default implementation returns an empty string.

Reimplemented from [Mustache::QtVariantContext](#).

8.30.1.4 `virtual QString CounterContext::eval (const QString & key, const QString & _template, Mustache::Renderer * renderer) [inline],[virtual]`

Callback used to render a template section with the given `key`. `renderer` will substitute the original section tag with the result of [eval\(\)](#).

The default implementation returns an empty string.

Reimplemented from [Mustache::QtVariantContext](#).

8.30.1.5 `virtual QString CounterContext::stringValue (const QString & key) const [inline],[virtual]`

Returns a string representation of the value for `key` in the current context. This is used to replace a Mustache value tag.

Reimplemented from [Mustache::QtVariantContext](#).

8.30.1.6 `virtual QString CounterContext::stringValue (const QString & key) const [inline],[virtual]`

Returns a string representation of the value for `key` in the current context. This is used to replace a Mustache value tag.

Reimplemented from [Mustache::QtVariantContext](#).

The documentation for this class was generated from the following file:

- `/home/travis/build/FACT-Team/FactDev/src/libs/qt-mustache/tests/test_mustache.cpp`

8.31 Models::Customer Class Reference

The [Customer](#) class [Customer](#).

```
#include <customer.h>
```

Inheritance diagram for Models::Customer:



Public Member Functions

- [Customer](#) ()
Customer::Customer Construct a [Customer](#).
- [Customer](#) (int id)
Customer::Customer Construct a [Customer](#) who is specified by id
- void [commit](#) ()
Customer::commit Update customer data on the database.
- void [hydrat](#) (int id)
Customer::hydrat Insert into database informations related to the [Customer](#) who is specified by id
- void [remove](#) ()
Customer::remove Remove the current customer.
- QVariantHash [getDataMap](#) ()
getDataMap Get all data of model with a HashMap key/value
- QString [getFirstnameReferent](#) () const
Customer::getFirstnameReferent Return the firstname of the referent [Customer](#).
- void [setFirstnameReferent](#) (const QString &firstnameReferent)
Customer::setFirstnameReferent Replace the referent firstname of the customer by firstnameReferent
- QString [getLastnameReferent](#) () const
Customer::getLastnameReferent Return the lastname of the referent [Customer](#).
- void [setLastnameReferent](#) (const QString &lastnameReferent)
Customer::setLarstnameReferent Replace the referent lastname of the customer by lastnameReferent
- QString [getCompany](#) () const
Customer::getCompany Return the name of the company customer.
- void [setCompany](#) (const QString &company)
Customer::setCompany Replace the company name by company
- QString [getAddress](#) () const
Customer::getAddress Return the address (name and street number) of the customer company.
- void [setAddress](#) (const QString &address)
Customer::setAddress Replace the current company address by the new address
- QString [getPostalCode](#) () const
Customer::getPostalCode Return the postal code of the customer company.
- void [setPostalCode](#) (const QString &postalCode)
Customer::setPostalCode Replace the current postal code of the customer company by the new postalCode
- QString [getCity](#) () const
Customer::getCity Return the city of the customer company.
- void [setCity](#) (const QString &city)
Customer::setCity Replace the current city of the customer company by the new city
- QString [getCountry](#) () const
Customer::getCountry Return the country of the customer company.
- void [setCountry](#) (const QString &country)

- Customer::setCountry* Replace the country of the *Customer* company by country

 - QString *getEmail* () const
 - Customer::getEmail* Return the email of the customer company.
 - void *setEmail* (const QString &email)
 - Customer::setEmail* Replace the email of the *Customer* company by email
 - QString *getMobilePhone* () const
 - Customer::getMobilePhone* Return the number of the mobile phone of the customer company.
 - void *setMobilePhone* (const QString &mobilePhone)
 - Customer::setMobilePhone* Replace the current mobile phone of the customer company by mobilePhone
 - QString *getPhone* () const
 - Customer::getPhone* Return the number of desktop phone.
 - void *setPhone* (const QString &phone)
 - Customer::setPhone* Replace the current number of desktop phone by phone
 - QString *getFax* () const
 - Customer::getFax* Return the fax number.
 - void *setFax* (const QString &fax)
 - Customer::setFax* Replace the current fax number by fax
 - QString *getPath* () const
 - Customer::getPath* Return the path of the workspace for the current *Customer*.
 - QString *getNameFolder* () const
 - Customer::getNameFolder* Return the name of the current *Customer*'s folder in the workspace.
 - bool *operator==* (const *Customer* &c)
 - Customer::operator ==* Re-define the operator "==" to compare if the current customer is the same to the other *Customer* c Return TRUE if both customers are the same, else FALSE.
 - bool *operator!=* (const *Customer* &c)
 - Customer::operator !=* Re-define the operator "!=" to compare if the current customer is different to the other *Customer* c Return TRUE if both customers are different, else FALSE.

Additional Inherited Members

8.31.1 Detailed Description

The *Customer* class *Customer*.

Author

Antoine de Roquemaurel
Florent Berbie

8.31.2 Constructor & Destructor Documentation

8.31.2.1 Models::Customer::Customer (int *id*)

Customer::Customer Construct a *Customer* who is specified by *id*

Parameters

<i>id</i>	<i>Customer</i> identify
-----------	--------------------------

8.31.3 Member Function Documentation

8.31.3.1 QString Models::Customer::getAddress () const

[Customer::getAddress](#) Return the address (name and street number) of the customer company.

Returns

company address

8.31.3.2 QString Models::Customer::getCity () const

[Customer::getCity](#) Return the city of the customer company.

Returns

city of the customer company

8.31.3.3 QString Models::Customer::getCompany () const

[Customer::getCompany](#) Return the name of the company customer.

Returns

name of the company customer

8.31.3.4 QString Models::Customer::getCountry () const

[Customer::getCountry](#) Return the country of the customer company.

Returns

country of the customer company

8.31.3.5 QVariantHash Models::Customer::getDataMap () [virtual]

getDataMap Get all data of model with a HashMap key/value

Returns

Model's data

Implements [Models::IModel](#).

8.31.3.6 QString Models::Customer::getEmail () const

[Customer::getEmail](#) Return the email of the customer company.

Returns

email of the customer company

8.31.3.7 QString Models::Customer::getFax () const

[Customer::getFax](#) Return the fax number.

Returns

fax number

8.31.3.8 QString Models::Customer::getFirstnameReferent () const

[Customer::getFirstnameReferent](#) Return the firstname of the referent [Customer](#).

Returns

Referent firstname of the customer

8.31.3.9 QString Models::Customer::getLastnameReferent () const

[Customer::getLastnameReferent](#) Return the lastname of the referent [Customer](#).

Returns

Referent lastname of the customer

8.31.3.10 QString Models::Customer::getMobilePhone () const

[Customer::getMobilePhone](#) Return the number of the mobile phone of the customer company.

Returns

number of mobile phone

8.31.3.11 QString Models::Customer::getNameFolder () const

[Customer::getNameFolder](#) Return the name of the current [Customer](#)'s folder in the workspace.

Returns

name of the [Customer](#)'s folder

8.31.3.12 QString Models::Customer::getPath () const

[Customer::getPath](#) Return the path of the workspace for the current [Customer](#).

Returns

workspace path

8.31.3.13 QString Models::Customer::getPhone () const

[Customer::getPhone](#) Return the number of desktop phone.

Returns

number of desktop phone

8.31.3.14 QString Models::Customer::getPostalCode () const

[Customer::getPostalCode](#) Return the postal code of the customer company.

Returns

postal code of the customer company

8.31.3.15 void Models::Customer::hydrat (int *id*) [virtual]

[Customer::hydrat](#) Insert into database informations related to the [Customer](#) who is specified by *id*

Parameters

<i>id</i>	Customer identify
-----------	-----------------------------------

Implements [Models::IModel](#).

8.31.3.16 bool Models::Customer::operator!= (const Customer & *c*)

[Customer::operator ==](#) Re-define the operator "!=" to compare if the current customer is differnt to the other [Customer](#) *c* Return TRUE if both customers are different, else FALSE.

Parameters

<i>c</i>	Customer to compare
----------	-------------------------------------

Returns

boolean

8.31.3.17 bool Models::Customer::operator== (const Customer & *c*)

[Customer::operator ==](#) Re-define the operator "==" to compare if the current customer is the same to the other [Customer](#) *c* Return TRUE if both customers are the same, else FALSE.

Parameters

<i>c</i>	Customer to compare
----------	-------------------------------------

Returns

boolean

8.31.3.18 void Models::Customer::setAddress (const QString & *address*)

[Customer::setAddress](#) Replace the current company address by the new *address*

Parameters

<i>address</i>	New company address
----------------	---------------------

8.31.3.19 void Models::Customer::setCity (const QString & *city*)

[Customer::setCity](#) Replace the current city of the customer company by the new *city*

Parameters

<i>city</i>	New city of the customer company
-------------	----------------------------------

8.31.3.20 void Models::Customer::setCompany (const QString & *company*)

[Customer::setCompany](#) Replace the company name by *company*

Parameters

<i>company</i>	New company name
----------------	------------------

8.31.3.21 void Models::Customer::setCountry (const QString & *country*)

[Customer::setCountry](#) Replace the country of the [Customer](#) company by *country*

Parameters

<i>country</i>	New country of the customer company
----------------	-------------------------------------

8.31.3.22 void Models::Customer::setEmail (const QString & *email*)

[Customer::setEmail](#) Replace the email of the [Customer](#) company by *email*

Parameters

<i>email</i>	New email of the customer company
--------------	-----------------------------------

8.31.3.23 void Models::Customer::setFax (const QString & *fax*)

[Customer::setFax](#) Replace the current fax number by *fax*

Parameters

<i>fax</i>	new fax number
------------	----------------

8.31.3.24 void Models::Customer::setFirstnameReferent (const QString & *firstnameReferent*)

[Customer::setFirstnameReferent](#) Replace the referent firstname of the customer by *firstnameReferent*

Parameters

<i>firstname-Referent</i>	New referent firstname of the Customer
---------------------------	--

8.31.3.25 void Models::Customer::setLastnameReferent (const QString & *lastnameReferent*)

[Customer::setLastnameReferent](#) Replace the referent lastname of the customer by *lastnameReferent*

Parameters

<i>lastname-Referent</i>	New referent lastname of the Customer
--------------------------	---

8.31.3.26 void Models::Customer::setMobilePhone (const QString & *mobilePhone*)

[Customer::setMobilePhone](#) Replace the current mobile phone of the customer company by *mobilePhone*

Parameters

<i>mobilePhone</i>	New number of mobile phone
--------------------	----------------------------

8.31.3.27 void Models::Customer::setPhone (const QString & *phone*)

[Customer::setPhone](#) Replace the current number of desktop phone by *phone*

Parameters

<i>phone</i>	New number of desktop phone
--------------	-----------------------------

8.31.3.28 void Models::Customer::setPostalCode (const QString & *postalCode*)

[Customer::setPostalCode](#) Replace the current postal code of the customer company by the new *postalCode*

Parameters

<i>postalCode</i>	New postal code of the customer company
-------------------	---

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/models/customer.h
- /home/travis/build/FACT-Team/FactDev/src/models/customer.cpp

8.32 Gui::Widgets::CustomerContextMenu Class Reference

Display contextual menu on a customer.

```
#include <customercontextualmenu.h>
```

Inheritance diagram for Gui::Widgets::CustomerContextMenu:



Public Member Functions

- [CustomerContextMenu](#) (QWidget *w=0)
[CustomerContextMenu](#) Construct a new contextual menu.
- [~CustomerContextMenu](#) ()
Destruct the contextual menu.

8.32.1 Detailed Description

Display contextual menu on a customer.

Author

Antoine de Roquemaurel

8.32.2 Constructor & Destructor Documentation

8.32.2.1 Gui::Widgets::CustomerContextualMenu::CustomerContextualMenu (QWidget * w = 0)

[CustomerContextualMenu](#) Construct a new contextual menu.

Parameters

<i>w</i>	Parent
----------	--------

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/customercontextualmenu.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/customercontextualmenu.cpp

8.33 Databases::CustomerDatabase Class Reference

The [CustomerDatabase](#) class Customer table database.

```
#include <customerdatabase.h>
```

Inheritance diagram for Databases::CustomerDatabase:



Public Member Functions

- [WdgModels::CustomersTableModel * getCustomersTable](#) (QString filter="") throw (DbException*)
[CustomerDatabase::getCustomersTable](#) Return an item model of customers for QTableView.
- [QStandardItemModel * getTree](#) (QString filter="") throw (DbException*)
[CustomerDatabase::getTree](#) Return an item model of customers for QTree.
- [QSharedPointer< Models::Customer > getCustomer](#) (const int pld)
[CustomerDatabase::getCustomer](#) get informations about the customer identified by pld
- [int addCustomer](#) (const [Models::Customer](#) &)
[CustomerDatabase::addCustomer](#) Add the customer pCustomer to the database.
- [void updateCustomer](#) (const [Models::Customer](#) &)
[CustomerDatabase::updateCustomer](#) Update informations about the customer pCustomer
- [void removeCustomer](#) (const int pld)
[CustomerDatabase::removeCustomer](#) Remove the customer with the id pld
- [int getNbCustomers](#) ()
[CustomerDatabase::getNbCustomers](#) Return the number of customers existing.
- [QStandardItem * getItemRoot](#) ()
[CustomerDatabase::getItemRoot](#) Return the first item for the QStandardItemModel.
- [QStandardItem * getItemCustomer](#) (QString q1)
[CustomerDatabase::getItemCustomer](#) Return the customer item for the QStandardItemModel.
- [QStandardItem * getItemProject](#) (QString q2)
[CustomerDatabase::getItemProject](#) Return the project item for the QStandardItemModel.
- [QStandardItem * getItemBillQuote](#) (QString q3)
[CustomerDatabase::getItemCustomer](#) Return the bill/quote item for the QStandardItemModel.
- [QSharedPointer< Models::Customer > getCustomer](#) (QString &q)

- [CustomerDatabase::getCustomer](#) Add the element of the *q* request and return their.
- void [updateCustomer](#) (QSqlQuery &q, [Customer](#) &pCustomer)
- [CustomerDatabase::updateCustomer](#) Update customer data according to the request *q*

Static Public Member Functions

- static [CustomerDatabase](#) * [instance](#) () throw (DbException*)
- [CustomerDatabase::instance](#) Return an instance of [CustomerDatabase](#)

Additional Inherited Members

8.33.1 Detailed Description

The [CustomerDatabase](#) class Customer table database.

Author

Antoine de Roquemaurel
Manantsoa Razanajatovo
Florent Berbie
Cédric Rohaut

See Also

[Database](#)
[Customer](#)

8.33.2 Member Function Documentation

8.33.2.1 int Databases::CustomerDatabase::addCustomer (const [Models::Customer](#) & *pCustomer*)

[CustomerDatabase::addCustomer](#) Add the customer *pCustomer* to the database.

Returns

customer id

8.33.2.2 QSharedPointer< [Models::Customer](#) > Databases::CustomerDatabase::getCustomer (const int *pld*)

[CustomerDatabase::getCustomer](#) get informations about the customer identified by *pld*

Parameters

<i>pld</i>	customer id
------------	-------------

Returns

the Customer

8.33.2.3 QSharedPointer< [Models::Customer](#) > Databases::CustomerDatabase::getCustomer (QSqlQuery & *q*)

[CustomerDatabase::getCustomer](#) Add the element of the *q* request and return their.

Parameters

<i>q</i>	SQL request
----------	-------------

Returns

a customer formed according to QSharedPointer

8.33.2.4 WdgModels::CustomersTableModel * Databases::CustomerDatabase::getCustomersTable (QString *filter* = " ") throw DbException *)

[CustomerDatabase::getCustomersTable](#) Return an item model of customers for QTableView.

Parameters

<i>filter</i>	Select only customers who are specified by <i>filter</i>
---------------	--

Exceptions

<i>DbException</i>	
--------------------	--

Returns

QStandardItemModel an item model for QTableView

8.33.2.5 QStandardItem * Databases::CustomerDatabase::getItemBillQuote (QSqlQuery *q3*)

[CustomerDatabase::getItemCustomer](#) Return the bill/quote item for the QStandardItemModel.

Parameters

<i>q3</i>	the first row of the sql query for bills/quotes
-----------	---

Returns

QStandardItem an item for QTree (level/depth 3)

8.33.2.6 QStandardItem * Databases::CustomerDatabase::getItemCustomer (QSqlQuery *q1*)

[CustomerDatabase::getItemCustomer](#) Return the customer item for the QStandardItemModel.

Parameters

<i>q1</i>	the row of the sql query for customers
-----------	--

Returns

QStandardItem an item for QTree (level/depth 1)

8.33.2.7 QStandardItem * Databases::CustomerDatabase::getItemProject (QSqlQuery *q2*)

[CustomerDatabase::getItemProject](#) Return the project item for the QStandardItemModel.

Parameters

<i>q2</i>	the row of the sql query for projects
-----------	---------------------------------------

Returns

QStandardItem an item for QTree (level/depth 2)

8.33.2.8 QStandardItem * Databases::CustomerDatabase::getItemRoot ()

[CustomerDatabase::getItemRoot](#) Return the first item for the QStandardItemModel.

Returns

QStandardItem an item for QTree (level/depth 0)

8.33.2.9 int Databases::CustomerDatabase::getNbCustomers ()

[CustomerDatabase::getNbCustomers](#) Return the number of customers existing.

Returns

number of customers

8.33.2.10 QStandardItemModel * Databases::CustomerDatabase::getTree (QString *filter* = " ") throw DbException *)

[CustomerDatabase::getTree](#) Return an item model of customers for QTree.

Parameters

<i>filter</i>	Select only customers who are specified by <i>filter</i>
---------------	--

Exceptions

<i>DbException</i>	
--------------------	--

Returns

QStandardItemModel an item model for QTreeView

8.33.2.11 CustomerDatabase * Databases::CustomerDatabase::instance () throw DbException *) [static]

[CustomerDatabase::instance](#) Return an instance of [CustomerDatabase](#)

See Also

DbException

Returns

Instance of [CustomerDatabase](#)

8.33.2.12 void Databases::CustomerDatabase::removeCustomer (const int *pld*)

[CustomerDatabase::removeCustomer](#) Remove the customer with the id *pld*

Parameters

<i>pId</i>	customer id
------------	-------------

8.33.2.13 void Databases::CustomerDatabase::updateCustomer (QSqlQuery & *q*, Customer & *pCustomer*)

[CustomerDatabase::updateCustomer](#) Update customer data according to the request *q*

Parameters

<i>q</i>	SQL request
----------	-------------

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/database/customerdatabase.h
- /home/travis/build/FACT-Team/FactDev/src/database/customerdatabase.cpp

8.34 CustomerDatabaseTest Class Reference

Inheritance diagram for CustomerDatabaseTest:



The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/tests/database/customerdatabasetest.h
- /home/travis/build/FACT-Team/FactDev/tests/database/customerdatabasetest.cpp

8.35 Gui::Widgets::CustomerDataWidget Class Reference

Class for display info of a customer.

```
#include <customerdatawidget.h>
```

Inheritance diagram for Gui::Widgets::CustomerDataWidget:



Public Member Functions

- **CustomerDataWidget** (QWidget *parent=0)
- void [printUserData](#) ()
printUserData Print Data of current user
- void [printInformations](#) (int id)
printInformations Print Data of customer id

8.35.1 Detailed Description

Class for display info of a customer.

Author

Cédric Rohaut

8.35.2 Member Function Documentation

8.35.2.1 void Gui::Widgets::CustomerDataWidget::printInformations (int *id*)

printInformations Print Data of customer id

Parameters

<i>id</i>	of customer to print
-----------	----------------------

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/customerdatawidget.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/customerdatawidget.cpp

8.36 CustomerModelTest Class Reference

Inheritance diagram for CustomerModelTest:



The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/tests/models/customermodeltest.h
- /home/travis/build/FACT-Team/FactDev/tests/models/customermodeltest.cpp

8.37 Gui::Widgets::WdgModels::CustomersTableModel Class Reference

The [CustomersTableModel](#) class for a customer table.

```
#include <customerstablemodel.h>
```

Inheritance diagram for Gui::Widgets::WdgModels::CustomersTableModel:



Public Member Functions

- [CustomersTableModel](#) (QObject *parent=0)
[CustomersTableModel::CustomersTableModel](#) Construct a [CustomersTableModel](#).
- int [rowCount](#) (const QModelIndex &) const
[CustomersTableModel::rowCount](#) Number of customers row.
- int [columnCount](#) (const QModelIndex &) const
[CustomersTableModel::columnCount](#) Number of column of a customer.
- QVariant [data](#) (const QModelIndex &index, int role=Qt::DisplayRole) const
[CustomersTableModel::data](#) Obtains data of a specify cell.
- QVariant [headerData](#) (int section, Qt::Orientation orientation, int role=Qt::DisplayRole) const
[CustomersTableModel::headerData](#) Obtains header title of table.
- bool [setData](#) (const QModelIndex &index, const QVariant &value, int role=Qt::EditRole)
[CustomersTableModel::setData](#) Change data of a cell.
- void [append](#) (const [Customer](#) &customer)
[CustomersTableModel::append](#) Add a new line in table.
- void [remove](#) (const int i)
[CustomersTableModel::remove](#) Remove a line.
- Qt::ItemFlags [flags](#) (const QModelIndex &index) const
[CustomersTableModel::flags](#) Differents table flags.
- int [count](#) ()
[CustomersTableModel::count](#) Number of customers in table.
- QList< [Customer](#) > [getCustomers](#) () const
[CustomersTableModel::getCustomers](#) Return the list of customers.

8.37.1 Detailed Description

The [CustomersTableModel](#) class for a customer table.

Author

Florent Berbie

See Also

[Customer](#)

8.37.2 Constructor & Destructor Documentation

8.37.2.1 Gui::Widgets::WdgModels::CustomersTableModel::CustomersTableModel (QObject * parent = 0)

[CustomersTableModel::CustomersTableModel](#) Construct a [CustomersTableModel](#).

Parameters

<i>parent</i>	Parent widget
---------------	---------------

8.37.3 Member Function Documentation

8.37.3.1 void Gui::Widgets::WdgModels::CustomersTableModel::append (const Customer & customer)

[CustomersTableModel::append](#) Add a new line in table.

Parameters

<i>Customer</i>	The new customer
-----------------	------------------

8.37.3.2 `int Gui::Widgets::WdgModels::CustomersTableModel::columnCount (const QModelIndex &) const`

[CustomersTableModel::columnCount](#) Number of column of a customer.

Returns

The number of column

8.37.3.3 `int Gui::Widgets::WdgModels::CustomersTableModel::count ()`

[CustomersTableModel::count](#) Number of customers in table.

Returns

The number of customers

8.37.3.4 `QVariant Gui::Widgets::WdgModels::CustomersTableModel::data (const QModelIndex & index, int role = Qt::DisplayRole) const`

[CustomersTableModel::data](#) Obtains data of a specify cell.

Parameters

<i>index</i>	The cell who we want data
<i>role</i>	The role of set

Returns

The data of cell

8.37.3.5 `Qt::ItemFlags Gui::Widgets::WdgModels::CustomersTableModel::flags (const QModelIndex & index) const`

[CustomersTableModel::flags](#) Differents table flags.

Parameters

<i>index</i>	The cell who we want to know flags
--------------	------------------------------------

Returns

Flags

8.37.3.6 `QList< Customer > Gui::Widgets::WdgModels::CustomersTableModel::getCustomers () const`

[CustomersTableModel::getCustomers](#) Return the list of customers.

Returns

list of Customers

8.37.3.7 `QVariant Gui::Widgets::WdgModels::CustomersTableModel::headerData (int section, Qt::Orientation orientation, int role = Qt::DisplayRole) const`

[CustomersTableModel::headerData](#) Obtains header title of table.

Parameters

<i>section</i>	The number of column
<i>orientation</i>	The table orientation
<i>role</i>	

Returns

The Title header of column

8.37.3.8 void Gui::Widgets::WdgModels::CustomersTableModel::remove (const int *i*)

[CustomersTableModel::remove](#) Remove a line.

Parameters

<i>i</i>	The number of line to remove
----------	------------------------------

8.37.3.9 int Gui::Widgets::WdgModels::CustomersTableModel::rowCount (const QModelIndex &) const

[CustomersTableModel::rowCount](#) Number of customers row.

Returns

The number of customers

8.37.3.10 bool Gui::Widgets::WdgModels::CustomersTableModel::setData (const QModelIndex & *index*, const QVariant & *value*, int *role* = Qt::EditRole)

[CustomersTableModel::setData](#) Change data of a cell.

Parameters

<i>index</i>	The cell to change data
<i>value</i>	The new value
<i>role</i>	The role of cell

Returns

True if we could edit

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/widgetmodels/customerstablemodel.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/widgetmodels/customerstablemodel.cpp

8.38 Databases::Database Class Reference

The [Database](#) class Master class for all database access.

```
#include <database.h>
```

Inheritance diagram for Databases::Database:



Public Member Functions

- QString [lastError](#) (const QSqlQuery &q) const
Database::lastError Return an error message on the last error occurred during the SQL request q
- void [testCases](#) ()
Database::testCases Realise a test cases.
- void [cleanDatabase](#) ()
Database::viderDatabase Clear database.
- void [executeFile](#) (QString pName)
Database::executerFichier Exeute a specified file named pName
- void [openTransaction](#) ()
Database::openTransaction Open new transaction.
- void [closeTransaction](#) ()
Database::closeTransaction Close current transaction.
- void [close](#) ()
Database::close Close database access.
- void [open](#) ()
Database::open Open database.
- [~Database](#) ()
Database::~~Database Suppression object, and close database access.
- void [setDatabase](#) (QSqlDatabase sql)
Database::setDatabase Set database.
- void [createDatabase](#) ()
Database::createDatabase Create a new database.
- void [updateBillingNumber](#) ()
Database::updateBillingNumber Update the billing number.

Static Public Member Functions

- static [Database * instance](#) () throw (DbException*)
Database::getInstance Return an instance of [Database](#).

Protected Member Functions

- [Database](#) () throw (DbException*)
Database::Database [Database](#) is a singleton.
- QVariant [value](#) (const QSqlQuery &q, const QString &champ) const
Database::valeur Value of database field.

Protected Attributes

- QSettings * [_settings](#)
settings
- QSqlDatabase [mDatabase](#)
contains Database
- QList< [Database * > _instances](#)
List of instances.

Static Protected Attributes

- static [Database](#) * [_instance](#) = 0
Instance.
- static bool [_dbInstance](#) = 0
an instance of db is open
- static bool [isOpen](#) = false
[Database](#) is open.

8.38.1 Detailed Description

The [Database](#) class Master class for all database access.

Author

Antoine de Roquemaurel

8.38.2 Member Function Documentation

8.38.2.1 void Databases::Database::executeFile (QString *pName*)

Database::executerFichier Exeute a specified file named *pName*

Parameters

<i>pNom</i>	File name
-------------	-----------

8.38.2.2 Database * Databases::Database::instance () throw DbException *) [static]

Database::getInstance Return an instance of [Database](#).

Returns

Instance of [Database](#)

8.38.2.3 QString Databases::Database::lastError (const QSqlQuery & *q*) const [inline]

[Database::lastError](#) Return an error message on the last error ocured during the SQL request *q*

Parameters

<i>q</i>	SQL request
----------	-------------

Returns

an error message

8.38.2.4 void Databases::Database::setDatabase (QSqlDatabase *sql*)

[Database::setDatabase](#) Set database.

Parameters

<i>sql</i>	The new database
------------	------------------

8.38.2.5 QVariant Databases::Database::value (const QSqlQuery & *q*, const QString & *champ*) const [protected]

Database::valeur Value of database field.

Parameters

<i>q</i>	Query
<i>champ</i>	Field

Returns

The value

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/database/database.h
- /home/travis/build/FACT-Team/FactDev/src/database/database.cpp

8.39 Exceptions::DbException Class Reference

The [DbException](#) class for database exception : queries, db file, ...

```
#include <dbexception.h>
```

Inheritance diagram for Exceptions::DbException:



Public Member Functions

- [DbException](#) (const QString fct, const QString fctName, const QString logError, float errorCode)
[DbException::DbException](#). Construct a [DbException](#).
- virtual [~DbException](#) () throw ()
[~DbException](#)
- void [popupMessage](#) (QWidget *parent)
[DbException::popupMessage](#). Display a popup message with the message error.

8.39.1 Detailed Description

The [DbException](#) class for database exception : queries, db file, ...

Author

Antoine de Roquemaurel

8.39.2 Constructor & Destructor Documentation

8.39.2.1 Exceptions::DbException::DbException (const QString *fct*, const QString *fctName*, const QString *logError*, float *errorCode*)

[DbException::DbException](#). Construct a [DbException](#).

Parameters

<i>userError</i>	ClassName of error
<i>fctName</i>	Function name
<i>logError</i>	Message error
<i>errorCode</i>	Code of error

8.39.3 Member Function Documentation

8.39.3.1 void Exceptions::DbException::popupMessage (QWidget * *parent*)

[DbException::popupMessage](#). Display a popup message with the message error.

Parameters

<i>parent</i>	
---------------	--

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/exceptions/dbexception.h
- /home/travis/build/FACT-Team/FactDev/src/exceptions/dbexception.cpp

8.40 Gui::Dialogs::DialogAddCustomer Class Reference

The [DialogAddCustomer](#) class Window to add or modify a Customer.

```
#include <dialogaddcustomer.h>
```

Inheritance diagram for Gui::Dialogs::DialogAddCustomer:



Public Slots

- void [checkFields](#) ()
setFieldsComponents

Public Member Functions

- [DialogAddCustomer](#) (int id=0, QWidget *parent=0)
DialogAddCustomer Construct a window to add/modify a Customer.
- void [fillFields](#) ()
fillFields If the Customer exists, fill line edits with the data of the current Customer
- void [accept](#) ()
accept Valid data inputed by user and add these data in Database
- void [reject](#) ()
reject Cancel the operation and close the windows

8.40.1 Detailed Description

The [DialogAddCustomer](#) class Window to add or modify a Customer.

Author

Cédric Rohaut

8.40.2 Constructor & Destructor Documentation

8.40.2.1 `Gui::Dialogs::DialogAddCustomer::DialogAddCustomer (int id = 0, QWidget * parent = 0) [explicit]`

[DialogAddCustomer](#) Construct a window to add/modify a Customer.

Parameters

<i>id</i>	Customer id
<i>parent</i>	QWidget parent

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/dialogs/dialogaddcustomer.h
- /home/travis/build/FACT-Team/FactDev/src/gui/dialogs/dialogaddcustomer.cpp

8.41 Utils::Directories Class Reference

Static Public Member Functions

- static QString [makeDirectory](#) (QDir &directory, const QString path, const QString folder) throw (Exceptions::FileException*)

MainWindow::makeDirectory If not exists make a new directory folder

8.41.1 Member Function Documentation

8.41.1.1 `QString Utils::Directories::makeDirectory (QDir & directory, const QString path, const QString folder) throw Exceptions::FileException *) [static]`

MainWindow::makeDirectory If not exists make a new directory folder

Parameters

<i>path</i>	Return the path of the folder just created
<i>folder</i>	Folder name to create

Returns


Path of the folder just created

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/Utils/directories.h
- /home/travis/build/FACT-Team/FactDev/src/Utils/directories.cpp

8.42 Gui::Widgets::Delegates::DoubleSpinBoxDelegate Class Reference

Inheritance diagram for Gui::Widgets::Delegates::DoubleSpinBoxDelegate:



Public Member Functions

- **DoubleSpinBoxDelegate** (QObject *parent=0)
- QWidget * **createEditor** (QWidget *parent, const QStyleOptionViewItem &option, const QModelIndex &index) const
- void **setEditorData** (QWidget *editor, const QModelIndex &index) const
- void **setModelData** (QWidget *editor, QAbstractItemModel *model, const QModelIndex &index) const
- void **updateEditorGeometry** (QWidget *editor, const QStyleOptionViewItem &option, const QModelIndex &index) const

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/delegates/doublespinboxdelegate.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/delegates/doublespinboxdelegate.cpp

8.43 Exceptions::FileException Class Reference

The [FileException](#) class for file/access file exception.

```
#include <fileexception.h>
```

Public Member Functions

- [FileException](#) (const QString userError, const QString fctName, const QString logError, float errorCode)
[FileException::FileException](#). Construct a [FileException](#).
- void [popupMessage](#) (QWidget *parent)
[FileException::popupMessage](#). Display a popup message with the message error.

8.43.1 Detailed Description

The [FileException](#) class for file/access file exception.

Author

Florent Berbie

8.43.2 Constructor & Destructor Documentation

- 8.43.2.1 Exceptions::FileException::FileException (const QString *userError*, const QString *fctName*, const QString *logError*, float *errorCode*)

[FileException::FileException](#). Construct a [FileException](#).

Parameters

<i>userError</i>	ClassName of error
<i>fctName</i>	Function name
<i>logError</i>	Message error
<i>errorCode</i>	Code of error

8.43.3 Member Function Documentation

8.43.3.1 void Exceptions::FileException::popupMessage (QWidget * *parent*)

[FileException::popupMessage](#). Display a popup message with the message error.

Parameters


<i>parent</i>	
---------------	--

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/exceptions/fileexception.h
- /home/travis/build/FACT-Team/FactDev/src/exceptions/fileexception.cpp

8.44 Generation Class Reference

Inheritance diagram for Generation:



The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/tests/generation.h
- /home/travis/build/FACT-Team/FactDev/tests/generation.cpp

8.45 Generator Class Reference

Public Member Functions

- **Generator** (QString tpl)
- void **generate** (QVariantHash data, QString path)

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/generator.h
- /home/travis/build/FACT-Team/FactDev/src/generator.cpp

8.46 Utils::HierarchicalSystem Class Reference

The [HierarchicalSystem](#) class Create class which contains hierarchical system of FactDev.

```
#include <hierarchicalsistem.h>
```

Public Member Functions

- [HierarchicalSystem \(\)](#)
[HierarchicalSystem::HierarchicalSystem](#) Construct a [HierarchicalSystem](#).
- void [getAllProjects \(\)](#)
[HierarchicalSystem::getAllProjects](#) Get all projects and add each project to Customer linked.
- void [getAllBillings \(\)](#)
[HierarchicalSystem::getAllBillings](#) Get all billings and add each billing to Project linked.
- void [updateData \(\)](#)
[HierarchicalSystem::updateData](#) Update data on Customers, Projects, Billings.
- void [addProjectToCustomer \(Project *p, Customer c\)](#)
[HierarchicalSystem::addProjectToCustomer](#) Add the Project p to the Customer c
- void [addBillingToProject \(Billing *b, Project *p\)](#)
[HierarchicalSystem::addBillingToProject](#) Add the Billing b to the Project p
- QMap< [Project *](#), [Customer](#) > [getCustomers \(\)](#) const
[HierarchicalSystem::getCustomers](#) Return all customers and these projects linked.
- QMap< [Billing *](#), [Project *](#) > [getProjects \(\)](#) const
[HierarchicalSystem::getProjects](#) Return all projects and these billing linked.

8.46.1 Detailed Description

The [HierarchicalSystem](#) class Create class which contains hierarchical system of FactDev.

Author

Florent Berbie

See Also

Customer
Project
Billing

8.46.2 Member Function Documentation

8.46.2.1 void Utils::HierarchicalSystem::addBillingToProject (Billing * b, Project * p)

[HierarchicalSystem::addBillingToProject](#) Add the Billing *b* to the Project *p*

Parameters

<i>b</i>	Billing
<i>p</i>	Project

8.46.2.2 void Utils::HierarchicalSystem::addProjectToCustomer (Project * p, Customer c)

[HierarchicalSystem::addProjectToCustomer](#) Add the Project *p* to the Customer *c*

Parameters

<i>p</i>	Project
<i>c</i>	Customer

8.46.2.3 QMap< Project *, Customer > Utils::HierarchicalSystem::getCustomers () const

[HierarchicalSystem::getCustomers](#) Return all customers and these projects linked.

Returns

Projects linked to Customers

8.46.2.4 QMap< Billing *, Project * > Utils::HierarchicalSystem::getProjects (void) const

[HierarchicalSystem::getProjects](#) Return all projects and these billing linked.

Returns

Billing linked to Projects

The documentation for this class was generated from the following files:


- /home/travis/build/FACT-Team/FactDev/src/utls/hierarchicalsystem.h
- /home/travis/build/FACT-Team/FactDev/src/utls/hierarchicalsystem.cpp

8.47 Gui::Widgets::CheckFields::ICheckField Class Reference

The [ICheckField](#) class Interface to check fields validity.

```
#include <icheckfield.h>
```

Inheritance diagram for Gui::Widgets::CheckFields::ICheckField:



Public Member Functions

- virtual bool [check](#) (QString text)=0
check Check if the field (line edit) is valid Return TRUE if the field is valid, else FALSE

8.47.1 Detailed Description

The [ICheckField](#) class Interface to check fields validity.

8.47.2 Member Function Documentation

8.47.2.1 virtual bool Gui::Widgets::CheckFields::ICheckField::check (QString text) [pure virtual]

check Check if the field (line edit) is valid Return TRUE if the field is valid, else FALSE

Returns

boolean

Implemented in [Gui::Widgets::CheckFields::CheckEmail](#), [Gui::Widgets::CheckFields::CheckPhone](#), [Gui::Widgets::CheckFields::CheckPostalCode](#), [Gui::Widgets::CheckFields::CheckSiretNumber](#), [Gui::Widgets::CheckFields::CheckUntilField](#), [Gui::Widgets::CheckFields::CheckFieldsLetters](#), and [Gui::Widgets::CheckFields::CheckValidField](#).

The documentation for this class was generated from the following file:


- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/checkfields/ichckfield.h

8.48 Models::IModel Class Reference

The [IModel](#) class.

```
#include <imodel.h>
```

Inheritance diagram for Models::IModel:



Public Member Functions

- virtual [~IModel](#) ()
~IModel Remove an instance of IModel
- virtual void [commit](#) ()=0
IModel::commit Update or insert data into the database.
- virtual void [hydrat](#) (int id)=0
IModel::hydrat Get data of the element which is specified by the identify id from the database.
- virtual void [remove](#) ()=0
IModel::remove Remove the current element in the database.
- virtual QVariantHash [getDataMap](#) ()=0
getDataMap Get all data of model with a HashMap key/value
- int [getId](#) () const
IModel::getId Return the identify of the element of the database.
- void [setId](#) (int id)
IModel::setId Replace the current identify by id
- bool [isToRemoved](#) () const
toRemoved return if object must be removed.
- void [setToRemoved](#) (bool toRemoved)
setToRemoved Change the flag for removed object

Protected Attributes

- `int _id`
Element identify.
- `bool _toRemoved`
Flag to know if the object must be removed.

8.48.1 Detailed Description

The `IModel` class.

Author

Antoine de Roquemaurel

8.48.2 Member Function Documentation

8.48.2.1 `virtual QVariantHash Models::IModel::getDataMap () [pure virtual]`

`getDataMap` Get all data of model with a HashMap key/value

Returns

Model's data

Implemented in `Models::Billing`, `Models::Project`, `Models::User`, `Models::Contributory`, and `Models::Customer`.

8.48.2.2 `int Models::IModel::getId () const [inline]`

`IModel::getId` Return the identify of the element of the database.

Returns

identity

8.48.2.3 `virtual void Models::IModel::hydrat (int id) [pure virtual]`

`IModel::hydrat` Get data of the element which is specified by the identify *id* from the database.

Parameters

<i>id</i>	
-----------	--

Implemented in `Models::Project`, `Models::Billing`, `Models::User`, `Models::Contributory`, and `Models::Customer`.

8.48.2.4 `bool Models::IModel::isToRemoved () const [inline]`

`toRemoved` return if object must be removed.

Returns

8.48.2.5 `void Models::IModel::setId (int id) [inline]`

`IModel::setId` Replace the current identify by *id*

Parameters

<i>id</i>	New identify
-----------	--------------

8.48.2.6 void Models::IModel::setToRemoved (bool *toRemoved*) [inline]

setToRemoved Change the flag for removed object

Parameters

<i>toRemoved</i>	The new flag
------------------	--------------

The documentation for this class was generated from the following file:

- /home/travis/build/FACT-Team/FactDev/src/models/imodel.h

8.49 Utils::ItemType Class Reference

The [ItemType](#) class Item type model.

```
#include <itemtype.h>
```

Public Member Functions

- [ItemType](#) (int type, QString name)
ItemType::ItemType Construct an Item type.
- QString [getName](#) () const
ItemType::getName Get item name.
- Models::IModel * [getModel](#) (int id)
ItemType::getModel Get the databasemodel of the [ItemType](#) according to this identity id
- void [setName](#) (const QString &name)
ItemType::setName Modify the item name.
- int [getType](#) () const
ItemType::getType Get the type of the current item.
- void [setType](#) (int type)
ItemType::setType Modify the type of the current item.

Static Public Attributes

- static const int [CUSTOMER](#) = 0
constant value assigned to Customer
- static const int [PROJECT](#) = 1
constant value assigned to Project
- static const int [BILLING](#) = 2
constant value assigned to Billing
- static const int [QUOTE](#) = 3
constant value assigned to Quote

8.49.1 Detailed Description

The [ItemType](#) class Item type model.

8.49.2 Constructor & Destructor Documentation

8.49.2.1 Utils::ItemType::ItemType (int *type*, QString *name*)

[ItemType::ItemType](#) Construct an Item type.

Parameters

<i>type</i>	Type of the item
<i>name</i>	Name of the item

8.49.3 Member Function Documentation

8.49.3.1 Models::IModel * Utils::ItemType::getModel (int *id*)

[ItemType::getModel](#) Get the databasemodel of the [ItemType](#) according to this identity *id*

Parameters

<i>id</i>	Item type identity
-----------	--------------------

Returns

database model

8.49.3.2 QString Utils::ItemType::getName () const

[ItemType::getName](#) Get item name.

Returns

item name

8.49.3.3 int Utils::ItemType::getType () const

[ItemType::getType](#) Get the type of the current item.

Returns

type of the current item

8.49.3.4 void Utils::ItemType::setName (const QString & *name*)

[ItemType::setName](#) Modify the item name.

Parameters

<i>name</i>	New Item name
-------------	---------------

8.49.3.5 void Utils::ItemType::setType (int *type*)

[ItemType::setType](#) Modify the type of the current item.

Parameters


<i>type</i>	New item type
-------------	---------------

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/utils/itemtype.h
- /home/travis/build/FACT-Team/FactDev/src/utils/itemtype.cpp

8.50 ItemTypeTest Class Reference

Inheritance diagram for ItemTypeTest:



The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/tests/utils/itemtypetest.h
- /home/travis/build/FACT-Team/FactDev/tests/utils/itemtypetest.cpp

8.51 Utils::Log Class Reference

The [Log](#) class for Simple management of log.

```
#include <log.h>
```

Public Member Functions

- [~Log](#) ()
Log::~~Log.
- void [write](#) (const QString text)
Log::write. Write log message in file.
- [Log](#) ()
Log::Log. Log is a singleton.

Static Public Member Functions

- static [Log](#) & [instance](#) (TypeLog type=INFO)
Log::instance. Return the instance of logger.

Friends

- [Log](#) & [operator<<](#) ([Log](#) &logger, const QString &text)
operator << for log writing

8.51.1 Detailed Description

The [Log](#) class for Simple management of log.

8.51.2 Member Function Documentation

8.51.2.1 `Log & Utils::Log::instance (TypeLog type = INFO) [static]`

[Log::instance](#). Return the instance of logger.

Parameters

<i>type</i>	Type of log : WARNING, INFO, ERROR
-------------	------------------------------------

Returns

Instance of logger.

8.51.2.2 `void Utils::Log::write (const QString text)`

[Log::write](#). Write log message in file.

Parameters

<i>text</i>	
-------------	--

8.51.3 Friends And Related Function Documentation

8.51.3.1 `Log & operator<< (Log & logger, const QString & text) [friend]`

operator << for log writing

Parameters

<i>logger</i>	Instance of Logger
<i>text</i>	Text to write

Returns

New logger.

The documentation for this class was generated from the following files:


- /home/travis/build/FACT-Team/FactDev/src/utils/log.h
- /home/travis/build/FACT-Team/FactDev/src/utils/log.cpp

8.52 Gui::MainWindow Class Reference

The [MainWindow](#) class Main Window of the software.

```
#include <mainwindow.h>
```

Inheritance diagram for Gui::MainWindow:



Public Slots

- void [addCustomer](#) ()
MainWindow::addCustomer open window to add a new customer.
- void [editCustomer](#) ()
MainWindow::editCustomer open window to modify a customer.
- void [removeCustomer](#) ()
MainWindow::removeCustomer open a popup to confirm the deletion of a customer, if ok remove the customer.
- void [addQuote](#) ()
MainWindow::addQuote open window to add a new quote.
- void [addBill](#) ()
MainWindow::addBill open window to add a new bill.
- void [billingsIsPaid](#) ()
MainWindow::billingsIsPaid Define the current billing as "paid".
- void [editUser](#) ()
MainWindow::editUser modify the user.
- void [search](#) (QString s)
MainWindow::search launch a new search.
- void [addProject](#) ()
MainWindow::addProject Create a new project for a customer.
- void [removeProject](#) (void)
MainWindow::removeProject Remove a project for a customer.
- void [editProject](#) (void)
MainWindow::editProject Modify the customer project.
- void [aboutQt](#) ()
MainWindow::aboutQt show Qt's details.
- void [aboutFact](#) ()
MainWindow::aboutFact show FACT's details (FACT team)
- void [aboutFactDev](#) ()
MainWindow::aboutFactDev() show FactDev's details (FactDev Software)
- void [aboutIcons](#) ()
MainWindow::aboutIcons() show icons's details.
- void [updateButtons](#) (void)
updateButton Update all button to disable or enabled its
- void [editDoc](#) ()
MainWindow::editDoc Edit the quote or bill of the project.
- void [removeDoc](#) ()
MainWindow::removeDoc Remove the quote or bill of the project.
- void [generateTex](#) ()
MainWindow::editQuote Edit the qupte or.

Public Member Functions

- [MainWindow](#) (QWidget *parent=0)
MainWindow: Construct a window.
- int [getCurrentCustomerId](#) ()
MainWindow::getCurrentCustomerId get the selected customer.
- int [getCurrentProjectId](#) ()
MainWindow::getCurrentProjectId get the selected project id.
- int [getCurrentQuoteId](#) ()
MainWindow::getCurrentQuoteId get the selected quote id.
- QString [getCurrentCustomerName](#) ()
MainWindow::getCurrentCustomerName get the selected customer name in the customers' table.
- QString [getCurrentProjectName](#) ()
MainWindow::getCurrentProjectName get the selected project name in the table of projects.
- int [treeLevel](#) ()
MainWindow::treeLevel return the level of the node selected in the tree.
- QModelIndex [rootTree](#) ()
MainWindow::rootTree return the root of the tree "Tous les clients".
- void [addDoc](#) (bool isBilling)
MainWindow::addDoc open window to add a new document.

8.52.1 Detailed Description

The [MainWindow](#) class Main Window of the software.

Author

Everybody

8.52.2 Constructor & Destructor Documentation

8.52.2.1 [Gui::MainWindow::MainWindow \(QWidget * parent = 0 \)](#) [explicit]

[MainWindow](#): Construct a window.

Parameters

<i>parent</i>	
---------------	--

8.52.3 Member Function Documentation

8.52.3.1 void [Gui::MainWindow::addBill \(\)](#) [slot]

[MainWindow::addBill](#) open window to add a new bill.

See Also

[AddQuoteDialog](#)

8.52.3.2 void [Gui::MainWindow::addDoc \(bool isBilling \)](#)

[MainWindow::addDoc](#) open window to add a new document.

Parameters

<i>bool</i>	quote or bill
-------------	---------------

See Also

[addBill](#) [addQuote](#)

8.52.3.3 void Gui::MainWindow::addProject () [slot]

[MainWindow::addProject](#) Create a new project for a customer.

See Also

[AddProjectDialog](#)

8.52.3.4 void Gui::MainWindow::addQuote () [slot]

[MainWindow::addQuote](#) open window to add a new quote.

See Also

[AddQuoteDialog](#)

8.52.3.5 void Gui::MainWindow::editUser () [slot]

[MainWindow::editUser](#) modify the user.

See Also

[UserDataDialog](#)

8.52.3.6 int Gui::MainWindow::getCurrentCustomerId ()

[MainWindow::getCurrentCustomerId](#) get the selected customer.

Returns

id of the selected customer

8.52.3.7 QString Gui::MainWindow::getCurrentCustomerName ()

[MainWindow::getCurrentCustomerName](#) get the selected customer name in the customers' table.

Returns

name of the selected customer

8.52.3.8 int Gui::MainWindow::getCurrentProjectId ()

[MainWindow::getCurrentProjectId](#) get the selected project id.

Returns

id of the selected project

8.52.3.9 QString Gui::MainWindow::getCurrentProjectName ()

[MainWindow::getCurrentProjectName](#) get the selected project name in the table of projects.

Returns

name of the selected project

8.52.3.10 int Gui::MainWindow::getCurrentQuoteld ()

[MainWindow::getCurrentQuoteld](#) get the selected quote id.

Returns

id of the selected quote

8.52.3.11 QModelIndex Gui::MainWindow::rootTree ()

[MainWindow::rootTree](#) return the root of the tree "Tous les clients".

Returns

QModelIndex

8.52.3.12 void Gui::MainWindow::search (QString s) [slot]

[MainWindow::search](#) launch a new search.

Parameters

s	text in field
---	---------------

8.52.3.13 int Gui::MainWindow::treeLevel ()

[MainWindow::treeLevel](#) return the level of the node selected in the tree.

Returns

integer, depth of the item in tree

The documentation for this class was generated from the following files:


- /home/travis/build/FACT-Team/FactDev/src/gui/mainwindow/mainwindow.h
- /home/travis/build/FACT-Team/FactDev/src/gui/mainwindow/mainwindow.cpp

8.53 Gui::Dialogs::MessageBox Class Reference

The [MessageBox](#) class Information window with message.

```
#include <messagebox.h>
```

Inheritance diagram for Gui::Dialogs::MessageBox:



Public Member Functions

- [MessageBox](#) (QWidget *parent=0)
[MessageBox::MessageBox](#) Construt a **MessageBox**
- void [aboutFact](#) ()
[MessageBox::aboutFact](#) Defines FACT team information.
- void [aboutFactDev](#) ()
[MessageBox::aboutFactDev](#) Defines FactDev software information.
- void [aboutIcons](#) ()
[MessageBox::aboutIcons](#) Defines icons theme information.
- void [setImage](#) (QString img, int width=128, int height=128)
[MessageBox::setImage](#) Add the icon img to the current window.
- void [setText](#) (QString txt)
[MessageBox::setText](#) Add the text txt to the current window.

Static Public Member Functions

- static void [showAboutFact](#) ()
[MessageBox::showAboutFact](#) Shows window about FACT team.
- static void [showAboutFactDev](#) ()
[MessageBox::showAboutFactDev](#) Shows window about FactDev software.
- static void [showAboutIcons](#) ()
[MessageBox::showAboutIcons](#) Shows about icons theme of FactDev software.

8.53.1 Detailed Description

The [MessageBox](#) class Information window with message.

Author

Florent Berbie

8.53.2 Constructor & Destructor Documentation

8.53.2.1 Gui::Dialogs::MessageBox::MessageBox (QWidget * parent = 0) [explicit]

[MessageBox::MessageBox](#) Construt a **MessageBox**

Parameters

<i>parent</i>	
---------------	--

8.53.3 Member Function Documentation

8.53.3.1 void Gui::Dialogs::MessageBox::setImage (QString img, int width = 128, int height = 128)

[MessageBox::setImage](#) Add the icon *img* to the current window.

Parameters

<i>img</i>	Icon
<i>width</i>	Icon width (default: 128)
<i>height</i>	Icon height (default: 128)

8.53.3.2 void Gui::Dialogs::MessageBox::setText (QString txt)

[MessageBox::setText](#) Add the text *txt* to the current window.

Parameters

<i>txt</i>	Text inside the current window
------------	--------------------------------

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/dialogs/messagebox.h
- /home/travis/build/FACT-Team/FactDev/src/gui/dialogs/messagebox.cpp

8.54 Parameters Class Reference

The [Parameters](#) class Class for simple user parameters.

```
#include <parameters.h>
```

Static Public Attributes

- static const QString [DB_FILENAME](#) = "database.db"
DB_FILENAME The database sqlite file name.
- static const double [VERSION](#) = 1.0
VERSION Version number of software.

8.54.1 Detailed Description

The [Parameters](#) class Class for simple user parameters.

Author

Antoine de Roquemaurel

8.54.2 Member Data Documentation

8.54.2.1 const QString Parameters::DB_FILENAME = "database.db" [static]

[DB_FILENAME](#) The database sqlite file name.

Database file name

8.54.2.2 const double Parameters::VERSION = 1.0 [static]

[VERSION](#) Version number of software.

Application version


The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/parameters.h
- /home/travis/build/FACT-Team/FactDev/src/parameters.cpp

8.55 Mustache::PartialFileLoader Class Reference

```
#include <mustache.h>
```

Inheritance diagram for Mustache::PartialFileLoader:



Public Member Functions

- **PartialFileLoader** (const QString &basePath)
- virtual QString [getPartial](#) (const QString &name)

8.55.1 Detailed Description

A partial fetcher when loads templates from '`<name>.mustache`' files in a given directory.

Once a partial has been loaded, it is cached for future use.

8.55.2 Member Function Documentation

8.55.2.1 QString PartialFileLoader::getPartial (const QString & *name*) [virtual]

Returns the partial template with a given `name`.

Implements [Mustache::PartialResolver](#).


The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/libs/qt-mustache/src/mustache.h
- /home/travis/build/FACT-Team/FactDev/src/libs/qt-mustache/src/mustache.cpp

8.56 Mustache::PartialMap Class Reference

```
#include <mustache.h>
```

Inheritance diagram for Mustache::PartialMap:



Public Member Functions

- **PartialMap** (const QHash< QString, QString > &partials)
- virtual QString [getPartial](#) (const QString &name)

8.56.1 Detailed Description

A simple partial fetcher which returns templates from a map of (partial name -> template)

8.56.2 Member Function Documentation

8.56.2.1 QString PartialMap::getPartial (const QString & name) [virtual]

Returns the partial template with a given `name`.

Implements [Mustache::PartialResolver](#).


The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/libs/qt-mustache/src/mustache.h
- /home/travis/build/FACT-Team/FactDev/src/libs/qt-mustache/src/mustache.cpp

8.57 Mustache::PartialResolver Class Reference

```
#include <mustache.h>
```

Inheritance diagram for Mustache::PartialResolver:



Public Member Functions

- virtual QString [getPartial](#) (const QString &name)=0

8.57.1 Detailed Description

Interface for fetching template partials.

8.57.2 Member Function Documentation

8.57.2.1 virtual QString Mustache::PartialResolver::getPartial (const QString & name) [pure virtual]

Returns the partial template with a given `name`.

Implemented in [Mustache::PartialFileLoader](#), and [Mustache::PartialMap](#).

The documentation for this class was generated from the following file:

- /home/travis/build/FACT-Team/FactDev/src/libs/qt-mustache/src/mustache.h

8.58 Utils::pointers Class Reference

Static Public Member Functions

- static void **deleteIfNotNull** (QObject *p)

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/utils/pointers.h
- /home/travis/build/FACT-Team/FactDev/src/utils/pointers.cpp

8.59 Gui::Widgets::Popup Class Reference

Class for display popup quickly.

```
#include <popup.h>
```

Static Public Member Functions

- static void **toImplement** (QString, QWidget *)
Popup::toImplement Method to display a critical message : feature is not implemented now.

8.59.1 Detailed Description

Class for display popup quickly.

Author

Antoine de Roquemaurel

The documentation for this class was generated from the following files:


- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/popup.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/popup.cpp

8.60 Models::Project Class Reference

The [Project](#) class : [Project](#) linked to a [Customer](#).

```
#include <project.h>
```

Inheritance diagram for Models::Project:



Public Member Functions

- [Project](#) ()
Project::Project Construct a [Project](#).
- [Project](#) (QString name)
Project::project Construct a project with a name.
- [Project](#) (int id)
Project::Project Construct a [Project](#) which is specified by an id
- virtual [~Project](#) ()
~Project Desctruct project object
- void [commit](#) ()
Project::commit Update project data in the database.
- void [hydrat](#) (int id)
Project::hydrat Insert project data which is specified by id in the database.
- void [remove](#) ()
Project::remove Remove the current project.
- QVariantHash [getDataMap](#) ()
getDataMap Get all data of model with a HashMap key/value
- QString [getName](#) () const
Project::getName Return the project name.
- void [setName](#) (const QString &name)
Project::setName Modify the project name
- QString [getDescription](#) () const
Project::getDescription Return a project description.
- void [setDescription](#) (const QString &description)
Project::setDescription Modify the project description
- QDate [getBeginDate](#) () const
Project::getBeginDate return the date of creation of the [Project](#)
- void [setBeginDate](#) (QDate beginDate)
Project::setBeginDate Modify beginDate of a [Project](#)
- QDate [getEndDate](#) () const
Project::getEndDate Return the endDate of the [Project](#)
- void [setEndDate](#) (QDate endDate)
Project::setEndDate Modify endDate of [Project](#)
- double [getDailyRate](#) () const
Project::getDailyRate Return the daily rate estimated for this project.
- void [setDailyRate](#) (double dailyRate)
Project::setDailyRate Modify the daily rate dailyRate of the current project.
- QSharedPointer< [Customer](#) > [getCustomer](#) () const
Project::getCustomer Return the reference to the customer linked to this project.
- void [setCustomer](#) (QSharedPointer< [Customer](#) > customer)
Project::setCustomer Modify the customer linked to this project.
- bool [operator==](#) (const [Project](#) &p)
Project::operator == Re-define the operator "==" to compare if the current project is the same to the other [Project](#) p
Return TRUE if both projects are the same, else FALSE.
- bool [operator<](#) (const [Project](#) &p) const
Project::operator < defines the operator "<" to compare two [Project](#) and to see if the first is anterior to the second.
- bool [operator!=](#) (const [Project](#) &p)
Project::operator != Re-define the operator "!=" to compare if the current project is differnt to the other [Project](#) p
Return TRUE if both projects are different, else FALSE.

Additional Inherited Members

8.60.1 Detailed Description

The [Project](#) class : [Project](#) linked to a [Customer](#).

Author

Florent Berbie

See Also

[IModel](#)

8.60.2 Constructor & Destructor Documentation

8.60.2.1 Models::Project::Project (int *id*)

[Project::Project](#) Construct a [Project](#) which is specified by an *id*

Parameters

<i>id</i>	
-----------	--

8.60.3 Member Function Documentation

8.60.3.1 QDate Models::Project::getBeginDate () const

[Project::getBeginDate](#) return the date of creation of the [Project](#)

Returns

the begin date of the [Project](#)

8.60.3.2 QSharedPointer< Customer > Models::Project::getCustomer () const

[Project::getCustomer](#) Return the reference to the customer linked to this project.

Returns

customer linked to this project

8.60.3.3 double Models::Project::getDailyRate () const

[Project::getDailyRate](#) Return the daily rate estimated for this project.

Returns

the daily rate linket to the current project

8.60.3.4 QVariantHash Models::Project::getDataMap () [virtual]

getDataMap Get all data of model with a HashMap key/value

Returns

Model's data

Implements [Models::IModel](#).

8.60.3.5 QString Models::Project::getDescription () const

[Project::getDescription](#) Return a project description.

Returns

project description

8.60.3.6 QDate Models::Project::getEndDate () const

[Project::getEndDate](#) Return the *endDate* of the [Project](#)

Returns

the end date of the project

8.60.3.7 QString Models::Project::getName () const

[Project::getName](#) Return the project name.

Returns

project name

8.60.3.8 void Models::Project::hydrat (int *id*) [virtual]

[Project::hydrat](#) Insert project data which is specified by *id* in the database.

Parameters

<i>id</i>	Project identify
-----------	----------------------------------

Implements [Models::IModel](#).

8.60.3.9 bool Models::Project::operator!= (const [Project](#) & *p*)

[Project::operator ==](#) Re-define the operator "!=" to compare if the current project is different to the other [Project](#) *p*
Return TRUE if both projects are different, else FALSE.

Parameters

<i>c</i>	Project to compare
----------	------------------------------------

Returns

boolean

8.60.3.10 `bool Models::Project::operator< (const Project & p) const`

`Project::operator <` defines the operator "<" to compare two `Project` and to see if the first is anterior to the second.

Parameters

<i>b</i>	the Project to compare with the current Project
----------	---

Returns

true if the [Project](#) are different else false

8.60.3.11 `bool Models::Project::operator==(const Project & p)`

[Project::operator ==](#) Re-define the operator "==" to compare if the current project is the same to the other [Project](#) *p*
Return TRUE if both projects are the same, else FALSE.

Parameters

<i>c</i>	Project to compare
----------	------------------------------------

Returns

boolean

8.60.3.12 `void Models::Project::setBeginDate (QDate beginDate)`

[Project::setBeginDate](#) Modify *beginDate* of a [Project](#)

Parameters

<i>beginDate</i>	the new date of creation of the project
------------------	---

8.60.3.13 `void Models::Project::setCustomer (QSharedPointer< Customer > customer)`

[Project::setCustomer](#) Modify the *customer* linked to this project.

Parameters

<i>customer</i>	New customer associated to this project
-----------------	---

8.60.3.14 `void Models::Project::setDailyRate (double dailyRate)`

[Project::setDailyRate](#) Modify the daily rate *dailyRate* of the current project.

Parameters

<i>dailyRate</i>	New daily rate associated to the current project
------------------	--

8.60.3.15 `void Models::Project::setDescription (const QString & description)`

[Project::setDescription](#) Modify the project *description*

Parameters

<i>description</i>	New project description
--------------------	-------------------------

8.60.3.16 `void Models::Project::setEndDate (QDate endDate)`

[Project::setEndDate](#) Modify *endDate* of [Project](#)

Parameters

<i>endDate</i>	the new end date of the project
----------------	---------------------------------

8.60.3.17 void Models::Project::setName (const QString & name)

[Project::setName](#) Modify the project *name*

Parameters


<i>name</i>	Project name
-------------	------------------------------

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/models/project.h
- /home/travis/build/FACT-Team/FactDev/src/models/project.cpp

8.61 Gui::Widgets::Delegates::ProjectComboDelegate Class Reference

Inheritance diagram for Gui::Widgets::Delegates::ProjectComboDelegate:



Public Member Functions


- **ProjectComboDelegate** (QSharedPointer< [Models::Customer](#) > c, QObject *parent=0)
- QWidget * **createEditor** (QWidget *parent, const QStyleOptionViewItem &option, const QModelIndex &index) const
- void **paint** (QPainter *painter, const QStyleOptionViewItem &option, const QModelIndex &index) const
- void **removeInCombo** (QList< int > &)
- QMap< int, [Models::Project](#) > **getProjects** () const
- bool **getLocked** () const
- void **setLocked** (bool getLocked)

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/delegates/projectcombodelegate.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/delegates/projectcombodelegate.cpp

8.62 Gui::Widgets::WdgModels::ProjectContributoriesTableModel Class Reference

Inheritance diagram for Gui::Widgets::WdgModels::ProjectContributoriesTableModel:



Public Member Functions

- [ProjectContributoriesTableModel](#) (QObject *parent=0)
ContributoriesTableModel Construct a *ContributoriesTableModel*.
- int [rowCount](#) (const QModelIndex &) const
rowCount Number of contributories row
- int [columnCount](#) (const QModelIndex &) const
columnCount Number of column of a contributory
- QVariant [data](#) (const QModelIndex &index, int role) const
data Obtains data of a specify cell
- QVariant [headerData](#) (int section, Qt::Orientation orientation, int role) const
headerData Obtains header title of table
- bool [setData](#) (const QModelIndex &index, const QVariant &value, int role=Qt::EditRole)
setData Change data of a cell
- Qt::ItemFlags [flags](#) (const QModelIndex &index) const
flags Differents table flags
- void **append** (QPair< [Models::Project](#) *, [Models::Rate](#) > p)
- void **append** ()
- bool **allProjectsChose** ()
- QList< int > & **getSelectedProjects** ()
- void **remove** (int index)
- QPair< [Models::Project](#) *, [Models::Rate](#) > **getProject** (const int row)
- QList< QPair< [Models::Project](#) *, [Models::Rate](#) > > **getProjects** (void)

8.62.1 Constructor & Destructor Documentation

8.62.1.1 `Gui::Widgets::WdgModels::ProjectContributoriesTableModel::ProjectContributoriesTableModel (QObject * parent = 0)`

[ContributoriesTableModel](#) Construct a [ContributoriesTableModel](#).

Parameters

<i>parent</i>	Parent widget
---------------	---------------

8.62.2 Member Function Documentation

8.62.2.1 `int Gui::Widgets::WdgModels::ProjectContributoriesTableModel::columnCount (const QModelIndex &) const`

columnCount Number of column of a contributory

Returns

The number of column

8.62.2.2 QVariant Gui::Widgets::WdgModels::ProjectContributoriesTableModel::data (const QModelIndex & *index*, int *role*)
const

data Obtains data of a specify cell

Parameters

<i>index</i>	The cell who we want data
<i>role</i>	The role of set

Returns

The data of cell

8.62.2.3 `Qt::ItemFlags Gui::Widgets::WdgModels::ProjectContributoriesTableModel::flags (const QModelIndex & index) const`

flags Differeents table flags

Parameters

<i>index</i>	The cell who we want to know flags
--------------	------------------------------------

Returns

Flags

8.62.2.4 `QVariant Gui::Widgets::WdgModels::ProjectContributoriesTableModel::headerData (int section, Qt::Orientation orientation, int role) const`

headerData Obtains header title of table

Parameters

<i>section</i>	The number of column
<i>orientation</i>	The table orientation
<i>role</i>	

Returns

The Title header of column

8.62.2.5 `int Gui::Widgets::WdgModels::ProjectContributoriesTableModel::rowCount (const QModelIndex &) const`

rowCount Number of contributories row

Returns

The number of contributories

8.62.2.6 `bool Gui::Widgets::WdgModels::ProjectContributoriesTableModel::setData (const QModelIndex & index, const QVariant & value, int role = Qt::EditRole)`

setData Change data of a cell

Parameters

<i>index</i>	The cell to change data
<i>value</i>	The new value
<i>role</i>	The role of cell

Returns

True if we could edit

The documentation for this class was generated from the following files:


- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/widgetmodels/projectcontributoriestablemodel.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/widgetmodels/projectcontributoriestablemodel.cpp

8.63 Databases::ProjectDatabase Class Reference

The [ProjectDatabase](#) class Project table database.

```
#include <projectdatabase.h>
```

Inheritance diagram for Databases::ProjectDatabase:

**Public Member Functions**

- [Models::Project](#) * [getProject](#) (const int pld)
ProjectDatabase::getProject Get informations about the project identified by 'pld'.
- [Models::Project](#) * [getProject](#) (QStringQuery &q)
ProjectDatabase::getProject.
- int [addProject](#) (const [Models::Project](#) &)
ProjectDatabase::addProject Add the project 'pProject' to the database.
- void [updateProject](#) (const [Models::Project](#) &)
ProjectDatabase::updateProject Update informations about the project.
- void [removeProject](#) (const int pld)
removeProject Remove the project with the id 'pld'
- int [getNbProjects](#) ()
ProjectDatabase::getNbProjects Return the number of projects existing.
- int [getNbProjectsForACustomer](#) (const int pld)
ProjectDatabase::getNbProjectsForACustomer Return the number of projects existing for an identify customer pld
- QMap< int, [Models::Project](#) > [getProjectsOfCustomer](#) (QSharedPointer< [Models::Customer](#) > c)
getProjectsOfCustomer Return all projects of a customer
- [WdgModels::ProjectsTableModel](#) * [getProjectsTable](#) (const int pld) throw (DbException*)
getProjectsTable Return all projects of a customer in QStandardItemModel
- QSharedPointer< [Project](#) > [updateProject](#) (QStringQuery &q)
getProject Obtain a project without new query
- QList< [Project](#) * > [getAllProjects](#) ()
Project::getAllProjects Return the list of projects.

Static Public Member Functions

- static [ProjectDatabase](#) * [instance](#) () throw (DbException*)
ProjectDatabase::getInstance Return an instance of [ProjectDatabase](#).

Additional Inherited Members

8.63.1 Detailed Description

The [ProjectDatabase](#) class Project table database.

Author

Florent Berbie

See Also

[Database](#)
[Project](#)

8.63.2 Member Function Documentation

8.63.2.1 `int Databases::ProjectDatabase::addProject (const Models::Project & pProject)`

[ProjectDatabase](#)::addProject Add the project 'pProject' to the database.

Returns

project id

8.63.2.2 `QList< Project * > Databases::ProjectDatabase::getAllProjects ()`

[ProjectDatabase](#)::getAllProjects Return the list of projects.

Returns

Projects list

8.63.2.3 `int Databases::ProjectDatabase::getNbProjects ()`

[ProjectDatabase](#)::getNbProjects Return the number of projects existing.

Returns

number of projects

8.63.2.4 `int Databases::ProjectDatabase::getNbProjectsForACustomer (const int pld)`

[ProjectDatabase](#)::getNbProjectsForACustomer Return the number of projects existing for an identify customer *pld*

Parameters

<i>pld</i>	Project id
------------	------------

Returns

number of projects

8.63.2.5 `Models::Project * Databases::ProjectDatabase::getProject (const int pld)`

[ProjectDatabase](#)::getProject Get informations about the project identified by 'pld'.

Parameters

<i>pld</i>	project
------------	---------

Returns

the project

8.63.2.6 Models::Project * Databases::ProjectDatabase::getProject (QSqlQuery & *q*)

[ProjectDatabase::getProject](#).

Parameters

<i>q</i>	
----------	--

Returns

8.63.2.7 QMap< int, Models::Project > Databases::ProjectDatabase::getProjectsOfCustomer (QSharedPointer< Models::Customer > *c*)

getProjectsOfCustomer Return all projects of a customer

Parameters

<i>c</i>	The customer
----------	--------------

Returns

All projects of *c* with id in key

8.63.2.8 WdgModels::ProjectsTableModel * Databases::ProjectDatabase::getProjectsTable (const int *pld*) throw DbException *)

getProjectsTable Return all projects of a customer in QStandardItemModel

Parameters

<i>filter</i>	Select only projects who are specified by <i>filter</i>
---------------	---

Returns

QStandardItemModel an item model for QTableView

8.63.2.9 ProjectDatabase * Databases::ProjectDatabase::instance () throw DbException *) [static]

ProjectDatabase::getInstance Return an instance of [ProjectDatabase](#).

Returns

Instance of [ProjectDatabase](#)

8.63.2.10 void Databases::ProjectDatabase::removeProject (const int *pld*)

removeProject Remove the project with the id 'pld'

Parameters

<i>pld</i>	project id
------------	------------

8.63.2.11 QSharedPointer< Models::Project > Databases::ProjectDatabase::updateProject (QSqlQuery & *q*)

getProject Obtain a project without new query

Parameters

<i>q</i>	The query to use
----------	------------------

Returns


The project linked to *q*

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/database/projectdatabase.h
- /home/travis/build/FACT-Team/FactDev/src/database/projectdatabase.cpp

8.64 ProjectDatabaseTest Class Reference

Inheritance diagram for ProjectDatabaseTest:




The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/tests/database/projectdatabasetest.h
- /home/travis/build/FACT-Team/FactDev/tests/database/projectdatabasetest.cpp

8.65 ProjectModelTest Class Reference

Inheritance diagram for ProjectModelTest:



The documentation for this class was generated from the following files:


- /home/travis/build/FACT-Team/FactDev/tests/models/projectmodeltest.h
- /home/travis/build/FACT-Team/FactDev/tests/models/projectmodeltest.cpp

8.66 Gui::Widgets::WdgModels::ProjectsTableModel Class Reference

The [ProjectsTableModel](#) class for a Project table.

```
#include <projectstablemodel.h>
```

Inheritance diagram for Gui::Widgets::WdgModels::ProjectsTableModel:



Public Member Functions

- [ProjectsTableModel](#) ()
ProjectsTableModel::ProjectsTableModel Construct a [ProjectsTableModel](#).
- int [rowCount](#) (const QModelIndex &) const
ProjectsTableModel::rowCount Number of projects row.
- int [columnCount](#) (const QModelIndex &) const
ProjectsTableModel::columnCount Number of column of a Project.
- QVariant [data](#) (const QModelIndex &index, int role=Qt::DisplayRole) const
ProjectsTableModel::data Obtains data of a specify cell.
- QVariant [headerData](#) (int section, Qt::Orientation orientation, int role=Qt::DisplayRole) const
ProjectsTableModel::headerData Obtains header title of table.
- bool [setData](#) (const QModelIndex &index, const QVariant &value, int role=Qt::EditRole)
ProjectsTableModel::setData Change data of a cell.
- void [append](#) (const [Project](#) &project)
ProjectsTableModel::append Add a new line in table.
- void [remove](#) (const int i)
ProjectsTableModel::remove Remove a line.
- Qt::ItemFlags [flags](#) (const QModelIndex &index) const
ProjectsTableModel::flags Differents table flags.
- int [count](#) ()
ProjectsTableModel::count Number of projects in table.
- QList< [Project](#) > [getProjects](#) () const
ProjectsTableModel::getProjects Return the list of projects.

8.66.1 Detailed Description

The [ProjectsTableModel](#) class for a Project table.

Author

Florent Berbie

See Also

[Project](#)

8.66.2 Constructor & Destructor Documentation

8.66.2.1 Gui::Widgets::WdgModels::ProjectsTableModel::ProjectsTableModel ()

[ProjectsTableModel::ProjectsTableModel](#) Construct a [ProjectsTableModel](#).

Parameters

<i>parent</i>	Parent widget
---------------	---------------

8.66.3 Member Function Documentation

8.66.3.1 void Gui::Widgets::WdgModels::ProjectsTableModel::append (const Project & *project*)

[ProjectsTableModel::append](#) Add a new line in table.

Parameters

<i>Project</i>	The new Project
----------------	-----------------

8.66.3.2 int Gui::Widgets::WdgModels::ProjectsTableModel::columnCount (const QModelIndex &) const

[ProjectsTableModel::columnCount](#) Number of column of a Project.

Returns

The number of column

8.66.3.3 int Gui::Widgets::WdgModels::ProjectsTableModel::count ()

[ProjectsTableModel::count](#) Number of projects in table.

Returns

The number of projects

8.66.3.4 QVariant Gui::Widgets::WdgModels::ProjectsTableModel::data (const QModelIndex & *index*, int *role* = Qt::DisplayRole) const

[ProjectsTableModel::data](#) Obtains data of a specify cell.

Parameters

<i>index</i>	The cell who we want data
<i>role</i>	The role of set

Returns

The data of cell

8.66.3.5 Qt::ItemFlags Gui::Widgets::WdgModels::ProjectsTableModel::flags (const QModelIndex & *index*) const

[ProjectsTableModel::flags](#) Differents table flags.

Parameters

<i>index</i>	The cell who we want to know flags
--------------	------------------------------------

Returns

Flags

8.66.3.6 `QList< Project > Gui::Widgets::WdgModels::ProjectsTableModel::getProjects (void) const`

[ProjectsTableModel::getProjects](#) Return the list of projects.

Returns

list of projects

8.66.3.7 `QVariant Gui::Widgets::WdgModels::ProjectsTableModel::headerData (int section, Qt::Orientation orientation, int role = Qt::DisplayRole) const`

[ProjectsTableModel::headerData](#) Obtains header title of table.

Parameters

<i>section</i>	The number of column
<i>orientation</i>	The table orientation
<i>role</i>	

Returns

The Title header of column

8.66.3.8 `void Gui::Widgets::WdgModels::ProjectsTableModel::remove (const int i)`

[ProjectsTableModel::remove](#) Remove a line.

Parameters

<i>i</i>	The number of line to remove
----------	------------------------------

8.66.3.9 `int Gui::Widgets::WdgModels::ProjectsTableModel::rowCount (const QModelIndex &) const`

[ProjectsTableModel::rowCount](#) Number of projects row.

Returns

The number of projects

8.66.3.10 `bool Gui::Widgets::WdgModels::ProjectsTableModel::setData (const QModelIndex & index, const QVariant & value, int role = Qt::EditRole)`

[ProjectsTableModel::setData](#) Change data of a cell.

Parameters

<i>index</i>	The cell to change data
<i>value</i>	The new value
<i>role</i>	The role of cell

Returns

True if we could edit

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/widgetsmodels/projectstablemodel.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/widgetsmodels/projectstablemodel.cpp

8.67 Gui::Widgets::ProjectsWidget Class Reference

The [ProjectsWidget](#) class Actions on Project.

```
#include <projectswidget.h>
```

Inheritance diagram for Gui::Widgets::ProjectsWidget:



Public Slots

- void [newProject](#) ()
ProjectsWidget::addProject Event which sends a signal to add a new project.
- void [editSelectedProject](#) ()
ProjectsWidget::editSelectedProject Event which sends a signal to edit the project selected.
- void [removeSelectedProject](#) ()
ProjectsWidget::removeSelectedProject Event which sends a signal to remove the project selected.
- void [updateBtn](#) (bool b)
ProjectsWidget::updateBtn Update the toolbar in tblProjects.

Signals

- void [addProject](#) ()
ProjectsWidget::addProject Add a new project to the current Customer.
- void [editProject](#) ()
ProjectsWidget::editProject Edit the current Customer selected.
- void [removeProject](#) ()
ProjectsWidget::removeProject Remove the current Customer selected.

Public Member Functions

- [ProjectsWidget](#) (QWidget *parent=0)
ProjectsWidget::ProjectsWidget Construct a [ProjectsWidget](#).

8.67.1 Detailed Description

The [ProjectsWidget](#) class Actions on Project.

Author

Florent Berbie

8.67.2 Constructor & Destructor Documentation

8.67.2.1 [Gui::Widgets::ProjectsWidget::ProjectsWidget](#) ([QWidget](#) * *parent* = 0) [explicit]

[ProjectsWidget::ProjectsWidget](#) Construct a [ProjectsWidget](#).

Parameters

<i>parent</i>	
---------------	--

8.67.3 Member Function Documentation

8.67.3.1 void Gui::Widgets::ProjectsWidget::updateBtn (bool *b*) [slot]

[ProjectsWidget::updateBtn](#) Update the toolbar in tblProjects.

Parameters

<i>boolean</i>	if a row is selected
----------------	----------------------


The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/projectswidget.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/projectswidget.cpp

8.68 Mustache::QtVariantContext Class Reference

```
#include <mustache.h>
```

Inheritance diagram for Mustache::QtVariantContext:



Public Types

- typedef QString(* [fn_t](#))(const QString &, [Mustache::Renderer](#) *, [Mustache::Context](#) *)

Public Member Functions

- [QtVariantContext](#) (const QVariant &root, [PartialResolver](#) *resolver=0)
- virtual QString [stringValue](#) (const QString &key) const
- virtual bool [isFalse](#) (const QString &key) const
- virtual int [listCount](#) (const QString &key) const
- virtual void [push](#) (const QString &key, int index=-1)
- virtual void [pop](#) ()
- virtual bool [canEval](#) (const QString &key) const
- virtual QString [eval](#) (const QString &key, const QString &_template, [Mustache::Renderer](#) *renderer)

8.68.1 Detailed Description

A context implementation which wraps a QVariantHash or QVariantMap.

8.68.2 Member Typedef Documentation

8.68.2.1 `typedef QString(* Mustache::QtVariantContext::fn_t)(const QString &, Mustache::Renderer *, Mustache::Context *)`

Construct a [QtVariantContext](#) which wraps a dictionary in a [QVariantHash](#) or a [QVariantMap](#).

8.68.3 Member Function Documentation

8.68.3.1 `bool QtVariantContext::canEval (const QString & key) const` [virtual]

Returns true if [eval\(\)](#) should be used to render section tags using `key`. If [canEval\(\)](#) returns true for a key, the renderer will pass the literal, unrendered block of text for the section to [eval\(\)](#) and replace the section with the result.

[canEval\(\)](#) and [eval\(\)](#) are equivalents for callable objects (eg. lambdas) in other Mustache implementations.

The default implementation always returns false.

Reimplemented from [Mustache::Context](#).

Reimplemented in [CounterContext](#), and [CounterContext](#).

8.68.3.2 `QString QtVariantContext::eval (const QString & key, const QString & _template, Mustache::Renderer * renderer)` [virtual]

Callback used to render a template section with the given `key`. `renderer` will substitute the original section tag with the result of [eval\(\)](#).

The default implementation returns an empty string.

Reimplemented from [Mustache::Context](#).

Reimplemented in [CounterContext](#), and [CounterContext](#).

8.68.3.3 `bool QtVariantContext::isFalse (const QString & key) const` [virtual]

Returns true if the value for `key` is 'false' or an empty list. 'False' values typically include empty strings, the boolean value false etc.

When processing a section Mustache tag, the section is not rendered if the key is false, or for an inverted section tag, the section is only rendered if the key is false.

Implements [Mustache::Context](#).

8.68.3.4 `int QtVariantContext::listCount (const QString & key) const` [virtual]

Returns the number of items in the list value for `key` or 0 if the value for `key` is not a list.

Implements [Mustache::Context](#).

8.68.3.5 `void QtVariantContext::pop ()` [virtual]

Exit the current context.

Implements [Mustache::Context](#).

8.68.3.6 `void QtVariantContext::push (const QString & key, int index = -1) [virtual]`

Set the current context to the value for `key`. If `index` is ≥ 0 , set the current context to the `index`'th value in the list value for `key`.

Implements [Mustache::Context](#).

8.68.3.7 `QString QtVariantContext::stringValue (const QString & key) const [virtual]`

Returns a string representation of the value for `key` in the current context. This is used to replace a Mustache value tag.

Implements [Mustache::Context](#).

Reimplemented in [CounterContext](#), and [CounterContext](#).

The documentation for this class was generated from the following files:

- `/home/travis/build/FACT-Team/FactDev/src/libs/qt-mustache/src/mustache.h`
- `/home/travis/build/FACT-Team/FactDev/src/libs/qt-mustache/src/mustache.cpp`

8.69 Models::Rate Class Reference

Public Member Functions


- **Rate** (double hourly)
- **Rate** (int idBilling, int idProject)
- void **setDailyRate** (const double &)
- void **setHourlyRate** (const double &)
- double **getDailyRate** () const
- double **getHourlyRate** () const
- int **getNbDailyHours** () const
- double **getLegalRate** () const

The documentation for this class was generated from the following files:

- `/home/travis/build/FACT-Team/FactDev/src/models/rate.h`
- `/home/travis/build/FACT-Team/FactDev/src/models/rate.cpp`

8.70 Databases::RateDatabase Class Reference

Inheritance diagram for Databases::RateDatabase:



Public Member Functions

- void **addRateProject** (int idProject, int idBilling, double hourlyRate)
- double **getRate** (const int idBilling, const int idProject) const
- void **updateRateProject** (int idProject, int idBilling, double hourlyRate)

Static Public Member Functions

- static [RateDatabase](#) * [instance](#) () throw (DbException*)
RateDatabase::getInstance Return an instance of [RateDatabase](#).

Additional Inherited Members

8.70.1 Member Function Documentation

8.70.1.1 [RateDatabase](#) * [Databases::RateDatabase::instance](#) () throw [DbException](#) * [static]

[RateDatabase::getInstance](#) Return an instance of [RateDatabase](#).

Returns


Instance of [RateDatabase](#)

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/database/ratedatabase.h
- /home/travis/build/FACT-Team/FactDev/src/database/ratedatabase.cpp

8.71 RateModelTest Class Reference

Inheritance diagram for RateModelTest:



The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/tests/models/ratemodeltest.h
- /home/travis/build/FACT-Team/FactDev/tests/models/ratemodeltest.cpp

8.72 Gui::Widgets::RateWidget Class Reference

Class for display Rate.

```
#include <ratewidget.h>
```

Inheritance diagram for Gui::Widgets::RateWidget:



Public Slots

- void [setDailyRate](#) ()
setDailyRate Set a new value for the daily rate
- void [setHourlyRate](#) ()
setHourlyRate Set a new value for the hourly rate

Public Member Functions

- [RateWidget](#) (QWidget *parent=0)
RateWidget::RateWidget Construct a rate widget.
- void [initRate](#) ()
RateWidget::initRate Initialize the rate.
- void [setWidgetDailyRateValue](#) (double value)
RateWidget::setWidgetDailyRateValue Modify the value of the daily rate spin box component.
- double [getDailyRate](#) ()
RateWidget::getDailyRate Get the daily rate.
- double [getHourlyRate](#) ()
RateWidget::getHourlyRate Get the hourly rate.
- void [setWidgetHourlyRateValue](#) (double value)
RateWidget::setWidgetHourlyRateValue Modify the value of the hourly rate spin box component.
- void [updateConversionRate](#) ()
updateConversionRate Update daily rate or hourly rate

8.72.1 Detailed Description

Class for display Rate.

Author

Florent Berbie

8.72.2 Constructor & Destructor Documentation

8.72.2.1 [Gui::Widgets::RateWidget::RateWidget \(QWidget * parent = 0 \)](#) [explicit]

[RateWidget::RateWidget](#) Construct a rate widget.

Parameters

<i>parent</i>	The QWidget parent
---------------	--------------------

8.72.3 Member Function Documentation

8.72.3.1 [double Gui::Widgets::RateWidget::getDailyRate \(\)](#)

[RateWidget::getDailyRate](#) Get the daily rate.

Returns

The daily rate

8.72.3.2 `double Gui::Widgets::RateWidget::getHourlyRate ()`

[RateWidget::getHourlyRate](#) Get the hourly rate.

Returns

The hourly rate

8.72.3.3 `void Gui::Widgets::RateWidget::setDailyRate () [slot]`

`setDailyRate` Set a new value for the daily rate

Parameters

<i>dailyRate</i>	The new daily rate
------------------	--------------------

8.72.3.4 `void Gui::Widgets::RateWidget::setHourlyRate () [slot]`

`setHourlyRate` Set a new value for the hourly rate

Parameters

<i>hourlyRate</i>	The new hourly rate
-------------------	---------------------

8.72.3.5 `void Gui::Widgets::RateWidget::setWidgetDailyRateValue (double value)`

[RateWidget::setWidgetDailyRateValue](#) Modify the *value* of the daily rate spin box component.

Parameters

<i>value</i>	New Value
--------------	-----------

8.72.3.6 `void Gui::Widgets::RateWidget::setWidgetHourlyRateValue (double value)`

[RateWidget::setWidgetHourlyRateValue](#) Modify the *value* of the hourly rate spin box component.

Parameters

<i>value</i>	New value
--------------	-----------

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/ratewidget.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/ratewidget.cpp

8.73 Mustache::Renderer Class Reference

```
#include <mustache.h>
```

Public Member Functions

- QString [render](#) (const QString &_template, [Context](#) *context)
- QString [error](#) () const
- int [errorPos](#) () const

- QString [errorPartial](#) () const
- void [setTagMarkers](#) (const QString &startMarker, const QString &endMarker)

8.73.1 Detailed Description

Renders Mustache templates, replacing mustache tags with values from a provided context.

8.73.2 Member Function Documentation

8.73.2.1 QString Renderer::error () const

Returns a message describing the last error encountered by the previous [render\(\)](#) call.

8.73.2.2 QString Renderer::errorPartial () const

Returns the name of the partial where the error occurred, or an empty string if the error occurred in the main template.

8.73.2.3 int Renderer::errorPos () const

Returns the position in the template where the last error occurred when rendering the template or -1 if no error occurred.

If the error occurred in a partial template, the returned position is the offset in the partial template.

8.73.2.4 QString Renderer::render (const QString &_template, Context * context)

Render a Mustache template, using `context` to fetch the values used to replace Mustache tags.

8.73.2.5 void Renderer::setTagMarkers (const QString &startMarker, const QString &endMarker)

Sets the default tag start and end markers. This can be overridden within a template.

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/libs/qt-mustache/src/mustache.h
- /home/travis/build/FACT-Team/FactDev/src/libs/qt-mustache/src/mustache.cpp

8.74 Models::Search Class Reference

The [Search](#) class.

```
#include <search.h>
```

Public Member Functions

- [Search](#) ()
[Search::Search](#) Construct a search.
- [~Search](#) ()
[Search::Search](#) Destruct a search.
- QString [getFilter](#) ()

- Search::getFilter* Return the search filter.
- void **filterOnVarcharElements** (QString &filter, const QStringList list, QString element)
 - Search::filterOnVarcharElements* Search, for each word of the list from the filter, if it corresponds to the element in the database.
 - void **filterOnNumberElements** (QString &filter, const QStringList list, QString element)
 - Search::filterOnNumberElements* Search, for each number of the list from the filter, if it corresponds to the element in the database.
 - void **filterOnCompany** (QString &filter, const QStringList list)
 - Search::filterOnCompany* Search all companies contained in the list of the filter
 - void **filterOnReferentLastname** (QString &filter, const QStringList list)
 - Search::filterOnReferentLastname* Search all referents last name contained in the list of the filter
 - void **filterOnProjects** (QString &filter, const QStringList list)
 - Search::filterOnProjects* Search all projects contained in the list of the filter
 - void **filterOnContributories** (QString &filter, const QStringList list)
 - Search::filterOnContributories* Search all contributories contained in the list of the filter
 - void **filterOnBillsOrQuotes** (QString &filter, const QStringList list)
 - Search::filterOnBillsOrQuotes* Search all bills or quotes which are contained in the list of the filter
 - void **filterOnCustomersWithoutProject** (QString &filter, const QStringList list)
 - Search::filterOnCustomersWithoutProject* Search all customers which are contained in the list of the filter
- bool **getSearchInCompanies** () const
 - Search::getSearchInCompanies* Return if we search a company.
 - void **setSearchInCompanies** (bool searchInCompanies)
 - Search::setSearchInCompanies* Modify the filter of companies search.
 - bool **getSearchInReferentLastname** () const
 - Search::getSearchInReferentLastname* Return if we search a Last name referent.
 - void **setSearchInReferentLastname** (bool searchInReferentLastname)
 - Search::setSearchInReferentLastname* Modify the filter of referents last name search.
 - bool **getSearchInProjects** () const
 - Search::getSearchInProjects* Return TRUE if it exists one or more projets in database.
 - void **setSearchInProjects** (bool searchInProjects)
 - Search::setSearchInProjects* Modify the filter of projects search.
 - bool **searchInContributories** () const
 - Search::getSearchInContributories* Return TRUE if it exists one or more projets in database.
 - void **setSearchInContributories** (bool **searchInContributories**)
 - Search::setSearchInContributories* Modify the filter of contributories search.
 - bool **getSearchInBillsQuotes** () const
 - Search::searchInBillsQuotes* Return TRUE if it exists one or more bills or quotes in database.
 - void **setSearchInBillsQuotes** (bool searchInBillsQuotes)
 - Search::setSearchInBillsQuotes* Modify the filter of bills and quotes search.
 - bool **getGroupFilter** () const
 - Search::getGroupFilter* Return if the filter is activated.
 - void **setGroupFilter** (bool **getGroupFilter**)
 - Search::setGroupFilter* Modify if we active search filter.
 - QString **getText** () const
 - Search::getText* Return sql portion of filter.
 - void **setText** (const QString &**getText**)
 - Search::setText* Modify sql portion.

8.74.1 Detailed Description

The [Search](#) class.

Author

Antoine de Roquemaurel
Florent Berbie

8.74.2 Member Function Documentation

8.74.2.1 void Models::Search::filterOnBillsOrQuotes (QString & *filter*, const QStringList *list*)

[Search::filterOnBillsOrQuotes](#) [Search](#) all bills or quotes which are contained in the *list* of the *filter*

Parameters

<i>filter</i>	Text inputed in searchbar
<i>list</i>	List of bills or quotes

8.74.2.2 void Models::Search::filterOnCompany (QString & *filter*, const QStringList *list*)

[Search::filterOnCompany](#) [Search](#) all companies contained in the *list* of the *filter*

Parameters

<i>filter</i>	Text inputed in searchbar
<i>list</i>	List of companies

8.74.2.3 void Models::Search::filterOnContributories (QString & *filter*, const QStringList *list*)

[Search::filterOnContributories](#) [Search](#) all contributories contained in the *list* of the *filter*

Parameters

<i>filter</i>	Text inputed in searchbar
<i>list</i>	List of contributories

8.74.2.4 void Models::Search::filterOnCustomersWithoutProject (QString & *filter*, const QStringList *list*)

[Search::filterOnCustomersWithoutProject](#) [Search](#) all customers which are contained in the *list* of the *filter*

Parameters

<i>filter</i>	Text inputed in searchbar
<i>list</i>	List of bills or quotes

8.74.2.5 void Models::Search::filterOnNumberElements (QString & *filter*, const QStringList *list*, QString *element*)

[Search::filterOnNumberElements](#) [Search](#), for each number of the *list* from the *filter*, if it corresponds to the *element* in the database.

Parameters

<i>filter</i>	Text inputed in the searchbar
<i>list</i>	List of numbers from the <i>filter</i>
<i>element</i>	Attribute name into the database

8.74.2.6 void Models::Search::filterOnProjects (QString & *filter*, const QStringList *list*)

[Search::filterOnProjects](#) Search all projects contained in the *list* of the *filter*

Parameters

<i>filter</i>	Text inputed in searchbar
<i>list</i>	List of projects

8.74.2.7 void Models::Search::filterOnReferentLastname (QString & *filter*, const QStringList *list*)

[Search::filterOnReferentLastname](#) Search all referents last name contained in the *list* of the *filter*

Parameters

<i>filter</i>	Text inputed in searchbar
<i>list</i>	List of referent last name

8.74.2.8 void Models::Search::filterOnVarcharElements (QString & *filter*, const QStringList *list*, QString *element*)

[Search::filterOnVarcharElements](#) Search, for each word of the *list* from the *filter*, if it corresponds to the *element* in the database.

Parameters

<i>filter</i>	Text inputed in the searchbar
<i>list</i>	List of words from the <i>filter</i>
<i>element</i>	Attribute name into the database

8.74.2.9 QString Models::Search::getFilter ()

[Search::getFilter](#) Return the search filter.

Returns

filter selected (sql portion)

8.74.2.10 bool Models::Search::getGroupFilter () const

[Search::getGroupFilter](#) Return if the filter is activated.

Returns

boolean if search filter is activated

8.74.2.11 bool Models::Search::getSearchInBillsQuotes () const

[Search::searchInBillsQuotes](#) Return TRUE if it exists one or more bills or quotes in database.

Returns

boolean if bills or quotes are existing

8.74.2.12 `bool Models::Search::getSearchInCompanies () const`

[Search::getSearchInCompanies](#) Return if we search a company.

Returns

boolean if we search a company

8.74.2.13 `bool Models::Search::getSearchInProjects () const`

[Search::getSearchInProjects](#) Return TRUE if it exists one or more projets in database.

Returns

boolean if project are existing

8.74.2.14 `bool Models::Search::getSearchInReferentLastname () const`

[Search::getSearchInReferentLastname](#) Return if we search a Last name referent.

Returns

boolean if search concerns the last name of referent

8.74.2.15 `QString Models::Search::getText () const`

[Search::getText](#) Return sql portion of filter.

Returns

QString the sql portion

8.74.2.16 `bool Models::Search::searchInContributories () const`

[Search::getSearchInContributories](#) Return TRUE if it exists one or more projets in database.

Returns

boolean if contributories are existing

8.74.2.17 `void Models::Search::setGroupFilter (bool getGroupFilter)`

[Search::setGroupFilter](#) Modify if we active search filter.

Parameters

<i>getGroupFilter</i>	Get if filter is actived
-----------------------	--------------------------

8.74.2.18 void Models::Search::setSearchInBillsQuotes (bool *searchInBillsQuotes*)

[Search::setSearchInBillsQuotes](#) Modify the filter of bills and quotes search.

Parameters

<i>searchInBills-Quotes</i>	Search in bills or quotes which are concerned
-----------------------------	---

8.74.2.19 void Models::Search::setSearchInCompanies (bool *searchInCompanies*)

[Search::setSearchInCompanies](#) Modify the filter of companies search.

Parameters

<i>getSearchIn-Companies</i>	Search in companies is concerned
------------------------------	--

8.74.2.20 void Models::Search::setSearchInContributories (bool *searchInContributories*)

[Search::setSearchInContributories](#) Modify the filter of contributories search.

Parameters

<i>searchIn-Contributories</i>	Search in contributories which are concerned
--------------------------------	--

8.74.2.21 void Models::Search::setSearchInProjects (bool *searchInProjects*)

[Search::setSearchInProjects](#) Modify the filter of projects search.

Parameters

<i>searchInProjects</i>	Search in projects which are concerned
-------------------------	--

8.74.2.22 void Models::Search::setSearchInReferentLastname (bool *searchInReferentLastname*)

[Search::setSearchInReferentLastname](#) Modify the filter of referents last name search.

Parameters

<i>searchIn-Referent-Lastname</i>	Search in referents last name which are concerned
-----------------------------------	---

8.74.2.23 void Models::Search::setText (const QString & *getText*)

[Search::setText](#) Modify sql portion.

Parameters


<i>getText</i>	Get sql portion
----------------	-----------------

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/models/search.h
- /home/travis/build/FACT-Team/FactDev/src/models/search.cpp

8.75 Gui::Docks::SearchDock Class Reference

Inheritance diagram for Gui::Docks::SearchDock:



Public Slots

- void **search** (QString text)

Signals

- void **textChanged** (QString text)

Public Member Functions


- **SearchDock** (QWidget *parent=0, Qt::WindowFlags flags=0)

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/docks/searchdock.h
- /home/travis/build/FACT-Team/FactDev/src/gui/docks/searchdock.cpp

8.76 searchTest Class Reference

Inheritance diagram for searchTest:



The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/tests/models/searchtest.h
- /home/travis/build/FACT-Team/FactDev/tests/models/searchtest.cpp

8.77 Gui::Widgets::searchWidget Class Reference

Class for search in database.

```
#include <searchwidget.h>
```

Inheritance diagram for Gui::Widgets::searchWidget:



Public Slots

- void [search](#) (QString toSearch)
searchWidget::launch a search
- void [getCustomerData](#) ()
searchWidget::getCustomerData Return data on the customer selected in the QTableView and display this data (First-name, Lastname, Company)

Signals

- void **selectCustomer** ()

Public Member Functions

- [searchWidget](#) (QWidget *parent=0)
searchWidget::searchWidget Construct a search widget
- int [getCurrentCustomerId](#) ()
searchWidget::getCurrentCustomerId Return the id of the customer selected in the table
- bool [isCustomerSelected](#) () const
isCustomerSelected Return TRUE if a customer is selected, else FALSE
- void **selectCustomer** (int id)
- int [getIdCustomer](#) () const
- void **setIdCustomer** (int getIdCustomer)

8.77.1 Detailed Description

Class for search in database.

Author

Antoine de Roquemaurel

8.77.2 Constructor & Destructor Documentation

8.77.2.1 [Gui::Widgets::searchWidget::searchWidget](#) (QWidget * *parent* = 0) [explicit]

[searchWidget::searchWidget](#) Construct a search widget

Parameters

<i>parent</i>	The QWidget parent
---------------	--------------------

8.77.3 Member Function Documentation

8.77.3.1 `int Gui::Widgets::searchWidget::getCurrentCustomerId ()`

[searchWidget::getCurrentCustomerId](#) Return the id of the customer selected in the table

Returns

id of the current customer

8.77.3.2 `bool Gui::Widgets::searchWidget::isCustomerSelected () const`

`isCustomerSelected` Return TRUE if a customer is selected, else FALSE

Returns

boolean

8.77.3.3 `void Gui::Widgets::searchWidget::search (QString toSearch) [slot]`

`searchWidget::launch` a search

Parameters


<i>toSearch</i>	The value to search
-----------------	---------------------

The documentation for this class was generated from the following files:

- `/home/travis/build/FACT-Team/FactDev/src/gui/widgets/searchwidget.h`
- `/home/travis/build/FACT-Team/FactDev/src/gui/widgets/searchwidget.cpp`

8.78 Gui::Dialogs::StartedWindowsDialog Class Reference

Inheritance diagram for `Gui::Dialogs::StartedWindowsDialog`:



Public Slots

- void [checkFields](#) ()
[UserDataDialog::checkFields](#) Check all fields of dialog components.
- void [browseWorkspacePath](#) ()
[UserDataDialog::browseWorkspacePath](#) Open a new window to define the workspace path of the user.
- void [nextToPage2](#) ()

- [StartedWindowsDialog::nextToPage2.](#)
- void [nextToPage3](#) ()
- [StartedWindowsDialog::nextToPage3.](#)
- void [saveSettings](#) ()
- [StartedWindowsDialog::saveSettings.](#)

Public Member Functions

- **StartedWindowsDialog** (QWidget *parent=0)
- void [fillFields](#) ()
- [UserDataDialog::fillFields](#) Fill line edits with the data of the user.
- void [accept](#) ()
- [accept](#) Valid data inputed by user and add these data in Database

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/dialogs/startedwindowsdialog.h
- /home/travis/build/FACT-Team/FactDev/src/gui/dialogs/startedwindowsdialog.cpp

8.79 Utils::String Class Reference

The Utils class.

```
#include <string.h>
```

Static Public Member Functions

- static QString [firstLetterToUpper](#) (QString s)
- [firstLetterToUpper](#) Put the first letter of a string in capslock

8.79.1 Detailed Description

The Utils class.

Author

Antoine de Roquemaurel

8.79.2 Member Function Documentation

8.79.2.1 QString Utils::String::firstLetterToUpper (QString s) [static]

[firstLetterToUpper](#) Put the first letter of a string in capslock

Parameters

s	The string to display
-------------------	-----------------------

Returns


The new string with caps

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/Utils/string.h
- /home/travis/build/FACT-Team/FactDev/src/Utils/string.cpp

8.80 StringTest Class Reference

Inheritance diagram for StringTest:



The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/tests/utls/stringtest.h
- /home/travis/build/FACT-Team/FactDev/tests/utls/stringtest.cpp

8.81 Mustache::Tag Struct Reference

```
#include <mustache.h>
```

Public Types

- enum `Type` {
Null, **Value**, **SectionStart**, **InvertedSectionStart**,
SectionEnd, **Partial**, **Comment**, **SetDelimiter** }
- enum **EscapeMode** { **Escape**, **Unescape**, **Raw** }

Public Attributes

- `Type` **type**
- `QString` **key**
- `int` **start**
- `int` **end**
- `EscapeMode` **escapeMode**

8.81.1 Detailed Description

Holds properties of a tag in a mustache template.

8.81.2 Member Enumeration Documentation

8.81.2.1 enum `Mustache::Tag::Type`

Enumerator

- SectionStart** A `{{key}}` or `{{{key}}}` tag.
- InvertedSectionStart** A `{{#section}}` tag.
- SectionEnd** An `{{^inverted-section}}` tag.
- Partial** A `{{/section}}` tag.
- Comment** A `{{^partial}}` tag.
- SetDelimiter** A `{{! comment }}` tag. A `{{=<% %>=}}` tag

The documentation for this struct was generated from the following file:

- /home/travis/build/FACT-Team/FactDev/src/libs/qt-mustache/src/mustache.h

8.82 TestAdder< T > Class Template Reference

Public Member Functions

- **TestAdder** (const QString &name)

The documentation for this class was generated from the following file:

- /home/travis/build/FACT-Team/FactDev/tests/CTestRunner/testadder.cpp


8.83 testadder Class Reference

The documentation for this class was generated from the following file:

- /home/travis/build/FACT-Team/FactDev/tests/CTestRunner/testadder.h

8.84 TestMustache Class Reference

Inheritance diagram for TestMustache:



The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/libs/qt-mustache/tests/test_mustache.h
- /home/travis/build/FACT-Team/FactDev/src/libs/qt-mustache/tests/test_mustache.cpp

8.85 TestRunner Class Reference

Public Member Functions

- template<typename T >
char **RegisterTest** (QString name)
- int **RunAll** (int argc, char *argv[])

Static Public Member Functions


- static **TestRunner** & **Instance** ()

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/tests/CTestRunner/testrunner.h
- /home/travis/build/FACT-Team/FactDev/tests/CTestRunner/testrunner.cpp

8.86 Gui::Widgets::Delegates::UnitComboDelegate Class Reference

Inheritance diagram for Gui::Widgets::Delegates::UnitComboDelegate:



Public Member Functions

- **UnitComboDelegate** (QObject *parent=0)
- QWidget * **createEditor** (QWidget *parent, const QStyleOptionViewItem &option, const QModelIndex &index) const
- void **paint** (QPainter *painter, const QStyleOptionViewItem &option, const QModelIndex &index) const

The documentation for this class was generated from the following files:


- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/delegates/unitcombodelegate.h
- /home/travis/build/FACT-Team/FactDev/src/gui/widgets/delegates/unitcombodelegate.cpp

8.87 Models::User Class Reference

The [User](#) class [User](#) of it application.

```
#include <user.h>
```

Inheritance diagram for Models::User:



Public Member Functions

- [User](#) ()
User::User. Construct an [User](#).
- [User](#) (int id)
User::User. Construct a [User](#) with the identify id
- void [commit](#) ()
User::commit Update user data in [User](#) table on the database.
- void [hydrat](#) (int id=1)
User::hydrat Get data of the user who is specified by id from the database.
- void [remove](#) ()
remove Remove the current [User](#)
- QVariantHash [getDataMap](#) ()

- getDataMap* Get all data of model with a HashMap key/value
- void [updateFolders](#) (void)
 - MainWindow::updateFolders* Make directories which contain quotes and billings. Directories are the same than theirs of the Tree organisation (without Projects).
- QString [getFirstname](#) () const
 - User::getFirstname* Return the user firstname.
- void [setFirstname](#) (const QString &firstname)
 - User::setFirstname* Modify the user firstname
- QString [getLastname](#) () const
 - User::getLastname* Return the user lastname.
- void [setLastname](#) (const QString &lastname)
 - User::setLastname* Modify the user lastname
- QString [getCompany](#) () const
 - User::getCompany* Return the user company.
- void [setCompany](#) (const QString &company)
 - User::setCompany* Modify the user company name.
- QString [getTitle](#) () const
 - User::getTitle* Return a short description of [User](#) (company) activity.
- void [setTitle](#) (const QString &title)
 - User::setTitle* Modify the user/company activities description
- QString [getAddress](#) () const
 - User::getAddress* Return the company address (Number and name of street)
- void [setAddress](#) (const QString &address)
 - User::setAddress* Modify the user company address
- QString [getPostalCode](#) () const
 - User::getPostalCode* Return the postal code.
- void [setPostalCode](#) (const QString &postalCode)
 - User::setPostalCode* Modify the postal code postalCode
- QString [getCity](#) () const
 - User::getCity* Return the city.
- void [setCity](#) (const QString &city)
 - User::setCity* Modify the city
- QString [getEmail](#) () const
 - User::getEmail* Return the user professional email
- void [setEmail](#) (const QString &email)
 - User::setEmail* Modify the user professional email
- QString [getMobilePhone](#) () const
 - User::getMobilePhone* Return the number of the professional mobile phone.
- void [setMobilePhone](#) (const QString &mobilePhone)
 - User::setMobilePhone* Modify the number of the professional user mobile phone mobilePhone
- QString [getPhone](#) () const
 - User::getPhone* Return the number of the desktop phone.
- void [setPhone](#) (const QString &phone)
 - User::setPhone* Modify the number of the desktop phone
- QString [getNoSiret](#) () const
 - User::getNoSiret* Return the SIRET number (company registration number)
- void [setNoSiret](#) (const QString &noSiret)
 - User::setNoSiret* Modify the SIRET number (company registration number) noSiret
- QString [getWorkspaceName](#) () const
 - User::getWorkspaceName* Return the name of the workspace user.
- void [setWorkspaceName](#) (const QString &workspaceName)

- [User::setWorkspaceName](#) *Change the current workspace name by the new workspaceName*
- QString [getWorkspacePath](#) () const
[User::getWorkspacePath](#) *Return the path of the workspace user.*
- void [setWorkspacePath](#) (const QString &workspacePath)
[User::setWorkspacePath](#) *Change the current workspace path by the new workspacePath*
- bool [operator==](#) (const [User](#) &u)
[User::operator ==](#) *Re-define the operator "==" to compare if the current [User](#) is the same to the other [User](#) c Return TRUE if both Users are the same, else FALSE.*
- bool [operator!=](#) (const [User](#) &u)
[User::operator !=](#) *Re-define the operator "!=" to compare if the current [User](#) is different to the other [User](#) c Return TRUE if both Users are different, else FALSE.*

Additional Inherited Members

8.87.1 Detailed Description

The [User](#) class [User](#) of it application.

Author

Florent Berbie

8.87.2 Constructor & Destructor Documentation

8.87.2.1 Models::User::User (int id)

[User::User](#). Construct a [User](#) with the identify *id*

Parameters

<i>id</i>	User id
-----------	-------------------------

8.87.3 Member Function Documentation

8.87.3.1 QString Models::User::getAddress () const

[User::getAddress](#) Return the company address (Number and name of street)

Returns

Address company

8.87.3.2 QString Models::User::getCity () const

[User::getCity](#) Return the city.

Returns

city

8.87.3.3 QString Models::User::getCompany () const

[User::getCompany](#) Return the user company.

Returns

New company name

8.87.3.4 QVariantHash Models::User::getDataMap () [virtual]

getDataMap Get all data of model with a HashMap key/value

Returns

Model's data

Implements [Models::IModel](#).

8.87.3.5 QString Models::User::getEmail () const

[User::getEmail](#) Return the user professional *email*

Returns

professional email

8.87.3.6 QString Models::User::getFirstname () const

[User::getFirstname](#) Return the user firstname.

Returns

[User](#) firstname

8.87.3.7 QString Models::User::getLastname () const

[User::getLastname](#) Return the user lastname.

Returns

[User](#) lastname

8.87.3.8 QString Models::User::getMobilePhone () const

[User::getMobilePhone](#) Return the number of the professional mobile phone.

Returns

number of mobile phone

8.87.3.9 QString Models::User::getNoSiret () const

[User::getNoSiret](#) Return the SIRET number (company registration number)

Returns

SIRET number

8.87.3.10 QString Models::User::getPhone () const

[User::getPhone](#) Return the number of the desktop phone.

Returns

number of the desktop phone

8.87.3.11 QString Models::User::getPostalCode () const

[User::getPostalCode](#) Return the postal code.

Returns

postal code

8.87.3.12 QString Models::User::getTitle () const

[User::getTitle](#) Return a short description of [User](#) (company) activity.

Returns

a short description of user (company) activity

8.87.3.13 QString Models::User::getWorkspaceName () const

[User::getWorkspaceName](#) Return the name of the workspace user.

Returns

workspace name

8.87.3.14 QString Models::User::getWorkspacePath () const

[User::getWorkspacePath](#) Return the path of the workspace user.

Returns

workspace path

8.87.3.15 void Models::User::hydrat (int *id* = 1) [virtual]

[User::hydrat](#) Get data of the user who is specified by *id* from the database.

Parameters

<i>id</i>	User identify
-----------	-------------------------------

Implements [Models::IModel](#).

8.87.3.16 `bool Models::User::operator!=(const User & u)`

[User::operator !=](#) Re-define the operator "!=" to compare if the current [User](#) is differnt to the other [User](#) c Return TRUE if both Users are different, else FALSE.

Parameters

<i>u</i>	User to compare
----------	---------------------------------

Returns

boolean

8.87.3.17 `bool Models::User::operator==(const User & u)`

[User::operator ==](#) Re-define the operator "==" to compare if the current [User](#) is the same to the other [User](#) c Return TRUE if both Users are the same, else FALSE.

Parameters

<i>u</i>	User to compare
----------	---------------------------------

Returns

boolean

8.87.3.18 `void Models::User::setAddress (const QString & address)`

[User::setAddress](#) Modify the user company *address*

Parameters

<i>address</i>	Company address (name and number of street)
----------------	---

8.87.3.19 `void Models::User::setCity (const QString & city)`

[User::setCity](#) Modify the *city*

Parameters

<i>city</i>	Company city address
-------------	----------------------

8.87.3.20 `void Models::User::setCompany (const QString & company)`

[User::setCompany](#) Modify the user *company* name.

Parameters

<i>company</i>	New user company name
----------------	-----------------------

8.87.3.21 void Models::User::setEmail (const QString & *email*)

[User::setEmail](#) Modify the user professional *email*

Parameters

<i>email</i>	The user professional email
--------------	-----------------------------

8.87.3.22 void Models::User::setFirstname (const QString & *firstname*)

[User::setFirstname](#) Modify the user *firstname*

Parameters

<i>firstname</i>	New user firstname
------------------	--------------------

8.87.3.23 void Models::User::setLastname (const QString & *lastname*)

[User::setLastname](#) Modify the user *lastname*

Parameters

<i>lastname</i>	New user lastname
-----------------	-------------------

8.87.3.24 void Models::User::setMobilePhone (const QString & *mobilePhone*)

[User::setMobilePhone](#) Modify the number of the professional user mobile phone *mobilePhone*

Parameters

<i>mobilePhone</i>	Number of the professional mobile phone
--------------------	---

8.87.3.25 void Models::User::setNoSiret (const QString & *noSiret*)

[User::setNoSiret](#) Modify the SIRET number (company registration number) *noSiret*

Parameters

<i>noSiret</i>	SIRET number
----------------	--------------

8.87.3.26 void Models::User::setPhone (const QString & *phone*)

[User::setPhone](#) Modify the number of the desktop *phone*

Parameters

<i>phone</i>	Number of the desktop phone
--------------	-----------------------------

8.87.3.27 void Models::User::setPostalCode (const QString & *postalCode*)

[User::setPostalCode](#) Modify the postal code *postalCode*

Parameters

<i>postalCode</i>	New postal code
-------------------	-----------------

8.87.3.28 void Models::User::setTitle (const QString & *title*)

[User::setTitle](#) Modify the user/company activities *description*

Parameters

<i>title</i>	Short description on activity(ies) of User company
--------------	--

8.87.3.29 void Models::User::setWorkspaceName (const QString & *workspaceName*)

[User::setWorkspaceName](#) Change the current workspace name by the new *workspaceName*

Parameters

<i>workspaceName</i>	
----------------------	--

8.87.3.30 void Models::User::setWorkspacePath (const QString & *workspacePath*)

[User::setWorkspacePath](#) Change the current workspace path by the new *workspacePath*

Parameters

<i>workspacePath</i>	
----------------------	--

8.87.3.31 void Models::User::updateFolders (void)

MainWindow::updateFolders Make directories which contain quotes and billings. Directories are the same than theirs of the Tree organisation (without Projects).

Organisation of folders are formed like this:

- COMPANY CustomerLastname CustomerFirstname/
 - Quotes/
 - * quote1 ...
 - Billings/
 - * billing1 ...

The documentation for this class was generated from the following files:


- /home/travis/build/FACT-Team/FactDev/src/models/user.h
- /home/travis/build/FACT-Team/FactDev/src/models/user.cpp

8.88 Databases::UserDatabase Class Reference

The [UserDatabase](#) class Access to User data in the the table User of the [Database](#)

```
#include <userdatabase.h>
```

Inheritance diagram for Databases::UserDatabase:



Public Member Functions

- [Models::User](#) * [getUser](#) (const int *pId*=1)
getUser Get informations about the user (identified by 'pId')
- void [updateUser](#) (const [Models::User](#) &)
updateUser Update informations about the user

Static Public Member Functions

- static [UserDatabase](#) * [instance](#) () throw (DbException*)
UserDatabase::getInstance Return an instance of [UserDatabase](#).

Additional Inherited Members

8.88.1 Detailed Description

The [UserDatabase](#) class Access to User data in the the table User of the [Database](#)

Author

Florent Berbie

See Also

[Database](#)
[User](#)

8.88.2 Member Function Documentation

8.88.2.1 [Models::User](#) * [Databases::UserDatabase::getUser](#) (const int *pId* = 1)

[getUser](#) Get informations about the user (identified by 'pId')

Parameters

<i>pId</i>	user id (1 default) *
------------	-----------------------

Returns

the user

8.88.2.2 [UserDatabase](#) * [Databases::UserDatabase::instance](#) () throw DbException *) [static]

[UserDatabase::getInstance](#) Return an instance of [UserDatabase](#).

Returns


Instance of [UserDatabase](#)

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/database/userdatabase.h
- /home/travis/build/FACT-Team/FactDev/src/database/userdatabase.cpp

8.89 UserDatabaseTest Class Reference

Inheritance diagram for UserDatabaseTest:



The documentation for this class was generated from the following files:


- /home/travis/build/FACT-Team/FactDev/tests/database/userdatabasetest.h
- /home/travis/build/FACT-Team/FactDev/tests/database/userdatabasetest.cpp

8.90 Gui::Dialogs::UserDataDialog Class Reference

The [UserDataDialog](#) class Window to fill user data.

```
#include <userdatadialog.h>
```

Inheritance diagram for Gui::Dialogs::UserDataDialog:



Public Slots

- void [checkFields](#) ()
[UserDataDialog::checkFields](#) Check all fields of dialog components.
- void [browseWorkspacePath](#) ()
[UserDataDialog::browseWorkspacePath](#) Open a new window to define the workspace path of the user.

Public Member Functions

- [UserDataDialog](#) (QWidget *parent=0)
[UserDataDialog](#): Construct a window with user data.
- void [fillFields](#) ()
[UserDataDialog::fillFields](#) Fill line edits with the data of the user.

- void [accept](#) ()
accept Valid data inputed by user and add these data in Database
- void [reject](#) ()
reject Cancel the operation and close the windows

8.90.1 Detailed Description

The [UserDataDialog](#) class Window to fill user data.

Author

Florent Berbie

See Also

[Project](#)

8.90.2 Constructor & Destructor Documentation

8.90.2.1 [Gui::Dialogs::UserDataDialog::UserDataDialog \(QWidget * *parent* = 0 \)](#) `[explicit]`

[UserDataDialog](#): Construct a window with user data.

Parameters


<i>parent</i>	
---------------	--

The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/src/gui/dialogs/userdatadialog.h
- /home/travis/build/FACT-Team/FactDev/src/gui/dialogs/userdatadialog.cpp

8.91 UserModelTest Class Reference

Inheritance diagram for UserModelTest:



The documentation for this class was generated from the following files:

- /home/travis/build/FACT-Team/FactDev/tests/models/usermodeltest.h
- /home/travis/build/FACT-Team/FactDev/tests/models/usermodeltest.cpp

Index

- add
 - Gui::Widgets::ContributoriesWidget, [58](#)
- addBill
 - Gui::MainWindow, [101](#)
- addBilling
 - Databases::BillingDatabase, [29](#)
- addBillingProject
 - Databases::BillingDatabase, [29](#)
- addBillingToProject
 - Utils::HierarchicalSystem, [92](#)
- addContributory
 - Databases::ContributoryDatabase, [64](#)
 - Models::Billing, [25](#)
- addCustomer
 - Databases::CustomerDatabase, [76](#)
- addDoc
 - Gui::MainWindow, [101](#)
- addProject
 - Databases::ProjectDatabase, [117](#)
 - Gui::MainWindow, [101](#)
- AddProjectDialog
 - Gui::Dialogs::AddProjectDialog, [22](#)
- addProjectToCustomer
 - Utils::HierarchicalSystem, [92](#)
- addQuote
 - Gui::MainWindow, [101](#)
- AddQuoteDialog
 - Gui::Dialogs::AddQuoteDialog, [23](#)
- append
 - Gui::Widgets::WdgModels::BillingsTableModel, [34](#)
 - Gui::Widgets::WdgModels::ContributoriesTable-Model, [56](#)
 - Gui::Widgets::WdgModels::CustomersTableModel, [83](#)
 - Gui::Widgets::WdgModels::ProjectsTableModel, [121](#)
- Billing
 - Models::Billing, [25](#)
- BillingDatabaseTest, [32](#)
- BillingModelTest, [32](#)
- BillingsTableModel
 - Gui::Widgets::WdgModels::BillingsTableModel, [33](#)
- canEval
 - CounterContext, [66](#)
 - Mustache::Context, [51](#)
 - Mustache::QtVariantContext, [127](#)
- check
 - Gui::Widgets::CheckFields::CheckEmail, [38](#)
 - Gui::Widgets::CheckFields::CheckFieldsLetters, [39](#)
 - Gui::Widgets::CheckFields::CheckPhone, [41](#)
 - Gui::Widgets::CheckFields::CheckPostalCode, [43](#)
 - Gui::Widgets::CheckFields::CheckSiretNumber, [47](#)
 - Gui::Widgets::CheckFields::CheckUntilField, [48](#)
 - Gui::Widgets::CheckFields::CheckValidField, [49](#)
 - Gui::Widgets::CheckFields::ICheckField, [93](#)
- CheckCity
 - Gui::Widgets::CheckFields::CheckCity, [36](#)
- CheckCountry
 - Gui::Widgets::CheckFields::CheckCountry, [37](#)
- CheckEmail
 - Gui::Widgets::CheckFields::CheckEmail, [38](#)
- CheckFieldsLetters
 - Gui::Widgets::CheckFields::CheckFieldsLetters, [39](#)
- CheckName
 - Gui::Widgets::CheckFields::CheckName, [40](#)
- CheckPhone
 - Gui::Widgets::CheckFields::CheckPhone, [41](#)
- CheckPostalCode
 - Gui::Widgets::CheckFields::CheckPostalCode, [43](#)
- CheckQLineEdit
 - Gui::Widgets::CheckFields::CheckQLineEdit, [45](#)
- CheckSiretNumber
 - Gui::Widgets::CheckFields::CheckSiretNumber, [47](#)
- CheckUntilField
 - Gui::Widgets::CheckFields::CheckUntilField, [48](#)
- CheckValidField
 - Gui::Widgets::CheckFields::CheckValidField, [49](#)
- columnCount
 - Gui::Widgets::WdgModels::BillingsTableModel, [34](#)
 - Gui::Widgets::WdgModels::ContributoriesTable-Model, [56](#)
 - Gui::Widgets::WdgModels::CustomersTableModel, [83](#)
 - Gui::Widgets::WdgModels::ProjectContributories-TableModel, [114](#)
 - Gui::Widgets::WdgModels::ProjectsTableModel, [121](#)
- Comment
 - Mustache::Tag, [143](#)
- Context
 - Mustache::Context, [51](#)
- ContributoriesDatabaseTest, [53](#)
- ContributoriesTableModel
 - Gui::Widgets::WdgModels::ContributoriesTable-Model, [55](#)
- Contributory
 - Models::Contributory, [60](#)

- ContributoryListTest, 65
- ContributoryModelTest, 65
- count
 - Gui::Widgets::WdgModels::BillingsTableModel, 34
 - Gui::Widgets::WdgModels::ContributoriesTable-Model, 56
 - Gui::Widgets::WdgModels::CustomersTableModel, 83
 - Gui::Widgets::WdgModels::ProjectsTableModel, 122
- CounterContext, 65
 - canEval, 66
 - eval, 66
 - stringValue, 66, 67
- Customer
 - Models::Customer, 69
- CustomerContextualMenu
 - Gui::Widgets::CustomerContextualMenu, 75
- CustomerDatabaseTest, 79
- CustomerModelTest, 80
- CustomersTableModel
 - Gui::Widgets::WdgModels::CustomersTableModel, 82
- DB_FILENAME
 - Parameters, 105
- data
 - Gui::Widgets::WdgModels::BillingsTableModel, 34
 - Gui::Widgets::WdgModels::ContributoriesTable-Model, 56
 - Gui::Widgets::WdgModels::CustomersTableModel, 83
 - Gui::Widgets::WdgModels::ProjectContributories-TableModel, 114
 - Gui::Widgets::WdgModels::ProjectsTableModel, 122
- Databases, 17
- Databases::BillingDatabase, 28
 - addBilling, 29
 - addBillingProject, 29
 - getAllBillingsOfProject, 30
 - getBilling, 30
 - getBillingsTable, 30
 - getMaxBillingNumber, 30
 - getMaxQuoteNumber, 31
 - instance, 31
 - isBillingPaid, 31
 - removeBilling, 31
 - removeBillingProject, 31
- Databases::ContributoryDatabase, 63
 - addContributory, 64
 - getContributory, 64
 - instance, 64
 - removeContributory, 64
- Databases::CustomerDatabase, 75
 - addCustomer, 76
 - getCustomer, 76, 77
 - getCustomersTable, 77
 - getItemBillQuote, 77
 - getItemCustomer, 77
 - getItemProject, 78
 - getItemRoot, 78
 - getNbCustomers, 78
 - getTree, 78
 - instance, 78
 - removeCustomer, 79
 - updateCustomer, 79
- Databases::Database, 85
 - executeFile, 86
 - instance, 86
 - lastError, 86
 - setDatabase, 86
 - value, 87
- Databases::ProjectDatabase, 116
 - addProject, 117
 - getAllProjects, 117
 - getNbProjects, 118
 - getNbProjectsForACustomer, 118
 - getProject, 118
 - getProjectsOfCustomer, 118
 - getProjectsTable, 119
 - instance, 119
 - removeProject, 119
 - updateProject, 119
- Databases::RateDatabase, 128
 - instance, 129
- Databases::UserDatabase, 153
 - getUser, 153
 - instance, 154
- DbException
 - Exceptions::DbException, 88
- DialogAddCustomer
 - Gui::Dialogs::DialogAddCustomer, 89
- editUser
 - Gui::MainWindow, 102
- error
 - Mustache::Renderer, 133
- errorPartial
 - Mustache::Renderer, 133
- errorPos
 - Mustache::Renderer, 133
- eval
 - CounterContext, 66
 - Mustache::Context, 51
 - Mustache::QtVariantContext, 127
- Exceptions::DbException, 87
 - DbException, 88
 - popupMessage, 88
- Exceptions::FileException, 90
 - FileException, 90
 - popupMessage, 91
- executeFile
 - Databases::Database, 86
- FileException
 - Exceptions::FileException, 90
- filterOnBillsOrQuotes

- Models::Search, [134](#)
- filterOnCompany
 - Models::Search, [135](#)
- filterOnContributories
 - Models::Search, [135](#)
- filterOnCustomersWithoutProject
 - Models::Search, [135](#)
- filterOnNumberElements
 - Models::Search, [135](#)
- filterOnProjects
 - Models::Search, [135](#)
- filterOnReferentLastname
 - Models::Search, [135](#)
- filterOnVarcharElements
 - Models::Search, [136](#)
- firstLetterToUpper
 - Utils::String, [142](#)
- flags
 - Gui::Widgets::WdgModels::BillingsTableModel, [34](#)
 - Gui::Widgets::WdgModels::ContributoriesTableModel, [56](#)
 - Gui::Widgets::WdgModels::CustomersTableModel, [83](#)
 - Gui::Widgets::WdgModels::ProjectContributoriesTableModel, [114](#)
 - Gui::Widgets::WdgModels::ProjectsTableModel, [122](#)
- fn_t
 - Mustache::QtVariantContext, [126](#)
- Generation, [91](#)
- Generator, [91](#)
- getAddress
 - Models::Customer, [69](#)
 - Models::User, [147](#)
- getAllBillingsOfProject
 - Databases::BillingDatabase, [30](#)
- getAllProjects
 - Databases::ProjectDatabase, [117](#)
- getBeginDate
 - Models::Project, [110](#)
- getBilling
 - Databases::BillingDatabase, [30](#)
- getBillings
 - Gui::Widgets::WdgModels::BillingsTableModel, [34](#)
- getBillingsTable
 - Databases::BillingDatabase, [30](#)
- getBtnValid
 - Gui::Widgets::CheckFields::CheckQLineEdit, [46](#)
- getCity
 - Models::Customer, [69](#)
 - Models::User, [147](#)
- getCompany
 - Models::Customer, [69](#)
 - Models::User, [147](#)
- getContributories
 - Gui::Widgets::ContributoriesWidget, [58](#)
 - Gui::Widgets::WdgModels::ContributoriesTableModel, [56](#)
- Models::Billing, [25](#)
- getContributory
 - Databases::ContributoryDatabase, [64](#)
- getCountry
 - Gui::Widgets::CheckFields::CheckPhone, [42](#)
 - Gui::Widgets::CheckFields::CheckPostalCode, [43](#)
 - Models::Customer, [69](#)
- getCurrentCustomerId
 - Gui::MainWindow, [102](#)
 - Gui::Widgets::searchWidget, [140](#)
- getCurrentCustomerName
 - Gui::MainWindow, [102](#)
- getCurrentProjectId
 - Gui::MainWindow, [102](#)
- getCurrentProjectName
 - Gui::MainWindow, [102](#)
- getCurrentQuoteId
 - Gui::MainWindow, [102](#)
- getCustomer
 - Databases::CustomerDatabase, [76, 77](#)
 - Models::Project, [110](#)
- getCustomers
 - Gui::Widgets::WdgModels::CustomersTableModel, [83](#)
 - Utils::HierarchicalSystem, [92](#)
- getCustomersTable
 - Databases::CustomerDatabase, [77](#)
- getDailyRate
 - Gui::Widgets::RateWidget, [130](#)
 - Models::Project, [110](#)
- getDataMap
 - Models::Billing, [25](#)
 - Models::Contributory, [60](#)
 - Models::Customer, [69](#)
 - Models::IModel, [95](#)
 - Models::Project, [110](#)
 - Models::User, [147](#)
- getDate
 - Models::Billing, [25](#)
- getDescription
 - Models::Billing, [25](#)
 - Models::Contributory, [60](#)
 - Models::Project, [110](#)
- getEmail
 - Models::Customer, [69](#)
 - Models::User, [147](#)
- getEndDate
 - Models::Project, [110](#)
- getFax
 - Models::Customer, [70](#)
- getFilter
 - Models::Search, [136](#)
- getFirstname
 - Models::User, [147](#)
- getFirstnameReferent
 - Models::Customer, [70](#)
- getGroupFilter
 - Models::Search, [136](#)

- getHourlyRate
 - Gui::Widgets::RateWidget, 130
- getId
 - Models::IModel, 95
- getItemBillQuote
 - Databases::CustomerDatabase, 77
- getItemCustomer
 - Databases::CustomerDatabase, 77
- getItemProject
 - Databases::CustomerDatabase, 78
- getItemRoot
 - Databases::CustomerDatabase, 78
- getLastName
 - Models::User, 148
- getLastNameReferent
 - Models::Customer, 70
- getMaxBillingNumber
 - Databases::BillingDatabase, 30
- getMaxQuoteNumber
 - Databases::BillingDatabase, 31
- getMobilePhone
 - Models::Customer, 70
 - Models::User, 148
- getModel
 - Utils::ItemType, 97
- getName
 - Models::Project, 110
 - Utils::ItemType, 97
- getNameFolder
 - Models::Customer, 70
- getNbCustomers
 - Databases::CustomerDatabase, 78
- getNbHours
 - Models::Contributory, 60
- getNbProjects
 - Databases::ProjectDatabase, 118
- getNbProjectsForACustomer
 - Databases::ProjectDatabase, 118
- getNoSiret
 - Models::User, 148
- getNumber
 - Gui::Dialogs::AddQuoteDialog, 23
 - Models::Billing, 26
- getPartial
 - Mustache::PartialFileLoader, 106
 - Mustache::PartialMap, 106
 - Mustache::PartialResolver, 107
- getPath
 - Models::Customer, 70
- getPhone
 - Models::Customer, 70
 - Models::User, 148
- getPostalCode
 - Models::Customer, 71
 - Models::User, 148
- getProject
 - Databases::ProjectDatabase, 118
 - Models::Contributory, 60
- getProjects
 - Gui::Widgets::WdgModels::ProjectsTableModel, 122
 - Utils::HierarchicalSystem, 93
- getProjectsOfCustomer
 - Databases::ProjectDatabase, 118
- getProjectsTable
 - Databases::ProjectDatabase, 119
- getSearchInBillsQuotes
 - Models::Search, 136
- getSearchInCompanies
 - Models::Search, 136
- getSearchInProjects
 - Models::Search, 136
- getSearchInReferentLastname
 - Models::Search, 136
- getText
 - Models::Search, 137
- getTitle
 - Models::Billing, 26
 - Models::User, 148
- getTree
 - Databases::CustomerDatabase, 78
- getType
 - Utils::ItemType, 97
- getUser
 - Databases::UserDatabase, 153
- getWorkspaceName
 - Models::User, 148
- getWorkspacePath
 - Models::User, 149
- Gui, 17
- Gui::Dialogs::AddProjectDialog, 21
 - AddProjectDialog, 22
- Gui::Dialogs::AddQuoteDialog, 22
 - AddQuoteDialog, 23
 - getNumber, 23
- Gui::Dialogs::DialogAddCustomer, 88
 - DialogAddCustomer, 89
- Gui::Dialogs::MessageBox, 103
 - MessageBox, 104
 - setImage, 104
 - setText, 104
- Gui::Dialogs::StartedWindowsDialog, 141
- Gui::Dialogs::UserDataDialog, 154
 - UserDataDialog, 155
- Gui::Docks::SearchDock, 138
- Gui::MainWindow, 99
 - addBill, 101
 - addDoc, 101
 - addProject, 101
 - addQuote, 101
 - editUser, 102
 - getCurrentCustomerId, 102
 - getCurrentCustomerName, 102
 - getCurrentProjectId, 102
 - getCurrentProjectName, 102
 - getCurrentQuoteId, 102

- MainWindow, 101
- rootTree, 102
- search, 103
- treeLevel, 103
- Gui::Widgets, 18
- Gui::Widgets::CheckFields::CheckCity, 36
 - CheckCity, 36
- Gui::Widgets::CheckFields::CheckCountry, 36
 - CheckCountry, 37
- Gui::Widgets::CheckFields::CheckEmail, 37
 - check, 38
 - CheckEmail, 38
- Gui::Widgets::CheckFields::CheckFieldsLetters, 39
 - check, 39
 - CheckFieldsLetters, 39
- Gui::Widgets::CheckFields::CheckName, 40
 - CheckName, 40
- Gui::Widgets::CheckFields::CheckPhone, 41
 - check, 41
 - CheckPhone, 41
 - getCountry, 42
 - setCountry, 42
- Gui::Widgets::CheckFields::CheckPostalCode, 42
 - check, 43
 - CheckPostalCode, 43
 - getCountry, 43
 - setCountry, 43
- Gui::Widgets::CheckFields::CheckQLineEdit, 44
 - CheckQLineEdit, 45
 - getBtnValid, 46
 - isValid, 46
 - setBtnValid, 46
- Gui::Widgets::CheckFields::CheckSiretNumber, 46
 - check, 47
 - CheckSiretNumber, 47
- Gui::Widgets::CheckFields::CheckUntilField, 47
 - check, 48
 - CheckUntilField, 48
- Gui::Widgets::CheckFields::CheckValidField, 48
 - check, 49
 - CheckValidField, 49
- Gui::Widgets::CheckFields::ICheckField, 93
 - check, 93
- Gui::Widgets::ComboBoxModelWidget, 50
- Gui::Widgets::ContributoriesWidget, 58
 - add, 58
 - getContributories, 58
- Gui::Widgets::CustomerContextualMenu, 74
 - CustomerContextualMenu, 75
- Gui::Widgets::CustomerDataWidget, 79
 - printInformations, 80
- Gui::Widgets::Delegates::ComboBoxDelegate, 50
- Gui::Widgets::Delegates::DoubleSpinBoxDelegate, 90
- Gui::Widgets::Delegates::ProjectComboDelegate, 112
- Gui::Widgets::Delegates::UnitComboDelegate, 144
- Gui::Widgets::Popup, 107
- Gui::Widgets::ProjectsWidget, 123
 - ProjectsWidget, 124
 - updateBtn, 125
- Gui::Widgets::RateWidget, 129
 - getDailyRate, 130
 - getHourlyRate, 130
 - RateWidget, 130
 - setDailyRate, 130
 - setHourlyRate, 132
 - setWidgetDailyRateValue, 132
 - setWidgetHourlyRateValue, 132
- Gui::Widgets::WdgModels::BillingsTableModel, 32
 - append, 34
 - BillingsTableModel, 33
 - columnCount, 34
 - count, 34
 - data, 34
 - flags, 34
 - getBillings, 34
 - headerData, 35
 - remove, 35
 - rowCount, 35
 - setData, 35
- Gui::Widgets::WdgModels::ContributoriesTableModel, 54
 - append, 56
 - columnCount, 56
 - ContributoriesTableModel, 55
 - count, 56
 - data, 56
 - flags, 56
 - getContributories, 56
 - headerData, 57
 - remove, 57
 - rowCount, 57
 - setData, 57
- Gui::Widgets::WdgModels::CustomersTableModel, 81
 - append, 83
 - columnCount, 83
 - count, 83
 - CustomersTableModel, 82
 - data, 83
 - flags, 83
 - getCustomers, 83
 - headerData, 84
 - remove, 84
 - rowCount, 84
 - setData, 84
- Gui::Widgets::WdgModels::ProjectContributoriesTableModel, 113
 - columnCount, 114
 - data, 114
 - flags, 114
 - headerData, 114
 - ProjectContributoriesTableModel, 114
 - rowCount, 116
 - setData, 116
- Gui::Widgets::WdgModels::ProjectsTableModel, 120
 - append, 121
 - columnCount, 121

- count, 122
- data, 122
- flags, 122
- getProjects, 122
- headerData, 122
- ProjectsTableModel, 121
- remove, 123
- rowCount, 123
- setData, 123
- Gui::Widgets::searchWidget, 139
- getCurrentCustomerId, 140
- isCustomerSelected, 140
- search, 140
- searchWidget, 140
- headerData
 - Gui::Widgets::WdgModels::BillingsTableModel, 35
 - Gui::Widgets::WdgModels::ContributoriesTable-Model, 57
 - Gui::Widgets::WdgModels::CustomersTableModel, 84
 - Gui::Widgets::WdgModels::ProjectContributories-TableModel, 114
 - Gui::Widgets::WdgModels::ProjectsTableModel, 122
- hydrat
 - Models::Billing, 26
 - Models::Contributory, 60
 - Models::Customer, 71
 - Models::IModel, 95
 - Models::Project, 111
 - Models::User, 149
- instance
 - Databases::BillingDatabase, 31
 - Databases::ContributoryDatabase, 64
 - Databases::CustomerDatabase, 78
 - Databases::Database, 86
 - Databases::ProjectDatabase, 119
 - Databases::RateDatabase, 129
 - Databases::UserDatabase, 154
 - Utils::Log, 98
- InvertedSectionStart
 - Mustache::Tag, 143
- isBilling
 - Models::Billing, 26
- isBillingPaid
 - Databases::BillingDatabase, 31
- isCustomerSelected
 - Gui::Widgets::searchWidget, 140
- isFalse
 - Mustache::Context, 52
 - Mustache::QtVariantContext, 127
- isPaid
 - Models::Billing, 26
- isToRemoved
 - Models::IModel, 95
- isValid
 - Gui::Widgets::CheckFields::CheckQLineEdit, 46
- ItemType
 - Utils::ItemType, 96
- ItemTypeTest, 98
- lastError
 - Databases::Database, 86
- listCount
 - Mustache::Context, 52
 - Mustache::QtVariantContext, 127
- MainWindow
 - Gui::MainWindow, 101
- makeDirectory
 - Utils::Directories, 89
- MessageBox
 - Gui::Dialogs::MessageBox, 104
- Models, 18
- Models::Billing, 23
 - addContributory, 25
 - Billing, 25
 - getContributories, 25
 - getDataMap, 25
 - getDate, 25
 - getDescription, 25
 - getNumber, 26
 - getTitle, 26
 - hydrat, 26
 - isBilling, 26
 - isPaid, 26
 - operator<, 27
 - operator==, 27
 - setDate, 27
 - setDescription, 27
 - setIsBilling, 27
 - setIsPaid, 28
 - setNumber, 28
 - setTitle, 28
- Models::ContributoriesList, 53
- Models::Contributory, 59
 - Contributory, 60
 - getDataMap, 60
 - getDescription, 60
 - getNbHours, 60
 - getProject, 60
 - hydrat, 60
 - operator==, 62
 - setDescription, 62
 - setNbHours, 62
 - setProject, 62
- Models::Customer, 67
 - Customer, 69
 - getAddress, 69
 - getCity, 69
 - getCompany, 69
 - getCountry, 69
 - getDataMap, 69
 - getEmail, 69
 - getFax, 70
 - getFirstnameReferent, 70

- getLastNameReferent, [70](#)
- getMobilePhone, [70](#)
- getNameFolder, [70](#)
- getPath, [70](#)
- getPhone, [70](#)
- getPostalCode, [71](#)
- hydrat, [71](#)
- operator==, [71](#)
- setAddress, [71](#)
- setCity, [72](#)
- setCompany, [72](#)
- setCountry, [72](#)
- setEmail, [72](#)
- setFax, [72](#)
- setFirstnameReferent, [72](#)
- setLastNameReferent, [72](#)
- setMobilePhone, [74](#)
- setPhone, [74](#)
- setPostalCode, [74](#)
- Models::IModel, [94](#)
 - getDataMap, [95](#)
 - getId, [95](#)
 - hydrat, [95](#)
 - isToRemoved, [95](#)
 - setId, [95](#)
 - setToRemoved, [95](#)
- Models::Project, [108](#)
 - getBeginDate, [110](#)
 - getCustomer, [110](#)
 - getDailyRate, [110](#)
 - getDataMap, [110](#)
 - getDescription, [110](#)
 - getEndDate, [110](#)
 - getName, [110](#)
 - hydrat, [111](#)
 - operator<, [111](#)
 - operator==, [111](#)
 - Project, [109](#)
 - setBeginDate, [111](#)
 - setCustomer, [112](#)
 - setDailyRate, [112](#)
 - setDescription, [112](#)
 - setEndDate, [112](#)
 - setName, [112](#)
- Models::Rate, [128](#)
- Models::Search, [133](#)
 - filterOnBillsOrQuotes, [134](#)
 - filterOnCompany, [135](#)
 - filterOnContributories, [135](#)
 - filterOnCustomersWithoutProject, [135](#)
 - filterOnNumberElements, [135](#)
 - filterOnProjects, [135](#)
 - filterOnReferentLastname, [135](#)
 - filterOnVarcharElements, [136](#)
 - getFilter, [136](#)
 - getGroupFilter, [136](#)
 - getSearchInBillsQuotes, [136](#)
 - getSearchInCompanies, [136](#)
 - getSearchInProjects, [136](#)
 - getSearchInReferentLastname, [136](#)
 - getText, [137](#)
 - searchInContributories, [137](#)
 - setGroupFilter, [137](#)
 - setSearchInBillsQuotes, [137](#)
 - setSearchInCompanies, [137](#)
 - setSearchInContributories, [137](#)
 - setSearchInProjects, [138](#)
 - setSearchInReferentLastname, [138](#)
 - setText, [138](#)
- Models::User, [145](#)
 - getAddress, [147](#)
 - getCity, [147](#)
 - getCompany, [147](#)
 - getDataMap, [147](#)
 - getEmail, [147](#)
 - getFirstname, [147](#)
 - getLastName, [148](#)
 - getMobilePhone, [148](#)
 - getNoSiret, [148](#)
 - getPhone, [148](#)
 - getPostalCode, [148](#)
 - getTitle, [148](#)
 - getWorkspaceName, [148](#)
 - getWorkspacePath, [149](#)
 - hydrat, [149](#)
 - operator==, [149](#)
 - setAddress, [149](#)
 - setCity, [150](#)
 - setCompany, [150](#)
 - setEmail, [150](#)
 - setFirstname, [150](#)
 - setLastName, [150](#)
 - setMobilePhone, [150](#)
 - setNoSiret, [150](#)
 - setPhone, [152](#)
 - setPostalCode, [152](#)
 - setTitle, [152](#)
 - setWorkspaceName, [152](#)
 - setWorkspacePath, [152](#)
 - updateFolders, [152](#)
 - User, [147](#)
- Mustache::Tag
 - Comment, [143](#)
 - InvertedSectionStart, [143](#)
 - Partial, [143](#)
 - SectionEnd, [143](#)
 - SectionStart, [143](#)
 - SetDelimiter, [143](#)
- Mustache::Context, [51](#)
 - canEval, [51](#)
 - Context, [51](#)
 - eval, [51](#)
 - isFalse, [52](#)
 - listCount, [52](#)
 - partialResolver, [52](#)
 - partialValue, [52](#)

- pop, [52](#)
- push, [52](#)
- stringValue, [52](#)
- Mustache::PartialFileLoader, [105](#)
 - getPartial, [106](#)
- Mustache::PartialMap, [106](#)
 - getPartial, [106](#)
- Mustache::PartialResolver, [107](#)
 - getPartial, [107](#)
- Mustache::QtVariantContext, [126](#)
 - canEval, [127](#)
 - eval, [127](#)
 - fn_t, [126](#)
 - isFalse, [127](#)
 - listCount, [127](#)
 - pop, [127](#)
 - push, [127](#)
 - stringValue, [127](#)
- Mustache::Renderer, [132](#)
 - error, [133](#)
 - errorPartial, [133](#)
 - errorPos, [133](#)
 - render, [133](#)
 - setTagMarkers, [133](#)
- Mustache::Tag, [142](#)
 - Type, [143](#)
- operator<
 - Models::Billing, [27](#)
 - Models::Project, [111](#)
- operator<<
 - Utils::Log, [99](#)
- operator==
 - Models::Billing, [27](#)
 - Models::Contributory, [62](#)
 - Models::Customer, [71](#)
 - Models::Project, [111](#)
 - Models::User, [149](#)
- Parameters, [105](#)
 - DB_FILENAME, [105](#)
 - VERSION, [105](#)
- Partial
 - Mustache::Tag, [143](#)
- partialResolver
 - Mustache::Context, [52](#)
- partialValue
 - Mustache::Context, [52](#)
- pop
 - Mustache::Context, [52](#)
 - Mustache::QtVariantContext, [127](#)
- popupMessage
 - Exceptions::DbException, [88](#)
 - Exceptions::FileException, [91](#)
- printInformations
 - Gui::Widgets::CustomerDataWidget, [80](#)
- Project
 - Models::Project, [109](#)
- ProjectContributoriesTableModel
 - Gui::Widgets::WdgModels::ProjectContributories-
TableModel, [114](#)
- ProjectDatabaseTest, [120](#)
- ProjectModelTest, [120](#)
- ProjectsTableModel
 - Gui::Widgets::WdgModels::ProjectsTableModel, [121](#)
- ProjectsWidget
 - Gui::Widgets::ProjectsWidget, [124](#)
- push
 - Mustache::Context, [52](#)
 - Mustache::QtVariantContext, [127](#)
- RateModelTest, [129](#)
- RateWidget
 - Gui::Widgets::RateWidget, [130](#)
- remove
 - Gui::Widgets::WdgModels::BillingsTableModel, [35](#)
 - Gui::Widgets::WdgModels::ContributoriesTable-
Model, [57](#)
 - Gui::Widgets::WdgModels::CustomersTableModel, [84](#)
 - Gui::Widgets::WdgModels::ProjectsTableModel, [123](#)
- removeBilling
 - Databases::BillingDatabase, [31](#)
- removeBillingProject
 - Databases::BillingDatabase, [31](#)
- removeContributory
 - Databases::ContributoryDatabase, [64](#)
- removeCustomer
 - Databases::CustomerDatabase, [79](#)
- removeProject
 - Databases::ProjectDatabase, [119](#)
- render
 - Mustache::Renderer, [133](#)
- rootTree
 - Gui::MainWindow, [102](#)
- rowCount
 - Gui::Widgets::WdgModels::BillingsTableModel, [35](#)
 - Gui::Widgets::WdgModels::ContributoriesTable-
Model, [57](#)
 - Gui::Widgets::WdgModels::CustomersTableModel, [84](#)
 - Gui::Widgets::WdgModels::ProjectContributories-
TableModel, [116](#)
 - Gui::Widgets::WdgModels::ProjectsTableModel, [123](#)
- search
 - Gui::MainWindow, [103](#)
 - Gui::Widgets::searchWidget, [140](#)
- searchInContributories
 - Models::Search, [137](#)
- searchTest, [139](#)
- searchWidget
 - Gui::Widgets::searchWidget, [140](#)
- SectionEnd
 - Mustache::Tag, [143](#)

SectionStart
 Mustache::Tag, 143
 SetDelimiter
 Mustache::Tag, 143
 setAddress
 Models::Customer, 71
 Models::User, 149
 setBeginDate
 Models::Project, 111
 setBtnValid
 Gui::Widgets::CheckFields::CheckQLineEdit, 46
 setCity
 Models::Customer, 72
 Models::User, 150
 setCompany
 Models::Customer, 72
 Models::User, 150
 setCountry
 Gui::Widgets::CheckFields::CheckPhone, 42
 Gui::Widgets::CheckFields::CheckPostalCode, 43
 Models::Customer, 72
 setCustomer
 Models::Project, 112
 setDailyRate
 Gui::Widgets::RateWidget, 130
 Models::Project, 112
 setData
 Gui::Widgets::WdgModels::BillingsTableModel, 35
 Gui::Widgets::WdgModels::ContributoriesTable-
 Model, 57
 Gui::Widgets::WdgModels::CustomersTableModel,
 84
 Gui::Widgets::WdgModels::ProjectContributories-
 TableModel, 116
 Gui::Widgets::WdgModels::ProjectsTableModel,
 123
 setDatabase
 Databases::Database, 86
 setDate
 Models::Billing, 27
 setDescription
 Models::Billing, 27
 Models::Contributory, 62
 Models::Project, 112
 setEmail
 Models::Customer, 72
 Models::User, 150
 setEndDate
 Models::Project, 112
 setFax
 Models::Customer, 72
 setFirstname
 Models::User, 150
 setFirstnameReferent
 Models::Customer, 72
 setGroupFilter
 Models::Search, 137
 setHourlyRate
 Gui::Widgets::RateWidget, 132
 setId
 Models::IModel, 95
 setImage
 Gui::Dialogs::MessageBox, 104
 setIsBilling
 Models::Billing, 27
 setIsPaid
 Models::Billing, 28
 setLastname
 Models::User, 150
 setLastnameReferent
 Models::Customer, 72
 setMobilePhone
 Models::Customer, 74
 Models::User, 150
 setName
 Models::Project, 112
 Utils::ItemType, 97
 setNbHours
 Models::Contributory, 62
 setNoSiret
 Models::User, 150
 setNumber
 Models::Billing, 28
 setPhone
 Models::Customer, 74
 Models::User, 152
 setPostalCode
 Models::Customer, 74
 Models::User, 152
 setProject
 Models::Contributory, 62
 setSearchInBillsQuotes
 Models::Search, 137
 setSearchInCompanies
 Models::Search, 137
 setSearchInContributories
 Models::Search, 137
 setSearchInProjects
 Models::Search, 138
 setSearchInReferentLastname
 Models::Search, 138
 setTagMarkers
 Mustache::Renderer, 133
 setText
 Gui::Dialogs::MessageBox, 104
 Models::Search, 138
 setTitle
 Models::Billing, 28
 Models::User, 152
 setToRemoved
 Models::IModel, 95
 setType
 Utils::ItemType, 97
 setWidgetDailyRateValue
 Gui::Widgets::RateWidget, 132
 setWidgetHourlyRateValue

- Gui::Widgets::RateWidget, 132
- setWorkspaceName
 - Models::User, 152
- setWorkspacePath
 - Models::User, 152
- StringTest, 142
- stringValue
 - CounterContext, 66, 67
 - Mustache::Context, 52
 - Mustache::QtVariantContext, 127
- TestAdder< T >, 143
- TestMustache, 144
- TestRunner, 144
- testadder, 143
- treeLevel
 - Gui::MainWindow, 103
- Type
 - Mustache::Tag, 143
- updateBtn
 - Gui::Widgets::ProjectsWidget, 125
- updateCustomer
 - Databases::CustomerDatabase, 79
- updateFolders
 - Models::User, 152
- updateProject
 - Databases::ProjectDatabase, 119
- User
 - Models::User, 147
- UserDataDialog
 - Gui::Dialogs::UserDataDialog, 155
- UserDatabaseTest, 154
- UserModelTest, 155
- Utils::Directories, 89
 - makeDirectory, 89
- Utils::HierarchicalSystem, 91
 - addBillingToProject, 92
 - addProjectToCustomer, 92
 - getCustomers, 92
 - getProjects, 93
- Utils::ItemType, 96
 - getModel, 97
 - getName, 97
 - getType, 97
 - ItemType, 96
 - setName, 97
 - setType, 97
- Utils::Log, 98
 - instance, 98
 - operator<<, 99
 - write, 99
- Utils::String, 141
 - firstLetterToUpper, 142
- Utils::pointers, 107
- VERSION
 - Parameters, 105
- value
 - Databases::Database, 87
 - write
 - Utils::Log, 99