

✔ Congratulations! You passed!

Grade received 100% To pass 80% or higher

Go to next item

1. When evaluating an ML model during training the goal is to improve top-level metrics such as overall accuracy. This information is used to decide whether the model is doing well or not, but it doesn't show how well it does on individual parts of the data. Which technique is extremely helpful to address this shortcoming?

1 / 1 point

- ☐ TensorFlow Metric Analysis (TFMA)
- ☒ Data Slicing
- ☐ Streaming metrics
- ☐ Apache Beam

✔ Correct

That's right! Slicing deals with understanding how a model is performing on each subset of data.

2. Streaming metrics are approximations to full-pass performance metrics computed on _____.

- ☒ mini-batches of data
- ☐ slices of data
- ☐ the full data set
- ☐ the full validation data set.



Correct

That's right! This is a nice way to approximate the full-pass metrics without incurring a huge computational overhead cost.

3. A recent credit card loyalty program offered by a big technology company has been labeled as “**sexist**”, a clear example of algorithm based social discrimination. Let’s examine a user complaint on Twitter: “My wife and I filed joint tax returns, live in a community-property state, and have been married for a long time. Yet the black box algorithm thinks I deserve 20x the credit limit she does. No appeals work.” These and other similar claims have triggered a full-blown investigation by the New York State Department of Financial Services. Which of the reviewed techniques in lecture could have been implemented to prevent this embarrassing problem?


- ☐ Data slicing
- ☐ Residual analysis
- ☒ Model debugging
- ☐ Model robustness



Correct

That’s right! Model debugging tries to improve the transparency of models by highlighting how data is flowing inside and thus can prevent harmful social discrimination.

4. State of the art convolutional neural networks can be fooled to misclassify craftily noise corrupted images with changes that are completely imperceptible to the human eye, as illustrated by the following picture:



What type of analysis can help us detect and prevent these types of scenarios?

- ☒ Sensitivity analysis
- ☐ Dimensionality reduction
- ☐ Residual Analysis
- ☐ Adversarial attack

1 / 1 point

5. A performance-metric gap between two or more groups could be a sign that an ML model may have unfair skews. Therefore, is achieving performance equality (on fairness indicators) across groups a definite sign that a model is fair?

☐ Yes

☒ No

 **Correct**

That's right! Systems are highly complex and achieving equality on one, or even all of the provided metrics can't guarantee fairness. Fairness evaluations should be run throughout the development process and post-launch as well.

1 / 1 point

6. After a model has been deployed, is it usually feasible to perform residual analysis?

☒ No

☐ Yes

 **Correct**

That's right! Once your model is deployed, you may not have a good amount of labeled data and consequently, residual analysis can prove to be a costly exercise as it might include you hiring workers to label your incoming test data.