


Convolutional Neural Networks


Convolution Layer

32x32x3 image



Convolution Layer

32x32x3 image




5x5x3 filter



Convolve the filter with the image
i.e. “slide over the image spatially,
computing dot products”

Convolution Layer

32x32x3 image




Filters always extend the full depth of the input volume

5x5x3 filter




Convolve the filter with the image
i.e. “slide over the image spatially,
computing dot products”

Convolution Layer




Convolution Layer




Convolution Layer

consider a second, **green** filter




For example, if we had 6 5x5 filters, we'll get 6 separate activation maps:




We stack these up to get a “new image” of size 28x28x6!

Preview: ConvNet is a sequence of Convolution Layers, interspersed with activation functions




Preview: ConvNet is a sequence of Convolutional Layers, interspersed with activation functions



Preview


[From recent Yann
LeCun slides]



Feature visualization of convolutional net trained on ImageNet from [Zeiler & Fergus 2013]




A closer look at spatial dimensions:



A closer look at spatial dimensions:

7




7

7x7 input (spatially)
assume 3x3 filter

A closer look at spatial dimensions:

7




7

7x7 input (spatially)
assume 3x3 filter

A closer look at spatial dimensions:

7




7

7x7 input (spatially)
assume 3x3 filter

A closer look at spatial dimensions:

7



7

7x7 input (spatially)
assume 3x3 filter

A closer look at spatial dimensions:


7

7

7x7 input (spatially)
assume 3x3 filter


=> 5x5 output

A closer look at spatial dimensions:




7x7 input (spatially)
assume 3x3 filter
applied **with stride 2**

A closer look at spatial dimensions:




7x7 input (spatially)
assume 3x3 filter
applied **with stride 2**

A closer look at spatial dimensions:




7x7 input (spatially)
assume 3x3 filter
applied **with stride 2**
=> 3x3 output!

A closer look at spatial dimensions:




7x7 input (spatially)
assume 3x3 filter
applied **with stride 3**?

A closer look at spatial dimensions:



7x7 input (spatially)
assume 3x3 filter
applied **with stride 3?**

doesn't fit!
cannot apply 3x3 filter on
7x7 input with stride 3.



Output size:
 $(N - F) / \text{stride} + 1$

e.g. $N = 7, F = 3$:

stride 1 $\Rightarrow (7 - 3)/1 + 1 = 5$

stride 2 $\Rightarrow (7 - 3)/2 + 1 = 3$

stride 3 $\Rightarrow (7 - 3)/3 + 1 = 2.33 \therefore \backslash$

In practice: Common to zero pad the border

0	0	0	0	0	0			
0								
0								
0								
0								

e.g. input 7x7

3x3 filter, applied with **stride 1**

pad with 1 pixel border => what is the output?

(recall:)

$$(N - F) / \text{stride} + 1$$

In practice: Common to zero pad the border

0	0	0	0	0	0			
0								
0								
0								
0								

e.g. input 7x7

3x3 filter, applied with **stride 1**

pad with 1 pixel border => what is the output?

7x7 output!

In practice: Common to zero pad the border

0	0	0	0	0	0			
0								
0								
0								
0								

e.g. input 7x7

3x3 filter, applied with **stride 1**

pad with 1 pixel border => what is the output?

7x7 output!

in general, common to see CONV layers with stride 1, filters of size $F \times F$, and zero-padding with $(F-1)/2$. (will preserve size spatially)


e.g. $F = 3 \Rightarrow$ zero pad with 1

$F = 5 \Rightarrow$ zero pad with 2

$F = 7 \Rightarrow$ zero pad with 3

Remember back to...

E.g. 32x32 input convolved repeatedly with 5x5 filters shrinks volumes spatially! (32 \rightarrow 28 \rightarrow 24 ...). Shrinking too fast is not good, doesn't work well.




Examples time:

Input volume: **32x32x3**

10 5x5 filters with stride 1, pad 2

Output volume size: ?



Examples time:


Input volume: **32x32x3**

10 **5x5** filters with stride **1**, pad **2**

Output volume size:

$(32 + 2 * 2 - 5) / 1 + 1 = 32$ spatially, so


32x32x10



Examples time:

Input volume: **32x32x3**

10 5x5 filters with stride 1, pad 2




Number of parameters in this layer?

Examples time:

Input volume: **32x32x3**

10 **5x5** filters with stride 1, pad 2



Number of parameters in this layer?

each filter has $5*5*3 + 1 = 76$ params (+1 for bias)

=> $76*10 = 760$

Summary. To summarize, the Conv Layer:

- Accepts a volume of size $W_1 \times H_1 \times D_1$
- Requires four hyperparameters:
 - Number of filters K ,
 - their spatial extent F ,
 - the stride S ,
 - the amount of zero padding P .
- Produces a volume of size $W_2 \times H_2 \times D_2$ where:
 - $W_2 = (W_1 - F + 2P)/S + 1$
 - $H_2 = (H_1 - F + 2P)/S + 1$ (i.e. width and height are computed equally by symmetry)
 - $D_2 = K$
- With parameter sharing, it introduces $F \cdot F \cdot D_1$ weights per filter, for a total of $(F \cdot F \cdot D_1) \cdot K$ weights and K biases.
- In the output volume, the d -th depth slice (of size $W_2 \times H_2$) is the result of performing a valid convolution of the d -th filter over the input volume with a stride of S , and then offset by d -th bias.

Common settings:

Summary. To summarize, the Conv Layer:

- Accepts a volume of size $W_1 \times H_1 \times D_1$
- Requires four hyperparameters:
 - Number of filters K ,
 - their spatial extent F ,
 - the stride S ,
 - the amount of zero padding P .
- Produces a volume of size $W_2 \times H_2 \times D_2$ where:
 - $W_2 = (W_1 - F + 2P)/S + 1$
 - $H_2 = (H_1 - F + 2P)/S + 1$ (i.e. width and height are computed equally by symmetry)
 - $D_2 = K$
- With parameter sharing, it introduces $F \cdot F \cdot D_1$ weights per filter, for a total of $(F \cdot F \cdot D_1) \cdot K$ weights and K biases.
- In the output volume, the d -th depth slice (of size $W_2 \times H_2$) is the result of performing a valid convolution of the d -th filter over the input volume with a stride of S , and then offset by d -th bias.

$K = (\text{powers of 2, e.g. 32, 64, 128, 512})$


- $F = 3, S = 1, P = 1$

- $F = 5, S = 1, P = 2$


- $F = 5, S = 2, P = ?$ (whatever fits)

- $F = 1, S = 1, P = 0$



(btw, 1x1 convolution layers make perfect sense)



The brain/neuron view of CONV Layer





The brain/neuron view of CONV Layer



It's just a neuron with local connectivity...

The brain/neuron view of CONV Layer





An activation map is a 28x28 sheet of neuron outputs:

1. Each is connected to a small region in the input
2. All of them share parameters

“5x5 filter” -> “5x5 receptive field for each neuron”

The brain/neuron view of CONV Layer




E.g. with 5 filters,
CONV layer consists of
neurons arranged in a 3D grid
(28x28x5)

There will be 5 different
neurons all looking at the same
region in the input volume




Pooling layer

- makes the representations smaller and more manageable
- operates over each activation map independently:



MAX POOLING



- Accepts a volume of size $W_1 \times H_1 \times D_1$
- Requires three hyperparameters:
 - their spatial extent F ,
 - the stride S ,
- Produces a volume of size $W_2 \times H_2 \times D_2$ where:
 - $W_2 = (W_1 - F)/S + 1$
 - $H_2 = (H_1 - F)/S + 1$
 - $D_2 = D_1$
- Introduces zero parameters since it computes a fixed function of the input
- Note that it is not common to use zero-padding for Pooling layers

Common settings:


$$F = 2, S = 2$$

$$F = 3, S = 2$$

- Accepts a volume of size $W_1 \times H_1 \times D_1$
- Requires three hyperparameters:
 - their spatial extent F ,
 - the stride S ,
- Produces a volume of size $W_2 \times H_2 \times D_2$ where:
 - $W_2 = (W_1 - F)/S + 1$
 - $H_2 = (H_1 - F)/S + 1$
 - $D_2 = D_1$
- Introduces zero parameters since it computes a fixed function of the input
- Note that it is not common to use zero-padding for Pooling layers


Fully Connected Layer (FC layer)

- Contains neurons that connect to the entire input volume, as in ordinary Neural Networks



Case Study: LeNet-5


[LeCun et al., 1998]



Conv filters were 5x5, applied at stride 1
Subsampling (Pooling) layers were 2x2 applied at stride 2
i.e. architecture is [CONV-POOL-CONV-POOL-CONV-FC]

Case Study: AlexNet

[Krizhevsky et al. 2012]



Input: 227x227x3 images


First layer (CONV1): 96 11x11 filters applied at stride 4

=>

Q: what is the output volume size? Hint: $(227-11)/4+1 = 55$

Case Study: AlexNet

[Krizhevsky et al. 2012]



Input: 227x227x3 images

First layer (CONV1): 96 11x11 filters applied at stride 4


=>

Output volume **[55x55x96]**

Q: What is the total number of parameters in this layer?

Case Study: AlexNet

[Krizhevsky et al. 2012]



Input: 227x227x3 images

First layer (CONV1): 96 11x11 filters applied at stride 4


=>

Output volume **[55x55x96]**

Parameters: $(11*11*3)*96 = \mathbf{35K}$

Case Study: AlexNet

[Krizhevsky et al. 2012]



Input: 227x227x3 images


After CONV1: 55x55x96

Second layer (POOL1): 3x3 filters applied at stride 2

Q: what is the output volume size? Hint: $(55-3)/2+1 = 27$

Case Study: AlexNet

[Krizhevsky et al. 2012]



Input: 227x227x3 images

After CONV1: 55x55x96


Second layer (POOL1): 3x3 filters applied at stride 2

Output volume: 27x27x96

Q: what is the number of parameters in this layer?

Case Study: AlexNet

[Krizhevsky et al. 2012]



Input: 227x227x3 images

After CONV1: 55x55x96


Second layer (POOL1): 3x3 filters applied at stride 2

Output volume: 27x27x96

Parameters: 0!

Case Study: AlexNet

[Krizhevsky et al. 2012]



Input: 227x227x3 images

After CONV1: 55x55x96

After POOL1: 27x27x96

...

Case Study: AlexNet

[Krizhevsky et al. 2012]

Full (simplified) AlexNet architecture:

[227x227x3] INPUT

[55x55x96] **CONV1**: 96 11x11 filters at stride 4, pad 0

[27x27x96] **MAX POOL1**: 3x3 filters at stride 2

[27x27x96] **NORM1**: Normalization layer

[27x27x256] **CONV2**: 256 5x5 filters at stride 1, pad 2

[13x13x256] **MAX POOL2**: 3x3 filters at stride 2

[13x13x256] **NORM2**: Normalization layer

[13x13x384] **CONV3**: 384 3x3 filters at stride 1, pad 1

[13x13x384] **CONV4**: 384 3x3 filters at stride 1, pad 1


[13x13x256] **CONV5**: 256 3x3 filters at stride 1, pad 1

[6x6x256] **MAX POOL3**: 3x3 filters at stride 2

[4096] **FC6**: 4096 neurons

[4096] **FC7**: 4096 neurons

[1000] **FC8**: 1000 neurons (class scores)



Case Study: AlexNet

[Krizhevsky et al. 2012]

Full (simplified) AlexNet architecture:

[227x227x3] INPUT

[55x55x96] **CONV1**: 96 11x11 filters at stride 4, pad 0

[27x27x96] **MAX POOL1**: 3x3 filters at stride 2

[27x27x96] **NORM1**: Normalization layer

[27x27x256] **CONV2**: 256 5x5 filters at stride 1, pad 2

[13x13x256] **MAX POOL2**: 3x3 filters at stride 2

[13x13x256] **NORM2**: Normalization layer

[13x13x384] **CONV3**: 384 3x3 filters at stride 1, pad 1

[13x13x384] **CONV4**: 384 3x3 filters at stride 1, pad 1


[13x13x256] **CONV5**: 256 3x3 filters at stride 1, pad 1

[6x6x256] **MAX POOL3**: 3x3 filters at stride 2

[4096] **FC6**: 4096 neurons

[4096] **FC7**: 4096 neurons

[1000] **FC8**: 1000 neurons (class scores)




Details/Retrospectives:

- first use of ReLU
- used Norm layers (not common anymore)
- heavy data augmentation
- dropout 0.5
- batch size 128
- SGD Momentum 0.9
- Learning rate 1e-2, reduced by 10 manually when val accuracy plateaus
- L2 weight decay 5e-4
- 7 CNN ensemble: 18.2% -> 15.4%


Case Study: ResNet [He et al., 2015]

ILSVRC 2015 winner (3.6% top 5 error)

Microsoft
Research

MSRA @ ILSVRC & COCO 2015 Competitions

- **1st places in all five main tracks**
 - ImageNet Classification: “*Ultra-deep*” (quote Yann) **152-layer** nets
 - ImageNet Detection: **16%** better than 2nd
 - ImageNet Localization: **27%** better than 2nd
 - COCO Detection: **11%** better than 2nd
 - COCO Segmentation: **12%** better than 2nd


ICCV 15
International Conference on Computer Vision

*improvements are relative numbers

Kaiming He, Xiangyu Zhang, Shaoqing Ren, & Jian Sun. “Deep Residual Learning for Image Recognition”. arXiv 2015.

Slide from Kaiming He’s recent presentation <https://www.youtube.com/watch?v=1PGLj-uKT1w>

Revolution of Depth



ImageNet Classification top-5 error (%)




Kaiming He, Xiangyu Zhang, Shaoqing Ren, & Jian Sun. "Deep Residual Learning for Image Recognition". arXiv 2015.


(slide from Kaiming He's recent presentation)

CIFAR-10 experiments

CIFAR-10 plain nets




CIFAR-10 ResNets



Case Study: ResNet [He et al., 2015]

ILSVRC 2015 winner (3.6% top 5 error)




2-3 weeks of training
on 8 GPU machine

at runtime: faster
than a VGGNet!
(even though it has
8x more layers)

(slide from Kaiming He's recent presentation)

Case Study: ResNet



[He et al., 2015]



spatial dimension
only 56x56!


Case Study: ResNet

[He et al., 2015]




Case Study: ResNet

[He et al., 2015]



Case Study: ResNet [He et al., 2015]



layer name	output size	18-layer	34-layer	50-layer	101-layer	152-layer
conv1	112×112	7×7, 64, stride 2				
conv2_x	56×56	3×3 max pool, stride 2				
		$\begin{bmatrix} 3 \times 3, 64 \\ 3 \times 3, 64 \end{bmatrix} \times 2$	$\begin{bmatrix} 3 \times 3, 64 \\ 3 \times 3, 64 \end{bmatrix} \times 3$	$\begin{bmatrix} 1 \times 1, 64 \\ 3 \times 3, 64 \\ 1 \times 1, 256 \end{bmatrix} \times 3$	$\begin{bmatrix} 1 \times 1, 64 \\ 3 \times 3, 64 \\ 1 \times 1, 256 \end{bmatrix} \times 3$	$\begin{bmatrix} 1 \times 1, 64 \\ 3 \times 3, 64 \\ 1 \times 1, 256 \end{bmatrix} \times 3$
conv3_x	28×28	$\begin{bmatrix} 3 \times 3, 128 \\ 3 \times 3, 128 \end{bmatrix} \times 2$	$\begin{bmatrix} 3 \times 3, 128 \\ 3 \times 3, 128 \end{bmatrix} \times 4$	$\begin{bmatrix} 1 \times 1, 128 \\ 3 \times 3, 128 \\ 1 \times 1, 512 \end{bmatrix} \times 4$	$\begin{bmatrix} 1 \times 1, 128 \\ 3 \times 3, 128 \\ 1 \times 1, 512 \end{bmatrix} \times 4$	$\begin{bmatrix} 1 \times 1, 128 \\ 3 \times 3, 128 \\ 1 \times 1, 512 \end{bmatrix} \times 8$
conv4_x	14×14	$\begin{bmatrix} 3 \times 3, 256 \\ 3 \times 3, 256 \end{bmatrix} \times 2$	$\begin{bmatrix} 3 \times 3, 256 \\ 3 \times 3, 256 \end{bmatrix} \times 6$	$\begin{bmatrix} 1 \times 1, 256 \\ 3 \times 3, 256 \\ 1 \times 1, 1024 \end{bmatrix} \times 6$	$\begin{bmatrix} 1 \times 1, 256 \\ 3 \times 3, 256 \\ 1 \times 1, 1024 \end{bmatrix} \times 23$	$\begin{bmatrix} 1 \times 1, 256 \\ 3 \times 3, 256 \\ 1 \times 1, 1024 \end{bmatrix} \times 36$
conv5_x	7×7	$\begin{bmatrix} 3 \times 3, 512 \\ 3 \times 3, 512 \end{bmatrix} \times 2$	$\begin{bmatrix} 3 \times 3, 512 \\ 3 \times 3, 512 \end{bmatrix} \times 3$	$\begin{bmatrix} 1 \times 1, 512 \\ 3 \times 3, 512 \\ 1 \times 1, 2048 \end{bmatrix} \times 3$	$\begin{bmatrix} 1 \times 1, 512 \\ 3 \times 3, 512 \\ 1 \times 1, 2048 \end{bmatrix} \times 3$	$\begin{bmatrix} 1 \times 1, 512 \\ 3 \times 3, 512 \\ 1 \times 1, 2048 \end{bmatrix} \times 3$
	1×1	average pool, 1000-d fc, softmax				
FLOPs		1.8×10^9	3.6×10^9	3.8×10^9	7.6×10^9	11.3×10^9

Summary

- ConvNets stack CONV, POOL, FC layers
- Trend towards smaller filters and deeper architectures
- Trend towards getting rid of POOL/FC layers (just CONV)
- Typical architectures look like
 $[(\text{CONV-RELU})^N\text{-POOL?}]^M\text{-(FC-RELU)}^K\text{,SOFTMAX}$
where N is usually up to ~5, M is large, $0 \leq K \leq 2$.
 - but recent advances such as ResNet/GoogLeNet challenge this paradigm